Details of automatic door accessories			
ITEM	Specification	Unit Price	Remark
MS01	Microwave sensor(10GHZ/24GHZ) Power: AC/DC 12~36V Radio frequency:10.525GHZ/24.125GHZ Protection level: IP52 Size:131×61×46mm(L×W×H) Max installation height: 4M Detection range and sensibility can be adjusted.	$12.00	Black/siver color optional
MS02	Microwave sensor(24GHZ) Power: AC/DC 12~36V Radio frequency: 24.125GHZ Protection level: IP52 Size:140×46×45mm(L×W×H) Max installation height: 4M Detection range and sensibility can be adjusted.	$12.00	
MS03	Microwave Sensor(24GHZ) Power: AC/DC 12~36V Radio frequency: 24.125GHZ Protection level: IP52 Size:121×80×51mm(L×W×H) Max installation height: 4M Detection range and sensibility can be adjusted.	$12.00	Black/siver color optional
MS-204 	Microwave Sensor(24GHZ) Power: AC/DC 12~30V±10% (50Hz to 60Hz) Radio frequency: 24.125GHZ Protection level: IP52 Size:150×50×38mm(L×W×H) Max installation height: 4M Detection range and sensibility can be adjusted.	$14.00	Black/siver color optional
IS01	Infrared sensor Power: AC/DC 12~36V Sensing distance：0.2m-2m Size:221×74×35mm(L×W×H) Max installation height: 3M Detection range and sensibility can be adjusted. The product can be used in the occasion where the building environment is narrow and close to street and the accuracy detection ability is demanded. Detection sensing distance adjustable, with high anti-interference , easy operation and reliable.	$24.00	

IS02 	Combined microwave&infrared sensor Power:AC/DC 12~36V Transmitting frequency:24.125GHZ Protection level:IP54 Size:262×55×44mm(L×W×H) Max installation height: 3M Combined radar activation and Infrared safety sensor is used for automatic sliding door, folding door and curve door. Radar technology is for door activation. Infrared technology is for door safety entrance. Unique anti-clip function design, no need extra safety beam sensors. Have function of background self-learn. Can learn background automatically when power on. Suit all kinds of occasions. Always self-correcting once be influenced by quake, distortion, move, dark and sunshine. Ensure the sensor can work durable. Microwave technology adopts the Germany Microwave sensor module, not influenced by temperature and humidity with reliable working performance.	$47.00	Black/siver color optional
IS03 	Infrared Motion &Presence Safety Sensor Power Input: AC/DC 12 24V(±10%) Transmitting frequency:24.125GHZ Protection level:IP54 Size:229×67×41mm(L×W×H) Max installation height: 3M 1.Applied to the opening and safety protection function of the translational door. Infrared sensing is used for starting and anti clamping; 2.Have function of background self-learn. Can learn background automatically when power on. Suit all kinds of occasions.Always self-correcting once be influenced by quake, distortion, move, dark and sunshine. Ensure the sensor can work durable;	$37.00	Black/siver color optional
IS04 	Microwave Motion & Infrared Presence Sensor Power Input: AC/DC 12~30V(±10%) Transmitting frequency:24.125GHZ Protection level:IP44 Size:267.2×61.1×46mm(L×W×H) Max installation height: 3.5M 1.Used for automatic sliding door,folding door and Curve door.Radar technology is for door activation.Infrared technology is for door safety entrance; 2.Have function of background self-learn. Can learn background automatically when power on. Suit all kinds of occasions.Always self-correcting once be influenced by quake, distortion, move, dark and sunshine. Ensure the sensor can work durable	$50.00	Black/siver color optional
V01 	Microwave Motion & Infrared Presence Sensor Power Input: AC/DC 12~24V(±10%) Transmitting frequency:24.125GHZ Protection level:IP44 Size:267×61×38mm(L×W×H) Max installation height: 3.5M 1.Used for automatic sliding door,folding door and Curve door.Radar technology is for door activation.Infrared technology is for door safety entrance; 2.Have function of background self-learn. Can learn background automatically when power on. Suit all kinds of occasions.Always self-correcting once be influenced by quake, distortion, move, dark and sunshine. Ensure the sensor can work durable	$37.00	Black/siver color optional
PT01 	Safety beam(photocell) Power:AC/DC12~30V Max transmission distance: 10m Type: single beam(one pair eyes)/ double beam(2 pairs eyes) Receiver dimension：105.5*53.4*28.5mm Electric eyes：19（length）*13（diameter）mm	$10.00	

FS01	Foot sensor switch Power:AC/DC12~36V Recommended installation height: 0.3M from the ground Active infrared ray of modulation-demodulation controlled by microcomputer. Widely used in the operating room of hospital and laboratory to prevent hand pollution.	$20.00	
FC01	Five-range programmed function switch Power: 12~36V Function status: full open, half open, exit only, lock, automatic Size:113×63×20mm(L×W×H) Function switch against passwords, safe and reliable. With memory function in case of power failure. Password can be reset.	$10.00	
FC02	Five-range function keypad Power: 12~36V Functions: full open, half open, exit only, lock, automatic Size:86×86×10mm(L×W×H)	$10.00	
KP01	Function key switch(five-range) Power: AC/DC 18~36V Functions: full open, half open, exit only, lock, automatic Size:86×86×10mm(L×W×H)	$10.00	
KP02	LED key switch(five-range) Power: AC/DC18~36V Size:92×92×46mm(L×W×H) Functions: full open, half open, exit only, lock, automatic This product is unidirectional command switch for automatic door accessory using. With special design with bottom panel, it is convenient for different installation occasions.	$21.00	
KP03	Five-range LCD key switch Power: AC/DC12~36V Size:92×92×33mm(L×W×H) Functions: full open, half open, exit only, lock, automatic This product is unidirectional command switch for automatic door. With TFT true color liquid display, special design with bottom panel, it is convenient for different installation occasions.	$30.00	

PB07	Infrared hand sensor switch Power: AC/DC12~36V Size:92×92×33mm(L×W×H) Transmit distance: 1-20cm, can be set according to actual occasion.	$15.00	
FC04	Learning code remote control device(4 channels) Power: 24VDC 433MHZ Learning code type Transmission distance: 25M Function status: full open, half open,lock, automatic	$15.00	Optional remote keys
FP01	Fingerprint access control device / time attendance machine Power supply：12VDC Fingerprint capacity：1000 Recorded capacity：100,000 Dimension：180*82*53(L×W×H) Identification mode: Fingerprint / ID card / Password Voice prompt: available	$70.00	
PB04	No touch hand sensor switch Power: DC 12V Working type: infrared induction Working distance: 1-15cm, can be set according to actual occasion. Weight: 83g Size: 89×89×37mm(L×W×H)	$6.00	
PB05	Infrared touchless hand sensor switch Power: AC/DC12~36V Working type: infrared induction Transmit distance: 1-15cm, can be set according to actual occasion. Size:113×63×20mm(L×W×H) Weight: 110g	$12.00	
PB06	Wireless push button switch Power: AC/DC12~36V Hold open time：1-9S adjustable Pushing panel：203（L）*41（W）*12.5（H）mm Receiver：123（L）*50（W）*32（H）mm Widely be used for auto door and door control equipment. With the wireless signal output,door can be open by the pushing the panel. Easy installation, specially designed for the occasions which have difficulty in wire embedding.	$25.00	

	One extra learning code wireless push button	$10.00	
PB07 	Wireless push button switch(PVC type) Power: AC/DC12~24V Wireless transmit distance: 50m Pushing panel：159（L）*35（W） Receiver：73（L）*41（W）*23（H）mm Widely be used for auto door and door control equipment. With the wireless signal output,door can be open by the pushing the panel.	$15.00	
PB08	Wireless push button switch(mirror type) Power: AC/DC12~24V Wireless transmit distance: 50m Pushing panel：159（L）*35（W） Receiver：73（L）*41（W）*23（H）mm Widely be used for auto door and door control equipment. With the wireless signal output,door can be open by the pushing the panel.	$19.00	
WS01	Wireless touchless switch(mirror type) Power: AC/DC12~24V Wireless transmit distance: 50m Pushing panel：162（L）*38（W） *14.4（H）mm Receiver：73（L）*41（W）*23（H）mm Widely be used for auto door and door control equipment. Inductive distance: 1-30cm adjustable	$22.00	
AK03	Access keypad Power: 12VDC Storage capacity: 1000 users Open method：Card, password, card+password. Dimension：115×75×21（mm)	$18.00	

AK04	Access keypad Power: 12VDC Storage capacity: 1000 users Open method：Card, password, card+password. Dimension：110×75×25（mm)	$25.00	
FP02	Finger printer(stainless) Power: DC 12V Memory capacity:120 Weight: 500g Size: 115×70×35mm(L×W×H)	$50.00	
PB03	Wired push button switch(plastic) Weight: 96g Size: 203×41×12.5mm(L×W×H)	$6.00	
PB02	Wired push button switch(stainless) with blue LED Weight: 65g Size: 86×86×35mm(L×W×H)	$5.00	
	Wired push button switch(stainless) with blue LED Weight:30g Size: 91×28×20mm(L×W×H)		
PB01	Wired Plastic switch Weight:50g Size: 86×86mm(L×W)	$1.20	

AK02	Access keypad(plastic) Power: 12VDC User capacity: 500 users Open method：Card, password, both. 1000 pcs card info can be stored Dimension：117×117×21（mm) Specific designed for office, housing, security system and building's access . It not only can work by reading card or password ,but also can control electric lock and auto-door.	$12.00	
NEW UPS	Automatic door backup lithium battery Input voltage：220VAC, 50HZ Output voltage：DC12V/5.2A, DC24V/2.6A Size: 243×59×45mm(L×W×H) When power off, it can make the door work 7 hours or open and close 500 times.	$37.00	
LC01	Metal manual lock Lock manually, open with key.	$13.00	
LC02	Electric lock Power: DC 12V Working current: 110mA Installation hole:212(L)*35(W) Deep into wall around 43mm Panel dimension:205×34×42mm(L×W×H)	$20.00	
LC03	Electromagnetic lock Power: DC 12V Working current: 180mA With the function of locking the access device, it uses with access control, and equip with bracket for installation.	$19.00	
LC04	Electromagnetic lock Power: DC 12V Working current: 960mA Load weight:180kgs The product uses with access control device , it can be installed on glass doors ,wooden doors, iron gate or fireproof doors.	$19.00	

DS01	Auto door disable switch Power:AC/DC12~36V Panel size：160（L）*120（W）*15（H）mm Stainless steel panel design,easy operation with key to choose different functions including: Emergency opening, Automatic and Full lock. Suitable for automatic door of disable-person washroom or washroom management of building.	$80.00	
MCR 	Magnetic card reader Input voltage:DC12V Storage capacity: 5600 cards Dimension：138*56*32mm (L*W*H) The product can be widely used as exit switch for bank VIP room.With the authorized card controlled by Magnetic card reader access controller, only some people have the right to enter. Online working or offline working is available.	$36.00	
GC01	Glass clamp(20cm) Connect glass door panel and hanger 2pcs for 1 door leaf	$4.00	
GC02	Glass clamp(1m) Connect glass and hangers for frameless glass door One pc for one glass door leaf	$15.00	
FG01	Framed door guider(rubber or brush type optional) 10-40mm	$1.50	
FG02 	Framed door guider(rubber or brush type optional) 30-60mm	$1.50	
FG03	Frameless glass door guider Max. 15mm	$1.00	

V01	Wireless Handicap access switch 1)SIZE:129mm（L）×129mm（W）×46mm（H）; 2)Battery life time::20000times, AA battery*2pcs; 3)The power supply of the receiver：AC/DC12-30V ; 4)press to open; 5)adopt 2.4G high frequency 6)distance between the receiver and switch: empty area 30meters	$25.00	
V02	Narrow Wireless Hand Press Switch (1)Low power panel design, long battery life. (2)Adopts 2.4G wireless communication technology with high wireless transceiver stability.(3)The receiver adopt relay signal output and can be used with automatic door and access control controller.(4)After received the signal, it outputs the door opening signal for 1.5s. Receiver with wide voltage input design,DC 12 ~ 30V power input. Receiver: Power supply: DC12-30V Static current:	$55.00	
V03	Autodoor control switch for rooms 1.Mainly used to limit the number of occasions. Such as: mother and baby room, private toilets, bathrooms and other limited number of occasions; 2.The automatic switch controller for the special purpose room is provided with a large panel key set, and is provided with Braille, Chinese and English display, and has speech and lamp hints, which is suitable for each Species use. 3.Inside and outside each panel,adopts the net line connection way, simple and convenient. This product has the maximum use time to time reminder function. 4.Input voltage:AC/DC 12-36V Language:English,Chinese,Korean Input:Relay contact Panel Size:245(L)*84(W)*12(H)mm Controller size:145(L)*57(W)*38(H)mm	**$72.00**	
V04	Moving Safety Curtain(Laser type) 1. It can be used to accurately detect a moving or standing body or objects, avoiding various automatic rotation door or automatic sliding door colliding with human bodies or objects, ensure the safety of the people and equipment. Widely used in anti-collision occasions of automatic rotation doors and automatic swing doors. 2. Output voltage: AC/DC 12-30V(-/+10%) Scanning range: Mechanical wheel adjustment 500-2800mm Detection area diameter: around 75mm Deduction re-action time: ≤100ms Operating mode: mobile or static mode adaptation Moving safety curtain size for automatic swing door: 620（L）×31（W）×20（H）mm 3. Exquisite structure, simple and fashionable appearance, installation is very easily. The detection height and sensing range do not require special tools to do adjustment, just via the mechanical wheel and locking screws fastly and accurately to adjust the position. The system is extremely stable, with a background, noise filtering system, and not affected by the environment (such as sunlight, snow, rain, etc.) The scanning angle of the probe detection can be	**Single Sensor inside:$50.00** **Double Sensors inside:$75.00**	