CS 331: Bayesian Networks 2

Bayesian Networks

- You've heard about how Bayesian networks have revolutionized AI
- · You've seen what they are
- There are two nagging questions:
 - 1. How do you come up with a Bayesian network structure?
 - 2. How do you do inference on Bayesian networks?
- We will deal with the first one today...

Bayesian Network Topology

- So how do you come up with the Bayesian network structure?
- · Two options:
 - 1. Design by hand
 - 2. Learn it from data

Designing Bayesian Networks By Hand

4

,

Getting an Expert to Design the Network by Hand

- Could get a domain expert to help design the Bayesian network
- Need the domain expert to come up with:
 - 1. Network Topology
 - 2. Parameters (i.e. probabilities) in the conditional probability tables

Designing the Network Topology

- Key point: Bayesian network exploits conditional independence to produce a compact representation of the full joint distribution
- Compactness is due to the fact that a Bayesian network is a locally structured system

Locally Structured Systems

- In a Bayes net, each node is directly influenced by a small number of other nodes (say k)
- This means that the CPT of each node has 2^k probabilities
- If there are n nodes overall, we need n2^k probabilities
- Suppose k = 5, n = 30, then n2^k=960
 probabilities but the full joint requires > 10⁹
 probabilities

7

What If The Network is Densely Connected?

Then your representation can't take advantage of conditional independence for compactness

- · Possible but unlikely
- Could drop a few links (sacrifice accuracy for compactness)


Constructing a Locally Structured Bayesian Network

- Needs:
 - Each variable to be directly influenced by a few others
 - 2. Parents are the direct influences of a node
- Process:
 - Add "root causes" first
 - Then the variables they influence
 - Keep going until you reach the "leaves" which do not have a direct causal influence on the other variables

9

Choosing the Wrong Order

What happens if you add nodes in the wrong order?



10

Choosing the Wrong Order

Compact network

Burglary Earthquake

Alarm

JohnCalls MaryCalls

Not-So-Compact Network

MaryCalls

JohnCalls

Alarm

Burglary

Earthquake

Two more links

Some links result in conditional probability tables that require unnatural/difficult probability judgments eg. P(Earthquake | Burglary, Alarm)

Choosing the Wrong Order

Compact network

Burglary Earthquake

Alarm

JohnCalls MaryCalls)

Not-So-Compact Network

MaryCalls

JohnCalls

Burglary

Earthquake

Note: Both networks can represent the same joint probability distribution. The problem is that the one on the right doesn't represent all the conditional independence relationships and some links need not be there

Diagnostic versus Causal models

- Build causal models i.e. a link from Node X to Node Y indicates X causes Y
- Don't build diagnostic models ie. Links go from symptoms to causes
- Diagnostic models result in additional dependencies between otherwise independent causes
- Causal models result in fewer parameters and easier parameters to come up with

13

Designing the Parameters in the Bayesian Network

- As was mentioned previously, make sure the probabilities in the CPT are natural and easy for an expert to come up with
- E.g. P(Earthquake | Burglary, Alarm) is not natural but P(Alarm | Burglary, Earthquake) is
- In general, coming up with these probabilities can be tricky
- E.g. A physician can't tell you exactly what P(Headache | Flu) is.

14

Designing the Parameters of the Bayesian Network

- Possible solutions:
 - Specify a range of values for that probability
 - Specify a distribution for the probability with a known form
 - Could get expert to encode relative relationships e.g. "This value is twice as likely as the other one"
 - Get probabilities from studies or census

15

Learning Bayesian Network Structure From Data

16

Learning Structure From Data

- You can think of the structure and parameters of the Bayesian network as representing causal knowledge about the domain
- If you don't have an expert, you can learn both the structure and parameters from data

17

Learning Structure From Data

- There are other good reasons for learning the structure/parameters from data
- The actual causal model may be unavailable or unknown
- The actual causal model may be subject to dispute (maybe because of a subjective bias by the domain expert)

Learning the Structure from Data

Two cases:

- 1. Complete data
- 2. Incomplete data

We will describe what these mean!

19

Complete Data

- Your domain is fully observable (i.e. you can observe the values of all the random variables in the data)
- · Your data has no missing values

No missing values

Has 3 missing values

140 illissing values			
Age	Gender	Home Zip	
50-60	Male	97330	
20-30	Female	97333	
40-50	Female	97331	

Age	Gender	Home Zip	
?	Male	97330	
20-30	Female	?	
?	Female	97331	

20

Parameter Learning From Complete Data

- Let's first assume that the Bayesian network structure is fixed
- Learning the parameters from complete data is easy (will say more in naïve Bayes context next time)
- We won't deal with incomplete data in this class

21

Learning the Structure

- Involves a search over possible directed acyclic graph structures to find the best fitting one
- However, for *n* nodes, there are the following number of possible structures [Robinson, 1973]:

 $O(n!2^{\binom{n}{2}})$


22

Learning the Structure

- This is clearly impossible to do an exhaustive search to find the optimal structure
- Need to resort to local search methods e.g. hill-climbing, simulated annealing
- We'll illustrate this using a 3 node example.

23

Local Search Methods Initial State: A B C Start with no links Start with a random set of links



Things to Watch Out For

- · Need to avoid introducing cycles
- Need to re-estimate parameters everytime you modify a link in the Bayes net
 - Do you need to re-estimate the parameters for all nodes?
 - No, just the ones that are affected by the modified link
- Lots of local optima problems. Use random restarts.

26

The Evaluation Function

- How do we know if a Bayes net structure is good?
- Two types of evaluation functions:
 - Evaluate if conditional independence relationships in the learned network match those in the data
 - 2. Evaluate how well the learned network explains the data (in the probabilistic sense).

27

What You Need To Know

- How to get an expert to design a Bayesian network by hand
- Briefly describe how you would use local search to learn the structure of a Bayesian network