
Trees

January 3, 2019

1 Binary Trees

- A Binary Tree is a collection of nodes
 - Each node has a left and a right pointer
 - A root node indicates the start of the tree
 - If the root is *None*, the tree is empty
- A Binary Search Tree is a binary tree where the value of any node is:
 - Greater than all the values in it's left subtree
 - Less than all the values in it's right subtree



2 Defining a Binary Search Tree

```
class Node:
    def __init__(self , item , left=None , right=None):
        self.item = item
        self.left = left
        self.right = right
class BST:
    \mathbf{def} __init__(self):
        self.root = None
    def rec_add(self, node, item):
        if node == None:
            return Node(item)
        elif item < node.item:</pre>
             node.left = self.rec_add(node.left, item)
        {f else}:
             node.rigth = self.rec_add(node.right, item)
        return node
    def add(self, item):
        self.root = self.rec_add(self.root, item)
```


3 Tree Traversals

- Tree Traversal is just a way to access every element in the tree
- This can be done in 3 orders;
 - InOrder
 - PreOrder
 - PostOrder

4 AVL trees

- \bullet An AVL tree is a Binary Search Tree where the height is maintained to O(logN)
 - This is done by adjusting the tree when it becomes unbalanced
 - A tree is considered unbalanced when the difference between the 2 child nodes is greater than 1
 - The add and delete operations need to be restructured to maintain balance

There are 4 ways that a tree can become unbalanced



In each case, the tree can be balanced by replacing the root with the middle element



5 AVL adding an element

- Add the node to the tree
- Starting at this node, move up the tree towards the root, checking to see if any node is unbalanced
 - If it is, find out which case it is and perform the corresponding restructuring
 - Do this every time an element is added
 - It seems like a lot of work, but it's only O(log N)
 - No more than one restructuring is required per insert