

---

# Problem Description

Working title:

- 1: Top-k relevant spatio-temporal retrieval on knowledge graphs using keyword search
- 2: Spatio-temporal keyword search on RDF graphs.

Work on problem description:

Knowledge graphs allows for easy extraction of facts from an entity, and the structure makes it efficient to find multi degree relations between different entities and facts. The task is to study indexing and search techniques on graphs containing spatio-temporal data, and propose effective ways to retrieve the data contained in the graph based on keyword searches.

---

---

# Introduction

## 1.1 Previous work

There has been done some work keyword search on RDF graphs. This includes [5] and [1]. None of these takes spatial or temporal data into consideration. The methods for keyword queries outlined in the papers are based on a combination of indexing the graph and traversing subgraphs. The indexing is similar in both papers, but retrieval, scoring and traversal methods varies. One method of retrieval and scoring that is used as a baseline is a breadth first search for traversal and a minimal subgraph for scoring. These methods are easy to implement and understand, but often inefficient, and inaccurate.

In paper [3] some methods for indexing, searching and ranking keyword searches on spatial RDF graphs is proposed. These methods builds upon the methods outlined in [5, 1]. The most substantial difference is the use of R-trees to index the spatial dimension of the graph. This is done so that a subgraph containing the keywords can be retrieved given a location. This method starts by finding the closest spatial vertex and uses that as the root for the subgraph. Subgraphs rooted in a spatial node requires different ranking, and there is proposed a set of rules in the paper.

R-trees are designed around the spatial dimension, but some work on modifications to include a temporal dimension has been done. Some research done on spatio-temporal tree structures include [4, 6]. Most of the spatio-temporal trees are however created to be able to query and index moving or frequently updated objects. To include a temporal dimension some differences in the tree structures are made. Most approaches builds on the R-tree, but modifies the tree in different aspects. For the purpose of this thesis a different tree structure is not needed.

---

---

# Spatio-temporal data structures

## 2.0.1 Spatial indexing

Most spatial indexing is done using R-trees. R-trees are based on a B-tree, but is optimized for indexing spatial dimensions. R-trees are able to effectively index spatial data by

## 2.0.2 Temporal indexing

In the dataset used in this thesis objects do not move, or move rarely. This makes indexing time unnecessary and it can be treated as a fact in the object with a start, and possible end time. This allows time to be retrieved as a fact when traversing the graph the same way as other facts.

---

---

## Basic retrieval methods

### 3.0.1 Bottom up BFS search

The most basic method of finding a match for keywords is using a bottom up breadth first search (BFS) [2]. For each keyword in the query the algorithm will find all vertices that contain the keyword. From that set of vertices the BFS search finds the first vertex that can connect all the vertices in the set. The vertex that connects the the rest of the set is the one that best fits the keywords in the search. There is however no guarantee that this set of vertices contains any spatial or temporal data. If this is the case, the search will continue until the a vertex containing spatial and temporal data is found. The first set of vertices containing all the keywords, a place, and time will be the best result using this search. The BFS search can however contain multiple times, or multiple places. To determine what time or what place best fits the query, a separate ranking algorithm can be used. BFS is also a time consuming algorithm and is used as a proof of concept and baseline in this thesis.

---

**Algorithm 1** Bottom up BFS

---

1: **procedure** BFS Insert algo here

---

---

---



# Bibliography

- [1] S. Elbassuoni and R. Blanco. Keyword search over rdf graphs. In *Proceedings of the 20th ACM International Conference on Information and Knowledge Management*, CIKM '11, pages 237–242, New York, NY, USA, 2011. ACM.
- [2] H. He, H. Wang, J. Yang, and P. S. Yu. Blinks: Ranked keyword searches on graphs. In *Proceedings of the 2007 ACM SIGMOD International Conference on Management of Data*, SIGMOD '07, pages 305–316, New York, NY, USA, 2007. ACM.
- [3] J. Shi, D. Wu, and N. Mamoulis. Top-k relevant semantic place retrieval on spatial rdf data. In *Proceedings of the 2016 International Conference on Management of Data*, SIGMOD '16, pages 1977–1990, New York, NY, USA, 2016. ACM.
- [4] Y. Tao, D. Papadias, and J. Sun. The tpr\*-tree: An optimized spatio-temporal access method for predictive queries. In *Proceedings of the 29th International Conference on Very Large Data Bases - Volume 29*, VLDB '03, pages 790–801. VLDB Endowment, 2003.
- [5] T. Tran, H. Wang, S. Rudolph, and P. Cimiano. Top-k exploration of query candidates for efficient keyword search on graph-shaped (rdf) data. In *2009 IEEE 25th International Conference on Data Engineering*, pages 405–416, March 2009.
- [6] S. Šaltenis, C. Jensen, C. (codirector, M. Böhlen, C. Dyreson, H. Gregersen, D. Simonas, J. Skyt, G. Slivinskas, K. Torp, R. (codirector, B. Moon, M. Soo, A. Com, and A. Timeconsult. R-tree based indexing of general spatio-temporal data. 01 2000.



---

# Appendix

Write your appendix here...