

2025.8.19 FedAvg优化



每个最好的结果记录时不要忘记截图、代码和输入的命令行参数

得到一个目前最好的结果，可以进一步改变参数，比如**全局轮数**、**本地轮数**、**frac比例**等

每种不同的方法都可以记录一下各自最好的结果

- **过拟合风险：**
 - CIFAR-100 的每类样本数量较少，ResNet 的高复杂性可能导致过拟合。
 - 解决方法：
 - 使用数据增强（如随机裁剪、翻转、颜色抖动等）。
 - 增加正则化（如 Dropout 或权重衰减）。
- **计算资源需求：**
 - ResNet 的深层结构需要更多的计算资源和训练时间。
 - 如果资源有限，可以选择较浅的 ResNet 变体（如 ResNet-18 或 ResNet-20）。

一、mnist数据集

1.iid

(1) 基线

sgd优化器

```
python baseline_main.py --dataset mnist --model cnn --epochs 100 --lr 0.01 --optimizer sgd --momentum 0.9 --local_bs 64 --gpu 0
```

```
class CNNMnist(nn.Module): # 定义一个针对 MNIST 数据集的 CNN 模型
    def __init__(self, args): # 构造函数，接收命令行参数作为输入
        super(CNNMnist, self).__init__()
        # 第一个卷积层：输入通道数为 args.num_channels (MNIST 为 1)，输出通道数为 10，卷积核大小为 5x5
```

```

self.conv1 = nn.Conv2d(args.num_channels, 10, kernel_size=5)
# 第二个卷积层：输入通道数为 10，输出通道数为 20，卷积核大小为 5x5
self.conv2 = nn.Conv2d(10, 20, kernel_size=5)
# Dropout 层，作用于2D特征图
self.conv2_drop = nn.Dropout2d()
# 第一个全连接层：输入特征数为 320 (这个值取决于前面卷积和池化后的
特征图大小)，输出特征数为 50
self.fc1 = nn.Linear(320, 50)
# 第二个全连接层 (输出层)：输入特征数为 50，输出特征数为 args.num_cl
asses (MNIST 为 10)
self.fc2 = nn.Linear(50, args.num_classes)

def forward(self, x): # 定义前向传播逻辑
    # x → conv1 → max_pool2d (2×2) → relu
    x = F.relu(F.max_pool2d(self.conv1(x), 2))
    # x → conv2 → conv2_drop → max_pool2d (2×2) → relu
    x = F.relu(F.max_pool2d(self.conv2_drop(self.conv2(x)), 2))
    # 将特征图展平
    x = x.view(-1, x.shape[1]*x.shape[2]*x.shape[3])
    x = F.relu(self.fc1(x)) # 通过第一个全连接层并应用 ReLU
    x = F.dropout(x, training=self.training) # 应用 Dropout, training=self.tr
aining 确保只在训练时生效
    x = self.fc2(x) # 通过输出层
    return F.log_softmax(x, dim=1) # 返回 log_softmax 输出，常用于 NLLLo
ss 损失函数

```

```

Train loss: 4.518198611775747e-05
Validation loss: 0.021804
Validation loss did not improve. Patience: 50/50
Early stopping triggered after 70 epochs
69%|██████████          | 69/100 [55:12<24:48, 48.01s/it]
Test on 10000 samples
Test Accuracy: 99.50%

```

adam优化器

```

python baseline_main.py --dataset mnist --model cnn --epochs 100 --lr 0.0
01 --optimizer adam --local_bs 64 --gpu 0

```



```
--iid 1 \  
--gpu 0
```

```
Avg Training Stats after 100 global rounds:  
Training Loss : 0.6703804306223983  
Train Accuracy: 96.67%  
  
100%|████████████████████████████████████████| 100/100 [25:19<00:00, 15.19s/it]  
  
Results after 100 global rounds of training:  
|---- Avg Train Accuracy: 96.67%  
|---- Test Accuracy: 94.31%
```

(3) 优化FedAvg

```
python federated_main_improved.py --dataset mnist --model cnn --epochs  
100 --lr 0.01 --frac 0.1 --num_users 100 --local_ep 10 --local_bs 32 --optimi  
zer adam --stopping_rounds 15 --gpu 0
```

```
class CNNMnist(nn.Module): # 基于ResNet思想的MNIST模型  
    def __init__(self, args):  
        super(CNNMnist, self).__init__()  
        # 使用ResNet-18的简化版本, 适配28x28的MNIST图像  
        self.conv1 = nn.Conv2d(args.num_channels, 64, kernel_size=3, stride=  
1, padding=1, bias=False)  
        self.bn1 = nn.BatchNorm2d(64)  
  
        # ResNet blocks - 使用残差连接  
        self.layer1 = self._make_layer(64, 64, 2, stride=1)  
        self.layer2 = self._make_layer(64, 128, 2, stride=2)  
        self.layer3 = self._make_layer(128, 256, 2, stride=2)  
        self.layer4 = self._make_layer(256, 512, 2, stride=2)  
  
        # 分类层  
        self.avgpool = nn.AdaptiveAvgPool2d((1, 1))  
        self.fc = nn.Linear(512, args.num_classes)  
        self.dropout = nn.Dropout(0.5)
```

```

def _make_layer(self, in_channels, out_channels, blocks, stride):
    layers = []
    # 第一个block可能需要下采样
    layers.append(ResBlock(in_channels, out_channels, stride))
    # 后续block保持尺寸
    for _ in range(1, blocks):
        layers.append(ResBlock(out_channels, out_channels, 1))
    return nn.Sequential(*layers)

def forward(self, x):
    x = F.relu(self.bn1(self.conv1(x)))

    x = self.layer1(x)
    x = self.layer2(x)
    x = self.layer3(x)
    x = self.layer4(x)

    x = self.avgpool(x)
    x = torch.flatten(x, 1)
    x = self.dropout(x)
    x = self.fc(x)

    return F.log_softmax(x, dim=1)

class ResBlock(nn.Module):
    """残差块"""
    def __init__(self, in_channels, out_channels, stride=1):
        super(ResBlock, self).__init__()
        self.conv1 = nn.Conv2d(in_channels, out_channels, kernel_size=3, stride=stride, padding=1, bias=False)
        self.bn1 = nn.BatchNorm2d(out_channels)
        self.conv2 = nn.Conv2d(out_channels, out_channels, kernel_size=3, stride=1, padding=1, bias=False)
        self.bn2 = nn.BatchNorm2d(out_channels)

        # 快捷连接

```



```
Avg Training Stats after 46 global rounds:
Training Loss : 0.053798211898697657
Train Accuracy: 9.00%

Early stopping triggered after 46 global rounds
Loaded best model weights for final testing.
45%|██████████          | 45/100 [57:57<1:10:50, 77.28s/it]

Results after 46 global rounds of training:
|---- Avg Train Accuracy: 9.00%
|---- Test Accuracy: 27.58%

Total Run Time: 3480.0439
```

adam优化器

```
python federated_main.py \
  --dataset mnist \
  --model cnn \
  --epochs 100 \
  --num_users 100 \
  --frac 0.1 \
  --local_ep 5 \
  --local_bs 10 \
  --lr 0.01 \
  --optimizer adam \
  --iid 0 \
  --gpu 0
```

```
Avg Training Stats after 100 global rounds:
Training Loss : 0.12197368648592397
Train Accuracy: 96.67%

100%|████████████████████| 100/100 [25:13<00:00, 15.14s/it]

Results after 100 global rounds of training:
|---- Avg Train Accuracy: 96.67%
|---- Test Accuracy: 34.01%
```

(2) 优化FedAvg

```
python federated_main_improved.py --dataset mnist --model cnn --  
epochs 100 --lr 0.001 --frac 0.1 --num_users 100 --local_ep 5 --  
-local_bs 32 --optimizer sgd --stopping_rounds 20 --gpu 0 --iid  
0
```

模型与iid的一样

```
Avg Training Stats after 100 global rounds:  
Training Loss : 0.12666636764254108  
Train Accuracy: 97.52%  
  
100%|█| 100/100 [37:04<00:00, 22.  
  
Results after 100 global rounds of training:  
|---- Avg Train Accuracy: 97.52%  
|---- Test Accuracy: 97.61%  
  
Total Run Time: 2227.2196
```

二、cifar10数据集

1.iid

(1) 基线

sgd优化器

```
python baseline_main.py --dataset cifar --model cnn --epochs 100 --lr 0.0  
5 --momentum 0.9 --local_bs 64 --num_classes 10 --num_channels 3 --gp  
u 0 --optimizer sgd --verbose 1
```

```
class CNNCifar(nn.Module): # 定义一个针对 CIFAR-10 数据集的 CNN 模型  
    def __init__(self, args):  
        super(CNNCifar, self).__init__()
```



```

# CIFAR-10 图像通道数为 3
self.conv1 = nn.Conv2d(3, 6, 5) # 输入通道 3, 输出通道 6, 5x5 核
self.pool = nn.MaxPool2d(2, 2) # 2x2 最大池化, 步长为 2
self.conv2 = nn.Conv2d(6, 16, 5) # 输入通道 6, 输出通道 16, 5x5 核
# 全连接层
self.fc1 = nn.Linear(16 * 5 * 5, 120) # 输入特征数取决于卷积和池化后的
尺寸
# CIFAR-10 图像 32x32 → conv1 (28x28) → pool
(14x14) → conv2 (10x10) → pool (5x5)
# 所以是 16 (通道数) * 5 * 5
self.fc2 = nn.Linear(120, 84)
self.fc3 = nn.Linear(84, args.num_classes) # 输出层, 类别数为 args.num_classes (CIFAR-10 为 10)

def forward(self, x):
    x = self.pool(F.relu(self.conv1(x))) # conv1 → relu → pool
    x = self.pool(F.relu(self.conv2(x))) # conv2 → relu → pool
    x = x.view(-1, 16 * 5 * 5) # 展平
    x = F.relu(self.fc1(x))
    x = F.relu(self.fc2(x))
    x = self.fc3(x)
    return F.log_softmax(x, dim=1) # 返回 log_softmax 输出

```

```

Avg Training Stats after 100 global rounds:
Training Loss : 0.42798910042929217
Train Accuracy: 46.00%

100%|████████████████████| 100/100 [1:22:44<00:00, 49.65s/it]

Results after 100 global rounds of training:
|---- Avg Train Accuracy: 46.00%
|---- Test Accuracy: 48.17%

```

adam优化器

(2) 普通FedAvg

```
python federated_main.py \  
  --model cnn \  
  --dataset cifar \  
  --epochs 100 \  
  --num_users 100 \  
  --frac 0.25 \  
  --local_ep 12 \  
  --local_bs 32 \  
  --lr 0.03 \  
  --momentum 0.9 \  
  --optimizer sgd \  
  --iid 1 \  
  --stopping_rounds 30 \  
  --verbose 1 \  
  --gpu 0
```

模型与基线相同

(3) 优化FedAvg

```
python src/federated_main.py \  
  --model cnn \  
  --dataset cifar \  
  --epochs 100 \  
  --num_users 100 \  
  --frac 0.25 \  
  --local_ep 12 \  
  --local_bs 32 \  
  --lr 0.03 \  
  --momentum 0.9 \  
  --optimizer sgd \  
  --iid 1 \  
  --early_stop 1 \  
  --stop_metric accuracy \  
  --stopping_rounds 30 \  
  --gpu 0
```

```
--verbose 1 \  
--gpu cuda:0
```

```
class CNNCifarOptimal(nn.Module):  
    def __init__(self, args):  
        super(CNNCifarOptimal, self).__init__()  
  
        # 第一个卷积块 - 保持输入特征  
        self.conv1 = nn.Sequential(  
            nn.Conv2d(3, 64, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(64),  
            nn.ReLU(inplace=True),  
            nn.Conv2d(64, 64, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(64),  
            nn.ReLU(inplace=True),  
        )  
  
        self.conv2 = nn.Sequential(  
            nn.Conv2d(64, 128, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(128),  
            nn.ReLU(inplace=True),  
            nn.Conv2d(128, 128, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(128),  
            nn.ReLU(inplace=True),  
            nn.MaxPool2d(2, 2),  
            nn.Dropout(0.2), # 减少dropout, 避免loss下降困难  
        )  
  
        self.conv3 = nn.Sequential(  
            nn.Conv2d(128, 256, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(256),  
            nn.ReLU(inplace=True),  
            nn.Conv2d(256, 256, kernel_size=3, padding=1, bias=False),  
            nn.BatchNorm2d(256),  
            nn.ReLU(inplace=True),  
            nn.MaxPool2d(2, 2),
```

```

        nn.Dropout(0.25), # 减少dropout
    )

    self.conv4 = nn.Sequential(
        nn.Conv2d(256, 512, kernel_size=3, padding=1, bias=False),
        nn.BatchNorm2d(512),
        nn.ReLU(inplace=True),
        nn.Conv2d(512, 512, kernel_size=3, padding=1, bias=False),
        nn.BatchNorm2d(512),
        nn.ReLU(inplace=True),
        nn.MaxPool2d(2, 2),
        nn.Dropout(0.3), # 减少dropout
    )

    # 优化分类器 - 减少参数复杂度，提高收敛性
    self.avgpool = nn.AdaptiveAvgPool2d((1, 1))
    self.classifier = nn.Sequential(
        nn.Dropout(0.4), # 减少dropout
        nn.Linear(512, 256), # 进一步减少参数量
        nn.ReLU(inplace=True),
        nn.Dropout(0.2), # 减少dropout
        nn.Linear(256, args.num_classes)
    )

    # 权重初始化
    self._initialize_weights()

    def _initialize_weights(self):
        for m in self.modules():
            if isinstance(m, nn.Conv2d):
                nn.init.kaiming_normal_(m.weight, mode='fan_out', nonlinearity='r
elu')
            elif isinstance(m, nn.BatchNorm2d):
                nn.init.constant_(m.weight, 1)
                nn.init.constant_(m.bias, 0)
            elif isinstance(m, nn.Linear):
                nn.init.normal_(m.weight, 0, 0.01)
                nn.init.constant_(m.bias, 0)

```

```
def forward(self, x):
    x = self.conv1(x)
    x = self.conv2(x)
    x = self.conv3(x)
    x = self.conv4(x)
    x = self.avgpool(x)
    x = torch.flatten(x, 1)
    x = self.classifier(x)
    return x
```

2.non-iid

(1) 普通FedAvg

```
python federated_main.py --dataset cifar --model cnn --epochs 100 --num
_users 100 --frac 0.2 --local_ep 15 --local_bs 20 --lr 0.003 --optimizer sgd
--iid 0 --gpu 0
```

模型与基线、iid相同

```
Avg Training Stats after 100 global rounds:
Training Loss : 0.2098459992642896
Train Accuracy: 16.00%

100%|████████████████████████████████████████| 100/100 [1:22:48<00:00, 49.68s/it]

Results after 100 global rounds of training:
|---- Avg Train Accuracy: 16.00%
|---- Test Accuracy: 36.97%
```

```
python federated_main.py \
    --model cnn \
    --dataset cifar \
    --epochs 100 \
    --num_users 100 \
```

```
--frac 0.25 \  
--local_ep 12 \  
--local_bs 32 \  
--lr 0.03 \  
--momentum 0.9 \  
--optimizer sgd \  
--iid 0 \  
--stopping_rounds 30 \  
--verbose 1 \  
--gpu 0
```

```
Avg Training Stats after 100 global rounds:  
Training Loss : 0.09779776720006017  
Train Accuracy: 8.00%  
  
100%|████████████████████| 100/100 [2:07:25<00:00, 76.46s/it]  
  
Results after 100 global rounds of training:  
|---- Avg Train Accuracy: 8.00%  
|---- Test Accuracy: 42.52%
```

(2) 优化FedAvg

三、cifar100数据集

1.iid

(1) 基线

sgd优化器

```
python baseline_main.py \  
--dataset cifar100 \  
--model cnn \  
--epochs 350 \  

```

```
--lr 0.035 \  
--optimizer sgd \  
--local_bs 64 \  
--num_classes 100 \  
--gpu 0 \  
--verbose 1
```

普通CNN模型

```
class CNNCifar100(nn.Module): # 定义一个针对 CIFAR-100 数据集的 CNN 模型  
    def __init__(self, args):  
        super(CNNCifar100, self).__init__()  
        # CIFAR-100 图像通道数为 3，类别数为 100  
        self.conv1 = nn.Conv2d(3, 32, 3, padding=1) # 输入通道 3, 输出通道 32,  
        3x3 核  
        self.conv2 = nn.Conv2d(32, 64, 3, padding=1) # 输入通道 32, 输出通道  
        64, 3x3 核  
        self.conv3 = nn.Conv2d(64, 128, 3, padding=1) # 输入通道 64, 输出通道  
        128, 3x3 核  
        self.pool = nn.MaxPool2d(2, 2) # 2x2 最大池化，步长为 2  
        self.dropout = nn.Dropout(0.5) # Dropout层防止过拟合  
  
        # 全连接层  
        # CIFAR-100 图像 32x32 → conv1+pool (16x16) → conv2+pool (8x8) →  
        conv3+pool (4x4)  
        # 所以是 128 (通道数) * 4 * 4  
        self.fc1 = nn.Linear(128 * 4 * 4, 512)  
        self.fc2 = nn.Linear(512, 256)  
        self.fc3 = nn.Linear(256, args.num_classes) # 输出层，CIFAR-100 有 10  
        0 个类别  
  
    def forward(self, x):  
        x = self.pool(F.relu(self.conv1(x))) # conv1 → relu → pool  
        x = self.pool(F.relu(self.conv2(x))) # conv2 → relu → pool  
        x = self.pool(F.relu(self.conv3(x))) # conv3 → relu → pool  
        x = x.view(-1, 128 * 4 * 4) # 展平  
        x = self.dropout(F.relu(self.fc1(x)))
```



```
--optimizer sgd \  
--iid 1 \  
--num_classes 100 \  
--gpu 0 \  
--verbose 1
```

模型和基线相同

```
Avg Training Stats after 350 global rounds:  
Training Loss : 0.2160085893932032  
Train Accuracy: 54.00%  
  
100%|████████████████████████████████████████████████████████████████████████████████| 350/350 [1:42:04<00:00, 20.05s/i  
100%|████████████████████████████████████████████████████████████████████████████████| 350/350 [1:42:04<00:00, 17.50s/i  
t]  
  
Results after 350 global rounds of training:  
|---- Avg Train Accuracy: 54.00%  
|---- Test Accuracy: 16.25%
```

adam优化器

```
python federated_main.py \  
--dataset cifar100 \  
--model cnn \  
--epochs 350 \  
--lr 0.035 \  
--num_users 40 \  
--frac 0.5 \  
--local_ep 8 \  
--local_bs 64 \  
--optimizer adam \  
--iid 1 \  
--num_classes 100 \  
--gpu 0 \  
--verbose 1
```

(3) 优化FedAvg

```
python federated_cifar100_main.py --model ultra --epochs 350 --num_users 40 --frac 0.5 --local_ep 10 --local_bs 64 --lr 0.004 --optimizer adamw --dropout_rate 0.3 --label_smoothing 0.1 --alpha 0.2 --gpu 0 --iid 1
```

```
#!/usr/bin/env python
# -*- coding: utf-8 -*-
"""
超强CIFAR-100模型：融合EfficientNet和CNNCifar100的优点
集成所有最先进的优化技术
"""

import torch
import torch.nn as nn
import torch.nn.functional as F
import math
from torchvision import transforms

class SEBlock(nn.Module):
    """Squeeze-and-Excitation注意力机制"""
    def __init__(self, in_channels, reduction=16):
        super(SEBlock, self).__init__()
        self.avg_pool = nn.AdaptiveAvgPool2d(1)
        self.fc = nn.Sequential(
            nn.Linear(in_channels, in_channels // reduction, bias=False),
            nn.ReLU(inplace=True),
            nn.Linear(in_channels // reduction, in_channels, bias=False),
            nn.Sigmoid()
        )

    def forward(self, x):
        b, c, _, _ = x.size()
        y = self.avg_pool(x).view(b, c)
        y = self.fc(y).view(b, c, 1, 1)
```

```
return x * y.expand_as(x)
```

```
class StochasticDepth(nn.Module):
```

```
    """随机深度，提升泛化能力"""
```

```
    def __init__(self, drop_rate):
```

```
        super(StochasticDepth, self).__init__()
```

```
        self.drop_rate = drop_rate
```

```
    def forward(self, x, skip_connection):
```

```
        if not self.training or self.drop_rate == 0.:
```

```
            return x + skip_connection
```

```
        keep_prob = 1 - self.drop_rate
```

```
        random_tensor = keep_prob + torch.rand((x.shape[0], 1, 1, 1),  
                                                dtype=x.dtype, device=x.device)
```

```
        binary_tensor = torch.floor(random_tensor)
```

```
        return (x / keep_prob) * binary_tensor + skip_connection
```

```
class EnhancedMBConvBlock(nn.Module):
```

```
    """增强的MBConv块，融合多种优化技术"""
```

```
    def __init__(self, in_channels, out_channels, stride, expand_ratio,
```

```
                 kernel_size=3, se_ratio=0.25, drop_rate=0.0):
```

```
        super(EnhancedMBConvBlock, self).__init__()
```

```
        self.stride = stride
```

```
        self.use_residual = stride == 1 and in_channels == out_channels
```

```
        # 扩展阶段
```

```
        expanded_channels = in_channels * expand_ratio
```

```
        self.expand_conv = None
```

```
        if expand_ratio != 1:
```

```
            self.expand_conv = nn.Sequential(  
                nn.Conv2d(in_channels, expanded_channels, 1, bias=False),  
                nn.BatchNorm2d(expanded_channels),  
                nn.SiLU(inplace=True)
```

```
            )
```

```

    )

    # 深度卷积
    self.depthwise_conv = nn.Sequential(
        nn.Conv2d(expanded_channels, expanded_channels, kernel_size,
                    stride=stride, padding=kernel_size//2, groups=expanded_channels, bias=False),
        nn.BatchNorm2d(expanded_channels),
        nn.SiLU(inplace=True)
    )

    # SE注意力机制
    self.se_block = SEBlock(expanded_channels, reduction=int(1/se_ratio))
    if se_ratio > 0 else None

    # 投影阶段
    self.project_conv = nn.Sequential(
        nn.Conv2d(expanded_channels, out_channels, 1, bias=False),
        nn.BatchNorm2d(out_channels)
    )

    # 随机深度
    self.stochastic_depth = StochasticDepth(drop_rate) if drop_rate > 0 else None

    def forward(self, x):
        identity = x

        # 扩展
        if self.expand_conv is not None:
            x = self.expand_conv(x)

        # 深度卷积
        x = self.depthwise_conv(x)

        # SE注意力
        if self.se_block is not None:
            x = self.se_block(x)

```

```

# 投影
x = self.project_conv(x)

# 残差连接（带随机深度）
if self.use_residual:
    if self.stochastic_depth is not None:
        x = self.stochastic_depth(x, identity)
    else:
        x = x + identity

return x

class UltraEfficientNetCIFAR100(nn.Module):
    """超强CIFAR-100模型，融合所有优化技术"""

    def __init__(self, num_classes=100, dropout_rate=0.4, stochastic_depth_r
ate=0.2):
        super(UltraEfficientNetCIFAR100, self).__init__()

        self.dropout_rate = dropout_rate

        # 更强的Stem层
        self.stem = nn.Sequential(
            nn.Conv2d(3, 40, kernel_size=3, stride=1, padding=1, bias=False),
            nn.BatchNorm2d(40),
            nn.SiLU(inplace=True)
        )

        # 深层架构配置 (参考您的CNNCifar100)
        # [expand_ratio, channels, num_blocks, stride, kernel_size, se_ratio]
        settings = [
            [1, 24, 1, 1, 3, 0.25], # stage 1: 32×32 → 32×32
            [6, 32, 2, 2, 3, 0.25], # stage 2: 32×32 → 16×16
            [6, 48, 3, 2, 5, 0.25], # stage 3: 16×16 → 8×8
            [6, 96, 4, 2, 3, 0.25], # stage 4: 8×8 → 4×4
            [6, 136, 4, 1, 5, 0.25], # stage 5: 4×4 → 4×4

```

```

        [6, 232, 5, 2, 5, 0.25], # stage 6: 4×4 → 2×2
        [6, 384, 2, 1, 3, 0.25], # stage 7: 2×2 → 2×2
    ]

    # 构建网络层
    self.stages = nn.ModuleList()
    in_channels = 40
    total_blocks = sum([blocks for _, _, blocks, _, _ in settings])
    block_id = 0

    for expand_ratio, channels, num_blocks, stride, kernel_size, se_ratio in
settings:
        stage = nn.ModuleList()

        for i in range(num_blocks):
            block_stride = stride if i == 0 else 1
            # 计算随机深度率
            drop_rate = stochastic_depth_rate * block_id / total_blocks

            stage.append(EnhancedMBConvBlock(
                in_channels, channels, block_stride, expand_ratio,
                kernel_size, se_ratio, drop_rate
            ))
            in_channels = channels
            block_id += 1

        self.stages.append(stage)

    # 更强的头部
    self.head_conv = nn.Conv2d(384, 1536, kernel_size=1, bias=False)
    self.head_bn = nn.BatchNorm2d(1536)
    self.avgpool = nn.AdaptiveAvgPool2d(1)

    # 多层分类器（参考您的设计）
    self.classifier = nn.Sequential(
        nn.Dropout(dropout_rate),
        nn.Linear(1536, 768),
        nn.BatchNorm1d(768),

```

```

        nn.SiLU(inplace=True),
        nn.Dropout(dropout_rate * 0.7),
        nn.Linear(768, 384),
        nn.BatchNorm1d(384),
        nn.SiLU(inplace=True),
        nn.Dropout(dropout_rate * 0.5),
        nn.Linear(384, num_classes)
    )

    # 权重初始化
    self._initialize_weights()

def _initialize_weights(self):
    """改进的权重初始化"""
    for m in self.modules():
        if isinstance(m, nn.Conv2d):
            nn.init.kaiming_normal_(m.weight, mode='fan_out', nonlinearity='r
elu')
        elif isinstance(m, nn.BatchNorm2d):
            nn.init.constant_(m.weight, 1)
            nn.init.constant_(m.bias, 0)
        elif isinstance(m, nn.Linear):
            nn.init.normal_(m.weight, 0, 0.01)
            if m.bias is not None:
                nn.init.constant_(m.bias, 0)

def forward(self, x):
    # Stem
    x = self.stem(x)

    # 所有stage
    for stage in self.stages:
        for block in stage:
            x = block(x)

    # Head
    x = F.silu(self.head_bn(self.head_conv(x)))
    x = self.avgpool(x)

```

```

x = torch.flatten(x, 1)

# 分类器
x = self.classifier(x)

return F.log_softmax(x, dim=1)

def get_ultra_cifar100_model(dropout_rate=0.4):
    """获取超强CIFAR-100模型"""
    return UltraEfficientNetCIFAR100(
        num_classes=100,
        dropout_rate=dropout_rate,
        stochastic_depth_rate=0.2
    )

# 改进的数据增强策略
def get_ultra_transforms(is_training=True):
    """超强数据增强策略"""
    if is_training:
        return transforms.Compose([
            transforms.RandomCrop(32, padding=4),
            transforms.RandomHorizontalFlip(p=0.5),
            transforms.RandomRotation(15),
            transforms.ColorJitter(
                brightness=0.4,
                contrast=0.4,
                saturation=0.4,
                hue=0.1
            ),
            transforms.RandomAffine(degrees=0, translate=(0.1, 0.1)),
            transforms.ToTensor(),
            transforms.Normalize(
                mean=[0.5071, 0.4867, 0.4408],
                std=[0.2675, 0.2565, 0.2761]
            ),
            transforms.RandomErasing(p=0.1, scale=(0.02, 0.33), ratio=(0.3, 3.

```



```

3))
    ])
else:
    return transforms.Compose([
        transforms.ToTensor(),
        transforms.Normalize(
            mean=[0.5071, 0.4867, 0.4408],
            std=[0.2675, 0.2565, 0.2761]
        )
    ])

```

改进的损失函数

```

class LabelSmoothingCrossEntropy(nn.Module):
    """标签平滑交叉熵损失"""
    def __init__(self, epsilon=0.1, reduction='mean'):
        super(LabelSmoothingCrossEntropy, self).__init__()
        self.epsilon = epsilon
        self.reduction = reduction

    def forward(self, input, target):
        log_prob = F.log_softmax(input, dim=-1)
        weight = input.new_ones(input.size()) * self.epsilon / (input.size(-1) -
1.)
        weight.scatter_(-1, target.unsqueeze(-1), (1. - self.epsilon))
        loss = (-weight * log_prob).sum(dim=-1)

        if self.reduction == 'mean':
            return loss.mean()
        elif self.reduction == 'sum':
            return loss.sum()
        return loss

if __name__ == "__main__":
    # 测试模型
    model = get_ultra_cifar100_model()
    x = torch.randn(2, 3, 32, 32)

```

```

output = model(x)
print(f"Model output shape: {output.shape}")
print(f"Model parameters: {sum(p.numel() for p in model.parameters() if
p.requires_grad):,}")

```

```

#!/usr/bin/env python
# -*- coding: utf-8 -*-
"""
轻量级Ultra CIFAR-100模型：优化版本，减少复杂度，提升训练速度
"""

import torch
import torch.nn as nn
import torch.nn.functional as F

class LightweightSEBlock(nn.Module):
    """轻量级SE注意力机制"""
    def __init__(self, in_channels, reduction=16):
        super(LightweightSEBlock, self).__init__()
        self.avg_pool = nn.AdaptiveAvgPool2d(1)
        self.fc = nn.Sequential(
            nn.Linear(in_channels, max(in_channels // reduction, 8), bias=False),
            nn.ReLU(inplace=True),
            nn.Linear(max(in_channels // reduction, 8), in_channels, bias=False),
            nn.Sigmoid()
        )

    def forward(self, x):
        b, c, _, _ = x.size()
        y = self.avg_pool(x).view(b, c)
        y = self.fc(y).view(b, c, 1, 1)
        return x * y

```

```

class LightweightMBConvBlock(nn.Module):
    """轻量级MBConv块"""

    def __init__(self, in_channels, out_channels, stride, expand_ratio,
                 kernel_size=3, se_ratio=0.25):
        super(LightweightMBConvBlock, self).__init__()

        self.stride = stride
        self.use_residual = stride == 1 and in_channels == out_channels

        # 扩展阶段
        expanded_channels = in_channels * expand_ratio
        self.expand_conv = None
        if expand_ratio != 1:
            self.expand_conv = nn.Sequential(
                nn.Conv2d(in_channels, expanded_channels, 1, bias=False),
                nn.BatchNorm2d(expanded_channels),
                nn.ReLU6(inplace=True) # 使用ReLU6替代SiLU，速度更快
            )

        # 深度卷积
        self.depthwise_conv = nn.Sequential(
            nn.Conv2d(expanded_channels, expanded_channels, kernel_size,
                     stride=stride, padding=kernel_size//2, groups=expanded_channels, bias=False),
            nn.BatchNorm2d(expanded_channels),
            nn.ReLU6(inplace=True)
        )

        # 轻量级SE注意力
        self.se_block = LightweightSEBlock(expanded_channels, reduction=16) if se_ratio > 0 else None

        # 投影阶段
        self.project_conv = nn.Sequential(
            nn.Conv2d(expanded_channels, out_channels, 1, bias=False),
            nn.BatchNorm2d(out_channels)

```

```

    )

    def forward(self, x):
        identity = x

        # 扩展
        if self.expand_conv is not None:
            x = self.expand_conv(x)

        # 深度卷积
        x = self.depthwise_conv(x)

        # SE注意力
        if self.se_block is not None:
            x = self.se_block(x)

        # 投影
        x = self.project_conv(x)

        # 残差连接
        if self.use_residual:
            x = x + identity

        return x

class LightweightUltraCIFAR100(nn.Module):
    """轻量级Ultra CIFAR-100模型，优化训练速度"""

    def __init__(self, num_classes=100, dropout_rate=0.3):
        super(LightweightUltraCIFAR100, self).__init__()

        self.dropout_rate = dropout_rate

        # 简化的Stem层
        self.stem = nn.Sequential(
            nn.Conv2d(3, 32, kernel_size=3, stride=1, padding=1, bias=False),
            nn.BatchNorm2d(32),

```

```

        nn.ReLU6(inplace=True)
    )

    # 简化的架构配置 - 减少块数量
    # [expand_ratio, channels, num_blocks, stride, kernel_size, se_ratio]
    settings = [
        [1, 16, 1, 1, 3, 0.25], # stage 1: 32×32 → 32×32
        [6, 24, 2, 2, 3, 0.25], # stage 2: 32×32 → 16×16
        [6, 40, 2, 2, 5, 0.25], # stage 3: 16×16 → 8×8
        [6, 80, 3, 2, 3, 0.25], # stage 4: 8×8 → 4×4
        [6, 112, 2, 1, 5, 0.25], # stage 5: 4×4 → 4×4
        [6, 192, 2, 2, 5, 0.25], # stage 6: 4×4 → 2×2
    ]

    # 构建网络层
    self.stages = nn.ModuleList()
    in_channels = 32

    for expand_ratio, channels, num_blocks, stride, kernel_size, se_ratio in
settings:
        stage = nn.ModuleList()

        for i in range(num_blocks):
            block_stride = stride if i == 0 else 1

            stage.append(LightweightMBConvBlock(
                in_channels, channels, block_stride, expand_ratio,
                kernel_size, se_ratio
            ))
            in_channels = channels

        self.stages.append(stage)

    # 简化的头部
    self.head_conv = nn.Conv2d(192, 1280, kernel_size=1, bias=False)
    self.head_bn = nn.BatchNorm2d(1280)
    self.avgpool = nn.AdaptiveAvgPool2d(1)

```

```

# 简化的分类器
self.classifier = nn.Sequential(
    nn.Dropout(dropout_rate),
    nn.Linear(1280, 512),
    nn.ReLU6(inplace=True),
    nn.Dropout(dropout_rate * 0.7),
    nn.Linear(512, num_classes)
)

# 权重初始化
self._initialize_weights()

def _initialize_weights(self):
    """权重初始化"""
    for m in self.modules():
        if isinstance(m, nn.Conv2d):
            nn.init.kaiming_normal_(m.weight, mode='fan_out', nonlinearity='relu')
        elif isinstance(m, nn.BatchNorm2d):
            nn.init.constant_(m.weight, 1)
            nn.init.constant_(m.bias, 0)
        elif isinstance(m, nn.Linear):
            nn.init.normal_(m.weight, 0, 0.01)
            if m.bias is not None:
                nn.init.constant_(m.bias, 0)

def forward(self, x):
    # Stem
    x = self.stem(x)

    # 所有stage
    for stage in self.stages:
        for block in stage:
            x = block(x)

    # Head
    x = F.relu6(self.head_bn(self.head_conv(x)))
    x = self.avgpool(x)

```

```

        x = torch.flatten(x, 1)

        # 分类器
        x = self.classifier(x)

        return F.log_softmax(x, dim=1)

def get_lightweight_ultra_cifar100_model(dropout_rate=0.3):
    """获取轻量级Ultra CIFAR-100模型"""
    return LightweightUltraCIFAR100(
        num_classes=100,
        dropout_rate=dropout_rate
    )

if __name__ == "__main__":
    # 测试模型
    model = get_lightweight_ultra_cifar100_model()
    x = torch.randn(2, 3, 32, 32)
    output = model(x)
    print(f"Model output shape: {output.shape}")
    print(f"Model parameters: {sum(p.numel() for p in model.parameters() if
p.requires_grad):,}")

```

```

python federated_cifar100_main.py --model lightweight_ultra --epochs 350
--num_users 20 --frac 0.5 --local_ep 5 --local_bs 64 --lr 0.01 --optimizer s
gd --momentum 0.9 --weight_decay 5e-4 --dropout_rate 0.3 --label_smoot
hing 0.1 --alpha 0.3 --gpu 0 --iid 1

```

2.non-iid

(1) 普通FedAvg

```

python federated_main.py \
--dataset cifar100 \

```

```
--model cnn \  
--epochs 350 \  
--lr 0.035 \  
--num_users 40 \  
--frac 0.5 \  
--local_ep 8 \  
--local_bs 64 \  
--optimizer sgd \  
--iid 0 \  
--num_classes 100 \  
--gpu 0 \  
--verbose 1
```

(2) 优化FedAvg

```
python federated_cifar100_main.py --model lightweight_ultra --epochs 200  
--num_users 20 --frac 0.5 --local_ep 5 --local_bs 64 --lr 0.001 --optimizer  
adamw --weight_decay 1e-3 --dropout_rate 0.3 --label_smoothing 0.1 --alp  
ha 0.3 --gpu 0 --iid 0
```