


Use case

Hosting a static website on S3


Use case discription

setting up a public bucket, uploading HTML files, and configuring permissions and static website hosting.


1. Login to AWS management console and navigate to S3 service - General Purpose Buckets
2. Create a new bucket




3. Enter the bucket configuration values like name, versioning, etc. and create bucket




- From the list of buckets, click on the newly created bucket and upload the objects from local machine



- In the upload section, add files that are required for static website hosting including html and other resource files and upload



- In the bucket properties, enable static website hosting



aws Search [Alt+S] Asia Pacific (Mumbai) aws-dineshkarasu (7704-2476-7712) dominic

Amazon S3 > Buckets > my-bucket-114 > Edit static website hosting

Edit static website hosting [Info](#)

Static website hosting
Use this bucket to host a website or redirect requests. [Learn more](#)

Static website hosting
☐ Disable
☒ Enable

Hosting type
☒ Host a static website
Use the bucket endpoint as the web address. [Learn more](#)
☐ Redirect requests for an object
Redirect requests to another bucket or domain. [Learn more](#)

For your customers to access content at the website endpoint, you must make all your content publicly readable. To do so, you can edit the S3 Block Public Access settings for the bucket. For more information, see [Using Amazon S3 Block Public Access](#)

Index document
Specify the home or default page of the website.

Error document - optional
This is returned when an error occurs.

Redirection rules - optional
Redirection rules, written in JSON, automatically redirect webpage requests for specific content. [Learn more](#)

7. Allow public access in bucket settings

aws Search [Alt+S] Asia Pacific (Mumbai) aws-dineshkarasu (7704-2476-7712) dominic

Amazon S3 > Buckets > my-bucket-114 > Edit Block public access (bucket settings)

Edit Block public access (bucket settings) [Info](#)

Block public access (bucket settings)
Public access is granted to buckets and objects through access control lists (ACLs), bucket policies, access point policies, or all. In order to ensure that public access to all your S3 buckets and objects is blocked, turn on Block all public access. These settings apply only to this bucket and its individual settings below to suit your specific storage use cases. [Learn more](#)

☐ **Block all public access**
Turning this setting on is the same as turning on all four settings below. Each of the following settings are independent of one another.

- ☐ **Block public access to buckets and objects granted through new access control lists (ACLs)**
S3 will block public access permissions applied to newly added buckets or objects, and prevent the creation of new public access ACLs for existing buckets and objects. This setting doesn't change any existing permissions that allow public access to S3 resources using ACLs.
- ☐ **Block public access to buckets and objects granted through any access control lists (ACLs)**
S3 will ignore all ACLs that grant public access to buckets and objects.
- ☐ **Block public access to buckets and objects granted through new public bucket or access point policies**
S3 will block new bucket and access point policies that grant public access to buckets and objects. This setting doesn't change any existing policies that allow public access to S3 resources.
- ☐ **Block public and cross-account access to buckets and objects through any public bucket or access point policies**
S3 will ignore public and cross-account access for buckets or access points with policies that grant public access to buckets and objects.

[Cancel](#) [Save changes](#)

8. Add GetObject Bucket policy to make the object publicly accessible

Use a comma to separate multiple values.

Actions
☐ All Actions (***)
--Select Actions--

Amazon Resource Name (ARN)
☐ All Resources (***)
ARN should follow the following format: arn:aws:s3:::my-bucket-114/*

Add conditions (optional)
[Add Statement](#)

Statements added (1)
You added the following statements. Click the **Remove** button to delete a statement.

Principal(s)	Effect
*	Allow

Step 3: Generate policy
A policy is a document (written in the Access Policy Language) that defines the permissions for your Amazon Web Services resources.

[Generate Policy](#)

Policy JSON Document

Click below to edit. To save the policy, copy the text below to a text editor. Changes made below will **not** be reflected in the policy generator tool.


```
1 {
2   "Version": "2012-10-17",
3   "Statement": [
4     {
5       "Sid": "Statement1",
6       "Effect": "Allow",
7       "Principal": "*",
8       "Action": [
9         "s3:GetObject"
10      ],
11      "Resource": "arn:aws:s3:::my-bucket-114/*"
12    }
13  ]
14 }
```

1:1 JSON


This AWS Policy Generator is provided for informational purposes only, you are still responsible for your use of Amazon Web Services technologies and ensuring that your use is in compliance with all applicable terms and conditions. This AWS Policy Generator is provided as is without warranty of any kind, whether express, implied, or statutory. This AWS Policy Generator does not modify the applicable terms and conditions governing your use of Amazon Web Services technologies.

[Close](#)

9. Now we can access our hosted website using the URL provided at the bottom of the static website hosting window



10. Verify the webpage hosted correctly



Hi

This is a static website hosted on S3



Key Takeaways :

1. Created S3 Bucket
2. Assigned proper bucket policy to make the objects available to everyone
3. Understood usage of Block/Allow public access of S3 buckets
4. Added files to the bucket and hosted a static website