

MySQL Transaction

Summary: in this tutorial, you will learn about **MySQL transaction** and how to use MySQL COMMIT statement and MySQL ROLLBACK statement to manage transactions in MySQL.

Introducing to MySQL Transaction

To understand what a transaction in MySQL is, let's take a look at an example of adding a new sales order in our [sample database](#). The steps of adding a sales order are as described as follows:

Query the latest sales order number from the `orders` table, and use the next sales order number as the new sales order number.

Insert a new sales order into the `orders` table for a given customer.

Insert new sales order items into the `orderdetails` table.

Get data from both table `orders` and `orderdetails` tables to confirm the changes

Now imagine what would happen to your data if one or more steps above fail because of database failure such as table lock security? If the step of adding order items into `orderdetails` table failed, you would have an empty sales order in your system without knowing it. Your data may not be integrity and the effort you have to spend to fix it is tremendous.

How do you solve this problem? That's why the transaction processing comes to the rescue. MySQL transaction enables you to execute a set of MySQL operations to ensure that the database never contains the result of partial operations. In a set of operations, if one of them fails, the rollback occurs to restore the database. If no error occurred, the entire set of statements is committed to the database.

Using MySQL Transaction

Let's review the most important MySQL transaction statements before we are using them for the adding sales order in the example above.

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL](#) ▼[INTERFACES](#) ▼[TIPS](#)[TRYIT](#)

```
1 CREATE / ALTER / DROP DATABASE
2 CREATE /ALTER / DROP / RENAME / TRUNCATE TABLE
3 CREATE / DROP INDEX
4 CREATE / DROP EVENT
5 CREATE / DROP FUNCTION
6 CREATE / DROP PROCEDURE
7 ...
```

To write the changes into the database within a transaction, you use the `COMMIT` statement. It is important to note that MySQL automatically commits the changes to the database by default.

To force MySQL not to commit changes automatically, you use the following statement:

```
1 SET autocommit = 0;
```

MySQL transaction example

In order to use MySQL transaction, you first have to break your MySQL statements into logical portions and determine when data should be committed or rolled back.

Let's take a look an example of using MySQL transaction to add new sales order into our sample database above and add the transaction processing steps:

Start a transaction using `START TRANSACTION` statement.

Get latest sales order number from the `orders` table, and use the next sales order number as the new sales order number.

Insert a new sales order into the `orders` table for a given customer.

Insert new sales order items into the `orderdetails` table.

Commit changes using `COMMIT` statement.

Get data from both table `orders` and `orderdetails` tables to confirm the changes.

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL](#) ▾[INTERFACES](#) ▾[TIPS](#)[TRYIT](#)

```
4 -- get latest order number
5 select @orderNumber := max(orderNumber)
6 from orders;
7 -- set new order number
8 set @orderNumber = @orderNumber + 1;
9
10 -- insert a new order for customer 145
11 insert into orders(orderNumber,
12                    orderDate,
13                    requiredDate,
14                    shippedDate,
15                    status,
16                    customerNumber)
17 values(@orderNumber,
18        now(),
19        date_add(now(), INTERVAL 5 DAY),
20        date_add(now(), INTERVAL 2 DAY),
21        'In Process',
22        145);
23 -- insert 2 order line items
24 insert into orderdetails(orderNumber,
25                          productCode,
26                          quantityOrdered,
27                          priceEach,
28                          orderLineNumber)
29 values(@orderNumber, 'S18_1749', 30, '136', 1),
30        (@orderNumber, 'S18_2248', 50, '55.09', 2);
31 -- commit changes
32 commit;
33
34 -- get the new inserted order
35 select * from orders a
36 inner join orderdetails b on a.orderNumber = b.orderNumber
37 where a.orderNumber = @orderNumber;
```

In this tutorial, you've learned how to use MySQL transaction statements that include `START TRANSACTION`, `COMMIT`, and `ROLLBACK` to manage transactions in MySQL to protect data integrity.

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL](#) ▼[INTERFACES](#) ▼[TIPS](#)[TRYIT](#)[MySQL JDBC Transaction](#)

MySQL Table Locking

 [Tweet](#) [in](#)

0



Previous Tutorial:

[MySQL REPLACE](#)

Next Tutorial:

[MySQL Table Locking](#)

MYSQL QUICK START

[What Is MySQL?](#)[Install MySQL Database Server](#)[Download MySQL Sample Database](#)[Load Sample Database](#)

MYSQL DATA MANIPULATION

[MySQL SELECT](#)[MySQL DISTINCT](#)[MySQL WHERE](#)[MySQL AND](#)[MySQL OR](#)

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL ▾](#)[INTERFACES ▾](#)[TIPS](#)[TRYIT](#)

[MySQL ORDER BY](#)[MySQL Alias](#)[MySQL Join](#)[MySQL INNER JOIN](#)[MySQL LEFT JOIN](#)[MySQL RIGHT JOIN](#)[MySQL CROSS JOIN](#)[MySQL Self Join](#)[MySQL GROUP BY](#)[MySQL HAVING](#)[MySQL Subquery](#)[MySQL UNION](#)[MySQL MINUS](#)[MySQL INTERSECT](#)[MySQL INSERT Statement](#)[MySQL Insert Or Update](#)[MySQL LAST_INSERT_ID Function](#)[MySQL UPDATE](#)[MySQL UPDATE JOIN](#)[MySQL DELETE](#)[MySQL DELETE JOIN](#)[MySQL ON DELETE CASCADE](#)[MySQL REPLACE](#)

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL ▾](#)[INTERFACES ▾](#)[TIPS](#)[TRYIT](#)

MySQL Data Types

[MySQL CREATE TABLE](#)[MySQL Primary Key](#)[MySQL Foreign Key](#)[MySQL Sequence](#)[MySQL INT Data Type](#)[MySQL BOOLEAN](#)[MySQL BIT](#)[MySQL DECIMAL Data Type](#)[MySQL DATE Data Type](#)[MySQL TIME Data Type](#)[MySQL TIMESTAMP](#)[MySQL DATETIME Data Type](#)[MySQL ENUM](#)[MySQL VARCHAR](#)[MySQL CHAR](#)[MySQL ALTER TABLE](#)[MySQL RENAME TABLE](#)[MySQL ADD COLUMN](#)[MySQL DROP TABLE](#)[MySQL Temporary Table](#)[MySQL JSON](#)

[HOME](#)[BASIC MYSQL](#)[ADVANCED MYSQL ▾](#)[INTERFACES ▾](#)[TIPS](#)[TRYIT](#)[Perl MySQL Tutorial](#)[MySQL JDBC Tutorial](#)

OTHER TUTORIALS

[MySQL Administration](#)[MySQL Full-Text Search](#)[MySQL Cheat Sheet](#)[MySQL Books and Video Training](#)[MySQL Hosting](#)[MySQL Resources](#)[MySQL MINUS](#)[MySQL Join Made Easy](#)[How To Delete Duplicate Rows in MySQL](#)[How To Find Duplicate Values in MySQL](#)[MySQL LAST_DAY Function](#)[MySQL EXTRACT Function](#)[MySQL SYSDATE Function](#)[MySQL CURDATE Function](#)

ABOUT MYSQL TUTORIAL WEBSITE

MySQLTutorial.org is a website dedicated to MySQL database. We regularly publish useful MySQL tutorials to help web developers and database administrators learn MySQL faster and more effectively.

All MySQL tutorials are practical and easy-to-follow, with SQL script and screenshots available. [More About Us](#)

SITE LINKS

[About Us](#)[Contact Us](#)[Request a Tutorial](#)[Privacy Policy](#)

[HOME](#)

[BASIC MYSQL](#)

[ADVANCED MYSQL](#) ▼

[INTERFACES](#) ▼

[TIPS](#)

[TRYIT](#)
