```php
use Illuminate\Support\Facades\App;

class LanguageManager
{
    /**
     * On s'assure que l'application applique la langue
     *
     * @param  \Closure(\Illuminate\Http\Request):
(\Symfony\Component\HttpFoundation\Response)  $next
     */
    public function handle(Request $request, Closure $next): Response
    {
        if (session()->has('locale'))
        {
            App::setLocale(session()->get('locale'));
        }

        return $next($request);
    }
}
```

app/Http/Kernel.php

```php
<?php

namespace App\Http;


use Illuminate\Foundation\Http\Kernel as HttpKernel;

class Kernel extends HttpKernel
{
    /**
     * The application's global HTTP middleware stack.
     *
     * These middleware are run during every request to your application.
     *
     * @var array<int, class-string|string>
     */
    protected $middleware = [
        \App\Http\Middleware\TrustProxies::class,
        \Illuminate\Http\Middleware\HandleCors::class,
        \App\Http\Middleware\PreventRequestsDuringMaintenance::class,
        \Illuminate\Foundation\Http\Middleware\ValidatePostSize::class,
        \App\Http\Middleware\TrimStrings::class,
        \Illuminate\Foundation\Http\Middleware\ConvertEmptyStringsToNull::class,
    ];

    /**
     * The application's route middleware groups.
     *
     * @var array<string, array<int, class-string|string>>
     */
    protected $middlewareGroups = [
```