Middleware / Kernel / Providers

app/Http/Middleware/Categorie.php
app/Http/Middleware/LanguageManager.php
app/Http/Kernel.php
app/Providers/RouteServiceProvider.php

app/Http/Middleware/Categorie.php

```php
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Symfony\Component\HttpFoundation\Response;

class Categorie
{
    /**
     * Vérification des droits d'accès
     *
     * @param  \Closure(\Illuminate\Http\Request):
(\Symfony\Component\HttpFoundation\Response)  $next
     */
    public function handle(Request $request, Closure $next, ... $categories):
Response
    {
        // On parcours les categories donnees en argument
        foreach($categories as $categorie)
        {
            // On s'assure si l'utilisateur a bien la categorie demandé
            if(Auth::user()->categorie->value == $categorie)
            {
                return $next($request);
            }
        }
        return redirect()->route('CMC');
    }
}
```

app/Http/Middleware/LanguageManager.php

```php
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\Response;
```

```php
use Illuminate\Support\Facades\App;

class LanguageManager
{
    /**
     * On s'assure que l'application applique la langue
     *
     * @param  \Closure(\Illuminate\Http\Request):
(\Symfony\Component\HttpFoundation\Response)  $next
     */
    public function handle(Request $request, Closure $next): Response
    {
        if (session()->has('locale'))
        {
            App::setLocale(session()->get('locale'));
        }

        return $next($request);
    }
}
```

app/Http/Kernel.php

```php
<?php

namespace App\Http;


use Illuminate\Foundation\Http\Kernel as HttpKernel;

class Kernel extends HttpKernel
{
    /**
     * The application's global HTTP middleware stack.
     *
     * These middleware are run during every request to your application.
     *
     * @var array<int, class-string|string>
     */
    protected $middleware = [
        \App\Http\Middleware\TrustProxies::class,
        \Illuminate\Http\Middleware\HandleCors::class,
        \App\Http\Middleware\PreventRequestsDuringMaintenance::class,
        \Illuminate\Foundation\Http\Middleware\ValidatePostSize::class,
        \App\Http\Middleware\TrimStrings::class,
        \Illuminate\Foundation\Http\Middleware\ConvertEmptyStringsToNull::class,
    ];

    /**
     * The application's route middleware groups.
     *
     * @var array<string, array<int, class-string|string>>
     */
    protected $middlewareGroups = [
```

```
        'web' => [
            \App\Http\Middleware\EncryptCookies::class,
            \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::class,
            \Illuminate\Session\Middleware\StartSession::class,
            \Illuminate\View\Middleware\ShareErrorsFromSession::class,
            \App\Http\Middleware\VerifyCsrfToken::class,
            \Illuminate\Routing\Middleware\SubstituteBindings::class,
            \App\Http\Middleware\LanguageManager::class,
        ],

        'api' => [
            \Illuminate\Routing\Middleware\ThrottleRequests::class.':api',
            \Illuminate\Routing\Middleware\SubstituteBindings::class,
        ],
    ];

    /**
     * The application's middleware aliases.
     *
     * Aliases may be used instead of class names to conveniently assign middleware
to routes and groups.
     *
     * @var array<string, class-string|string>
     */
    protected $middlewareAliases = [
        'auth' => \App\Http\Middleware\Authenticate::class,
        'auth.basic' => \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
        'auth.session' => \Illuminate\Session\Middleware\AuthenticateSession::class,
        'cache.headers' => \Illuminate\Http\Middleware\SetCacheHeaders::class,
        'can' => \Illuminate\Auth\Middleware\Authorize::class,
        'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
        'password.confirm' => \Illuminate\Auth\Middleware\RequirePassword::class,
        'signed' => \App\Http\Middleware\ValidateSignature::class,
        'throttle' => \Illuminate\Routing\Middleware\ThrottleRequests::class,
        'verified' => \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
        'categorie' => \App\Http\Middleware\Categorie::class,
    ];
}
```

app/Providers/RouteServiceProvider.php

```
<?php

namespace App\Providers;

use Illuminate\Cache\RateLimiting\Limit;
use Illuminate\Foundation\Support\Providers\RouteServiceProvider as ServiceProvider;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\RateLimiter;
use Illuminate\Support\Facades\Route;

class RouteServiceProvider extends ServiceProvider
{
    /**
```

```php
     * The path to your application's "home" route.
     *
     * Typically, users are redirected here after authentication.
     *
     * @var string
     */
    public const HOME = '/creation_modification_comptes';

    /**
     * Define your route model bindings, pattern filters, and other route
configuration.
     */
    public function boot(): void
    {
        RateLimiter::for('api', function (Request $request) {
            return Limit::perMinute(60)->by($request->user()?->id ?: $request->ip());
        });

        $this->routes(function () {
            Route::middleware('api')
                ->prefix('api')
                ->group(base_path('routes/api.php'));

            Route::middleware('web')
                ->group(base_path('routes/web.php'));
        });
    }
}
```