resources/views/components/primary-button.blade.php

```
<button {{ $attributes->merge(['type' => 'submit', 'class' => 'inline-flex items-center px-4 py-2 bg-[#ab0800] border border-transparent rounded-md font-semibold text-xs text-white dark:text-white uppercase tracking-widest hover:bg-gray-700 dark:hover:bg-red-500 focus:bg-gray-700 dark:focus:bg-white active:bg-gray-900 dark:active:bg-gray-300 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2 dark:focus:ring-offset-gray-800 transition ease-in-out duration-150']) }}>
    {{ $slot }}
</button>
```

resources/views/includes/head.blade.php

```
<meta charset="utf-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<meta name="csrf-token" content="{{ csrf_token() }}">
<title>GLV - {{$namepage ?? __('head.Title')}}</title>
<!-- Fonts -->
<link rel="preconnect" href="https://fonts.bunny.net">
<link href="https://fonts.bunny.net/css?family=figtree:400,500,600&display=swap" rel="stylesheet" />
<!-- Scripts -->
@vite(['resources/css/app.css', 'resources/js/app.js'])
{{-- Icon --}}
<link rel="icon" href="{{ asset('storage/logo/favicon.ico') }}">
```

resources/views/layouts/app.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
    <head>
        @include('includes.head')
    </head>
    <body class="font-sans antialiased">
        <div class="min-h-screen bg-gray-100 dark:bg-[#363A43]">
            @include('layouts.navigation')
            <!-- Page Content -->
            <main>
                {{ $slot }}
                <div class="flex flex-row justify-center w-full py-6 lg:hidden">
                    <div class="w-full max-w-sm rounded-lg smax:max-w-xs bg-info dark:bg-sky-600">
                        <a href="{{ asset('pdf/Manuel_utilisateur.pdf') }}" class="w-full text-black btn glass dark:text-white">{{ __('manuelUtilisateur.LabelMU') }}</a>
                    </div>
                </div>
            </main>
            {{-- Accès manuel utilisateur --}}
```