

Lexical Analysis

CMPT 379: Compilers

Instructor: Anoop Sarkar

anoopsarkar.github.io/compilers-class

*This algorithm was first used by Alfred Aho in egrep and later used in awk, lex and flex.

Regex with Distinct Symbols

- Associate with each occurrence of a symbol in a regular expression a position
 - Add an end marker $((ab)|(ba))^* \#$
- For example: $((ab)|(ba))^* \#$
 - There are 5 positions:

1:a

2:b

3:b


4:a

5:#

Regex with Distinct Symbols


- Associate with each occurrence of a symbol in a regular expression a position
 - Add an end marker $((ab)|(ba))^* \#$

Regex to DFA: $((ab)|(ba))^*\#$




Regex to DFA: $((ab)|(ba))^*\#$

- ϵ -node: if the sub-expression has ϵ in its language




Regex to DFA: $((ab)|(ba))^*\#$

- ϵ -node: if the sub-expression has ϵ in its language




Regex to DFA: $((ab)|(ba))^*\#$

- ϵ -node: if the sub-expression has ϵ in its language
- $\text{firstpos}(n)$: the set of positions in the subtree rooted at n corresponding to the first symbol of at least one string



Regex to DFA: $((ab)|(ba))^*\#$

- ϵ -node: if the sub-expression has ϵ in its language
- $\text{firstpos}(n)$: the set of positions in the subtree rooted at n corresponding to the first symbol of at least one string




Regex to DFA: $((ab)|(ba))^*\#$

- ϵ -node: if the sub-expression has ϵ in its language

- $\text{firstpos}(n)$: the set of positions in the subtree rooted at n corresponding to the first symbol of at least one string

- $\text{lastpos}(n)$: the set of positions in the subtree rooted at n corresponding to the last symbol of at least one string




Regex to DFA: $((ab)|(ba))^*\#$


- ϵ -node: if the sub-expression has ϵ in its language

- $\text{firstpos}(n)$: the set of positions in the subtree rooted at n corresponding to the first symbol of at least one string


- $\text{lastpos}(n)$: the set of positions in the subtree rooted at n corresponding to the last symbol of at least one string



Regex to DFA: $((ab)|(ba))^*\#$




Regex to DFA: ((ab)|(ba))*#




firstpos = {}
lastpos = ()

Regex to DFA: ((ab)|(ba))*#




Regex to DFA: ((ab)|(ba))*#




firstpos = {}
lastpos = ()

Regex to DFA: ((ab)|(ba))*#




$firstpos = \{\}$
 $lastpos = ()$

Regex to DFA: ((ab)|(ba))*#




$firstpos = \{\}$
 $lastpos = ()$


Regex to DFA: ((ab)|(ba))*#




Regex to DFA: ((ab)|(ba))*#




Regex to DFA: ((ab)|(ba))*#




Regex to DFA: $((ab)|(ba))^* \#$




Regex to DFA: $((ab)|(ba))^*\#$



Regex to DFA: ((ab)|(ba))*#



Regex to DFA: ((ab)|(ba))*#




Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* `{}` and *lastpos* `()` information


Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information




Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information



Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information




followpos(i)+=k,l

followpos(j)+=k,l

Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information





*
|
...

followpos(i)+=k,l

followpos(j)+=k,l

Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information




followpos(i)+=k,l


followpos(j)+=k,l

Regex to DFA: *followpos*

- *followpos(p)*: tells us which positions can follow a position *p*
- There are two rules that use the *firstpos* {} and *lastpos* () information




$followpos(i) += k, l$
 $followpos(j) += k, l$




$followpos(i) += k, l$
 $followpos(j) += k, l$


Regex to DFA: $((ab)|(ba))^*\#$




Regex to DFA: $((ab)|(ba))^*\#$




Regex to DFA: ((ab)|(ba))*#




Regex to DFA: ((ab)|(ba))*#



Regex to DFA: ((ab)|(ba))*#



Regex to DFA: ((ab)|(ba))*#



$root = \{1,3,5\}$
 $fp(1) = 2$
 $fp(3) = 4$
 $fp(2) = 1,3,5$
 $fp(4) = 1,3,5$

Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

1:a

2:b

3:b

4:a

5:a

Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$\{1, 3, 5\}$ A

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$\{1, 3, 5\}$ A

$fp(1) = 2$

$A: fp(1), a \{2\}, a B, a$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

$\{1, 3, 5\}$ A

A: $fp(1), a$ $\{2\}, a$ B, a

A: $fp(3), b$ $\{4\}, b$ C, b


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

$\{1, 3, 5\}$ A

A: $fp(1), a$ $\{2\}, a$ B, a

A: $fp(3), b$ $\{4\}, b$ C, b

A: $fp(5), \#$ $\{\}, \#$ E, #


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

$\{1, 3, 5\} A$

$A: fp(1), a \{2\}, a B, a$

$A: fp(3), b \{4\}, b C, b$

$A: fp(5), \# \{\}, \# E, \#$

$B: fp(2), b \{1, 3, 5\}, b A, b$


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

$\{1, 3, 5\} A$

$A: fp(1), a \{2\}, a B, a$

$A: fp(3), b \{4\}, b C, b$

$A: fp(5), \# \{\}, \# E, \#$

$B: fp(2), b \{1, 3, 5\}, b A, b$

$C: fp(4), a \{1, 3, 5\}, a A, a$


1:a

2:b

3:b

4:a

5:a



Regex to DFA: $((ab)|(ba))^*\#$

$root = \{1, 3, 5\}$

$fp(1) = 2$

$fp(3) = 4$

$fp(2) = 1, 3, 5$

$fp(4) = 1, 3, 5$

$\{1, 3, 5\} A$

$A: fp(1), a \{2\}, a B, a$



$A: fp(3), b \{4\}, b C, b$

$A: fp(5), \# \{\}, \# E, \#$

$B: fp(2), b \{1, 3, 5\}, b A, b$

$C: fp(4), a \{1, 3, 5\}, a A, a$

**Any state with a transition on #
will be marked as final state**



1:a

2:b

3:b

4:a

5:a