

Project:

Thermal Insulating Paint for
Exterior Masonry and Walls

Product:

SurfaPaint ThermoDry
Exterior

Benefits:

- Conserves energy
- Thermal insulation
- Reflects 94,2% of IR radiation
- Elastomeric formulation for crack bridging
- UV and Alkali resistant
- Extended lifetime
- Low VOC, water based paint
- Easy surface application
- Excellent opacity and coverage
- Prevents mould growth
- Formaldehyde Free

Applications:

Exterior surfaces, such as walls, masonry, concrete, plaster board and wherever water based, acrylic paints are applied.

Color:

White

Can be used as a tinting base for light shades (RAL or NCS system)

Packaging:

10L Plastic (HDPE) Buckets

www.NanoPhos.com




SurfaPaint ThermoDry Exterior

Water Based, 100% Acrylic Thermal Insulating Paint for Exterior Masonry Surfaces

When thermal energy “travels” through walls and other surfaces, large amounts of energy are often necessary for cooling in the summer and heating in the winter. SurfaPaint ThermoDry Exterior is a high quality acrylic elastomeric emulsion paint with thermal insulating properties, ideal for exterior use. Powered by SurfaPore ThermoDry, it contains special nano and micro-sized thermal insulating ingredients contributing to energy savings during winter and summer. The thermal insulating particles block heat transfer, reflect thermal radiation, and create a moisture barrier that can result in significant energy savings. Suitable for application on masonry exposed to adverse weather conditions and for the protection of damaged surfaces with micro cracks. Excellent gap bridging even in very low temperature conditions (-20°C) and/or high temperature differences without risk of flaking. Excellent resistance to UV radiation and alkali. It is a breathable paint, preventing at the same time water penetration. Due to its UV cross linking mechanism and the nanoparticles it contains, the tendency to pick-up dirt particles and atmospheric pollution is significantly reduced. Available in white colour for optimum thermal insulation properties. It can be used as a tinting base for light shades.

**The triple action of SurfaPaint ThermoDry Interior paint,
i.e. thermal radiation reflectance, heat transfer resistance and water repellence
protects painted surfaces and improves energy efficiency.**




SurfaPaint® and ThermoDry® logos are registered trademarks of:
NanoPhos SA
Science & Technology Park of Lavrio,
Lavrio 19500, Greece
Tel.: (+30) 22920 69312 Fax: (+30) 22920 69303
W: www.NanoPhos.com E: info@NanoPhos.com

NanoPhos
Pioneering
Nanotechnology 

SurfaPaint ThermoDry Exterior Description

SurfaPaint ThermoDry Exterior combines a unique external acrylic paint with the thermal insulating properties of SurfaPore ThermoDry. This paint composition delivers all the benefits of a high quality paint: Excellent opacity and coverage, strong adhesion, coating flexibility, elastomeric behaviour for crack bridging, UV and alkali resistance. SurfaPaint ThermoDry Exterior also contains the ideal quantity of SurfaPore ThermoDry that assures all the benefits of a superior thermally insulating paint: Significant reduction in thermal conductivity, reflectance of thermal radiation (infrared) and decreased water absorption of the final coating. Therefore, the application of SurfaPaint ThermoDry Exterior can prevent the development of Urban Heat Islands (UHIs), by reflecting more than 94% of the incident heat radiation away from a building's structure. It is an ideal solution for enhancing conventional heat insulation, just by painting the external surfaces. Thus, the energy efficiency of buildings is increased and tangible savings are achieved.



Thermal insulating particles of SurfaPaint ThermoDry Exterior

International Standards Testing

Thermal Conductivity: $<0,1 \text{ W/(mK)}$, (EN ISO 12667:2004). The corresponding value of a conventional paint is $0,50 \text{ W/(mK)}$.

Thermal Reflectance: 94,2% Reflection in the InfraRed region of light (700nm - $2,2\mu\text{m}$ ASTM G173).

Liquid water permeability: "non-permeable" by water according to EN ISO 1062-3:2008

Fungal resistance: excellent resistant against fungi & algae, Class 1 according to BS3900-G6:1989

Applicability: SurfaPaint ThermoDry Exterior can be applied directly on exterior wall surfaces (masonry, concrete, plaster, drywalls), and wherever water based, acrylic paints are applied. New substrates from cement or masonry should have cured for more than 3-4 weeks before primer application. Adverse conditions during or immediately after application may affect the coating's properties. **Preparation:** Ensure all surfaces are clean and dry prior to application. Remove any dust and dirt. **Application note:** Stir well before application. Do not dilute for bridging gaps and hairline cracks of up to 0,5 mm. For cracks bigger than 1mm, fill the gap with a suitable putty. If thinning is required add up to 10% water by volume. Application temperature should be between 8 - 35°C. Apply 2-3 even coats using a good quality brush, roller or by spraying with a tip of a diameter 1,4mm or more. Do not over-brush. Ensure corners and edges are adequately covered. Additional coats should be applied 4-6 hours after the previous application. **Spreading Rate:** 10-12 m^2/L . **Drying Time:** Typically 1 hour depending upon coat thickness. Low temperatures and high humidity will lengthen drying times. **Cleaning of tools:** All tools and equipment should be cleaned immediately after use with water. **Storage:** Store in a cool, dry, well ventilated area away from heat and direct sunlight. Carefully reseal partly used containers. Protect from frost. To avoid risk of spillage, always store and transport in a secure and upright position. The shelf life of the product in airtight containers is 18 months post production date. **Safety:** Keep out of reach of children. Do not use empty container for storing food. Avoid contact with skin and eyes. After contact with skin wash immediately with soap and. Do not use solvent thinners. In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice. If swallowed seek medical advice immediately and show this container or label. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation. **VOC (Volatile Organic Compounds):** Maximum EU VOC content limit value (Directive 2004/42/CE) of the product in a ready to use condition (category A/c "Exterior walls of mineral substrate", Type WB): 40 g/L (2010). **Maximum VOC content of this product is 11 g/L.**

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY. The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that NanoPhos' products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent. NanoPhos specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. NanoPhos disclaims liability for any incidental or consequential damages. This product is neither tested nor represented as suitable for medical or pharmaceutical uses.



What is Nanotechnology?

Nanotechnology refers to the scientific field, which deals with very small structures, usually sized below 100 nm. One nanometer (nm) is one billionth of a meter (10^{-9} m) - it is so small that if earth were one meter in diameter, then one nanometer would have been the size of an apple! Nanosized materials reveal unique properties when compared to ordinary, bulk materials or even molecules.

NanoPhos at a Glance...

At NanoPhos, we take advantage of the unique properties of nanotechnology and invent clever materials that solve every day problems. By harnessing nanotechnology, we seek to create a more comfortable, safe and trouble-free living environment. We transfer innovations out of our lab into the hands of consumers. Our vision is clear: "Tune the nanoworld to serve the macroworld" – in simple terms we make nanoparticles solve common problems. NanoPhos was recognized in January of 2008 by Bill Gates as one of the most innovative companies and also received the 1st prize for innovation at the prestigious 100% Detail Show in London. SurfaShield technology, received the prestigious GAIA award at the 2010 International Building and Construction Show BIG5 in Dubai for its environmentally friendly and innovative profile. NanoPhos is a rapidly growing company that is actively expanding its distribution network. Currently, the company is present in the UK, Norway, Sweden, Portugal, France, Italy, Greece, Cyprus, Turkey, Egypt, Saudi Arabia, Bahrain, UAE, Iran, India, China, New Zealand, Japan and Mexico.

www.NanoPhos.com



NanoPhos SA has been approved by Lloyd's Register Quality Assurance to follow the EN ISO 9001:2008 Quality Management System and EN ISO 14001:2004 Environmental Management System for the production and sales of chemical products for cleaning and protection of surfaces and nanotechnology products.