

Implement caching in Java microservices using Redis Cluster



Sina Salmani · Follow

3 min read · Jul 25, 2022



23



When it comes to boosting your application's speed, every millisecond matters. New research from Google has found that 53% of mobile website visitors will leave if a webpage doesn't load within three seconds.

. . .

Why do we need cache for microservices?

Cache reduces latency and increases performance and scalability in microservices.

The scenario

Consider these microservices:

- Add a Product
- Fetch All Products
- Delete a Product by Id

Implement these services and use three annotations **@Cacheable** **@CacheEvict** **@CachePut** to use Redis cache in inserting, fetching, and updating data. At the first call of fetch service, all products were retrieved from DB but for the next call, use cache. In case of deleting a product, it must remove from the cache, and when adding a new product, it should add to the cache.

Where to start?

Install Redis on your system; use this for mac OS:

```
$ brew install redis
```

In case you want to install Redis using the docker container, use this link:

<https://www.atlantic.net/dedicated-server-hosting/how-to-install-redis-server-using-docker-container/>

Start Redis server:

```
$ redis-server
```

Implementation

Step 1: Init spring boot and add this dependency for Redis connection:

```
<dependency>  
  <groupId>org.springframework.boot</groupId>  
  <artifactId>spring-boot-starter-data-redis</artifactId>  
</dependency>
```

Spring provides Data Redis lib for easy configuration and access to Redis from Spring; besides, using Lettuce driver help to develop reactive API.

Step 2: Create a Product entity with @RedisHash

```
@Data
@AllArgsConstructor
@NoArgsConstructor
@RedisHash("pro")
public class Product implements Serializable {

    @Id
    private int id;
    private String name;
    private long price;
}
```

Redis hashes are an implementation of the hash table or hash map data structure. Hash tables map unique keys to values.

Step 3: Create Redis configuration class

```
@Configuration
public class RedisConfig {

    //Creating Connection with Redis
    @Bean
    public RedisConnectionFactory redisConnectionFactory() {
        return new LettuceConnectionFactory();
    }

    //Creating RedisTemplate for Entity 'Product'
    @Bean
    public RedisTemplate<Integer, Product> redisTemplate(){
        RedisTemplate<Integer, Product> redisTemplate = new
        RedisTemplate<>();
        redisTemplate.setConnectionFactory(redisConnectionFactory());
        return redisTemplate;
    }
}
```

```
}  
}
```

Step 4: Create Product Repo

Based on Spring documentation `@EnableRedisRepositories` Annotation to activate Redis repositories. If no base package is configured through either `value()`, `basePackages()` or `basePackageClasses()` it will trigger scanning of the package of annotated class.

```
@EnableRedisRepositories  
public interface ProductRepo extends CrudRepository<Product,Integer>  
{}
```

Step 5: Create a service layer

```
@Service  
public class ProductServiceImpl implements ProductService {  
  
    @Autowired  
    private ProductRepo productRepo;  
  
    public Product addProduct(Product product){  
        return productRepo.save(product);  
    }  
  
    @Override  
    public List<Product> getAllProduct() {  
  
        System.out.println("HI");  
        return (List<Product>) productRepo.findAll();  
    }  
  
    @Override  
    public int deleteProductById(int id) {  
        productRepo.deleteById(id);  
        return 1;  
    }  
}
```

```
}  
}
```

Step 6: Create a controller layer

```
@RestController  
@RequestMapping("/api")  
public class ProductController {  
  
    @Autowired  
    private ProductService productService;  
  
    @PostMapping("/v1.1/add")  
    @CachePut(value="product")  
    public Product addProduct(@RequestBody Product product){  
  
        return productService.addProduct(product);  
    }  
  
    @GetMapping("/v1.1/getAllProducts")  
    @Cacheable(value="Product")  
    public List<Product> getProduct(){  
  
        return productService.getAllProduct();  
    }  
  
    @GetMapping("/v1.1/del/{id}")  
    @CacheEvict(value = "Product",key = "id")  
    public int deleteProduct(@PathVariable int id){  
  
        return productService.deleteProductById(id);  
    }  
}
```

Step 7: Add @EnableCaching above the main Spring Boot application class

This annotation triggers a post-processor that inspects every Spring bean for the presence of caching annotations on public methods.

Step 8: Add this to application.properties

```
spring.cache.redis.time-to-live=60000
```

Spring provides a comprehensive abstraction for common caching scenarios. If we want to set Time To Live of a cache, the configuration of the chosen cache provider must be tuned. You can also implement multiple TTL caches in Spring boot.

Step 9: add swagger to the project.

- in pom.xml

```
<dependency>
  <groupId>io.springfox</groupId>
  <artifactId>springfox-swagger2</artifactId>
  <version>2.7.0</version>
</dependency>
<dependency>
  <groupId>io.springfox</groupId>
  <artifactId>springfox-swagger-ui</artifactId>
  <version>2.7.0</version>
</dependency>
```

- Add this annotation above the main Spring Boot application class

```
@EnableSwagger2
```

- In properties file

```
spring.mvc.pathmatch.matching-strategy=ant_path_matcher
```




The image shows the Swagger UI for a REST API. The top bar is green with the Swagger logo, a dropdown menu set to 'default (v2/api-docs)', and an 'Explore' button. Below this, the title 'Api Documentation' is followed by 'Api Documentation' and a link to 'Apache 2.0'. The main section is titled 'product-controller : Product Controller' and includes three tabs: 'Show/Hide', 'List Operations', and 'Expand Operations'. The 'List Operations' tab is active, showing a table of three API endpoints. The first endpoint is a POST request to '/api/v1.1/add' with the operation name 'addProduct'. The second is a GET request to '/api/v1.1/del/{id}' with the operation name 'deleteProduct'. The third is a GET request to '/api/v1.1/getAllProducts' with the operation name 'getProduct'. At the bottom, it states '[BASE URL: / , API VERSION: 1.0]'.

Method	Path	Operation
POST	/api/v1.1/add	addProduct
GET	/api/v1.1/del/{id}	deleteProduct
GET	/api/v1.1/getAllProducts	getProduct

Result in Redis

Install RedisInsight to profile the process and see Hash and Set that initialized when using cache. Adding three objects create a Set(the name set in @RedisHash). And per object, generate a Hash(pro:2,pro:3,pro:4 name of hash set: key)




Follow

What are your thoughts?

Respond

Recommended from Medium



 Tharindu Dulshan

Optimizing Spring Boot Applications with Redis Caching

In my previous blog, I explained what is Caching and different methods of caching...

Sep 20



 Technical Life

Solving Redis Connection Issues in a Spring Boot Application

Troubleshooted Redis connection issues in Spring Boot

★ Jun 24




Lists



Staff picks

780 stories · 1492 saves



Stories to Help You Level-Up at Work

19 stories · 891 saves

**Self-Improvement 101**

20 stories · 3126 saves

**Productivity 101**

20 stories · 2641 saves




In Stackademic by Mpavani

Microservices tricky interview questions must know

1.You have two microservices, Order Service and Payment Service. When an order is...



Oct 30



Balian's technologies and innovation lab


API Gateway Patterns with Spring Cloud Gateway: Routing, Load...

In microservices architectures, an API Gateway acts as the single entry point for all...



Nov 12





Sanjay Singh

Implementing Caching in a Spring Boot Application: A Complete...

Overview



Oct 11



Jobin J

Redis Caching with Java using Jedis

Redis caching is a technique that uses Redis, an open-source, in-memory data structure...

Aug 27

[See more recommendations](#)