

Spark-submit Spring Boot profiles.active variable

Asked 6 years, 4 months ago Modified 6 years, 3 months ago Viewed 1k times



Good day for you colleagues. I am trying run my appliication on a cluster. My script looks like:

1

```
#!/usr/bin/env bash
/usr/hdp/current/spark2-client/bin/spark-submit \
--driver-memory 12G \
--master yarn \
--driver-java-options -Dspring.profiles.active=vf \
--driver-java-options -Doperation.localDate=2018-06-01 \
/mnt/store/vm/base-operations/my.jar
```



But when my app starts, Spring Boot shows to me next:

```
18/07/10 16:34:19 INFO OperationRunner: The following profiles are active: hadoop
```

Then i try to start it like:

```
java -jar -Dspring.profiles.active=vf multirating-bigdata-operations-MASTER-SNAPSHOT.jar
```



I see:

```
18/07/10 16:34:19 INFO OperationRunner: The following profiles are active: vf
```

Whats wrong with spark-submit? How to force needed applicataion-{suffix}.yml for start app?

java

apache-spark

spring-boot

spark-submit

Share Edit Follow

asked Jul 10, 2018 at 13:44



Александр Шаповалов

495 ● 1 ● 6 ● 20

1 Answer

Sorted by: Highest score (default)



It works with double quotes in one line.



1



```
#!/usr/bin/env bash
/usr/hdp/current/spark2-client/bin/spark-submit \
--driver-java-options "-Dspring.profiles.active=vf -Doperation.localDate=2018-06-01" \
--driver-memory 12G \
--master yarn \
/mnt/store/viewing-maker/base-operations/multirating-bigdata-operations-MASTER-SNAPSHOT.jar
```

[Share](#) [Edit](#) [Follow](#)

answered Jul 11, 2018 at 6:14

[Александр Шаповалов](#)

495 ● 1 ● 6 ● 20

