

Model Selection and Shrinkage

Vahid Partovi Nia

Lecture 05



Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

- 1 Credit dataset
- 2 All subsets
- 3 Stepwise selection
- 4 Manual Implementation
- 5 Shrinkage
- 6 Ridge Implementation
- 7 Lasso Implementation

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

- Credit dataset involves 11 attributes. The objective is to model 'Balance'.
- Available attributes are: Income, Limit, Rating, Cards, Age, Education, Gender, Student, Married, and Ethnicity.
- Focus on quantitative variables: Income, Limit, Rating, Cards, Age, and Education.

Notation n observation, p features

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

$$\boldsymbol{\varepsilon} = \begin{pmatrix} \varepsilon_1 \\ \vdots \\ \varepsilon_n \end{pmatrix}, \mathbf{y} = \begin{pmatrix} y_1 \\ \vdots \\ y_n \end{pmatrix}, \mathbf{x} = \begin{pmatrix} x_1 \\ \vdots \\ x_p \end{pmatrix}, \boldsymbol{\beta} = \begin{pmatrix} \beta_0 \\ \beta_1 \\ \vdots \\ \beta_p \end{pmatrix}$$

$$\mathbf{X}_{n \times p} = \begin{pmatrix} \mathbf{x}_1^\top \\ \vdots \\ \mathbf{x}_n^\top \end{pmatrix} = \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1p} \\ x_{21} & x_{22} & \dots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \dots & x_{np} \end{pmatrix}$$

$$\mathbf{X}_{n \times (p+1)} = \begin{pmatrix} 1 & x_{11} & \dots & x_{1p} \\ 1 & x_{21} & \dots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ 1 & x_{n1} & \dots & x_{np} \end{pmatrix}$$

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \boldsymbol{\varepsilon}$$

$$S(\boldsymbol{\beta}) = (\mathbf{y} - \mathbf{X}\boldsymbol{\beta})^\top (\mathbf{y} - \mathbf{X}\boldsymbol{\beta})$$

What is the minimizer of $S(\boldsymbol{\beta})$?

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

$$\mathbf{y} = \mathbf{X}\boldsymbol{\beta} + \boldsymbol{\varepsilon}$$

$$S(\boldsymbol{\beta}) = (\mathbf{y} - \mathbf{X}\boldsymbol{\beta})^\top (\mathbf{y} - \mathbf{X}\boldsymbol{\beta})$$

What is the minimizer of $S(\boldsymbol{\beta})$?

$$\frac{\partial \mathbf{X}\boldsymbol{\beta}}{\partial \boldsymbol{\beta}} = \mathbf{X}^\top$$

$$\frac{\partial \boldsymbol{\beta}^\top \mathbf{A} \boldsymbol{\beta}}{\partial \boldsymbol{\beta}} = (\mathbf{A} + \mathbf{A}^\top) \boldsymbol{\beta}$$

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

$$\begin{aligned}\min \quad & S(\boldsymbol{\beta}) \\ \frac{\partial S(\boldsymbol{\beta})}{\partial \boldsymbol{\beta}} &= 0 \\ (\mathbf{X}^\top \mathbf{X})\boldsymbol{\beta} &= \mathbf{X}^\top \mathbf{y} \\ \boldsymbol{\beta} &= (\mathbf{X}^\top \mathbf{X})^{-1} \mathbf{X}^\top \mathbf{y}\end{aligned}$$

Quantitative attributes

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

	Balance	Income	Limit	Rating	Cards	Age	Education
0	333	14.891	3606	283	2	34	11
1	903	106.025	6645	483	3	82	15
2	580	104.593	7075	514	4	71	11
3	964	148.924	9504	681	3	36	11
4	331	55.882	4897	357	2	68	16

Scatterplot Implementation

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
import pandas as pd
path='data/'
filename = path+'Credit.csv'
credit = pd.read_csv(filename)
credit = credit[['Balance', 'Income', 'Limit',
                 'Rating', 'Cards', 'Age', 'Education']]
credit.head()
```

```
from pandas.plotting import scatter_matrix
%matplotlib inline
scatter_matrix(credit, alpha=0.2);
```

Scatterplot

Credit dataset

All subsets


Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation



Credit dataset

All subsets



Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation



Effect of collinearity on estimation

Credit dataset

All subsets



Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation



Effect of collinearity on estimation

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

		Coefficient	Std. error	t-statistic	p-value
Model 1	Intercept	-173.411	43.828	-3.957	< 0.0001
	age	-2.292	0.672	-3.407	0.0007
	limit	0.173	0.005	34.496	< 0.0001
Model 2	Intercept	-377.537	45.254	-8.343	< 0.0001
	rating	2.202	0.952	2.312	0.0213
	limit	0.025	0.064	0.384	0.7012

All possible subsets

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

Suppose you have the response vector y and $\mathbf{x}_j, j = 1, \dots, p$ attributes.

- Fit 2^p possible models
- Choose the model with the best AIC or BIC.

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
ImplementationLasso
Implementation

Suppose you have the response vector \mathbf{y} and $\mathbf{x}_j, j = 1, \dots, p$ attributes.

Repeat the following algorithm until all attributes are in the model.

- 1 Initialize with the constant model $\mathbf{y} = \beta_0$
- 2 Compute $\hat{\mathbf{y}}$
- 3 Compute the residual $\mathbf{r} = \mathbf{y} - \hat{\mathbf{y}}$
- 4 Find j' the most correlated attribute $\mathbf{x}_{j'}$ with \mathbf{r} .
- 5 Enter j' to the model
- 6 Go to 2

Select one of these models using AIC or BIC.

Model size = 1

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import LinearRegression
y = credit['Balance'].values
X = credit[['Income']].values
lr = LinearRegression()
lr.fit(X,y)
score1 = lr.score(X,y)
```


Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import LinearRegression
y = credit['Balance'].values
X = credit[['Income']].values
lr = LinearRegression()
lr.fit(X,y)
score1 = lr.score(X,y)
```

```
y = credit['Balance'].values
X = credit[['Limit']].values
lr = LinearRegression()
lr.fit(X,y)
score2 = lr.score(X,y)
```

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import LinearRegression
y = credit['Balance'].values
X = credit[['Income']].values
lr = LinearRegression()
lr.fit(X,y)
score1 = lr.score(X,y)
```

```
y = credit['Balance'].values
X = credit[['Limit']].values
lr = LinearRegression()
lr.fit(X,y)
score2 = lr.score(X,y)
```

```
y = credit['Balance'].values
X = credit[['Rating']].values
lr = LinearRegression()
lr.fit(X,y)
score3 = lr.score(X,y)
```

Which attribute you choose?

Model size = 2

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
y = credit['Balance'].values
X = credit[['Rating', 'Income']].values
lr = LinearRegression()
lr.fit(X,y)
score31 = lr.score(X,y)
```

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
y = credit['Balance'].values
X = credit[['Rating', 'Income']].values
lr = LinearRegression()
lr.fit(X,y)
score31 = lr.score(X,y)
```

```
y = credit['Balance'].values
X = credit[['Rating', 'Limit']].values
lr = LinearRegression()
lr.fit(X,y)
score32 = lr.score(X,y)
```

Which attribute you choose next?

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

# Variables	Best subset	Forward stepwise
One	rating	rating
Two	rating, income	rating, income
Three	rating, income, student	rating, income, student
Four	cards, income student, limit	rating, income, student, limit

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
ImplementationLasso
Implementation

Suppose you have the response vector \mathbf{y} and $\mathbf{x}_j, j = 1, \dots, p$ attributes.

Repeat the following algorithm until there is no attribute in the model.

- 1 Initialize with the full $\mathbf{y} = \beta_0 + \beta_1 \mathbf{x}_1 + \dots + \beta_p x_p$
- 2 Compute $\hat{\mathbf{y}}$
- 3 Compute the residual $\mathbf{r} = \mathbf{y} - \hat{\mathbf{y}}$ and $\text{RSS} = \mathbf{r}^\top \mathbf{r}$
- 4 Find j' the attribute the drops RSS the least possible
- 5 Remove j' from the model
- 6 Go to 2

Select one of these models using AIC or BIC.

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
ImplementationLasso
Implementation

Least squares

$$\hat{\beta} = \min (\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta)$$

Subset selection

$$\begin{aligned} \hat{\beta} &= \min (\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) \\ \text{s.t. } &\#\{\beta_j \neq 0\} \leq s \end{aligned}$$

or

$$\begin{aligned} \hat{\beta} &= \min (\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) \\ \text{s.t. } &\sum_{j=1}^p I(\beta_j \neq 0) \leq s \end{aligned}$$

for a given model size s , where $I(\cdot)$ is the indicator function.

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

for a given ball size s

Ridge regression

$$\begin{aligned}\hat{\beta} &= \min(\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) \\ \text{s.t. } &\sum_{j=1}^p \beta_j^2 \leq s\end{aligned}$$

Lasso regression

$$\begin{aligned}\hat{\beta} &= \min(\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) \\ \text{s.t. } &\sum_{j=1}^p |\beta_j| \leq s\end{aligned}$$

Shrinkage versus selection

Credit dataset

All subsets



Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation



Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

For a given penalization constant λ
Ridge regression

$$\hat{\beta} = \min(\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) + \lambda \sum_{j=1}^p \beta_j^2$$

Lasso regression

$$\hat{\beta} = \min(\mathbf{y} - \mathbf{X}\beta)^\top (\mathbf{y} - \mathbf{X}\beta) + \lambda \sum_{j=1}^p |\beta_j|$$

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import Ridge
import numpy as np
y = credit['Balance'].values
X = credit[['Income', 'Limit', 'Rating',
            'Cards', 'Age', 'Education']].values
rr = Ridge(alpha=0, normalize=True)
rr.fit(X, y)
```

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import Ridge
import numpy as np
y = credit['Balance'].values
X = credit[['Income', 'Limit', 'Rating',
            'Cards', 'Age', 'Education']].values
rr = Ridge(alpha=0, normalize=True)
rr.fit(X, y)

X_pred = np.array([15, 3000, 300, 2, 34, 16]).reshape(1,6)
rr.predict(X_pred)
```

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import Ridge
import numpy as np
y = credit['Balance'].values
X = credit[['Income', 'Limit', 'Rating',
            'Cards', 'Age', 'Education']].values
rr = Ridge(alpha=0, normalize=True)
rr.fit(X, y)
```

```
X_pred = np.array([15, 3000, 300, 2, 34, 16]).reshape(1,6)
rr.predict(X_pred)
```

```
rr = Ridge(alpha=10, normalize=True)
rr.fit(X, y)
rr.predict(X_pred)
```

Ridge Generalized Cross-validation

Credit dataset

All subsets

Stepwise selection

Manual
Implementation


Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import RidgeCV
alpha_values = np.linspace(0.0001, 0.01, num= 100)
rrcv = RidgeCV(alphas=alpha_values,
               normalize = True, store_cv_values = True)
rrcv.fit(X, y)
```

```
import matplotlib.pyplot as plt
cv_values = np.sum(rrcv.cv_values_, axis=0)
plt.plot(alpha_values, cv_values, 'or');
```



Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import Lasso
lr = Lasso(alpha = 0.1, normalize = True)
lr.fit(X,y)
lr.predict(X_pred)
```

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

```
from sklearn.linear_model import Lasso
lr = Lasso(alpha = 0.1, normalize = True)
lr.fit(X,y)
lr.predict(X_pred)
```

```
from sklearn.linear_model import LassoCV
lrcv = LassoCV(alphas = alpha_values, cv = 10, normalize = True)
lrcv.fit(X, y)
lrcv.alpha_
```


Least Angle Regression

Credit dataset

All subsets

Stepwise selection

Manual
Implementation

Shrinkage

Ridge
Implementation

Lasso
Implementation

The least angle regression provides a fast framework similar to forward selection gives the solution path for lasso.

```
import matplotlib.pyplot as plt
from sklearn.linear_model import lars_path
alphas, _, coefs = lars_path(X, y, method='lasso', verbose=True)
alphas[1]
coefs[:, 1]
```

