# Core Java

UNIT 3 – Abstract Classes & Methods , Method Overriding

Single Inheritance

Multilevel Inheritance

Super

Review

# Review – Identify the missing lines in the code if any

```
class Furniture{
        Furniture(){
        System.out.println("Furniture class Constructor");
                }
}
class Chair extends Furniture{
        Chair(){
        System.out.println("Chair class Constructor");
        }
}
```

```
class MainClass {
        public static void main(String args[])
        {
                Chair d=new Chair();
        }
}
```

# Review – Identify the missing lines in the code if any

```
class Furniture{
        Furniture(String type){
        System.out.println("Furniture class Constructor");
                }
}
class Chair extends Furniture{
        Chair(){          ──────────►  super("softwood")
        System.out.println("Chair class Constructor");
        }
}
```

```
class MainClass {
        public static void main(String args[])
        {
                Chair d=new Chair();
        }
}
```




# Abstraction in Java

- **Abstraction** is a process of hiding the implementation details and showing only functionality to the user.




# ABSTRACT CLASS

A class which is declared with the abstract keyword

# Abstract Methods

A method without body (no implementation) is known as abstract method.

A method must always be declared in an abstract class

Example:

```
public abstract int myMethod(int n1, int n2);
```

# Method Overriding

If subclass (child class) has the same method as declared in the parent class, it is known as method overriding in Java.

Also Known as **Run-Time** Polymorphism

## Rules for Java Method Overriding

| | |
|---|---|
| The method must have the same name as in the parent class | The method must have the same parameter as in the parent class. |

# DISTINGUISH BETWEEN METHOD OVERLOADING AND OVERRIDING

| | Overloading | Overriding |
|---|---|---|
| **Definition** | Methods having same name but each must have different number of parameters or parameters having different types & order. | Sub class have method with same name and exactly the same number and type of parameters and same return type as super class method. |
| **Meaning** | More than one method shares the same name in the class but having different signature. | Method of base class is re-defined in the derived class having same signature. |
| **Behaviour** | To Add/Extend more to method's behaviour. | To Change existing behaviour of method. |
| **Polymorphism** | Compile Time | Run Time |
| **Inheritance** | Not Required | Always Required |
| **Method Signature** | Must have different signature | Must have same signature. |



# QUIZ

# THANK YOU