



Lyon 1

Mesh and Computational Geometry

Raphaëlle Chaine

Université Claude Bernard Lyon 1

Master Informatique
ID3D
Image, Développement
et Technologie 3D



1


Triangulation of 2D points

- What if the Delaunay triangulation does not comply the boundaries of the domain or a network of constraints?
- Constraint : a segment to be inserted into the triangulation

2

Case of a digital 2D or 2D½ model

- Unconstrained Triangulation
- Constrained Triangulation




Images by B. Kornberger

3

Case of a digital 2D or 2D½ model

- Constrained triangulation



4

Constrained triangulation of 2D points

- What if the Delaunay triangulation does not comply the boundaries of the domain or a network of constraints?
- We insert the constraints into the triangulation
 - Using the *flip* operation
 - Flip of edges intersecting the constraint edges
 - Orient the constraint edges to set an order for the flip of the intersecting edges

5

Constrained triangulation of 2D points

- What about the non constrained edges?
 - Slightly modify the (locally)-Delaunay Criterion
 - A constraint is seen as a wall stopping the visibility
 - A vertex can be located inside a circumscribed circle if it is not visible from inside the triangle
 - Flip any un-constrained edge that is non locally Delaunay

6

5

6


Incremental Constrained triangulation of 2D points

- Incremental insertion of a point in a constrained 2D triangulation
 - Constrained edges cannot be flipped
 - Slightly modify the (locally)-Delaunay Criterion
 - A constraint is seen as a wall stopping the visibility
 - A vertex can be located inside a circumscribed circle if it is not visible from inside the triangle

7


3D Shape Modelling

- How to obtain a mesh?
- Input data
 - Range images
 - Volumetric voxel images
 - CAD/CAM
 - Dirty meshes provided by graphic designers
 - 2D Images + stereovision



8


3D objects digitization



Laser scanner (Michelangelo Project)

9

From 3D digitization to surface reconstruction



Art3D project (ANRT)

10

Shape Reconstruction

- Problem of 2D reconstruction
 - Reconstruct a curve from 2D input point samples on that curve
- Problem of 3D reconstruction
 - Reconstruct a surface from 3D input point samples on that surface

11

Mesh generation from input point set

- 2D reconstruction
 - A problem from your childhood
 - Input: a finite set of 2D points, with numbers or not




12

2

Mesh generation from input point set

- 2D reconstruction

- Output: A polygonal curve of the contour of the shape
- ... thanks to your pencil, your intelligence and your dexterity!



13


Mesh generation from input point set

- 2D and 3D reconstruction

- Now we remove the numbers!

- 3D reconstruction

- How to generalize an algorithm to reconstruct a triangulated surface from input 3D points?



14

Mesh generation from input point set

- 3D Reconstruction

- Approximation of a surface from a point set
- Different approaches characterized by a more or less global knowledge of the surface to be produced
- Numerous algorithms in computational geometry

15

- Points 3D and additional information

- X-ray scanner, ultrasound, MRI, PET, stereovision
- Structured (depth images) or not
- Possibility of an organization into slices
- Additional information : normal at the surface



16

Mesh generation from input point set

- 2D and 3D Reconstruction

- How to build an approximation of the shape based on the input points?
- In what cases can we guarantee the geometric and topological validity of the surface?
- Which additional assumptions should we provide on the sampling of the unknown surface?

17

Mesh generation from input point set

- Be careful :

- We know how to build a 2D mesh (composed of triangles) from 2D data
- We know how to build a 3D mesh (composed of tetrahedra) from 3D data
- But we do not know how to build
 - A 1D mesh (composed of segments) from 2D data sampled on a curve!!
 - a 2D mesh (composed of triangles) from 3D data sampled on a surface !!!

18

17

18

Case of a digital terrain model

- Data can be parameterized as a height function with respect to a reference plane (2D ½ dimension)
- Delaunay triangulation of the points projected on the reference plane
 - Triangulation maximizing the angles of the triangle projected on the 2D plane, not the angles of the 3D triangles

19

Case of a digital terrain model

- How to better consider the height information?
 - Find the triangulation maximizing the angles of the 3D triangles
 - Remark : each pair of adjacent triangles can locally be flattened with a preservation of the angles
 - It is possible to reuse Lawson's flipping algorithm, without guaranteeing a global optimum
 - Non Delaunay edges $\Pi - (\alpha + \beta) < 0$


20

19

20

Mesh generation from 3D point set

- Reconstruction 3D
 - Idea : link points that are close
 - What is a close point?



21

Mesh generation from 3D point set

- Reconstruction 3D
 - Idea : link points that are close
 - ... This is partly what is done by 3D Delaunay, which triangulates the volume delimited by the convex hull with 3-simplexes (tetrahedra)!




22

21

22

Mesh generation from 2D or 3D point set

- 2D Reconstruction
 - Look for the curve as a sub-graph of the 2D Delaunay triangulation
 - Provided it should be present in it!
- 3D Reconstruction
 - Look for the surface mesh as a sub-graph of the 3D Delaunay triangulation



23

23

In the following...

- 2D reconstruction
 - Reconstruction of a 2D curve as a subset of the edges of a 2D Delaunay triangulation
- ... to better understand what is happening in 3D
 - Reconstruction of a 3D surface as a subset of the triangular facets of a 3D Delaunay triangulation

24

24

In the following...

- We will distinguish
 - The original shape on which the input points have been sampled and which one seeks to approximate
 - The provided samples
- Care should be taken to maintain an equivalence between **continuous** and **discrete** notions

25


One of the first reconstruction algorithm

- CRUST (Amenta et al)
 - Algorithm provided with necessary and sufficient conditions on the **sampling density** to guarantee the result of the reconstruction
 - Minimal Sampling density characterized by using the « Local Feature Size » : distance from the **surface points** to the **skeleton** (medial axis) of the shape
 - Skeleton : set of maximal balls centers approximated by **Voronoi Centers**

26

2D/3D Reconstruction

- Given ϵ , an ϵ -sampling of a shape is a set of samples P_i such that for each x there is a i such that $\|x - P_i\| \leq \epsilon lfs(x)$




Sampling density locally proportional to $1/lfs$
Measure of the thickness and of the curvature

27

2D Reconstruction

- Guarantees provided by Crust
 - Adjacent points on the curve are linked by the algorithm in the case of 0.4-sampling




But additional points may also be linked....

~

28

Reconstruction

- Crust provides guarantees
 - Homoeomorphism of the curve and its approximation in the case of a 0.25-sampling



29

An other simple reconstruction algorithm

- Alpha-shape
- Ball pivoting
- Those approach require a sampling denser than a uniform density
- Easy to parallelize

30


29

30

2D Reconstruction

- α -shape

- pq is an edge of the α -shape if there exists an empty circle of radius $1/\alpha$ that is passing through p and q




31

2D Reconstruction

- α -shape

- pq is an edge of the α -shape if there exists an empty circle of radius $1/\alpha$ that is passing through p and q




32

2D Reconstruction

- α -shape

- If α is too small (circle too big) : pockets are closed




33

2D Reconstruction

- α -shape

- If α is too big (circle too small) : the curve is opened




34

2D Reconstruction

- α -shape

- Need for a sampling denser than a sufficiently fine uniform sampling



- The resolution is determined using the radius to be used to enter in every pocket

35

2D/3D Reconstruction

- α -shape

- Need for a sampling denser than a sufficiently fine uniform sampling, but sometimes some areas are too narrow




- Algorithms also available in 3D

- empty ball going passing through 3 points

- Ball pivoting (parallelization possibilities)

36


Other algorithms based on Delaunay



37

Restricted Voronoi Diagram

- Given a set of points on a surface
- Restricted Voronoi cell :
 - Intersection between a Voronoi cell and the surface
- Can be used to construct triangles between points with adjacent restricted Voronoi cells




B. Levy

38

Voronoi diagram restricted to a surface

- Restricted Voronoi diagram
 - Intersections between the 3D Voronoi cells and the surface of the original shape (**if ever we have it!!**)




B. Levy

39

Restricted Delaunay Triangulation

- Restricted Delaunay :
 - Defined by duality
 - Each adjacency between 2 restricted Voronoi cells results in a restricted Delaunay edge
 - Creation of triangles of restricted Delaunay by duality to a vertex of Restricted Voronoi




B. Levy

40

Restricted Delaunay Triangulation

- Edelsbrunner and Shah's theorem[1997]
 - If each face of the Restricted Voronoi diagram is homeomorphic to a topological disc, then the restricted Delaunay triangulation is homeomorphic to the unknown surface.




B. Levy

41

Restricted Delaunay Triangulation

- Topological disk property not satisfied for insufficient sampling....



B. Levy

42

41


Restricted Delaunay Triangulation

- In presence of an ϵ -sampling with $\epsilon < 0.1$, the property of the topological disk is satisfied [Amenta and Bern 99]
- The problem is that we do not know the original surface, and we need it to build the restricted Voronoi cells and the associated dual triangulation...

43

43

What if the surface is unknown? Cocone : An other reconstruction approach using Voronoi diagram and Delaunay triangulation




44

44

Voronoi diagram restricted to a curve

- Restricted Voronoi diagram
 - Intersections between the 2D Voronoi cells and the curve of the original shape (**that we do not know !!**)




45

45

Cocone

- Idea: find some kind of thickened version of the original surface and make a restricted Delaunay triangulation of this thickened version




46

46

Cocone

- Thickening of the unknown surface :
 - For this purpose, a Cocone is placed at each sampled point [Amenta et al 2000]
 - Positioning using the tangent plane
 - using unoriented normal or estimating it from Voronoi 3D cell
 - A triangle is created from every triplet of adjacent cocones
 - Residual filtering still needed (non manifoldness)



47

47

Other reconstruction approaches based on an approximation of the skeleton

48


48

Power Crust

- Observation :

- any point of a compact surface is on the boundary of two maximal balls centered on the skeleton
- an outer ball and an inner medial ball

- Use the idea that the inside of any closed surface is a union of balls




49

Back to the medial axis/ skeleton

- In 2D :

- Center of the maximal balls contained within the curve
- All points that have more than one nearest neighbor on the curve




50

Back to the medial axis

- 2D approximation :

- Voronoi balls are the discrete equivalent of maximal balls



51

2D reconstruction

- By approximating the medial axis


- We can therefore approximate a 2D shape as a union of inner Voronoi balls
- What we need to know is which balls are inside (resp. outside) or at least which ones have different signs

52

Back to the Medial Axis

- In 3D:

- The medial axis of a surface is a surface (possibly with pieces of curves)





53

3D reconstruction by approximating the Medial Axis

- 3D approximation:


- Beware of Voronoi balls that are centered on the surface (sliver)
- Even for a good surface sampling



54

Back to Voronoi


- In case of a dense and noise free sampling
 - Long and thin Voronoi cells,
 - Direction aligned with the normal to the surface
 - With extremities close to the medial axis



55

Poles


- Poles
 - Voronoi vertices at the extremities of the elongated cells



56

Poles


- Approximation
 - Let V_p be the Voronoi cell of a point p
 - Positive pole p^+ : Voronoi vertex of V_p furthest from p .
 - Vector pole pp^+ : approximation of the normal direction at p .
 - The negative pole p^- : vertex of V_p furthest from p^+ in the direction opposite to the vector pp^+



57

3D reconstruction by approximating the medial axis

- 3D approximation:
 - Retain only polar balls (centered on the poles)



58

3D reconstruction by approximating the medial axis

- 3D approximation:
 - Retain only polar balls (centered on the poles)
 - Yes, but which ones?

59

Power Crust

- It is difficult to know which polar balls are internal
- However, local criteria make it possible to distinguish polar balls of different natures
 - Two adjacent "deeply intersecting" polar balls are considered to be on the same side of the surface
 - Two "barely intersecting" polar balls are one internal and the other external

60

59

60


Power Crust

- Labelling of polar balls
- Global heuristics
 - "External" labelling of the poles incident to a large enclosing box
- Propagation of labels:
 - For any pole p labelled "external".
 - each unlabelled neighbor q such that the polar balls associated with p and q intersect deeply is labelled "external".
 - For each point s of S considering p is the pole, the other pole is labelled internal.
 - For any pole labelled "internal".
 - Symmetrical work
- Using a priority queue

61

Power Crust


- How to switch from a set of balls to a mesh?



62

Power Crust

- How to switch from a set of balls to a mesh?
 - Construction of a ball **power diagram**.




63

Power diagram

- Can be seen as a Voronoi diagram of balls with an adhoc metric
 - Ball B of center c and radius r
 - Power distance of a point x with respect to B :


$$d_{\text{pow}} = d^2(c, x) - r^2$$



64

Power Crust


- Note: The dual of a power diagram is a triangulation connecting the centers of the circles (Regular triangulation)



65

Power Crust

- Construction of a power diagram using polar balls
- Reconstructed surface:
 - set of facets of the diagram whose dual edges link an inner pole and an outer pole.



66

65


66

Power-Crust Results




67

Power Crust results



68

Power-Crust Result



69

Power Crust

- Robustness:

- The output mesh is the boundary of a solid (by construction) but does not only contain triangles
- No surface extraction or hole filling steps

- Correctness:


- Theoretical results that relate the geometric and topological validity of the result to the quality of the sampling

70

Power Crust

- Correctness:


- All the (wide) polar balls passing through a sample s are nearly tangential to the surface in s



71

Power Crust

- Given a ϵ - sampling of a surface S , the angle between the normal at S in s and the vector joining s to one of its poles is in $O(\epsilon)$




72

71

72

Power Crust Results



- Robustness to noise

73


Power Crust

- Power crust also provides an approximation of the medial axis
- Connection of the inner poles with adjacent cells in the power diagram



74

Power Crust results




- Simplification of the skeleton (noisy samples or not)

75

Power Crust Results


- Sharp edges can be inferred



76

Power Crust results


- Respect of sharp edges :
 - Ignore poles associated with malformed Voronoi cells



77

Offset surface management

- Narrowing of the internal polar balls
- Widening of the external polar balls




78

77

Handling noise

- By simplifying the medial axis
- Delete polar balls associated with vertices that are too close to the pole



79

79