

Boutique International (P) LTD

C-45-46-47 Hosiery Complex Noida, PH-II, Gautam Budh Nagar, U.P. 201305.

GST No: 09AAACB4905C1Z5, Tel: (+91) 120 6797979, Fax: (+91) 120 6797999, E-mail: info@boutique.in

Purchase Order

PO No: BAA475 PO 11 Jan 23 Supplier: BIPL ACCESSORY ₹1.3 (0 Days) (11 Jan ETA 11 Jan 23 Date: (Wed) Date: (Wed)

Client Code: EMP

	Accessory Quality (Size) Color/Print	Shrnkg	Wstg	Accessory Type	Quantity*			Finance*	
					Send	Receivable	Unit	Rate	Total Amount
	Metal Logo	8 %	5 %	Greige		8,009	Pcs	₹ 1.3	₹ 10,412

History Of Revise Purchase Order				
Date	PO Quantity			
11 Jan 23 (Wed)	8,009 Pcs			

From Qty.	To Qty.	ETA Dates
1	8,009 Label	11 <mark>Jan</mark> 23 (We <mark>d)</mark>
TI	H.	
4		

Remarks:

General Instructions :-

- 1. All bills must state the Purchase Order number. Missing PO numbers on bills will nullify the bill.
- 2. Good must be 100% checked on tables by vendor. It is complete responsibility of the supplier to dispatch only acceptable goods under 4 point AQL. If goods fail 5% check at BIPL or arrives without 100% checking reports, BIPL reserves the right to return goods to vendor or charge them damages and checking charges.
- 3. Any quality issues related base quality parameters will lead to discounts or cancellations by BIPL.
- 4. Rejected goods must be collected within a week, else BIPL will not be responsible for the returnable goods.
- 5. All disputes will be subject to Delhi NCR jurisdiction.

Processed Instructions:-

- 1. Matching to be on D65
- 2. Finishing should be silicon finished in overfeeding. Soft Handfeel. All polyester and Nylon antistatic finish is a must.
- 3. Finishing shrinkage/Dimensional stability to steam to be +/-2%.
- 4. Banned chemicals: Azo, PCP, PH Value -6, heavy metals.
- 5. Bowing less than 3 inches will be acceptable.
- 6. After wash shrinkage should be less than 2%.
- 7.BIPL stamp on both ends of the Accessories should not be removed.
- 8. Colour fastness on multi fiber: Rubbing, Dry Cleaning, Washing 40 *C, Sun Fastness, Light Fastness must be minimum 4.
- 9. Pilling should be 4-5.
- 10. Tensile Strength 15 kg, Tear strength 1000 GM and Seam Slippage 8kg.

