🚩 Challenge #0: 🧙‍♂️ Simple NFT Example

🎫 This tutorial is meant for developers that already understand the 🔏 basics.

🐣 If you would like a more gentle introduction for developers, watch our 15 video 📺 Web2 to Web3 series.

🎥 Create a simple NFT.

🧑‍🏫 You'll compile and deploy your first smart contracts. Then, you'll use a template React DApp full of important Ethereum components and hooks. Finally, you'll deploy an NFT to a public network to share with friends! 🚀

💾 The final deliverable is an app that lets users purchase and transfer NFTs. Deploy your contracts to a testnet, then build and upload your app to a public web server. Submit the url to SpeedRunEthereum.com!

🏃 Head over to builders working on this challenge and get help in the Challenge 0: Telegram!

💬 If you have any question during your Challenge, you can try out the Challenge #0 assistant, and get answers to your Challenge/SpeedRun ETH questions. Please reach us in Telegram if something feels wrong!

Checkpoint 0: 📦 Environment 📚

Before you begin, you need to install the following tools:

- Node (>= v18.18)
- Yarn (v1 - v3)
- Git

Then download the challenge to your computer and install dependencies by running:

```
git clone challenge-0-simple-nft challenge-0-simple-nft
cd challenge-0-simple-nft
```

In the same terminal, start your local network (a local instance of a blockchain):

```
yarn chain
```

In a second terminal window, 🛰 deploy your contract (locally):

```
cd challenge-0-simple-nft
yarn deploy
```

In a third terminal window, start your 📱 frontend:

```
cd challenge-0-simple-nft
yarn start
```

🔭 Open http://localhost:3000 to see the app.

Checkpoint 1: ⛽ Gas & Wallets 👛

📝 *You'll need to get some funds from the faucet for gas.*



🦊 *At first, don't connect MetaMask. If you are already connected, click Disconnect.*

📝 *We'll use burner wallets on localhost.*

📝 *Explore two burner wallets work in 🦊 Brafdtef ETH if by opening a new incognito window and navigate to http://localhost:3000. You'll notice it has a new wallet address in the top right. Copy the incognito browser's address and send localhost test funds to it from your first browser (using the Faucet button in the bottom left)!*



📝 *When you close the incognito window, the account is gone forever. Burner wallets are great for local development but you'll move to more permanent wallets when you interact with public networks.*

Checkpoint 2: 💵 Minting

📝 *Mint some NFTs! Click the MINT NFT button in the My NFTs tab.*

🤔 You should see your NFTs start to show up:



🎨 Open an incognito window and navigate to http://localhost:3000

🔀 Transfer an NFT to the incognito window address using the UI:



🤔 Try to send an NFT back from the incognito window.

Can you mint an NFT with no funds in this address? You might need to grab funds from the faucet to pay for the gas!

🤓 Inspect the `debug Contracts` tab to figure out what address is the owner of YourCollectible!

🤔 You can also check out your latest contract `nextOwnerToMint` on http://localhost:3000/contracts

🤖 Take a quick look at your deploy script `00_deploy_your_contract.js` in `packages/hardhat/deploy`

📄 If you want to edit the frontend, navigate to `packages/nextjs/pages` and open the specific page you want to modify. For instance, `nextjs/pages/index.tsx`. For guidance on routing and configuring pages/layouts checkout the Next.js documentation.

Checkpoint 3: 🛰 Deploy your contract! 🚀

🚀 Ready to deploy to a public testnet?!?

Change the defaultNetwork in `packages/hardhat/hardhat.config.ts` to `sepolia`.

```
const config: HardhatUserConfig = {
  solidity: "0.8.9",
  defaultNetwork: "sepolia",
```

🔐 Generate a deployer address with `yarn generate` This creates a unique deployer address and saves the mnemonic locally.

This local account will deploy your contracts, allowing you to avoid entering a personal private key.

```
cd challenge-0-simple-nft
yarn generate
```

```
👛 Generating new wallet
🔐 Private Key saved to packages/hardhat/.env file
```

🔍 Use `yarn account` to view your deployer account balances.

```
cd challenge-0-simple-nft
yarn account
```



🔑 You will need to send ETH to your deployer address with your wallet, or get it from a public faucet of your chosen network.

Some popular Sepolia faucets are the Alchemy faucet, Infura faucet, and Google Cloud Faucet.

If the Quest Keep a 🦊 scaffold-eth on your phone's home screen and keep it loaded with testnet eth. 😉 You'll look like a wizard when funds your deployer address from your phone in seconds.

🚀 Deploy your NFT smart contract with `yarn deploy`

**If `00_deploy_your_contract.js` in `hardhat-config.ts` is `sepolia` (30 gwei) and `yarn deploy --network sepolia`*

Checkpoint 4: 🚢 Ship your frontend! 🚁

Edit your frontend config in `packages/nextjs/scaffold.config.ts` to change the `targetNetwork` to `chains.sepolia`.

```
const scaffoldConfig = {
  // The networks on which your DApp is live
  targetNetworks: [chains.sepolia],
```

You should see the correct network in the frontend (http://localhost:3000)



📡 *Since we have deployed to a public testnet, you will now need to connect using a wallet you own or use a burner wallet. By default 🔥 burner wallets are only available on `hardhat`. You can enable them on every chain by setting `onlyLocalBurnerWallet: false` in your frontend config `scaffold.config.ts` in `packages/nextjs`.*

📝 *Edit your faster loading of your transfer page, consider updating the `fromBlock` passed to `useScaffoldEventHistory` in `packages/nextjs/app/transfers/page.tsx` to `YourContract` or `0` which your contract was deployed. Example: `fromBlock: process.env.NEXT_PUBLIC_DEPLOY_BLOCK` this environment variable is your contract's address on Ethereum and that the `deployed-contracts` transaction block.*

🚀 Deploy your NextJS App

```
yarn vercel
```

You might need to log in to Vercel first by running `yarn vercel:login` (Once you log in (email, GitHub, etc), the default options should work.

If you want to redeploy to the same production URL you can run `yarn vercel:prod`. If you want the `prod` flag it will deploy it to a preview/test URL.

Follow the steps to deploy to Vercel. It'll give you a public URL.

🔏 Run the automated testing function to make sure your app passes

```
yarn test
```

Configuration of Third-Party Services for Production-Grade Apps.

By default, 👷 Brafdtef ETH 2 provides prioritized API keys for popular services such as Alchemy and Etherscan. This allows you to begin developing and testing your applications more easily, avoiding the need to register for these services. This is great to complete your SpeedRunEthereum.

For production-grade applications, it's recommended to obtain your own API keys (to prevent rate limiting issues). You can configure these at:

1. `ALCHEMY_API_KEY` variable in `packages/hardhat/.env` and `packages/nextjs/.env.local`. You can create API keys from the Alchemy dashboard.
2. `ETHERSCAN_API_KEY` variable in `packages/hardhat/.env` with your generated API key. You can get your key here.

🔥 Note: it's recommended to store env's for nextjs in Vercel/system env config for live apps and use .env.local for local testing.

Checkpoint 5: 📜 Contract Verification

You can verify your smart contract on Etherscan by running `yarn verify --network network_name`

```
yarn verify --network sepolia
```

It is okay if it says your contract is already verified. Copy the address of YourCollectible.sol and search it on sepolia Etherscan to find the correct URL you need to submit this checkpoint.

Checkpoint 6: 💪 Flex!

🚢 Share your public url with a friend and ask them for their address to send them a collectible :)

⚔️ Side Quests

👀 Open Sea

📝 *Want to see your new NFTs on Opensea? Head to Testnets Opensea*

📝 *Make sure you have minted some NFTs on your Hardhat chain, then connect to Opensea using that same wallet.*

📝 *You can see your collection of shiny new NFTs on a testnet!*

(It can take a while before they show up, but here is an example:) https://testnets.opensea.io/assets/sepolia/0x17ed035999553f7fe4a75f4d5351cf0d73bdbc12

🏃 Next to your next challenge here *

📝 *Problems, questions, comments on the stack? Post them to the 🏗 scaffold-eth developers chat!*

View on GitHub ↗

Related guides

ERC721 vs. ERC1155: Key Differences, Use Cases & How to Choose

Mastering ERC20: Developer Guide to NFT Metadata & Best Practices

NFTs in Web3: Understanding Use Cases Beyond Digital Art

Solidity NFT Security: 12 Best Practices to Protect Your Collectibles