

RogueShooter – All Scripts

Generated: 2025-10-27 13.43 UTC

Files: 122

Scanned: Assets/scripts

RogueShooter – All Scripts

Assets/scripts/Boot/OfflineSceneBoot.cs

```
using System.Collections;
using UnityEngine;
using UnityEngine.SceneManagement;

public static class OfflineSceneBoot
{
    // Ajetaan aina, heti kun ensimmäinen scene on ladattu (buildissä Core)
    [RuntimeInitializeOnLoadMethod(RuntimeInitializeLoadType.AfterSceneLoad)]
    static void EnsureOfflineLevel()
    {
        if (NetMode.IsOnline) return;

        // Jos jokin muu kuin Core on jo auki (esim. online host vaihtoi scenen), älä tee mitään
        for (int i = 0; i < SceneManager.sceneCount; i++)
        {
            var s = SceneManager.GetSceneAt(i);
            if (s.isLoaded && s.name != (LevelLoader.Instance?.CoreSceneName ?? "Core"))
                return;
        }

        // Offline-käynnistys: ei tukeuduta Mirrorin tilaan ollenkaan
        var _ = CoroutineRunner.Run(Co_Boot());
    }

    static IEnumerator Co_Boot()
    {
        // 1) Core ladattuna ja aktiiviseksi
        string coreName = LevelLoader.Instance?.CoreSceneName ?? "Core";

        var core = SceneManager.GetSceneByName(coreName);
        if (!core.IsValid() || !core.isLoaded)
        {
            var loadCore = SceneManager.LoadSceneAsync(coreName, LoadSceneMode.Additive);
            while (loadCore != null && !loadCore.isDone) yield return null;
            core = SceneManager.GetSceneByName(coreName);
        }
        if (core.IsValid()) SceneManager.SetActiveScene(core);

        // 2) Päätä ladattava kenttä LevelLoaderista
        string requested =
            LevelLoader.Instance?.CurrentLevel ??
            LevelLoader.Instance?.DefaultLevel;

        // Fallback: vain jos "Level 0" on oikeasti Build Settingsissä
        if (string.IsNullOrEmpty(requested) || !Application.CanStreamedLevelBeLoaded(requested))
        {
            if (!string.IsNullOrEmpty(requested))
                Debug.LogWarning($"[OfflineBoot] '{requested}' ei ole Build Settingsissä. Yritetään fallbackia.");

            if (Application.CanStreamedLevelBeLoaded("Level 0"))
            {

```

RogueShooter – All Scripts

```
        requested = "Level 0";
    else
    {
        Debug.LogError("[OfflineBoot] Ei löydy ladattavaa kenttää: Current/Default puuttuu ja 'Level 0' ei ole Build Settingsissä.");
        yield break;
    }
}

// 3) Lataa kenttä additiivisesti
Debug.Log($"[OfflineBoot] Loading offline level '{requested}'");
var op = SceneManager.LoadSceneAsync(requested, LoadSceneMode.Additive);
while (op != null && !op.isDone) yield return null;

var map = SceneManager.GetSceneByName(requested);
if (!map.IsValid() || !map.isLoaded)
{
    Debug.LogError($"[OfflineBoot] Scene '{requested}' ei latautunut.");
    yield break;
}

// 4) Aktivoi map yhdeksi frameksi, jotta sen Start/OnEnable ehtivät
SceneManager.SetActiveScene(map);
yield return null; // 1 frame
yield return new WaitForEndOfFrame();

// 5) Kenttäkohtaiset hookit (esim. edge bake, miehitys)
var edgeBaker = Object.FindFirstObjectByType<EdgeBaker>();
edgeBaker?.BakeAllEdges();

if (LevelGrid.Instance != null)
    LevelGrid.Instance.RebuildOccupancyFromScene();

// 6) Palauta Core aktiiviseksi (UI yms.) ja ilmoita, että level on valmis
if (core.IsValid()) SceneManager.SetActiveScene(core);

try { LevelLoader.RaiseLevelReady(map); } catch { /* ei kriittinen */ }

Debug.Log($"[OfflineBoot] Core + '{requested}' valmiina.");
}

// Minimaalinen "global coroutine host" ilman mitään GameObjectia
private sealed class CoroutineRunner : MonoBehaviour
{
    static CoroutineRunner _inst;
    public static Coroutine Run(IEnumerable e)
    {
        {
            if (_inst == null)
            {
                var go = new GameObject("~OfflineBoot");
                Object.DontDestroyOnLoad(go);
                _inst = go.AddComponent<CoroutineRunner>();
            }
        }
    }
}
```

RogueShooter - All Scripts

```
        return _inst.StartCoroutine(e);  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/Camera/CameraController.cs

```
using UnityEngine;
using Unity.Cinemachine;

// <summary>
// This script controls the camera movement, rotation, and zoom in a Unity game using the Cinemachine package.
// It allows the player to move the camera using WASD keys, rotate it using Q and E keys, and zoom in and out using the mouse scroll wheel.
// The camera follows a target object with a specified offset, and the zoom level is clamped to a minimum and maximum value.
// </summary>
public class CameraController : MonoBehaviour
{
    private const float MIN_FOLLOW_Y_OFFSET = 2f;
    private const float MAX_FOLLOW_Y_OFFSET = 18f;//12f;

    public static CameraController Instance { get; private set; }
    [SerializeField] private CinemachineCamera cinemachineCamera;

    private CinemachineFollow cinemachineFollow;
    private Vector3 targetFollowOffset;

    private float moveSpeed = 10f;
    private float rotationSpeed = 100f;
    private float zoomSpeed = 5f;

    private void Awake()
    {
        if (Instance != null)
        {
            Debug.LogError("CameraController: More than one CameraController in the scene! " + transform + " - " + Instance);
            Destroy(gameObject);
            return;
        }

        Instance = this;
    }

    private void Start()
    {
        cinemachineFollow = cinemachineCamera.GetComponent<CinemachineFollow>();
        targetFollowOffset = cinemachineFollow.FollowOffset;
    }

    private void Update()
    {
        HandleMovement(moveSpeed);
        HandleRotation(rotationSpeed);
        HandleZoom(zoomSpeed);
    }

    private void HandleMovement(float moveSpeed)
    {

```

RogueShooter – All Scripts

```
        Vector2 inputMoveDirection = InputManager.Instance.GetCameraMoveVector();
        Vector3 moveVector = transform.forward * inputMoveDirection.y + transform.right * inputMoveDirection.x;
        transform.position += moveSpeed * Time.deltaTime * moveVector;
    }

    private void HandleRotation(float rotationSpeed)
    {
        Vector3 rotationVector = new Vector3(0, 0, 0);
        rotationVector.y = InputManager.Instance.GetCameraRotateAmount();
        transform.eulerAngles += rotationSpeed * Time.deltaTime * rotationVector;
    }

    private void HandleZoom(float zoomSpeed)
    {
        float zoomIncreaseAmount = 1f;
        targetFollowOffset.y += InputManager.Instance.GetCameraZoomAmount() * zoomIncreaseAmount;

        targetFollowOffset.y = Mathf.Clamp(targetFollowOffset.y, MIN_FOLLOW_Y_OFFSET, MAX_FOLLOW_Y_OFFSET);
        cinemachineFollow.FollowOffset = Vector3.Lerp(cinemachineFollow.FollowOffset, targetFollowOffset, Time.deltaTime * zoomSpeed);
    }

    public float GetCameraHeight()
    {
        return targetFollowOffset.y;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Camera/CameraManager.cs

```
using System;
using UnityEngine;

public class CameraManager : MonoBehaviour
{
    [SerializeField] private GameObject actionCameraGameObject;

    [SerializeField] private float actionCameraVerticalPosition = 2.5f;

    void OnEnable()
    {
        BaseAction.OnAnyActionStarted += BaseAction_OnAnyActionStarted;
        BaseAction.OnAnyActionCompleted += BaseAction_OnAnyActionCompleted;
        HideActionCamera();
    }

    void OnDisable()
    {
        BaseAction.OnAnyActionStarted -= BaseAction_OnAnyActionStarted;
        BaseAction.OnAnyActionCompleted -= BaseAction_OnAnyActionCompleted;
    }

    private void ShowActionCamera()
    {
        actionCameraGameObject.SetActive(true);
    }

    private void HideActionCamera()
    {
        actionCameraGameObject.SetActive(false);
    }

    private void BaseAction_OnAnyActionStarted(object sender, EventArgs e)
    {
        switch (sender)
        {
            case ShootAction shootAction:
                Unit shooterUnit = shootAction.GetUnit();
                Unit targetUnit = shootAction.GetTargetUnit();

                Vector3 cameraCharacterHeight = Vector3.up * actionCameraVerticalPosition; //1.7f;
                Vector3 shootDir = (targetUnit.GetWorldPosition() - shooterUnit.GetWorldPosition()).normalized;

                float shoulderOffsetAmount = 0.5f;
                Vector3 shoulderOffset = Quaternion.Euler(0, 90, 0) * shootDir * shoulderOffsetAmount;
                Vector3 actionCameraPosition =
                    shooterUnit.GetWorldPosition() +
                    cameraCharacterHeight +
                    shoulderOffset +
                    (shootDir * -1);
            break;
        }
    }
}
```

RogueShooter – All Scripts

```
        actionCameraGameObject.transform.position = actionCameraPosition;
        actionCameraGameObject.transform.LookAt(targetUnit.GetWorldPosition() + cameraCharacterHeight);
        ShowActionCamera();
        break;
    }
}

private void BaseAction_OnAnyActionCompleted(object sender, EventArgs e)
{
    switch (sender)
    {
        case ShootAction shootAction:
            HideActionCamera();
            break;
    }
}
}
```


RogueShooter – All Scripts

Assets/scripts/Camera/FloorVisibility.cs

```
using System.Collections.Generic;
using UnityEngine;

public class FloorVisibility : MonoBehaviour
{
    [SerializeField] private bool dynamicFloorPosition;
    [SerializeField] private List<Renderer> ignoreRendererList;
    private HashSet<Renderer> ignoreSet;
    private Renderer[] rendererArray;
    private int floor;
    private bool? lastVisible;           // vältä turhat muutokset
    private Unit unit;                  // jos kohde on Unit tai sen alla
    private bool forceHidden;           // ulkoinen lukko (esim. kuolema)

    private void Awake()
    {
        rendererArray = GetComponentsInChildren<Renderer>(true);
        unit = GetComponentInParent<Unit>(); // tai GetComponent<Unit>() jos scripti istuu suoraan Unitissa

        if (unit != null)
        {
            // reagoi heti piilotukseen/poistoon
            unit.OnHiddenChangedEvent += OnUnitHiddenChanged;
            forceHidden = unit.IsHidden();
        }

        ignoreSet = new HashSet<Renderer>(ignoreRendererList);
    }

    void OnDisable()
    {
        if (unit != null) unit.OnHiddenChangedEvent -= OnUnitHiddenChanged;
    }

    private void Start()
    {
        floor = LevelGrid.Instance.GetFloor(transform.position);
        Recompute();
    }

    private void OnDestroy()
    {
        if (unit != null) unit.OnHiddenChangedEvent -= OnUnitHiddenChanged;
    }

    private void Update()
    {
        if (dynamicFloorPosition)
        {
```

RogueShooter – All Scripts

```
        floor = LevelGrid.Instance.GetFloor(transform.position);
    }

    Recompute();
}

private void Recompute()
{
    // 1) kamerakorkeuteen perustuva perusnäkyvyys
    float cameraHeight = CameraController.Instance.GetCameraHeight();
    float floorHeightOffset = 2f;
    bool cameraWantsVisible = (cameraHeight > LevelGrid.FLOOR_HEIGHT * floor + floorHeightOffset) || floor == 0;

    // 2) unitin piilotus "lukitsee" näkymättömäksi
    bool visible = cameraWantsVisible && !forceHidden;

    if (lastVisible.HasValue && lastVisible.Value == visible) return; // ei muutosta
    lastVisible = visible;

    ApplyVisible(visible);
}

private void ApplyVisible(bool visible)
{
    foreach (var r in rendererArray)
    {
        if (!r) continue;
        if (ignoreSet.Contains(r)) continue;
        r.enabled = visible;
    }
}

// Jos haluat ulkopuolelta pakottaa piiloon (esim. ragdollin spawner tms.)
public void SetForceHidden(bool hidden)
{
    forceHidden = hidden;
    Recompute();
}

private void OnUnitHiddenChanged(bool hidden)
{
    forceHidden = hidden;
    Recompute();
}

public void AddIgnore(Renderer r)
{
    ignoreRendererList.Add(r);
    ignoreSet.Add(r);
}

public void RemoveIgnore(Renderer r)
{
}
```

RogueShooter – All Scripts

```
        ignoreRendererList.Remove(r);  
        ignoreSet.Remove(r);  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/Camera/Look At Camera.cs

```
using UnityEngine;

/// <summary>
/// Turn wordUI elements ( Like Unit Health and action points) toward to camera.
/// </summary>
public class LookAtCamera : MonoBehaviour
{
    [SerializeField] private bool invert;

    private Transform cameraTransform;

    private void Awake()
    {
        cameraTransform = Camera.main.transform;
    }

    private void LateUpdate()
    {
        if (invert)
        {
            Vector3 dirToCamera = (cameraTransform.position - transform.position).normalized;
            transform.LookAt(transform.position + dirToCamera * -1);
        } else
        {
            transform.LookAt(cameraTransform);
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Camera/ScreenShake.cs

```
using Unity.Cinemachine;
using UnityEngine;

public class ScreenShake : MonoBehaviour
{
    public static ScreenShake Instance { get; private set; }

    [SerializeField]
    private CinemachineImpulseSource cinemachineRecoilImpulseSource;

    [SerializeField]
    private CinemachineImpulseSource cinemachineExplosiveImpulseSource;

    private void Awake()
    {
        // Ensure that there is only one instance in the scene
        if (Instance != null)
        {
            Debug.LogError("ScreenShake: More than one ScreenShake in the scene!" + transform + " " + Instance);
            Destroy(gameObject);
            return;
        }

        Instance = this;
    }

    public void ExplosiveCameraShake(float ShakeStrength)
    {
        cinemachineExplosiveImpulseSource.GenerateImpulse(ShakeStrength);
    }

    public void RecoilCameraShake(float ShakeStrength)
    {
        cinemachineRecoilImpulseSource.GenerateImpulse(ShakeStrength);
    }
}
```

RogueShooter – All Scripts

Assets/scripts/CoverSystem/CoverService.cs

```
public static class CoverService
{
    public enum CoverType { None, Low, High }

    public static float GetCoverMitigationBase(CoverType t)
        => t == CoverType.High ? .6f : (t == CoverType.Low ? .7f : 0);

    public static float GetCoverMitigationPoints(CoverType t)
    {
        float basePts = GetCoverMitigationBase(t);
        return basePts;
    }

    public static CoverType EvaluateCoverHalfPlane(GridPosition attacker, GridPosition target, PathNode node)
    {
        if (attacker.floor != target.floor) return CoverType.None; // pidä yksinkertaisena

        int dx = attacker.x - target.x;
        int dz = attacker.z - target.z;

        if (node == null) return CoverType.None;

        bool ge = false; // "greater or equal" rajalla?
        bool facesN = ge ? (dz >= 0) : (dz > 0);
        bool facesS = ge ? (dz <= 0) : (dz < 0);
        bool facesE = ge ? (dx >= 0) : (dx > 0);
        bool facesW = ge ? (dx <= 0) : (dx < 0);

        bool high =
            (facesN && node.HasHighCover(CoverMask.N)) ||
            (facesS && node.HasHighCover(CoverMask.S)) ||
            (facesE && node.HasHighCover(CoverMask.E)) ||
            (facesW && node.HasHighCover(CoverMask.W));

        if (high) return CoverType.High;

        bool low =
            (facesN && node.HasLowCover(CoverMask.N)) ||
            (facesS && node.HasLowCover(CoverMask.S)) ||
            (facesE && node.HasLowCover(CoverMask.E)) ||
            (facesW && node.HasLowCover(CoverMask.W));

        return low ? CoverType.Low : CoverType.None;
    }

    public static CoverType GetNodeAnyCover(PathNode node)
    {
        if (node == null) return CoverType.None;
    }
}
```

RogueShooter – All Scripts

```
    if (node.GetHighCoverMask() != CoverMask.None) return CoverType.High;  
    if (node.GetLowCoverMask() != CoverMask.None) return CoverType.Low;  
    return CoverType.None;  
}  
}
```

RogueShooter – All Scripts

Assets/scripts/CoverSystem/CoverVisualizer.cs

```
using UnityEngine;

[DefaultExecutionOrder(200)]
[DisallowMultipleComponent]
public class CoverVisualizer : MonoBehaviour
{
    [Header("Refs")]
    [SerializeField] private PathFinding pathfinding;
    [SerializeField] private LevelGrid levelGrid;
    [SerializeField] private Camera cam;
    [SerializeField] private Material unlitTransparentMat; // Unlit/Transparent tms.

    [Header("Raycast")]
    [SerializeField] private LayerMask groundMask = ~0; // millä layereilla lattia/maa on

    [Header("Style")]
    [SerializeField] private float yOffset = 0.05f; // nosta vähän lattiasta
    [SerializeField] private float edgeInset = 0.48f; // 0.45-0.49
    [SerializeField] private float barLen = 0.90f; // suhteessa cellSizeen
    [SerializeField] private float barWidth = 0.06f; // X/Z -ohuus
    [SerializeField] private float barHeight = 0.06f; // Y-paksuus
    [SerializeField] private Color lowColor = new(0.2f, 1f, 0.2f, 0.55f);
    [SerializeField] private Color highColor = new(0.2f, 0.5f, 1f, 0.80f);

    [Header("Walls (optional)")]
    [SerializeField] private bool showWalls = true;
    [SerializeField] private Color wallColor = new(1f, 0.4f, 0.1f, 0.80f);

    Transform n,e,s,w; MeshRenderer rn,re,rs,rw; float cell;

    void Awake() {
        if (!pathfinding) pathfinding = FindFirstObjectByType<PathFinding>();
        if (!levelGrid) levelGrid = LevelGrid.Instance;
        if (!cam) cam = Camera.main;

        if (levelGrid == null) { enabled = false; return; }

        cell = levelGrid.GetCellSize();
        (n,rn) = CreateBar("N");
        (e,re) = CreateBar("E");
        (s,rs) = CreateBar("S");
        (w,rw) = CreateBar("W");
        HideAll();
    }

    (Transform, MeshRenderer) CreateBar(string name) {
        var go = GameObject.CreatePrimitive(PrimitiveType.Cube);
        go.name = $"CoverHover_{name}";
        Destroy(go.GetComponent<Collider>());
        go.transform.SetParent(transform, false);
    }
}
```


RogueShooter – All Scripts

```
var mr = go.GetComponent<MeshRenderer>();
if (unlitTransparentMat) mr.sharedMaterial = unlitTransparentMat;
go.SetActive(false);
return (go.transform, mr);
}

void Update() {
    BaseAction action = UnitActionSystem.Instance.GetSelectedAction();
    if (action == null) return;
    if (!pathfinding || !levelGrid || !cam || action.GetActionName() != "Move") { HideAll(); return; }

    var ray = cam.ScreenPointToRay(Input.mousePosition);
    if (!Physics.Raycast(ray, out var hit, 500f, groundMask, QueryTriggerInteraction.Collide)) { HideAll(); return; }

    // Ruudukkoon
    var gp = levelGrid.GetGridPosition(hit.point);
    var node = pathfinding.GetNode(gp.x, gp.z, gp.floor);
    if (node == null || !node.GetIsWalkable()) { HideAll(); return; }

    var c = levelGrid.GetWorldPosition(gp);
    c.y += yOffset;

    // Reunan keskikohdat
    var north = c + new Vector3(0, 0, cell * edgeInset);
    var south = c + new Vector3(0, 0, -cell * edgeInset);
    var eastP = c + new Vector3(cell * edgeInset, 0, 0);
    var westP = c + new Vector3(-cell * edgeInset, 0, 0);

    // N/S = pituus X-suunnassa, E/W = pituus Z-suunnassa
    DrawBar(node.HasHighCover(CoverMask.N), node.HasLowCover(CoverMask.N), node.HasWall(EdgeMask.N), n, rn, north, new Vector3(cell*barLen, barHeight, barWidth));
    DrawBar(node.HasHighCover(CoverMask.S), node.HasLowCover(CoverMask.S), node.HasWall(EdgeMask.S), s, rs, south, new Vector3(cell*barLen, barHeight, barWidth));
    DrawBar(node.HasHighCover(CoverMask.E), node.HasLowCover(CoverMask.E), node.HasWall(EdgeMask.E), e, re, eastP, new Vector3(barWidth, barHeight, cell*barLen));
    DrawBar(node.HasHighCover(CoverMask.W), node.HasLowCover(CoverMask.W), node.HasWall(EdgeMask.W), w, rw, westP, new Vector3(barWidth, barHeight, cell*barLen));
}

void DrawBar(bool high, bool low, bool wall, Transform tr, MeshRenderer mr, Vector3 pos, Vector3 size) {
    if (!high && !low && !(showWalls && wall)) { tr.gameObject.SetActive(false); return; }
    tr.gameObject.SetActive(true);
    tr.position = pos;
    tr.localScale = size;

    // Väri prioriteetilla: seinä > high cover > low cover
    var color = (showWalls && wall) ? wallColor : (high ? highColor : lowColor);
    var m = mr.material; // runtime-instanssi
    m.color = color;
}

void HideAll() {
    if (n) n.gameObject.SetActive(false);
    if (e) e.gameObject.SetActive(false);
    if (s) s.gameObject.SetActive(false);
    if (w) w.gameObject.SetActive(false);
}
```

```
}  
}
```

RogueShooter – All Scripts

Assets/scripts/CoverSystem/EdgeBaker.cs

```
using System;
using System.Collections;
using UnityEngine;

[DefaultExecutionOrder(500)] // After Pathfindingin
[DisallowMultipleComponent]

/// @file EdgeBaker.cs
/// @brief Edge-based obstacle detection and wall baking system for RogueShooter.
///
/// The EdgeBaker scans the environment to detect narrow obstacles (walls, fences, railings, doorframes)
/// between adjacent grid cells and encodes them as edge-wall flags in the pathfinding data.
/// This ensures that unit movement and line-of-sight calculations align precisely with physical geometry.
///
/// ### Overview
/// EdgeBaker operates immediately after walkability baking has been performed by the `PathFinding` system.
/// It iterates through all walkable cells and performs four narrow physics checks (north, east, south, west)
/// to detect thin colliders lying between grid borders. Any detected obstacle is stored as an `EdgeMask`
/// flag on both affected nodes to maintain symmetric connectivity.
///
/// ### System integration
/// - **LevelGrid** - Provides spatial dimensions and world→grid coordinate mapping for each cell.
/// - **PathFinding** - Supplies the `PathNode` data structure where edge walls are stored and queried.
/// - **EdgeBaker** - Bridges the physical Unity scene and the logical pathfinding layer by detecting edge blockers.
///
/// ### Key features
/// - Detects fine-grained edge blockers that are smaller than a full grid cell.
/// - Writes edge-wall data symmetrically to adjacent nodes (no “one-way walls”).
/// - Supports incremental rebaking after runtime geometry changes (doors opening, walls destroyed).
/// - Uses Physics.CheckBox for reliable thin-edge detection with adjustable thickness and scan height.
/// - Operates deterministically and independently of Unity’s NavMesh system.
///
/// ### Why this exists in RogueShooter
/// - The game’s tactical combat requires accurate cover and movement restrictions based on geometry.
/// - Standard per-cell walkability alone cannot capture small barriers or partial walls.
/// - This system creates a precise “micro-collision” layer between cells, allowing units to interact
///   with the environment in a realistic and strategically meaningful way.
///
/// In summary, this file defines the edge-detection system that enhances the grid-based pathfinding
/// with sub-cell precision, ensuring that RogueShooter’s movement, visibility, and cover mechanics
/// reflect the actual physical layout of each combat environment.

/// <summary>
/// Automatically detects and marks impassable edges between walkable grid cells,
/// based on physical obstacles present in the scene (walls, fences, railings, doorframes, etc.).
///
/// This component “bakes” thin collision lines along cell borders using Physics.CheckBox tests,
/// writing wall data directly into the PathFinding grid nodes (via EdgeMask flags).
/// It ensures that movement and line-of-sight calculations align with the actual environment geometry.
///
```

RogueShooter – All Scripts

```
/// Design notes specific to RogueShooter:
/// - Used right after walkability baking to identify fine-grained obstacles between adjacent cells.
/// - Prevents units from moving or shooting through narrow environmental blockers
///   that don't occupy a full cell (e.g., half-walls, railings, or destroyed doorframes).
/// - Enables more realistic tactical cover and movement logic without relying on Unity's full NavMesh system.
/// - Automatically rebakes affected areas when dynamic obstacles (like doors or destructible walls) change state.
/// </summary>
public class EdgeBaker : MonoBehaviour
{
    public static EdgeBaker Instance { get; private set; }

    // ==== TallWall (kapeat korkeat seinät) - asetukset ====
    [SerializeField] private LayerMask obstaclesMask; // aseta Inspectorissa "Obstacles"
    [SerializeField] private float tallWallThresholdY = 1.7f; // yli tämän = blokkaa LoS
    [SerializeField] private float edgeProbeHeight = 6f; // kaistan korkeus
    [SerializeField] private float edgeProbeThicknessFactor = 0.12f; // kaistan paksuus suhteessa cellSizeen

    /// ====

    [Header("References")]
    [SerializeField] private PathFinding pathfinding;
    [SerializeField] private LevelGrid levelGrid;

    [Header("When to run")]
    [SerializeField] private bool autoBakeOnStart = true;

    [Header("Edge scan")]
    [Tooltip("Layerit, jotka edustavat RUUTUJEN VÄLISIÄ, ohuita liikkumista estäviä juttuja (kaiteet, seinäviivat, ovenpielet, tms.)")]
    [SerializeField] private LayerMask edgeBlockerMask;

    [Header("Cover scan")]
    [SerializeField] private LayerMask coverMask;

    [Tooltip("Reunan skannauksen 'nauhan' paksuus suhteessa cellSizeen (0.05-0.2 on tyypillinen).")]
    [Range(0.01f, 0.5f)]
    [SerializeField] private float edgeStripThickness = 0.1f;

    [Tooltip("Kuinka korkealta skannataan (metreinä). Yleensä hieman ukkelin pään korkeuden yläpuolelle.")]
    [SerializeField] private float edgeScanHeight = 2.0f;

    [Header("Cover height")]
    [SerializeField] private float lowCoverY = 1.0f; // ~vyötärö
    [SerializeField] private float highCoverY = 1.6f; // ~pää/olkapää

    // ---- Lyhyet aliasit, ettei tarvitse arvailla mistä mikäkin tulee ----
    private PathFinding PF => pathfinding != null ? pathfinding : (pathfinding = FindFirstObjectByType<PathFinding>());
    private LevelGrid LG => levelGrid != null ? levelGrid : (levelGrid = LevelGrid.Instance);

    private int Width;
    private int Height;
    private int FloorAmount;
```

RogueShooter – All Scripts

```
private float CellSize;

private void Awake()
{
    if (Instance != null && Instance != this) { Destroy(gameObject); return; }
    Instance = this;
}

private IEnumerator Start()
{
    yield return new WaitUntil(() => LevelGrid.Instance != null && PathFinding.Instance != null);

    if (pathfinding == null) pathfinding = FindFirstObjectByType<PathFinding>();
    if (levelGrid == null) levelGrid = LevelGrid.Instance;

    Width = levelGrid.GetWidth();
    Height = levelGrid.GetHeight();
    FloorAmount = levelGrid.GetFloorAmount();
    CellSize = levelGrid.GetCellSize();

    if (GameManager.SelectedMode == GameMode.SinglePlayer && autoBakeOnStart)
    {
        BakeAllEdges(); // offline / yksinpeli
    }
}

// ----- PUBLIC API -----
/// <summary>
/// Performs a full edge bake across the entire grid.
///
/// Clears all previously marked walls, then scans every walkable cell
/// in all floors to detect thin obstacles (edges) between neighboring cells.
///
/// Design notes specific to RogueShooter:
/// - This is typically called once at level initialization, right after walkability checks.
/// - It ensures that all cell borders reflect real physical blockers,
///   so units cannot move or shoot through walls, fences, or other narrow obstacles.
/// - Provides the foundation for accurate tactical pathfinding and cover detection.
/// </summary>
public void BakeAllEdges()
{
    if (!Preflight()) return;

    // 1) Clear all existing wall data from every node in every floor
    for (int f = 0; f < FloorAmount; f++)
        for (int x = 0; x < Width; x++)
            for (int z = 0; z < Height; z++)
            {
                var node = PF.GetNode(x, z, f);
                if (node != null) node.ClearWalls();
            }
}
```

RogueShooter – All Scripts

```
// 2) Scan each walkable cell and bake its N/E/S/W edge data
for (int f = 0; f < FloorAmount; f++)
    for (int x = 0; x < Width; x++)
        for (int z = 0; z < Height; z++)
        {
            var gp = new GridPosition(x, z, f);
            if (!IsWalkable(gp)) continue;

            BakeEdgesForCell(gp);
        }

// 3) Update TallWall registry for LoS checks
BakeTallWalls();
}

/// <summary>
/// Rebuilds edge data locally around a given grid position.
///
/// Used when the environment changes dynamically – for example,
/// when a door opens or closes, or when a wall is destroyed.
/// This function rescans a small area instead of rebaking the entire map,
/// keeping pathfinding and cover data up to date with minimal performance cost.
///
/// Design notes specific to RogueShooter:
/// - Ensures that tactical movement and line-of-sight stay accurate
///   after real-time map changes during combat.
/// - Called automatically by interactive elements like doors or destructible props.
/// </summary>
public void RebakeEdgesAround(GridPosition center, int radius = 1)
{
    if (!Preflight()) return;

    // Loop through a square area centered on the target grid position
    for (int dx = -radius; dx <= radius; dx++)
        for (int dz = -radius; dz <= radius; dz++)
        {
            var gp = new GridPosition(center.x + dx, center.z + dz, center.floor);
            if (!IsValidGridPosition(gp) || !IsWalkable(gp)) continue;

            var node = PF.GetNode(gp.x, gp.z, gp.floor);
            if (node == null) continue;

            // 1) Clear old wall data
            node.ClearWalls();

            // 2) Rescan and rebuild edge data for this cell
            BakeEdgesForCell(gp);
        }
}

// ----- CORE -----
/// <summary>
```

RogueShooter – All Scripts

```
/// Scans the four borders (N/E/S/W) of a single walkable grid cell and writes edge-wall flags.
///
/// What it does:
/// - Builds four thin, axis-aligned 3D “strips” (AABBs) that sit exactly on the cell borders.
/// - Uses Physics.CheckBox to detect narrow blockers (rails, thin walls, door frames) at a chosen height.
/// - For every detected blocker, sets the matching EdgeMask flag on the current node
///   and mirrors the opposite flag on the neighboring node to keep graph connectivity symmetric.
///
/// Why this exists in RogueShooter:
/// - Our levels contain many obstacles that do NOT fill the whole cell but still block movement/LOS across an edge.
/// - Baking per-edge blockers yields more faithful tactical movement and cover behavior than cell-only walkability.
/// - Keeping the data symmetric (both sides of the shared edge agree) avoids pathfinding inconsistencies.
///
/// Implementation notes:
/// - Each cell does a constant amount of physics work (4 × Physics.CheckBox).
/// - The strip thickness is a fraction of the cell size (edgeStripThickness), tuned to “catch” thin geometry
///   without overlapping interiors.
/// - The scan runs at edgeScanHeight (centered at Y = edgeScanHeight * 0.5), typically around head-height,
///   so low floor clutter doesn’t cause false positives while walls/rails are still detected.
/// </summary>
private void BakeEdgesForCell(GridPosition gridPosition)
{
    var node = PF.GetNode(gridPosition.x, gridPosition.z, gridPosition.floor);
    node.ClearCover();

    // World-space center of this cell (at floor level)
    Vector3 center = LG.GetWorldPosition(gridPosition);
    float sellSize = CellSize;

    // Place the four strip centers exactly on the cell borders and lift to mid-scan height.
    float scanHeight = edgeScanHeight * 0.5f;
    Vector3 north = center + new Vector3(0f, scanHeight, +sellSize * 0.5f);
    Vector3 south = center + new Vector3(0f, scanHeight, -sellSize * 0.5f);
    Vector3 east = center + new Vector3(+sellSize * 0.5f, scanHeight, 0f);
    Vector3 west = center + new Vector3(-sellSize * 0.5f, scanHeight, 0f);

    PathBlocker(north, south, east, west, sellSize, node, gridPosition);
    WallCovers(north, south, east, west, sellSize, node, gridPosition);
}

private void PathBlocker(Vector3 north, Vector3 south, Vector3 east, Vector3 west, float sellSize, PathNode node, GridPosition gridPosition)
{
    // Define half-extents for the thin scanning strips:
    // - North/South strips are long along Z, thin along X.
    // - East/West strips are long along X, thin along Z.
    // Height half-extent is half of edgeScanHeight (so total box height == edgeScanHeight).
    Vector3 halfNorthSouth = new(sellSize * edgeStripThickness * 0.5f, edgeScanHeight * 0.5f, sellSize * 0.45f);
    Vector3 halfEastWest = new(sellSize * 0.45f, edgeScanHeight * 0.5f, sellSize * edgeStripThickness * 0.5f);

    // Probe NORTH edge; if blocked, mark N on this node and S on the northern neighbor.
    if (HasEdgeBlock(north, halfNorthSouth, Quaternion.identity))
```

RogueShooter – All Scripts

```
{
    node.AddWall(EdgeMask.N);
    MarkOpposite(gridPosition, +0, +1, EdgeMask.S);
}
// Probe SOUTH edge; mirror to the southern neighbor.
if (HasEdgeBlock(south, halfNorthSouth, Quaternion.identity))
{
    node.AddWall(EdgeMask.S);
    MarkOpposite(gridPosition, +0, -1, EdgeMask.N);
}
// Probe EAST edge; mirror to the eastern neighbor.
if (HasEdgeBlock(east, halfEastWest, Quaternion.identity))
{
    node.AddWall(EdgeMask.E);
    MarkOpposite(gridPosition, +1, +0, EdgeMask.W);
}
// Probe WEST edge; mirror to the western neighbor.
if (HasEdgeBlock(west, halfEastWest, Quaternion.identity))
{
    node.AddWall(EdgeMask.W);
    MarkOpposite(gridPosition, -1, +0, EdgeMask.E);
}
}

private void WallCovers(Vector3 north, Vector3 south, Vector3 east, Vector3 west, float sellSize, PathNode node, GridPosition gridPosition)
{
    // --- Cover (sama geometria saa olla eri layerillä kuin edgeBlocker) ---
    // Tehdään matala ja korkea testi erikseen: low = vain vyötäröosuma, high = osuu myös pään korkeuteen.
    // Rajataan boksi vain yhdelle Y-korkeudelle (pieni korkeus), ettei pöydän jalat tms. vaikuta.
    Vector3 lowHalfNS = new Vector3(sellSize * edgeStripThickness * 0.5f, 0.1f, sellSize * 0.45f);
    Vector3 lowHalfEW = new Vector3(sellSize * 0.45f, 0.1f, sellSize * edgeStripThickness * 0.5f);
    Vector3 highHalfNS = lowHalfNS;
    Vector3 highHalfEW = lowHalfEW;

    // pisteet cover-korkeuksille
    Vector3 nLow = new Vector3(north.x, lowCoverY, north.z);
    Vector3 nHigh = new Vector3(north.x, highCoverY, north.z);
    Vector3 sLow = new Vector3(south.x, lowCoverY, south.z);
    Vector3 sHigh = new Vector3(south.x, highCoverY, south.z);
    Vector3 eLow = new Vector3(east.x, lowCoverY, east.z);
    Vector3 eHigh = new Vector3(east.x, highCoverY, east.z);
    Vector3 wLow = new Vector3(west.x, lowCoverY, west.z);
    Vector3 wHigh = new Vector3(west.x, highCoverY, west.z);

    // North
    bool nLowHit = Physics.CheckBox(nLow, lowHalfNS, Quaternion.identity, coverMask);
    bool nHighHit = Physics.CheckBox(nHigh, highHalfNS, Quaternion.identity, coverMask);
    if (nHighHit) node.AddHighCover(CoverMask.N);
    else if (nLowHit) node.AddLowCover(CoverMask.N);

    // South
    bool sLowHit = Physics.CheckBox(sLow, lowHalfNS, Quaternion.identity, coverMask);
```


RogueShooter – All Scripts

```
bool sHighHit = Physics.CheckBox(sHigh, highHalfNS, Quaternion.identity, coverMask);
if (sHighHit) node.AddHighCover(CoverMask.S);
else if (sLowHit) node.AddLowCover(CoverMask.S);

// East
bool eLowHit = Physics.CheckBox(eLow, lowHalfEW, Quaternion.identity, coverMask);
bool eHighHit = Physics.CheckBox(eHigh, highHalfEW, Quaternion.identity, coverMask);
if (eHighHit) node.AddHighCover(CoverMask.E);
else if (eLowHit) node.AddLowCover(CoverMask.E);

// West
bool wLowHit = Physics.CheckBox(wLow, lowHalfEW, Quaternion.identity, coverMask);
bool wHighHit = Physics.CheckBox(wHigh, highHalfEW, Quaternion.identity, coverMask);
if (wHighHit) node.AddHighCover(CoverMask.W);
else if (wLowHit) node.AddLowCover(CoverMask.W);
}

/// <summary>
/// Checks whether a physical obstacle exists along a specific cell edge.
///
/// Uses Physics.CheckBox with the configured <see cref="edgeBlockerMask"/> to detect
/// any geometry that should prevent movement or line-of-sight across that border.
///
/// Why this exists in RogueShooter:
/// - We rely on thin colliders (walls, railings, doorframes) placed between grid cells.
/// - Detecting those lets the pathfinding system respect scene geometry more accurately
///   than simple per-cell walkability checks.
/// - Called four times per cell (once for each direction) during edge baking.
///
/// Implementation notes:
/// - Returns true if *any* collider in the given layer mask overlaps the test volume.
/// - QueryTriggerInteraction.Ignore avoids false positives from trigger colliders.
/// </summary>
private bool HasEdgeBlock(Vector3 center, Vector3 halfExtents, Quaternion rot)
{
    return Physics.CheckBox(center, halfExtents, rot, edgeBlockerMask, QueryTriggerInteraction.Ignore);
}

/// <summary>
/// Mirrors an edge-wall flag to the neighboring grid cell so both sides of the shared border agree.
///
/// What it does:
/// - Computes the neighbor position by offset (dx, dz) on the same floor.
/// - If the neighbor node exists, adds the opposite direction wall flag to it.
///
/// Why this exists in RogueShooter:
/// - Keeps pathfinding data consistent between adjacent nodes.
/// - Prevents "one-way walls," where one node thinks the edge is blocked
///   but its neighbor does not – a common cause of desyncs in tactical grids.
///
/// Implementation notes:
/// - This method assumes edge baking is done in grid order, so each pair
```

RogueShooter – All Scripts

```
/// of adjacent cells will eventually synchronize their shared edge data.
/// </summary>
private void MarkOpposite(GridPosition a, int dx, int dz, EdgeMask oppositeDir)
{
    var b = new GridPosition(a.x + dx, a.z + dz, a.floor);
    if (!IsValidGridPosition(b)) return;

    var nb = PF.GetNode(b.x, b.z, b.floor);
    if (nb == null) return;

    // Add the mirrored wall flag to the neighbor node
    nb.AddWall(oppositeDir);
}

// ----- HELPERS -----
/// <summary>
/// Performs a quick validation before baking begins.
///
/// Checks that references to <see cref="PathFinding"/> and <see cref="LevelGrid"/> are valid,
/// either through serialized fields or automatic runtime lookup.
///
/// Why this exists in RogueShooter:
/// - Prevents null-reference errors during scene startup.
/// - Ensures that the grid and pathfinding systems are fully initialized
///   before attempting any edge scanning or node modification.
///
/// Implementation notes:
/// - Logs descriptive errors to help diagnose missing scene references.
/// - Returns false if any critical dependency is missing, stopping the bake safely.
/// </summary>
private bool Preflight()
{
    if (PF == null)
    {
        Debug.LogError("[EdgeBaker] Pathfinding reference missing (and not found automatically).");
        return false;
    }
    if (LG == null)
    {
        Debug.LogError("[EdgeBaker] LevelGrid reference missing (and not found automatically).");
        return false;
    }
    return true;
}

/// <summary>
/// Determines whether the specified grid position corresponds to a walkable node.
///
/// Why this exists in RogueShooter:
/// - Edge baking should only occur on cells that units can actually occupy.
/// - Avoids unnecessary physics checks for blocked or void cells (improves performance).
///
```

RogueShooter – All Scripts

```
/// Implementation notes:
/// - Fetches the node from PathFinding and queries its <c>GetIsWalkable()</c> flag.
/// </summary>
private bool IsWalkable(GridPosition gp)
{
    var node = PF.GetNode(gp.x, gp.z, gp.floor);
    return node != null && node.GetIsWalkable();
}

/// <summary>
/// Validates that a given grid position exists within the bounds of the level grid.
///
/// Why this exists in RogueShooter:
/// - Edge baking frequently queries neighboring cells ( $\pm 1$  in X/Z).
/// - Ensures that no out-of-range indices are accessed, preventing runtime errors.
///
/// Implementation notes:
/// - Uses LevelGrid's built-in <c>IsValidGridPosition()</c> if available for the current floor.
/// - Falls back to manual bounds checking if no grid system reference is found.
/// </summary>
private bool IsValidGridPosition(GridPosition gp)
{
    var gridSystem = LG.GetGridSystem(gp.floor);
    if (gridSystem != null) return gridSystem.IsValidGridPosition(gp);

    return gp.x >= 0 && gp.z >= 0 && gp.x < Width && gp.z < Height && gp.floor >= 0 && gp.floor < FloorAmount;
}

public void BakeTallWalls()
{
    Debug.Log("[EdgeBaker] Baking TallWall data for LoS checks...");
    var lg = LevelGrid.Instance;
    if (lg == null) return;

    EdgeOcclusion.Clear();

    int w = lg.GetWidth();          // jos nimet eri, vaihda omiin
    int h = lg.GetHeight();
    int floors = lg.GetFloorAmount(); // jos käytössä esim. GetFloorAmount(), vaihda siihen

    float cell = lg.GetCellSize();
    float halfCell = cell * 0.5f;
    float thickness = Math.Max(0.05f, cell * edgeProbeThicknessFactor);
    float halfH = edgeProbeHeight * 0.5f;

    // OverlapBox-extents: N/S (x-suunnassa pitkä), E/W (z-suunnassa pitkä)
    var extN = new UnityEngine.Vector3(halfCell, halfH, thickness * 0.5f);
    var extE = new UnityEngine.Vector3(thickness * 0.5f, halfH, halfCell);

    for (int f = 0; f < floors; f++)
    {
        for (int z = 0; z < h; z++)
```

RogueShooter – All Scripts

```
{
    for (int x = 0; x < w; x++)
    {
        var gp = new GridPosition(x, z, f);
        var basePos = lg.GetWorldPosition(gp);
        float baseY = basePos.y;

        // N-reuna (z+)
        {
            var centerN = basePos + UnityEngine.Vector3.up * halfH + new UnityEngine.Vector3(0f, 0f, halfCell);
            var cols = UnityEngine.Physics.OverlapBox(centerN, extN, UnityEngine.Quaternion.identity, obstaclesMask, UnityEngine.QueryTriggerInteraction.Ignore);

            float maxTopAboveBase = 0f;
            for (int i = 0; i < cols.Length; i++)
            {
                float topRel = cols[i].bounds.max.y - baseY;
                if (topRel > maxTopAboveBase) maxTopAboveBase = topRel;
            }
            if (maxTopAboveBase >= tallWallThresholdY)
                EdgeOcclusion.AddSymmetric(gp, EdgeMask.N);
        }

        // E-reuna (x+)
        {
            var centerE = basePos + UnityEngine.Vector3.up * halfH + new UnityEngine.Vector3(halfCell, 0f, 0f);
            var cols = UnityEngine.Physics.OverlapBox(centerE, extE, UnityEngine.Quaternion.identity, obstaclesMask, UnityEngine.QueryTriggerInteraction.Ignore);

            float maxTopAboveBase = 0f;
            for (int i = 0; i < cols.Length; i++)
            {
                float topRel = cols[i].bounds.max.y - baseY;
                if (topRel > maxTopAboveBase) maxTopAboveBase = topRel;
            }
            if (maxTopAboveBase >= tallWallThresholdY)
                EdgeOcclusion.AddSymmetric(gp, EdgeMask.E);
        }

        // HUOM: S ja W syntyvät symmetrisesti naapurista, joten niitä ei tarvitse skannata erikseen.
    }
}
}
```

RogueShooter – All Scripts

Assets/scripts/CoverSystem/EdgeOcclusion.cs

```
using System;
using System.Collections.Generic;

/// <summary>
/// TallWall-occlusion per ruutu: mitkä reunat (N/E/S/W) ovat "korkeita kapeita seiniä".
/// Tallennetaan vain ruudut joissa on vähintään yksi bitti.
/// </summary>
public static class EdgeOcclusion
{
    private static readonly Dictionary<GridPosition, EdgeMask> _tallWalls = new();

    public static void Clear() => _tallWalls.Clear();

    public static bool HasTallWall(GridPosition cell, EdgeMask side)
    {
        if (!_tallWalls.TryGetValue(cell, out var m)) return false;
        return (m & side) != 0;
    }

    public static void AddSymmetric(GridPosition cell, EdgeMask side)
    {
        // aseta celliin
        if (_tallWalls.TryGetValue(cell, out var m)) _tallWalls[cell] = m | side;
        else _tallWalls[cell] = side;

        // aseta myös naapuriin vastakkaiselle reunalle
        var lg = LevelGrid.Instance;
        if (lg == null) return;

        GridPosition n; EdgeMask opposite;
        switch (side)
        {
            case EdgeMask.N: n = new GridPosition(cell.x, cell.z + 1, cell.floor); opposite = EdgeMask.S; break;
            case EdgeMask.E: n = new GridPosition(cell.x + 1, cell.z, cell.floor); opposite = EdgeMask.W; break;
            case EdgeMask.S: n = new GridPosition(cell.x, cell.z - 1, cell.floor); opposite = EdgeMask.N; break;
            case EdgeMask.W: n = new GridPosition(cell.x - 1, cell.z, cell.floor); opposite = EdgeMask.E; break;
            default: return;
        }
        if (!lg.IsValidGridPosition(n)) return;

        if (_tallWalls.TryGetValue(n, out var nm)) _tallWalls[n] = nm | opposite;
        else _tallWalls[n] = opposite;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/GridDebug/CoverDebugGizmos.cs

```
using UnityEngine;

[ExecuteAlways]
[DisallowMultipleComponent]
public class CoverDebugGizmos : MonoBehaviour
{
    [Header("Refs")]
    [SerializeField] private PathFinding pathfinding;
    [SerializeField] private LevelGrid levelGrid;

    [Header("Filter")]
    [Tooltip("Piirretään vain tämä kerros (floor).")]
    [SerializeField] private int visibleFloor = 0;
    [SerializeField] private bool drawOnlyVisibleFloor = true;

    [Header("What to draw")]
    [SerializeField] private bool drawWalls = true;
    [SerializeField] private bool drawLowCover = true;
    [SerializeField] private bool drawHighCover = true;

    [Header("Style")]
    [SerializeField] private float yOffset = 0.05f; // nosta viivaa vähän lattiasta
    [SerializeField] private float edgeInset = 0.48f; // kuinka lähellä ruudun reunaa (0.5 = ihan reunalla)
    [SerializeField] private float wallThickness = 0.08f;
    [SerializeField] private float coverThickness = 0.05f;
    [SerializeField] private float coverLength = 0.35f; // viivan pituus reunan suuntaisesti

    [Header("Colors")]
    [SerializeField] private Color wallColor = new Color(1f, 0.4f, 0.1f, 0.9f); // oranssi
    [SerializeField] private Color lowColor = new Color(0.2f, 1f, 0.2f, 0.9f); // vihreä
    [SerializeField] private Color highColor = new Color(0.2f, 0.5f, 1f, 0.9f); // sininen

    private PathFinding PF => pathfinding ? pathfinding : (pathfinding = FindFirstObjectByType<PathFinding>());
    private LevelGrid LG => levelGrid ? levelGrid : (levelGrid = LevelGrid.Instance);

    private void OnDrawGizmos()
    {
        if (PF == null || LG == null) return;

        int width = PF.GetWidth();
        int height = PF.GetHeight();
        int floors = LG.GetFloorAmount();
        float s = LG.GetCellSize();

        for (int f = 0; f < floors; f++)
        {
            if (drawOnlyVisibleFloor && f != visibleFloor) continue;

            for (int x = 0; x < width; x++)
                for (int z = 0; z < height; z++)
```

RogueShooter – All Scripts

```
{
    var node = PF.GetNode(x, z, f);
    if (node == null) continue;

    Vector3 c = LG.GetWorldPosition(new GridPosition(x, z, f));
    c.y += yOffset;

    // TESTI: piirrä pieni pallo jos ruudulla on coveria
    if (node.GetHighCoverMask() != 0 || node.GetLowCoverMask() != 0)
    {
        Gizmos.color = Color.cyan;
        Gizmos.DrawSphere(c + Vector3.up * 0.2f, 0.05f);
    }

    // Reunakohdat (keskitettyinä reunoille)
    Vector3 n = c + new Vector3(0, 0, +s * edgeInset);
    Vector3 s_ = c + new Vector3(0, 0, -s * edgeInset);
    Vector3 e = c + new Vector3(+s * edgeInset, 0, 0);
    Vector3 w = c + new Vector3(-s * edgeInset, 0, 0);

    // Seinät
    if (drawWalls)
    {
        Gizmos.color = wallColor;
        if (node.HasWall(EdgeMask.N)) DrawEdgeBar(n, Vector3.right, wallThickness, s * 0.9f);
        if (node.HasWall(EdgeMask.S)) DrawEdgeBar(s_, Vector3.right, wallThickness, s * 0.9f);
        if (node.HasWall(EdgeMask.E)) DrawEdgeBar(e, Vector3.forward, wallThickness, s * 0.9f);
        if (node.HasWall(EdgeMask.W)) DrawEdgeBar(w, Vector3.forward, wallThickness, s * 0.9f);
    }

    // Cover (valinnainen: toimii, jos lisäsit CoverMaskin PathNodeen)
    if (drawLowCover)
    {
        Gizmos.color = lowColor;
        if (node.HasLowCover(CoverMask.N)) DrawEdgeBar(n, Vector3.right, coverThickness, s * coverLength);
        if (node.HasLowCover(CoverMask.S)) DrawEdgeBar(s_, Vector3.right, coverThickness, s * coverLength);
        if (node.HasLowCover(CoverMask.E)) DrawEdgeBar(e, Vector3.forward, coverThickness, s * coverLength);
        if (node.HasLowCover(CoverMask.W)) DrawEdgeBar(w, Vector3.forward, coverThickness, s * coverLength);
    }

    if (drawHighCover)
    {
        Gizmos.color = highColor;
        if (node.HasHighCover(CoverMask.N)) DrawEdgeBar(n + Vector3.up * 0.02f, Vector3.right, coverThickness, s * coverLength);
        if (node.HasHighCover(CoverMask.S)) DrawEdgeBar(s_ + Vector3.up * 0.02f, Vector3.right, coverThickness, s * coverLength);
        if (node.HasHighCover(CoverMask.E)) DrawEdgeBar(e + Vector3.up * 0.02f, Vector3.forward, coverThickness, s * coverLength);
        if (node.HasHighCover(CoverMask.W)) DrawEdgeBar(w + Vector3.up * 0.02f, Vector3.forward, coverThickness, s * coverLength);
    }
}
}
```

RogueShooter – All Scripts

```
// Piirtää "paksun viivan" reunan suuntaisesti pienenä laatikkona
private void DrawEdgeBar(Vector3 center, Vector3 along, float thickness, float length)
{
    // along = joko Vector3.right (itä-länsi) tai Vector3.forward (pohjois-etelä)
    Vector3 size = new Vector3(
        Mathf.Abs(along.x) > 0 ? length : thickness,
        thickness,
        Mathf.Abs(along.z) > 0 ? length : thickness
    );
    Gizmos.DrawCube(center, size);
}
```


RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/GridDebug/GridDebugObject.cs

```
using UnityEngine;
using TMPro;

// <summary>
// This script is used to display the grid object information in the scene view.
// </summary>
public class GridDebugObject : MonoBehaviour
{
    [SerializeField] private TextMeshPro textMeshPro;

    private object gridObject;
    public virtual void SetGridObject(object gridObject)
    {
        this.gridObject = gridObject;
    }
    protected virtual void Update()
    {
        textMeshPro.text = gridObject.ToString();
    }
}
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/GridDebug/PathFindingDebugGridObject.cs

```
using TMPro;
using UnityEngine;

public class PathFindingDebugGridObject : GridDebugObject
{
    [SerializeField] private TextMeshPro gCostText;
    [SerializeField] private TextMeshPro hCostText;
    [SerializeField] private TextMeshPro fCostText;

    [SerializeField] private SpriteRenderer isWalkableSpriteRenderer;

    private PathNode pathNode;
    public override void SetGridObject(object gridObject)
    {
        base.SetGridObject(gridObject);
        pathNode = (PathNode)gridObject;
    }

    protected override void Update()
    {
        base.Update();
        gCostText.text = pathNode.GetGCost().ToString();
        hCostText.text = pathNode.GetHCost().ToString();
        fCostText.text = pathNode.GetFCost().ToString();
        isWalkableSpriteRenderer.color = pathNode.GetIsWalkable() ? Color.green : Color.red;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/PathfindingDebug/PathDiagHotkey.cs

```
using UnityEngine;

public class PathDiagHotkey : MonoBehaviour
{
    public KeyCode dumpKey = KeyCode.O;
    public KeyCode resetKey = KeyCode.P;

    void Update()
    {
        var diag = PathfindingDiagnostics.Instance;
        if (diag == null) return;

        if (Input.GetKeyDown(dumpKey))
        {
            Debug.Log(
                $"[PathDiag] Samples={diag.SamplesCount} | Avg={diag.AvgMs:F3} ms | P50={diag.P50Ms:F3} ms | P95={diag.P95Ms:F3} ms | Calls={diag.CallsTotal} | OK={diag.SuccessesTotal} | Fail={diag.FailuresTotal}"
            );
        }

        if (Input.GetKeyDown(resetKey))
        {
            diag.ResetStats();
            Debug.Log("[PathDiag] Reset");
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/PathfindingDebug/PathfindingDiagnostics.cs

```
#if PERFORMANCE_DIAG

using System;
using System.Collections.Generic;
using UnityEngine;

[DefaultExecutionOrder(-10000)]
public class PathfindingDiagnostics : MonoBehaviour
{
    public static PathfindingDiagnostics Instance { get; private set; }

    [Header("On/Off")]
    public bool enabledRuntime = false;    // kytkin pelissä

    [Header("Window")]
    public int windowSize = 200;          // montako viimeisintä mittausta pidetään

    // Näkyvät lukemat
    public int SamplesCount => samples.Count;
    public double AvgMs { get; private set; }
    public double P95Ms { get; private set; }
    public double P50Ms { get; private set; } // mediaani
    public int CallsTotal { get; private set; }
    public int SuccessesTotal { get; private set; }
    public int FailuresTotal => CallsTotal - SuccessesTotal;

    struct Sample { public double ms; public bool success; public int pathLen; public int expanded; }
    readonly Queue<Sample> samples = new Queue<Sample>();

    void Awake()
    {
        if (Instance != null) { Destroy(gameObject); return; }
        Instance = this;
        DontDestroyOnLoad(gameObject);
    }

    public void AddSample(double ms, bool success, int pathLen, int expanded)
    {
        if (!enabledRuntime) return;

        CallsTotal++;
        if (success) SuccessesTotal++;

        samples.Enqueue(new Sample { ms = ms, success = success, pathLen = pathLen, expanded = expanded });
        while (samples.Count > windowSize) samples.Dequeue();

        RecomputeStats();
    }

    void RecomputeStats()

```

RogueShooter – All Scripts

```
{
    if (samples.Count == 0)
    {
        AvgMs = P95Ms = P50Ms = 0;
        return;
    }

    double sum = 0;
    List<double> arr = new List<double>(samples.Count);
    foreach (var s in samples) { sum += s.ms; arr.Add(s.ms); }

    arr.Sort();
    AvgMs = sum / samples.Count;
    P50Ms = Percentile(arr, 0.50);
    P95Ms = Percentile(arr, 0.95);
}

static double Percentile(List<double> sorted, double p)
{
    if (sorted.Count == 0) return 0;
    double idx = (sorted.Count - 1) * p;
    int lo = (int)Math.Floor(idx);
    int hi = (int)Math.Ceiling(idx);
    if (lo == hi) return sorted[lo];
    double w = idx - lo;
    return sorted[lo] * (1 - w) + sorted[hi] * w;
}

// Helppo nollaus napista
public void ResetStats()
{
    samples.Clear();
    CallsTotal = 0;
    SuccessesTotal = 0;
    AvgMs = P95Ms = P50Ms = 0;
}
}

#else

using UnityEngine;

// Stubbi, joka kääntyy release-buildiin mutta ei tee mitään
public class PathfindingDiagnostics : MonoBehaviour
{
    public static PathfindingDiagnostics Instance => null;
    public bool enabledRuntime => false;
    public void AddSample(double ms, bool success, int pathLen, int expanded) { }
    public void ResetStats() { }
}

#endif
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/ScreenLogger.cs

```
using UnityEngine;
using TMPro;
using System.Collections.Generic;

public class ScreenLogger : MonoBehaviour
{
    static ScreenLogger inst;
    TextMeshProUGUI text;
    readonly Queue<string> lines = new Queue<string>();
    [Range(1,100)] public int maxLines = 100;

    void Awake()
    {
        if (inst != null) { Destroy(gameObject); return; }
        inst = this;
        DontDestroyOnLoad(gameObject);

        // Canvas
        var canvasGO = new GameObject("ScreenLogCanvas");
        var canvas = canvasGO.AddComponent<Canvas>();
        canvas.renderMode = RenderMode.ScreenSpaceOverlay;
        canvas.sortingOrder = 9999;

        // Text
        var tgo = new GameObject("Log");
        tgo.transform.SetParent(canvasGO.transform);
        var rt = tgo.AddComponent<RectTransform>();
        rt.anchorMin = new Vector2(0, 0);
        rt.anchorMax = new Vector2(1, 0);
        rt.pivot = new Vector2(0.5f, 0);
        rt.offsetMin = new Vector2(10, 10);
        rt.offsetMax = new Vector2(-10, 210);

        text = tgo.AddComponent<TextMeshProUGUI>();
        text.fontSize = 18;
        text.textWrappingMode = TextWrappingModes.NoWrap;

        Application.logMessageReceived += HandleLog;
    }

    void OnDestroy() { Application.logMessageReceived -= HandleLog; }

    void HandleLog(string msg, string stack, LogType type)
    {
        string prefix = type == LogType.Error || type == LogType.Exception ? "[ERR]" :
            type == LogType.Warning ? "[WARN]" : "[LOG]";
        lines.Enqueue($"{System.DateTime.Now:HH:mm:ss} {prefix} {msg}");
        while (lines.Count > maxLines) lines.Dequeue();
        if (text != null) text.text = string.Join("\n", lines);
    }
}
```

```
}
```

RogueShooter – All Scripts

Assets/scripts/DebuggingAndTesting/Testing.cs

```
using System.Collections.Generic;
using UnityEngine;

/// <summary>
/// This class is responsible for testing the grid system and unit actions in the game.
/// It provides functionality to visualize the grid positions and interact with unit actions.
/// </summary>
public class Testing : MonoBehaviour
{
    [SerializeField] private Unit unit;
    private void Start()
    {
    }

    private void Update()
    {
        if (Input.GetKeyDown(KeyCode.T))
        {
            // ScreenShake.Instance.Shake(5f);

            // ScreenShake.Instance.RecoilCameraShake();

            //Show pathfind line
            /*
            GridPosition mouseGridPosition = LevelGrid.Instance.GetGridPosition(MouseWorld.GetMouseWorldPosition());
            GridPosition startGridPosition = new GridPosition(0, 0, 0);

            List<GridPosition> gridPositionList = PathFinding.Instance.FindPath(startGridPosition, startGridPosition, out int pathLeght, 6);

            for (int i = 0; i < gridPositionList.Count - 1; i++)
            {
                Debug.DrawLine(
                    LevelGrid.Instance.GetWorldPosition(gridPositionList[i]),
                    LevelGrid.Instance.GetWorldPosition(gridPositionList[i + 1]),
                    Color.white,
                    10f
                );
            }
            */

            /*
            //Resetoi pelin alkamaan alusta.
            if (Input.GetKeyDown(KeyCode.R))
            {
                if (Mirror.NetworkServer.active) {
```


RogueShooter – All Scripts

```
        ResetService.Instance.HardResetServerAuthoritative();
    } else if (Mirror.NetworkClient.active) {
        // käskytä serveriä
        ResetService.Instance.CmdRequestHardReset();
    } else {
        GameReset.HardReloadSceneKeepMode();
    }
}
*/
}
}
```

RogueShooter – All Scripts

Assets/scripts/Editor/PathfindingLinkMonoBehaviourEditor.cs

```
using System.Collections;
using System.Collections.Generic;
using UnityEngine;
using UnityEditor;
[CustomEditor(typeof(PathfindingLinkMonoBehaviour))]
public class PathfindingLinkMonoBehaviourEditor : Editor
{
    private void OnSceneGUI()
    {
        var m = (PathfindingLinkMonoBehaviour)target;
        var t = m.transform;

        // Local -> World kahvoille
        Vector3 aW = t.TransformPoint(m.linkPositionA);
        Vector3 bW = t.TransformPoint(m.linkPositionB);

        EditorGUI.BeginChangeCheck();
        Vector3 naW = Handles.PositionHandle(aW, Quaternion.identity);
        Vector3 nbW = Handles.PositionHandle(bW, Quaternion.identity);
        if (EditorGUI.EndChangeCheck())
        {
            Undo.RecordObject(m, "Change Link Position");
            // World -> Local talteen
            m.linkPositionA = t.InverseTransformPoint(naW);
            m.linkPositionB = t.InverseTransformPoint(nbW);
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Editor/UnusedMonoBehavioursReporter.cs

```
#if UNITY_EDITOR
using System;
using System.Collections.Generic;
using System.Diagnostics;
using System.IO;
using System.Linq;
using UnityEditor;
using UnityEditor.SceneManagement;
using UnityEngine;

namespace RogueShooter.Tools
{
    /// <summary>
    /// Reports MonoBehaviour scripts that do not appear in any prefab or scene dependencies.
    /// Limitations:
    /// - Does NOT detect scripts that are only added at runtime via AddComponent/Reflection.
    /// - Excludes scripts under any *Editor* folder by default.
    /// - Skips abstract classes and classes that don't inherit MonoBehaviour.
    /// - Prefabs & scenes outside the current project (Packages, external) are not scanned.
    /// </summary>
    public class UnusedMonoBehavioursReporter : EditorWindow
    {
        private const string ScanRoot = "Assets/Scripts";

        [MenuItem("Tools/RogueShooter/Report Unused MonoBehaviours")]
        public static void Open()
        {
            var win = GetWindow<UnusedMonoBehavioursReporter>(true, "Unused MonoBehaviours Report", true);
            win.minSize = new Vector2(820, 480);
            win.RefreshScan();
        }

        private Vector2 _scroll;
        private string _search = string.Empty;
        private bool _includeEditorFolderScripts = false; // Usually false; keep Editor scripts out
        private bool _showUsedAlso = false;

        private List<ScriptInfo> _allCandidates = new(); // All MonoBehaviour scripts in project (filtered)
        private HashSet<string> _usedScriptPaths = new(StringComparer.OrdinalIgnoreCase); // .cs paths used by scenes/prefabs
        private List<ScriptInfo> _unused = new(); // Candidates not referenced by any scene/prefab
        private List<ScriptInfo> _used = new(); // Candidates referenced
        private string _status = "";
        private double _elapsedMs;

        private class ScriptInfo
        {
            public MonoScript Mono;
            public Type Type;
            public string Path;
        }
    }
}
```

RogueShooter – All Scripts

```
    public string AssemblyName;
    public bool IsAbstract;
    public bool InEditorFolder;
}

private void OnGUI()
{
    GUILayout.Space(6);

    using (new EditorGUILayout.HorizontalScope())
    {
        _includeEditorFolderScripts = GUILayout.Toggle(_includeEditorFolderScripts, new GUIContent("Include /Editor scripts"), GUILayout.Width(170));
        _showUsedAlso = GUILayout.Toggle(_showUsedAlso, new GUIContent("Show used scripts too"), GUILayout.Width(170));
        GUILayout.Space(12);

        GUILayout.Label("Search:", GUILayout.Width(48));
        _search = GUILayout.TextField(_search ?? string.Empty);
        GUILayout.FlexibleSpace();

        if (GUILayout.Button("Refresh", GUILayout.Width(100)))
            RefreshScan();

        if (GUILayout.Button("Export CSV...", GUILayout.Width(120)))
            ExportCsv();
    }

    GUILayout.Space(4);
    EditorGUILayout.LabelField($"Scan root: {ScanRoot}");
    EditorGUILayout.HelpBox("Lists MonoBehaviour scripts that are NOT referenced by any prefab or scene in this project. " +
        "Dynamic AddComponent() usage will not be detected.", MessageType.Info);

    if (!string.IsNullOrEmpty(_status))
        EditorGUILayout.LabelField(_status);
    EditorGUILayout.LabelField($"Scanned in {_elapsedMs:F0} ms | Candidates: {_allCandidates.Count} | Used: {_used.Count} | Unused: {_unused.Count}");

    GUILayout.Space(6);

    using (var scroll = new EditorGUILayout.ScrollViewScope(_scroll))
    {
        _scroll = scroll.scrollPosition;

        DrawTableHeader();
        DrawList(_unused, title: "UNUSED SCRIPTS", color: new Color(1f, 0.5f, 0.5f));
        if (_showUsedAlso)
        {
            GUILayout.Space(6);
            DrawList(_used, title: "USED SCRIPTS", color: new Color(0.65f, 0.9f, 0.65f));
        }
    }
}

private void DrawTableHeader()
```

RogueShooter – All Scripts

```
{
    var rect = GUILayoutUtility.GetRect(10, 24, GUILayout.ExpandWidth(true));
    EditorGUI.DrawRect(rect, new Color(0.18f, 0.18f, 0.18f));
    var r = rect; r.x += 6; r.width -= 12; r.y += 3;
    GUI.Label(r, "Name | Namespace | Assembly | Path");
}

private void DrawList(List<ScriptInfo> list, string title, Color color)
{
    var shown = ApplySearch(list);

    var head = GUILayoutUtility.GetRect(10, 24, GUILayout.ExpandWidth(true));
    EditorGUI.DrawRect(head, color);
    var hr = head; hr.x += 6; hr.width -= 12; hr.y += 3;
    GUI.Label(hr, $"{title} ({shown.Count})");

    foreach (var s in shown)
    {
        var row = GUILayoutUtility.GetRect(10, 22, GUILayout.ExpandWidth(true));
        if (Event.current.type == EventType.MouseDown && row.Contains(Event.current.mousePosition))
        {
            Selection.activeObject = s.Mono; // select asset
            EditorGUIUtility.PingObject(s.Mono);
            Repaint();
        }

        EditorGUI.DrawRect(row, new Color(0.12f, 0.12f, 0.12f));
        var rr = row; rr.x += 6; rr.width -= 12; rr.y += 2;
        var name = s.Type != null ? s.Type.Name : Path.GetFileNameWithoutExtension(s.Path);
        var ns = s.Type != null ? (string.IsNullOrEmpty(s.Type.Namespace) ? "-" : s.Type.Namespace) : "-";
        var asm = s.AssemblyName ?? "-";
        GUI.Label(rr, $"{name} | {ns} | {asm} | {s.Path}");
    }
}

private List<ScriptInfo> ApplySearch(List<ScriptInfo> src)
{
    if (string.IsNullOrEmpty(_search)) return src;
    var q = _search.Trim();
    return src.Where(s =>
        (s.Type != null && (s.Type.Name.IndexOf(q, StringComparison.OrdinalIgnoreCase) >= 0 ||
            (!string.IsNullOrEmpty(s.Type.Namespace) && s.Type.Namespace.IndexOf(q, StringComparison.OrdinalIgnoreCase) >= 0)))
        || (!string.IsNullOrEmpty(s.Path) && s.Path.IndexOf(q, StringComparison.OrdinalIgnoreCase) >= 0)
    ).ToList();
}

private static bool IsUnderRoot(string assetPath)
{
    return !string.IsNullOrEmpty(assetPath) && assetPath.StartsWith(ScanRoot, StringComparison.OrdinalIgnoreCase);
}

private void RefreshScan()
```

RogueShooter – All Scripts

```
{
    try
    {
        EditorUtility.DisplayProgressBar("Scanning", "Collecting scripts...", 0f);
        var sw = Stopwatch.StartNew();

        _allCandidates = CollectCandidateScripts(_includeEditorFolderScripts);

        EditorUtility.DisplayProgressBar("Scanning", "Collecting prefab/scene dependencies...", 0.33f);
        _usedScriptPaths = CollectUsedScriptPaths();

        EditorUtility.DisplayProgressBar("Scanning", "Comparing...", 0.66f);
        _unused = new List<ScriptInfo>();
        _used = new List<ScriptInfo>();

        foreach (var s in _allCandidates)
        {
            if (_usedScriptPaths.Contains(s.Path)) _used.Add(s);
            else _unused.Add(s);
        }

        sw.Stop();
        _elapsedMs = sw.Elapsed.TotalMilliseconds;
        _status = $"Found {_unused.Count} potentially unused MonoBehaviour scripts.";
    }
    catch (Exception e)
    {
        UnityEngine.Debug.LogError($"[UnusedMonoBehavioursReporter] Scan failed: {e}\n{e.StackTrace}");
        _status = "Scan failed – see Console.";
    }
    finally
    {
        EditorUtility.ClearProgressBar();
        Repaint();
    }
}

private static List<ScriptInfo> CollectCandidateScripts(bool includeEditorFolder)
{
    var results = new List<ScriptInfo>();
    var guids = AssetDatabase.FindAssets("t:MonoScript");

    for (int i = 0; i < guids.Length; i++)
    {
        if (i % 200 == 0)
            EditorUtility.DisplayProgressBar("Scanning", $"Inspecting scripts ({i}/{guids.Length})...", Mathf.InverseLerp(0, guids.Length, i));

        var path = AssetDatabase.GUIDToAssetPath(guids[i]);
        if (string.IsNullOrEmpty(path) || !IsUnderRoot(path)) continue;
        var mono = AssetDatabase.LoadAssetAtPath<MonoScript>(path);
        if (mono == null) continue;
    }
}
```

RogueShooter – All Scripts

```
var type = mono.GetClass();
if (type == null) continue; // no class in file or compile error

if (!typeof(MonoBehaviour).IsAssignableFrom(type))
    continue; // not a MonoBehaviour

if (type.IsAbstract)
    continue; // we report only concrete components

var inEditorFolder = path.Split('/')
    .Any(seg => string.Equals(seg, "Editor", StringComparison.OrdinalIgnoreCase));
if (inEditorFolder && !includeEditorFolder)
    continue; // ignore Editor scripts unless explicitly included

var asmName = type.Assembly?.GetName().Name;

results.Add(new ScriptInfo
{
    Mono = mono,
    Type = type,
    Path = path,
    AssemblyName = asmName,
    IsAbstract = false,
    InEditorFolder = inEditorFolder,
});
}

return results;
}

private static HashSet<string> CollectUsedScriptPaths()
{
    var used = new HashSet<string>(StringComparer.OrdinalIgnoreCase);

    // Gather all prefab & scene asset paths
    var prefabGuids = AssetDatabase.FindAssets("t:Prefab");
    var sceneGuids = AssetDatabase.FindAssets("t:Scene");

    // Unity's dependency graph: scenes/prefabs depend on MonoScript assets referenced by m_Script
    void Accumulate(string guid, int index, int total, string label)
    {
        if (index % 100 == 0)
            EditorUtility.DisplayProgressBar("Scanning", $"{label} ({index}/{total})...", Mathf.InverseLerp(0, total, index));

        var path = AssetDatabase.GUIDToAssetPath(guid);
        if (string.IsNullOrEmpty(path)) return;

        var deps = AssetDatabase.GetDependencies(path, true);
        foreach (var d in deps)
        {
            if (d.EndsWith(".cs", StringComparison.OrdinalIgnoreCase))
                used.Add(d);
        }
    }
}
```

RogueShooter – All Scripts

```
    }
}

for (int i = 0; i < prefabGuids.Length; i++)
    Accumulate(prefabGuids[i], i, prefabGuids.Length, "Scanning prefabs");

for (int i = 0; i < sceneGuids.Length; i++)
    Accumulate(sceneGuids[i], i, sceneGuids.Length, "Scanning scenes");

return used;
}

private void ExportCsv()
{
    try
    {
        var path = EditorUtility.SaveFilePanelInProject("Export CSV", "UnusedMonoBehaviours.csv", "csv", "Select save location");
        if (string.IsNullOrEmpty(path)) return;

        var lines = new List<string> { "Name,Namespace,Assembly,AssetPath" };
        foreach (var s in ApplySearch(_unused))
        {
            var name = s.Type != null ? s.Type.Name : Path.GetFileNameWithoutExtension(s.Path);
            var ns = s.Type != null ? (s.Type.Namespace ?? string.Empty) : string.Empty;
            var asm = s.AssemblyName ?? string.Empty;

            string Escape(string x) => "'" + (x?.Replace("\\", "\\\"") ?? string.Empty) + "'";
            lines.Add(string.Join(",", new[] { Escape(name), Escape(ns), Escape(asm), Escape(s.Path) }));
        }

        File.WriteAllLines(path, lines);
        AssetDatabase.ImportAsset(path);
        EditorUtility.RevealInFinder(path);
    }
    catch (Exception e)
    {
        UnityEngine.Debug.LogError($"[UnusedMonoBehavioursReporter] Export failed: {e}");
        EditorUtility.DisplayDialog("Export CSV", "Export failed. See Console.", "OK");
    }
}
}

#endif
```


RogueShooter – All Scripts

Assets/scripts/Enemy/EnemyAI.cs

```
using System;
using System.Collections;
using UnityEngine;
using Utp;

/// <summary>
/// Control EnemyAI. Go through all possible actions what current enemy Unit can do and chose the best one.
/// Listen to TurnSystem and when turn OnTurnChanged, AI state switch WaitingForEnemyTurn to the TakingTurn state
/// and try to find best action to all enemy Units. All enemy Unit do this independently based on
/// action values.
/// </summary>
public class EnemyAI : MonoBehaviour
{
    public static EnemyAI Instance { get; private set; }

    private enum State
    {
        WaitingForEnemyTurn,
        TakingTurn,
        Busy,
    }

    private State state;
    private float timer;

    void Awake()
    {
        state = State.WaitingForEnemyTurn;

        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;
    }

    private void Start()
    {
        if (GameManager.SelectedMode == GameMode.SinglePlayer)
        {
            TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
        }

        if (GameNetworkManager.Instance != null &&
            GameNetworkManager.Instance.GetNetworkClientConnected() &&
            !GameNetworkManager.Instance.GetNetworkServerActive())
        {
            // Coop gamemode using IEnumerator RunEnemyTurnCoroutine() through the server. No local calls
            if (GameManager.SelectedMode == GameMode.CoOp)
                enabled = false;
        }
    }
}
```

RogueShooter – All Scripts

```
}

void OnDisable()
{
    if (GameManager.SelectedMode == GameMode.SinglePlayer)
    {
        TurnSystem.Instance.OnTurnChanged -= TurnSystem_OnTurnChanged;
    }
}

private void Update()
{
    //NOTE! Only solo game!
    if (GameManager.SelectedMode != GameMode.SinglePlayer) return;
    if (TurnSystem.Instance.IsPlayerTurn()) return;

    //If game mode is SinglePlayer and is not PlayerTurn then runs Enemy AI.
    EnemyAITick(Time.deltaTime);
}

/// <summary>
/// Enemy start taking actions after small waiting time.
/// Update call this every frame.
/// </summary>
private bool EnemyAITick(float dt)
{
    switch (state)
    {
        // It is Player turn so keep waiting untill TurnSystem_OnTurnChanged switch state to TakingTurn.
        case State.WaitingForEnemyTurn:
            return false;

        case State.TakingTurn:
            timer -= dt;
            if (timer <= 0f)
            {
                //Return false when all Enemy Units have make they actions
                if (SelectEnemyUnitToTakeAction(SetStateTakingTurn))
                {
                    state = State.Busy;
                    return false;
                }
            }
            else
            {
                // If enemy cant make actions. Return turn back to player.
                // NOTE! In Coop mode CoopTurnCoordinator make this.
                if (GameManager.SelectedMode == GameMode.SinglePlayer)
                {
                    TurnSystem.Instance.NextTurn();
                }

                // Enemy AI switch back to waiting.
            }
        }
    }
}
```

RogueShooter – All Scripts

```
        state = State.WaitingForEnemyTurn;
        return true;
    }
}
return false;

case State.Busy:
    // When Enemy doing action just return.
    // Waiting c# Action call from base action and then call funktion SetStateTakingTurn()
    return false;
}
return false;
}

/// <summary>
/// c# Action callback. SelectEnemyUnitToTakeAction use this and when action is ready. This occurs
/// </summary>
private void SetStateTakingTurn()
{
    timer = 0.5f;
    state = State.TakingTurn;
}

/// <summary>
/// Go through all enemy Units on EnemyUnit List and try to take action.
/// </summary>
private bool SelectEnemyUnitToTakeAction(Action onEnemyAIActionComplete)
{
    foreach (Unit enemyUnit in UnitManager.Instance.GetEnemyUnitList())
    {
        if (enemyUnit == null)
        {
            Debug.LogWarning("[EnemyAI][UnitManager]EnemyUnit list is null:" + enemyUnit);
            continue;
        }
        if (TryTakeEnemyAIAction(enemyUnit, onEnemyAIActionComplete))
        {
            return true;
        }
    }

    return false;
}

/// <summary>
/// Selected Unit Go through all possible actions what Enemy Unit can do
/// and choosing the best one based on them action value.
/// Then make action if have enough action points.
/// </summary>
private bool TryTakeEnemyAIAction(Unit enemyUnit, Action onEnemyAIActionComplete)
{

```

RogueShooter – All Scripts

```
// Contains Gridposition and action value (How good action is)
EnemyAIAction bestEnemyAIAction = null;

BaseAction bestBaseAction = null;

// Choosing the best action, based on them action value.
foreach (BaseAction baseAction in enemyUnit.GetBaseActionsArray())
{
    if (!enemyUnit.CanSpendActionPointsToTakeAction(baseAction))
    {
        // Enemy cannot afford this action.
        continue;
    }

    if (bestEnemyAIAction == null)
    {
        bestEnemyAIAction = baseAction.GetBestEnemyAIAction();
        bestBaseAction = baseAction;
    }
    else
    {
        // Go trough all actions and take the best one.
        EnemyAIAction testEnemyAIAction = baseAction.GetBestEnemyAIAction();
        if (testEnemyAIAction != null && testEnemyAIAction.actionValue > bestEnemyAIAction.actionValue)
        {
            bestEnemyAIAction = baseAction.GetBestEnemyAIAction();
            bestBaseAction = baseAction;
        }
    }
}

// Try to take action
if (bestEnemyAIAction != null && enemyUnit.TrySpendActionPointsToTakeAction(bestBaseAction))
{
    bestBaseAction.TakeAction(bestEnemyAIAction.gridPosition, onEnemyAIActionComplete);
    return true;
}
else
{
    return false;
}
}

/// <summary>
/// When turn changed. Switch state to taking turn and enemy turn start.
/// </summary>
private void TurnSystem_OnTurnChanged(object sender, EventArgs e)
{
    if (!TurnSystem.Instance.IsPlayerTurn())
    {
        state = State.TakingTurn;
        timer = 1f; // Small holding time before action.
    }
}
```

RogueShooter – All Scripts

```
    }  
}  
  
/// <summary>  
/// When playing online: (Coop mode) Server handle All AI actions.  
/// </summary>  
[Mirror.Server]  
public IEnumerator RunEnemyTurnCoroutine()  
{  
  
    SetStateTakingTurn();  
  
    while (true)  
    {  
        if (TurnSystem.Instance.IsPlayerTurn())  
        {  
            Debug.LogWarning("[EnemyAI] Players get turn before AI has ended own turn! This sould not be possibble");  
            yield break;  
        }  
  
        bool finished = EnemyAITick(Time.deltaTime);  
        if (finished)  
            yield break; // AI-Turn ready. CoopTurnCoordinator continue and give turn back to players.  
  
        yield return null; // wait one frame.  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/Enemy/EnemyAIAction.cs

```
using UnityEngine;

[System.Serializable]
public class EnemyAIAction
{
    public GridPosition gridPosition;
    public int actionValue;
}
```

RogueShooter – All Scripts

Assets/scripts/GameBalance/GameBalance.cs

```
using UnityEngine;

[DefaultExecutionOrder(-1000)]
public class GameBalance : MonoBehaviour {
    public static GameBalance I { get; private set; }
    [SerializeField] CombatRanges ranges;
    public static CombatRanges R => I ? I.ranges : null;

    void Awake() {
        if (I && I != this) { Destroy(gameObject); return; }
        I = this;
        DontDestroyOnLoad(gameObject);
        if (ranges == null)
            Debug.LogWarning("GameBalance.ranges puuttuu – käytetään Resources-fallbackia jos saatavilla.");
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/BattleLogic/TurnSystem.cs

```
using System;
using System.Collections.Generic;
//using Mirror;
using UnityEngine;

public class TurnSystem : MonoBehaviour
{
    public static TurnSystem Instance { get; private set; }
    public Team CurrentTeam { get; set; } = Team.Player;
    public int TurnId { get; set; } = 0;

    public event Action<Team,int> OnTurnStarted;
    public event Action<Team,int> OnTurnEnded;

    public event EventHandler OnTurnChanged;
    private int turnNumber = 1;
    private bool isPlayerTurn = true;

    private void Awake()
    {
        // Ensure that there is only one instance in the scene
        if (Instance != null)
        {
            Debug.LogError(" More than one TurnSystem in the scene!" + transform + " " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;
    }

    private void Start()
    {
        OnTurnChanged += turnSystem_OnTurnChanged;
        // Ensimmäinen vuoro.
        OnTurnStarted?.Invoke(CurrentTeam, TurnId);
        // Varmista, että alkutila lähetetään kaikille UI:lle
        PlayerLocalTurnGate.Set(isPlayerTurn); // true = Player turn alussa
        OnTurnChanged?.Invoke(this, EventArgs.Empty); // jos haluat myös muut UI:t liikkeelle
    }

    private void OnDisable()
    {
        OnTurnChanged -= turnSystem_OnTurnChanged;
    }

    private void turnSystem_OnTurnChanged(object sender, EventArgs e)
    {
        GridSystemVisual.Instance.HideAllGridPositions();
        UnitActionSystem.Instance.ResetSelectedAction();
    }
}
```


RogueShooter – All Scripts

```
        UnitActionSystem.Instance.ResetSelectedUnit();
    }

    public void NextTurn()
    {
        Debug.Log($"[TurnSystem] NextTurn(): end={CurrentTeam}, id={TurnId}");
        if (GameManager.SelectedMode != GameMode.SinglePlayer && !NetMode.IsOnline) // !NetworkServer.active
        {
            Debug.LogWarning("Client yritti kääntää vuoroa lokaalisti, ignoroidaan.");
            return;
        }

        OnTurnEnded?.Invoke(CurrentTeam, TurnId);
        CurrentTeam = (CurrentTeam == Team.Player) ? Team.Enemy : Team.Player;
        TurnId++;
        OnTurnStarted?.Invoke(CurrentTeam, TurnId);

        if (GameManager.SelectedMode == GameMode.SinglePlayer)
        {
            turnNumber++;
            isPlayerTurn = !isPlayerTurn;
            OnTurnChanged?.Invoke(this, EventArgs.Empty);
            PlayerLocalTurnGate.Set(isPlayerTurn);
        }
        else if (GameManager.SelectedMode == GameMode.CoOp)
        {
            Debug.Log("Co-Op mode: Proceeding to the next turn.");
        }
        else if (GameManager.SelectedMode == GameMode.Versus)
        {
            Debug.Log("Versus mode: Proceeding to the next turn.");
        }
    }

    public void ForcePhase(bool isPlayerTurn, bool incrementTurnNumber)
    {
        if (incrementTurnNumber) turnNumber++;

        if (NetMode.IsOnline && isPlayerTurn) // NetworkServer.active
        {
            ConvertUnusedActionPointsToCoverPoints();
        }

        this.isPlayerTurn = isPlayerTurn;
        OnTurnChanged?.Invoke(this, EventArgs.Empty);
    }

    public void SetHudFromNetwork(int newTurnNumber, bool isPlayersPhase)
    {
        turnNumber = newTurnNumber;
```

RogueShooter – All Scripts

```
        isPlayerTurn = isPlayersPhase;
        OnTurnChanged?.Invoke(this, EventArgs.Empty);
    }

    private void ConvertUnusedActionPointsToCoverPoints()
    {
        Debug.Log("Konvertoidaan käyttämättömät pisteet coveriksi");
        List<Unit> ownUnits = UnitManager.Instance.GetFriendlyUnitList();
        for (int i = 0; i < ownUnits.Count; i++)
        {
            Unit u = ownUnits[i];
            int ap = u.GetActionPoints();
            if (ap <= 0) continue;
            int per = u.GetCoverRegenPerUnusedAP();
            u.RegenCoverBy(ap * per);
        }
    }

    public int GetTurnNumber()
    {
        return turnNumber;
    }

    public void ResetTurnNumber()
    {
        turnNumber = 1;
    }

    public void ResetTurnId()
    {
        TurnId = 0;
    }

    public bool IsPlayerTurn()
    {
        return isPlayerTurn;
    }

    public bool IsUnitsTurn(Unit u) => u.Team == CurrentTeam;

    /// <summary>
    /// Offline/SP: nollaa paikallisen vuorotilan ja aloittaa alusta.
    /// Kutsu tätä heti, kun yksiköt on spawnattu uudelleen level-reloadin jälkeen.
    /// </summary>
    /// <param name="resetTurnNumber">Asetetaanko turnNumber takaisin 1:een.</param>
    /// <param name="playersPhase">Aloitetaanko Players-vaiheesta (yleensä true).</param>
    public void ResetAndBegin(bool resetTurnNumber = true, bool playersPhase = true)
    {
        // Online-tilassa varoitetaan: online-reset hoidetaan NetTurnManagerin kautta
        if (GameModeManager.SelectedMode != GameMode.SinglePlayer && Mirror.NetworkServer.active)
        {
            Debug.LogWarning("[TurnSystem] ResetAndBegin() on offline/SP-apu. Verkossa käytä NetTurnManager.ServerResetAndBegin().");
        }
    }
}
```

RogueShooter – All Scripts

```
}

// Nollaa paikalliset laskurit/tila
if (resetTurnNumber) turnNumber = 1;

// UI-/SP-luupin peruskentät
CurrentTeam = playersPhase ? Team.Player : Team.Enemy;
TurnId = 0; // sisäinen vaihtolaskuri, alkaa alusta
var wasPlayerTurn = IsPlayerTurn();

// Päivitä "onko pelaajan vuoro" -portti ja kerro UI:lle
ForcePhase(isPlayerTurn: playersPhase, incrementTurnNumber: false); // kutsuu OnTurnChanged, käyttää nykyistä logiikkaasi
PlayerLocalTurnGate.Set(playersPhase); // HUD/input-portti heti oikein

// Ilmoita uuden vuoron alkamisesta niille, jotka kuuntelevat OnTurnStarted
OnTurnStarted?.Invoke(CurrentTeam, TurnId);

// Jos haluat täydellisen synkan HUDissa, voit vielä varmistaa:
// SetHudFromNetwork(turnNumber, playersPhase);
}

public void BeginPlayersTurn(bool incrementTurnId)
{
    if (incrementTurnId) TurnId++;
    CurrentTeam = Team.Player;
    OnTurnStarted?.Invoke(CurrentTeam, TurnId);
    ForcePhase(isPlayerTurn: true, incrementTurnNumber: false);
}

public void BeginEnemyTurn(bool incrementTurnId)
{
    if (incrementTurnId) TurnId++;
    CurrentTeam = Team.Enemy;
    OnTurnStarted?.Invoke(CurrentTeam, TurnId);
    ForcePhase(isPlayerTurn: false, incrementTurnNumber: false);
}
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/BattleLogic/WinBattle.cs

```
using UnityEngine;
using UnityEngine.UI;
using TMPro;
using Mirror;

public class WinBattle : MonoBehaviour
{
    [Header("UI")]
    [SerializeField] private GameObject panel;           // koko voitto-UI:n root (piilossa aluksi)
    [SerializeField] private TextMeshProUGUI titleText; // "Players Win!" / "Enemies Win!"
    [SerializeField] private Button playAgainButton;    // käynnistää resetin

    private bool gameEnded;

    private void Awake()
    {
        if (panel) panel.SetActive(false);
    }

    private void OnEnable()
    {
        Unit.OnAnyUnitDead += Unit_OnAnyUnitDead;
    }

    private void OnDisable()
    {
        Unit.OnAnyUnitDead -= Unit_OnAnyUnitDead;
    }

    private void Start()
    {
        if (panel) panel.SetActive(false);
        if (playAgainButton)
        {
            playAgainButton.onClick.RemoveAllListeners();
            playAgainButton.onClick.AddListener(OnClickPlayAgain);
        }

        // Jos aloitetaan tilasta, jossa toista puolta ei ole
        // EvaluateWin();
    }

    private void Unit_OnAnyUnitDead(object sender, System.EventArgs e)
    {
        if (GameModeManager.SelectedMode != GameMode.SinglePlayer)
        {
            if (NetMode.IsOnline) EvaluateWin_Server(); // vain server päättää
            return;
        }
    }
}
```

RogueShooter – All Scripts

```
// Offline/SP
EvaluateWin_Local();
}

// ---- UUSI: vain server ----
[Server]
private void EvaluateWin_Server()
{
    if (gameEnded) return;
    var um = UnitManager.Instance; if (um == null) return;

    int friendCount = um.GetFriendlyUnitList().Count;
    int enemyCount = um.GetEnemyUnitList().Count;

    Debug.Log($"[WinBattle] EvaluateWin_Server: Friends={friendCount}, Enemies={enemyCount}");

    bool hostWins = enemyCount <= 0;
    bool hostLoses = friendCount <= 0;
    if (!(hostWins || hostLoses)) return;

    gameEnded = true; // gate, kunnes ResetService nollaa

    // Lähetä tulos jokaiselle pelaajalle henkilökohtaisesti
    foreach (var kvp in NetworkServer.connections)
    {
        var conn = kvp.Value;
        if (conn?.identity == null) continue;

        var pc = conn.identity.GetComponent<PlayerController>();
        if (!pc) continue;

        bool isHost = conn.connectionId == 0; // hostin connectionId on 0
        bool youWon = (hostWins && isHost) || (hostLoses && !isHost);
        pc.TargetShowEnd(conn, youWon); // näyttää WinBattle-paneelin clientillä
    }
}

// ---- Vanhasta EvaluateWinistä jää SinglePlayer-haara tähän ----
private void EvaluateWin_Local()
{
    if (gameEnded) return;
    var um = UnitManager.Instance; if (um == null) return;

    int friendCount = um.GetFriendlyUnitList().Count;
    int enemyCount = um.GetEnemyUnitList().Count;

    if (enemyCount <= 0) ShowEnd("Players Win!");
    else if (friendCount <= 0) ShowEnd("Enemies Win!");
}

public void ShowEnd(string title)
```

RogueShooter – All Scripts

```
{
    gameEnded = true;

    if (titleText) titleText.text = title;
    if (panel) panel.SetActive(true);
}

private void OnClickPlayAgain()
{
    // Yksi reitti kaikkeen: ResetService → LevelLoader
    if (NetMode.IsOnline)
    {
        ResetService.Instance.RequestReset();
        return;
    }
    gameEnded = false;
    if (panel) panel.SetActive(false);
    // OFFLINE → suoraan LevelLoaderin kautta
    LevelLoader.Instance.ReloadOffline(LevelLoader.Instance.DefaultLevel);
}

public void HideEndPanel()
{
    gameEnded = false;
    if (panel) panel.SetActive(false);
}
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/InputManager.cs

```
#define USE_NEW_INPUT_SYSTEM
using UnityEngine;
using UnityEngine.InputSystem;

public class InputManager : MonoBehaviour
{
    public static InputManager Instance { get; private set; }

    private PlayerInputActions playerInputActions;

    private void Awake()
    {
        // Ensure that there is only one instance in the scene
        if (Instance != null)
        {
            Debug.LogError("InputManager: More than one InputManager in the scene!" + transform + " " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;

#if USE_NEW_INPUT_SYSTEM
        playerInputActions = new PlayerInputActions();
        // Voit halutessasi enablettää koko collectionin:
        // playerInputActions.Enable();
        playerInputActions.Player.Enable();
#endif
    }

#if USE_NEW_INPUT_SYSTEM
    private void OnDisable()
    {
        // Vähintään tämä: disabloi kaikki käytössä olevat mapit
        if (playerInputActions != null)
        {
            // Jos käytät vain Player-mapia:
            playerInputActions.Player.Disable();
            // Tai koko collection:
            // playerInputActions.Disable();
        }
    }

    private void OnDestroy()
    {
        // Vapauta resurssit -> poistaa finalizer-varoituksen
        playerInputActions?.Dispose();
        playerInputActions = null;

        if (Instance == this) Instance = null;
    }
#endif
}
```

RogueShooter – All Scripts

```
    public Vector2 GetMouseScreenPosition()
    {
#if USE_NEW_INPUT_SYSTEM
        return Mouse.current.position.ReadValue();
#else
        return Input.mousePosition;
#endif
    }

    public bool IsMouseButtonDownThisFrame()
    {
#if USE_NEW_INPUT_SYSTEM
        return playerInputActions.Player.Click.WasPressedThisFrame();
#else
        return Input.GetMouseButtonDown(0);
#endif
    }

    public Vector2 GetCameraMoveVector()
    {
#if USE_NEW_INPUT_SYSTEM
        return playerInputActions.Player.CameraMovement.ReadValue<Vector2>();
#else
        Vector2 inputMoveDirection = new Vector2(0, 0);
        if (Input.GetKey(KeyCode.W))
        {
            inputMoveDirection.y = +1f;
        }
        if (Input.GetKey(KeyCode.S))
        {
            inputMoveDirection.y = -1f;
        }
        if (Input.GetKey(KeyCode.A))
        {
            inputMoveDirection.x = -1f;
        }
        if (Input.GetKey(KeyCode.D))
        {
            inputMoveDirection.x = +1f;
        }

        return inputMoveDirection;
#endif
    }

    public float GetCameraRotateAmount()
    {
#if USE_NEW_INPUT_SYSTEM
        return playerInputActions.Player.CameraRotate.ReadValue<float>();
#else
        float rotateAmount = 0;
#endif
    }
}
```


RogueShooter – All Scripts

```
        if (Input.GetKey(KeyCode.Q))
        {
            rotateAmount = +1f;
        }
        if (Input.GetKey(KeyCode.E))
        {
            rotateAmount = -1f;
        }

        return rotateAmount;
    #endif
    }

    public float GetCameraZoomAmount()
    {
    #if USE_NEW_INPUT_SYSTEM
        return playerInputActions.Player.CameraZoom.ReadValue<float>();
    #else
        float zoomAmount = 0f;
        if (Input.mouseScrollDelta.y > 0)
        {
            zoomAmount = -1f;
        }
        if (Input.mouseScrollDelta.y < 0)
        {
            zoomAmount = +1f;
        }

        return zoomAmount;
    #endif
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/MouseWorld.cs

```
using UnityEngine;

/// <summary>
/// This class is responsible for handling mouse interactions in the game world.
/// It provides a method to get the mouse position in the world space based on the camera's perspective.
/// </summary>

public class MouseWorld : MonoBehaviour
{
    private static MouseWorld instance;
    [SerializeField] private LayerMask mousePlaneLayerMask;

    private void Awake()
    {
        instance = this;
    }

    public static Vector3 GetMouseWorldPosition()
    {
        Ray ray = Camera.main.ScreenPointToRay(InputManager.Instance.GetMouseScreenPosition());
        Physics.Raycast(ray, out RaycastHit raycastHit, float.MaxValue, instance.mousePlaneLayerMask);
        return raycastHit.point;
    }

    /// <summary>
    /// Ignore non visible objects, floors and walls what FloorVisibily has set to hidden.
    /// </summary>
    public static Vector3 GetPositionOnlyHitVisible()
    {
        Ray ray = Camera.main.ScreenPointToRay(InputManager.Instance.GetMouseScreenPosition());
        RaycastHit[] raycastHitArray = Physics.RaycastAll(ray, float.MaxValue, instance.mousePlaneLayerMask);
        System.Array.Sort(raycastHitArray,
            (a, b) => a.distance.CompareTo(b.distance));

        foreach (RaycastHit raycastHit in raycastHitArray)
        {
            if (raycastHit.transform.TryGetComponent(out Renderer renderer))
            {
                if (renderer.enabled)
                {
                    return raycastHit.point;
                }
            }
        }
        return Vector3.zero;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/Player/PlayerController.cs

```
using Mirror;
using UnityEngine;

///<summary>
/// PlayerController handles per-player state in a networked game.
/// Each connected player has one PlayerController instance attached to PlayerController GameObject prefab
/// It tracks whether the player has ended their turn and communicates with the UI.
///</summary>
public class PlayerController : NetworkBehaviour
{
    [SyncVar] public bool hasEndedThisTurn;

    public static PlayerController Local; // helppo viittaus UI:lle

    public override void OnStartLocalPlayer()
    {
        base.OnStartLocalPlayer();
        Local = this;
    }

    // UI-nappi kutsuu tätä (vain local player)
    public void ClickEndTurn()
    {
        if (!isLocalPlayer) return;
        if (hasEndedThisTurn) return;
        if (NetTurnManager.Instance && NetTurnManager.Instance.phase != TurnPhase.Players) return;
        CmdEndTurn();
    }

    [Command(requiresAuthority = true)]
    void CmdEndTurn()
    {
        if (hasEndedThisTurn) return;
        hasEndedThisTurn = true;

        // Estä kaikki toiminnot clientillä
        TargetNotifyCanAct(connectionToClient, false);

        // Varmista myös että koordinaattori löytyy serveripuolelta:
        if (NetTurnManager.Instance == null)
        {
            Debug.LogWarning("[PC][SERVER] NetTurnManager.Instance is NULL on server!");
            return;
        }

        NetTurnManager.Instance.ServerPlayerEndedTurn(netIdentity.netId);
    }

    // Server kutsuu tämän kierroksen alussa nollatakseen tilan
}
```

RogueShooter – All Scripts

```
[Server]
public void ServerSetHasEnded(bool v)
{
    hasEndedThisTurn = v;
    TargetNotifyCanAct(connectionToClient, !v);
}

[TargetRpc]
void TargetNotifyCanAct(NetworkConnectionToClient __, bool canAct)
{
    // Update End Turn Button
    var ui = FindFirstObjectByType<TurnSystemUI>();
    if (ui != null)
        ui.SetCanAct(canAct);
    if (!canAct) ui.SetTeammateReady(false, null);

    // Lock/Unlock UnitActionSystem input
    if (UnitActionSystem.Instance != null)
    {
        if (canAct) UnitActionSystem.Instance.UnlockInput();
        else UnitActionSystem.Instance.LockInput();
    }

    // Set AP visibility in versus game
    PlayerLocalTurnGate.Set(canAct);
}

[TargetRpc]
public void TargetShowEnd(NetworkConnectionToClient conn, bool youWon)
{
    var ui = FindFirstObjectByType<WinBattle>();
    if (ui) ui.ShowEnd(youWon ? "You win!" : "You lost");
}
}
```

RogueShooter – All Scripts

Assets/scripts/GameLogic/Player/PlayerLocalTurnGate.cs

```
using System;

/// <summary>
/// Static gate that tracks whether the local player turn is. (e.g., enabling/disabling UI).
/// Other systems can subscribe to the <see cref="LocalPlayerTurnChanged"/> event to update their state
/// </summary>
///
public static class PlayerLocalTurnGate
{
    // public static int PlayerReady { get; private set; }

    // public static event Action<int> OnPlayerReadyChanged;
    /// <summary>
    /// Gets whether the local player can currently act.
    /// </summary>
    public static bool LocalPlayerTurn { get; private set; }

    /// <summary>
    /// Event fired whenever the <see cref="LocalPlayerTurn"/> state changes.
    /// The bool argument indicates the new state.
    /// </summary>
    public static event Action<bool> LocalPlayerTurnChanged;

    /// <summary>
    /// Updates the <see cref="LocalPlayerTurn"/> state.
    /// If the value changes, invokes <see cref="LocalPlayerTurnChanged"/> to notify listeners.
    /// </summary>
    /// <param name="canAct">True if the player may act; false otherwise.</param>
    public static void Set(bool canAct)
    {
        if (LocalPlayerTurn == canAct) return;
        LocalPlayerTurn = canAct;
        LocalPlayerTurnChanged?.Invoke(LocalPlayerTurn);
    }

    public static void SetCanAct(bool canAct)
    {
        LocalPlayerTurn = canAct;
        LocalPlayerTurnChanged?.Invoke(LocalPlayerTurn);
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameModes/GameModeManager.cs

```
using System.Collections;
using UnityEngine;
using UnityEngine.SceneManagement;
using Utp;

public enum GameMode { SinglePlayer, CoOp, Versus }

public class GameModeManager : MonoBehaviour
{
    public static GameModeManager Instance { get; private set; }
    public static GameMode SelectedMode { get; private set; } = GameMode.SinglePlayer;

    public static void SetSinglePlayer() => SelectedMode = GameMode.SinglePlayer;
    public static void SetCoOp() => SelectedMode = GameMode.CoOp;
    public static void SetVersus() => SelectedMode = GameMode.Versus;

    private void Awake()
    {
        if (Instance != null && Instance != this)
        {
            Destroy(gameObject);
            return;
        }
        Instance = this;
    }

    private void OnEnable()
    {
        LevelLoader.LevelReady += OnLevelReady;    // ← kuuntele jokaista level-latausta
    }

    private void OnDisable()
    {
        LevelLoader.LevelReady -= OnLevelReady;
    }

    private void OnLevelReady(Scene _)
    {
        if (!NetMode.IsOnline) return; // vain offline
        StartCoroutine(OfflineBootstrap()); // ← käynnistä spawnaus myös reloadin jälkeen
    }

    public bool LevelIsLoaded()
    {
        for (int i = 0; i < SceneManager.sceneCount; i++)
        {
            Scene scene = SceneManager.GetSceneAt(i);
            if (scene.isLoaded && scene.name != "Core")
            {
                return true;
            }
        }
    }
}
```

RogueShooter – All Scripts

```
    }
}
return false;
}

public Scene GetLoadedLevelScene()
{
    for (int i = 0; i < SceneManager.sceneCount; i++)
    {
        Scene scene = SceneManager.GetSceneAt(i);
        if (scene.isLoaded && scene.name != "Core")
        {
            return scene;
        }
    }
    return default;
}

private IEnumerator OfflineBootstrap()
{
    // Nämä guardit ovat jo projektissa: odota että kaikki on olemassa
    yield return new WaitUntil(() => SpawnUnitsCoordinator.Instance != null);
    yield return new WaitUntil(() => LevelGrid.Instance != null && PathFinding.Instance != null);

    if (SelectedMode == GameMode.SinglePlayer)
    {
        // Spawn offline -unitit siihen sceneen, missä koordinaattori on
        SpawnUnitsCoordinator.Instance.SpawnSinglePlayerUnits();
        LevelGrid.Instance.RebuildOccupancyFromScene();
    }
}

/*
void Handle_LevelReady(Scene s)
{
    if (!NetMode.IsServer) return;          // vain server
    StartCoroutine(Co_ServerSpawnUnits());
}

IEnumerator Co_ServerSpawnUnits()
{
    // odota riippuvuudet
    yield return new WaitUntil(() =>
        SpawnUnitsCoordinator.Instance != null &&
        LevelGrid.Instance != null &&
        PathFinding.Instance != null);

    // Spawnaa serveriltä nykyisen pelitilan mukaan
    // (tee koordinaattoriin yksi sisäänajo, ettei tarvitse miettiä moodia tässä)
    //SpawnUnitsCoordinator.Instance.ServerSpawnUnitsForCurrentMode();

    // päivitä miehitys varmuudeksi
```

RogueShooter – All Scripts

```
        LevelGrid.Instance.RebuildOccupancyFromScene();  
    }  
    */  
}
```


RogueShooter – All Scripts

Assets/scripts/GameModes/GameReset.cs

```
using UnityEngine.SceneManagement;

public static class GameReset
{
    public static void HardReloadSceneKeepMode()
    {
        // GameManager.SelectedMode säilyy, jos se on staattinen / DontDestroyOnLoad
        var scene = SceneManager.GetActiveScene().name;
        SceneManager.LoadScene(scene);
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameObjects/DestructibleObject.cs

```
using Unity.Mathematics;
using UnityEngine;
using Mirror;
using System.Collections;

public class DestructibleObject : NetworkBehaviour
{
    private GridPosition gridPosition;
    [SerializeField] private GameObject objectDestroyPrefab;
    [SerializeField] private int health = 3;

    // Ruutujen välissä olevat seinämät eivät blokkaa. True niille jotka täyttävät kokonaisia ruutuja.
    [SerializeField] private bool blocksCell = false;

    // To prevent multiple destruction events
    private bool isDestroyed;

    private bool _walkabilitySet;
    void Awake()
    {
        isDestroyed = false;
    }

    private void Start()
    {
        gridPosition = LevelGrid.Instance.GetGridPosition(transform.position);

        // UUSI: älä tee mitään jos tämä prop on gridin ulkopuolella
        if (!LevelGrid.Instance.IsValidGridPosition(gridPosition))
        {
            Debug.LogWarning($"[DestructibleObject] {name} at {transform.position} maps OUTSIDE grid ({gridPosition}). Skip walkability.");
            return;
        }

        if (blocksCell) TryMarkBlocked();
    }

    /// <summary>
    /// Marks the grid position as blocked if not already set.
    /// </summary>
    private void TryMarkBlocked()
    {
        if (_walkabilitySet) return;

        // UUSI: jos PF ei ole valmis, deferoi kunnes leveys > 0
        if (PathFinding.Instance == null || PathFinding.Instance.GetWidth() <= 0)
        {
            StartCoroutine(DeferBlockUntilReady());
            return;
        }
    }
}
```

RogueShooter – All Scripts

```
    }

    if (PathFinding.Instance != null)
    {
        PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, false);
        _walkabilitySet = true;
    }
    else
    {
        // jos PathFinding käynnistyy myöhemmin (scene-reload + spawn)
        StartCoroutine(DeferBlockOneFrame());
    }
}

private IEnumerator DeferBlockUntilReady()
{
    yield return new WaitUntil(() =>
        PathFinding.Instance != null &&
        PathFinding.Instance.GetWidth() > 0);

    if (!LevelGrid.Instance.IsValidGridPosition(gridPosition)) yield break;

    PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, false);
    _walkabilitySet = true;
}

private IEnumerator DeferBlockOneFrame()
{
    yield return null; // 1 frame
    if (PathFinding.Instance != null)
    {
        Debug.Log("Later update: Deferring walkability set for destructible object at " + gridPosition);
        PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, false);
        _walkabilitySet = true;
    }
}

public GridPosition GetGridPosition()
{
    return gridPosition;
}

public void Damage(int damageAmount, Vector3 hitPosition)
{
    if (isDestroyed) return;

    health -= damageAmount;
    if (health > 0) return;

    int overkill = math.abs(health) + 1;
    health = 0;
    isDestroyed = true;
}
```

RogueShooter – All Scripts

```
if (isServer)
{
    RpcPlayDestroyFx(hitPosition, overkill);
    RpcSetSoftHidden(true);
    StartCoroutine(DestroyAfter(0.30f));
    return;
}

// Offline (ei serveriä eikä clienttia)
if (!NetworkClient.active && !NetworkServer.active)
{
    PlayDestroyFx(hitPosition, overkill);
    SetSoftHiddenLocal(true);
    StartCoroutine(DestroyAfter(0.30f));
    PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, true);
    EdgeBaker.Instance.RebakeEdgesAround(gridPosition);
}
}

private void PlayDestroyFx(Vector3 hitPosition, int overkill)
{
    // Sama sijainti, sama rotaatio, sama parent kuin alkuperäisellä
    var go = SpawnRouter.SpawnLocal(
        prefab: objectDestroyPrefab,
        pos: transform.position,
        rot: transform.rotation,
        source: transform,           // ← ohjaa samaan sceneen kuin tuhottava objekti
        sceneName: LevelLoader.Instance.CurrentLevel,
        parent: null,               // ← älä periytä Core-parenttia vahingossa
        beforeReturn: go =>
        {
            // jos haluat säilyttää skaalan:
            go.transform.localScale = transform.localScale;
            ApplyPushForceToChildren(go.transform, 10f * overkill, hitPosition, 10f);
        }
    );
}

[ClientRpc]
private void RpcPlayDestroyFx(Vector3 hitPosition, int overkill)
{
    // Clientit: toista sama paikallisesti
    PlayDestroyFx(hitPosition, overkill);
}

private void ApplyPushForceToChildren(Transform root, float pushForce, Vector3 pushPosition, float PushRange)
{
    foreach (Transform child in root)
    {
```

RogueShooter – All Scripts

```
        if (child.TryGetComponent<Rigidbody>(out Rigidbody childRigidbody))
        {
            childRigidbody.AddExplosionForce(pushForce, pushPosition, PushRange);
        }

        ApplyPushForceToChildren(child, pushForce, pushPosition, PushRange);
    }
}

private IEnumerator DestroyAfter(float seconds)
{
    yield return new WaitForSeconds(seconds);

    if (isServer)
    {
        // Server: vapauta ruutu ja rebake serverillä
        PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, true);
        EdgeBaker.Instance.RebakeEdgesAround(gridPosition);

        // Lähetä sama clienteleille ennen tuhoa
        RpcOnDestroyed(gridPosition);

        // Pieni hengähdys (valinnainen, usein ei pakollinen)
        // yield return null;

        NetworkServer.Destroy(gameObject);
    } else {
        // Offline-tapaus tms.
        Destroy(gameObject);
    }
}

// Lisää tämä luokkaan
[ClientRpc]
private void RpcOnDestroyed(GridPosition pos)
{
    var lg = LevelGrid.Instance;
    var pf = PathFinding.Instance;
    var eb = EdgeBaker.Instance;

    if (lg != null && pf != null)
        pf.SetIsWalkableGridPosition(pos, true);

    if (lg != null && pf != null && eb != null)
        eb.RebakeEdgesAround(pos);
}

// Varmistus myös tilanteeseen, jossa RPC hukkuu tai tulee myöhässä
public override void OnStopClient()
{
}
```

RogueShooter – All Scripts

```
var lg = LevelGrid.Instance;
var pf = PathFinding.Instance;
var eb = EdgeBaker.Instance;

// Palauta walkable vain jos LevelGrid + PathFinding ovat olemassa
if (lg != null && pf != null)
    pf.SetIsWalkableGridPosition(gridPosition, true);

// Älä rebakea jos yksikin puuttuu (teardownissa usein puuttuu)
if (lg != null && pf != null && eb != null)
    eb.RebakeEdgesAround(gridPosition);
}

[ClientRpc]
private void RpcSetSoftHidden(bool hidden)
{
    SetSoftHiddenLocal(hidden);
}

private void SetSoftHiddenLocal(bool hidden)
{
    foreach (var r in GetComponentsInChildren<Renderer>(true))
        r.enabled = !hidden;

    foreach (var c in GetComponentsInChildren<Collider>(true))
        c.enabled = !hidden;
}
}
```

RogueShooter – All Scripts

Assets/scripts/GameObjects/Door.cs

```
using UnityEngine;
using Mirror;
using System;

public class Door : NetworkBehaviour, IInteractable
{
    [Header("State")]
    [SyncVar(hook = nameof(OnIsOpenChanged))]
    [SerializeField] private bool isOpen = false;    // alkutila scene-objektille

    [SerializeField] string openParam = "IsOpen";
    [SerializeField] float interactDuration = 0.5f;

    private GridPosition gridPosition;
    private Animator animator;

    // Interact-viiveen hallinta (vain kutsujan koneella UI/turn-rytmitystä varten)
    private Action onInteractComplete;
    private bool isActive;
    private float timer;

    private static bool NetOffline => !NetworkClient.active && !NetworkServer.active;

    private void Awake()
    {
        animator = GetComponent<Animator>();

        // Pakota alkupose heti oikein (ei välähdyksiä)
        animator.SetBool("IsOpen", isOpen);
        animator.Play(isOpen ? "DoorOpen" : "DoorClose", 0, 1f);
        animator.Update(0f);
    }

    private void Start()
    {
        gridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
        LevelGrid.Instance.SetInteractableAtGridPosition(gridPosition, this);

        // AINA: päivitä käveltävyys tämän hetken tilan mukaan
        if (PathFinding.Instance != null)
        {
            PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, isOpen);
        }
    }

    private void Update()
    {
        if (!isActive) return;
    }
}
```

RogueShooter – All Scripts

```
        timer -= Time.deltaTime;
        if (timer <= 0f)
        {
            isActive = false;
            onInteractComplete?.Invoke();
            onInteractComplete = null;
        }
    }

    // KUTSUTAAN InteractActionista (sekä offline, host että puhdas client)
    public void Interact(Action onInteractComplete)
    {
        // Gate (estää spämmin)
        if (isActive) return;

        this.onInteractComplete = onInteractComplete;
        isActive = true;
        timer = interactDuration; // haluttu viive actionille

        if (NetOffline)
        {
            // SINGLEPLAYER: vaihda paikallisesti
            ToggleLocal();
        }
        else if (isServer)
        {
            // HOST / SERVER: vaihda suoraan serverillä
            ToggleServer();
        }
        else
        {
            // PUHDAS CLIENT: pyydä serveriä
            CmdToggleServer();
        }
    }

    [Command(requiresAuthority = false)]
    private void CmdToggleServer()
    {
        ToggleServer();
    }

    [Server]
    private void ToggleServer()
    {
        isOpen = !isOpen; // Tämä käynnistää hookin kaikilla
        // EI suoraa animator-kutsua täällä; hook hoitaa sen kauniisti
    }

    private void ToggleLocal()
    {
        // Offline-haara: päivitä animaatio ja pathfinding paikallisesti
    }
}
```


RogueShooter – All Scripts

```
        isOpen = !isOpen;
        ApplyAnimator(isOpen);
        PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, isOpen);

    }

    // SyncVar hook – ajetaan kaikilla kun isOpen muuttuu serverillä
    private void OnIsOpenChanged(bool oldVal, bool newVal)
    {
        ApplyAnimator(newVal);

        // Pathfinding vain serverillä (tai offline Startissa/ToggleLocalissa)
        if (PathFinding.Instance != null)
            PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, newVal);
    }

    private void ApplyAnimator(bool open)
    {
        animator.SetBool(openParam, open);
    }

    // Nämä jätetään jos muu koodi tarvitsee suoraviivaisia kutsuja
    public void OpenDoor()
    {
        if (NetOffline || NetworkServer.active)
        {
            isOpen = true; // käynnistää hookin vain serverillä; offline: päivitä itse
            if (NetOffline)
            {
                ApplyAnimator(true);
                PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, true);
            }
        }
    }

    public void CloseDoor()
    {
        if (NetOffline || NetworkServer.active)
        {
            isOpen = false;
            if (NetOffline)
            {
                ApplyAnimator(false);
                PathFinding.Instance.SetIsWalkableGridPosition(gridPosition, false);
            }
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/GameObjects/IInreractable.cs

```
using System;

public interface IInteractable
{
    void Interact(Action onInteractComplete);
}
```

RogueShooter – All Scripts

Assets/scripts/GameObjects/InteractableItem.cs

```
using System;
using UnityEngine;
using Mirror;
public class InteractableItem : NetworkBehaviour, IInteractable
{
    [Header("State")]
    [SyncVar(hook = nameof(OnIsInteractChanged))]
    [SerializeField] private bool isGreen;

    [Header("Visuals")]
    [SerializeField] private Material greenMaterial;
    [SerializeField] private Material redMaterial;
    [SerializeField] private MeshRenderer meshRenderer;

    [Header("Interact")]
    [SerializeField] private float interactDuration = 0.5f;

    private GridPosition gridPosition;
    private Action onInteractComplete;
    private bool isActive;
    private float timer;

    private static bool NetOffline => !NetworkClient.active && !NetworkServer.active;

    void Awake()
    {
        // Pakota alkupose heti oikein (ei välähdyksiä)
        if (!meshRenderer) meshRenderer = GetComponentInChildren<MeshRenderer>();
        SetVisualFromState(isGreen);
    }
    private void Start()
    {
        gridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
        LevelGrid.Instance.SetInteractableAtGridPosition(gridPosition, this);
        // SetColorRed();
    }
    private void Update()
    {
        if (!isActive) return;

        timer -= Time.deltaTime;
        if (timer <= 0f)
        {
            isActive = false;
            onInteractComplete?.Invoke();
            onInteractComplete = null;
        }
    }

    private void SetColorGreen()
```

RogueShooter – All Scripts

```
{
    isGreen = true;
    meshRenderer.material = greenMaterial;
}

private void SetColorRed()
{
    isGreen = false;
    meshRenderer.material = redMaterial;
}

public void Interact(Action onInteractComplete)
{
    this.onInteractComplete = onInteractComplete;
    isActive = true;
    timer = interactDuration;

    if (NetOffline)
    {
        // SINGLEPLAYER: vaihda paikallisesti
        ToggleLocal();
    }
    else if (isServer)
    {
        // HOST / SERVER: vaihda suoraan serverillä
        ToggleServer();
    }
    else
    {
        // PUHDAS CLIENT: pyydä serveriä
        CmdToggleServer();
    }
}

private void ToggleLocal()
{
    isGreen = !isGreen;
    SetVisualFromState(isGreen);
}

[Server]
private void ToggleServer()
{
    // SERVER: muuta vain tila; visuaali päivittyy hookista kaikkialla
    isGreen = !isGreen;
    SetVisualFromState(isGreen); // valinnainen: tekee serverille välittömän visuaalin ilman uutta SyncVar-kirjoitusta
}

[Command(requiresAuthority = false)]
void CmdToggleServer() => ToggleServer();

private void OnIsInteractChanged(bool oldValue, bool newVal)
```

RogueShooter – All Scripts

```
{
    SetVisualFromState(newVal);
}

private void SetVisualFromState(bool state)
{
    if (!meshRenderer) return;
    meshRenderer.material = state ? greenMaterial : redMaterial;
}
}
```

RogueShooter – All Scripts

Assets/scripts/GameObjects/LosBlocker.cs

```
using System.Collections.Generic;
using UnityEngine;

[DisallowMultipleComponent]
public class LoSBlocker : MonoBehaviour
{
    public enum Mode { Manual, AutoFromBounds }

    [Header("Mode")]
    [SerializeField] private Mode mode = Mode.AutoFromBounds;

    [Tooltip("Jos Manual: true = blokkaa LoS:n")]
    [SerializeField] private bool blocksLineOfSight = true;

    [Header("AutoFromBounds-asetukset")]
    [Tooltip("Yli tämän y-kynnyksen (ruudun pohjasta) tulkitaan 'korkeaksi'")]
    [SerializeField] private float heightThresholdY = 1.7f;

    [Tooltip("Käytä näitä kollidereita. Tyhjä = hae automaattisesti lapsista.")]
    [SerializeField] private List<Collider> colliders = new();

    // Seurataan mitä ruutuja tämä tällä hetkellä kattaa
    private readonly HashSet<GridPosition> _covered = new();
    private bool _registered;
    private LevelGrid _lg;

    void OnEnable()
    {
        _lg = LevelGrid.Instance;
        if (colliders.Count == 0)
            colliders.AddRange(GetComponentsInChildren<Collider>());

        Rebuild(); // laske ruudut + blokkaako
        Register(); // vie registryyn
    }

    void OnDisable()
    {
        Unregister();
        colliders.Clear();
        _covered.Clear();
    }

    /// <summary>
    /// Kutsu tätä kun objektin korkeus/muoto muuttuu (esim. tuhoutuessa).
    /// </summary>
    public void Rebuild()
    {
        if (_lg == null) return;
```

RogueShooter – All Scripts

```
// 1) Laske yhdistetty bounds (vain colliderit jotka ovat aktiivisia)
var haveAny = false;
var bounds = new Bounds(transform.position, Vector3.zero);
foreach (var c in colliders)
{
    if (c == null || !c.enabled) continue;
    if (!haveAny) { bounds = c.bounds; haveAny = true; }
    else { bounds.Encapsulate(c.bounds); }
}
if (!haveAny)
{
    blocksLineOfSight = false; // ei kollidereita → ei blokkaa
    RefreshCoveredTiles(bounds, hasBounds:false);
    return;
}

// 2) Määritä blokkaako: Manual vs Auto
if (mode == Mode.AutoFromBounds)
{
    // Ruudun pohjataso: mitaamme korkeuden paikallisesti jokaisessa ruudussa,
    // mutta yksinkertaisuuden vuoksi arvioi koko objektin "max korkeus"
    float maxTop = bounds.max.y;

    // Arvioi peruslattia käyttämällä bounds.min ja LevelGridiä
    var gpMin = _lg.GetGridPosition(bounds.min);
    var basePos = _lg.GetWorldPosition(gpMin);
    float baseY = basePos.y;

    float topAboveBase = maxTop - baseY;
    blocksLineOfSight = topAboveBase >= heightThresholdY;
}
// Manual: blocksLineOfSight pysyy sellaisenaan

// 3) Päivitä mitkä ruudut tämä kattaa
RefreshCoveredTiles(bounds, hasBounds:true);
}

/// <summary>
/// Rekisteröi/poistaa rekisteristä nykyiset ruudut.
/// </summary>
private void Register()
{
    if (_registered || !blocksLineOfSight || _covered.Count == 0) return;
    LoSBlockerRegistry.AddTiles(_covered);
    _registered = true;
}

private void Unregister()
{
    if (!_registered) return;
    LoSBlockerRegistry.RemoveTiles(_covered);
    _registered = false;
}
```

RogueShooter – All Scripts

```
}

/// <summary>
/// Päivittää _covered-ruudut boundsien perusteella ja synkkaa registryyn.
/// </summary>
private void RefreshCoveredTiles(Bounds worldBounds, bool hasBounds)
{
    // Poista vanhat ruudut registryltä
    Unregister();
    _covered.Clear();

    if (!hasBounds || _lg == null || !blocksLineOfSight) return;

    // Muunna bounds → grid-alue
    var min = _lg.GetGridPosition(worldBounds.min);
    var max = _lg.GetGridPosition(worldBounds.max);

    // Jos objekti voi levitä usealle floorille, tässä voi rajata/vahvistaa.
    int floor = min.floor;

    for (int x = Mathf.Min(min.x, max.x); x <= Mathf.Max(min.x, max.x); x++)
    for (int z = Mathf.Min(min.z, max.z); z <= Mathf.Max(min.z, max.z); z++)
    {
        var gp = new GridPosition(x, z, floor);
        if (_lg.IsValidGridPosition(gp))
            _covered.Add(gp);
    }

    // Rekisteröi päivitetty setti
    Register();
}
}
```


RogueShooter – All Scripts

Assets/scripts/GameObjects/ObjectSpawnPlaceholder.cs

```
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;

public class ObjectSpawnPlaceholder : MonoBehaviour
{
    [SerializeField] private GameObject objectPrefab;
    public GameObject Prefab => objectPrefab;

    private void Start()
    {
        // OFFLINE: käytä SpawnRouter.SpawnLocal → asettaa instanssin samaan level-sceneeseen kuin placeholder
        if (!NetworkClient.active && !NetworkServer.active)
        {
            SpawnRouter.SpawnLocal(
                prefab: objectPrefab,
                pos: transform.position,
                rot: transform.rotation,
                source: transform,
                sceneName: gameObject.scene.name
            );
            Destroy(gameObject);
            return;
        }

        // PUHDAS CLIENT: server spawnaa → placeholder pois
        if (NetworkClient.active && !NetworkServer.active)
        {
            Destroy(gameObject);
        }
    }

    // Kutsutaan serveriltä (esim. MapContentSpawnerista)
    public GameObject CreateObject()
    {
        if (!NetworkServer.active) return null;

        Scene levelScene = gameObject.scene;

        var go = SpawnRouter.SpawnNetworkServer(
            prefab: objectPrefab,
            pos: transform.position,
            rot: transform.rotation,
            source: transform,           // → tämän placeholderin scene
            sceneName: levelScene.name,  // → ohita Core, lukitse oikeaan level-sceneeseen
            parent: null,
            owner: null,                 // ympäristöpropsit eivät tarvitse owneria
            beforeSpawn: obj =>
            {
                // Jos haluat inittejä (HP tms.), tee ne tässä
            }
        );
    }
}
```

RogueShooter – All Scripts

```
        // esim: if (obj.TryGetComponent<DestructibleObject>(out var d)) d.Init(...);
    }
};

Destroy(gameObject);
return go;
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/GridObject.cs

```
using System.Collections.Generic;

// <summary>
// This class represents a grid object in the grid system.
// It contains a list of units that are present in the grid position.
// It also contains a reference to the grid system and the grid position.
// </summary>
public class GridObject
{
    private GridSystem<GridObject> gridSystem;
    private GridPosition gridPosition;
    private List<Unit> unitList;
    private IInteractable interactable;

    public GridObject(GridSystem<GridObject> gridSystem, GridPosition gridPosition)
    {
        this.gridSystem = gridSystem;
        this.gridPosition = gridPosition;
        unitList = new List<Unit>();
    }

    public override string ToString()
    {
        string unitListString = "";
        foreach (Unit unit in unitList)
        {
            unitListString += unit + "\n";
        }
        return gridPosition.ToString() + "\n" + unitListString;
    }

    public void AddUnit(Unit unit)
    {
        /*
        unitList.Add(unit);
        */

        if (unit == null) return;
        var list = GetUnitList();
        if (!list.Contains(unit)) list.Add(unit);
    }

    public void RemoveUnit(Unit unit)
    {
        unitList.Remove(unit);
    }

    public List<Unit> GetUnitList()
    {
        unitList.RemoveAll(u => u == null);
    }
}
```

RogueShooter – All Scripts

```
        return unitList;
    }

    public bool HasAnyUnit()
    {
        // Poista tuhotut viitteet (Unity-null huomioiden)
        unitList.RemoveAll(u => u == null);
        return unitList.Count > 0;
    }

    public Unit GetUnit()
    {
        for (int i = unitList.Count - 1; i >= 0; i--)
        {
            if (unitList[i] == null) { unitList.RemoveAt(i); continue; }
        }
        return unitList.Count > 0 ? unitList[0] : null;
    }

    public IInteractable GetInteractable()
    {
        return interactable;
    }

    public void SetInteractable(IInteractable interactable)
    {
        this.interactable = interactable;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/GridPosition.cs

```
using System;

// <summary>
// This struct represents a position in a grid system.
// It contains two integer values, x and z, which represent the coordinates of the position in the grid.
// It also contains methods for comparing two GridPosition objects, adding and subtracting them, and converting them to a string representation.
// </summary>
public struct GridPosition:IEquatable<GridPosition>
{
    public int x;
    public int z;

    public int floor;

    public GridPosition(int x, int z, int floor)
    {
        this.x = x;
        this.z = z;
        this.floor = floor;
    }

    public override bool Equals(object obj)
    {
        return obj is GridPosition position &&
            x == position.x &&
            z == position.z &&
            floor == position.floor;
    }

    public bool Equals(GridPosition other)
    {
        return this == other;
    }

    public override int GetHashCode()
    {
        return GetHashCode.Combine(x, z, floor);
    }

    public override string ToString()
    {
        return $"(x:{x}, z:{z}, floor:{floor})";
    }

    public static bool operator ==(GridPosition a, GridPosition b)
    {
        return a.x == b.x && a.z == b.z && a.floor == b.floor;
    }

    public static bool operator !=(GridPosition a, GridPosition b)
```

RogueShooter – All Scripts

```
{  
    return !(a == b);  
}  
  
public static GridPosition operator +(GridPosition a, GridPosition b)  
{  
    return new GridPosition(a.x + b.x, a.z + b.z, a.floor + b.floor);  
}  
  
public static GridPosition operator -(GridPosition a, GridPosition b)  
{  
    return new GridPosition(a.x - b.x, a.z - b.z, a.floor - b.floor);  
}  
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/GridSystem.cs

```
using System;
using UnityEngine;

/// <summary>
/// This class represents a grid system in a 2D space.
/// It contains methods to create a grid, convert between grid and world coordinates,
/// and manage grid objects.
/// </summary>

public class GridSystem<TGridObject>
{
    private int width;
    private int height;
    private float cellSize;
    private int floor;

    private float floorHeigth;
    private TGridObject[,] gridObjectsArray;

    public GridSystem(int width, int height, float cellSize, int floor, float floorHeigth, Func<GridSystem<TGridObject>, GridPosition, TGridObject> createGridObject)
    {
        this.width = width;
        this.height = height;
        this.cellSize = cellSize;
        this.floor = floor;
        this.floorHeigth = floorHeigth;

        gridObjectsArray = new TGridObject[width, height];

        for (int x = 0; x < width; x++)
        {
            for (int z = 0; z < height; z++)
            {
                GridPosition gridPosition = new GridPosition(x, z, floor);
                gridObjectsArray[x, z] = createGridObject(this, gridPosition);
            }
        }
    }

    /// Purpose: This method converts grid coordinates (x, z) to world coordinates.
    /// It multiplies the grid coordinates by the cell size to get the world position.
    public Vector3 GetWorldPosition(GridPosition gridPosition)
    {
        return new Vector3(gridPosition.x, 0, gridPosition.z) * cellSize +
            new Vector3(0, gridPosition.floor, 0) * floorHeigth;
    }

    /// Purpose: This is used to find the grid position of a unit in the grid system.
    /// It is used to check if the unit is within the bounds of the grid system.
    /// It converts the world position to grid coordinates by dividing the world position by the cell size.
```

RogueShooter – All Scripts

```
public GridPosition GetGridPosition(Vector3 worldPosition)
{
    return new GridPosition( Mathf.RoundToInt(worldPosition.x/cellSize),
        Mathf.RoundToInt(worldPosition.z/cellSize),
        floor);
}

/// Purpose: This method creates debug objects in the grid system for visualization purposes.
/// It instantiates a prefab at each grid position and sets the grid object for that position.
public void CreateDebugObjects(Transform debugPrefab)
{
    for (int x = 0; x< width; x++)
    {
        for(int z = 0; z < height; z++)
        {
            GridPosition gridPosition = new GridPosition(x, z, floor);
            Transform debugTransform = GameObject.Instantiate(debugPrefab, GetWorldPosition(gridPosition), Quaternion.identity);
            GridDebugObject gridDebugObject = debugTransform.GetComponent<GridDebugObject>();
            gridDebugObject.SetGridObject(GetGridObject(gridPosition));
        }
    }
}

/// Purpose: This method returns the grid object at a specific grid position.
/// It is used to get the grid object for a specific position in the grid system.
public TGridObject GetGridObject(GridPosition gridPosition)
{
    return gridObjectsArray[gridPosition.x, gridPosition.z];
}

/// Purpose: This method checks if a grid position is valid within the grid system.
/// It checks if the x and z coordinates are within the bounds of the grid width and height.
public bool IsValidGridPosition(GridPosition gridPosition)
{
    return gridPosition.x >= 0 &&
        gridPosition.x < width &&
        gridPosition.z >= 0 &&
        gridPosition.z < height &&
        gridPosition.floor == floor;
}

public int GetWidth()
{
    return width;
}

public int GetHeight()
{
    return height;
}
}
```


RogueShooter – All Scripts

Assets/scripts/Grid/GridSystemVisual.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;

/// <summary>
/// This class is responsible for visualizing the grid system in the game.
/// It creates a grid of visual objects that represent the grid positions.
/// </summary>
[DefaultExecutionOrder(-100)]
public class GridSystemVisual : MonoBehaviour
{
    public static GridSystemVisual Instance { get; private set; }

    [Serializable]
    public struct GridVisualTypeMaterial
    {
        public GridVisualType gridVisualType;
        public Material material;
    }
    public enum GridVisualType
    {
        white,
        Blue,
        Red,
        RedSoft,
        Yellow
    }

    /// Purpose: This prefab is used to create the visual representation of each grid position.
    [SerializeField] private Transform gridSystemVisualSinglePrefab;
    [SerializeField] private List<GridVisualTypeMaterial> gridVisualTypeMaterialList;

    /// Purpose: This array holds the visual objects for each grid position.
    private GridSystemVisualSingle[, ,] gridSystemVisualSingleArray;

    private void Awake()
    {
        /// Purpose: Ensure that there is only one instance in the scene
        if (Instance != null)
        {
            Debug.LogError("More than one GridSystemVisual in the scene!" + transform + " " + Instance);
            Destroy(gameObject);
            return;
        }

        Instance = this;
    }
}
```

RogueShooter – All Scripts

```
private void Start()
{
    gridSystemVisualSingleArray = new GridSystemVisualSingle[
        LevelGrid.Instance.GetWidth(),
        LevelGrid.Instance.GetHeight(),
        LevelGrid.Instance.GetFloorAmount()
    ];

    /// Purpose: Create a grid of visual objects that represent the grid positions.
    /// It instantiates a prefab at each grid position and sets the grid object for that position.
    for (int x = 0; x < LevelGrid.Instance.GetWidth(); x++)
    {
        for (int z = 0; z < LevelGrid.Instance.GetHeight(); z++)
        {
            for (int floor = 0; floor < LevelGrid.Instance.GetFloorAmount(); floor++)
            {
                GridPosition gridPosition = new(x, z, floor);
                Transform gridSystemVisualSingleTransform = Instantiate(gridSystemVisualSinglePrefab, LevelGrid.Instance.GetWorldPosition(gridPosition),
Quaternion.identity);
                gridSystemVisualSingleArray[x, z, floor] = gridSystemVisualSingleTransform.GetComponent<GridSystemVisualSingle>();
            }
        }
    }

    UnitActionSystem.Instance.OnSelectedActionChanged += UnitActionSystem_OnSelectedActionChanged;
    UnitActionSystem.Instance.OnBusyChanged += UnitActionSystem_OnBusyChanged;
    LevelGrid.Instance.onAnyUnitMoveGridPosition += LevelGrid_onAnyUnitMoveGridPosition;

    UpdateGridVisuals();
}

void OnDisable()
{
    UnitActionSystem.Instance.OnSelectedActionChanged -= UnitActionSystem_OnSelectedActionChanged;
    UnitActionSystem.Instance.OnBusyChanged -= UnitActionSystem_OnBusyChanged;
    LevelGrid.Instance.onAnyUnitMoveGridPosition -= LevelGrid_onAnyUnitMoveGridPosition;
}

public void HideAllGridPositions()
{
    for (int x = 0; x < LevelGrid.Instance.GetWidth(); x++)
    {
        for (int z = 0; z < LevelGrid.Instance.GetHeight(); z++)
        {
            for (int floor = 0; floor < LevelGrid.Instance.GetFloorAmount(); floor++)
            {
                gridSystemVisualSingleArray[x, z, floor].Hide();
            }
        }
    }
}
```

RogueShooter – All Scripts

```
private void ShowGridPositionRange(GridPosition gridPosition, int range, GridVisualType gridVisualType)
{
    List<GridPosition> gridPositionsList = new List<GridPosition>();

    for (int x = -range; x <= range; x++)
    {
        for (int z = -range; z <= range; z++)
        {
            GridPosition testGridPosition = gridPosition + new GridPosition(x, z, 0);

            if (!LevelGrid.Instance.IsValidGridPosition(testGridPosition))
            {
                continue;
            }

            int cost = SircleCalculator.Sircle(x, z);
            if (cost > 10 * range) continue;

            gridPositionsList.Add(testGridPosition);
        }
    }

    ShowGridPositionList(gridPositionsList, gridVisualType);
}

private void ShowGridPositionRangeSquare(GridPosition gridPosition, int range, GridVisualType gridVisualType)
{
    List<GridPosition> gridPositionsList = new List<GridPosition>();

    for (int x = -range; x <= range; x++)
    {
        for (int z = -range; z <= range; z++)
        {
            GridPosition testGridPosition = gridPosition + new GridPosition(x, z, 0);

            if (!LevelGrid.Instance.IsValidGridPosition(testGridPosition))
            {
                continue;
            }

            gridPositionsList.Add(testGridPosition);
        }
    }

    ShowGridPositionList(gridPositionsList, gridVisualType);
}

public void ShowGridPositionList(List<GridPosition> gridPositionList, GridVisualType gridVisualType)
{
    foreach (GridPosition gridPosition in gridPositionList)
```

RogueShooter – All Scripts

```
{
    gridSystemVisualSingleArray[gridPosition.x, gridPosition.z, gridPosition.floor].
    Show(GetGridVisualTypeMaterial(gridVisualType));
}

private void UpdateGridVisuals()
{
    HideAllGridPositions();
    Unit selectedUnit = UnitActionSystem.Instance.GetSelectedUnit();
    if (selectedUnit == null) return;

    BaseAction selectedAction = UnitActionSystem.Instance.GetSelectedAction();

    GridVisualType gridVisualType;

    switch (selectedAction)
    {
        default:
        case MoveAction moveAction:
            gridVisualType = GridVisualType.white;
            break;
        case TurnTowardsAction turnTowardsAction:
            gridVisualType = GridVisualType.Blue;
            break;
        /*
        case ShootAction shootAction:
            gridVisualType = GridVisualType.Red;
            ShowGridPositionRange(selectedUnit.GetGridPosition(), shootAction.GetMaxShootDistance(), GridVisualType.RedSoft);
            break;
        */
        case ShootAction shootAction:
        {
            gridVisualType = GridSystemVisual.GridVisualType.Red;

            var origin = selectedUnit.GetGridPosition();
            int range = shootAction.GetMaxShootDistance();

            // UUSI: näyttä vain ne ruudut, joihin on LoS ilman korkeita blokkeja tai väli-uniteja
            var visible = VisibilityService.ComputeVisibleTiles(origin, range, occludeByUnits: true);

            // Piirrä "pehmeä kehä" vain näkyvistä ruuduista
            ShowGridPositionList(new List<GridPosition>(visible), GridVisualType.RedSoft);
            break;
        }
        case GrenadeAction grenadeAction:
            gridVisualType = GridVisualType.Yellow;
            break;
        case MeleeAction meleeAction:
            gridVisualType = GridVisualType.Red;
            ShowGridPositionRangeSquare(selectedUnit.GetGridPosition(), 1, GridVisualType.RedSoft);
            break;
    }
}
```

RogueShooter – All Scripts

```
        case InteractAction interactAction:
            gridVisualType = GridVisualType.Blue;
            break;

    }

    ShowGridPositionList(
        selectedAction.GetValidGridPositionList(), gridVisualType);

}

private void UnitActionSystem_OnSelectedActionChanged(object sender, EventArgs e)
{
    UpdateGridVisuals();
}

private void LevelGrid_onAnyUnitMoveGridPosition(object sender, EventArgs e)
{
    UpdateGridVisuals();
}

private void UnitActionSystem_OnBusyChanged(object sender, bool e)
{
    UpdateGridVisuals();
}

private Material GetGridVisualTypeMaterial(GridVisualType gridVisualType)
{
    foreach (GridVisualTypeMaterial gridVisualTypeMaterial in gridVisualTypeMaterialList)
    {
        if (gridVisualTypeMaterial.gridVisualType == gridVisualType)
        {
            return gridVisualTypeMaterial.material;
        }
    }
    Debug.LogError("Cloud not find GridVisualTypeMaterial for GridVisualType" + gridVisualType);
    return null;
}

}
```

RogueShooter – All Scripts

Assets/scripts/Grid/GridSystemVisualSingle.cs

```
using UnityEngine;

/// <summary>
/// This class is responsible for visualizing a single grid position in the game.
/// It contains a MeshRenderer component that is used to show or hide the visual representation of the grid position.
/// </summary>
public class GridSystemVisualSingle : MonoBehaviour
{
    [SerializeField] private MeshRenderer meshRenderer;

    public void Show(Material material)
    {
        meshRenderer.enabled = true;
        meshRenderer.material = material;
    }

    public void Hide()
    {
        meshRenderer.enabled = false;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/LevelGrid.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;

/// @file LevelGrid.cs
/// @brief Core grid management system for RogueShooter.
///
/// The LevelGrid defines and manages the tactical grid used by all gameplay systems.
/// It stores spatial occupancy data, translates between world-space and grid-space coordinates,
/// and provides the structural backbone for the pathfinding and edge-baking systems.
///
/// ### Overview
/// Each level in RogueShooter is represented as one or more layered grids (floors).
/// Every grid cell corresponds to a physical area in the game world and may contain
/// references to units, obstacles, or other gameplay entities. The LevelGrid keeps
/// this data synchronized with the actual scene state and provides efficient lookup
/// and update operations.
///
/// ### System integration
/// - **LevelGrid** - Manages spatial layout, unit occupancy, and coordinate conversions.
/// - **EdgeBaker** - Uses LevelGrid data (width, height, cell size, floor count) to detect edge obstacles.
/// - **PathFinding** - Queries LevelGrid to determine walkable areas and world→grid mapping for A* searches.
///
/// ### Key features
/// - Multi-floor grid architecture with configurable width, height, and cell size.
/// - Fast world→grid coordinate conversion for unit and object placement.
/// - Real-time occupancy tracking of all units on the grid.
/// - Scene rebuild capability (`RebuildOccupancyFromScene`) for reinitializing unit positions after reload.
/// - Event-driven notifications for unit movement (`onAnyUnitMoveGridPosition`).
///
/// ### Why this exists in RogueShooter
/// - The game's turn-based, tile-based design requires precise spatial logic independent of Unity's physics.
/// - Provides a unified "source of truth" for spatial relationships used by both AI and player systems.
/// - Keeps the game's tactical layer deterministic, debuggable, and efficient.
///
/// In summary, this file defines the foundational grid layer of RogueShooter's tactical engine,
/// acting as the shared coordinate and occupancy system for all movement, visibility, and interaction logic.
///
/// <summary>
/// This class is responsible for managing the game's grid system.
/// It keeps track of the units on the grid and their positions.
/// It provides methods to add, remove, and move units on the grid.
/// Note: This class Script Execution Order is set to be executed after UnitManager.cs. High priority.
/// </summary>
public class LevelGrid : MonoBehaviour
{
    public static LevelGrid Instance { get; private set; }

    public const float FLOOR_HEIGHT = 4f;
    public event EventHandler onAnyUnitMoveGridPosition;
```

RogueShooter – All Scripts

```
[SerializeField] private Transform debugPrefab;
// [SerializeField] private bool debugVisible = true;
[SerializeField] private int width;
[SerializeField] private int height;
private const float CELLSIZE = 2f;
[SerializeField] private int floorAmount;

private List<GridSystem<GridObject>> gridSystemList;

private void Awake()
{
    // Ensure that there is only one instance in the scene
    if (Instance != null)
    {
        Debug.LogError("LevelGrid: More than one LevelGrid in the scene!" + transform + " " + Instance);
        Destroy(gameObject);
        return;
    }
    Instance = this;

    gridSystemList = new List<GridSystem<GridObject>>(floorAmount);

    for (int floor = 0; floor < floorAmount; floor++)
    {
        var gridSystem = new GridSystem<GridObject>(
            width, height, CELLSIZE, floor, FLOOR_HEIGHT,
            (GridSystem<GridObject> g, GridPosition gridPosition) => new GridObject(g, gridPosition)
        );
        //gridSystem.CreateDebugObjects(debugPrefab);
        gridSystemList.Add(gridSystem); // NullReferenceException: Object reference not set to an instance of an object!
    }
}

private void Start()
{
    PathFinding.Instance.Setup(width, height, CELLSIZE, floorAmount);
}

public GridSystem<GridObject> GetGridSystem(int floor)
{
    if (floor < 0 || floor >= gridSystemList.Count) { Debug.LogError($"Invalid floor {floor}"); return null; }
    return gridSystemList[floor];
}

public int GetFloor(Vector3 worldPosition)
{
    return Mathf.RoundToInt(worldPosition.y / FLOOR_HEIGHT);
}
```


RogueShooter – All Scripts

```
public void AddUnitAtGridPosition(GridPosition gridPosition, Unit unit)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    gridObject.AddUnit(unit);
}

public List<Unit> GetUnitListAtGridPosition(GridPosition gridPosition)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    if (gridObject != null)
    {
        return gridObject.GetUnitList();
    }
    return null;
}

public IInteractable GetInteractableAtGridPosition(GridPosition gridPosition)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    if (gridObject != null)
    {
        return gridObject.GetInteractable();
    }
    return null;
}

public void SetInteractableAtGridPosition(GridPosition gridPosition, IInteractable interactable)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    gridObject?.SetInteractable(interactable);
}

public void RemoveUnitAtGridPosition(GridPosition gridPosition, Unit unit)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    gridObject.RemoveUnit(unit);
}

public void UnitMoveToGridPosition(GridPosition fromGridPosition, GridPosition toGridPosition, Unit unit)
{
    RemoveUnitAtGridPosition(fromGridPosition, unit);
    AddUnitAtGridPosition(toGridPosition, unit);
    onAnyUnitMoveGridPosition?.Invoke(this, EventArgs.Empty);
}

public GridPosition GetGridPosition(Vector3 worldPosition)
{
    int floor = GetFloor(worldPosition);
    return GetGridSystem(floor).GetGridPosition(worldPosition);
}
```

RogueShooter – All Scripts

```
public Vector3 GetWorldPosition(GridPosition gridPosition)
{
    return GetGridSystem(gridPosition.floor).GetWorldPosition(gridPosition);
}

public bool IsValidGridPosition(GridPosition gridPosition)
{
    if (gridPosition.floor < 0 || gridPosition.floor >= floorAmount)
    {
        return false;
    }
    return GetGridSystem(gridPosition.floor).IsValidGridPosition(gridPosition);
}

public int GetWidth() => GetGridSystem(0).GetWidth();

public int GetHeight() => GetGridSystem(0).GetHeight();

public int GetFloorAmount() => floorAmount;

public float GetCellSize() => CELLSIZE;

public bool HasAnyUnitOnGridPosition(GridPosition gridPosition)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    return gridObject.HasAnyUnit();
}

public Unit GetUnitAtGridPosition(GridPosition gridPosition)
{
    GridObject gridObject = GetGridSystem(gridPosition.floor).GetGridObject(gridPosition);
    return gridObject.GetUnit();
}

public void ClearAllOccupancy()
{
    if (gridSystemList == null) return;

    for (int floor = 0; floor < gridSystemList.Count; floor++)
    {
        var grid = gridSystemList[floor];
        if (grid == null) continue;

        for (int x = 0; x < grid.GetWidth(); x++)
        {
            for (int z = 0; z < grid.GetHeight(); z++)
            {
                var gp = new GridPosition(x, z, floor);
                var gridObj = grid.GetGridObject(gp);
                gridObj?.GetUnitList()?.Clear();
            }
        }
    }
}
```

RogueShooter – All Scripts

```
    }  
}  
  
/// <summary>  
/// Rebuilds all grid occupancy data by scanning the current scene for active units.  
///  
/// What it does:  
/// - Clears all existing unit occupancy from the <see cref="LevelGrid"/>.  
/// - Finds every active <see cref="Unit"/> in the scene.  
/// - Converts each unit's world position into a grid position and re-registers it.  
///  
/// Why this exists in RogueShooter:  
/// - Used after a scene or level is (re)loaded to ensure that the grid accurately reflects  
///   the current in-scene unit placements.  
/// - Called by systems like <see cref="GameModeSelectUI"/> and <see cref="ServerBootstrap"/>  
///   to synchronize game state after spawning or initialization events.  
///  
/// Implementation notes:  
/// - Intended for runtime reinitialization, not per-frame updates.  
/// - Safe to call at any time; automatically rebuilds the occupancy layer from scratch.  
/// </summary>  
public void RebuildOccupancyFromScene()  
{  
    ClearAllOccupancy();  
    var units = FindObjectsByType<Unit>(FindObjectsSortMode.None);  
    foreach (var u in units)  
    {  
        var gp = GetGridPosition(u.transform.position);  
        AddUnitAtGridPosition(gp, u);  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/LoSBlockerRegistry.cs

```
using System.Collections.Generic;

public static class LoSBlockerRegistry
{
    // Kuinka monella "tall-blockerilla" ruutu on peitetty
    private static readonly Dictionary<GridPosition, int> _counts = new();

    public static void Reset() => _counts.Clear();

    public static void AddTiles(IEnumerable<GridPosition> tiles)
    {
        foreach (var t in tiles)
        {
            _counts.TryGetValue(t, out int c);
            _counts[t] = c + 1;
        }
    }

    public static void RemoveTiles(IEnumerable<GridPosition> tiles)
    {
        foreach (var t in tiles)
        {
            if (!_counts.TryGetValue(t, out int c)) continue;
            c--;
            if (c <= 0) _counts.Remove(t);
            else _counts[t] = c;
        }
    }

    public static bool TileHasTallBlocker(GridPosition p)
        => _counts.TryGetValue(p, out int c) && c > 0;
}
```

RogueShooter – All Scripts

Assets/scripts/Grid/VisibilityService.cs

```
using System.Collections.Generic;
using UnityEngine;

public static class VisibilityService
{
    // Kynnyksen voi myöhemmin lukea EdgeBakerista, nyt selkeä vakio
    private const float LOS_BLOCK_HEIGHT_Y = 1.7f;

    // Välimuisti ruudun "onko korkea blokkeri" -tiedolle
    // Tyhjennä esim. vuoron vaihtuessa tai kun kenttä muuttuu
    private static readonly Dictionary<GridPosition, bool> _tallBlockerCache = new();

    /// <summary>
    /// Palauttaa näkyvät ruudut (sama floor) originista maxRangeen.
    /// Estäjät: 1) koko-ruudun korkeat esteet (PF: !walkable), 2) välissä seisovat unitit.
    /// Ei käytä EdgeBakereita tässä vaiheessa.
    /// </summary>
    public static HashSet<GridPosition> ComputeVisibleTiles(GridPosition origin, int maxRange, bool occludeByUnits = true)
    {
        var visible = new HashSet<GridPosition>();
        var lg = LevelGrid.Instance;
        var pf = PathFinding.Instance;
        if (lg == null || pf == null) return visible;

        for (int dx = -maxRange; dx <= maxRange; dx++)
        {
            for (int dz = -maxRange; dz <= maxRange; dz++)
            {
                var cost = SircleCalculator.Sircle(dx, dz);
                if (cost > 10 * maxRange) continue;

                var gp = new GridPosition(origin.x + dx, origin.z + dz, origin.floor);
                if (!lg.IsValidGridPosition(gp)) continue;

                if (HasLineOfSight(origin, gp, occludeByUnits))
                    visible.Add(gp);
            }
        }
        return visible;
    }

    /// <summary>
    /// Palauttaa true, jos ruudussa on Obstacles-layerin kollidereita,
    /// joiden "top" ylittää kynnykskorkeuden ruudun pohjasta laskien.
    /// </summary>
    private static bool TileHasTallBlocker(GridPosition p)
    {
        if (_tallBlockerCache.TryGetValue(p, out bool cached))
            return cached;
    }
}
```

RogueShooter – All Scripts

```
var lg = LevelGrid.Instance;
if (lg == null) return false;

// Ruudun "pohja" - käytä samaa metodologia, millä sijoitat unittien y:n
Vector3 basePos = lg.GetWorldPosition(p); // ruudun keskipiste pohjatasolla
float baseY = basePos.y;

// Kapea laatikko ruudun alueelle, korkeus riittää useimpiin esteisiin
float half = lg.GetCellSize() * 0.5f * 0.9f;
Vector3 halfExtents = new(half, 3.0f, half); // 6 m kokonaiskorkeus
Vector3 center = basePos + Vector3.up * halfExtents.y;

// Vain Obstacles-layer
int obstaclesMask = LayerMask.GetMask("Obstacles");

var cols = Physics.OverlapBox(
    center, halfExtents, Quaternion.identity,
    obstaclesMask, QueryTriggerInteraction.Ignore
);

float maxTopAboveBase = 0f;
for (int i = 0; i < cols.Length; i++)
{
    // Kuinka korkealle kollideri ulottuu tämän ruudun "pohjasta" mitattuna
    float topRel = cols[i].bounds.max.y - baseY;
    if (topRel > maxTopAboveBase) maxTopAboveBase = topRel;
}

bool isTall = maxTopAboveBase >= LOS_BLOCK_HEIGHT_Y;
_tallBlockerCache[p] = isTall;
return isTall;
}

/// <summary>Tyhjennä korkeablokkeri-välimuisti (kutsu esim. vuoron vaihtuessa, kun yksiköt/liikuteltavat esteet liikkuvat tai kun map spawnaa asioita).</summary>
public static void ResetTallBlockerCache() => _tallBlockerCache.Clear();

/// <summary>
/// Näkötesti ruuturajojen yli. Ei käytä fysiikkaa; nojaa PF:n nodeihin ja unit-miehitykseen.
/// </summary>
public static bool HasLineOfSight(GridPosition from, GridPosition to, bool occludeByUnits = true)
{
    if (from.floor != to.floor) return false; // pidetään helppona tässä vaiheessa

    var lg = LevelGrid.Instance;
    var pf = PathFinding.Instance;
    if (lg == null || pf == null) return false;

    GridPosition prev = from;

    foreach (var p in Line(from, to))
```

RogueShooter – All Scripts

```
{
    if (p.Equals(from))
    {
        prev = p;
        continue;
    }
    // lähtöruutu ei estä
    if (!lg.IsValidGridPosition(p)) return false;

    if (CrossesTallEdge(prev, p))
        return false;

    if (LoSBlockerRegistry.TileHasTallBlocker(p))
        return false;

    // 2) Välissä seisova unit estää LoS:n (mutta kohderuutu saa sisältää unittinsa)
    if (occludeByUnits && !p.Equals(to) && lg.HasAnyUnitOnGridPosition(p))
        return false;

    prev = p;
}
return true;
}

/// <summary>
/// Bresenham 2D viiva ruutujen (x,z) yli; floor säilyy samana.
/// </summary>
private static IEnumerable<GridPosition> Line(GridPosition from, GridPosition to)
{
    int x0 = from.x, z0 = from.z;
    int x1 = to.x, z1 = to.z;

    int dx = Mathf.Abs(x1 - x0);
    int dz = Mathf.Abs(z1 - z0);
    int sx = x0 < x1 ? 1 : -1;
    int sz = z0 < z1 ? 1 : -1;
    int err = dx - dz;

    // mukaan myös lähtö
    yield return from;

    while (x0 != x1 || z0 != z1)
    {
        int e2 = 2 * err;
        if (e2 > -dz) { err -= dz; x0 += sx; }
        if (e2 < dx) { err += dx; z0 += sz; }
        yield return new GridPosition(x0, z0, from.floor);
    }
}

// Jos haluat sallivamman kulmapeekkaamisen, aseta false (blokkaa vasta kun MOLEMMAT reunat ovat TallWall)
private const bool DIAGONAL_BLOCK_IF_ANY = true;
```

RogueShooter – All Scripts

```
/// <summary>
/// Palauttaa true, jos siirtymä ruudusta 'a' ruutuun 'b' ylittää TallWall-reunan.
/// Käyttää EdgeOcclusion.HasTallWall -dataa (N/E/S/W-bitit per reuna).
/// </summary>
private static bool CrossesTallEdge(GridPosition a, GridPosition b)
{
    int dx = b.x - a.x;
    int dz = b.z - a.z;
    if (dx == 0 && dz == 0) return false;

    // Kardinaaliset askeleet (Bresenham tuottaa yksiaskelisiä steppejä)
    if (dx == 1 && dz == 0) return EdgeOcclusion.HasTallWall(a, EdgeMask.E);
    if (dx == -1 && dz == 0) return EdgeOcclusion.HasTallWall(a, EdgeMask.W);
    if (dx == 0 && dz == 1) return EdgeOcclusion.HasTallWall(a, EdgeMask.N);
    if (dx == 0 && dz == -1) return EdgeOcclusion.HasTallWall(a, EdgeMask.S);

    // Diagonaalit: tarkista kaksi mahdollista reunaa kulmassa
    if (dx == 1 && dz == 1)
    {
        bool e = EdgeOcclusion.HasTallWall(a, EdgeMask.E);
        bool n = EdgeOcclusion.HasTallWall(new GridPosition(a.x + 1, a.z, a.floor), EdgeMask.N);
        return DIAGONAL_BLOCK_IF_ANY ? (e || n) : (e && n);
    }
    if (dx == 1 && dz == -1)
    {
        bool e = EdgeOcclusion.HasTallWall(a, EdgeMask.E);
        bool s = EdgeOcclusion.HasTallWall(new GridPosition(a.x + 1, a.z - 1, a.floor), EdgeMask.S);
        return DIAGONAL_BLOCK_IF_ANY ? (e || s) : (e && s);
    }
    if (dx == -1 && dz == 1)
    {
        bool w = EdgeOcclusion.HasTallWall(a, EdgeMask.W);
        bool n = EdgeOcclusion.HasTallWall(new GridPosition(a.x - 1, a.z, a.floor), EdgeMask.N);
        return DIAGONAL_BLOCK_IF_ANY ? (w || n) : (w && n);
    }
    if (dx == -1 && dz == -1)
    {
        bool w = EdgeOcclusion.HasTallWall(a, EdgeMask.W);
        bool s = EdgeOcclusion.HasTallWall(new GridPosition(a.x - 1, a.z - 1, a.floor), EdgeMask.S);
        return DIAGONAL_BLOCK_IF_ANY ? (w || s) : (w && s);
    }

    // Diagonaalit: tarkista kaksi mahdollista reunaa kulmassa
    /*
    if (dx == 1 && dz == 1)
    {
        bool e = EdgeOcclusion.HasTallWall(a, EdgeMask.E);
        bool n = EdgeOcclusion.HasTallWall(a, EdgeMask.N); // Muutettu: käytä ruutua 'a'
        return DIAGONAL_BLOCK_IF_ANY ? (e || n) : (e && n);
    }
    if (dx == 1 && dz == -1)
```


RogueShooter – All Scripts

```
{
    bool e = EdgeOcclusion.HasTallWall(a, EdgeMask.E);
    bool s = EdgeOcclusion.HasTallWall(a, EdgeMask.S); // Muutettu: käytä ruutua 'a'
    return DIAGONAL_BLOCK_IF_ANY ? (e || s) : (e && s);
}
if (dx == -1 && dz == 1)
{
    bool w = EdgeOcclusion.HasTallWall(a, EdgeMask.W);
    bool n = EdgeOcclusion.HasTallWall(a, EdgeMask.N); // Muutettu: käytä ruutua 'a'
    return DIAGONAL_BLOCK_IF_ANY ? (w || n) : (w && n);
}
if (dx == -1 && dz == -1)
{
    bool w = EdgeOcclusion.HasTallWall(a, EdgeMask.W);
    bool s = EdgeOcclusion.HasTallWall(a, EdgeMask.S); // Muutettu: käytä ruutua 'a'
    return DIAGONAL_BLOCK_IF_ANY ? (w || s) : (w && s);
}
*/

// Turvakäsittely: jos askel olisi jostain syystä > 1 (ei pitäisi tapahtua Bresenhamilla),
// pilko se yksiaskeleisiin ja tarkista rekursiivisesti.
int steps = Mathf.Max(Mathf.Abs(dx), Mathf.Abs(dz));
var prev = a;
int stepx = Mathf.Clamp(dx, -1, 1);
int stepz = Mathf.Clamp(dz, -1, 1);
for (int i = 1; i <= steps; i++)
{
    var mid = new GridPosition(a.x + stepx * i, a.z + stepz * i, a.floor);
    if (CrossesTallEdge(prev, mid)) return true;
    prev = mid;
}
return false;
}
}
```

RogueShooter – All Scripts

Assets/scripts/Helpers/AllUnitsList.cs

```
using Mirror;
using UnityEngine;
/// <summary>
/// Only used for cleaning the field from units.
/// </summary>
[DisallowMultipleComponent]
public class FriendlyUnit : NetworkBehaviour {}

[DisallowMultipleComponent]
public class EnemyUnit : NetworkBehaviour {}
```

RogueShooter – All Scripts

Assets/scripts/Helpers/AuthorityHelper.cs

```
using Mirror;

public static class AuthorityHelper
{
    /// <summary>
    /// Checks if the given NetworkBehaviour has local control.
    /// Prevents the player from controlling the object if they are not the owner.
    /// </summary>
    public static bool HasLocalControl(NetworkBehaviour netBehaviour)
    {
        return NetworkClient.isConnected && !netBehaviour.isOwned;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Helpers/BalanceDB.cs

```
using UnityEngine;

public static class BalanceDB {
    const string RES_PATH = "CombatRanges"; // => Assets/Resources/CombatRanges.asset
    static CombatRanges _cached;
    static bool _warned;

    public static CombatRanges Ranges {
        get {
            if (GameBalance.R != null) return GameBalance.R;           // ensisijainen
            if (_cached != null) return _cached;                       // cache
            _cached = UnityEngine.Resources.Load<CombatRanges>(RES_PATH); // fallback
            if (_cached == null && !_warned) {
                _warned = true;
                Debug.LogWarning("[BalanceDB] CombatRanges puuttuu.\n"+
                                "- Suositus: aseta se Core>GameBalance.ranges -kenttään.\n"+
                                "- Fallback: laita asset polkuun Assets/Resources/"+RES_PATH+".asset");
            }
            return _cached;
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Helpers/FieldCleaner.cs

```
using System.Linq;
using UnityEngine;
using UnityEngine.SceneManagement;
using Utp;

public class FieldCleaner : MonoBehaviour
{
    public static void ClearAll()
    {
        // Varmista: älä yritä siivota puhtaalta clientiltä verkossa
        if (GameNetworkManager.Instance != null &&
            GameNetworkManager.Instance.GetNetWorkClientConnected() &&
            !GameNetworkManager.Instance.GetNetWorkServerActive())
        {
            Debug.LogWarning("[FieldCleaner] Don't clear field from a pure client.");
            return;
        }

        // Find all friendly and enemy units (also inactive, just in case)
        var friendlies = Resources.FindObjectsOfTypeAll<FriendlyUnit>()
            .Where(u => u != null && u.gameObject.scene.IsValid());
        var enemies = Resources.FindObjectsOfTypeAll<EnemyUnit>()
            .Where(u => u != null && u.gameObject.scene.IsValid());

        foreach (var u in friendlies) Despawn(u.gameObject);
        foreach (var e in enemies) Despawn(e.gameObject);

        UnitManager.Instance.ClearAllUnitLists();
        LevelGrid.Instance.ClearAllOccupancy();
    }

    static void Despawn(GameObject go)
    {
        // if server is active, use Mirror's destroy; otherwise normal Unity Destroy
        if (GameNetworkManager.Instance.GetNetWorkServerActive())
        {
            GameNetworkManager.Instance.NetworkDestroy(go);
        }
        else
        {
            Destroy(go);
        }
    }

    public static void ReloadMap()
    {

```

RogueShooter – All Scripts

```
        Debug.Log("[FieldCleaner] Reloading map.");  
        SceneManager.LoadScene(SceneManager.GetActiveScene().name);  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/DebrisUtil.cs

```
using UnityEngine;
using UnityEngine.SceneManagement;

/// <summary>
/// Kevyt util: poista Debris-layerillä olevat paikalliset GameObjectit kaikista ei-Core -sceneistä.
/// Tämä on pelkkä "varmistuskerros" - varsinainen siivous tapahtuu jo scene-unloadissa.
/// </summary>
public static class DebrisUtil
{
    public static int DestroyAllDebrisExceptCore(string coreName = "Core", string debrisLayerName = "Debris")
    {
        int debrisLayer = LayerMask.NameToLayer(debrisLayerName);
        if (debrisLayer == -1) return 0;

        int destroyed = 0;
        for (int i = 0; i < SceneManager.sceneCount; i++)
        {
            var s = SceneManager.GetSceneAt(i);
            if (!s.isLoaded || s.name == coreName) continue;

            var roots = s.GetRootGameObjects();
            for (int r = 0; r < roots.Length; r++)
            {
                destroyed += DestroyDebrisRecursive(roots[r].transform, debrisLayer);
            }
        }
        return destroyed;
    }

    private static int DestroyDebrisRecursive(Transform t, int debrisLayer)
    {
        int cnt = 0;
        for (int i = t.childCount - 1; i >= 0; i--)
        {
            var c = t.GetChild(i);
            if (c.gameObject.layer == debrisLayer)
            {
                Object.Destroy(c.gameObject);
                cnt++;
            }
            else
            {
                cnt += DestroyDebrisRecursive(c, debrisLayer);
            }
        }
        return cnt;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/LevelCatalog.cs

```
// RogueShooter/LevelCatalog.cs
using System;
using System.Collections.Generic;
using UnityEngine;

#if UNITY_EDITOR
using UnityEditor;
#endif

[CreateAssetMenu(fileName = "LevelCatalog", menuName = "RogueShooter/Level Catalog")]
public class LevelCatalog : ScriptableObject {
    public List<LevelEntry> levels = new();

    public int Count => levels?.Count ?? 0;
    public LevelEntry Get(int i) => (i >= 0 && i < Count) ? levels[i] : null;
    public int IndexOfScene(string sceneName) => levels.FindIndex(l => l != null && l.sceneName == sceneName);

    private void OnValidate()
    {
#if UNITY_EDITOR
        foreach (var l in levels)
        {
            if (l == null || string.IsNullOrEmpty(l.sceneName)) continue;
            bool inBuild = false;
            foreach (var s in EditorBuildSettings.scenes)
            {
                if (s.enabled && s.path.EndsWith($"{l.sceneName}.unity")) { inBuild = true; break; }
            }
            if (!inBuild)
                Debug.LogWarning($"[LevelCatalog] '{l.sceneName}' ei ole Build Settingsissä (enabled).");
        }
#endif
    }
}

[Serializable]
public class LevelEntry
{
    [Tooltip("Scene name täsmälleen Build Settingsissä")]
    public string sceneName;
    public string displayName;
    public Sprite thumbnail;

    // Valinnainen metadata editorityöhön
    public Vector3Int gridSize = new(30, 1, 30);
    public int floors = 1;
}
```


RogueShooter – All Scripts

Assets/scripts/LevelCreation/LevelLoader.cs

```
using System;
using System.Collections;
using UnityEngine;
using UnityEngine.SceneManagement;

public class LevelLoader : MonoBehaviour
{
    public static LevelLoader Instance { get; private set; }

    [SerializeField] private string coreSceneName = "Core";
    [SerializeField] private string defaultLevel = "Level 0";

    public string CoreSceneName => coreSceneName;
    public string DefaultLevel => defaultLevel;
    public string CurrentLevel { get; private set; }

    // [SerializeField] private bool forceDefaultOnStart = true;

    // --- NÄMÄ KAKSI UUTTA ---
    public static bool IsServerLevelReady { get; private set; }
    public static void SetServerLevelReady(bool ready) => IsServerLevelReady = ready;

    // Event pysyy LevelLoaderissa; muiden pitää kutsua RaiseLevelReady(...)
    public static event Action<Scene> LevelReady;
    public static void RaiseLevelReady(Scene scene) => LevelReady?.Invoke(scene);

    [SerializeField] private LevelCatalog catalog;
    [SerializeField] private int currentIndex;

#if UNITY_EDITOR
    private const string EDITOR_REQ_KEY = "RS_EditorRequestedLevel";
#endif

    private void Awake()
    {
        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;

#if UNITY_EDITOR
        // 1) Lue editorin one-shot-pyyntö
        string req = PlayerPrefs.GetString(EDITOR_REQ_KEY, string.Empty);
        if (!string.IsNullOrEmpty(req))
        {
            // 2) Siivoa avain heti (one-shot)
            PlayerPrefs.DeleteKey(EDITOR_REQ_KEY);

            // 3) Varmista että kenttä on ladattavissa (Build Settingsissä)
            if (Application.CanStreamedLevelBeLoaded(req))
            {
                RaiseLevelReady(SceneManager.GetSceneByName(req));
            }
        }
#endif
    }
}
```

RogueShooter – All Scripts

```
        {
            // 4) Ohjaa sekä CurrentLevel että DefaultLevel tähän
            CurrentLevel = req;
            defaultLevel = req;

            Debug.Log($"[LevelLoader] Editor one-shot → Current & Default = '{req}'");
        }
        else
        {
            Debug.LogWarning($"[LevelLoader] Pyydetty '{req}', mutta sitä ei löydy Build Settingsistä.");
        }
    }
#endif
    // if (string.IsNullOrEmpty(CurrentLevel)) CurrentLevel = defaultLevel;
}

public void LoadByIndex(int index)
{
    StartCoroutine(Co_LoadLocal(index));
}

public void Reload() => LoadByIndex(currentIndex);

private IEnumerator Co_LoadLocal(int index)
{
    // Unload edellinen, load uusi, set active...
    // Sama pattern kuin NetLevelLoaderissa, mutta ilman RPC:itä
    currentIndex = index;
    yield break;
}

public void StartLocalReload(string levelName = null)
{
    var target = string.IsNullOrEmpty(levelName) ? CurrentLevel ?? defaultLevel : levelName;
    StopAllCoroutines();
}

// Kutsu tämä Play Again -napista OFFLINE-tilassa
public void ReloadOffline(string levelName = null)
{
    var target = string.IsNullOrEmpty(levelName) ? (CurrentLevel ?? DefaultLevel) : levelName;
    StopAllCoroutines();
    StartCoroutine(Co_ReloadOffline(target));
}

private IEnumerator Co_ReloadOffline(string levelName)
{
    string coreName = CoreSceneName ?? "Core";

    Debug.Log($"[LevelLoader] ===== OFFLINE RELOAD START: '{levelName}' =====");

    // 0) Lista ennen (debug)
```

RogueShooter – All Scripts

```
for (int i = 0; i < SceneManager.sceneCount; i++)
{
    var s = SceneManager.GetSceneAt(i);
    Debug.Log($"[LevelLoader] BEFORE: {i} → '{s.name}' (loaded={s.isLoaded})");
}

// 1) Pura kaikki ei-Core -scenet
for (int i = 0; i < SceneManager.sceneCount; i++)
{
    var s = SceneManager.GetSceneAt(i);
    if (!s.isLoaded || s.name == coreName) continue;

    Debug.Log($"[LevelLoader] Unloading scene '{s.name}'");
    var op = SceneManager.UnloadSceneAsync(s);
    if (op != null) while (!op.isDone) yield return null;

    // koska sceneCount muuttuu, aloita alusta
    i = -1;
}

// 2) Varmista Core ladattu + aktiivinen
var core = SceneManager.GetSceneByName(coreName);
if (!core.IsValid() || !core.isLoaded)
{
    Debug.Log($"[LevelLoader] Loading Core scene");
    var loadCore = SceneManager.LoadSceneAsync(coreName, LoadSceneMode.Additive);
    while (!loadCore.isDone) yield return null;
    core = SceneManager.GetSceneByName(coreName);
}
SceneManager.SetActiveScene(core);

// (siivoo roskat - vapauttaa tuhotun scenen asetteja)
yield return Resources.UnloadUnusedAssets();
yield return null;

// 3) Lataa uusi taso additiivisesti
Debug.Log($"[LevelLoader] Loading new level '{levelName}'");
var op2 = SceneManager.LoadSceneAsync(levelName, LoadSceneMode.Additive);
while (!op2.isDone) yield return null;

var map = SceneManager.GetSceneByName(levelName);
if (!map.IsValid() || !map.isLoaded)
{
    Debug.LogError($"[LevelLoader] Failed to load '{levelName}'. Is it in Build Settings?");
    yield break;
}

// 4) Aseta map aktiiviseksi yhdeksi frameksi (Start/Awake/OnEnable → placeholderit spawn)
SceneManager.SetActiveScene(map);
yield return null; // 1 frame
yield return new WaitForEndOfFrame(); // varmistaa että scene-Startit ehtii
```

RogueShooter – All Scripts

```
// 5) Hookit (kuten OfflineBootissa)
var edgeBaker = UnityEngine.Object.FindFirstObjectByType<EdgeBaker>();
if (edgeBaker != null) edgeBaker.BakeAllEdges();

// (valinn.) jos käytössä: miehitys uudelleen sceneen spawnesta
if (LevelGrid.Instance != null) LevelGrid.Instance.RebuildOccupancyFromScene();

// 6) Core takaisin aktiiviseksi, ilmoita että valmis
SceneManager.SetActiveScene(core);
CurrentLevel = levelName;

try { RaiseLevelReady(map); } catch { }

// Debug-listaus
Debug.Log($"[LevelLoader] ===== OFFLINE RELOAD DONE: '{levelName}' =====");
for (int i = 0; i < SceneManager.sceneCount; i++)
{
    var s = SceneManager.GetSceneAt(i);
    Debug.Log($"[LevelLoader] AFTER: {i} → '{s.name}' (loaded={s.isLoaded})");
}
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/MapContentSpawner.cs

```
using System.Collections;
using UnityEngine;
using UnityEngine.SceneManagement;

public class MapContentSpawner : MonoBehaviour // ← EI NetworkBehaviour
{
    private void Start()
    {
        if (!NetMode.IsServer) return;    // varmistus
        LoSBlockerRegistry.Reset();
        StartCoroutine(SpawnThenBake_ServerOnly());
    }

    private IEnumerator SpawnThenBake_ServerOnly()
    {
        Scene mapScene = gameObject.scene;

        var placeholders = FindObjectsByType<ObjectSpawnPlaceholder>(FindObjectsSortMode.None);
        int spawned = 0;
        foreach (var sp in placeholders)
        {
            if (sp.gameObject.scene == mapScene)
            {
                var go = sp.CreateObject();    // tämä jo käyttää SpawnRouteria → assetId-prefab spawn, ei sceneId
                if (go) spawned++;
            }
        }

        // Odotetaan, että LevelGrid/PathFinding/EdgeBaker ovat valmiit
        yield return new WaitUntil(() =>
            EdgeBaker.Instance != null &&
            LevelGrid.Instance != null &&
            PathFinding.Instance != null
        );
        yield return null;

        // Server bake
        EdgeBaker.Instance.BakeAllEdges();
    }
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/PostLevelBootstrap.cs

```
using System.Collections;
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;

/// <summary>
/// Tämä toistaiseksi auttaa vain Solopelissä alussa lataamaan pelaajan yksiköt.
/// </summary>
public class PostLevelBootstrap : MonoBehaviour
{
    private void OnEnable()
    {
        LevelLoader.LevelReady += OnLevelReady;
    }

    private void OnDisable()
    {
        LevelLoader.LevelReady -= OnLevelReady;
    }

    private void OnLevelReady(Scene mapScene)
    {
        if (NetMode.IsRemoteClient) return;
        StartCoroutine(Co_BootstrapAfterLevelReady(mapScene));
    }

    private IEnumerator Co_BootstrapAfterLevelReady(Scene mapScene)
    {
        // Odota 1 frame että Level-skenen Start/OnStartServer ehtivät
        yield return null;

        var spawner = FindFirstObjectByType<SpawnUnitsCoordinator>(FindObjectsInactive.Include);

        if (!spawner)
        {
            Debug.LogError("[Bootstrap] SpawnUnitsCoordinator not found in Level scene.");
            yield break;
        }

        // OFFLINE: (jos haluat tukea SP-tilan bootstrapin tässä)
        if (!NetworkClient.active && !NetworkServer.active)
        {
            // Kutsu suoraan omaa SP-metodiasi, esim:
            spawner.SpawnSinglePlayerUnits();
            LevelGrid.Instance?.RebuildOccupancyFromScene();
            TurnSystem.Instance?.ResetAndBegin();
        }
    }
}
```

```
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/SpawnUnitsCoordinator.cs

```
using UnityEngine;
using UnityEngine.SceneManagement;
using Mirror;
using System.Collections.Generic;
using System.Linq;

public class SpawnUnitsCoordinator : MonoBehaviour
{
    public static SpawnUnitsCoordinator Instance { get; private set; }

    // ...luokan sisälle:
    [Header("Use placeholders instead of arrays")]
    public bool usePlaceholders = true;

    [Tooltip("Jos true, koordinaattori disabloi/tuhouttaa käytetyt placeholderit serverillä heti spawnin jälkeen.")]
    public bool consumePlaceholdersOnServer = true;

    private bool enemiesSpawned;

    [Header("Co-op squad prefabs")]
    public GameObject unitHostPrefab;
    public GameObject unitClientPrefab;

    [Header("Enemy spawn (Co-op)")]
    public GameObject enemyPrefab;

    [Header("Spawn positions (world coords on your grid)")]
    public Vector3[] hostSpawnPositions = {
        new Vector3(0, 0, 0),
        new Vector3(2, 0, 0),
    };
    public Vector3[] clientSpawnPositions = {
        new Vector3(0, 0, 6),
        new Vector3(2, 0, 6),
    };
    public Vector3[] enemySpawnPositions = {
        new Vector3(4, 0, 8),
        new Vector3(6, 0, 8),
    };

    void Awake()
    {
        if (Instance != null && Instance != this)
        {
            var myScene = gameObject.scene;
            var oldScene = Instance.gameObject.scene;

            // Jos edellinen on eri scenessä (jääne purkamatta), tuhoa se ja ota tämä käyttöön
            if (oldScene != myScene)
            {

```


RogueShooter – All Scripts

```
        Debug.LogWarning($"[SpawnUnitsCoordinator] Replacing leftover instance from scene '{oldScene.name}' with current '{myScene.name}'.");
        Destroy(Instance.gameObject);
        Instance = this;
        return;
    }

    // Sama scene → tämä on tupla oikeasti: tuhoa tämä
    Debug.LogError($"There's more than one SpawnUnitsCoordinator! {Instance} - {this}");
    Destroy(gameObject);
    return;
}

Instance = this;
}

void OnDestroy()
{
    if (Instance == this) Instance = null;
}

public GameObject[] SpawnPlayersForNetwork(NetworkConnectionToClient conn, bool isHost)
{
    GameObject unitPrefab = GetUnitPrefabForPlayer(isHost);
    Vector3[] spawnPoints = GetSpawnPositionsForPlayer(isHost);

    if (unitPrefab == null)
    {
        Debug.LogError($"[SpawnUnitsCoordinator] {(isHost ? "unitHostPrefab" : "unitClientPrefab")} puuttuu!");
        return null;
    }
    if (spawnPoints == null || spawnPoints.Length == 0)
    {
        Debug.LogError($"[SpawnUnitsCoordinator] {(isHost ? "hostSpawnPositions" : "clientSpawnPositions")} ei ole asetettu!");
        return null;
    }

    var spawnedPlayersUnit = new GameObject[spawnPoints.Length];

    // Hae Level-scene (tämä SpawnUnitsCoordinator on Level-scenessä)
    Scene levelScene = gameObject.scene;
    Debug.Log($"[SpawnUnitsCoordinator] Spawning {spawnPoints.Length} units for {(isHost ? "HOST" : "CLIENT")} to scene '{levelScene.name}'");

    for (int i = 0; i < spawnPoints.Length; i++)
    {
        // Käytä SpawnRouteria → varmistaa että unitit menevät Level-sceneen
        var playerUnit = SpawnRouter.SpawnNetworkServer(
            prefab: unitPrefab,
            pos: spawnPoints[i],
            rot: Quaternion.identity,
            source: transform, // Käytä tämän objektin sceneä
            sceneName: levelScene.name,
            parent: null,
```

RogueShooter – All Scripts

```
        owner: conn,
        beforeSpawn: (go) =>
        {
            if (go.TryGetComponent<Unit>(out var u) && conn.identity != null)
                u.OwnerId = conn.identity.netId;
        }
    );

    Debug.Log($"[SpawnUnitsCoordinator] Spawned unit '{playerUnit.name}' at {spawnPoints[i]} in scene '{playerUnit.scene.name}");
    spawnedPlayersUnit[i] = playerUnit;
}

return spawnedPlayersUnit;
}

public GameObject GetUnitPrefabForPlayer(bool isHost)
{
    if (unitHostPrefab == null || unitClientPrefab == null)
    {
        Debug.LogError("Unit prefab references not set in SpawnUnitsCoordinator!");
        return null;
    }

    return isHost ? unitHostPrefab : unitClientPrefab;
}

public void SetEnemiesSpawned(bool value)
{
    enemiesSpawned = value;
}

public bool AreEnemiesSpawned()
{
    return enemiesSpawned;
}

public GameObject GetEnemyPrefab()
{
    if (enemyPrefab == null)
    {
        Debug.LogError("Enemy prefab reference not set in SpawnUnitsCoordinator!");
        return null;
    }

    return enemyPrefab;
}

// Get Spawn positions from placeholders in the scene

private Vector3[] GetSpawnPositionsFromPlaceholders(UnitSpawnPlaceholder.Side side)
{
    var scene = gameObject.scene;
```

RogueShooter – All Scripts

```
var all = FindObjectsByType<UnitSpawnPlaceholder>(FindObjectsSortMode.None);
var mine = new List<UnitSpawnPlaceholder>(all.Length);

foreach (var ph in all)
{
    if (!ph) continue;
    if (ph.gameObject.scene != scene) continue; // vain tämän Level-skenen placeholderit
    if (ph.side != side) continue;
    mine.Add(ph);
}

if (mine.Count == 0) return System.Array.Empty<Vector3>();

// deterministinen järjestys order-kentän mukaan, sitten nimi/instanceID fallback
var ordered = mine.OrderBy(p => p.order).ThenBy(p => p.name).ToList();

var result = new Vector3[ordered.Count];
for (int i = 0; i < ordered.Count; i++)
    result[i] = ordered[i].GetSpawnWorldPosition();

// serverillä siivotaan placeholderit jos niin halutaan
if (consumePlaceholdersOnServer && Mirror.NetworkServer.active)
    foreach (var ph in ordered) ph.Consume();

return result;
}

public Vector3[] GetEnemySpawnPositions()
{
    Debug.Log("[SpawnUnitsCoordinator] GetEnemySpawnPositions() called.");
    if (usePlaceholders)
    {
        var pos = GetSpawnPositionsFromPlaceholders(UnitSpawnPlaceholder.Side.Enemy);
        if (pos.Length > 0) return pos;
        Debug.LogWarning("[SpawnUnitsCoordinator] No enemy placeholders found, falling back to arrays.");
    }

    if (enemySpawnPositions.Length == 0)
    {
        Debug.LogError("Enemy spawn position array not set in SpawnUnitsCoordinator!");
        return new Vector3[0];
    }
    return enemySpawnPositions;
}

public Vector3[] GetSpawnPositionsForPlayer(bool isHost)
{
    Debug.Log("[SpawnUnitsCoordinator] GetSpawnPositionsForPlayer() called.");
    if (usePlaceholders)
    {
        var side = isHost ? UnitSpawnPlaceholder.Side.Host : UnitSpawnPlaceholder.Side.Client;
        var pos = GetSpawnPositionsFromPlaceholders(side);
    }
}
```

RogueShooter – All Scripts

```
        if (pos.Length > 0) return pos;
        Debug.LogWarning("[SpawnUnitsCoordinator] No placeholders found, falling back to arrays.");
    }

    if (hostSpawnPositions.Length == 0 || clientSpawnPositions.Length == 0)
    {
        Debug.LogError("Spawn position arrays not set in SpawnUnitsCoordinator!");
        return new Vector3[0];
    }
    return isHost ? hostSpawnPositions : clientSpawnPositions;
}

public void SpawnSinglePlayerUnits()
{
    Scene targetScene = gameObject.scene;

    // PLAYER (Host) - hae paikat placeholderista (tai fallback taulukkoon)
    var playerSpawns = GetSpawnPositionsForPlayer(true);
    Debug.Log($"[SpawnUnitsCoordinator] Offline spawn PLAYER units: {playerSpawns.Length} pcs → scene '{targetScene.name}");
    for (int i = 0; i < playerSpawns.Length; i++)
    {
        var unit = SpawnRouter.SpawnLocal(
            prefab: unitHostPrefab,
            pos: playerSpawns[i],
            rot: Quaternion.identity,
            source: transform,
            sceneName: targetScene.name
        );
        Debug.Log($"[SpawnUnitsCoordinator] Offline PLAYER unit spawned '{unit.name}' at {playerSpawns[i]} in '{unit.scene.name}");
    }

    // ENEMY - samoin placeholderista (tai fallback)
    var enemySpawns = GetEnemySpawnPositions();
    Debug.Log($"[SpawnUnitsCoordinator] Offline spawn ENEMY units: {enemySpawns.Length} pcs → scene '{targetScene.name}");
    for (int i = 0; i < enemySpawns.Length; i++)
    {
        var enemy = SpawnRouter.SpawnLocal(
            prefab: GetEnemyPrefab(),
            pos: enemySpawns[i],
            rot: Quaternion.identity,
            source: transform,
            sceneName: targetScene.name
        );
        Debug.Log($"[SpawnUnitsCoordinator] Offline ENEMY unit spawned '{enemy.name}' at {enemySpawns[i]} in '{enemy.scene.name}");
    }

    SetEnemiesSpawned(true);
}

public GameObject[] SpawnEnemies()
{
    // 1) Hae paikat (placeholderit jos käytössä, muuten fallback-taulukko)
```

RogueShooter – All Scripts

```
var enemySpawns = GetEnemySpawnPositions();
Scene targetScene = gameObject.scene;

var spawnedEnemies = new GameObject[enemySpawns.Length];
Debug.Log($"[SpawnUnitsCoordinator] {(NetworkServer.active ? "Network" : "Local")} spawn ENEMY units: {enemySpawns.Length} pcs → scene '{targetScene.name}');

for (int i = 0; i < enemySpawns.Length; i++)
{
    if (NetworkServer.active)
    {
        var go = SpawnRouter.SpawnNetworkServer(
            prefab: GetEnemyPrefab(),
            pos: enemySpawns[i],
            rot: Quaternion.identity,
            source: transform,
            sceneName: targetScene.name,
            parent: null,
            owner: null
        );
        spawnedEnemies[i] = go;
        Debug.Log($"[SpawnUnitsCoordinator] Network ENEMY spawned '{go.name}' at {enemySpawns[i]} in '{go.scene.name}');
    }
    else
    {
        var go = SpawnRouter.SpawnLocal(
            prefab: GetEnemyPrefab(),
            pos: enemySpawns[i],
            rot: Quaternion.identity,
            source: transform,
            sceneName: targetScene.name
        );
        spawnedEnemies[i] = go;
        Debug.Log($"[SpawnUnitsCoordinator] Local ENEMY spawned '{go.name}' at {enemySpawns[i]} in '{go.scene.name}');
    }
}

SetEnemiesSpawned(true);
return spawnedEnemies;
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/UnitSpawnPlaceholder.cs

```
using UnityEngine;

#if UNITY_EDITOR
[ExecuteAlways]
#endif
[DisallowMultipleComponent]
public class UnitSpawnPlaceholder : MonoBehaviour
{
    public enum Side { Host, Client, Enemy }

    [Header("Who spawns here?")]
    public Side side = Side.Host;

    [Header("Options")]
    [Tooltip("Snäppää paikan ruudun keskelle, jos LevelGrid on käytössä.")]
    public bool snapToGridCenter = true;

    [Tooltip("Piilota renderöijät play-tilassa (Editorissa näkyy).")]
    public bool hideRendererInPlayMode = true;

    [Tooltip("Tuhotaan palvelimella spawnin jälkeen (muussa tapauksessa disabloidaan).")]
    public bool destroyOnServerAfterUse = true;

    [Tooltip("Vapaa järjestysnumero deterministiseen spawn-järjestykseen (pienin ensin).")]
    public int order = 0;

    public Vector3 GetSpawnWorldPosition()
    {
        var pos = transform.position;
        Debug.Log($"[UnitSpawnPlaceholder] GetSpawnWorldPosition(): placeholder at {pos}");

        if (snapToGridCenter && LevelGrid.Instance != null)
        {
            var gp = LevelGrid.Instance.GetGridPosition(pos);
            pos = LevelGrid.Instance.GetWorldPosition(gp); // keskittää ruutuun
        }
        Debug.Log($"[UnitSpawnPlaceholder] GetSpawnWorldPosition(): returning spawn pos {pos}");
        return pos;
    }

    private void OnEnable()
    {
        {
#if UNITY_EDITOR
            if (!Application.isPlaying) return;
#endif
            if (hideRendererInPlayMode) ToggleRenderers(false);
        }

        public void Consume()
        {

```

RogueShooter – All Scripts

```
        if (destroyOnServerAfterUse)
        {
            if (Application.isPlaying) Destroy(gameObject);
            else DestroyImmediate(gameObject);
        }
        else
        {
            gameObject.SetActive(false);
        }
    }

    private void ToggleRenderers(bool visible)
    {
        foreach (var r in GetComponentsInChildren<Renderer>(true)) r.enabled = visible;
    }

#if UNITY_EDITOR
    private void OnDrawGizmos()
    {
        // yksinkertainen "keila": väri puolen mukaan
        Color c = side == Side.Host ? new Color(0f, 0.9f, 1f, 0.9f)
            : side == Side.Client ? new Color(1f, 0f, 1f, 0.9f)
            : new Color(1f, 0.2f, 0.2f, 0.9f);
        Gizmos.color = c;
        Gizmos.DrawWireCube(transform.position + Vector3.up * 0.05f, new Vector3(0.6f, 0.1f, 0.6f));
        Gizmos.DrawLine(transform.position, transform.position + Vector3.up * 0.8f);
    }
#endif
}
```

RogueShooter – All Scripts

Assets/scripts/LevelCreation/WarmBootGuard.cs

```
using UnityEngine;
using UnityEngine.SceneManagement;
using Mirror;

// Tämä on vain fallback - jos LevelLoader toimii, tämä tekee ei mitään.
public static class WarmBootGuard
{
    /*
    [RuntimeInitializeOnLoadMethod(RuntimeInitializeLoadType.AfterSceneLoad)]
    static void AfterSceneLoad()
    {
        // Koskee vain offline-starttia. Host/client-tilan latauksen hoitaa NetLevelLoader.
        if (NetworkServer.active || NetworkClient.active) return;

        // jos LevelLoaderia ei jostain syystä löydy tai se ei toimi,
        // lataa varmuuden vuoksi Level 0 additiivisesti.
        var loader = Object.FindFirstObjectByType<LevelLoader>(FindObjectsInactive.Include);
        if (loader == null)
        {
            Debug.LogWarning("[WarmBootGuard] LevelLoader not found → loading 'Level 0' additively as a fallback.");
            SceneManager.LoadSceneAsync("Level 0", LoadSceneMode.Additive);
        }
    }
    */
}
```


RogueShooter – All Scripts

Assets/scripts/LevelGridGizmos.cs

```
using UnityEngine;

#if UNITY_EDITOR
using UnityEditor;
using UnityEngine.Rendering;
#endif

[ExecuteInEditMode]
public class LevelGridGizmos : MonoBehaviour
{
    [Header("Visualization Settings")]
    [SerializeField] private bool showGrid = true;
    [SerializeField] private bool showGridNumbers = false;
    [SerializeField] private bool showEdgeWalls = true;
    [SerializeField] private bool showCoverLines = true;

    [Header("Grid Settings (for Edit Mode)")]
    [SerializeField] private int editorWidth = 10;
    [SerializeField] private int editorHeight = 10;
    [SerializeField] private float editorCellSize = 2f;
    [SerializeField] private int editorFloorAmount = 1;

    [Header("Colors")]
    [SerializeField] private Color gridColor = new Color(0.7f, 0.7f, 0.7f, 0.4f);
    [SerializeField] private Color wallColor = new Color(1f, 0f, 0f, 0.8f);
    [SerializeField] private Color lowCoverColor = new Color(1f, 1f, 0f, 0.6f);
    [SerializeField] private Color highCoverColor = new Color(1f, 0.5f, 0f, 0.8f);

    [Header("Line Thickness")]
    [SerializeField] private float gridLineThickness = 1f;
    [SerializeField] private float wallLineThickness = 3f;
    [SerializeField] private float coverLineThickness = 2f;

    public enum DepthMode { XRay, Occluded, Dual }
    [Header("Depth/Overlay")]
    [SerializeField] private DepthMode depthMode = DepthMode.Occluded;
    [SerializeField] private float gridYOffset = 0.01f; // pieni nosto lattian yläpuolelle

    [Header("References")]
    [SerializeField] private LevelGrid levelGrid;

    private const float WALL_HEIGHT_OFFSET = 0.5f;
    private const float COVER_HEIGHT_OFFSET = 0.3f;

    private void OnValidate()
    {
        if (levelGrid == null)
        {
            levelGrid = GetComponent<LevelGrid>();
        }
    }
}
```

RogueShooter – All Scripts

```
    }  
}  
  
private void OnDrawGizmos()  
{  
    if (!showGrid && !showEdgeWalls && !showCoverLines) return;  
  
    if (Application.isPlaying && levelGrid != null)  
    {  
        DrawPlayModeGizmos();  
    }  
    else if (!Application.isPlaying)  
    {  
        DrawEditModeGizmos();  
    }  
}  
  
private static Vector3 Centerize(Vector3 corner, float cell)  
=> corner + new Vector3(cell * 0.5f, 0f, cell * 0.5f);  
  
private void DrawPlayModeGizmos()  
{  
    if (levelGrid == null) return;  
  
    int width = 0;  
    int height = 0;  
    int floorAmount = 0;  
    float cellSize = 0f;  
  
    try  
    {  
        width = levelGrid.GetWidth();  
        height = levelGrid.GetHeight();  
        floorAmount = levelGrid.GetFloorAmount();  
        cellSize = levelGrid.GetCellSize();  
    }  
    catch  
    {  
        return;  
    }  
  
    if (width <= 0 || height <= 0 || cellSize <= 0) return;  
  
    for (int floor = 0; floor < floorAmount; floor++)  
    {  
        if (showGrid)  
        {  
            DrawGridLines(width, height, cellSize, floor);  
        }  
  
        if (showGridNumbers)  
        {  

```

RogueShooter – All Scripts

```
        DrawGridNumbers(width, height, floor);
    }

    if (showEdgeWalls || showCoverLines)
    {
        DrawEdgesAndCovers(width, height, floor);
    }
}

private void DrawEditModeGizmos()
{
    if (!showGrid) return;

    for (int floor = 0; floor < editorFloorAmount; floor++)
    {
        DrawGridLines(editorWidth, editorHeight, editorCellSize, floor);

        if (showGridNumbers)
        {
            DrawEditModeGridNumbers(editorWidth, editorHeight, editorCellSize, floor);
        }
    }
}

private void DrawGridLines(int width, int height, float cellSize, int floor)
{
    Gizmos.color = gridColor;
    float floorY = floor * LevelGrid.FLOOR_HEIGHT + gridYOffset; // pieni offset

    float o = 0.5f * cellSize; // siirto että ruudukko alkaa (0,0) vasen/alareunasta

    for (int x = 0; x <= width; x++)
    {
        Vector3 start = new Vector3(x * cellSize - o, floorY, -o);
        Vector3 end = new Vector3(x * cellSize - o, floorY, height * cellSize - o);
        DrawThickLine(start, end, gridLineThickness);
    }

    for (int z = 0; z <= height; z++)
    {
        Vector3 start = new Vector3(-o, floorY, z * cellSize - o);
        Vector3 end = new Vector3(width * cellSize - o, floorY, z * cellSize - o);
        DrawThickLine(start, end, gridLineThickness);
    }
}

#if UNITY_EDITOR
// Pieni apu: piirrä viiva depth-asetuksella
private void DrawWithDepth(System.Action draw)
{

```

RogueShooter – All Scripts

```
var prev = Handles.zTest;
switch (depthMode)
{
    case DepthMode.XRay:
        Handles.zTest = CompareFunction.Always;    // aina näkyvissä
        draw();
        break;
    case DepthMode.Occluded:
        Handles.zTest = CompareFunction.LessEqual; // kunnioittaa syvyyttä
        draw();
        break;
    case DepthMode.Dual:
        // 1) haalea x-ray taustalle
        Handles.zTest = CompareFunction.Always;
        var c = Gizmos.color; var faint = new Color(c.r, c.g, c.b, c.a * 0.25f);
        Handles.DrawBezier(_s, _e, _s, _e, faint, null, _t);
        // 2) täysi viiva vain näkyvissä osissa
        Handles.zTest = CompareFunction.LessEqual;
        draw();
        break;
}
Handles.zTest = prev;
}

// Väliaikaiset muuttujat Dual-moodin sisäpiirtoa varten
private Vector3 _s, _e; private float _t;
#endif
private void DrawThickLine(Vector3 start, Vector3 end, float thickness)
{
    #if UNITY_EDITOR
        _s = start; _e = end; _t = thickness;
        DrawWithDepth(() =>
        {
            Handles.DrawBezier(start, end, start, end, Gizmos.color, null, thickness);
        });
    #else
        Gizmos.DrawLine(start, end);
    #endif
}

private void DrawGridNumbers(int width, int height, int floor)
{
    #if UNITY_EDITOR
        float cell = levelGrid.GetCellSize();
        for (int x = 0; x < width; x++)
            for (int z = 0; z < height; z++)
            {
                GridPosition gp = new GridPosition(x, z, floor);
                Vector3 worldPosCorner;
                try { worldPosCorner = levelGrid.GetWorldPosition(gp); }
                catch { continue; }
            }
    #endif
}
```

RogueShooter – All Scripts

```
        Vector3 worldPos = Centerize(worldPosCorner, cell);
        worldPos.y += 0.1f;

        var style = new GUIStyle { normal = { textColor = Color.white }, fontSize = 10, alignment = TextAnchor.MiddleCenter };
        Handles.Label(worldPos, $"{{x}},{{z}}", style);
    }
#endif
}

private void DrawEditModeGridNumbers(int width, int height, float cellSize, int floor)
{
    #if UNITY_EDITOR
        float floorY = floor * LevelGrid.FLOOR_HEIGHT;
        for (int x = 0; x < width; x++)
            for (int z = 0; z < height; z++)
            {
                Vector3 worldPos = new Vector3((x + 0.5f) * cellSize, floorY, (z + 0.5f) * cellSize);
                worldPos.y += 0.1f;

                var style = new GUIStyle { normal = { textColor = Color.white }, fontSize = 10, alignment = TextAnchor.MiddleCenter };
                Handles.Label(worldPos, $"{{x}},{{z}}", style);
            }
    #endif
}

private void DrawEdgesAndCovers(int width, int height, int floor)
{
    var pathfinding = PathFinding.Instance;
    if (pathfinding == null) return;

    float cell = levelGrid.GetCellSize();

    for (int x = 0; x < width; x++)
        for (int z = 0; z < height; z++)
        {
            PathNode node;
            try { node = pathfinding.GetNode(x, z, floor); } catch { continue; }
            if (node == null) continue;

            GridPosition gp = new GridPosition(x, z, floor);
            Vector3 corner;
            try { corner = levelGrid.GetWorldPosition(gp); } catch { continue; }

            // *** TÄRKEÄ: käytä ruudun keskikohtaa piirtämisen lähtöpisteenä
            Vector3 center = Centerize(corner, cell);

            if (showEdgeWalls) DrawEdgeWalls(node, center, cell);
            if (showCoverLines) DrawCoverLines(node, center, cell);
        }
}
```

RogueShooter – All Scripts

```
private void DrawEdgeWalls(PathNode node, Vector3 center, float cellSize)
{
    Gizmos.color = wallColor;
    float halfCell = cellSize * 0.5f;
    float y = center.y + WALL_HEIGHT_OFFSET;

    if (node.HasWall(EdgeMask.N))
    {
        Vector3 start = new Vector3(center.x - halfCell, y, center.z + halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, wallLineThickness);
    }

    if (node.HasWall(EdgeMask.S))
    {
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z - halfCell);
        DrawThickLine(start, end, wallLineThickness);
    }

    if (node.HasWall(EdgeMask.E))
    {
        Vector3 start = new Vector3(center.x + halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, wallLineThickness);
    }

    if (node.HasWall(EdgeMask.W))
    {
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x - halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, wallLineThickness);
    }
}

private void DrawCoverLines(PathNode node, Vector3 center, float cellSize)
{
    float halfCell = cellSize * 0.5f;
    float y = center.y + COVER_HEIGHT_OFFSET;

    if (node.HasHighCover(CoverMask.N))
    {
        Gizmos.color = highCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z + halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }
    else if (node.HasLowCover(CoverMask.N))
    {
        Gizmos.color = lowCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z + halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
    }
}
```

RogueShooter – All Scripts

```
        DrawThickLine(start, end, coverLineThickness);
    }

    if (node.HasHighCover(CoverMask.S))
    {
        Gizmos.color = highCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z - halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }
    else if (node.HasLowCover(CoverMask.S))
    {
        Gizmos.color = lowCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z - halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }

    if (node.HasHighCover(CoverMask.E))
    {
        Gizmos.color = highCoverColor;
        Vector3 start = new Vector3(center.x + halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }
    else if (node.HasLowCover(CoverMask.E))
    {
        Gizmos.color = lowCoverColor;
        Vector3 start = new Vector3(center.x + halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x + halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }

    if (node.HasHighCover(CoverMask.W))
    {
        Gizmos.color = highCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x - halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }
    else if (node.HasLowCover(CoverMask.W))
    {
        Gizmos.color = lowCoverColor;
        Vector3 start = new Vector3(center.x - halfCell, y, center.z - halfCell);
        Vector3 end = new Vector3(center.x - halfCell, y, center.z + halfCell);
        DrawThickLine(start, end, coverLineThickness);
    }
}
}
```

RogueShooter – All Scripts

Assets/scripts/MenuUI/BackButtonUI.cs

```
using UnityEngine;
using UnityEngine.UI;

public class BackButtonUI : MonoBehaviour
{
    // Serialized fields
    [Header("Canvas References")]
    [SerializeField] private GameObject connectCanvas; // this (self)
    [SerializeField] private GameObject gameModeSelectCanvas; // Hidden on start

    [Header("Buttons")]
    [SerializeField] private Button backButton;

    private void Awake()
    {
        // Add button listener
        backButton.onClick.AddListener(BackButton_OnClick);
    }

    private void BackButton_OnClick()
    {
        // Sign out the player from Unity Services
        Authentication authentication = connectCanvas.GetComponent<Authentication>();
        authentication.SignOutPlayerFromUnityServer();

        // Hide the connect canvas and show the game mode select canvas
        connectCanvas.SetActive(false);
        gameModeSelectCanvas.SetActive(true);
    }
}
```


RogueShooter – All Scripts

Assets/scripts/MenuUI/GameModeSelectUI.cs

```
using TMPro;
using UnityEngine;
using UnityEngine.UI;

public class GameModeSelectUI : MonoBehaviour
{
    // Serialized fields
    [Header("Canvas References")]
    [SerializeField] private GameObject gameModeSelectCanvas; // this (self)
    [SerializeField] private GameObject connectCanvas; // Hidden on start
    [SerializeField] private GameObject connectCodePanel; // Hidden on start

    [Header("Services")]
    [SerializeField] private Authentication authentication; // <-- UUSI

    [Header("Join Code UI")]
    [SerializeField] private TMP_Text joinCodeText;

    // UI Elements
    [Header("Buttons")]
    [SerializeField] private Button coopButton;
    [SerializeField] private Button pvpButton;

    private void Awake()
    {
        // Ensure the game mode select canvas is active and connect canvas is inactive at start
        gameModeSelectCanvas.SetActive(true);
        connectCanvas.SetActive(false);
        connectCodePanel.SetActive(false);

        // Add button listeners
        coopButton.onClick.AddListener(OnClickCoOp);
        pvpButton.onClick.AddListener(OnClickPvP);
    }

    public void OnClickCoOp()
    {
        GameManager.SetCoOp();
        OnSelected();
    }

    public void OnClickPvP()
    {
        GameManager.SetVersus();
        OnSelected();
    }

    public async void OnSelected()
    {
        // 0) Varmista että Authentication löytyy (älä luota pelkkään connectCanvas-viitteeseen)
```

RogueShooter – All Scripts

```
    if (!authentication)
        authentication = FindFirstObjectByType<Authentication>(FindObjectsInactive.Include);

    if (!authentication)
    {
        Debug.LogError("[GameModeSelectUI] Authentication-componenttia ei löytynyt scenestä.");
        return;
    }

    // 1) Sign-in Unity Servicesiin
    await authentication.SingInPlayerToUnityServerAsync();

    // 2) UI-flown jatko
    FieldCleaner.ClearAll();
    StartCoroutine(ResetGridNextFrame());
    if (gameModeSelectCanvas) gameModeSelectCanvas.SetActive(false);
    if (connectCanvas) connectCanvas.SetActive(true);
}

private System.Collections.IEnumerator ResetGridNextFrame()
{
    yield return new WaitForEndOfFrame();
    var lg = LevelGrid.Instance;
    if (lg != null) lg.RebuildOccupancyFromScene();
}

public void Reset()
{
    // Pieni "siivous" ennen reloadia on ok, mutta ei pakollinen
    FieldCleaner.ClearAll();

    if (Mirror.NetworkServer.active)
    {
        // ResetService.Instance.RequestReset();
    }
    else
    {
        // Yksinpeli
        GameReset.HardReloadSceneKeepMode();
    }
}

public void SetConnectCodePanelVisibility(bool active)
{
    connectCodePanel.SetActive(active);
}

public void SetJoinCodeText(string s)
{
    if (!joinCodeText)
```

RogueShooter – All Scripts

```
{
    Debug.LogWarning("[GameModeSelectUI] joinCodeText not assigned.");
    return;
}

s = (s ?? "").Trim().ToUpperInvariant();
joinCodeText.text = $"JOIN CODE: {s}";

// (valinnainen) kopioi koodi leikepöydälle:
// GUIUtility.systemCopyBuffer = s;

// (valinnainen) varmista että paneeli on näkyvissä:
// if (connectCodePanel && !connectCodePanel.activeSelf) connectCodePanel.SetActive(true);
}
```

RogueShooter – All Scripts

Assets/scripts/OfflineCalls/OfflineGameSimulator.cs

```
using UnityEngine;

public static class OfflineGameSimulator
{
    public static void SpawnBullet(GameObject bulletPrefab, Vector3 spawnPos, Vector3 targetPos)
    {
        SpawnRouter.SpawnLocal(
            bulletPrefab, spawnPos, Quaternion.identity,
            source: null,
            sceneName: LevelLoader.Instance.CurrentLevel,
            parent: null,
            beforeReturn: go =>
            {
                if (go.TryGetComponent<BulletProjectile>(out var gp))
                    gp.Setup(targetPos);
            });
    }

    public static void SpawnGrenade(GameObject grenadePrefab, Vector3 spawnPos, Vector3 targetPos)
    {
        SpawnRouter.SpawnLocal(
            grenadePrefab, spawnPos, Quaternion.identity,
            source: null,
            sceneName: LevelLoader.Instance.CurrentLevel,
            parent: null,
            beforeReturn: go =>
            {
                if (go.TryGetComponent<GrenadeProjectile>(out var gp))
                    gp.Setup(targetPos);
            });
    }

    public static void SpawnRagdoll(GameObject prefab, Vector3 pos, Quaternion rot, uint sourceUnitNetId, Transform originalRootBone, Vector3 lastHitPosition, int overkill)
    {
        // OFFLINE: paikallinen spawn, ohjaa samaan sceneen kuin originalRootBone
        SpawnRouter.SpawnLocal(
            prefab, pos, rot,
            source: originalRootBone, // → sama scene kuin ruumiilla/luurangolla (level)
            sceneName: null,
            parent: null,
            beforeReturn: go =>
            {
                if (go.TryGetComponent<UnitRagdoll>(out var unitRagdoll))
                {
                    unitRagdoll.SetOverkill(overkill);
                    unitRagdoll.SetLastHitPosition(lastHitPosition);
                    unitRagdoll.Setup(originalRootBone);
                }
            });
    }
}
```

```
}  
}
```

RogueShooter – All Scripts

Assets/scripts/Online/Authentication.cs

```
using System;
using System.Threading.Tasks;
using Unity.Services.Authentication;
using Unity.Services.Core;
using UnityEngine;

/// <summary>
/// This class is responsible for handling the authentication process.
/// It initializes the Unity Services and signs in the user anonymously.
/// Required when using Unity Relay, as it provides player authentication
/// and enables online multiplayer without port forwarding or direct IP connections.
/// </summary>
public class Authentication : MonoBehaviour
{
    public async Task SingInPlayerToUnityServerAsync()
    {
        try
        {
            await UnityServices.InitializeAsync();
            await AuthenticationService.Instance.SignInAnonymouslyAsync();
            Debug.Log("Logged into Unity, player ID: " + AuthenticationService.Instance.PlayerId);
        }
        catch (Exception e)
        {
            Debug.LogError(e);
        }
    }

    public void SignOutPlayerFromUnityServer()
    {
        if (AuthenticationService.Instance.IsSignedIn)
        {
            AuthenticationService.Instance.SignOut();
            Debug.Log("Player signed out of Unity Services");
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/ClientPreJoinCleaner.cs

```
// ClientPreJoinCleaner.cs
using System.Collections;
using System.Linq;
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;

public static class ClientPreJoinCleaner
{
    public static IEnumerator PrepareForOnlineJoin()
    {
        Debug.Log("[ClientPreJoinCleaner] Pura ei Core Scenet");
        // 1) Pura kaikki ei-Core -scenet pois
        string core = LevelLoader.Instance ? LevelLoader.Instance.CoreSceneName : "Core";
        for (int i = SceneManager.sceneCount - 1; i >= 0; i--)
        {
            var s = SceneManager.GetSceneAt(i);
            if (s.isLoaded && s.name != core)
            {
                var op = SceneManager.UnloadSceneAsync(s);
                if (op != null) yield return op;
            }
        }

        // 2) Siivoa mahdolliset offline-jäänteet Coresta,
        // jotka pitäisi tulla serveriltä netin kautta
        DestroyServerProvidedLeftoversInCore(core);

        // (valinnainen)
        yield return Resources.UnloadUnusedAssets();
    }

    static void DestroyServerProvidedLeftoversInCore(string core)
    {
        Debug.Log("[ClientPreJoinCleaner] Siivotaan kaikki offline jäänteet");
        var coreScene = SceneManager.GetSceneByName(core);
        if (!coreScene.IsValid()) return;

        // Hae kaikki juuret Core-scenen alta ja siivoa tunnetut tyypit
        foreach (var root in coreScene.GetRootGameObjects())
        {
            // Unitit (mukaan lukien ystävä/vihollis-tagit)
            foreach (var u in root.GetComponentsInChildren<Unit>(true)) Object.Destroy(u.gameObject);
            foreach (var f in root.GetComponentsInChildren<FriendlyUnit>(true)) Object.Destroy(f.gameObject);
            foreach (var e in root.GetComponentsInChildren<EnemyUnit>(true)) Object.Destroy(e.gameObject);

            // Tuhoutuvat objektit
            foreach (var d in root.GetComponentsInChildren<DestructibleObject>(true)) Object.Destroy(d.gameObject);

            // Ragdollit & binderit
        }
    }
}
```

RogueShooter – All Scripts

```
foreach (var rb in root.GetComponentsInChildren<RagdollPoseBinder>(true)) Object.Destroy(rb.gameObject);
foreach (var rd in root.GetComponentsInChildren<UnitRagdoll>(true)) Object.Destroy(rd.gameObject);

// (Tarvittaessa: ohjukset/granaatit, placeholderit yms.)
// foreach (var b in root.GetComponentsInChildren<BulletProjectile>(true)) Object.Destroy(b.gameObject);
// foreach (var g in root.GetComponentsInChildren<GrenadeProjectile>(true)) Object.Destroy(g.gameObject);
// foreach (var ph in root.GetComponentsInChildren<ObjectSpawnPlaceHolder>(true)) Object.Destroy(ph.gameObject);
}

// Nollaa ruudukon miehitykset varmuudeksi
LevelGrid.Instance?.ClearAllOccupancy();
}
}
```


RogueShooter – All Scripts

Assets/scripts/Online/Connect.cs

```
using UnityEngine;
using TMPro;
using Mirror;
using Utp;
using UnityEngine.SceneManagement;
using System.Collections;
using UnityEngine.UI;

/// <summary>
/// This class is responsible for connecting to a game as a host or client.
///
/// NOTE: Button callbacks are set in the Unity Inspector.
/// </summary>
public class Connect : MonoBehaviour
{
    [SerializeField] private GameNetworkManager gameNetworkManager; // vedä tämä Inspectorissa
    [SerializeField] private TMP_InputField ipField;
    [SerializeField] private GameModeSelectUI gameModeSelectUI;

    [SerializeField] private GameObject joinInputPanel; // JoinInputPanel (inactive alussa)
    [SerializeField] private TMP_InputField joinCodeField;
    [SerializeField] private Button joinButton;

    void Awake()
    {
        // find the NetworkManager in the scene if not set in Inspector
        if (!gameNetworkManager) gameNetworkManager = NetworkManager.singleton as GameNetworkManager;
        if (!gameNetworkManager) gameNetworkManager = FindFirstObjectByType<GameNetworkManager>();
        if (!gameNetworkManager) Debug.LogError("[Connect] GameNetworkManager not found in scene.");

        if (joinInputPanel) joinInputPanel.SetActive(false);
        if (joinButton) joinButton.onClick.AddListener(JoinWithFieldValue);
        if (joinCodeField) joinCodeField.onSubmit.AddListener(_ => JoinWithFieldValue());
    }

    public void HostLAN()
    {
        if (!gameNetworkManager)
        {
            gameNetworkManager = NetworkManager.singleton as GameNetworkManager
                ?? FindFirstObjectByType<GameNetworkManager>();
            if (!gameNetworkManager) { Debug.LogError("[Connect] GameNetworkManager not found."); return; }
        }

        gameNetworkManager.StartStandardHost();
    }
}
```

RogueShooter – All Scripts

```
public void ClientLAN()
{
    string ip = (ipField != null && !string.IsNullOrEmpty(ipField.text))
        ? ipField.text.Trim()
        : "localhost"; // tai 127.0.0.1

    Debug.Log($"[Connect] Joining server at {ip}");

    gameNetworkManager.networkAddress = ip;
    // 1) Puhdistetaan clientin oma kenttä ja offline-jäänteet
    StartCoroutine(CleanThenJoin());
}

private IEnumerator CleanThenJoin()
{
    // 1) Puhdistetaan clientin oma kenttä ja offline-jäänteet
    yield return ClientPreJoinCleaner.PrepareForOnlineJoin();
    gameNetworkManager.JoinStandardServer(); // useRelay=false ja StartClient()
}

public void Host()
{
    if (!gameNetworkManager)
    {
        gameNetworkManager = NetworkManager.singleton as GameNetworkManager
            ?? FindFirstObjectByType<GameNetworkManager>();
        if (!gameNetworkManager) { Debug.LogError("[Connect] GameNetworkManager not found."); return; }
    }

    StartCoroutine(StartRelayHostThenLoadLevel());
}

private RelayJoinCodeUI GetJoinUI()
{
    // Etsi ensin singletonista, jos puuttuu, etsi hierarkiasta (myös inaktiivisista)
    return RelayJoinCodeUI.Instance
        ?? FindFirstObjectByType<RelayJoinCodeUI>(FindObjectsInactive.Include);
}

private IEnumerator StartRelayHostThenLoadLevel()
{
    if (NetworkServer.active) yield break;

    gameNetworkManager.StartRelayHost(2, null);

    // 1) Odota että oikea join-koodi valmistuu
    yield return new WaitUntil(() => !string.IsNullOrEmpty(gameNetworkManager.relayJoinCode));

    // 2) Näytä koodi turvallisesti (ei NRE:tä vaikka Instance olisi vielä null)
    var ui = GetJoinUI();
}
```

RogueShooter – All Scripts

```
if (ui != null) ui.ShowCode(gameNetworkManager.relayJoinCode);
else Debug.LogError("[Connect] RelayJoinCodeUI puuttuu Corescenestä - ei voida näyttää koodia.");

// 3) Odota että serveri on varmasti aktiivinen
yield return new WaitUntil(() => NetworkServer.active);

// 4) Varmista että level on ladattu additiivisesti
yield return EnsureLevelLoadedAfterServerUp();

// 5) Pidä koodi näkyvissä kunnes 2. pelaaja on mukana (host + 1 client)
var minConn = gameNetworkManager ? gameNetworkManager.HideJoinCodeAfterConnections : 2;
yield return new WaitUntil(() => NetworkServer.connections != null &&
    NetworkServer.connections.Count >= minConn);

HideJoinPanel();
if (ui != null) ui.Hide();
}

private IEnumerator EnsureLevelLoadedAfterServerUp()
{
    // Odota että serveri on oikeasti ylhäällä
    yield return new WaitUntil(() => NetworkServer.active);
    yield return null; // 1 frame väliin, että Core-komponentit ehtivät herätä

    // Jos taso ei ole vielä valmis → kysy lataus NetLevelLoaderilta
    if (!LevelLoader.IsServerLevelReady)
    {
        // 1) Jos LevelLoader kertoo nykyisen tai oletustason, käytä sitä
        string desired = LevelLoader.Instance
            ? (LevelLoader.Instance.CurrentLevel ?? LevelLoader.Instance.DefaultLevel)
            : null;

        // 2) Muuten pyydä NetLevelLoaderilta sen oletustaso
        if (string.IsNullOrEmpty(desired) && NetLevelLoader.Instance)
            desired = NetLevelLoader.Instance.ResolveDefaultLevelName();

        if (!string.IsNullOrEmpty(desired) && NetLevelLoader.Instance)
        {
            NetLevelLoader.Instance.ServerLoadLevel(desired);
        }
        else
        {
            Debug.LogError("[Connects] Ei pystytty ratkaisemaan ladattavaa leveliä: puuttuuko LevelLoader.DefaultLevel tai NetLevelLoader?");
        }
    }
}

public void Client()
{
    if (!gameNetworkManager)
```

RogueShooter – All Scripts

```
{
    gameNetworkManager = NetworkManager.singleton as GameNetworkManager
    ?? FindFirstObjectByType<GameNetworkManager>();
    if (!gameNetworkManager)
    {
        Debug.LogError("[Connect] GameNetworkManager not found.");
        return;
    }
}

ShowJoinPanel();
}

private void JoinWithFieldValue()
{
    if (!gameNetworkManager)
    {
        Debug.LogError("[Connect] GameNetworkManager not set.");
        return;
    }

    string code = (joinCodeField ? joinCodeField.text : "").Trim().ToUpperInvariant();
    if (string.IsNullOrEmpty(code) || code.Length != 6)
    {
        Debug.LogWarning("[Connect] Join code missing/invalid.");
        return;
    }

    // Käynnistä join-prosessi yhdestä paikasta (coroutinesta)
    StartCoroutine(Co_CleanThenJoin(code));
}

private IEnumerator Co_CleanThenJoin(string code)
{
    // Piilota UI heti kun liitytään (ettei jää päälle kentän latautuessa)
    HideJoinPanel();
    if (joinButton) joinButton.interactable = false;

    // Puhdista ennen liittymistä
    yield return ClientPreJoinCleaner.PrepareForOnlineJoin();

    // Aseta koodi ja liity (vain KERRAN)
    gameNetworkManager.relayJoinCode = code;
    gameNetworkManager.JoinRelayServer();
}

// Cancel tai Back
public void HideJoinPanel()
{
    if (joinInputPanel) joinInputPanel.SetActive(false);
    if (joinCodeField) { joinCodeField.text = ""; joinCodeField.DeactivateInputField(); }
```

RogueShooter – All Scripts

```
}

private void ShowJoinPanel()
{
    if (joinInputPanel) joinInputPanel.SetActive(true);
    if (joinCodeField)
    {
        // (valinnainen) esitäyttö leikepöydästä, jos näyttää koodilta
        var clip = GUIUtility.systemCopyBuffer?.Trim().ToUpperInvariant();
        if (!string.IsNullOrEmpty(clip) && clip.Length == 6)
            joinCodeField.text = clip;

        joinCodeField.ActivateInputField();
        joinCodeField.caretPosition = joinCodeField.text.Length;
    }
}

/// <summary>
/// Starts a LAN host and loads the current scene for all clients.
/// </summary>
public void LoadSceneToAllHostLAN()
{
    gameNetworkManager.StartStandardHost();
    var sceneName = SceneManager.GetActiveScene().name;
    NetworkManager.singleton.ServerChangeScene(sceneName);
}

/// <summary>
/// Starts a relay host and loads the current scene for all clients.
/// </summary>
public void LoadSceneToAllHost()
{
    StartCoroutine(StartRelayHostThenChangeScene());
}

private IEnumerator StartRelayHostThenChangeScene()
{
    if (NetworkServer.active) yield break;

    gameNetworkManager.StartRelayHost(2, null);

    // 1) Odota kunnes OIKEA relay-join-koodi on valmis
    yield return new WaitUntil(() => !string.IsNullOrEmpty(gameNetworkManager.relayJoinCode));
    RelayJoinCodeUI.Instance.ShowCode(gameNetworkManager.relayJoinCode);

    // 2) Odota kunnes serveri on aktiivinen
    yield return new WaitUntil(() => NetworkServer.active);

    // 3) Pidä koodi näkyvässä kunnes 2. pelaaja on mukana (host + 1 client)
    yield return new WaitUntil(() =>
        NetworkServer.connections != null && NetworkServer.connections.Count >= 2);
}
```

RogueShooter – All Scripts

```
        RelayJoinCodeUI.Instance.Hide();  
    }  
}
```

RogueShooter – All Scripts

Assets/scripts/Online/CoopTurnCoordinator.cs

```
using System.Collections;
using System.Linq;
using Mirror;
using UnityEngine;

public class CoopTurnCoordinator : NetworkBehaviour
{
    public static CoopTurnCoordinator Instance { get; private set; }

    void Awake()
    {
        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;
    }

    [Server]
    public void TryAdvanceIfReady()
    {
        if (NetTurnManager.Instance.phase == TurnPhase.Players && NetTurnManager.Instance.endedPlayers.Count >= Mathf.Max(1, NetTurnManager.Instance.requiredCount))
        {
            StartCoroutine(ServerEnemyTurnThenNextPlayers());
        }
    }

    [Server]
    private IEnumerator ServerEnemyTurnThenNextPlayers()
    {
        UnitUIBroadcaster.Instance.BroadcastUnitWorldUIVisibility(true);

        // Vihollisvuoro alkaa domainissa
        TurnSystem.Instance.BeginEnemyTurn(incrementTurnId:false);
        RpcTurnPhaseChanged(TurnPhase.Enemy, NetTurnManager.Instance.turnNumber, false);

        // Aja AI
        yield return RunEnemyAI();

        // Siirtymä pelaajille
        NetTurnManager.Instance.turnNumber++;
        NetTurnManager.Instance.ResetTurnState();

        TurnSystem.Instance.BeginPlayersTurn(incrementTurnId:true); // laukoo eventit coresta
        RpcTurnPhaseChanged(TurnPhase.Players, NetTurnManager.Instance.turnNumber, true);

        UnitUIBroadcaster.Instance.BroadcastUnitWorldUIVisibility(false);
    }

    [Server]
    IEnumerator RunEnemyAI()
    {
        if (EnemyAI.Instance != null)
```

RogueShooter – All Scripts

```
        yield return EnemyAI.Instance.RunEnemyTurnCoroutine();
    else
        yield return null; // fallback, ettei ketju katkea
    }

// ---- Client-notifikaatiot UI:lle ----
[ClientRpc]
public void RpcTurnPhaseChanged(TurnPhase newPhase, int newTurnNumber, bool isPlayersPhase)
{
    // Päivitä paikallinen SP-UI-luuppi (ei Mirror-kutsuja)
    if (TurnSystem.Instance != null)
        TurnSystem.Instance.SetHudFromNetwork(newTurnNumber, isPlayersPhase);

    // Vaihe vaihtui → varmuuden vuoksi piilota mahdollinen "READY" -teksti
    var ui = FindFirstObjectByType<TurnSystemUI>();
    if (ui != null) ui.SetTeammateReady(false, null);
}

// Näyttää toiselle pelaajalle "Player X READY"
[ClientRpc]
public void RpcUpdateReadyStatus(int[] whoEndedIds, string[] whoEndedLabels)
{
    var ui = FindFirstObjectByType<TurnSystemUI>();
    if (ui == null) return;

    // Selvitä oma netId
    uint localId = 0;
    if (NetworkClient.connection != null && NetworkClient.connection.identity)
        localId = NetworkClient.connection.identity.netId;

    bool show = false;
    string label = null;

    // Jos joku muu kuin minä on valmis → näytä hänen labelinsa
    for (int i = 0; i < whoEndedIds.Length; i++)
    {
        if ((uint)whoEndedIds[i] != localId)
        {
            show = true;
            label = (i < whoEndedLabels.Length) ? whoEndedLabels[i] : "Teammate";
            break;
        }
    }

    ui.SetTeammateReady(show, label);
}

// ---- Server-apurit ----
[Server] string GetLabelByNetId(uint id)
{
    foreach (var kvp in NetworkServer.connections)
```


RogueShooter – All Scripts

```
    {
        var conn = kvp.Value;
        if (conn != null && conn.identity && conn.identity.netId == id)
            return conn.connectionId == 0 ? "Player 1" : "Player 2";
    }
    return "Teammate";
}

[Server]
public string[] BuildEndedLabels()
{
    // HashSetin järjestys ei ole merkityksellinen, näytetään mikä tahansa toinen
    return NetTurnManager.Instance.endedPlayers.Select(id => GetLabelByNetId(id)).ToArray();
}
}
```

RogueShooter – All Scripts

Assets/scripts/Online/EndgameAnnouncer.cs

```
using System;
using Mirror;
using UnityEngine;

public class EndgameAnnouncer : NetworkBehaviour
{
    public override void OnStartServer()
    {
        Unit.OnAnyUnitDead += OnAnyUnitDead_Server;
    }
    public override void OnStopServer()
    {
        Unit.OnAnyUnitDead -= OnAnyUnitDead_Server;
    }

    [ServerCallback]
    private void OnAnyUnitDead_Server(object sender, EventArgs e)
    {
        var um = UnitManager.Instance;
        if (um == null) return;

        int friendly = um.GetFriendlyUnitList().Count; // hostin puoli
        int enemy = um.GetEnemyUnitList().Count;      // ei-hostin puoli

        Debug.Log($"EndgameAnnouncer: Units remaining - Friendly: {friendly}, Enemy: {enemy}");

        bool end = (enemy <= 0) || (friendly <= 0);
        if (!end) return;

        bool hostWon = enemy <= 0;

        // Lähetä kullekin clientille oma viesti
        foreach (var kv in NetworkServer.connections)
        {
            var conn = kv.Value;
            if (conn?.identity == null) continue;

            var pc = conn.identity.GetComponent<PlayerController>();
            if (pc == null) continue;

            bool isHostConn = conn.connectionId == 0;
            bool youWon = hostWon ? isHostConn : !isHostConn;

            pc.TargetShowEnd(conn, youWon);
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/GameNetworkManager.cs

```
using System;
using System.Collections.Generic;
using Mirror;
using UnityEngine;
using Unity.Services.Relay.Models;
using UnityEngine.SceneManagement;

namespace Utp
{
    [RequireComponent(typeof(UtpTransport))]
    public class GameNetworkManager : NetworkManager
    {
        public static GameNetworkManager Instance { get; private set; }

        private readonly List<NetworkConnectionToClient> _pendingConns = new();

        [SerializeField] private int hideJoinCodeAfterConnections = 2; // Host + 1 client

        public int HideJoinCodeAfterConnections => Mathf.Max(1, hideJoinCodeAfterConnections);

        private UtpTransport utpTransport;

        /// <summary>
        /// Server's join code if using Relay.
        /// </summary>
        public string relayJoinCode = "";

        public override void Awake()
        {
            if (Instance != null && Instance != this)
            {
                Debug.LogError("There's more than one GameNetworkManager! " + transform + " - " + Instance);
                Destroy(gameObject);
                return;
            }
            Instance = this;

            base.Awake();
            autoCreatePlayer = false;

            utpTransport = GetComponent<UtpTransport>();

            string[] args = Environment.GetCommandLineArgs();
            for (int key = 0; key < args.Length; key++)
            {
                if (args[key] == "-port")
                {
                    if (key + 1 < args.Length)
                    {

```

RogueShooter – All Scripts

```
        string value = args[key + 1];

        try
        {
            utpTransport.Port = ushort.Parse(value);
        }
        catch
        {
            UtpLog.Warning($"Unable to parse {value} into transport Port");
        }
    }
}

public override void OnStartServer()
{
    base.OnStartServer();
    LevelLoader.LevelReady += OnLevelReady_Server;

    SpawnUnitsCoordinator.Instance.SetEnemiesSpawned(false);
}

public override void OnStopServer()
{
    LevelLoader.LevelReady -= OnLevelReady_Server;
    base.OnStopServer();
}
/*
void OnEnable()
{
    LevelLoader.LevelReady += OnLevelReady_Server;
}
*/

void OnDisable() { LevelLoader.LevelReady -= OnLevelReady_Server; }

[ServerCallback]
public override void OnDestroy()
{
    LevelLoader.LevelReady -= OnLevelReady_Server;
}

[Server]
private void OnLevelReady_Server(Scene mapScene)
{
    if (!NetworkServer.active) return;

    Debug.Log("[GameNetworkManager] OnLevelReady_Server - Processing level ready");

    // 1) Ensilataus: pending-jonon finalisointi
```

RogueShooter – All Scripts

```
foreach (var c in _pendingConns)
    if (c != null) ServerFinalizeAddPlayer(c);
_pendingConns.Clear();

// 2) RELOAD: spawn kaikille aktiivisille conneille
Debug.Log($"[GameNetworkManager] Active connections: {NetworkServer.connections.Count}");

foreach (var kv in NetworkServer.connections)
{
    var conn = kv.Value;
    if (conn == null) continue;

    Debug.Log($"[GameNetworkManager] Processing conn {conn.connectionId}, identity: {(conn.identity != null ? conn.identity.name : "NULL")}");

    // Jos identity on null, luo se uudelleen
    if (conn.identity == null)
    {
        Debug.Log($"[GameNetworkManager] Creating new PlayerController for conn {conn.connectionId}");
        if (playerPrefab != null)
        {
            base.OnServerAddPlayer(conn);
        }
        else
        {
            Debug.LogError("[GameNetworkManager] PlayerPrefab is null!");
            continue;
        }
    }
}

// Tarkista onko uniteja
uint ownerId = conn.identity != null ? conn.identity.netId : 0u;
bool hasUnits = ownerId != 0 && HasOwnedUnit(ownerId);

Debug.Log($"[GameNetworkManager] Conn {conn.connectionId} - ownerId: {ownerId}, hasUnits: {hasUnits}");

if (!hasUnits)
{
    bool isHost = conn == NetworkServer.localConnection;
    Debug.Log($"[GameNetworkManager] Spawning units for {(isHost ? "HOST" : "CLIENT")} (conn {conn.connectionId})");

    var units = SpawnUnitsCoordinator.Instance?.SpawnPlayersForNetwork(conn, isHost);
    if (units != null)
    {
        Debug.Log($"[GameNetworkManager] Successfully spawned {units.Length} units for conn {conn.connectionId}");
    }
    else
    {
        Debug.LogWarning($"[GameNetworkManager] Failed to spawn units for conn {conn.connectionId}");
    }
}
}
```

RogueShooter – All Scripts

```
// 3) Viholliset jos tarvitaan
if (GameManager.SelectedMode == GameMode.CoOp)
{
    if (!SpawnUnitsCoordinator.Instance.AreEnemiesSpawned())
    {
        Debug.Log("[GameNetworkManager] Spawning enemies for Co-op mode");
        ServerSpawnEnemies();
    }
}

// 4) Käynnistä uusi matsi
LevelGrid.Instance?.RebuildOccupancyFromScene();
EdgeBaker.Instance?.BakeAllEdges();
NetTurnManager.Instance?.ServerResetAndBegin();

Debug.Log("[GameNetworkManager] OnLevelReady_Server - Complete");
}

[Server]
private bool HasOwnedUnit(uint ownerNetId)
{
    var units = FindObjectsByType<Unit>(FindObjectsSortMode.None);
    for (int i = 0; i < units.Length; i++)
        if (units[i] && units[i].OwnerId == ownerNetId)
            return true;
    return false;
}

/// <summary>
/// Get the port the server is listening on.
/// </summary>
/// <returns>The port.</returns>
public ushort GetPort()
{
    return utpTransport.Port;
}

/// <summary>
/// Get whether Relay is enabled or not.
/// </summary>
/// <returns>True if enabled, false otherwise.</returns>
public bool IsRelayEnabled()
{
    return utpTransport.useRelay;
}

/// <summary>
/// Ensures Relay is disabled. Starts the server, listening for incoming connections.
/// </summary>
public void StartStandardServer()
{
}
```

RogueShooter – All Scripts

```
    utpTransport.useRelay = false;
    StartServer();
}

/// <summary>
/// Ensures Relay is disabled. Starts a network "host" - a server and client in the same application
/// </summary>
public void StartStandardHost()
{
    utpTransport.useRelay = false;
    StartHost();
}

/// <summary>
/// Gets available Relay regions.
/// </summary>
///
public void GetRelayRegions(Action<List<Region>> onSuccess, Action onFailure)
{
    utpTransport.GetRelayRegions(onSuccess, onFailure);
}

/// <summary>
/// Ensures Relay is enabled. Starts a network "host" - a server and client in the same application
/// </summary>
public void StartRelayHost(int maxPlayers, string regionId = null)
{
    utpTransport.useRelay = true;
    utpTransport.AllocateRelayServer(maxPlayers, regionId,
    (string joinCode) =>
    {
        relayJoinCode = joinCode;
        // Debug.LogError($"Relay join code: {joinCode}");
        Debug.Log($"Relay join code: {joinCode}");
        StartHost();
    },
    () =>
    {
        UtpLog.Error($"Failed to start a Relay host.");
    });
}

/// <summary>
/// Ensures Relay is disabled. Starts the client, connects it to the server with networkAddress.
/// </summary>
public void JoinStandardServer()
{
    utpTransport.useRelay = false;
    StartClient();
}

/// <summary>
```

RogueShooter – All Scripts

```
/// Ensures Relay is enabled. Starts the client, connects to the server with the relayJoinCode.
/// </summary>
public void JoinRelayServer()
{
    utpTransport.useRelay = true;
    utpTransport.ConfigureClientWithJoinCode(relayJoinCode,
    () =>
    {
        StartClient();
    },
    () =>
    {
        UtpLog.Error($"Failed to join Relay server.");
    });
}

public override void OnValidate()
{
    base.OnValidate();
}

/// <summary>
/// Make sure that the clien sends a AddPlayer request once the scene is loaded.
/// </summary>
public override void OnClientSceneChanged()
{
    base.OnClientSceneChanged();

    Debug.Log($"[NM] OnClientSceneChanged - ready: {NetworkClient.ready}");

    if (!NetworkClient.ready)
        NetworkClient.Ready();

    // Pyydä pelaaja jos ei vielä ole
    if (NetworkClient.connection != null && NetworkClient.connection.identity == null)
    {
        Debug.Log("[NM] OnClientSceneChanged requesting player via AddPlayer()");
        NetworkClient.AddPlayer();
    }
}

public override void OnClientConnect()
{
    base.OnClientConnect();

    Debug.Log($"[NM] OnClientConnect - NetworkClient.ready: {NetworkClient.ready}");

    // Varmista että client on ready
    if (!NetworkClient.ready)
    {
        NetworkClient.Ready();
    }
}
```


RogueShooter – All Scripts

```
// Pyydä pelaaja heti
if (NetworkClient.connection != null && NetworkClient.connection.identity == null)
{
    Debug.Log("[NM] Client requesting player via AddPlayer()");
    NetworkClient.AddPlayer();
}
}

public override void OnStopClient()
{
    base.OnStopClient();
}

public override void OnClientDisconnect()
{
    base.OnClientDisconnect();
}

/// <summary>
/// Tämä metodi spawnaa jokaiselle clientille oman Unitin ja tekee siitä heidän ohjattavan yksikkönsä.
/// </summary>
public override void OnServerAddPlayer(NetworkConnectionToClient conn)
{
    Debug.Log($"[NM] ===== OnServerAddPlayer called for conn {conn.connectionId} =====");
    Debug.Log($"[NM] LevelLoader.IsServerLevelReady = {LevelLoader.IsServerLevelReady}");
    Debug.Log($"[NM] NetworkServer.active = {NetworkServer.active}");

    if (!LevelLoader.IsServerLevelReady)
    {
        _pendingConns.Add(conn);
        Debug.Log($"[NM] 🛑 Queued player join (conn {conn.connectionId}) until LevelReady. Pending count: {_pendingConns.Count}");
        return;
    }

    Debug.Log($"[NM] ✅ Level ready, calling ServerFinalizeAddPlayer for conn {conn.connectionId}");
    ServerFinalizeAddPlayer(conn);
}

[Server]
private void ServerFinalizeAddPlayer(NetworkConnectionToClient conn)
{
    Debug.Log($"[NM] ServerFinalizeAddPlayer for conn {conn.connectionId}");

    if (conn.identity == null)
    {
        if (playerPrefab == null)
        {
            Debug.LogError("[NM] Player Prefab puuttuu!");
            return;
        }
    }
}
```

RogueShooter – All Scripts

```
base.OnServerAddPlayer(conn);
}

bool isHost = conn.connectionId == 0;

var spawner = SpawnUnitsCoordinator.Instance;
if (spawner == null)
{
    Debug.LogError("[NM] SpawnUnitsCoordinator.Instance puuttuu!");
    return;
}

// Spawna yksiköt JOKAISELLE pelaajalle (host JA client)
Debug.Log($"[NM] Spawning units for {(isHost ? "HOST" : "CLIENT")} conn {conn.connectionId}");
var units = spawner.SpawnPlayersForNetwork(conn, isHost);

if (units != null && units.Length > 0)
{
    Debug.Log($"[NM] Spawned {units.Length} units for conn {conn.connectionId}");
}

// Loput koodista...
var turnMgr = NetTurnManager.Instance;
if (turnMgr != null)
    turnMgr.ServerUpdateRequiredCount(NetworkServer.connections.Count);

if (NetTurnManager.Instance && NetTurnManager.Instance.phase == TurnPhase.Players)
{
    var pc = conn.identity ? conn.identity.GetComponent<PlayerController>() : null;
    if (pc != null) pc.ServerSetHasEnded(false);
}

if (CoopTurnCoordinator.Instance && NetTurnManager.Instance)
{
    CoopTurnCoordinator.Instance.RpcTurnPhaseChanged(
        NetTurnManager.Instance.phase,
        NetTurnManager.Instance.turnNumber,
        true
    );
}

if (GameModeManager.SelectedMode == GameMode.Versus)
{
    var pc = conn.identity ? conn.identity.GetComponent<PlayerController>() : null;
    if (pc != null && PvPTurnCoordinator.Instance != null)
        PvPTurnCoordinator.Instance.ServerRegisterPlayer(pc);
}
}

/*
[Server]
public void ServerSpawnEnemies()
```

RogueShooter – All Scripts

```
{
    // Pyydä SpawnUnitsCoordinatoria luomaan viholliset
    var enemies = SpawnUnitsCoordinator.Instance.SpawnEnemies();

    // Synkronoi viholliset verkkoon Mirrorin avulla
    foreach (var enemy in enemies)
    {
        if (enemy != null)
        {
            NetworkServer.Spawn(enemy);
        }
    }
}
*/

[Server]
public void ServerSpawnEnemies()
{
    var enemies = SpawnUnitsCoordinator.Instance.SpawnEnemies();

    foreach (var enemy in enemies)
    {
        if (enemy == null) continue;

        NetworkServer.Spawn(enemy); // olemassa oleva rivi

        // UUSI: pakota oikea alkulayout
        var vis = enemy.GetComponentInChildren<WeaponVisibilitySync>();
        if (vis) vis.ServerForceSet(rifleRight: true, rifleLeft: false, meleeLeft: false, grenade: false);
    }
}

public override void OnServerDisconnect(NetworkConnectionToClient conn)
{
    base.OnServerDisconnect(conn);
    // päivitä pelaajamäärä koordinaattorille
    var coord = NetTurnManager.Instance;
    //var coord = CoopTurnCoordinator.Instance;
    if (coord != null)
        coord.ServerUpdateRequiredCount(NetworkServer.connections.Count);
}

public bool IsNetworkActive()
{
    return GetNetWorkServerActive() || GetNetWorkClientConnected();
}

public bool GetNetWorkServerActive()
{
    return NetworkServer.active;
}
```

RogueShooter – All Scripts

```
public bool GetNetWorkClientConnected()
{
    return NetworkClient.isConnected;
}

public NetworkConnection NetWorkClientConnection()
{
    return NetworkClient.connection;
}

public void NetworkDestroy(GameObject go)
{
    NetworkServer.Destroy(go);
}

public void SetEnemies()
{
    SpawnUnitsCoordinator.Instance.SetEnemiesSpawned(false);

    if (GameModeManager.SelectedMode == GameMode.CoOp)
    {
        ServerSpawnEnemies();
    }
}
}
```

RogueShooter – All Scripts

Assets/scripts/Online/NetLevelLoader.cs

```
using System.Collections;
using System.Collections.Generic;
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;

public class NetLevelLoader : NetworkBehaviour
{
    public static NetLevelLoader Instance { get; private set; }

    [SyncVar(hook = nameof(OnLevelChanged))]
    private string _currentLevel;

    [SerializeField] private string _fallbackDefaultLevelName; // valinnainen: aseta Inspectorissa jos haluat

    private int _reloadTick = 0;
    private readonly HashSet<int> _clientReadyAcks = new HashSet<int>();

    private static bool _clientIsLoading;
    private static string _clientPreparedLevel;

    [Header("Catalog")]
    [SerializeField] private LevelCatalog catalog;
    [SerializeField] private int currentIndex = -1; // tällä hetkellä ladattu kartta (katalogin indeksi)

    public int CurrentIndex => currentIndex;

    private void Awake()
    {
        if (Instance != null && Instance != this)
        {
            Debug.LogError("There's more than one NetLevelLoader! " + transform + " - " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;
    }

    public override void OnStartServer()
    {
        base.OnStartServer();

        int idx = ResolveDefaultIndex();
        var sceneName = catalog.Get(idx).sceneName;
        _currentLevel = sceneName;
        currentIndex = idx;
        Debug.Log($"[NetLevelLoader] (SERVER) OnStartServer → loading index {idx}");
        StartCo(Co_LoadLevel(idx));
    }
}
```

RogueShooter – All Scripts

```
public override void OnStartClient()
{
    base.OnStartClient();
}

void OnLevelChanged(string oldValue, string newValue)
{
    if (isServer) return;
    if (string.IsNullOrEmpty(newValue)) return;
    if (newValue.StartsWith("__RELOAD_TICK__")) return;

    if (_clientPreparedLevel == newValue)
    {
        Debug.Log($"[NetLevelLoader] (CLIENT) OnLevelChanged ignored - already prepared '{newValue}'");
        _clientPreparedLevel = null;
        return;
    }

    Debug.Log($"[NetLevelLoader] (CLIENT) OnLevelChanged triggered → '{newValue}'");
    StartCoroutine(Co_LoadLevel_Client(newValue));
}

[Server]
public void ServerLoadLevel(string levelName)
{
    if (string.IsNullOrEmpty(levelName))
    {
        Debug.LogError("[NetLevelLoader] ServerLoadLevel sai tyhjän scenenimen.");
        return;
    }

    StopAllCoroutines();
    StartCo(Co_ReloadLevel_All(levelName));
}

[Server]
private IEnumerator Co_ReloadLevel_All(string levelName)
{
    string coreName = LevelLoader.Instance?.CoreSceneName ?? "Core";

    _reloadTick++;
    _clientReadyAcks.Clear();

    Debug.Log($"[NetLevelLoader] (SERVER) ===== RELOAD ALL START → '{levelName}', tick={_reloadTick} =====");

    _currentLevel = $"__RELOAD_TICK__{_reloadTick}";
    RpcClientPrepareReload(coreName, levelName, _reloadTick);

    int expectedClients = ExpectedClientCount();
    Debug.Log($"[NetLevelLoader] (SERVER) Waiting for {expectedClients} clients to be ready...");
}
```

RogueShooter – All Scripts

```
float timeout = 15f;
float elapsed = 0f;

while (_clientReadyAcks.Count < expectedClients && elapsed < timeout)
{
    yield return null;
    elapsed += Time.deltaTime;
}

if (elapsed >= timeout)
{
    Debug.LogWarning($"[NetLevelLoader] (SERVER) Timeout! Got {_clientReadyAcks.Count}/{expectedClients} acks");
}
else
{
    Debug.Log($"[NetLevelLoader] (SERVER) All {_clientReadyAcks.Count} clients ready!");
}

int idx = IndexOfScene(levelName);
if (idx < 0) idx = ResolveDefaultIndex();

_currentLevel = levelName;
yield return StartCoroutine(Co_LoadLevel(idx));
}

private IEnumerator Co_LoadLevel(int index)
{
    // 0) Siivous + unload edellinen (jo teillä koodissa)
    UnitManager.Instance?.ClearAllUnitLists();

    var current = CurrentSceneName;
    if (!string.IsNullOrEmpty(current)) {
        var s = SceneManager.GetSceneByName(current);
        if (s.isLoaded) {
            var opUnload = SceneManager.UnloadSceneAsync(s);
            while (!opUnload.isDone) yield return null;
        }
    }

    // 1) Lataa uusi additiivisesti (jo teillä)
    var entry = catalog.Get(index);
    var sceneName = entry.sceneName;
    _currentLevel = sceneName;

    var opLoad = SceneManager.LoadSceneAsync(sceneName, LoadSceneMode.Additive);
    while (!opLoad.isDone) yield return null;

    // 2) Aseta map aktiiviseksi ja anna 1-2 framea heräämiseen
    Scene newScene = SceneManager.GetSceneByName(sceneName);
    SceneManager.SetActiveScene(newScene);
    yield return null;
}
```

RogueShooter – All Scripts

```
// ★ TÄRKEÄT LISÄYKSET (kuten string-polussa)
Debug.Log($"[NetLevelLoader] (SERVER) Spawning scene NetworkObjects (catalog path)");
NetworkServer.SpawnObjects(); // pakollinen additiivisen scenen scene-objekteille
yield return null;
EdgeBaker.Instance?.BakeAllEdges();

// 3) Päivitä indeksi vasta onnistumisen jälkeen (jo teillä)
currentIndex = index;

// 4) Palauta Core aktiiviseksi jos haluat samaan tapaan kuin toisessa polussa
var coreName = LevelLoader.Instance?.CoreSceneName ?? "Core";
var core = SceneManager.GetSceneByName(coreName);
if (core.IsValid() && core.isLoaded)
    SceneManager.SetActiveScene(core);

// 5) Ilmoita että servupuoli on valmis → käynnistää OnLevelReady_Server-ketjun
LevelLoader.SetServerLevelReady(true);
LevelLoader.RaiseLevelReady(newScene); // 🚩 tämä käynnistää GameNetworkManagerin spawnit
Debug.Log($"[NetLevelLoader] (SERVER) ===== LEVEL LOAD COMPLETE (catalog): '{sceneName}' =====");

// 6) (valinn.) UI-siivo RPC: kuten teillä jo on
RpcOnLevelLoaded(sceneName, currentIndex);
}

[ClientRpc]
private void RpcClientPrepareReload(string coreName, string levelName, int tick)
{
    if (isServer) return;

    StartCoroutine(Co_ClientPrepareAndAck(coreName, levelName, tick));
}

[Client]
private IEnumerator Co_ClientPrepareAndAck(string coreName, string levelName, int tick)
{
    Debug.Log($"[NetLevelLoader] (CLIENT) ===== PREPARE RELOAD START → '{levelName}', tick={tick} =====");

    int n = DebrisUtil.DestroyAllDebrisExceptCore(coreName);
    if (n > 0) Debug.Log($"[NetLevelLoader] (CLIENT) Cleared {n} debris objects");

    yield return Co_LoadLevel_Client_Internal(levelName);

    _clientPreparedLevel = levelName;

    Debug.Log($"[NetLevelLoader] (CLIENT) Scene ready, sending ACK for tick {tick}");
    CmdAckSceneReady(tick);
}

[Command(requiresAuthority = false)]
void CmdAckSceneReady(int tick, NetworkConnectionToClient sender = null)
{
}
```


RogueShooter – All Scripts

```
        if (tick != _reloadTick || sender == null) return;

        Debug.Log($"[NetLevelLoader] (SERVER) Received ACK from conn {sender.connectionId} for tick {tick}");
        _clientReadyAcks.Add(sender.connectionId);
    }

    [Server]
    int ExpectedClientCount()
    {
        int c = 0;
        foreach (var kv in NetworkServer.connections)
        {
            if (kv.Value != null && kv.Value.isAuthenticated)
            {
                if (kv.Value == NetworkServer.localConnection)
                    continue;
                c++;
            }
        }
        return c;
    }

    [Client]
    private IEnumerator Co_LoadLevel_Client(string levelName)
    {
        if (_clientIsLoading)
        {
            Debug.Log($"[NetLevelLoader] (CLIENT) Already loading, skipping duplicate");
            yield break;
        }

        _clientIsLoading = true;

        try
        {
            yield return Co_LoadLevel_Client_Internal(levelName);
        }
        finally
        {
            _clientIsLoading = false;
        }
    }

    [Client]
    private IEnumerator Co_LoadLevel_Client_Internal(string levelName)
    {
        string coreName = LevelLoader.Instance?.CoreSceneName ?? "Core";

        Debug.Log($"[NetLevelLoader] (CLIENT) Start reload → '{levelName}'");

        var core = SceneManager.GetSceneByName(coreName);
        if (!core.IsValid() || !core.isLoaded)
```

RogueShooter – All Scripts

```
{
    Debug.Log($"[NetLevelLoader] (CLIENT) Loading Core scene");
    var loadCore = SceneManager.LoadSceneAsync(coreName, LoadSceneMode.Additive);
    while (!loadCore.isDone) yield return null;
    core = SceneManager.GetSceneByName(coreName);
}
SceneManager.SetActiveScene(core);

for (int i = 0; i < SceneManager.sceneCount; i++)
{
    var s = SceneManager.GetSceneAt(i);
    if (!s.isLoaded || s.name == coreName) continue;

    Debug.Log($"[NetLevelLoader] (CLIENT) Unloading scene '{s.name}'");
    yield return SceneManager.UnloadSceneAsync(s);
    i = -1;
}

Debug.Log($"[NetLevelLoader] (CLIENT) Loading level '{levelName}'");
var op2 = SceneManager.LoadSceneAsync(levelName, LoadSceneMode.Additive);
while (!op2.isDone) yield return null;

var map = SceneManager.GetSceneByName(levelName);
if (!map.IsValid() || !map.isLoaded)
{
    Debug.LogError($"[NetLevelLoader] (CLIENT) Failed to load '{levelName}'. Is it in Build Settings?");
    yield break;
}

SceneManager.SetActiveScene(map);
yield return null;
SceneManager.SetActiveScene(core);
LevelLoader.RaiseLevelReady(map);

Debug.Log($"[NetLevelLoader] (CLIENT) Reload complete → '{levelName}'");
}

private void StartCo(IEnumerator r)
{
    if (isActiveAndEnabled) StartCoroutine(r);
    //else GlobalCoroutineHost.StartRoutine(r);
}

[Server]
public void ServerReloadCurrentLevel()
{
    if (currentIndex < 0) currentIndex = ResolveDefaultIndex();

    var entry = catalog.Get(currentIndex);
    if (entry == null)
    {
        Debug.LogError($"[NetLevelLoader] Cannot reload - invalid index {currentIndex}");
    }
}
```

RogueShooter – All Scripts

```
        return;
    }

    string sceneName = entry.sceneName;
    Debug.Log($"[NetLevelLoader] ServerReloadCurrentLevel → reloading '{sceneName}' (index {currentIndex})");

    StopAllCoroutines();
    StartCo(Co_ReloadLevel_All(sceneName));
}

public string CurrentSceneName =>
    (catalog != null && catalog.Count > 0) ? catalog.Get(currentIndex)?.sceneName : null;

// Julkinen entry point: lataa nimen perusteella
[Server]
public void ServerLoadLevelByName(string sceneName) {
    if (catalog == null) { Debug.LogError("[NetLevelLoader] Catalog puuttuu"); return; }
    int i = catalog.IndexOfScene(sceneName);
    if (i < 0) { Debug.LogError($"[NetLevelLoader] Scene '{sceneName}' ei löydy catalogista"); return; }
    ServerLoadLevelByIndex(i);
}

// Julkinen entry point: lataa indeksillä
[Server]
public void ServerLoadLevelByIndex(int index) {
    if (catalog == null || catalog.Count == 0) { Debug.LogError("[NetLevelLoader] Catalog tyhjä"); return; }
    if (index < 0 || index >= catalog.Count) { Debug.LogError("[NetLevelLoader] Index out of range"); return; }

    StartCoroutine(Co_LoadLevel(index));
}

[Server]
public void ServerLoadNextLevelLoop() {
    if (catalog == null || catalog.Count == 0) return;
    int next = (currentIndex + 1) % catalog.Count;
    ServerLoadLevelByIndex(next);
}

[ClientRpc]
void RpcOnLevelLoaded(string sceneName, int index)
{
    // Client-päässä: UI/HUD siivous, WinPanel piiloon jne.
    var win = FindFirstObjectByType<WinBattle>(FindObjectsInactive.Include);
    if (win) win.HideEndPanel();
}

public string ResolveDefaultLevelName()
{
    // 1) Jos _currentLevel on jo asetettu (esim. edellisestä pelistä / valikosta)
    if (!string.IsNullOrEmpty(_currentLevel)) return _currentLevel;
```

RogueShooter – All Scripts

```
// 2) Jos LevelLoaderissa on määritelty oletus
if (LevelLoader.Instance && !string.IsNullOrEmpty(LevelLoader.Instance.DefaultLevel))
    return LevelLoader.Instance.DefaultLevel;

// 3) Lopuksi oma (inspectorista asetettava) fallback
if (!string.IsNullOrEmpty(_fallbackDefaultLevelName))
    return _fallbackDefaultLevelName;

// 4) Ei keksitty mitään
Debug.LogError("[NetLevelLoader] ResolveDefaultLevelName() epäonnistui: ei current/default/fallback-nimeä.");
return null;
}

public int IndexOfScene(string sceneName)
{
    if (catalog == null) return -1;
    return catalog.IndexOfScene(sceneName); // LevelCatalogissa on tämä valmiina
}

// 2) Oletusindeksin ratkaisu ilman defaultIndex-kenttää
public int ResolveDefaultIndex()
{
    // Jos katalogi puuttuu/tyhjä → 0
    if (catalog == null || catalog.Count == 0) return 0;

    // a) Yritä LevelLoaderin oletusnimeä
    if (LevelLoader.Instance && !string.IsNullOrEmpty(LevelLoader.Instance.DefaultLevel))
    {
        int idx = catalog.IndexOfScene(LevelLoader.Instance.DefaultLevel);
        if (idx >= 0) return idx;
    }

    // b) Jos _currentLevel on asetettu (esim. aiemmasta pelistä)
    if (!string.IsNullOrEmpty(_currentLevel))
    {
        int idx = catalog.IndexOfScene(_currentLevel);
        if (idx >= 0) return idx;
    }

    // c) Fallback: katalogin ensimmäinen
    return 0;
}
}
```

RogueShooter – All Scripts

Assets/scripts/Online/NetSceneReload.cs

```
using Mirror;
using UnityEngine.SceneManagement;

public static class NetSceneReload {

    /*
    public static void ReloadForAll()
    {
        string sceneName = SceneManager.GetActiveScene().name;
        NetworkManager.singleton.ServerChangeScene(sceneName);
    }
    */
}
```

RogueShooter – All Scripts

Assets/scripts/Online/NetTurnManager.cs

```
using UnityEngine;
using Mirror;
using System.Collections.Generic;
using System.Collections;
using System.Linq;
///<summary>
/// NetTurnManager coordinates turn phases in a networked multiplayer game.
/// It tracks which players have ended their turns and advances the game phase accordingly.
///</summary>
public enum TurnPhase { Players, Enemy }
public class NetTurnManager : NetworkBehaviour
{
    public static NetTurnManager Instance { get; private set; }
    [SyncVar] public TurnPhase phase = TurnPhase.Players;
    [SyncVar] public int turnNumber = 1;

    // Seurannat (server)
    [SyncVar] public int endedCount = 0;
    [SyncVar] public int requiredCount = 0; // päivitetään kun pelaajia liittyy/lähtee

    public readonly HashSet<uint> endedPlayers = new();

    void Awake()
    {
        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;
    }

    public override void OnStartServer()
    {
        base.OnStartServer();
        // jos haluat lukita kahteen pelaajaan protoa varten:
        if (GameManager.SelectedMode == GameMode.CoOp) requiredCount = 2;
        StartCoroutine(DeferResetOneFrame());
    }

    [Server]
    private IEnumerator DeferResetOneFrame()
    {
        yield return null; // odota että SpawnObjects on valmis
        ResetTurnState(); // nyt RpcUpdateReadyStatus on turvallinen
    }

    [Server]
    public void ResetTurnState()
    {
        phase = TurnPhase.Players;
        endedPlayers.Clear();
        endedCount = 0;
    }
}
```

RogueShooter – All Scripts

```
    SetPlayerStartState();
}

[Server]
public void ServerPlayerEndedTurn(uint playerNetId)
{
    // PvP: siirrä vuoro heti vastustajalle
    if (GameManager.SelectedMode == GameMode.Versus)
    {
        if (PvPTurnCoordinator.Instance)
            PvPTurnCoordinator.Instance.ServerHandlePlayerEndedTurn(playerNetId);
        return;
    }

    if (phase != TurnPhase.Players) return;          // ei lasketa jos ei pelaajavuoro
    if (!endedPlayers.Add(playerNetId)) return;       // älä laske tuplia

    endedCount = endedPlayers.Count;

    // Ilmoita kaikille, KUKA on valmis → UI näyttää "Player X READY" toisella pelaajalla. Käytössä vain Co-opissa
    if (GameManager.SelectedMode == GameMode.CoOp)
    {
        // Asettaa yksiköiden UI Näkyvyydet
        UnitUIBroadcaster.Instance.BroadcastUnitWorldUIVisibility(false);

        CoopTurnCoordinator.Instance.
            RpcUpdateReadyStatus(
                endedPlayers.Select(id => (int)id).ToArray(),
                CoopTurnCoordinator.Instance.BuildEndedLabels()
            );

        CoopTurnCoordinator.Instance.TryAdvanceIfReady();
    }
}

[Server]
public void ServerUpdateRequiredCount(int playersNow)
{
    requiredCount = Mathf.Max(1, playersNow); // Co-opissa yleensä 2
                                              // jos yksi poistui kesken odotuksen, tarkista täyttyikö ehto nyt

    if (GameManager.SelectedMode == GameMode.CoOp)
    {
        CoopTurnCoordinator.Instance.TryAdvanceIfReady();
    }
}

public void SetPlayerStartState()
{
    // Asettaa pelaajan tilan pelaajan vuoroksi.
    foreach (var kvp in NetworkServer.connections)
    {
```

RogueShooter – All Scripts

```
        var id = kvp.Value.identity;
        if (!id) continue;
        var pc = id.GetComponent<PlayerController>();
        if (pc) pc.ServerSetHasEnded(false); // <<< TÄRKEIN RIVI
    }
}

/// <summary>
/// Serverillä: nollaa vuorot ja aloittaa Players-vaiheen. Kutsutaan aina kun leveli latautuu (myös reloadissa).
/// </summary>
/// <param name="resetTurnNumber">Jos true, turnNumber asetetaan 1:een. Jos false, säilytetään nykyinen (tai voit itse inkrementoida muualla).</param>
[Server]
public void ServerResetAndBegin(bool resetTurnNumber = true)
{
    // Co-op: laske tällä hetkellä aktiiviset pelaajat ja päivitä requiredCount
    if (GameManager.SelectedMode == GameMode.CoOp)
    {
        int playersNow = 0;
        foreach (var kv in NetworkServer.connections)
            if (kv.Value != null && kv.Value.identity != null) playersNow++;

        ServerUpdateRequiredCount(playersNow);
    }

    if (resetTurnNumber)
        turnNumber = 1;

    if (GameManager.SelectedMode == GameMode.Versus && PvPTurnCoordinator.Instance)
    {
        PvPTurnCoordinator.Instance.ServerGiveFirstTurnToHost();
    }

    ResetTurnState();
}
}
```


RogueShooter – All Scripts

Assets/scripts/Online/NetVisibility.cs

```
using Mirror;
using UnityEngine;

public class NetVisibility : NetworkBehaviour
{
    [SerializeField] private GameObject target; // se esine jonka näkyvyyttä halutaan ohjata

    [SyncVar(hook = nameof(OnChanged))]
    private bool isVisible;

    void OnChanged(bool _, bool now) => Apply(now);

    public override void OnStartClient() => Apply(isVisible);

    private void Apply(bool now)
    {
        if (target) target.SetActive(now);
    }

    // --- SERVER-API ---
    [Server] public void ServerShow()          { isVisible = true;  Apply(true); }
    [Server] public void ServerHide()         { isVisible = false; Apply(false); }
    [Server] public void ServerSetVisible(bool v){ isVisible = v;    Apply(v);    }

    // --- CLIENT-API (authority) ---
    [Command] private void CmdSetVisible(bool v) => ServerSetVisible(v);

    /// Kutsu tätä mistä tahansa: hoitaa sekä server- että client-puolen.
    public void SetVisibleAny(bool v)
    {
        if (isServer) ServerSetVisible(v);
        else          CmdSetVisible(v); // vaatii client authorityn tälle objektille
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/NetWorkSceneBinder.cs

```
using System.Collections;
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;
/// <summary>
/// Tämä pitää huolen siitä että kaikki objektit luodaan clientille oikeaan Level skeneen, kun client liittyy peliin.
/// Ilman tätä kaikki luotavat objektit latautuisivat Coreen, mikä ei ole toivottavaa.
/// Käytä tätä kaikissa sellaisissa objekteissa jotka täytyy kentän latautuessa siirtyä oikeaan sceneen.
/// Esim Unit, Tuhoutuvat objektit jne.
/// Huom! SpawnRouter hoitaa objekti siirron oikeaan sceneen varsinainen pelin aikana.
/// </summary>
[DisallowMultipleComponent]
public class NetworkSceneBinder : NetworkBehaviour
{
    [SyncVar] public string targetSceneName; // server täyttää tämän ennen spawnia

    public override void OnStartClient()
    {
        base.OnStartClient();
        // Hostilla server on jo siirtänyt oikein - ei tarvetta uudelleen siirtoon
        if (isServer) return;

        if (!string.IsNullOrEmpty(targetSceneName))
            StartCoroutine(MoveWhenLoaded(targetSceneName));
    }

    private IEnumerator MoveWhenLoaded(string sceneName)
    {
        // odota että kohdescene on varmasti ladattu clientillä
        while (true)
        {
            {
                var sc = SceneManager.GetSceneByName(sceneName);
                if (sc.IsValid() && sc.isLoaded)
                {
                    SceneManager.MoveGameObjectToScene(gameObject, sc);
                    yield break;
                }
            }
            yield return null;
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/PvpPerception.cs

```
using System.Reflection;
using Mirror;
using UnityEngine;

public class PvpPerception : MonoBehaviour
{
    // Kutsu tätä aina kun vuoro vaihtuu (ja bootstrapissa)
    public static void ApplyEnemyFlagsLocally(bool isMyTurn)
    {
        var units = FindObjectsByType<Unit>(FindObjectsSortMode.None);

        foreach (var u in units)
        {
            var ni = u.GetComponent<NetworkIdentity>();
            if (!ni) continue;

            // Onko tämä yksikkö minun (tässä clientissä)?
            bool unitIsMine = ni.isOwned || ni.isLocalPlayer;

            // Vuorologiikka:
            // - Jos on MINUN vuoro: vastustajan yksiköt ovat enemy
            // - Jos EI ole minun vuoro: MINUN omat yksiköt ovat enemy
            bool enemy = isMyTurn ? !unitIsMine : unitIsMine;

            SetUnitEnemyFlag(u, enemy);
        }
    }

    static void SetUnitEnemyFlag(Unit u, bool enemy)
    {
        // Unitissa on [SerializeField] private bool isEnemy; -> käytä BindingFlagsia! :contentReference[oaicite:1]{index=1}
        var field = typeof(Unit).GetField("isEnemy",
            BindingFlags.Instance | BindingFlags.NonPublic | BindingFlags.Public);
        if (field != null) { field.SetValue(u, enemy); return; }

        // Varalle, jos joskus lisäät setterin
        var m = typeof(Unit).GetMethod("SetEnemy",
            BindingFlags.Instance | BindingFlags.Public | BindingFlags.NonPublic,
            null, new[] { typeof(bool) }, null);
        if (m != null) { m.Invoke(u, new object[] { enemy }); return; }

        Debug.LogWarning("[PvP] Unitilta puuttuu isEnemy/SetEnemy(bool). Lisää jompikumpi.");
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/PvPTurnCoordinator.cs

```
using System.Collections.Generic;
using System.Linq;
using Mirror;

public class PvPTurnCoordinator : NetworkBehaviour
{
    public static PvPTurnCoordinator Instance { get; private set; }

    [SyncVar] private uint currentOwnerNetId; // kumman pelaajan vuoro on

    void Awake()
    {
        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;
    }

    // Kutsutaan, kun pelaaja liittyy. Hostista tehdään aloitusvuoron omistaja.
    [Server]
    public void ServerRegisterPlayer(PlayerController pc)
    {
        // Host (connectionId == 0) asettaa aloitusvuoron, jos ei vielä asetettu
        if (currentOwnerNetId == 0 && pc.connectionToClient != null && pc.connectionToClient.connectionId == 0)
        {
            currentOwnerNetId = pc.netId;
            pc.ServerSetHasEnded(false); // host saa toimia
            foreach (var other in GetAllPlayers().Where(p => p != pc))
                other.ServerSetHasEnded(true); // muut lukkoon varmuudeksi

            RpcTurnChanged(GetTurnNumber(), currentOwnerNetId);
        }
        else
        {
            // Myöhemmin liittynyt (client) - lukitaan kunnes hänen vuoronsa alkaa
            pc.ServerSetHasEnded(true);
            RpcTurnChanged(GetTurnNumber(), currentOwnerNetId);
        }
    }

    // Kutsutaan, kun joku painaa End Turn
    [Server]
    public void ServerHandlePlayerEndedTurn(uint whoEndedNetId)
    {
        var players = GetAllPlayers().ToList();
        var ended = players.FirstOrDefault(p => p.netId == whoEndedNetId);
        var next = players.FirstOrDefault(p => p.netId != whoEndedNetId);
        if (next == null) return; // ei vastustajaa vielä

        // Nosta vuorolaskuria (kierrätetään olemassaolevaa turnNumberia)
        if (NetTurnManager.Instance) NetTurnManager.Instance.turnNumber++;
    }
}
```

RogueShooter – All Scripts

```
currentOwnerNetId = next.netId;

// Anna seuraavalle vuoro
next.ServerSetHasEnded(false); // avaa syötteen ja nappulan
// ended pysyy lukossa (hasEndedThisTurn = true)
RpcTurnChanged(GetTurnNumber(), currentOwnerNetId);

if (TurnSystem.Instance != null)
    TurnSystem.Instance.NextTurn();
}

int GetTurnNumber() => NetTurnManager.Instance ? NetTurnManager.Instance.turnNumber : 1;

[ClientRpc]
void RpcTurnChanged(int newTurnNumber, uint ownerNetId)
{
    // Päivitä paikallinen HUD "player/enemy turn" -logiikalla
    bool isMyTurn = false;
    if (NetworkClient.connection != null && NetworkClient.connection.identity != null)
        isMyTurn = NetworkClient.connection.identity.netId == ownerNetId;

    PvpPerception.ApplyEnemyFlagsLocally(isMyTurn);

    if (TurnSystem.Instance != null)
        TurnSystem.Instance.SetHudFromNetwork(newTurnNumber, isMyTurn);
}

[Server]
IEnumerable<PlayerController> GetAllPlayers()
{
    foreach (var kvp in NetworkServer.connections)
    {
        var id = kvp.Value.identity;
        if (!id) continue;
        var pc = id.GetComponent<PlayerController>();
        if (pc) yield return pc;
    }
}

[Server]
public void ServerGiveFirstTurnToHost()
{
    // heti kun ensimmäinen vuoro on annettu hostille:
    if (TurnSystem.Instance != null)
    {
        TurnSystem.Instance.ResetTurnId(); // siisti lähtö (0)
        TurnSystem.Instance.ResetAndBegin(false, true); // älä koske turnNumberiin; aloita Players-vaiheesta
    }

    var players = GetAllPlayers().ToList();
    var host = players.FirstOrDefault(p => p.connectionToClient != null && p.connectionToClient.connectionId == 0);
```

RogueShooter – All Scripts

```
    if (host == null) return;

    currentOwnerNetId = host.netId;

    // Host saa toimia, vastustaja lukkoon
    foreach (var p in players)
        p.ServerSetHasEnded(p != host);

    RpcTurnChanged(GetTurnNumber(), currentOwnerNetId);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Online/ResetService.cs

```
using Mirror;
using UnityEngine;

public class ResetService : NetworkBehaviour
{
    public static ResetService Instance;
    void Awake() => Instance = this;

    /// <summary>
    /// Kutsu tätä Play Again -napista. Hoitaa online/offline-haarat.
    /// </summary>
    public void RequestReset()
    {
        if (NetworkServer.active)                // HOST / DEDISERVER
        {
            var win = FindFirstObjectByType<WinBattle>(FindObjectsInactive.Include);
            if (win != null) win.HideEndPanel();

            // UUSI: tyhjennä unit-listat ennen reloadia
            var um = FindFirstObjectByType<UnitManager>(FindObjectsInactive.Include);
            if (um) um.ClearAllUnitLists();

            NetTurnManager.Instance.ResetTurnState();
            TurnSystem.Instance.ResetTurnId();
            TurnSystem.Instance.ResetTurnNumber();

            RpcPreResetHud(); // siistii kaikkien HUDit
            NetLevelLoader.Instance.ServerReloadCurrentLevel();
            return;
        }

        if (NetworkClient.active)                // PUHDAS CLIENT
        {
            // Serveri hoitaa reloadin ja aloituksen
            return;
        }

        // OFFLINE
        LevelLoader.Instance.ReloadOffline(LevelLoader.Instance.DefaultLevel);
    }

    /// <summary>
    /// Kevyt ja turvallinen UI-siistintä: piilota end-panelit.
    /// </summary>
    [ClientRpc]
    void RpcPreResetHud()
    {
        TurnSystem.Instance.ResetTurnId();
        var win = FindFirstObjectByType<WinBattle>(FindObjectsInactive.Include);
        if (win != null) win.HideEndPanel();
    }
}
```

RogueShooter – All Scripts

```
    // UUSI: myös asiakkaan UnitManager nollaan  
    var um = FindFirstObjectByType<UnitManager>(FindObjectsInactive.Include);  
    if (um) um.ClearAllUnitLists();  
  }  
}
```


RogueShooter – All Scripts

Assets/scripts/Online/Secure/ActorIdUtil.cs

```
using Mirror;
using UnityEngine;

/// <summary>
/// Yksinkertainen, yhteinen paikka hakea "actorin" netId.
/// Käyttö: this.GetActorId() MISTÄ tahansa MonoBehaviourista.
/// </summary>
public static class ActorIdUtil
{
    /// <summary>
    /// Hakee lähimmän yläjuuren NetworkIdentityn ja palauttaa sen netId:n.
    /// Käy kaikissa: Actionit, Animatorit, ym. joissa 'this' on Component.
    /// </summary>
    public static uint GetActorId(this Component self)
    {
        if (!self) return 0;
        var ni = self.GetComponentInParent<NetworkIdentity>();
        return ni ? ni.netId : 0;
    }

    /// <summary>
    /// Jos haluat hakea suoraan Unitista (jos se on saatavilla).
    /// </summary>
    public static uint GetActorId(this Unit unit)
    {
        if (!unit) return 0;
        var ni = unit.GetComponent<NetworkIdentity>();
        return ni ? ni.netId : 0;
    }

    /// <summary>
    /// Variaatiot, jos joskus tarvitset GameObjectista tai Transformista.
    /// </summary>
    public static uint GetActorId(this GameObject go) => go ? go.transform.GetActorId() : 0;
    public static uint GetActorId(this Transform t)
    {
        if (!t) return 0;
        var ni = t.GetComponentInParent<NetworkIdentity>();
        return ni ? ni.netId : 0;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/ServerBootstrap.cs

```
using System.Collections;
using Mirror;
using UnityEngine;
using Utp;

/// <summary>
/// This ensures that the server starts correctly and in the correct order.
/// </summary>

[DefaultExecutionOrder(10000)]          // aja myöhään
[DisallowMultipleComponent]
public class ServerBootstrap : NetworkBehaviour
{
    public override void OnStartServer()
    {
        // varmistaa että tämä ei ajaudu clientillä
        StartCoroutine(Bootstrap());
    }

    private IEnumerator Bootstrap()
    {
        // 1) Odota että Mirror on spawnannut scene-identiteetit
        //    (2 frameä riittää, mutta odotetaan lisäksi koordinaattorit)
        yield return null;
        yield return null;

        // Odota kunnes koordinaattori(t) ovat varmasti olemassa ja spawned
        yield return new WaitUntil(() =>
            CoopTurnCoordinator.Instance &&
            CoopTurnCoordinator.Instance.netIdentity &&
            CoopTurnCoordinator.Instance.netIdentity.netId != 0
        );

        // 2) Nollaa vuorologiikka vain serverillä
        NetTurnManager.Instance.ResetTurnState(); // EI UI-RPC:itä täällä

        // 3) Spawnaa viholliset vain Co-opissa ja vain jos tarvitaan
        if (GameModeManager.SelectedMode == GameMode.CoOp &&
            !SpawnUnitsCoordinator.Instance.AreEnemiesSpawned())
        {
            GameNetworkManager.Instance.SetEnemies();
        }

        // 4) Rakenna occupancy nykyisestä scenestä (unitit/esteet)
        LevelGrid.Instance.RebuildOccupancyFromScene();
        // 4b) Varmista että edge/cover-data on synkassa occupancy/geometryn kanssa
        EdgeBaker.Instance.BakeAllEdges();

        // 5) Pakota aloitus Players turniin ja turnNumber = 1
        NetTurnManager.Instance.turnNumber = 1;
    }
}
```

RogueShooter – All Scripts

```
NetTurnManager.Instance.phase = TurnPhase.Players;
TurnSystem.Instance.ForcePhase(isPlayerTurn: true, incrementTurnNumber: false);

// 6) Nyt on turvallista lähettää UI/RPC:t kaikille
var endedIds = System.Array.Empty<int>();
var endedLabels = CoopTurnCoordinator.Instance.BuildEndedLabels();

CoopTurnCoordinator.Instance.RpcUpdateReadyStatus(endedIds, endedLabels);
CoopTurnCoordinator.Instance.RpcTurnPhaseChanged(
    NetTurnManager.Instance.phase,
    NetTurnManager.Instance.turnNumber,
    true // isPlayersPhase
);

// (valinnainen) piilota enemy-WorldUI tms. alussa
UnitUIBroadcaster.Instance.BroadcastUnitWorldUIVisibility(false);

// (valinnainen) client-init, jos sinulla on tällainen
// ResetService.Instance.RpcPostResetClientInit(NetTurnManager.Instance.turnNumber);

NetTurnManager.Instance.SetPlayerStartState();
}
```

RogueShooter – All Scripts

Assets/scripts/Online/Sync/NetMode.cs

```
public static class NetMode
{
    public static bool IsOnline      => Mirror.NetworkServer.active || Mirror.NetworkClient.active;
    public static bool IsServer      => Mirror.NetworkServer.active;           // host tai dedicated
    public static bool IsClient      => Mirror.NetworkClient.active;           // host + remote client
    public static bool IsHost        => Mirror.NetworkServer.active && Mirror.NetworkClient.active;
    public static bool IsRemoteClient => Mirror.NetworkClient.active && !Mirror.NetworkServer.active;
    public static bool IsDedicated => Mirror.NetworkServer.active && !Mirror.NetworkClient.active;
    public static bool ServerOrOff => Mirror.NetworkServer.active || !Mirror.NetworkClient.isConnected; // Server or offline.
}
```

RogueShooter – All Scripts

Assets/scripts/Online/Sync/NetworkSync.cs

```
using Mirror;
using UnityEngine;
using UnityEngine.SceneManagement;

/// <summary>
/// NetworkSync is a static helper class that centralizes all network-related actions.
///
/// Responsibilities:
/// - Provides a single entry point for spawning and synchronizing networked effects and objects.
/// - Decides whether the game is running in server/host mode, client mode, or offline mode.
/// - In online play:
///   - If running on the server/host, spawns objects directly with NetworkServer.Spawn.
///   - If running on a client, forwards the request to the local NetworkSyncAgent, which relays it to the server via Command.
/// - In offline/singleplayer mode, simply instantiates objects locally with Instantiate.
///
/// Usage:
/// Call the static methods from gameplay code (e.g. UnitAnimator, Actions) instead of
/// directly instantiating or spawning prefabs. This ensures consistent behavior in all game modes.
///
/// Example:
/// NetworkSync.SpawnBullet(bulletPrefab, shootPoint.position, targetPosition);
/// </summary>
public static class NetworkSync
{
    /// <summary>
    /// Spawns a bullet projectile in the game world.
    /// Handles both offline (local Instantiate) and online (NetworkServer.Spawn) scenarios.
    ///
    /// In server/host:
    ///   - Instantiates and spawns the bullet directly with NetworkServer.Spawn.
    /// In client:
    ///   - Forwards the request to NetworkSyncAgent.Local, which executes a Command.
    /// In offline:
    ///   - Instantiates the bullet locally.
    /// </summary>
    /// <param name="bulletPrefab">The bullet prefab to spawn (must have NetworkIdentity if used online).</param>
    /// <param name="spawnPos">The starting position of the bullet (usually weapon muzzle).</param>
    /// <param name="targetPos">The target world position the bullet should travel towards.</param>
    public static void SpawnBullet(GameObject bulletPrefab, Vector3 spawnPos, Vector3 targetPos, uint actorNetId)
    {
        if (NetworkServer.active) // Online: server or host
        {
            Transform src = null;
            if (NetworkServer.spawned.TryGetValue(actorNetId, out var srcNI) && srcNI != null)
                src = srcNI.transform;

            SpawnRouter.SpawnNetworkServer(
                bulletPrefab, spawnPos, Quaternion.identity,
                source: src, // löydetty actorNetId:llä
                sceneName: null,
```

RogueShooter – All Scripts

```
        parent: null,
        owner: null,
        beforeSpawn: go =>
        {
            if (go.TryGetComponent<BulletProjectile>(out var gp))
            {
                gp.actorUnitNetId = actorNetId;
                gp.Setup(targetPos);
            }
        });

    return;

}

if (NetworkClient.active && NetworkSyncAgent.Local != null) // Online: client
{
    NetworkSyncAgent.Local.CmdSpawnBullet(actorNetId, targetPos);
}

}

// HUOM: käytä tätä myös AE:stä (UnitAnimatorista)
public static void SpawnGrenade(GameObject grenadePrefab, Vector3 spawnPos, Vector3 targetPos, uint actorNetId)
{
    if (NetworkServer.active) // Online: server tai host
    {
        Transform src = null;
        if (NetworkServer.spawned.TryGetValue(actorNetId, out var srcNI) && srcNI != null)
            src = srcNI.transform;

        SpawnRouter.SpawnNetworkServer(
            grenadePrefab, spawnPos, Quaternion.identity,
            source: src,           // löydetty actorNetId:llä
            sceneName: null,
            parent: null,
            owner: null,
            beforeSpawn: go =>
            {
                if (go.TryGetComponent<GrenadeProjectile>(out var gp)) {
                    gp.actorUnitNetId = actorNetId;
                    gp.Setup(targetPos);
                }
            });

        return;
    }

    if (NetworkClient.active && NetworkSyncAgent.Local != null) // Online: client
    {

```

RogueShooter – All Scripts

```
        NetworkSyncAgent.Local.CmdSpawnGrenade(actorNetId, targetPos);
    }
}

/// <summary>
/// Apply damage to a Unit in SP/Host/Client modes.
/// - Server/Host: call HealthSystem.Damage directly (authoritative).
/// - Client: send a Command via NetworkSyncAgent to run on server.
/// - Offline: call locally.
/// </summary>
public static void ApplyDamageToUnit(Unit target, int amount, Vector3 hitPosition, uint actorNetId)
{
    if (target == null) return;

    if (NetworkServer.active) // Online: server or host
    {
        var healthSystem = target.GetComponent<HealthSystem>();
        if (healthSystem == null) return;

        healthSystem.Damage(amount, hitPosition);
        UpdateHealthBarUI(healthSystem, target);
        return;
    }

    if (NetworkClient.active) // Online: client
    {
        var ni = target.GetComponent<NetworkIdentity>();
        if (ni && NetworkSyncAgent.Local != null)
        {
            NetworkSyncAgent.Local.CmdApplyDamage(actorNetId, ni.netId, amount, hitPosition);
            return;
        }
    }

    // Offline fallback
    Debug.Log("ApplyDamageToUnit.");
    target.GetComponent<HealthSystem>().Damage(amount, hitPosition);
}

public static void ApplyDamageToObject(DestructibleObject target, int amount, Vector3 hitPosition, uint actorNetId)
{
    if (target == null) return;

    if (NetworkServer.active) // Online: server or host
    {
        target.Damage(amount, hitPosition);
        return;
    }

    if (NetworkClient.active) // Online: client
    {

```

RogueShooter – All Scripts

```
        var ni = target.GetComponent<NetworkIdentity>();
        if (ni && NetworkSyncAgent.Local != null)
        {
            NetworkSyncAgent.Local.CmdApplyDamageToObject(actorNetId, ni.netId, amount, hitPosition);
            return;
        }
    }

    // Offline fallback
    target.Damage(amount, hitPosition);
}

private static void UpdateHealthBarUI(HealthSystem healthSystem, Unit target)
{
    if (target == null || healthSystem == null) return;
    // → ilmoita kaikille clientele, jotta UnitWorldUI saa eventin
    if (NetworkSyncAgent.Local == null)
    {
        // haetaan mikä tahansa agentti serveriltä (voi olla erillinen manageri)
        var agent = Object.FindFirstObjectByType<NetworkSyncAgent>();
        if (agent != null)
            agent.ServerBroadcastHp(target, healthSystem.GetHealth(), healthSystem.GetHealthMax());
        return;
    }

    if (NetworkClient.active && NetworkSyncAgent.Local != null)
    {
        var ni = target.GetComponent<NetworkIdentity>();
        if (ni != null)
            NetworkSyncAgent.Local.CmdRequestHpRefresh(ni.netId);
    }
}

public static void UpdateCoverUI(Unit target)
{
    if (target == null) return;

    // SERVER: broadcastaa suoraan
    if (NetworkServer.active)
    {
        var agent = UnityEngine.Object.FindFirstObjectByType<NetworkSyncAgent>();
        if (agent != null)
            agent.ServerBroadcastCover(target, target.GetPersonalCover(), target.GetPersonalCoverMax());
        return;
    }

    // CLIENT: pyydä serveriä tekemään virallinen päivitys
    if (NetworkClient.active && NetworkSyncAgent.Local != null)
    {
        var ni = target.GetComponent<NetworkIdentity>();
        if (ni != null)
            NetworkSyncAgent.Local.CmdRequestCoverRefresh(ni.netId);
    }
}
```


RogueShooter – All Scripts

```
    }

}

/// <summary>
/// Server: Control when Pleyers can see own and others Unit stats,
/// Like only active player AP(Action Points) are visible.
/// When is Enemy turn only Enemy Units Action points are visible.
/// Solo and Versus mode handle this locally because there is no need synchronisation.
/// </summary>
public static void BroadcastActionPoints(Unit unit, int apValue)
{
    if (unit == null) return;

    if (NetworkServer.active)
    {
        var agent = Object.FindFirstObjectByType<NetworkSyncAgent>();
        if (agent != null)
            agent.ServerBroadcastAp(unit, apValue);
        return;
    }

    // CLIENT-haara: lähetä peilauspyyntö serverille
    if (NetworkClient.active && NetworkSyncAgent.Local != null)
    {
        var ni = unit.GetComponent<NetworkIdentity>();
        if (ni) NetworkSyncAgent.Local.CmdMirrorAp(ni.netId, apValue);
    }
}

public static void SpawnRagdoll(GameObject prefab, Vector3 pos, Quaternion rot, uint sourceUnitNetId, Vector3 lastHitPosition, int overkill)
{
    if (NetworkServer.active)
    {
        // 1) Hae kaatuneen unitin Transform serveriltä netId:llä
        Transform src = null;
        if (NetworkServer.spawned.TryGetValue(sourceUnitNetId, out var srcNI) && srcNI != null)
            src = srcNI.transform;

        // 2) Spawnaa verkossa: siirto oikeaan level-sceneen hoituu SpawnRouterissa
        SpawnRouter.SpawnNetworkServer(
            prefab, pos, rot,
            source: src,          // → sama scene kuin kaatuneella unitilla
            sceneName: null,
            parent: null,
            owner: null,
            beforeSpawn: go =>
            {
                if (go.TryGetComponent<UnitRagdoll>(out var rg))
                {
                    rg.SetOverkill(overkill);
                }
            }
        );
    }
}
```

RogueShooter – All Scripts

```
        rg.SetLastHitPosition(lastHitPosition);
    }
    if (go.TryGetComponent<RagdollPoseBinder>(out var binder))
    {
        binder.sourceUnitNetId = sourceUnitNetId;
        binder.lastHitPos = lastHitPosition;
        binder.overkill = overkill;
    }
    else
    {
        Debug.LogWarning("[Ragdoll] Ragdoll prefab lacks RagdollPoseBinder.");
    }
    });
    return;
}
}

public static bool IsOwnerHost(uint ownerId)
{
    if (!NetworkServer.active) return false; // varmin tieto vain serverillä
    foreach (var kv in NetworkServer.connections)
    {
        var conn = kv.Value;
        if (conn?.identity && conn.identity.netId == ownerId)
            return conn.connectionId == 0; // 0 = host
    }
    return false;
}
}
```

RogueShooter – All Scripts

Assets/scripts/Online/Sync/NetworkSyncAgent.cs

```
using System.Collections;
using Mirror;
using UnityEngine;
/// <summary>
/// Attached to the PlayerController GameObject.
/// NetworkSyncAgent is a helper NetworkBehaviour to relay Commands from clients to the server.
/// Each client should have exactly one instance of this script in the scene.
///
/// Responsibilities:
/// - Receives local calls from NetworkSync (static helper).
/// - Sends Commands to the server when the local player performs an action (e.g. shooting).
/// - On the server, instantiates and spawns networked objects (like projectiles).
/// </summary>
public class NetworkSyncAgent : NetworkBehaviour
{
    public static NetworkSyncAgent Local; // Easy access for NetworkSync static helper
    public override void OnStartAuthority() { Local = this; }
    public override void OnStopAuthority() { if (Local == this) Local = null; }

    [SerializeField] private GameObject bulletPrefab; // Prefab for the bullet projectile
    [SerializeField] private GameObject grenadePrefab;

    public override void OnStartLocalPlayer()
    {
        base.OnStartLocalPlayer();
        Local = this;
    }

    /// <summary>
    /// Command from client → server.
    /// The client requests the server to spawn a bullet at the given position.
    /// The server instantiates the prefab, sets it up, and spawns it to all connected clients.
    /// </summary>
    /// <param name="spawnPos">World position where the bullet starts (usually weapon muzzle).</param>
    /// <param name="clientSuggestedTarget">World position the bullet is travelling towards.</param>

    [Command(requiresAuthority = true)]
    public void CmdSpawnBullet(uint actorNetId, Vector3 clientSuggestedTarget)
    {
        if (!NetworkServer.active) return;
        if (bulletPrefab == null) { Debug.LogWarning("[NetSyncAgent] bulletPrefab missing"); return; }
        if (actorNetId == 0 || !RightOwner(actorNetId)) return;

        if (!NetworkServer.spawned.TryGetValue(actorNetId, out var actorNi) || actorNi == null) return;

        var ua = actorNi.GetComponent<UnitAnimator>();
        Vector3 origin = (ua && ua.ShootPoint) ? ua.ShootPoint.position : actorNi.transform.position;
        Vector3 target = clientSuggestedTarget;

        // tärkeää: käytä SpawnRouteria ja anna source = actor
    }
}
```

RogueShooter – All Scripts

```
SpawnRouter.SpawnNetworkServer(
    bulletPrefab, origin, Quaternion.identity,
    source: actorNi.transform,
    sceneName: null,
    parent: null,
    owner: connectionToClient,          // omistajuus halutessa
    beforeSpawn: go =>
    {
        if (go.TryGetComponent<BulletProjectile>(out var bp))
        {
            bp.actorUnitNetId = actorNetId;
            bp.Setup(target);
        }
    });
});

[Command(requiresAuthority = true)]
public void CmdSpawnGrenade(uint actorNetId, Vector3 clientSuggestedTarget)
{
    if (!NetworkServer.active) return;
    if (grenadePrefab == null) { Debug.LogWarning("[NetSyncAgent] GrenadePrefab missing"); return; }
    if (actorNetId == 0 || !RightOwner(actorNetId)) return;

    if (!NetworkServer.spawned.TryGetValue(actorNetId, out var actorNi) || actorNi == null) return;

    var ua = actorNi.GetComponent<UnitAnimator>();
    if (!ua || !ua.ThrowPoint) return;

    Vector3 origin = ua.ThrowPoint.position;
    Vector3 target = clientSuggestedTarget;

    SpawnRouter.SpawnNetworkServer(
        grenadePrefab, origin, Quaternion.identity,
        source: actorNi.transform,
        sceneName: null,
        parent: null,
        owner: connectionToClient,
        beforeSpawn: go =>
        {
            if (go.TryGetComponent<GrenadeProjectile>(out var gp))
            {
                gp.actorUnitNetId = actorNetId;
                gp.Setup(target);
            }
        });
});

private bool RightOwner(uint actorNetId)
{
    // Varmista että soittaja omistaa kyseisen actor-yksikön
    if (!NetworkServer.spawned.TryGetValue(actorNetId, out var actorIdentity) || actorIdentity == null) return false;
}
```

RogueShooter – All Scripts

```
// actorin todellinen omistaja.
var actorUnit = actorIdentity.GetComponent<Unit>();

// Client joka lähetti comennon.
var callerOwnerId = connectionToClient.identity?.netId ?? 0;

// Unitissa on OwnerId, jonka asetus tehdään spawnnaessa (SpawnUnitsCoordinator) → käytä sitä checkissä
// OwnerId = PlayerController-objektin netId
if (actorUnit == null || actorUnit.OwnerId != callerOwnerId) return false;

return true;
}

/// <summary>
/// Client → Server: resolve target by netId and apply damage on server.
/// then broadcast the new HP to all clients for UI.
/// </summary>
[Command(requiresAuthority = true)]
public void CmdApplyDamage(uint actorNetId, uint targetNetId, int amount, Vector3 hitPosition)
{
    if (!NetworkServer.spawned.TryGetValue(targetNetId, out var targetNi) || targetNi == null) return;
    if (!RightOwner(actorNetId)) return;

    var unit = targetNi.GetComponent<Unit>();
    var hs = targetNi.GetComponent<HealthSystem>();
    if (unit == null || hs == null)
        return;

    // --- NEW: server-side sanity cap ---
    int maxAllowed = 0;
    if (NetworkServer.spawned.TryGetValue(actorNetId, out var attackerNi) && attackerNi != null)
    {
        var attacker = attackerNi.GetComponent<Unit>();
        var w = attacker != null ? attacker.GetCurrentWeapon() : null;

        // Aseesta johdettu maksimi: Miss/Graze/Hit/Crit → enintään base + critBonus
        if (w != null)
            maxAllowed = Mathf.Max(maxAllowed, w.baseDamage + w.critBonusDamage); // esim. 10 + 8, jne.

        // Lähitaistelulle varmuuskatto (sinulla MeleeAction.damage = 100 → ota vähintään tämä)
        // Vältetään riippuvuus MeleeActionin yksityiseen kenttään ottamalla varovainen fallback:
        maxAllowed = Mathf.Max(maxAllowed, 100); // MeleeActionissa serialize'd damage=100. :contentReference[oaicite:2]{index=2}
    }

    int safe = Mathf.Clamp(amount, 0, maxAllowed);
    if (safe != amount)
        Debug.LogWarning($"[Server] Clamped damage from {amount} to {safe} (actor {actorNetId} → target {targetNetId}).");

    // 1) Server tekee damagen
    hs.Damage(amount, hitPosition);

    // 2) Broadcast UI (kuten ennenkin)
```

RogueShooter – All Scripts

```
    ServerBroadcastHp(unit, hs.GetHealth(), hs.GetHealthMax());
}

[Command(requiresAuthority = true)]
public void CmdApplyDamageToObject(uint actorNetId, uint targetNetId, int amount, Vector3 hitPosition)
{
    if (!NetworkServer.spawned.TryGetValue(targetNetId, out var targetNi) || targetNi == null) return;
    if (!RightOwner(actorNetId)) return;

    var obj = targetNi.GetComponent<DestructibleObject>();
    if (obj == null) return;

    obj.Damage(amount, hitPosition);
}

[Command(requiresAuthority = false)]
public void CmdRequestHpRefresh(uint unitNetId)
{
    if (!NetworkServer.active) return;
    if (!NetworkServer.spawned.TryGetValue(unitNetId, out var id)) return;

    var u = id.GetComponent<Unit>();
    var hs = u ? u.GetComponent<HealthSystem>() : null;
    if (u == null || hs == null) return;

    ServerBroadcastHp(u, hs.GetHealth(), hs.GetHealthMax()); // server lukee
}

// ---- SERVER-puolen helperit: kutsu näitä palvelimelta
[Server]
public void ServerBroadcastHp(Unit unit, int current, int max)
{
    var ni = unit.GetComponent<NetworkIdentity>();
    if (ni) RpcNotifyHpChanged(ni.netId, current, max);
}

[Server]
public void ServerBroadcastAp(Unit unit, int ap)
{
    var ni = unit.GetComponent<NetworkIdentity>();
    if (ni) RpcNotifyApChanged(ni.netId, ap);
}

[Server]
public void ServerBroadcastCover(Unit unit, int current, int max)
{
    var ni = unit.GetComponent<NetworkIdentity>();
    if (ni) RpcNotifyCoverChanged(ni.netId, current, max);
}

// ---- SERVER → ALL CLIENTS: Cover-muutos ilmoitus
[ClientRpc]
```

RogueShooter – All Scripts

```
void RpcNotifyCoverChanged(uint unitNetId, int current, int max)
{
    if (!NetworkClient.spawned.TryGetValue(unitNetId, out var id) || id == null) return;

    var unit = id.GetComponent<Unit>();
    if (unit == null) return;

    unit.ApplyNetworkCover(current, max);
}

[Command(requiresAuthority = false)]
public void CmdRequestCoverRefresh(uint unitNetId)
{
    if (!NetworkServer.spawned.TryGetValue(unitNetId, out var id) || id == null) return;
    var unit = id.GetComponent<Unit>();
    if (unit == null) return;

    // Server lukee arvot ja broadcastaa
    ServerBroadcastCover(unit, unit.GetPersonalCover(), unit.GetPersonalCoverMax());
}

[Command(requiresAuthority = false)]
public void CmdSetUnitCover(uint unitNetId, int value)
{
    if (!NetworkServer.spawned.TryGetValue(unitNetId, out var id) || id == null) return;
    var unit = id.GetComponent<Unit>();
    if (!unit) return;

    unit.SetPersonalCover(Mathf.Clamp(value, 0, unit.GetPersonalCoverMax()));
}

[Command(requiresAuthority = false)]
public void CmdSetUnderFire(uint unitNetId, bool value)
{
    if (!NetworkServer.spawned.TryGetValue(unitNetId, out var id) || id == null) return;
    var unit = id.GetComponent<Unit>();
    if (!unit) return;

    unit.SetUnderFireServer(value);
}

[Server]
public void ServerBroadcastUnderFire(Unit unit, bool value)
{
    var ni = unit.GetComponent<NetworkIdentity>();
    if (ni) RpcNotifyUnderFireChanged(ni.netId, value);
}

[ClientRpc]
void RpcNotifyUnderFireChanged(uint unitNetId, bool value)
{
    if (!NetworkClient.spawned.TryGetValue(unitNetId, out var id) || id == null) return;
```

RogueShooter – All Scripts

```
        var unit = id.GetComponent<Unit>();
        if (!unit) return;

        unit.ApplyNetworkUnderFire(value);
    }

    // ---- SERVER → ALL CLIENTS: HP-muutos ilmoitus
    [ClientRpc]
    void RpcNotifyHpChanged(uint unitNetId, int current, int max)
    {
        if (!NetworkClient.spawned.TryGetValue(unitNetId, out var id) || id == null) return;

        var hs = id.GetComponent<HealthSystem>();
        if (hs == null) return;

        hs.ApplyNetworkHealth(current, max);
    }

    // ---- SERVER → ALL CLIENTS: AP-muutos ilmoitus
    [ClientRpc]
    void RpcNotifyApChanged(uint unitNetId, int ap)
    {
        ApplyApClient(unitNetId, ap);
    }

    [Command]
    public void CmdMirrorAp(uint unitNetId, int ap)
    {
        RpcNotifyApChanged(unitNetId, ap);
    }

    void ApplyApClient(uint unitNetId, int ap)
    {
        if (!NetworkClient.spawned.TryGetValue(unitNetId, out var id) || id == null) return;
        var unit = id.GetComponent<Unit>();
        if (!unit) return;

        unit.ApplyNetworkActionPoints(ap); // päivittää arvon + triggaa eventin
    }

    [Command]
    public void CmdRegenCoverOnMove(uint unitNetId, int distance)
    {
        if (!NetworkServer.spawned.TryGetValue(unitNetId, out NetworkIdentity ni)) return;
        var cs = ni.GetComponent<CoverSkill>();
        if (cs != null) cs.ServerRegenCoverOnMove(distance);
    }

    [Command]
    public void CmdResetCurrentCoverBonus(uint unitNetId)
    {
        if (!NetworkServer.spawned.TryGetValue(unitNetId, out NetworkIdentity ni)) return;
        var cs = ni.GetComponent<CoverSkill>();
```


RogueShooter – All Scripts

```
        if (cs != null) cs.ServerResetCurrentCoverBonus();
    }

    [Command(requiresAuthority = false)]
    public void CmdApplyCoverBonus(uint unitNetId)
    {
        if (!NetworkServer.spawned.TryGetValue(unitNetId, out NetworkIdentity ni)) return;
        var cs = ni.GetComponent<CoverSkill>(); // tai GetComponentInChildren<CoverSkill>()
        if (cs != null) cs.ServerApplyCoverBonus();
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Online/UI/RelayJoinCodeUI.cs

```
using UnityEngine;
using TMPro;

[DefaultExecutionOrder(-100)]
public class RelayJoinCodeUI : MonoBehaviour
{
    public static RelayJoinCodeUI Instance { get; private set; }

    [SerializeField] private GameObject root;      // vedä tähän CodeCanvas TAI paneelin juuri
    [SerializeField] private TMP_Text codeText;    // vedä JoinCodeText

    void Awake()
    {
        if (Instance != null && Instance != this) { Destroy(gameObject); return; }
        Instance = this;

        if (root == null) root = gameObject;        // fallback: käytä CodeCanvasia juurena
        DontDestroyOnLoad(root);                    // pysy scene-vaihdon yli
        if (root.activeSelf) root.SetActive(false);
        //Hide();
    }

    // Turvahaku siltä varalta, että Instance ei ole vielä asetettu
    public static RelayJoinCodeUI GetOrFind()
    {
        if (Instance != null) return Instance;
        var found = FindFirstObjectByType<RelayJoinCodeUI>(FindObjectsInactive.Include);
        if (found != null)
        {
            Instance = found;
            if (found.root == null) found.root = found.gameObject;
        }
        return Instance;
    }

    public void ShowCode(string code)
    {
        var c = (code ?? "").Trim().ToUpperInvariant();
        if (codeText) codeText.text = $"JOIN CODE: {c}";
        root.SetActive(true);
    }

    public void Hide() => root.SetActive(false);
}
```

RogueShooter – All Scripts

Assets/scripts/Online/WeaponVisibilitySync.cs

```
using Mirror;
using UnityEngine;

public class WeaponVisibilitySync : NetworkBehaviour
{
    [Header("Unit Weapons Refs")]
    [SerializeField] private Transform rifleRightHandTransform;
    [SerializeField] private Transform rifleLeftHandTransform;
    [SerializeField] private Transform meleeLeftHandTransform;
    [SerializeField] private Transform grenadeRightHandTransform;

    private NetVisibility rifleRightVis, rifleLeftVis ,meleeLeftVis, grenadeRightVis;

    void Awake()
    {
        if (rifleRightHandTransform) rifleRightVis = rifleRightHandTransform.GetComponent<NetVisibility>();
        if (rifleLeftHandTransform) rifleLeftVis= rifleLeftHandTransform.GetComponent<NetVisibility>();
        if (meleeLeftHandTransform) meleeLeftVis = meleeLeftHandTransform.GetComponent<NetVisibility>();
        if (grenadeRightHandTransform) grenadeRightVis = grenadeRightHandTransform.GetComponent<NetVisibility>();
    }

    // --- OWNER kutsuu tätä (esim. AE:ssä) ---
    public void OwnerRequestSet(bool rifleRight,bool rifleLeft, bool meleeLeft, bool grenade)
    {
        // Offline: suoraan paikalliset
        if (!NetworkClient.active && !NetworkServer.active)
        {
            SetLocal(rifleRight, rifleLeft, meleeLeft, grenade);
            return;
        }

        // Online: vain omistaja saa pyytää
        var ni = GetComponent<NetworkIdentity>();
        if (isClient && ni && ni.isOwned)
        {
            CmdSet(rifleRight, rifleLeft,meleeLeft, grenade);
        }
    }

    [Command(requiresAuthority = true)]
    private void CmdSet(bool rifleRight, bool rifleLeft ,bool meleeLeft, bool grenade)
    {
        // Serverissä voi halutessa käyttää server-authoritatiivista NetVisibilityä:
        // jos käytössä, aseta serverillä -> SyncVar/RPC hoitaa muille
        if (rifleRightVis) rifleRightVis.ServerSetVisible(rifleRight);
        if (rifleLeftVis) rifleLeftVis.ServerSetVisible(rifleLeft);
        if (meleeLeftVis) meleeLeftVis.ServerSetVisible(meleeLeft);
        if (grenadeRightVis) grenadeRightVis.ServerSetVisible(grenade);
    }
}
```

RogueShooter – All Scripts

```
// Lisäksi varma ClientRpc (jos NetVisibility ei kata kaikkea):
RpcSet(rifleRight, rifleLeft ,meleeLeft, grenade);
}

[ClientRpc]
private void RpcSet(bool rifleRight, bool rifleLeft ,bool meleeLeft, bool grenade)
{
    SetLocal(rifleRight, rifleLeft ,meleeLeft, grenade);
}

private void SetLocal(bool rifleRight,bool rifleLeft, bool meleeLeft, bool grenade)
{
    // Jos sinulla on NetVisibility, käytä sen "pehmeää" piilotusta,
    // muuten pelkkä SetActive/renderer.enabled
    if (rifleRightHandTransform) rifleRightHandTransform.gameObject.SetActive(rifleRight);
    if (rifleLeftHandTransform) rifleLeftHandTransform.gameObject.SetActive(rifleLeft);
    if (meleeLeftHandTransform) meleeLeftHandTransform.gameObject.SetActive(meleeLeft);
    if (grenadeRightHandTransform) grenadeRightHandTransform.gameObject.SetActive(grenade);

    // Esim. renderer-tason piilotus:
    // ToggleRenderers(rifleTransform, rifle);
    // ToggleRenderers(meleeTransform, melee);
    // ToggleRenderers(grenadeTransform, grenade);
}

private static void ToggleRenderers(Transform t, bool visible)
{
    if (!t) return;
    foreach (var r in t.GetComponentsInChildren<Renderer>(true))
        r.enabled = visible;
}

[Server]
public void ServerForceSet(bool rifleRight, bool rifleLeft, bool meleeLeft, bool grenade)
{
    // Aseta server-authoritatiivinen tila (jos käytät NetVisibilityä)
    if (rifleRightVis) rifleRightVis.ServerSetVisible(rifleRight);
    if (rifleLeftVis) rifleLeftVis.ServerSetVisible(rifleLeft);
    if (meleeLeftVis) meleeLeftVis.ServerSetVisible(meleeLeft);
    if (grenadeRightVis) grenadeRightVis.ServerSetVisible(grenade);

    // Ja lähetä varmuuden vuoksi kaikille klienteille
    RpcSet(rifleRight, rifleLeft, meleeLeft, grenade);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Systems/SpawnRouter.cs

```
// Assets/Scripts/Runtime/Systems/SpawnRouter.cs
using System;
using UnityEngine;
using UnityEngine.SceneManagement;
using Mirror;

public static class SpawnRouter
{
    /// <summary>Muokkaa tätä jos Core on eri nimellä.</summary>
    public static string CoreSceneName = "Core";

    /// <summary>
    /// Paikallinen spawn (ei NetworkServer.Spawn). Palauttaa instanssin.
    /// </summary>
    public static GameObject SpawnLocal(
        GameObject prefab,
        Vector3 pos,
        Quaternion rot,
        Transform source = null,
        string sceneName = null,
        Transform parent = null,
        Action<GameObject> beforeReturn = null)
    {
        var go = UnityEngine.Object.Instantiate(prefab, pos, rot);
        if (parent != null) go.transform.SetParent(parent, true);

        var targetScene = ResolveScene(source, sceneName);
        if (targetScene.IsValid()) SceneManager.MoveGameObjectToScene(go, targetScene);

        beforeReturn?.Invoke(go);
        return go;
    }

    /// <summary>
    /// Server-spawn (Mirror). Luo instanssin, siirtää sen level-scenelle ja kutsuu NetworkServer.Spawn.
    /// </summary>
    public static GameObject SpawnNetworkServer(
        GameObject prefab,
        Vector3 pos,
        Quaternion rot,
        Transform source = null,
        string sceneName = null,
        Transform parent = null,
        NetworkConnectionToClient owner = null,
        Action<GameObject> beforeSpawn = null)
    {
        if (!NetworkServer.active)
        {
            Debug.LogWarning("[SpawnRouter] SpawnNetworkServer() called without an active server.");
            return null;
        }
    }
}
```

RogueShooter – All Scripts

```
}

var go = UnityEngine.Object.Instantiate(prefab, pos, rot);
if (parent != null) go.transform.SetParent(parent, true);

// 1) Siirrä instanssi oikeaan level-scenelle (host/servu puolella)
var targetScene = ResolveScene(source, sceneName);
if (targetScene.IsValid()) SceneManager.MoveGameObjectToScene(go, targetScene);

// 2) Tee mahdolliset initit ennen spawnia
beforeSpawn?.Invoke(go);

// 3) (UUSI) Kerro myös clientele mihin sceneen tämä kuuluu
var binder = go.GetComponent<NetworkSceneBinder>();
if (binder != null && targetScene.IsValid())
    binder.targetSceneName = targetScene.name;
#if UNITY_EDITOR
else
    Debug.LogWarning($"[SpawnRouter] Prefab '{prefab.name}' lacks NetworkSceneBinder. Client will keep it in Core.");
#endif

// 4) Verkkoon
if (!go.TryGetComponent<NetworkIdentity>(out _))
    Debug.LogWarning("[SpawnRouter] Network spawn prefab has no NetworkIdentity.");

if (owner != null) NetworkServer.Spawn(go, owner);
else NetworkServer.Spawn(go);

return go;
}

/// <summary>
/// Yhtenäinen scene-resoluutio:
/// 1) nimellä, 2) lähdeobjektin scene, 3) ensimmäinen ladattu ei-Core, 4) muuten default (invalid).
/// </summary>
private static Scene ResolveScene(Transform source, string sceneName)
{
    // 1) Nimen perusteella
    if (!string.IsNullOrEmpty(sceneName))
    {
        var byName = SceneManager.GetSceneByName(sceneName);
        if (byName.IsValid() && byName.isLoaded) return byName;
    }

    // 2) Lähdeobjektin scene (esim. kuollut unit, ase tms.)
    if (source != null)
    {
        var fromSource = source.gameObject.scene;
        if (fromSource.IsValid() && fromSource.isLoaded) return fromSource;
    }

    // 3) Ensimmäinen ladattu ei-Core-scene (nykyinen level)
```

RogueShooter – All Scripts

```
    for (int i = 0; i < SceneManager.sceneCount; i++)
    {
        var s = SceneManager.GetSceneAt(i);
        if (s.isLoaded && !string.Equals(s.name, CoreSceneName, StringComparison.OrdinalIgnoreCase))
            return s;
    }

    // 4) Ei löytynyt - palautetaan invalid (kutsuja voi itse päättää mitä tekee)
    return default;
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/EmptySquad.cs

```
using UnityEngine;

/// <summary>
/// GameNetorkManager is required to have a NetworkManager component.
/// This is an empty class just to satisfy that requirement.
/// </summary>
public class EmptySquad : MonoBehaviour
{
}
```


RogueShooter – All Scripts

Assets/scripts/Units/HealthSystem.cs

```
using System;
using UnityEngine;

public class HealthSystem : MonoBehaviour
{
    public event EventHandler OnDead;
    public event EventHandler OnDamaged;

    [SerializeField] private int health = 100;
    private int healthMax;

    // To prevent multiple death events
    private bool isDead;
    private Vector3 lastHitPosition;
    public Vector3 LastHitPosition => lastHitPosition;

    private int overkill;
    public int Overkill => overkill;

    void Awake()
    {
        healthMax = health;
        isDead = false;
    }

    public void Damage(int damageAmount, Vector3 hitPosition)
    {
        if (isDead) return;

        health -= damageAmount;
        if (health <= 0)
        {
            overkill = Math.Abs(health) + 1;
            health = 0;

            if (!isDead)
            {
                lastHitPosition = hitPosition;
                isDead = true;
                Die();
            }
        }

        OnDamaged?.Invoke(this, EventArgs.Empty);
    }

    private void Die()
    {
        OnDead?.Invoke(this, EventArgs.Empty);
    }
}
```

RogueShooter – All Scripts

```
public float GetHealthNormalized()
{
    return (float)health / healthMax;
}

public int GetHealth()
{
    return health;
}

public int GetHealthMax()
{
    return healthMax;
}

public void ApplyNetworkHealth(int current, int max)
{
    healthMax = Mathf.Max(1, max);
    health = Mathf.Clamp(current, 0, healthMax);
    OnDamaged?.Invoke(this, EventArgs.Empty);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/Unit.cs

```
using Mirror;
using System;
using System.Collections;
using UnityEngine;

/// <summary>
///     This class represents a unit in the game.
///     Actions can be called on the unit to perform various actions like moving or shooting.
///     The class inherits from NetworkBehaviour to support multiplayer functionality.
/// </summary>
public enum Team { Player, Enemy }
[RequireComponent(typeof(HealthSystem))]
[RequireComponent(typeof(MoveAction))]
[RequireComponent(typeof(TurnTowardsAction))]
[RequireComponent(typeof(CoverSkill))]
public class Unit : NetworkBehaviour
{
    public Team Team;

    [SerializeField] public CoverSkill Cover { get; private set; }

    // This is off long as this is under development...
    // private const int ACTION_POINTS_MAX = 2;
    // private int actionPoints = ACTION_POINTS_MAX;

    [SerializeField, Min(0)] private int ACTION_POINTS_MAX = 2;
    private int actionPoints;

    [SyncVar] public uint OwnerId;

    [SyncVar] private bool underFire = false;
    public bool IsUnderFire => underFire;

    public event Action<int, int> OnCoverPoolChanged;

    [SerializeField] public UnitArchetype archetype;
    [SerializeField] private WeaponDefinition currentWeapon;

    //Events
    public static event EventHandler OnAnyActionPointsChanged;
    public static event EventHandler OnAnyUnitSpawned;
    public static event EventHandler OnAnyUnitDead;

    public event Action<bool> OnHiddenChangedEvent;

    [SerializeField] public bool isEnemy;

    private GridPosition gridPosition;
    private HealthSystem healthSystem;
```

RogueShooter – All Scripts

```
private BaseAction[] baseActionsArray;

private int maxMoveDistance;

[SyncVar(hook = nameof(OnHiddenChanged))]
private bool isHidden;

private Renderer[] renderers;
private Collider[] colliders;
private Animator anim;

private int grenadePCS;

private void Awake()
{
    renderers = GetComponentsInChildren<Renderer>(true);
    colliders = GetComponentsInChildren<Collider>(true);
    TryGetComponent(out anim);

    healthSystem = GetComponent<HealthSystem>();
    baseActionsArray = GetComponents<BaseAction>();
    maxMoveDistance = GetComponent<MoveAction>().GetMaxMoveDistance();
    Cover = GetComponent<CoverSkill>();
}

private void Start()
{
    if (LevelGrid.Instance != null)
    {
        gridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
        LevelGrid.Instance.AddUnitAtGridPosition(gridPosition, this);
    }

    actionPoints = ACTION_POINTS_MAX;

    TurnSystem.Instance.OnTurnStarted += OnTurnStarted_HandleTurnStarted;
    TurnSystem.Instance.OnTurnEnded += OnTurnEnded_HandleTurnEnded;
    healthSystem.OnDead += HealthSystem_OnDead;

    OnAnyUnitSpawned?.Invoke(this, EventArgs.Empty);
    underFire = false;

    //***** Items *****
    grenadePCS = archetype.grenadeCapacity;
}

private void OnEnable()
{
    if (Cover != null) Cover.OnCoverPoolChanged += ForwardCoverChanged;
```

RogueShooter – All Scripts

```
}

private void OnDisable()
{
    TurnSystem.Instance.OnTurnStarted -= OnTurnStarted_HandleTurnStarted;
    TurnSystem.Instance.OnTurnEnded -= OnTurnEnded_HandleTurnEnded;

    if (Cover != null) Cover.OnCoverPoolChanged -= ForwardCoverChanged;
}

private void ForwardCoverChanged(int cur, int max) => OnCoverPoolChanged?.Invoke(cur, max);

private void Update()
{
    GridPosition newGridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
    if (newGridPosition != gridPosition)
    {
        GridPosition oldGridposition = gridPosition;
        gridPosition = newGridPosition;
        LevelGrid.Instance.UnitMoveToGridPosition(oldGridposition, newGridPosition, this);
    }
}

/// <summary>
///     When unit get destroyed, this clears grid system under destroyed unit.
/// </summary>
void OnDestroy()
{
    if (LevelGrid.Instance != null)
    {
        gridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
        LevelGrid.Instance.RemoveUnitAtGridPosition(gridPosition, this);
    }
}

public T GetAction<T>() where T : BaseAction
{
    foreach (BaseAction baseAction in baseActionsArray)
    {
        if (baseAction is T t)
        {
            return t;
        }
    }
    return null;
}

public GridPosition GetGridPosition()
{
    return gridPosition;
}
```

RogueShooter – All Scripts

```
public Vector3 GetWorldPosition()
{
    return transform.position;
}

public BaseAction[] GetBaseActionsArray()
{
    return baseActionsArray;
}

public bool TrySpendActionPointsToTakeAction(BaseAction baseAction)
{
    if (CanSpendActionPointsToTakeAction(baseAction))
    {
        SpendActionPoints(baseAction.GetActionPointsCost());
        return true;
    }
    return false;
}

public bool CanSpendActionPointsToTakeAction(BaseAction baseAction)
{
    if (actionPoints >= baseAction.GetActionPointsCost())
    {
        return true;
    }
    return false;
}

private void SpendActionPoints(int amount)
{
    actionPoints -= amount;

    OnAnyActionPointsChanged?.Invoke(this, EventArgs.Empty);
    NetworkSync.BroadcastActionPoints(this, actionPoints);
}

public int GetActionPoints()
{
    return actionPoints;
}

/// <summary>
///     Online: Updating ActionPoints usage to otherplayers.
/// </summary>
public void ApplyNetworkActionPoints(int ap)
{
    if (actionPoints == ap) return;
    actionPoints = ap;
    OnAnyActionPointsChanged?.Invoke(this, EventArgs.Empty);
}
```

RogueShooter – All Scripts

```
public bool IsEnemy()
{
    return isEnemy;
}

private void HealthSystem_OnDead(object sender, System.EventArgs e)
{
    OnAnyUnitDead?.Invoke(this, EventArgs.Empty);
    if (!NetworkServer.active)
    {
        // OFFLINE: suoraan tuho
        if (!NetworkClient.active) { Destroy(gameObject); return; }
        return;
    }

    // Piilota jotta client ehtii kopioida omaan ragdolliin tiedot
    isHidden = true;
    SetSoftHiddenLocal(true);
    StartCoroutine(DestroyAfter(0.30f));
}

private IEnumerator DestroyAfter(float seconds)
{
    yield return new WaitForSeconds(seconds);
    NetworkServer.Destroy(gameObject);
}

private void SetSoftHiddenLocal(bool hidden)
{
    bool visible = !hidden;
    foreach (var r in renderers) if (r) r.enabled = visible;
    foreach (var c in colliders) if (c) c.enabled = visible;
    if (anim) anim.enabled = visible;
}

public float GetHealthNormalized()
{
    return healthSystem.GetHealthNormalized();
}

private void OnHiddenChanged(bool oldVal, bool newVal)
{
    OnHiddenChangedEvent?.Invoke(newVal);
}

public bool IsHidden()
{
    return isHidden;
}

public int GetMaxMoveDistance()
{

```

RogueShooter – All Scripts

```
        return maxMoveDistance;
    }

    public void SetUnderFire(bool value)
    {
        if (!NetworkServer.active && !NetworkClient.active)
        {
            Debug.Log("Set underfire:" + value);
            underFire = value;
            return;
        }

        if (NetworkServer.active)
        {
            SetUnderFireServer(value);
            return;
        }

        var ni = GetComponent<NetworkIdentity>();
        if (NetworkClient.active && NetworkSyncAgent.Local != null && ni != null)
        {
            NetworkSyncAgent.Local.CmdSetUnderFire(ni.netId, value);
        }
    }

    [Server]
    public void SetUnderFireServer(bool value)
    {
        underFire = value;
        var agent = FindFirstObjectByType<NetworkSyncAgent>();
        if (agent != null)
            agent.ServerBroadcastUnderFire(this, value);
    }

    public void ApplyNetworkUnderFire(bool value)
    {
        underFire = value;
    }

    // ***** Cover Skill *****
    public int GetPersonalCover() => Cover ? Cover.GetPersonalCover() : 0;
    public int GetPersonalCoverMax() => Cover ? Cover.GetPersonalCoverMax() : 1;
    public float GetCoverNormalized() => Cover ? Cover.GetCoverNormalized() : 0f;
    public int GetCoverRegenPerUnusedAP() => Cover ? Cover.GetCoverRegenPerUnusedAP() : 0;

    public bool HasMoved() => Cover ? Cover.HasMoved() : false;

    public void SetPersonalCover(int v) { if (Cover) Cover.SetPersonalCover(v); }
    //public void SetCoverBonus() { if (Cover) Cover.SetCoverBonus(); }
    public void SetCoverBonus() { if (Cover) Cover.ServerApplyCoverBonus(); }

    public int GetCurrentCoverBonus() => Cover ? Cover.GetCurrentCoverBonus() : 0;
```


RogueShooter – All Scripts

```
public void ResetCurrentCoverBonus() { if (Cover) Cover.ResetCurrentCoverBonus(); }

public void RegenCoverBy(int amount) { if (Cover) Cover.RegenCoverBy(amount); }
public void RegenCoverOnMove(int distance) { if (Cover) Cover.RegenCoverOnMove(distance); }

public void ApplyNetworkCover(int cur, int max) { if (Cover) Cover.ApplyNetworkCover(cur, max); }

// public void AddPersonalCover(int delta) { if (Cover) Cover.AddPersonalCover(delta); }

//*****

// ***** weapons *****
public void UseGrenade()
{
    if (grenadePCS <= 0)
    {
        grenadePCS = 0;
        return;
    }
    grenadePCS -= 1;
}

public int GetGrenadePCS() => grenadePCS;

public WeaponDefinition GetCurrentWeapon()
{
    return currentWeapon;
}

private int _lastApStartTurnId = -1;
private void OnTurnStarted_HandleTurnStarted(Team startTurnTeam, int turnId)
{
    if (NetworkClient.active && !NetworkServer.active) return;
    if (Team != startTurnTeam) return;          // vain oman puolen alussa
    if (_lastApStartTurnId == turnId) return;    // duplikaattisuoja
    _lastApStartTurnId = turnId;

    actionPoints = ACTION_POINTS_MAX;
    OnAnyActionPointsChanged?.Invoke(this, EventArgs.Empty);

    // LISÄÄ TÄMÄ: Broadcastaa AP-muutos myös verkossa
    if (NetworkServer.active || NetworkClient.active)
    {
        NetworkSync.BroadcastActionPoints(this, actionPoints);
    }
}

private void OnTurnEnded_HandleTurnEnded(Team endTurnTeam, int turnId)
{
    if (NetworkClient.active && !NetworkServer.active) return;
    if (Team != endTurnTeam) return;          // vain sen puolen lopussa joka oli vuorossa
    int ap = GetActionPoints();
```

RogueShooter – All Scripts

```
int per = GetCoverRegenPerUnusedAP();          // palauttaa >0 vain jos ei underFire
if (ap > 0 && per > 0) Cover.RegenCoverBy(ap * per); // coverSkill hoitaa clampit jne.
// (valinnainen) nollaa AP:t heti vuoron päättyessä:
actionPoints = 0;
OnAnyActionPointsChanged?.Invoke(this, EventArgs.Empty);
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/BaseAction.cs

```
using UnityEngine;
using Mirror;
using System;
using System.Collections.Generic;

/// <summary>
/// Base class for all unit actions in the game.
/// This class inherits from NetworkBehaviour and provides common functionality for unit actions.
/// </summary>
[RequireComponent(typeof(Unit))]
public abstract class BaseAction : NetworkBehaviour
{
    public static event EventHandler OnAnyActionStarted;
    public static event EventHandler OnAnyActionCompleted;

    protected Unit unit;
    protected bool isActive;
    protected Action onActionComplete;

    protected virtual void Awake()
    {
        unit = GetComponent<Unit>();
    }

    // Defines the action button text for the Unit UI.
    public abstract string GetActionName();

    // Executes the action at the specified grid position and invokes the callback upon completion.
    public abstract void TakeAction(GridPosition gridPosition, Action onActionComplete);

    // Checks if the specified grid position is valid for the action, when mouse is over a grid position.
    public virtual bool IsValidGridPosition(GridPosition gridPosition)
    {
        List<GridPosition> validGridPositionsList = GetValidGridPositionList();
        return validGridPositionsList.Contains(gridPosition);
    }

    // Returns a list of valid grid positions for the action.
    public abstract List<GridPosition> GetValidGridPositionList();

    // Returns the action points cost for performing the action.
    public virtual int GetActionPointsCost()
    {
        return 1;
    }

    // Called when the action starts, sets the action as active and stores the completion callback.
```

RogueShooter – All Scripts

```
// Prevents the player from performing multiple actions at the same time.
protected void ActionStart(Action onActionComplete)
{
    isActive = true;
    this.onActionComplete = onActionComplete;

    OnAnyActionStarted?.Invoke(this, EventArgs.Empty);
}

// Called when the action is completed, sets the action as inactive and invokes the completion callback.
// Allows the player to perform new actions.
protected void ActionComplete()
{
    isActive = false;
    onActionComplete();

    OnAnyActionCompleted?.Invoke(this, EventArgs.Empty);
}

public Unit GetUnit()
{
    return unit;
}

public void MakeDamage(int damage, Unit targetUnit)
{
    // Peruspaikat (world-space)
    Vector3 attacerPos = unit.GetWorldPosition() + Vector3.up * 1.6f; // silmä/rinta
    Vector3 targetPos = targetUnit.GetWorldPosition() + Vector3.up * 1.2f;
    // Suunta
    Vector3 dir = targetPos - attacerPos;
    if (dir.sqrMagnitude < 0.0001f) dir = targetUnit.transform.forward; // fallback
    dir.Normalize();

    // Siirrä osumakeskus hieman kohti hyökkääjää (0.5-1.0 m toimii yleensä hyvin)
    float backOffset = 0.7f;
    Vector3 hitPosition = targetPos - dir * backOffset;

    // (valinnainen) pieni satunnainen sivuttaisjitter, ettei kaikki näytä identtiseltä
    Vector3 side = Vector3.Cross(dir, Vector3.up).normalized;
    hitPosition += side * UnityEngine.Random.Range(-0.1f, 0.1f);

    NetworkSync.ApplyDamageToUnit(targetUnit, damage, hitPosition, this.GetActorId());
}

public void ApplyHit(int damage, Unit targetUnit, bool melee)
{
    targetUnit.SetUnderFire(true);
    var ct = GetCoverType(targetUnit);

    if (ct == CoverService.CoverType.None && !melee)
```

RogueShooter – All Scripts

```
{
    MakeDamage(damage, targetUnit);
    return;
}

float mitigate = 1;
if (targetUnit.GetPersonalCover() > 0)
{
    mitigate = CoverService.GetCoverMitigationPoints(ct);
}

int toCover = Mathf.RoundToInt(damage * mitigate);
int before = targetUnit.GetPersonalCover();
int after = before - toCover;

if (melee)
{
    after -= damage;
}

if (after >= 0)
{
    targetUnit.SetPersonalCover(after);
    NetworkSync.UpdateCoverUI(targetUnit);
}
else
{
    targetUnit.SetPersonalCover(0);
    NetworkSync.UpdateCoverUI(targetUnit);
    MakeDamage(damage - before, targetUnit);
}
}

public CoverService.CoverType GetCoverType(Unit targetUnit)
{
    var gp = targetUnit.GetGridPosition();
    var node = PathFinding.Instance.GetNode(gp.x, gp.z, gp.floor);
    var ct = CoverService.EvaluateCoverHalfPlane(unit.GetGridPosition(), targetUnit.GetGridPosition(), node);
    return ct;
}

public bool RotateTowards(Vector3 targetPosition, float rotationSpeed = 10f)
{
    // Suuntavektori
    Vector3 aimDirection = (targetPosition - unit.GetWorldPosition()).normalized;
    aimDirection.y = 0f;

    transform.forward = Vector3.Slerp(transform.forward, aimDirection, Time.deltaTime * rotationSpeed);

    // Kääntyminen on suoritettu.
    float tolerance = 0.99f;
    float dot = Vector3.Dot(transform.forward.normalized, aimDirection);
```

RogueShooter – All Scripts

```
        return dot > tolerance;
    }

    // ----- ENEMY AI ACTIONS -----

    /// <summary>
    /// ENEMY AI:
    /// Empty ENEMY AI ACTIONS abstract class.
    /// Every Unit action like MoveAction.cs, ShootAction.cs and so on defines this differently
    /// Contains gridposition and action value
    /// </summary>
    public abstract EnemyAIAction GetEnemyAIAction(GridPosition gridPosition);

    /// <summary>
    /// ENEMY AI:
    /// Making a list all possible actions an enemy Unit can take, and shorting them
    /// based on highest action value.(Gives the enemy the best outcome)
    /// The best Action is in the enemyAIActionList[0]
    /// </summary>
    public EnemyAIAction GetBestEnemyAIAction()
    {
        List<EnemyAIAction> enemyAIActionList = new();

        List<GridPosition> validActionGridPositionList = GetValidGridPositionList();

        foreach (GridPosition gridPosition in validActionGridPositionList)
        {
            // All actions have own EnemyAIAction to set griposition and action value.
            EnemyAIAction enemyAIAction = GetEnemyAIAction(gridPosition);
            enemyAIActionList.Add(enemyAIAction);
        }

        if (enemyAIActionList.Count > 0)
        {
            enemyAIActionList.Sort((a, b) => b.actionValue - a.actionValue);
            return enemyAIActionList[0];
        }
        else
        {
            // No possible Enemy AI Actions
            return null;
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/GranadeAction.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using UnityEngine;

public class GranadeAction : BaseAction
{
    public event EventHandler ThrowGranade;

    public event EventHandler ThrowReady;

    public Vector3 TargetWorld { get; private set; }

    [SerializeField] private Transform grenadeProjectilePrefab;

    private void Update()
    {
        if (!IsActive)
        {
            return;
        }
    }

    public override string GetActionName()
    {
        return "Granade";
    }

    public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
    {
        return new EnemyAIAction
        {
            gridPosition = gridPosition,
            actionValue = 0,
        };
    }

    public override List<GridPosition> GetValidGridPositionList()
    {
        List<GridPosition> validGridPositionList = new();

        GridPosition unitGridPosition = unit.GetGridPosition();
        int range = unit.archetype.throwingRange;
        for (int x = -range; x <= range; x++)
        {
            for (int z = -range; z <= range; z++)
            {
                GridPosition offsetGridPosition = new(x, z, 0);
                GridPosition testGridPosition = unitGridPosition + offsetGridPosition;
```

RogueShooter – All Scripts

```
        // Check if the test grid position is within the valid range
        if (!LevelGrid.Instance.IsValidGridPosition(testGridPosition)) continue;

        int cost = SircleCalculator.Sircle(x, z);
        if (cost > 10 * range) continue;

        validGridPositionList.Add(testGridPosition);
    }
}

return validGridPositionList;
}

public override void TakeAction(GridPosition gridPosition, Action onActionComplete)
{
    GetUnit().UseGrenade();
    ActionStart(onActionComplete);
    TargetWorld = LevelGrid.Instance.GetWorldPosition(gridPosition);
    StartCoroutine(TurnAndThrow(.5f, TargetWorld));
}

private IEnumerator TurnAndThrow(float delay, Vector3 targetWorld)
{
    // Odotetaan kunnes RotateTowards palaa true
    float waitAfterAligned = 0.1f; // pienen odotuksen verran
    float alignedTime = 0f;

    while (true)
    {
        bool aligned = RotateTowards(targetWorld);

        if (aligned)
        {
            alignedTime += Time.deltaTime;
            if (alignedTime >= waitAfterAligned)
                break; // ollaan kohdistettu ja odotettu tarpeeksi
        }
        else
        {
            alignedTime = 0f; // resetoit jos ei vielä kohdallaan
        }

        yield return null;
    }

    ThrowGranade?.Invoke(this, EventArgs.Empty);
}

public void OnGrenadeBehaviourComplete()
{
    ThrowReady?.Invoke(this, EventArgs.Empty);
}
```


RogueShooter - All Scripts

```
    }  
    ActionComplete();  
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/InteractAction.cs

```
using System;
using System.Collections.Generic;

public class InteractAction : BaseAction
{
    private void Update()
    {
        if (!isActive)
        {
            return;
        }
    }

    public override string GetActionName()
    {
        return "Interact";
    }

    public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
    {
        return new EnemyAIAction
        {
            gridPosition = gridPosition,
            actionValue = 0,
        };
    }

    public override List<GridPosition> GetValidGridPositionList()
    {
        List<GridPosition> validGridPositionList = new();

        GridPosition unitGridPosition = unit.GetGridPosition();

        for (int x = -1; x <= 1; x++)
        {
            for (int z = -1; z <= 1; z++)
            {
                GridPosition offsetGridPosition = new(x, z, 0);
                GridPosition testGridPosition = unitGridPosition + offsetGridPosition;

                if (!LevelGrid.Instance.IsValidGridPosition(testGridPosition)) continue;
                IInteractable interactable = LevelGrid.Instance.GetInteractableAtGridPosition(testGridPosition);
                if (interactable == null) continue;
                validGridPositionList.Add(testGridPosition);
            }
        }

        return validGridPositionList;
    }
}
```

RogueShooter – All Scripts

```
public override void TakeAction(GridPosition gridPosition, Action onActionComplete)
{
    IInteractable interactable = LevelGrid.Instance.GetInteractableAtGridPosition(gridPosition);
    interactable.Interact(OnInteractComplete);
    ActionStart(onActionComplete);
}

private void OnInteractComplete()
{
    ActionComplete();
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/MeleeAction.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;

public class MeleeAction : BaseAction
{
    public static event EventHandler OnAnyMeleeActionHit;

    public event EventHandler OnMeleeActionStarted;
    public event EventHandler OnMeleeActionCompleted;
    [SerializeField] private int damage = 100;

    private enum State
    {
        MeleeActionBeforeHit,
        MeleeActionAfterHit,
    }

    private int maxMeleedDistance = 1;
    private State state;
    private float stateTimer;
    private Unit targetUnit;

    private void Update()
    {
        if (!isActive)
        {
            return;
        }
        stateTimer -= Time.deltaTime;
        switch (state)
        {
            case State.MeleeActionBeforeHit:
                if (targetUnit != null)
                {
                    if (RotateTowards(targetUnit.GetWorldPosition()))
                    {
                        stateTimer = Mathf.Min(stateTimer, 0.4f);
                    }
                }
                break;
            case State.MeleeActionAfterHit:
                break;
        }

        if (stateTimer <= 0f)
        {
            NextState();
        }
    }
}
```

RogueShooter – All Scripts

```
private void NextState()
{
    switch (state)
    {
        case State.MeleeActionBeforeHit:
            state = State.MeleeActionAfterHit;
            float afterHitStateTime = 1f;
            stateTimer = afterHitStateTime;
            ApplyHit(damage, targetUnit, true);
            OnAnyMeleeActionHit?.Invoke(this, EventArgs.Empty);
            break;
        case State.MeleeActionAfterHit:
            OnMeleeActionCompleted?.Invoke(this, EventArgs.Empty);
            ActionComplete();
            break;
    }
}

public override string GetActionName()
{
    return "Melee";
}

public override List<GridPosition> GetValidGridPositionList()
{
    var valid = new List<GridPosition>();
    GridPosition origin = unit.GetGridPosition();

    for (int dx = -maxMeleedDistance; dx <= maxMeleedDistance; dx++)
    {
        for (int dz = -maxMeleedDistance; dz <= maxMeleedDistance; dz++)
        {
            if (dx == 0 && dz == 0) continue; // ei itseään

            var gp = origin + new GridPosition(dx, dz, 0);

            // 1) RAJAT ENSIN -> estää out-of-range -virheen
            if (!LevelGrid.Instance.IsValidGridPosition(gp)) continue;

            // Manhattan -> sulkee diagonaalit
            // if (Mathf.Abs(dx) + Mathf.Abs(dz) > maxMeleedDistance) continue;

            // Chebyshev -> sallii diagonaalit
            if (Mathf.Max(Mathf.Abs(dx), Mathf.Abs(dz)) > maxMeleedDistance) continue;

            // 2) onko ruudussa ketään?
            if (!LevelGrid.Instance.HasAnyUnitOnGridPosition(gp)) continue;

            var target = LevelGrid.Instance.GetUnitAtGridPosition(gp);
            if (target == null || target == unit) continue; // varmistus
            if (target.IsEnemy() == unit.IsEnemy()) continue; // ei omia
        }
    }

    return valid;
}
```

RogueShooter – All Scripts

```
        valid.Add(gp);
    }
}
return valid;
}

public override void TakeAction(GridPosition gridPosition, Action onActionComplete)
{
    targetUnit = LevelGrid.Instance.GetUnitAtGridPosition(gridPosition);

    state = State.MeleeActionBeforeHit;
    float beforeHitStateTime = 0.7f;
    stateTimer = beforeHitStateTime;
    OnMeleeActionStarted?.Invoke(this, EventArgs.Empty);
    ActionStart(onActionComplete);
}

//----- ENEMY AI ACTIONS -----
public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
{
    return new EnemyAIAction
    {
        gridPosition = gridPosition,
        actionValue = 200,
    };
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/MoveAction.cs

```
using System;
using System.Collections.Generic;
using Mirror;
using UnityEngine;

/// <summary>
/// The MoveAction class is responsible for handling the movement of a unit in the game.
/// It allows the unit to move to a target position, and it calculates valid move grid positions based on the unit's current position.
/// </summary>
public class MoveAction : BaseAction
{
    public event EventHandler OnStartMoving;
    public event EventHandler OnStopMoving;

    GridPosition thisTurnStartingGridPosition;
    GridPosition thisTurnEndridPosition;

    [SerializeField] private int maxMoveDistance = 4;

    private int distance;

    private List<Vector3> positionList;
    private int currentPositionIndex;

    private bool isChangingFloors;
    private float differentFloorsTeleportTimer;
    private float differentFloorsTeleportTimerMax = .5f;

    private void Start()
    {
        distance = 0;
        thisTurnStartingGridPosition = unit.GetGridPosition();
        thisTurnEndridPosition = unit.GetGridPosition();
        TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
    }

    void OnDisable()
    {
        TurnSystem.Instance.OnTurnChanged -= TurnSystem_OnTurnChanged;
    }

    private void TurnSystem_OnTurnChanged(object sender, EventArgs e)
    {
        thisTurnStartingGridPosition = unit.GetGridPosition();
        distance = 0;
    }

    private void Update()
```

RogueShooter – All Scripts

```
{
    if (!isActive) return;

    Vector3 targetPosition = positionList[currentPositionIndex];

    if (isChangingFloors)
    {
        Vector3 targetSameFloorPosition = targetPosition;
        targetSameFloorPosition.y = transform.position.y;
        Vector3 rotateDirection = (targetSameFloorPosition - transform.position).normalized;

        float rotationSpeed = 10f;
        transform.forward = Vector3.Slerp(transform.forward, rotateDirection, Time.deltaTime * rotationSpeed);
        differentFloorsTeleportTimer -= Time.deltaTime;
        if (differentFloorsTeleportTimer < 0f)
        {
            isChangingFloors = false;
            transform.position = targetPosition;
        }
    }
    else
    {
        Vector3 moveDirection = (targetPosition - transform.position).normalized;

        // Rotate towards the target position
        float rotationSpeed = 10f;
        transform.forward = Vector3.Slerp(transform.forward, moveDirection, Time.deltaTime * rotationSpeed);

        // Move towards the target position
        float moveSpeed = 6f;
        transform.position += moveSpeed * Time.deltaTime * moveDirection;
    }

    float stoppingDistance = 0.2f;
    if (Vector3.Distance(transform.position, targetPosition) < stoppingDistance)
    {
        thisTurnEndridPosition = LevelGrid.Instance.GetGridPosition(transform.position);
        DistanceFromStartingPoint();

        currentPositionIndex++;
        if (currentPositionIndex >= positionList.Count)
        {
            if (thisTurnStartingGridPosition != thisTurnEndridPosition)
            {
                unit.SetUnderFire(false);
                CheckAndApplyCoverBonus();
            }
            else
            {
                unit.SetUnderFire(true);
            }
        }
    }
}
```


RogueShooter – All Scripts

```
        CheckAndApplyCoverBonus();
    }

    OnStopMoving?.Invoke(this, EventArgs.Empty);
    ActionComplete();
}

else
{
    targetPosition = positionList[currentPositionIndex];
    GridPosition targetGridPosition = LevelGrid.Instance.GetGridPosition(targetPosition);
    GridPosition unitGridPosition = LevelGrid.Instance.GetGridPosition(transform.position);

    if (targetGridPosition.floor != unitGridPosition.floor)
    {
        //Different floors
        isChangingFloors = true;
        differentFloorsTeleportTimer = differentFloorsTeleportTimerMax;
    }
}
}

}

private void CheckAndApplyCoverBonus()
{
    // Offline
    if (!NetworkServer.active && !NetworkClient.active)
    {
        unit.SetCoverBonus();
        return;
    }

    // Server suorittaa suoraan
    if (NetworkServer.active)
    {
        unit.SetCoverBonus();
        return;
    }

    // Client lähettää Command Serverille
    if (NetworkClient.active && NetworkSyncAgent.Local != null)
    {
        var ni = unit.GetComponent<NetworkIdentity>();
        if (ni != null)
        {
            NetworkSyncAgent.Local.CmdApplyCoverBonus(ni.netId);
        }
    }
}

public override void TakeAction(GridPosition gridPosition, Action onActionComplete)
{
}
```

RogueShooter – All Scripts

```
List<GridPosition> pathGridPositionsList = PathFinding.Instance.FindPath(unit.GetGridPosition(), gridPosition, out int pathLeght, maxMoveDistance);

currentPositionIndex = 0;
positionList = new List<Vector3>();

foreach (GridPosition pathGridPosition in pathGridPositionsList)
{
    positionList.Add(LevelGrid.Instance.GetWorldPosition(pathGridPosition));
}

OnStartMoving?.Invoke(this, EventArgs.Empty);
ActionStart(onActionComplete);
}

private void DistanceFromStartingPoint()
{
    int newDistance = PathFinding.Instance.CalculateDistance(thisTurnStartingGridPosition, thisTurnEndridPosition);

    int delta = newDistance - distance;
    if (Mathf.Abs(delta) < 10) return;
    if (delta != 0)
    {
        unit.RegenCoverOnMove(delta);
    }

    distance = newDistance;
}

public override List<GridPosition> GetValidGridPositionList()
{
    var valid = new List<GridPosition>();
    var candidates = new HashSet<GridPosition>(); // estää duplikaatit

    GridPosition unitPos = unit.GetGridPosition();
    int startFloor = unitPos.floor;

    // Jos maxMoveDistance on RUUTUJA, kustannusbudjetti on *10 per ruutu*
    const int COST_PER_TILE = 10;
    int moveBudgetCost = maxMoveDistance * COST_PER_TILE;

    // --- 1) Nykyisen kerroksen ruudut (perus-offsetit) ---
    for (int dx = -maxMoveDistance; dx <= maxMoveDistance; dx++)
    {
        for (int dz = -maxMoveDistance; dz <= maxMoveDistance; dz++)
        {
            var test = new GridPosition(unitPos.x + dx, unitPos.z + dz, startFloor);
            candidates.Add(test);
        }
    }
}
```

RogueShooter – All Scripts

```
// --- 2) Linkkien kautta saavutettavat kerrokset (hybridi) ---
var links = PathFinding.Instance.GetPathfindingLinks();
if (links != null && links.Count > 0)
{
    foreach (var link in links)
    {
        // A -> B
        if (link.gridPositionA.floor == startFloor)
        {
            int lbToA = PathFinding.Instance.CalculateDistance(unitPos, link.gridPositionA);
            if (lbToA <= moveBudgetCost)
            {
                int remaining = moveBudgetCost - lbToA;
                int radiusTiles = Mathf.Max(0, remaining / COST_PER_TILE);

                for (int dx = -radiusTiles; dx <= radiusTiles; dx++)
                {
                    for (int dz = -radiusTiles; dz <= radiusTiles; dz++)
                    {
                        var aroundB = new GridPosition(
                            link.gridPositionB.x + dx,
                            link.gridPositionB.z + dz,
                            link.gridPositionB.floor
                        );
                        candidates.Add(aroundB);
                    }
                }
            }
        }

        // B -> A
        if (link.gridPositionB.floor == startFloor)
        {
            int lbToB = PathFinding.Instance.CalculateDistance(unitPos, link.gridPositionB);
            if (lbToB <= moveBudgetCost)
            {
                int remaining = moveBudgetCost - lbToB;
                int radiusTiles = Mathf.Max(0, remaining / COST_PER_TILE);

                for (int dx = -radiusTiles; dx <= radiusTiles; dx++)
                {
                    for (int dz = -radiusTiles; dz <= radiusTiles; dz++)
                    {
                        var aroundA = new GridPosition(
                            link.gridPositionA.x + dx,
                            link.gridPositionA.z + dz,
                            link.gridPositionA.floor
                        );
                        candidates.Add(aroundA);
                    }
                }
            }
        }
    }
}
```

RogueShooter – All Scripts

```
    }
}

// --- 3) Suodata & tee vain yksi A* per kandidaatti (välimuistilla) ---
foreach (var test in candidates)
{
    // Perusvalidoinnit
    if (!LevelGrid.Instance.IsValidGridPosition(test)) continue;
    if (test == unitPos) continue;
    if (LevelGrid.Instance.HasAnyUnitOnGridPosition(test)) continue;
    if (!PathFinding.Instance.IsWalkableGridPosition(test)) continue;

    // Heuristiikkakarsinta (Manhattan*10): jos edes optimistinen kustannus > budjetti, skip
    int lowerBound = PathFinding.Instance.CalculateDistance(unitPos, test);
    if (lowerBound > moveBudgetCost) continue;

    // *** VAIN YKSI A* per ruutu (mutta nyt cachetettuna saman framen sisällä) ***
    if (!TryGetPathCostCached(unitPos, test, out int pathCost)) continue; // ei polkua
    if (pathCost > moveBudgetCost) continue;

    valid.Add(test);
}

return valid;
}

public override string GetActionName()
{
    return "Move";
}

// --- Per-frame pathfinding cache ---
private struct PathQuery : IEquatable<PathQuery> {
    public GridPosition start;
    public GridPosition end;
    public bool Equals(PathQuery other) => start == other.start && end == other.end;
    public override bool Equals(object obj) => obj is PathQuery pq && Equals(pq);
    public override int GetHashCode() => (start.GetHashCode() * 397) ^ end.GetHashCode();
}

private struct PathCacheEntry {
    public bool exists;
    public int cost;
    // Jos joskus haluat itse polun, voit lisätä: public List<GridPosition> path;
}

// Yhteinen cache tälle actionille (voisi olla myös static jos haluat jakaa yli instanssien)
private Dictionary<PathQuery, PathCacheEntry> _pathCache = new Dictionary<PathQuery, PathCacheEntry>(256);
private int _cacheFrame = -1;

private bool TryGetPathCostCached(GridPosition start, GridPosition end, out int cost)
```

RogueShooter – All Scripts

```
{
    // Nollaa cache kerran per frame
    int frame = Time.frameCount;
    if (_cacheFrame != frame) {
        _pathCache.Clear();
        _cacheFrame = frame;
    }

    var key = new PathQuery { start = start, end = end };
    if (_pathCache.TryGetValue(key, out var entry)) {
        cost = entry.cost;
        return entry.exists;
    }

    // Ei ollut välimuistissa -> laske kerran
    var path = PathFinding.Instance.FindPath(start, end, out int pathCost, maxMoveDistance);
    bool exists = path != null;
    _pathCache[key] = new PathCacheEntry { exists = exists, cost = pathCost };

    cost = pathCost;
    return exists;
}

public int GetMaxMoveDistance()
{
    return maxMoveDistance;
}

/// <summary>
/// ENEMY AI:
/// Move toward to Player unit to make shoot action.
/// </summary>
public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
{
    int targetCountAtGridPosition = unit.GetAction<ShootAction>().GetTargetCountAtPosition(gridPosition);

    return new EnemyAIAction
    {
        gridPosition = gridPosition,
        actionValue = targetCountAtGridPosition * 10,
    };
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/ShootAction.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;

public class ShootAction : BaseAction
{
    public static event EventHandler<OnShootEventArgs> OnAnyShoot;

    public event EventHandler<OnShootEventArgs> OnShoot;

    public class OnShootEventArgs : EventArgs
    {
        public Unit targetUnit;
        public Unit shootingUnit;
    }

    private enum State
    {
        Aiming,
        Shooting,
        Cooloff
    }

    [SerializeField] private LayerMask obstaclesLayerMask;
    private State state;
    [SerializeField] private WeaponDefinition weapon;

    private float stateTimer;
    private Unit targetUnit;
    private bool canShootBullet;

    // Update is called once per frame
    void Update()
    {
        if (!isActive) return;

        stateTimer -= Time.deltaTime;
        switch (state)
        {
            case State.Aiming:
                if (targetUnit != null)
                {
                    if (RotateTowards(targetUnit.GetWorldPosition()))
                    {
                        stateTimer = Mathf.Min(stateTimer, 0.4f);
                    }
                }
                break;
            case State.Shooting:
```

RogueShooter – All Scripts

```
        if (canShootBullet)
        {
            Shoot();
            canShootBullet = false;
        }
        break;
    case State.Cooloff:
        break;
}

if (stateTimer <= 0f)
{
    NextState();
}
}

private void NextState()
{
    switch (state)
    {
        case State.Aiming:
            state = State.Shooting;
            float shootingStateTime = 0.1f;
            stateTimer = shootingStateTime;
            break;
        case State.Shooting:
            state = State.Cooloff;
            float cooloffStateTime = 0.5f;
            stateTimer = cooloffStateTime;
            break;
        case State.Cooloff:
            ActionComplete();
            break;
    }
}

private void Shoot()
{
    OnAnyShoot?.Invoke(this, new OnShootEventArgs
    {
        targetUnit = targetUnit,
        shootingUnit = unit
    });

    OnShoot?.Invoke(this, new OnShootEventArgs
    {
        targetUnit = targetUnit,
        shootingUnit = unit
    });
}

// Laske tulos
```

RogueShooter – All Scripts

```
var result = ShootingResolver.Resolve(unit, targetUnit, weapon);

// Debug: näe mihin kategoriaan osui
Debug.Log($"[{unit.name}] → [{targetUnit.name}] | {result.tier} | dmg:{result.damage}");

switch (result.tier)
{
    case ShotTier.CritMiss:
        // Täysi huti – ei vaikutusta
        Debug.Log("Critical miss! Bullet flies off wildly.");
        return;

    case ShotTier.Miss:
        // Luo painetta ja vähentää henkilökohtaista suojaa mutta ei voi kuitenkaan osua.
        ApplyHit(result.damage, targetUnit, false);
        return;

    case ShotTier.Graze:
        // Luo painetta ja vähentää henkilökohtaista suojaa ja voi aiheuttaa
        // pientävahinkoa jos suoja on kulunut loppuun.
        // Jos suojaa ei ole ollenkaan niin tämäkin lasketaan suoraksi osumaksi.
        if (GetCoverType(targetUnit) == CoverService.CoverType.None)
        {
            MakeDamage(result.damage + weapon.NoCoverDamageBonus, targetUnit);
            return;
        }

        ApplyHit(result.damage, targetUnit, false);
        return;

    case ShotTier.Hit:
        // Vähentää ensin suojaa ja sitten osuu kokovahingolla.
        // Myös suojasta jäljelle jäänyt vahinko menee vahinkoon.
        if (GetCoverType(targetUnit) == CoverService.CoverType.None)
        {
            MakeDamage(result.damage + weapon.NoCoverDamageBonus, targetUnit);
            return;
        }

        ApplyHit(result.damage, targetUnit, false);
        return;

    case ShotTier.Crit:
        // Kriittinen osuma vähentää suojaa sekä menee suoraan läpi tehden vahinkoa.
        if (GetCoverType(targetUnit) == CoverService.CoverType.None)
        {
            ApplyHit(result.damage + weapon.NoCoverDamageBonus, targetUnit, false);
            return;
        }
        Debug.Log("Critical hit!");
        ApplyHit(result.damage, targetUnit, false);
        return;
}
```


RogueShooter – All Scripts

```
    }

}

public override int GetActionPointsCost()
{
    return 1;
}

public override string GetActionName()
{
    return "Shoot";
}

public List<GridPosition> GetValidActionGridPositionList(GridPosition unitGridPosition)
{
    List<GridPosition> validGridPositionList = new();

    for (int x = -weapon.maxShootRange; x <= weapon.maxShootRange; x++)
    {
        for (int z = -weapon.maxShootRange; z <= weapon.maxShootRange; z++)
        {
            for (int floor = -weapon.maxShootRange; floor <= weapon.maxShootRange; floor++)
            {
                GridPosition offsetGridPosition = new(x, z, floor);
                GridPosition testGridPosition = unitGridPosition + offsetGridPosition;

                // Check if the test grid position is within the valid range and not occupied by another unit
                if (!LevelGrid.Instance.IsValidGridPosition(testGridPosition)) continue;

                int cost = SircleCalculator.Sircle(x, z);

                if (cost > 10 * weapon.maxShootRange) continue;
                if (!LevelGrid.Instance.HasAnyUnitOnGridPosition(testGridPosition)) continue;

                Unit targetUnit = LevelGrid.Instance.GetUnitAtGridPosition(testGridPosition);
                if (targetUnit == null) continue;
                // Make sure we don't include friendly units.
                if (targetUnit.IsEnemy() == unit.IsEnemy()) continue;

                Vector3 unitWorldPosition = LevelGrid.Instance.GetWorldPosition(unitGridPosition);
                Vector3 shootDir = (targetUnit.GetWorldPosition() - unitWorldPosition).normalized;
                float unitShoulderHeight = 2.5f;

                // Check for obstacles between the shooting unit and the target unit
                if (Physics.Raycast(
                    unitWorldPosition + Vector3.up * unitShoulderHeight,
                    shootDir,
                    Vector3.Distance(unitWorldPosition, targetUnit.GetWorldPosition()),
                    obstaclesLayerMask))
                {
                    //Target Unit is Blocked by an Obstacle
                }
            }
        }
    }
}
```

RogueShooter – All Scripts

```
        continue;
    }

    // Check if there is a unit between the shooting unit and the target unit
    validGridPositionList.Add(testGridPosition);
}
}
}

return validGridPositionList;
}

public override void TakeAction(GridPosition gridPosition, Action onActionComplete)
{
    targetUnit = LevelGrid.Instance.GetUnitAtGridPosition(gridPosition);

    state = State.Aiming;
    float aimingStateTime = 1f;
    stateTimer = aimingStateTime;

    canShootBullet = true;

    ActionStart(onActionComplete);
}

public Unit GetTargetUnit()
{
    return targetUnit;
}

public int GetMaxShootDistance()
{
    return weapon.maxShootRange;
}

/// ----- AI -----
/// <summary>
/// ENEMY AI: Make a list about Player Units what Enemy Unit can shoot.
/// </summary>
public override List<GridPosition> GetValidGridPositionList()
{
    GridPosition unitGridPosition = unit.GetGridPosition();
    return GetValidActionGridPositionList(unitGridPosition);
}

/// <summary>
/// ENEMY AI: How "good" target is. Target who have a lowest health, gets a higher actionvalue
/// </summary>
public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
{

```

RogueShooter – All Scripts

```
        Unit targetUnit = LevelGrid.Instance.GetUnitAtGridPosition(gridPosition);

        return new EnemyAIAction
        {
            gridPosition = gridPosition,
            actionValue = 100 + Mathf.RoundToInt((1 - targetUnit.GetHealthNormalized()) * 100f), //Take at target who have a lowest health.
        };
    }

    public int GetTargetCountAtPosition(GridPosition gridPosition)
    {
        return GetValidActionGridPositionList(gridPosition).Count;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/Actions/TurnTowardsAction.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using UnityEngine;

/// <summary>
///     This class is responsible for spinning a unit around its Y-axis.
/// </summary>
/// <remarks>
///     Change to turn towards the direction the mouse is pointing
/// </remarks>

public class TurnTowardsAction : BaseAction
{
    private enum State
    {
        StartTurning,
        EndTurning,
    }
    private State state;
    public Vector3 TargetWorld { get; private set; }

    private float stateTimer;
    GridPosition gridPosition;

    private void Update()
    {
        if (!isActive)
        {
            return;
        }
        stateTimer -= Time.deltaTime;
        switch (state)
        {
            case State.StartTurning:
                if (RotateTowards(TargetWorld))
                {
                    stateTimer = 0;
                }
                break;
            case State.EndTurning:
                break;
        }

        if (stateTimer <= 0f)
        {
            NextState();
        }
    }
}
```

RogueShooter – All Scripts

```
    }  
  
}  
  
private void NextState()  
{  
    switch (state)  
    {  
        case State.StartTurning:  
            state = State.EndTurning;  
            float afterTurnStateTime = 0.5f;  
            stateTimer = afterTurnStateTime;  
  
            break;  
        case State.EndTurning:  
            ActionComplete();  
            break;  
    }  
}  
  
public override void TakeAction(GridPosition gridPosition, Action onActionComplete)  
{  
    TargetWorld = LevelGrid.Instance.GetWorldPosition(gridPosition);  
    this.gridPosition = gridPosition;  
    state = State.StartTurning;  
    float beforeTurnStateTime = 0.7f;  
    stateTimer = beforeTurnStateTime;  
    ActionStart(onActionComplete);  
}  
  
public override string GetActionName()  
{  
    return "Turn";  
}  
  
public override List<GridPosition> GetValidGridPositionList()  
{  
    List<GridPosition> validGridPositionList = new();  
  
    GridPosition unitGridPosition = unit.GetGridPosition();  
  
    for (int x = -1; x <= 1; x++)  
    {  
        for (int z = -1; z <= 1; z++)  
        {  
            GridPosition offsetGridPosition = new(x, z, 0);  
            GridPosition testGridPosition = unitGridPosition + offsetGridPosition;  
            validGridPositionList.Add(testGridPosition);  
        }  
    }  
  
    return validGridPositionList;  
}
```

RogueShooter – All Scripts

```
public override int GetActionPointsCost()
{
    return 100;
}

/// <summary>
/// ENEMY AI:
/// Currently this action has no value. Just testing!
/// </summary>

public override EnemyAIAction GetEnemyAIAction(GridPosition gridPosition)
{
    return new EnemyAIAction
    {
        gridPosition = gridPosition,
        actionValue = 0,
    };
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/ScreenShakeActions.cs

```
using System;
using UnityEngine;

public class ScreenShakeActions : MonoBehaviour
{
    private void Start()
    {
        ShootAction.OnAnyShoot += ShootAction_OnAnyShoot;
        GrenadeProjectile.OnAnyGranadeExploded += GrenadeProjectile_OnAnyGranadeExploded;
        MeleeAction.OnAnyMeleeActionHit += MeleeAction_OnAnyMeleeActionHit;
    }

    private void OnDisable()
    {
        ShootAction.OnAnyShoot -= ShootAction_OnAnyShoot;
        GrenadeProjectile.OnAnyGranadeExploded -= GrenadeProjectile_OnAnyGranadeExploded;
        MeleeAction.OnAnyMeleeActionHit -= MeleeAction_OnAnyMeleeActionHit;
    }

    private void ShootAction_OnAnyShoot(object sender, ShootAction.OnShootEventArgs e)
    {
        ScreenShake.Instance.RecoilCameraShake(1f);
    }

    private void GrenadeProjectile_OnAnyGranadeExploded(object sender, EventArgs e)
    {
        ScreenShake.Instance.ExplosiveCameraShake(2f);
    }

    private void MeleeAction_OnAnyMeleeActionHit(object sender, EventArgs e)
    {
        ScreenShake.Instance.RecoilCameraShake(3f);
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitActions/UnitActionSystem.cs

```
using System;
using UnityEngine;
using UnityEngine.EventSystems;

/// <summary>
/// This script handles the unit action system in the game.
/// It allows the player to select units and perform actions on them, such as moving or shooting.
/// It also manages the state of the selected unit and action, and prevents the player from performing multiple actions at the same time.
/// Note: This class Script Execution Order is set to be executed before UnitManager.cs. High priority.
/// </summary>
public class UnitActionSystem : MonoBehaviour
{
    public static UnitActionSystem Instance { get; private set; }

    public event EventHandler OnSelectedUnitChanged;
    public event EventHandler OnSelectedActionChanged;
    public event EventHandler<bool> OnBusyChanged;
    public event EventHandler OnActionStarted;

    // This allows the script to only interact with objects on the specified layer
    [SerializeField] private LayerMask unitLayerMask;
    [SerializeField] private Unit selectedUnit;

    private BaseAction selectedAction;

    // Prevents the player from performing multiple actions at the same time
    private bool isBusy;

    private void Awake()
    {
        selectedUnit = null;
        // Ensure that there is only one instance in the scene
        if (Instance != null)
        {
            Debug.LogError("UnitActionSystem: More than one UnitActionSystem in the scene!" + transform + " " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;
    }

    private void Start()
    {
    }

    private void Update()
    {
        // Debug.Log(LevelGrid.Instance.GetGridPosition(MouseWorld.GetMouseWorldPosition()));
        // Prevents the player from performing multiple actions at the same time
        if (isBusy) return;
    }
}
```


RogueShooter – All Scripts

```
// if is not the player's turn, ignore input
if (!TurnSystem.Instance.IsPlayerTurn()) return;

// Ignore input if the mouse is over a UI element
if (EventSystem.current.IsPointerOverGameObject()) return;

// Check if the player is trying to select a unit or move the selected unit
if (TryHandleUnitSelection()) return;

HandleSelectedAction();
}

private void HandleSelectedAction()
{
    if (selectedUnit == null || selectedAction == null) return;

    if (InputManager.Instance.IsMouseButtonDownThisFrame() && selectedAction is GrenadeAction)
    {
        if (selectedUnit.GetGrenadePCS() <= 0) return;
    }

    GridPosition targetGridPosition;

    if (InputManager.Instance.IsMouseButtonDownThisFrame() && selectedAction is ShootAction)
    {
        Ray ray = Camera.main.ScreenPointToRay(InputManager.Instance.GetMouseScreenPosition());
        if (Physics.Raycast(ray, out RaycastHit hit, float.MaxValue, unitLayerMask))
        {
            if (hit.transform.TryGetComponent<Unit>(out Unit unit))
            {
                if (unit.IsEnemy())
                {
                    targetGridPosition = unit.GetGridPosition();
                    TryExecuteSelectedAction(targetGridPosition);
                }
            }
        }
    }
    else if (InputManager.Instance.IsMouseButtonDownThisFrame())
    {
        Vector3 world = MouseWorld.GetPositionOnlyHitVisible();
        targetGridPosition = LevelGrid.Instance.GetGridPosition(world);
        TryExecuteSelectedAction(targetGridPosition);
    }
}

private void TryExecuteSelectedAction(GridPosition gp)
{
    int steps = selectedUnit.GetMaxMoveDistance();
    int moveBudgetCost = PathFinding.CostFromSteps(steps);
```

RogueShooter – All Scripts

```
int estCost = PathFinding.Instance.CalculateDistance(selectedUnit.GetGridPosition(), gp);
if (estCost > moveBudgetCost * 10) return;

if (!selectedAction.IsValidGridPosition(gp) ||
    !selectedUnit.TrySpendActionPointsToTakeAction(selectedAction)) return;

SetBusy();
selectedAction.TakeAction(gp, ClearBusy);
OnActionStarted?.Invoke(this, EventArgs.Empty);
}

/// <summary>
///     Prevents the player from performing multiple actions at the same time
/// </summary>
private void SetBusy()
{
    isBusy = true;
    OnBusyChanged?.Invoke(this, isBusy);
}

/// <summary>
///     This method is called when the action is completed.
/// </summary>
private void ClearBusy()
{
    isBusy = false;
    OnBusyChanged?.Invoke(this, isBusy);
}

/// <summary>
///     This method is called when the player clicks on a unit in the game world.
///     Check if the mouse is over a unit
///     If so, select the unit and return
///     If not, move the selected unit to the mouse position
/// </summary>
private bool TryHandleUnitSelection()
{
    if (InputManager.Instance.IsMouseButtonDownThisFrame())
    {
        Ray ray = Camera.main.ScreenPointToRay(InputManager.Instance.GetMouseScreenPosition());
        if (Physics.Raycast(ray, out RaycastHit hit, float.MaxValue, unitLayerMask))
        {
            if (hit.transform.TryGetComponent<Unit>(out Unit unit))
            {
                if (AuthorityHelper.HasLocalControl(unit) || unit == selectedUnit) return false;
                SetSelectedUnit(unit);
                return true;
            }
        }
    }

    return false;
}
```

RogueShooter – All Scripts

```
}

/// <summary>
///     Sets the selected unit and triggers the OnSelectedUnitChanged event.
///     By defaults set the selected action to the unit's move action. The most common action.
/// </summary>
private void SetSelectedUnit(Unit unit)
{
    if (unit.IsEnemy())
    {
        if(selectedAction is ShootAction)
        {
            HandleSelectedAction();
        }
        return;
    }
    selectedUnit = unit;
    SetSelectedAction(unit.GetAction<MoveAction>());
    OnSelectedUnitChanged?.Invoke(this, EventArgs.Empty);
}

/// <summary>
///     Sets the selected action and triggers the OnSelectedActionChanged event.
/// </summary>
public void SetSelectedAction(BaseAction baseAction)
{
    selectedAction = baseAction;
    OnSelectedActionChanged?.Invoke(this, EventArgs.Empty);
}

public Unit GetSelectedUnit()
{
    return selectedUnit;
}

public BaseAction GetSelectedAction()
{
    return selectedAction;
}

public void ResetSelectedAction()
{
    selectedAction = null;
}

public void ResetSelectedUnit()
{
    selectedUnit = null;
}

// Lock/Unlock input methods for PlayerController when playing online
public void LockInput() { if (!isBusy) SetBusy(); }
```

RogueShooter – All Scripts

```
public void UnlockInput() { if (isBusy) ClearBusy(); }  
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitAnimator.cs

```
using UnityEngine;
using System;
using Mirror;

[RequireComponent(typeof(MoveAction))]
public class UnitAnimator : NetworkBehaviour
{
    [Header("UnitWeaponVisibilitySync")]
    [SerializeField] private WeaponVisibilitySync weaponVis;

    [Header("Animators")]
    [SerializeField] private Animator animator;
    [SerializeField] private NetworkAnimator netAnim;

    [Header("Projectiles")]
    [SerializeField] private GameObject bulletProjectilePrefab;
    [SerializeField] private GameObject grenadeProjectilePrefab;

    [Header("Spawnpoints")]
    [SerializeField] private Transform shootPointTransform;
    [SerializeField] private Transform rightHandTransform;

    private static bool IsNetworkActive() => NetworkClient.active || NetworkServer.active;

    private MoveAction _move;
    private ShootAction _shoot;
    private GrenadeAction _grenade;
    private MeleeAction _melee;

    private bool useNetwork;

    private void Awake()
    {
        if (!animator) animator = GetComponent<Animator>();
        if (!netAnim) netAnim = GetComponent<NetworkAnimator>();

        useNetwork = NetMode.IsOnline
            && netAnim != null
            && (isServer || isOwned); // NetworkBehaviourin omat propertyt

        TryGetComponent(out _move);
        TryGetComponent(out _shoot);
        TryGetComponent(out _grenade);
        TryGetComponent(out _melee);
    }

    private void OnEnable()
    {
        // Varmuus: poista ensin, tilaa sitten -> estää tuplat vaikka OnEnable ajettaisiin useasti
    }
}
```

RogueShooter – All Scripts

```
    if (_move)
    {
        _move.OnStartMoving -= MoveAction_OnStartMoving;
        _move.OnStopMoving -= MoveAction_OnStopMoving;
        _move.OnStartMoving += MoveAction_OnStartMoving;
        _move.OnStopMoving += MoveAction_OnStopMoving;
    }

    if (_shoot)
    {
        _shoot.OnShoot -= ShootAction_OnShoot;
        _shoot.OnShoot += ShootAction_OnShoot;
    }

    if (_grenade)
    {
        _grenade.ThrowGranade -= GrenadeAction_ThrowGranade;
        _grenade.ThrowReady -= GrenadeAction_ThrowReady;
        _grenade.ThrowGranade += GrenadeAction_ThrowGranade;
        _grenade.ThrowReady += GrenadeAction_ThrowReady;
    }

    if (_melee)
    {
        _melee.OnMeleeActionStarted -= MeleeAction_OnMeleeActionStarted;
        _melee.OnMeleeActionCompleted -= MeleeAction_OnMeleeActionCompleted;
        _melee.OnMeleeActionStarted += MeleeAction_OnMeleeActionStarted;
        _melee.OnMeleeActionCompleted += MeleeAction_OnMeleeActionCompleted;
    }
}

private void OnDisable()
{
    if (_move)
    {
        _move.OnStartMoving -= MoveAction_OnStartMoving;
        _move.OnStopMoving -= MoveAction_OnStopMoving;
    }
    if (_shoot)
    {
        _shoot.OnShoot -= ShootAction_OnShoot;
    }
    if (_grenade)
    {
        _grenade.ThrowGranade -= GrenadeAction_ThrowGranade;
        _grenade.ThrowReady -= GrenadeAction_ThrowReady;
    }
    if (_melee)
    {
        _melee.OnMeleeActionStarted -= MeleeAction_OnMeleeActionStarted;
        _melee.OnMeleeActionCompleted -= MeleeAction_OnMeleeActionCompleted;
    }
}
```

RogueShooter – All Scripts

```
}

private void Start()
{
    EquipRifle();
}

// Valitsee automaattisesti oikean verkko/offline animaation.
public void SetTrigger(string name)
{
    if (useNetwork) netAnim.SetTrigger(name);
    else animator.SetTrigger(name);
}

private void MoveAction_OnStartMoving(object sender, EventArgs e)
{
    animator.SetBool("IsRunning", true);
}
private void MoveAction_OnStopMoving(object sender, EventArgs e)
{
    animator.SetBool("IsRunning", false);
}

public Transform ShootPoint => shootPointTransform;
public GameObject BulletPrefab => bulletProjectilePrefab;

private void ShootAction_OnShoot(object sender, ShootAction.OnShootEventArgs e)
{
    SetTrigger("Shoot");

    Vector3 target = e.targetUnit.GetWorldPosition();
    float unitShoulderHeight = 2.5f;
    target.y += unitShoulderHeight;

    if (NetMode.IsOnline)
    {
        NetworkSync.SpawnBullet(bulletProjectilePrefab, shootPointTransform.position, target, this.GetActorId());
    }
    else
    {
        OfflineGameSimulator.SpawnBullet(bulletProjectilePrefab, shootPointTransform.position, target);
    }
}

private void MeleeAction_OnMeleeActionStarted(object sender, EventArgs e)
{
    EquipMelee();
    SetTrigger("Melee");
}

/*
```

RogueShooter – All Scripts

```
        if (!IsNetworkActive())
        {
            animator.SetTrigger("Melee");
        }
        else
        {
            netAnim.SetTrigger("Melee");
        }
    }
    */

}
private void MeleeAction_OnMeleeActionCompleted(object sender, EventArgs e)
{
    EquipRifle();
}

private void GrenadeActionStart()
{
    weaponVis.OwnerRequestSet(rifleRight: false, rifleLeft: true, meleeLeft: false, grenade: false);
}
private Vector3 pendingGrenadeTarget;
private GrenadeAction pendingGrenadeAction;
private void GrenadeAction_ThrowGrenade(object sender, EventArgs e)
{
    pendingGrenadeAction = (GrenadeAction)sender;
    pendingGrenadeTarget = pendingGrenadeAction.TargetWorld;
    GrenadeActionStart();
    SetTrigger("ThrowGrenade");
}

// ----- START Grenade Animation events START -----
// Event marks is set in animation. UnitAnimations -> Throw Grenade Stand
public void AE_PickGrenadeStand()
{
    EguipGranade();
}

public Transform ThrowPoint => rightHandTransform;
public GameObject GrenadePrefab => grenadeProjectilePrefab;

public void AE_ThrowGrenadeStandRelease()
{
    // --- GUARD: jos pending on jo käytetty, älä tee mitään (estää tuplan samalta koneelta)
    if (pendingGrenadeAction == null) return;

    // --- GATE: onlinessa vain omistaja-client saa jatkaa (server ja ei-ownerit return)
    if (NetworkClient.active || NetworkServer.active)
    {
        var ni = GetComponentInParent<NetworkIdentity>();
        if (!(isClient && ni && ni.isOwned)) return;
    }
}
```


RogueShooter – All Scripts

```
// Mistä kranaatti lähtee (sama logiikka kuin luodeilla)
Vector3 origin = rightHandTransform.position;

// Kutsu keskitettyä synkkaa (täsmälleen kuin luodeissa)
if (NetMode.IsOnline)
    NetworkSync.SpawnGrenade(granadeProjectilePrefab, origin, pendingGrenadeTarget, this.GetActorId());
else
    OfflineGameSimulator.SpawnGrenade(granadeProjectilePrefab, origin, pendingGrenadeTarget);

// Siivous kuten ennen
pendingGrenadeAction?.OnGrenadeBehaviourComplete();
pendingGrenadeAction = null;
}

public void AE_OnGrenadeThrowStandFinished()
{
    EquipRifle();
}
//----- END Grenade Animation events END -----
private void GrenadeAction_ThrowReady(object sender, EventArgs e)
{
    weaponVis.OwnerRequestSet(rifleRight: false, rifleLeft: true, meleeLeft: false, grenade: false);
}

private void EquipRifle()
{
    weaponVis.OwnerRequestSet(rifleRight: true, rifleLeft: false, meleeLeft: false, grenade: false);
}
private void EquipMelee()
{
    weaponVis.OwnerRequestSet(rifleRight: true, rifleLeft: false, meleeLeft: true, grenade: false);
}
private void EquipGranade()
{
    weaponVis.OwnerRequestSet(rifleRight: false, rifleLeft: true, meleeLeft: false, grenade: true);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitAnimatorEventRelay.cs

```
using UnityEngine;

/// <summary>
/// This is needed so that animation event-bound functions in UnitAnimator can be used. Such as AE_Throw Grenade Stand Release()
/// </summary>
public class AnimationEventRelay : MonoBehaviour
{
    [SerializeField] private UnitAnimator unitAnimator;

    void Awake()
    {
        // Etsi parentista jos ei asetettu Inspectorissa
        if (!unitAnimator) unitAnimator = GetComponentInParent<UnitAnimator>();
    }

    // Täsmälleen sama nimi kuin Animation Eventin Function-kentässä
    public void AE_ThrowGrenadeStandRelease()
    {
        unitAnimator?.AE_ThrowGrenadeStandRelease();
    }

    public void AE_PickGrenadeStand()
    {
        unitAnimator?.AE_PickGrenadeStand();
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitArchetypes/UnitArchetype.cs

```
using UnityEngine;

[CreateAssetMenu(menuName = "RogueShooter/UnitArchetype")]
public class UnitArchetype : ScriptableObject
{
    [Header("BASE SKILLS")]
    [Space(10)]
    [Header("Covering Skill")]
    public int personalCoverMax = 200;
    public int coverRegenOnMove = 1;
    public int coverRegenPerUnusedAP = 25;
    public int lowCoverPenalty = 12; // -12% osumatodennäköisyys
    public int highCoverPenalty = 25; // -25%

    [Space(10)]
    [Header("Shooting Skill")]
    public int basicShootinSkill = 69;
    public int shootingSkillLevel = 0; // 0..10
    public int accuracyBonusPerSkillLevel = 3; // +3% tarkkuutta / taso

    [Space(10)]
    [Header("Grenade Skill")]
    public int grenadeCapacity = 2;
    public int throwingRange = 7;

    [Header("Progression (optional)")]
    public AnimationCurve coverMaxByLevel = AnimationCurve.Linear(1, 200, 10, 300);
    public AnimationCurve regenByLevel = AnimationCurve.Linear(1, 20, 10, 35);
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitArchetypes/UnitSkills.cs

```
[System.Serializable]
public class UnitSkills
{
    public int personalCoverMax = 200;
    public int CoverRegenOnMove = 20;
    public float coverMitigationMultiplier = 1f; // varalle jatsoon (+% vaimennukseen)
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitManager.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;

/// <summary>
/// This class is responsible for managing all units in the game.
/// It keeps track of all units, friendly units, and enemy units.
/// It listens to unit spawn and death events to update its lists accordingly.
/// Note: This class Script Script Execution Order is set to be executed after UnitActionSystem.cs. High priority.
/// </summary>
public class UnitManager : MonoBehaviour
{
    public static UnitManager Instance { get; private set; }
    private List<Unit> unitList;
    private List<Unit> friendlyUnitList;
    private List<Unit> enemyUnitList;

    private readonly HashSet<Unit> unitSet = new();

    private void Awake()
    {
        if (Instance != null)
        {
            Debug.LogError("There's more than one UnitManager! " + transform + " - " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;

        unitList = new List<Unit>();
        friendlyUnitList = new List<Unit>();
        enemyUnitList = new List<Unit>();
    }

    void OnEnable()
    {
        Unit.OnAnyUnitSpawned += Unit_OnAnyUnitSpawned;
        Unit.OnAnyUnitDead += Unit_OnAnyUnitDead;
    }

    void OnDisable()
    {
        Unit.OnAnyUnitSpawned -= Unit_OnAnyUnitSpawned;
        Unit.OnAnyUnitDead -= Unit_OnAnyUnitDead;
    }

    private void Unit_OnAnyUnitSpawned(object sender, EventArgs e)
    {
        /*
```

RogueShooter – All Scripts

```
Unit unit = sender as Unit;
unitList.Add(unit);
*/
// 1) Estä duplikaatit
Unit unit = sender as Unit;
if (!unitSet.Add(unit)) return;
if (!unitList.Contains(unit)) unitList.Add(unit);

if (GameManager.SelectedMode == GameMode.SinglePlayer || GameManager.SelectedMode == GameMode.CoOp)
{
    /*
    if (unit.IsEnemy())
    {
        enemyUnitList.Add(unit);
        unit.Team = Team.Enemy;
    }
    else
    {
        friendlyUnitList.Add(unit);
        unit.Team = Team.Player;
    }
    */

    if (unit.IsEnemy())
    {
        if (!enemyUnitList.Contains(unit)) enemyUnitList.Add(unit);
        unit.Team = Team.Enemy;
    }
    else
    {
        if (!friendlyUnitList.Contains(unit)) friendlyUnitList.Add(unit);
        unit.Team = Team.Player;
    }
}

if (GameManager.SelectedMode == GameMode.Versus)
{
    if(NetworkSync.IsOwnerHost(unit.OwnerId))
    {
        friendlyUnitList.Add(unit);
        unit.Team = Team.Player;
    } else
    {
        enemyUnitList.Add(unit);
        unit.Team = Team.Enemy;
    }
}
}

private void Unit_OnAnyUnitDead(object sender, EventArgs e)
{
```

RogueShooter – All Scripts

```
Unit unit = sender as Unit;
// unitList.Remove(unit);
unitSet.Remove(unit);

// Poista kaikki esiintymät JA siivoa nullit samalla
unitList.RemoveAll(u => u == null || u == unit);
friendlyUnitList.RemoveAll(u => u == null || u == unit);
enemyUnitList.RemoveAll(u => u == null || u == unit);
/*
if (GameManager.SelectedMode == GameMode.SinglePlayer || GameManager.SelectedMode == GameMode.CoOp)
{
    if (unit.IsEnemy())
    {
        enemyUnitList.Remove(unit);
    }
    else
    {
        friendlyUnitList.Remove(unit);
    }
}
if (GameManager.SelectedMode == GameMode.Versus)
{
    if (NetworkSync.IsOwnerHost(unit.OwnerId))
    {
        friendlyUnitList.Remove(unit);
    }
    else
    {
        enemyUnitList.Remove(unit);
    }
}
*/
}

// Yksinkertainen "puhdas" read-API
public IReadOnlyList<Unit> GetEnemyUnitList()
{
    enemyUnitList.RemoveAll(u => u == null);
    return enemyUnitList;
}

public List<Unit> GetUnitList()
{
    return unitList;
}

public List<Unit> GetFriendlyUnitList()
{
    return friendlyUnitList;
}
```

RogueShooter – All Scripts

```
    /*  
    public List<Unit> GetEnemyUnitList()  
    {  
        return enemyUnitList;  
    }  
    */  
  
    public void ClearAllUnitLists()  
    {  
        unitList.Clear();  
        friendlyUnitList.Clear();  
        enemyUnitList.Clear();  
    }  
}
```


RogueShooter – All Scripts

Assets/scripts/Units/UnitPathFinding/PathFinding.cs

```
using System.Collections.Generic;
using UnityEngine;

/// @file PathFinding.cs
/// @brief Core pathfinding system for RogueShooter.
///
/// This component implements the game's grid-based navigation logic using a custom A* algorithm
/// with full support for multi-floor environments, movement budgets, and edge-based wall detection.
///
/// ### Overview
/// The pathfinding system converts Unity scene geometry into an abstract tactical grid used
/// by both player and AI units. Each cell is represented by a `PathNode` containing walkability,
/// cost, and edge-wall information. The system supports 8-directional movement (N, NE, E, SE, S, SW, W, NW)
/// and dynamically links multiple floors through designer-placed `PathfindingLink` components.
///
/// ### System integration
/// - **LevelGrid** - Defines grid dimensions and provides world-to-grid coordinate conversions.
/// - **EdgeBaker** - Scans scene colliders to detect thin obstacles between cells and marks walls accordingly.
/// - **PathFinding** - Performs A* searches using the processed node and edge data.
///
/// ### Key features
/// - Fully deterministic and allocation-free per search (generation-ID based node reuse).
/// - Accurate obstacle handling using edge blockers (no corner clipping or one-way walls).
/// - Move-budget based path truncation for tactical range queries and AI planning.
/// - Extensible multi-floor connectivity via `PathfindingLink` objects.
/// - Optional runtime diagnostics through `PathfindingDiagnostics` (profiling search times and expansions).
///
/// ### Why this exists in RogueShooter
/// - The game's tactical, turn-based design requires predictable and grid-aligned movement.
/// - Unity's built-in NavMesh system is unsuitable for deterministic tile-based combat logic.
/// - Custom A* implementation allows tight integration with game-specific mechanics such as
///   cover, destructible walls, and limited-range actions.
///
/// In summary, this file defines the core pathfinding logic that powers all unit movement
/// and AI navigation in RogueShooter, ensuring consistency between physical scene geometry
/// and tactical gameplay rules.

/// <summary>
/// Grid-based A* pathfinding for 8-directional movement (N, NE, E, SE, S, SW, W, NW) across multiple floors.
///
/// What it does:
/// - Builds and queries a per-floor grid of PathNodes and computes shortest paths using A* with an octile heuristic.
/// - Respects fine-grained edge blockers (walls/rails/doorframes) baked by <see cref="EdgeBaker"/> so units can't
///   cut corners or move/shoot through narrow obstacles.
/// - Supports optional move budgets (in "steps") for tactical range queries and AI decisions.
/// - Supports explicit inter-cell "links" (stairs/elevators/hatches) that connect arbitrary cells and floors.
///
/// Why this exists in RogueShooter:
/// - The game is turn-based and tile-based; we need deterministic, frame-stable paths that match tactical rules,
///   not freeform NavMesh paths.
```

RogueShooter – All Scripts

```
/// - Edge-aware movement prevents diagonal corner-cutting and enforces cover/door behavior consistent with combat.
/// - Budgeted pathfinding enables fast “reachable area” calculations for UI previews and AI planning.
///
/// Design notes:
/// - Uses a lightweight custom PriorityQueue and generation IDs to avoid per-search allocations and stale scores.
/// - Movement costs: straight = 10, diagonal = 20 (octile distance for heuristic and step costs).
/// - Runs after <see cref="LevelGrid"/> initialization; floor walkability is raycasted once, edges baked next,
///   then A* queries can safely rely on up-to-date node/edge data.
/// - Optional debug visualizations can create grid debug objects for inspection in the editor.
/// </summary>
public class PathFinding : MonoBehaviour
{
    public static PathFinding Instance { get; private set; }

    private const int MOVE_STRAIGHT_COST = 10;
    private const int MOVE_DIAGONAL_COST = 14;

    [Header("Debug")]
    [SerializeField] private bool showDebug = false;
    [SerializeField] private Transform gridDebugPrefab;

    [Header("Layers")]
    [SerializeField] private LayerMask obstaclesLayerMask;
    [SerializeField] private LayerMask floorLayerMask;

    [Header("Links")]
    [SerializeField] private Transform pathfindingLinkContainer;

    private int width;
    private int height;
    private int currentGenerationID = 0;

    private List<GridSystem<PathNode>> gridSystemList;
    private List<PathfindingLink> pathfindingLinkList;

    private void Awake()
    {
        if (Instance != null)
        {
            Debug.LogError("PathFinding: More than one PathFinding in the scene! " + transform + " - " + Instance);
            Destroy(gameObject);
            return;
        }
        Instance = this;
    }

    /// <summary>
    /// Initializes the pathfinding system and builds all per-floor grid data.
    ///
    /// What it does:
    /// - Creates a <see cref="GridSystem{PathNode}"/> for each floor with the given dimensions.
    /// - Performs raycast-based walkability detection for every grid cell using floor and obstacle layers.
```

RogueShooter – All Scripts

```
/// - Invokes <see cref="EdgeBaker"/> to detect thin edge blockers between walkable cells.
/// - Collects any explicit <see cref="PathfindingLink"/> connections (stairs, elevators, etc.) from the scene.
///
/// Why this exists in RogueShooter:
/// - Converts the 3D scene geometry into a grid-based navigation map used by all AI and tactical systems.
/// - Ensures that units move on valid walkable surfaces and respect real physical barriers.
/// - Keeps the runtime logic deterministic and self-contained without relying on Unity's NavMesh.
///
/// Implementation notes:
/// - Should be called once during level initialization (by LevelGrid or GameManager).
/// - Automatically performs full edge baking after walkability setup.
/// - Uses layer masks for flexibility: <c>floorLayerMask</c> defines valid surfaces, <c>obstaclesLayerMask</c> blocks them.
/// </summary>
public void Setup(int width, int height, float cellSize, int floorAmount)
{
    this.width = width;
    this.height = height;

    gridSystemList = new List<GridSystem<PathNode>>();

    // 1) Create one grid per floor
    for (int floor = 0; floor < floorAmount; floor++)
    {
        GridSystem<PathNode> gridSystem = new GridSystem<PathNode>(
            width, height, cellSize, floor, LevelGrid.FLOOR_HEIGHT,
            (GridSystem<PathNode> g, GridPosition gridPosition) => new PathNode(gridPosition)
        );

        // Optional: visualize grid in editor for debugging
        if (showDebug && gridDebugPrefab != null)
        {
            gridSystem.CreateDebugObjects(gridDebugPrefab);
        }

        gridSystemList.Add(gridSystem);
    }

    // 2) Raycast: determine which cells are walkable or blocked
    float raycastOffsetDistance = 1f;
    float raycastDistance = raycastOffsetDistance * 2f;

    for (int x = 0; x < width; x++)
    {
        for (int z = 0; z < height; z++)
        {
            for (int floor = 0; floor < floorAmount; floor++)
            {
                GridPosition gridPosition = new GridPosition(x, z, floor);
                Vector3 worldPosition = LevelGrid.Instance.GetWorldPosition(gridPosition);

                // Default to non-walkable
                GetNode(x, z, floor).SetIsWalkable(false);
            }
        }
    }
}
```

RogueShooter – All Scripts

```
// Downward ray: detect if a valid floor exists under this cell
if (Physics.Raycast(
    worldPosition + Vector3.up * raycastOffsetDistance,
    Vector3.down,
    raycastDistance,
    floorLayerMask))
{
    GetNode(x, z, floor).SetIsWalkable(true);
}

// Upward ray: short check for obstacles blocking this space
if (Physics.Raycast(
    worldPosition + Vector3.down * raycastOffsetDistance,
    Vector3.up,
    raycastDistance,
    obstaclesLayerMask))
{
    GetNode(x, z, floor).SetIsWalkable(false);
}
}

// 3) Bake edges between cells (walls, rails, etc.)
EdgeBaker.Instance.BakeAllEdges();

// 4) Gather explicit pathfinding links (stairs, lifts, portals)
pathfindingLinkList = new List<PathfindingLink>();
if (pathfindingLinkContainer != null)
{
    foreach (Transform linkTf in pathfindingLinkContainer)
    {
        if (linkTf.TryGetComponent(out PathfindingLinkMonoBehaviour linkMb))
        {
            pathfindingLinkList.Add(linkMb.GetPathfindingLink());
        }
    }
} else
{
    // Muuten etsi kaikki scenestä
    var allLinkMbs = FindObjectsByType<PathfindingLinkMonoBehaviour>(FindObjectsSortMode.None);
    if (allLinkMbs == null)
    {
        Debug.LogWarning("[PF] No PathfindingLinkMonoBehaviour found in scene");
        return;
    }

    foreach (var linkMb in allLinkMbs)
    {

```

RogueShooter – All Scripts

```
        pathfindingLinkList.Add(linkMb.GetPathfindingLink());
    }
}

}

/// <summary>
/// Finds a path between two grid positions using the A* algorithm with an optional move budget.
///
/// What it does:
/// - Serves as the public entry point for pathfinding queries.
/// - Wraps the internal implementation (<see cref="FindPathInternal"/>) while exposing a simpler interface.
/// - Returns a list of grid positions representing the optimal route, or <c>null</c> if no valid path exists.
///
/// Why this exists in RogueShooter:
/// - Gameplay systems (player input, AI, ability targeting) request paths through this single method.
/// - The move budget allows computing reachable tiles for tactical range previews (e.g. 6 steps max).
///
/// Implementation notes:
/// - <paramref name="moveBudgetSteps"/> can be set to <c>int.MaxValue</c> for unrestricted pathfinding.
/// - Outputs <paramref name="pathLength"/> as total F-cost (movement cost + heuristic) of the found path.
/// </summary>
public List<GridPosition> FindPath(
    GridPosition startGridPosition,
    GridPosition endGridPosition,
    out int pathLength,
    int moveBudgetSteps)
{
    return FindPathInternal(startGridPosition, endGridPosition, out pathLength, moveBudgetSteps);
}

/// <summary>
/// Core A* pathfinding algorithm implementation with movement budget and edge-aware navigation.
///
/// What it does:
/// - Expands nodes using standard A* logic (G = actual cost, H = heuristic, F = G + H).
/// - Honors per-edge blockers from <see cref="EdgeBaker"/> via <c>CanStep()</c>.
/// - Supports a movement budget (in "steps") to limit search range for tactical actions.
/// - Uses a lightweight custom <see cref="PriorityQueue{T}"/> for open list management.
///
/// Why this exists in RogueShooter:
/// - Provides deterministic and efficient tactical pathfinding across destructible, multi-floor maps.
/// - Integrates movement range rules directly into path expansion, avoiding separate "reachable area" passes.
/// - Enables AI and player systems to share the same consistent grid and cost rules.
///
/// Algorithm overview:
/// 1. Convert <paramref name="moveBudgetSteps"/> into internal cost units (straight = 10, diagonal = 20).
/// 2. Early reject if even the heuristic distance exceeds the available budget.
/// 3. Initialize open and closed sets and enqueue the start node.
/// 4. While the open queue is not empty:
///     - Dequeue the node with the lowest F-cost.
```

RogueShooter – All Scripts

```
/// - If its G-cost exceeds the movement budget → skip.
/// - If this is the end node → reconstruct the path and return.
/// - Otherwise, expand all valid neighbors that are walkable and not blocked by edges.
/// 5. Return <c>null</c> if no path exists within the allowed movement cost.
///
/// Performance notes:
/// - Avoids heap allocations via <see cref="EnsureInit"/> using generation IDs.
/// - Supports optional runtime diagnostics through <see cref="PathfindingDiagnostics"/> (#if PERFORMANCE_DIAG).
/// - Handles diagonal movement correctly with octile distances and no corner clipping.
/// </summary>
private List<GridPosition> FindPathInternal(
    GridPosition startGridPosition,
    GridPosition endGridPosition,
    out int pathLeght,
    int moveBudgetSteps)
{
#if PERFORMANCE_DIAG

    var diag = PathfindingDiagnostics.Instance;
    bool diagOn = diag != null && diag.enabledRuntime;

    System.Diagnostics.Stopwatch sw = null;
    if (diagOn) { sw = new System.Diagnostics.Stopwatch(); sw.Start(); }

    int expanded = 0; // kuinka monta solmua laajennettiin (pop + käsitelty)

#endif
    // 1) Convert step-based budget to internal movement cost units
    int moveBudgetCost = (moveBudgetSteps == int.MaxValue)
        ? int.MaxValue
        : moveBudgetSteps * MOVE_STRAIGHT_COST;

    // Early pruning: skip search if even the heuristic distance exceeds the move budget
    int minPossibleCost = CalculateDistance(startGridPosition, endGridPosition);
    if (minPossibleCost > moveBudgetCost)
    {
        pathLeght = 0;
    }

#if PERFORMANCE_DIAG

    if (diagOn) { sw.Stop(); diag.AddSample(sw.Elapsed.TotalMilliseconds, false, 0, expanded); }

#endif

    return null;
}

currentGenerationID++;

var openQueue = new PriorityQueue<PathNode>();
HashSet<PathNode> openSet = new HashSet<PathNode>();
```

RogueShooter – All Scripts

```
HashSet<PathNode> closedSet = new HashSet<PathNode>();

PathNode startNode = GetGridSystem(startGridPosition.floor).GetGridObject(startGridPosition);
PathNode endNode = GetGridSystem(endGridPosition.floor).GetGridObject(endGridPosition);

// Initialize start node
EnsureInit(startNode);
startNode.SetGCost(0);
startNode.SetHCost(CalculateDistance(startGridPosition, endGridPosition));
startNode.CalculateFCost();

openQueue.Enqueue(startNode, startNode.GetFCost());
openSet.Add(startNode);

// 2) Main A* loop
while (openQueue.Count > 0)
{
    // Dequeue the node with the lowest F-cost; skip outdated entries
    PathNode currentNode = openQueue.Dequeue();
    if (closedSet.Contains(currentNode)) continue;

    EnsureInit(currentNode);

#if PERFORMANCE_DIAG
    expanded++;
#endif

    // Stop expanding if the current path already exceeds move budget
    if (currentNode.GetGCost() > moveBudgetCost)
        continue;

    // Goal reached → build final path
    if (currentNode == endNode)
    {
        pathLeght = endNode.GetFCost();
        var path = CalculatePath(endNode);

#if PERFORMANCE_DIAG
        if (diagOn)
        {
            sw.Stop();
            diag.AddSample(sw.Elapsed.TotalMilliseconds, success: true, pathLen: path.Count, expanded: expanded);
        }
#endif
        return path;
    }

    openSet.Remove(currentNode);
    closedSet.Add(currentNode);

    // 3) Expand all valid neighbor nodes
    foreach (PathNode neighbourNode in GetNeighbourList(currentNode))
```

RogueShooter – All Scripts

```
{
    if (closedSet.Contains(neighbourNode)) continue;

    if (!neighbourNode.GetIsWalkable())
    {
        closedSet.Add(neighbourNode);
        continue;
    }

    EnsureInit(neighbourNode);

    int stepCost = CalculateDistance(currentNode.GetGridPosition(), neighbourNode.GetGridPosition());
    int tentativeG = currentNode.GetGCost() + stepCost;

    // Skip paths that already exceed movement budget
    if (tentativeG > moveBudgetCost)
        continue;

    // If this route to the neighbor is cheaper, record it
    if (tentativeG < neighbourNode.GetGCost())
    {
        neighbourNode.SetCameFromPathNode(currentNode);
        neighbourNode.SetGCost(tentativeG);
        neighbourNode.SetHCost(CalculateDistance(neighbourNode.GetGridPosition(), endGridPosition));
        neighbourNode.CalculateFCost();

        if (!openSet.Contains(neighbourNode))
        {
            openQueue.Enqueue(neighbourNode, neighbourNode.GetFCost());
            openSet.Add(neighbourNode);
        }
        else
        {
            // No decrease-key in PriorityQueue → push duplicate, old entry ignored when dequeued
            openQueue.Enqueue(neighbourNode, neighbourNode.GetFCost());
        }
    }
}

// 4) No valid path within move budget
pathLeght = 0;

#if PERFORMANCE_DIAG
if (diagOn)
{
    sw.Stop();
    diag.AddSample(sw.Elapsed.TotalMilliseconds, success: false, pathLen: 0, expanded: expanded);
}
```


RogueShooter – All Scripts

```
#endif
    return null;
}

/// <summary>
/// Octile-distance cost between two grid positions for 8-directional movement.
///
/// What it does:
/// - Computes the admissible A* heuristic and unit step costs using:
///   diagonal = min(|dx|, |dz|), straight = | |dx| - |dz| |.
/// - Returns MOVE_DIAGONAL_COST * diagonal + MOVE_STRAIGHT_COST * straight.
///
/// Why this exists in RogueShooter:
/// - Matches our movement rules exactly (orthogonal and diagonal with different costs),
///   keeping A* both admissible and consistent (no overestimation).
///
/// Implementation notes:
/// - MOVE_STRAIGHT_COST = 10, MOVE_DIAGONAL_COST = 20 to align with budget-in-steps logic.
/// </summary>
public int CalculateDistance(GridPosition a, GridPosition b)
{
    GridPosition d = a - b;
    int xDistance = Mathf.Abs(d.x);
    int zDistance = Mathf.Abs(d.z);
    int diagonal = Mathf.Min(xDistance, zDistance);
    int straight = Mathf.Abs(xDistance - zDistance);
    return MOVE_DIAGONAL_COST * diagonal + MOVE_STRAIGHT_COST * straight;
}

/// <summary>
/// Retrieves the grid system instance for a given floor index.
///
/// What it does:
/// - Returns the <see cref="GridSystem{PathNode}" /> corresponding to the specified floor.
///
/// Why this exists in RogueShooter:
/// - Supports multi-floor pathfinding where each floor maintains its own grid structure.
/// - Allows systems to query and operate on nodes per-floor without global lookups.
///
/// Implementation notes:
/// - Assumes grids were created during <see cref="Setup" /> and stored in <c>gridSystemList</c>.
/// </summary>
private GridSystem<PathNode> GetGridSystem(int floor) => gridSystemList[floor];

/// <summary>
/// Retrieves a single pathfinding node at the given (x, z, floor) position.
///
/// What it does:
/// - Resolves to the correct grid system (via <see cref="GetGridSystem" />) and returns its node.
///
/// Why this exists in RogueShooter:
/// - Simplifies code that frequently needs to access individual nodes by absolute coordinates.
```

RogueShooter – All Scripts

```
/// - Used heavily in A*, edge baking, and AI systems for node-level data manipulation.
///
/// Implementation notes:
/// - Returns <null> if the grid system or node does not exist (should not normally happen after Setup()).
/// </summary>
public PathNode GetNode(int x, int z, int floor)
    => GetGridSystem(floor).GetGridObject(new GridPosition(x, z, floor));

/// <summary>
/// Converts a unit orthogonal delta (dx, dz) into an EdgeMask direction.
///
/// What it does:
/// - Maps (0,+1)→N, (+1,0)→E, (0,-1)→S, (-1,0)→W.
/// - Returns <see cref="EdgeMask.None"/> for non-orthogonal deltas.
///
/// Why this exists in RogueShooter:
/// - Used by <see cref="CanStep"/> to check per-edge walls symmetrically for orthogonal moves.
/// - Keeps edge checks readable and centralized.
///
/// Implementation notes:
/// - Diagonal deltas are intentionally not mapped (handled separately in <see cref="CanStep"/>).
/// </summary>
private EdgeMask DirFromDelta(int dx, int dz)
{
    if (dx == 0 && dz == +1) return EdgeMask.N;
    if (dx == +1 && dz == 0) return EdgeMask.E;
    if (dx == 0 && dz == -1) return EdgeMask.S;
    if (dx == -1 && dz == 0) return EdgeMask.W;
    return EdgeMask.None;
}

/// <summary>
/// Returns the opposite edge direction (N↔S, E↔W).
///
/// What it does:
/// - Maps a cardinal edge to its opposite; otherwise returns <see cref="EdgeMask.None"/>.
///
/// Why this exists in RogueShooter:
/// - Ensures symmetric edge checks (A's east equals B's west) in movement validation.
/// - Avoids "one-way walls" by enforcing consistency across neighboring nodes.
/// </summary>
private EdgeMask Opposite(EdgeMask d) => d switch
{
    EdgeMask.N => EdgeMask.S,
    EdgeMask.E => EdgeMask.W,
    EdgeMask.S => EdgeMask.N,
    EdgeMask.W => EdgeMask.E,
    _ => EdgeMask.None
};

/// <summary>
/// Determines whether movement from cell A to cell B is allowed,
```

RogueShooter – All Scripts

```
/// honoring edge walls and preventing diagonal corner-cutting.
///
/// What it does:
/// - Validates that the delta is a single orthogonal or diagonal step.
/// - For orthogonal moves: blocks movement if either side of the shared edge has a wall flag.
/// - For diagonal moves: requires at least one orthogonal “L-shaped” two-step route to be clear
///   (A→X→B or A→Z→B), preventing cutting through blocked corners.
///
/// Why this exists in RogueShooter:
/// - Enforces tactical rules consistent with baked edge data (from EdgeBaker).
/// - Prevents unrealistic diagonal slips past doorframes/rails and yields robust cover behavior.
///
/// Implementation notes:
/// - Uses <see cref="DirFromDelta"/> and <see cref="Opposite(EdgeMask)"/> to test symmetric edge walls.
/// - For diagonals, both intermediate orthogonal neighbors must be valid and walkable before testing paths.
/// </summary>
private bool CanStep(GridPosition a, GridPosition b)
{
    int dx = b.x - a.x;
    int dz = b.z - a.z;

    bool diagonal = Mathf.Abs(dx) == 1 && Mathf.Abs(dz) == 1;
    bool ortho = (dx == 0) ^ (dz == 0);
    if (!diagonal && !ortho) return false; // Disallow jumps longer than 1 cell

    var nodeA = GetNode(a.x, a.z, a.floor);
    var nodeB = GetNode(b.x, b.z, b.floor);

    // ORTHOGONAL MOVE: both sides of the shared edge must be open
    if (ortho)
    {
        var dir = DirFromDelta(dx, dz);
        if (dir == EdgeMask.None) return false;
        if (nodeA.HasWall(dir)) return false; // wall on A's side
        if (nodeB.HasWall(Opposite(dir))) return false; // wall on B's side
        return true;
    }

    // DIAGONAL MOVE: require at least one clear L-route (no corner clipping)
    var aToX = new GridPosition(a.x + dx, a.z, a.floor);
    var aToZ = new GridPosition(a.x, a.z + dz, a.floor);

    // Both intermediates must be inside bounds and walkable to be considered
    if (!IsValidGridPosition(aToX) || !IsValidGridPosition(aToZ)) return false;
    if (!IsWalkable(aToX) || !IsWalkable(aToZ)) return false;

    // Route 1: A -> X -> B (two orthogonal steps)
    bool pathViaX = CanStep(a, aToX) && CanStep(aToX, b);

    // Route 2: A -> Z -> B (two orthogonal steps)
    bool pathViaZ = CanStep(a, aToZ) && CanStep(aToZ, b);
```

RogueShooter – All Scripts

```
        return pathViaX || pathViaZ;
    }

    private bool IsValidGridPosition(GridPosition gridPosition)
    {
        return LevelGrid.Instance.GetGridSystem(gridPosition.floor).IsValidGridPosition(gridPosition);
    }

    public bool IsWalkable(GridPosition gridPosition)
    {
        PathNode node = GetNode(gridPosition.x, gridPosition.z, gridPosition.floor);
        return node != null && node.GetIsWalkable();
    }

    /// <summary>
    /// Collects all valid neighbor nodes (up to 8) for A* expansion from the given node.
    ///
    /// What it does:
    /// - Iterates orthogonal and diagonal neighbors within the current floor bounds.
    /// - Filters out non-walkable cells early.
    /// - Uses <see cref="CanStep"/> to enforce edge walls and anti-corner-cutting rules.
    /// - Additionally appends any explicit link targets (e.g., stairs/elevators) connected to this cell.
    ///
    /// Why this exists in RogueShooter:
    /// - Centralizes movement rules so both AI and player pathfinding share identical constraints.
    /// - Supports multi-floor traversal via designer-authored links without special-casing A*.
    ///
    /// Implementation notes:
    /// - Neighbor order is stable to keep behavior deterministic across runs.
    /// - Links bypass edge checks by design (they represent explicit allowed transitions).
    /// </summary>
    private List<PathNode> GetNeighbourList(PathNode currentNode)
    {
        List<PathNode> result = new List<PathNode>(8);

        GridPosition gp = currentNode.GetGridPosition();

        // Candidate offsets (W, SW, NW, E, SE, NE, S, N)
        static IEnumerable<(int dx, int dz)> Offsets()
        {
            yield return (-1, 0); // W
            yield return (-1, -1); // SW
            yield return (-1, +1); // NW

            yield return (+1, 0); // E
            yield return (+1, -1); // SE
            yield return (+1, +1); // NE

            yield return (0, -1); // S
            yield return (0, +1); // N
        }
    }
```

RogueShooter – All Scripts

```
}

// 1) Same-floor neighbors with edge rules
foreach (var (dx, dz) in Offsets())
{
    int nx = gp.x + dx;
    int nz = gp.z + dz;

    // Bounds check
    if (nx < 0 || nz < 0 || nx >= width || nz >= height) continue;

    var ngp = new GridPosition(nx, nz, gp.floor);

    // Early reject: must be walkable
    if (!IsWalkable(ngp)) continue;

    // Respect edge blockers and corner rules
    if (!CanStep(gp, ngp)) continue;

    result.Add(GetNode(nx, nz, gp.floor));
}

// 2) Explicit links (stairs/lifts/portals) – allowed transitions across floors
foreach (GridPosition linkGp in GetPathfindingLinkConnectedGridPositionList(gp))
{
    // Varmista ettei mennä ulos
    if (!IsValidGridPosition(linkGp)) continue;
    if (!IsWalkable(linkGp)) continue;

    // Links intentionally bypass edge checks; they model designer-approved moves
    result.Add(GetNode(linkGp.x, linkGp.z, linkGp.floor));
}

return result;
}

/// <summary>
/// Returns all grid positions directly connected to the given position via explicit pathfinding links.
///
/// What it does:
/// - Searches the prebuilt <see cref="pathfindingLinkList"/> for connections where the given cell
///   is either endpoint (A or B).
/// - Collects and returns the corresponding linked destinations.
///
/// Why this exists in RogueShooter:
/// - Enables multi-floor traversal and special transitions (stairs, elevators, hatches, ladders, etc.)
///   that bypass standard neighbor logic.
/// - Keeps such transitions data-driven: designers place <see cref="PathfindingLinkMonoBehaviour"/> objects
///   in the scene instead of hardcoding connections.
///
/// Implementation notes:
/// - Links are treated as bidirectional: A↔B.
```

RogueShooter – All Scripts

```
/// - The returned positions are later validated for walkability before use.
/// </summary>
private List<GridPosition> GetPathfindingLinkConnectedGridPositionList(GridPosition gridPosition)
{
    List<GridPosition> result = new List<GridPosition>();
    if (pathfindingLinkList == null || pathfindingLinkList.Count == 0) return result;

    foreach (PathfindingLink link in pathfindingLinkList)
    {
        if (link.gridPositionA == gridPosition) result.Add(link.gridPositionB);
        if (link.gridPositionB == gridPosition) result.Add(link.gridPositionA);
    }
    return result;
}

/// <summary>
/// Reconstructs a complete path from the end node by backtracking through parent pointers.
///
/// What it does:
/// - Traces the <c>CameFrom</c> chain from the goal node back to the start.
/// - Reverses the collected list and converts it into grid positions for gameplay use.
///
/// Why this exists in RogueShooter:
/// - Converts A*'s internal node traversal history into a usable list of <see cref="GridPosition"/> steps.
/// - Provides a deterministic, minimal path sequence for units to follow.
///
/// Implementation notes:
/// - Result always includes both the start and end positions.
/// - Returned list is ordered from start → goal.
/// </summary>
private List<GridPosition> CalculatePath(PathNode endNode)
{
    List<PathNode> pathNodes = new List<PathNode> { endNode };
    PathNode current = endNode;

    while (current.GetCameFromPathNode() != null)
    {
        pathNodes.Add(current.GetCameFromPathNode());
        current = current.GetCameFromPathNode();
    }

    pathNodes.Reverse();

    List<GridPosition> gridPositions = new List<GridPosition>(pathNodes.Count);
    foreach (PathNode n in pathNodes) gridPositions.Add(n.GetGridPosition());

    return gridPositions;
}

/// <summary>
/// Returns whether the given grid position is currently walkable.
///
```

RogueShooter – All Scripts

```
/// Why this exists in RogueShooter:
/// - Unified query for gameplay/AI to check if a tile can be occupied.
/// - Mirrors the internal node flag computed during Setup() (raycasts + edge bake).
/// </summary>
public bool IsWalkableGridPosition(GridPosition gridPosition)
    => GetGridSystem(gridPosition.floor).GetGridObject(gridPosition).GetIsWalkable();

/// <summary>
/// Sets the walkability of a grid position at runtime.
///
/// Why this exists in RogueShooter:
/// - Dynamic gameplay (e.g., collapses, placed barricades, hazards) can toggle occupancy rules.
/// - Lets designers/systems override the initial raycast result if needed.
///
/// Implementation notes:
/// - Consider calling <see cref="EdgeBaker.RebakeEdgesAround"/> if geometry changes near this tile.
/// </summary>
/*
public void SetIsWalkableGridPosition(GridPosition gridPosition, bool isWalkable)
    => GetGridSystem(gridPosition.floor).GetGridObject(gridPosition).SetIsWalkable(isWalkable);
*/
public void SetIsWalkableGridPosition(GridPosition gridPosition, bool isWalkable)
{
    if (LevelGrid.Instance == null) { Debug.LogWarning("[PF] SetIsWalkable before LevelGrid"); return; }
    if (!LevelGrid.Instance.IsValidGridPosition(gridPosition))
    {
        Debug.LogWarning($"[PF] Ignore SetIsWalkable for OUT-OF-BOUNDS {gridPosition}");
        return;
    }

    GetGridSystem(gridPosition.floor).GetGridObject(gridPosition).SetIsWalkable(isWalkable);
}
/// <summary>
/// Lazily resets per-search A* fields on a node using a generation ID guard.
///
/// What it does:
/// - If the node was last touched in a previous search (generation mismatch),
///   resets G/H/F, clears the “came from” pointer, and marks the node with the current generation.
///
/// Why this exists in RogueShooter:
/// - Avoids per-search heap allocations and dictionary clears by reusing nodes safely.
/// - Ensures stale scores from earlier searches never leak into the current query.
///
/// Implementation notes:
/// - Must be called on any node before reading/updating A* fields during a search.
/// </summary>
void EnsureInit(PathNode node)
{
    if (node.LastGenerationID != currentGenerationID)
    {
        node.SetGCost(int.MaxValue);
        node.SetHCost(0);
    }
}
```

RogueShooter – All Scripts

```
        node.CalculateFCost();
        node.ResetCameFromPathNode();
        node.MarkGeneration(currentGenerationID);
    }
}

/// <summary>
/// Converts a movement budget in steps to internal cost units.
///
/// Why this exists in RogueShooter:
/// - Keeps UI/AI logic readable (work in “steps”) while A* uses cost units (10 per orthogonal step).
/// </summary>
public static int CostFromSteps(int steps) => steps * MOVE_STRAIGHT_COST;

/// <summary>
/// Gets all explicit pathfinding links collected from the scene (stairs, elevators, robes).
///
/// Why this exists in RogueShooter:
/// - External systems (UI, debugging, AI) may need to inspect or visualize cross-cell/floor connections.
/// </summary>
public List<PathfindingLink> GetPathfindingLinks()
{
    return pathfindingLinkList ?? new List<PathfindingLink>();
}

public int GetWidth()
{
    return width;
}

public int GetHeight()
{
    return height;
}
}
```


RogueShooter – All Scripts

Assets/scripts/Units/UnitPathFinding/PathfindingLink.cs

```
public class PathfindingLink
{
    public GridPosition gridPositionA;
    public GridPosition gridPositionB;
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitPathFinding/PathfindingLinkMonoBehaviour.cs

```
using UnityEngine;

// Linkit asetetaan tyhjään linkkejä sisältävään game objektiin joka annetaan PathFindig.cs
// Pathfinding etsii yhteydet Editorissa ennakoon annetusta linkki containerista.
public class PathfindingLinkMonoBehaviour : MonoBehaviour
{
    public Vector3 linkPositionA;
    public Vector3 linkPositionB;

    void OnDrawGizmos()
    {
        Gizmos.color = Color.yellow;
        Vector3 aW = transform.TransformPoint(linkPositionA);
        Vector3 bW = transform.TransformPoint(linkPositionB);
        Gizmos.DrawSphere(aW, 0.15f);
        Gizmos.DrawSphere(bW, 0.15f);
        Gizmos.DrawLine(aW, bW);
    }

    public PathfindingLink GetPathfindingLink()
    {
        var aW = transform.TransformPoint(linkPositionA);
        var bW = transform.TransformPoint(linkPositionB);
        return new PathfindingLink
        {
            gridPositionA = LevelGrid.Instance.GetGridPosition(aW),
            gridPositionB = LevelGrid.Instance.GetGridPosition(bW),
        };
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitPathFinding/PathNode.cs

```
[System.Flags]
public enum EdgeMask { None = 0, N = 1, E = 2, S = 4, W = 8 }

[System.Flags]
public enum CoverMask { None = 0, N = 1, E = 2, S = 4, W = 8 }

public class PathNode
{
    private GridPosition gridPosition;
    private int gCost;
    private int hCost;
    private int fCost;
    private PathNode cameFromPathNode;

    private bool isWalkable = true;
    private EdgeMask walls; // ← ruudun reunaesteet

    private CoverMask highCover; // täyskorkea suoja suunnittain
    private CoverMask lowCover; // matala suoja suunnittain

    public void ClearWalls() => walls = EdgeMask.None;
    public void AddWall(EdgeMask dir) => walls |= dir;
    public bool HasWall(EdgeMask dir) => (walls & dir) != 0;

    public void ClearCover() { highCover = CoverMask.None; lowCover = CoverMask.None; }
    public void AddHighCover(CoverMask d) => highCover |= d;
    public void AddLowCover(CoverMask d) => lowCover |= d;
    public bool HasHighCover(CoverMask d) => (highCover & d) != 0;
    public bool HasLowCover(CoverMask d) => (lowCover & d) != 0;

    public CoverMask GetHighCoverMask() => highCover;
    public CoverMask GetLowCoverMask() => lowCover;

    public PathNode(GridPosition gridPosition)
    {
        this.gridPosition = gridPosition;
    }

    public int LastGenerationID { get; private set; } = -1;
    public void MarkGeneration(int generationID) => LastGenerationID = generationID;

    public override string ToString()
    {
        return gridPosition.ToString();
    }

    public int GetGCost()
    {

```

RogueShooter – All Scripts

```
        return gCost;
    }

    public int GetHCost()
    {
        return hCost;
    }

    public int GetFCost()
    {
        return fCost;
    }

    public void SetGCost(int gCost)
    {
        this.gCost = gCost;
    }

    public void SetHCost(int hCost)
    {
        this.hCost = hCost;
    }

    public void CalculateFCost()
    {
        fCost = gCost + hCost;
    }

    public void ResetCameFromPathNode()
    {
        cameFromPathNode = null;
    }

    public void SetCameFromPathNode(PathNode pathNode)
    {
        cameFromPathNode = pathNode;
    }

    public PathNode GetCameFromPathNode()
    {
        return cameFromPathNode;
    }

    public GridPosition GetGridPosition()
    {
        return gridPosition;
    }

    public bool GetIsWalkable()
    {
        return isWalkable;
    }
```

RogueShooter – All Scripts

```
    public void SetIsWalkable(bool isWalkable)
    {
        this.isWalkable = isWalkable;
    }

    public bool IsWalkable()
    {
        return isWalkable;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitRagdoll/RagdollPoseBinder.cs

```
/*
using System.Collections;
using Mirror;
using UnityEngine;

/// <summary>
/// Online: Client need this to get destroyed unit rootbone to create ragdoll form it.
/// </summary>
public class RagdollPoseBinder : NetworkBehaviour
{
    [SyncVar] public uint sourceUnitNetId;
    [SyncVar] public Vector3 lastHitPos;
    [SyncVar] public int overkill;

    [ClientCallback]
    private void Start()
    {
        StartCoroutine(ApplyPoseWhenReady());
    }

    private IEnumerator ApplyPoseWhenReady()
    {
        var (root, why) = TryFindOriginalRootBone(sourceUnitNetId);
        if (root != null)
        {
            if (TryGetComponent<UnitRagdoll>(out var unitRagdoll))
            {
                unitRagdoll.SetOverkill(overkill);
                unitRagdoll.SetLastHitPosition(lastHitPos);
                unitRagdoll.Setup(root);
            }
            yield break;
        }

        Debug.Log($"[Ragdoll] waiting root for netId {sourceUnitNetId} ({why})");

        yield return new WaitForEndOfFrame();
        Debug.LogWarning($"[RagdollPoseBinder] Source root not found for netId {sourceUnitNetId}");
    }

    private static (Transform root, string why) TryFindOriginalRootBone(uint netId)
    {
        if (netId == 0) return (null, "netId==0");
        if (!Mirror.NetworkClient.spawned.TryGetValue(netId, out var id) || id == null)
            return (null, "identity not in NetworkClient.spawned");

        // Löydä UnitRagdollSpawn myös hierarkiasta
        var spawner = id.GetComponent<UnitRagdollSpawn>()
            ?? id.GetComponentInChildren<UnitRagdollSpawn>(true)
    }
}
```

RogueShooter – All Scripts

```
        ?? id.GetComponentInParent<UnitRagdollSpawn>());
    if (spawner == null) return (null, "UnitRagdollSpawn missing under identity");

    if (spawner.OriginalRagdollRootBone == null) return (null, "OriginalRagdollRootBone null");
    return (spawner.OriginalRagdollRootBone, null);
}

}
*/
using Mirror;
using UnityEngine;
using System.Collections;

public class RagdollPoseBinder : NetworkBehaviour
{
    [SyncVar] public uint sourceUnitNetId;
    [SyncVar] public Vector3 lastHitPos;
    [SyncVar] public int overkill;

    [SerializeField] float bindTimeout = 0.75f;    // varalta jos hierarkia/NetID tulee myöhässä

    UnitRagdoll ragdoll;

    void Awake()
    {
        ragdoll = GetComponent<UnitRagdoll>();
    }

    public override void OnStartClient()
    {
        base.OnStartClient();
        StartCoroutine(Co_TryBindUntilFound());
    }

    IEnumerator Co_TryBindUntilFound()
    {
        float t = 0f;
        while (t < bindTimeout)
        {
            Transform rootBone = TryResolveOriginalRootBoneOnClient();
            if (rootBone != null)
            {
                // siirrä metadatat ja sido pose
                if (ragdoll != null)
                {
                    ragdoll.SetOverkill(overkill);
                    ragdoll.SetLastHitPosition(lastHitPos);
                    ragdoll.Setup(rootBone);
                }
                yield break;
            }
        }
    }
}
```

RogueShooter – All Scripts

```
        t += Time.deltaTime;
        yield return null;
    }

    Debug.LogWarning("[RagdollPoseBinder] Failed to bind original root bone in time.");
}

Transform TryResolveOriginalRootBoneOnClient()
{
    if (!NetworkClient.active) return null;
    if (!NetworkClient.spawned.TryGetValue(sourceUnitNetId, out var srcNi) || srcNi == null) return null;

    // Hae kaatuneen unitin spawneri, jossa viite on serialized
    var spawner = srcNi.GetComponentInChildren<UnitRagdollSpawn>(true);
    if (spawner != null && spawner.OriginalRagdollRootBone != null) // (huom. kirjoitusasu)
        return spawner.OriginalRagdollRootBone;

    return null;
}
}
```


RogueShooter – All Scripts

Assets/scripts/Units/UnitRagdoll/UnitRagdoll.cs

```
using System.Collections.Generic;
using UnityEngine;

public class UnitRagdoll : MonoBehaviour
{
    [SerializeField] private Transform ragdollRootBone;

    private Vector3 lastHitPosition;

    private int overkill;

    public Transform Root => ragdollRootBone;

    public void Setup(Transform originalRootBone)
    {
        MatchAllChildTransforms(originalRootBone, ragdollRootBone);
        // Vector3 randomDir = new Vector3(Random.Range(-1f, +1f), 0, Random.Range(-1, +1));
        ApplyPushForceToRagdoll(ragdollRootBone, 500f + overkill, lastHitPosition, 50f);
    }

    /// <summary>
    /// Sets all ragdoll bones to match dying unit bones rotation and position
    /// </summary>
    private static void MatchAllChildTransforms(Transform sourceRoot, Transform targetRoot)
    {
        var stack = new Stack<(Transform sourceBone, Transform targetBone)>();
        stack.Push((sourceRoot, targetRoot));

        while (stack.Count > 0)
        {
            var (currentSourceBone, currentTargetBone) = stack.Pop();

            currentTargetBone.SetPositionAndRotation(currentSourceBone.position, currentSourceBone.rotation);

            if (currentSourceBone.childCount == currentTargetBone.childCount)
            {
                for (int i = 0; i < currentSourceBone.childCount; i++)
                {
                    stack.Push((currentSourceBone.GetChild(i), currentTargetBone.GetChild(i)));
                }
            }
        }
    }

    private void ApplyPushForceToRagdoll(Transform root, float pushForce, Vector3 pushPosition, float PushRange)
    {
        foreach (Transform child in root)
        {
```

RogueShooter – All Scripts

```
        if (child.TryGetComponent<Rigidbody>(out Rigidbody childRigidbody))
        {
            childRigidbody.AddExplosionForce(pushForce, pushPosition, PushRange);
        }

        ApplyPushForceToRagdoll(child, pushForce, pushPosition, PushRange);
    }

    public void SetLastHitPosition(Vector3 hitPosition)
    {
        lastHitPosition = hitPosition;
    }

    public void SetOverkill(int overkill)
    {
        this.overkill = overkill;
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitRagdoll/UnitRagdollSpawn.cs

```
using System;
using UnityEngine;

[RequireComponent(typeof(HealthSystem))]
public class UnitRagdollSpawn : MonoBehaviour
{
    [SerializeField] private Transform ragdollPrefab;
    [SerializeField] private Transform originalRagdollRootBone;
    public Transform OriginalRagdollRootBone => originalRagdollRootBone;

    private HealthSystem healthSystem;

    // To prevent multiple spawns
    private bool spawned;

    private void Awake()
    {
        healthSystem = GetComponent<HealthSystem>();
        healthSystem.OnDead += HealthSystem_OnDied;
    }

    private void OnDisable()
    {
        healthSystem.OnDead -= HealthSystem_OnDied;
    }

    private void HealthSystem_OnDied(object sender, EventArgs e)
    {
        if (spawned) return;
        spawned = true;
        Vector3 lastHitPosition = healthSystem.LastHitPosition;
        int overkill = healthSystem.Overkill;
        var ni = GetComponentInParent<Mirror.NetworkIdentity>();
        uint id = ni ? ni.netId : 0;

        if (NetMode.IsServer)
        {
            NetworkSync.SpawnRagdoll(
                ragdollPrefab.gameObject,
                transform.position,
                transform.rotation,
                id,
                lastHitPosition,
                overkill);
        } else
        {
            OfflineGameSimulator.SpawnRagdoll(
                ragdollPrefab.gameObject,
                transform.position,
```

RogueShooter – All Scripts

```
        transform.rotation,  
        id,  
        originalRagdollRootBone,  
        lastHitPosition,  
        overkill);  
    }  
  
    healthSystem.OnDead -= HealthSystem_OnDied;  
}  
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitsControlUI/TurnSystemUI.cs

```
using System;
using UnityEngine;
using UnityEngine.UI;
using TMPPro;
using Utp;

///<summary>
/// TurnSystemUI manages the turn system user interface.
/// It handles both singleplayer and multiplayer modes.
/// In multiplayer, it interacts with PlayerController to manage turn ending.
/// It also updates UI elements based on the current turn state.
///</summary>
public class TurnSystemUI : MonoBehaviour
{
    [SerializeField] private Button endTurnButton;
    [SerializeField] private TextMeshProUGUI turnNumberText;           // (valinnainen, käytä SP:ssä)
    [SerializeField] private GameObject enemyTurnVisualGameObject;    // (valinnainen, käytä SP:ssä)
    [SerializeField] private TextMeshProUGUI playerReadyText;         // (Online)

    bool isCoop;
    private PlayerController localPlayerController;

    void Start()
    {
        isCoop = GameManager.SelectedMode == GameMode.CoOp;

        // kiinnitä handler tasan kerran
        if (endTurnButton != null)
        {
            endTurnButton.onClick.RemoveAllListeners();
            endTurnButton.onClick.AddListener(OnEndTurnClicked);
        }

        if (isCoop)
        {
            // Co-opissa nappi on DISABLED kunnes serveri kertoo että saa toimia
            TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
            SetCanAct(false);
        }
        else
        {
            // Singleplayerissa kuuntele vuoron vaihtumista
            if (TurnSystem.Instance != null)
            {
                TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
                UpdateForSingleplayer();
            }
        }

        if (playerReadyText) playerReadyText.gameObject.SetActive(false);
    }
}
```

RogueShooter – All Scripts

```
}

void OnDisable()
{
    TurnSystem.Instance.OnTurnChanged -= TurnSystem_OnTurnChanged;
}

// ===== julkinen kutsu PlayerController.TargetNotifyCanAct:ista =====
public void SetCanAct(bool canAct)
{
    if (endTurnButton == null) return;

    endTurnButton.onClick.RemoveListener(OnEndTurnClicked);
    if (canAct) endTurnButton.onClick.AddListener(OnEndTurnClicked);

    endTurnButton.gameObject.SetActive(canAct); // jos haluat pitää aina näkyvissä, vaihda SetActive(true)
    endTurnButton.interactable = canAct;
}

// ===== nappi =====
private void OnEndTurnClicked()
{
    // Päättele co-op -tila tilannekohtaisesti (ei SelectedMode)
    bool isOnline =
        NetTurnManager.Instance != null &&
        (GameNetworkManager.Instance.GetNetworkServerActive() || GameNetworkManager.Instance.GetNetworkClientConnected());

    if (!isOnline)
    {
        if (TurnSystem.Instance != null)
        {
            TurnSystem.Instance.NextTurn();
            return;
        }
        else
        {
            Debug.LogWarning("[UI] TurnSystem.Instance is null");
        }
    }

    CacheLocalPlayerController();
    if (localPlayerController == null)
    {
        Debug.LogWarning("[UI] Local PlayerController not found");
        return;
    }
    // Instantly lock input
    if (UnitActionSystem.Instance != null)
    {
        UnitActionSystem.Instance.LockInput();
    }
    // Prevent double clicks
}
```

RogueShooter – All Scripts

```
        SetCanAct(false);
        // Lähetä serverille
        localPlayerController.ClickEndTurn();
    }

    private void CacheLocalPlayerController()
    {
        if (localPlayerController != null) return;

        // 1) Varmista helpoimman kautta
        if (PlayerController.Local != null)
        {
            localPlayerController = PlayerController.Local;
            return;
        }

        // 2) Fallback: Mirrorin client-yhteyden identity
        var conn = GameNetworkManager.Instance != null
            ? GameNetworkManager.Instance.NetworkClientConnection()
            : null;
        if (conn != null && conn.identity != null)
        {
            localPlayerController = conn.identity.GetComponent<PlayerController>();
            if (localPlayerController != null) return;
        }

        // 3) Viimeinen oljenkorsi: etsi skenestä local-pelaaja
        var pcs = FindObjectsByType<PlayerController>(FindObjectsSortMode.InstanceID);
        foreach (var pc in pcs)
        {
            if (pc.isLocalPlayer) { localPlayerController = pc; break; }
        }

        TurnSystem.Instance.NextTurn();
    }

    // ===== singleplayer UI (valinnainen) =====
    private void TurnSystem_OnTurnChanged(object s, EventArgs e) => UpdateForSingleplayer();

    private void UpdateForSingleplayer()
    {
        if (turnNumberText != null)
            turnNumberText.text = "Turn: " + TurnSystem.Instance.GetTurnNumber();

        if (enemyTurnVisualGameObject != null)
            enemyTurnVisualGameObject.SetActive(!TurnSystem.Instance.IsPlayerTurn());

        if (endTurnButton != null)
            endTurnButton.gameObject.SetActive(TurnSystem.Instance.IsPlayerTurn());
    }
}
```

RogueShooter – All Scripts

```
    }

    // Kutsutaan verkosta
    public void SetTeammateReady(bool visible, string whoLabel = null)
    {
        if (!playerReadyText) return;
        if (visible)
        {
            playerReadyText.text = $"{whoLabel} READY";
            playerReadyText.gameObject.SetActive(true);
        }
        else
        {
            playerReadyText.gameObject.SetActive(false);
        }
    }
}
```


RogueShooter – All Scripts

Assets/scripts/Units/UnitsControlUI/UnitActionBusyUI.cs

```
using UnityEngine;

/// <summary>
/// This class is responsible for displaying the busy UI when the unit action system is busy
/// </summary>
public class UnitActionBusyUI : MonoBehaviour
{
    private void Start()
    {
        // UnitActionSystem.Instance.OnBusyChanged += UnitActionSystem_OnBusyChanged;
        Hide();
    }

    void OnEnable()
    {
        UnitActionSystem.Instance.OnBusyChanged += UnitActionSystem_OnBusyChanged;
    }

    void OnDisable()
    {
        UnitActionSystem.Instance.OnBusyChanged -= UnitActionSystem_OnBusyChanged;
    }

    private void Show()
    {
        gameObject.SetActive(true);
    }

    private void Hide()
    {
        gameObject.SetActive(false);
    }

    /// <summary>
    /// This method is called when the unit action system is busy or not busy
    /// </summary>
    private void UnitActionSystem_OnBusyChanged(object sender, bool isBusy)
    {
        if (isBusy)
        {
            Show();
        }
        else
        {
            Hide();
        }
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitsControlUI/UnitActionButtonUI.cs

```
using UnityEngine;
using UnityEngine.UI;
using TMPro;
using System;

/// <summary>
///     This class is responsible for displaying the action button TXT in the UI
/// </summary>

public class UnitActionButtonUI : MonoBehaviour
{
    [SerializeField] private TextMeshProUGUI textMeshPro;
    [SerializeField] private Button actionButton;
    [SerializeField] private GameObject actionButtonSelectedVisual;

    // --- UUTTA: kulmabadge
    [Header("Corner badge (optional)")]
    [SerializeField] private RectTransform cornerRoot;    // drag: CornerBadge
    [SerializeField] private TextMeshProUGUI cornerText; // drag: CornerText

    private BaseAction baseAction;

    public void SetBaseAction(BaseAction baseAction)
    {
        this.baseAction = baseAction;
        textMeshPro.text = baseAction.GetActionName().ToUpper();

        actionButton.onClick.AddListener(() =>
        {
            UnitActionSystem.Instance.SetSelectedAction(baseAction);
        });

        RefreshCorner();
    }

    void OnEnable()
    {
        TrySub(true);
        RefreshCorner();
    }

    void OnDisable()
    {
        TrySub(false);
    }

    private void TrySub(bool on)
    {
        // turvallisest unsub/sub -kutsut
        if (UnitActionSystem.Instance != null)
```

RogueShooter – All Scripts

```
{
    if (on)
    {
        UnitActionSystem.Instance.OnSelectedUnitChanged += OnUiRefresh;
        UnitActionSystem.Instance.OnSelectedActionChanged += OnUiRefresh;
        UnitActionSystem.Instance.OnActionStarted += OnUiRefresh;

        // HUOM: tämä on EventHandler<bool>, EI EventHandler
        UnitActionSystem.Instance.OnBusyChanged += OnBusyChanged;
    }
    else
    {
        UnitActionSystem.Instance.OnSelectedUnitChanged -= OnUiRefresh;
        UnitActionSystem.Instance.OnSelectedActionChanged -= OnUiRefresh;
        UnitActionSystem.Instance.OnActionStarted -= OnUiRefresh;
        UnitActionSystem.Instance.OnBusyChanged -= OnBusyChanged;
    }
}

if (TurnSystem.Instance != null)
{
    if (on) TurnSystem.Instance.OnTurnChanged += OnTurnChanged;
    else TurnSystem.Instance.OnTurnChanged -= OnTurnChanged;
}

if (on)
    BaseAction.OnAnyActionStarted += OnAnyActionStarted;
else
    BaseAction.OnAnyActionStarted -= OnAnyActionStarted;
}

private void OnUiRefresh(object sender, EventArgs e) => RefreshCorner();
private void OnAnyActionStarted(object sender, EventArgs e) => RefreshCorner();
private void OnTurnChanged(object sender, EventArgs e) => RefreshCorner();

private void OnBusyChanged(object sender, bool isBusy) => RefreshCorner();

private void RefreshCorner()
{
    // Näytä kulmalaskuri vain kranaatti-napissa
    bool isGrenade = baseAction is GrenadeAction;
    if (!isGrenade)
    {
        if (cornerRoot) cornerRoot.gameObject.SetActive(false);
        return;
    }

    var unit = UnitActionSystem.Instance ? UnitActionSystem.Instance.GetSelectedUnit() : null;
    int pcs = unit ? unit.GetGrenadePCS() : 0; // Unitilla on GetGrenadePCS()
    if (cornerText) cornerText.text = pcs.ToString();
    if (cornerRoot) cornerRoot.gameObject.SetActive(true);
}
```

RogueShooter – All Scripts

```
    }  
  
    public void UpdateSelectedVisual()  
    {  
        BaseAction selectedbaseAction = UnitActionSystem.Instance.GetSelectedAction();  
        actionButtonSelectedVisual.SetActive(selectedbaseAction == baseAction);  
    }  
  
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitsControlUI/UnitActionSystemUI.cs

```
using System;
using System.Collections.Generic;
using UnityEngine;
using TMPro;

/// <summary>
///     This class is responsible for displaying the action buttons for the selected unit in the UI.
///     It creates and destroys action buttons based on the selected unit's actions.
/// </summary>

public class UnitActionSystemUI : MonoBehaviour
{
    [SerializeField] private Transform actionButtonPrefab;
    [SerializeField] private Transform actionButtonContainerTransform;
    [SerializeField] private TextMeshProUGUI actionPointsText;

    private List<UnitActionButtonUI> actionButtonUIList;

    private void Awake()
    {
        actionButtonUIList = new List<UnitActionButtonUI>();
    }

    private void Start()
    {
        if (UnitActionSystem.Instance != null)
        {
            UnitActionSystem.Instance.OnSelectedUnitChanged += UnitActionSystem_OnSelectedUnitChanged;
            UnitActionSystem.Instance.OnSelectedActionChanged += UnitActionSystem_OnSelectedActionChanged;
            UnitActionSystem.Instance.OnActionStarted += UnitActionSystem_OnActionStarted;
        }
        else
        {
            Debug.Log("UnitActionSystem instance found.");
        }
        if (TurnSystem.Instance != null)
        {
            TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
        }
        else
        {
            Debug.Log("TurnSystem instance not found.");
        }

        Unit.OnAnyActionPointsChanged += Unit_OnAnyActionPointsChanged;
    }

    void OnDisable()
    {
        UnitActionSystem.Instance.OnSelectedUnitChanged -= UnitActionSystem_OnSelectedUnitChanged;
    }
}
```

RogueShooter – All Scripts

```
UnitActionSystem.Instance.OnSelectedActionChanged -= UnitActionSystem_OnSelectedActionChanged;
UnitActionSystem.Instance.OnActionStarted -= UnitActionSystem_OnActionStarted;
TurnSystem.Instance.OnTurnChanged -= TurnSystem_OnTurnChanged;
Unit.OnAnyActionPointsChanged -= Unit_OnAnyActionPointsChanged;
}

private void CreateUnitActionButtons()
{
    Unit selectedUnit = UnitActionSystem.Instance.GetSelectedUnit();
    if (selectedUnit == null)
    {
        Debug.Log("No selected unit found.");
        return;
    }
    actionButtonUIList.Clear();

    foreach (BaseAction baseAction in selectedUnit.GetBaseActionsArray())
    {
        Transform actionButtonTransform = Instantiate(actionButtonPrefab, actionButtonContainerTransform);
        UnitActionButtonUI actionButtonUI = actionButtonTransform.GetComponent<UnitActionButtonUI>();
        actionButtonUI.SetBaseAction(baseAction);
        actionButtonUIList.Add(actionButtonUI);
    }
}

private void DestroyActionButtons()
{
    foreach (Transform child in actionButtonContainerTransform)
    {
        Destroy(child.gameObject);
    }
}

private void UnitActionSystem_OnSelectedUnitChanged(object sender, EventArgs e)
{
    DestroyActionButtons();
    CreateUnitActionButtons();
    UpdateSelectedVisual();
    UpdateActionPointsVisual();
}

private void UnitActionSystem_OnSelectedActionChanged(object sender, EventArgs e)
{
    UpdateSelectedVisual();
}

private void UnitActionSystem_OnActionStarted(object sender, EventArgs e)
{
    UpdateActionPointsVisual();
}
```

RogueShooter – All Scripts

```
private void UpdateSelectedVisual()
{
    foreach (UnitActionButtonUI actionButtonUI in actionButtonUIList)
    {
        actionButtonUI.UpdateSelectedVisual();
    }
}

private void UpdateActionPointsVisual()
{
    // Jos tekstiä ei ole kytketty Inspectorissa, poistu siististi
    if (actionPointsText == null) return;

    // Jos järjestelmä ei ole vielä valmis, näytä viiva
    if (UnitActionSystem.Instance == null)
    {
        actionPointsText.text = "Action Points: -";
        return;
    }
    Unit selectedUnit = UnitActionSystem.Instance.GetSelectedUnit();
    if (selectedUnit == null)
    {
        actionPointsText.text = "Action Points: -";
        return;
    }
    actionPointsText.text = "Action Points: " + selectedUnit.GetActionPoints();
}

/// <summary>
///     This method is called when the turn changes. It resets the action points UI to the maximum value.
/// </summary>
private void TurnSystem_OnTurnChanged(object sender, EventArgs e)
{
    UpdateActionPointsVisual();
}

/// <summary>
///     This method is called when the action points of any unit change. It updates the action points UI.
/// </summary>
private void Unit_OnAnyActionPointsChanged(object sender, EventArgs e)
{
    UpdateActionPointsVisual();
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitSelectedVisual.cs

```
using System;
using UnityEngine;

/// <summary>
/// This class is responsible for displaying a visual indicator when a unit is selected in the game.
/// It uses a MeshRenderer component to show or hide the visual representation of the selected unit.
/// </summary>
public class UnitSelectedVisual : MonoBehaviour
{
    [SerializeField] private Unit unit;
    [SerializeField] private MeshRenderer meshRenderer;

    private void Awake()
    {
        if (!meshRenderer) meshRenderer = GetComponentInChildren<MeshRenderer>(true);
        if (meshRenderer) meshRenderer.enabled = false;
    }

    void OnEnable()
    {
        if (UnitActionSystem.Instance != null)
        {
            UnitActionSystem.Instance.OnSelectedUnitChanged += UnitActionSystem_OnSelectedUnitChanged;
            UpdateVisual();
        }

        TurnSystem.Instance.OnTurnChanged += turnSystem_OnTurnChanged;
    }

    void OnDisable()
    {
        if (UnitActionSystem.Instance != null)
        {
            UnitActionSystem.Instance.OnSelectedUnitChanged -= UnitActionSystem_OnSelectedUnitChanged;
            UpdateVisual();
        }

        TurnSystem.Instance.OnTurnChanged -= turnSystem_OnTurnChanged;
    }

    private void UnitActionSystem_OnSelectedUnitChanged(object sender, EventArgs empty)
    {
        UpdateVisual();
    }

    private void UpdateVisual()
    {

```


RogueShooter – All Scripts

```
        if (!this || meshRenderer == null || UnitActionSystem.Instance == null) return;
        var selected = UnitActionSystem.Instance.GetSelectedUnit();
        meshRenderer.enabled = unit != null && selected == unit;
    }

    public void ResetSelectedVisual()
    {
        if (meshRenderer) meshRenderer.enabled = false;
    }

    private void turnSystem_OnTurnChanged(object sender, EventArgs e)
    {
        ResetSelectedVisual();
    }
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitSkills/CoverSkill.cs

```
using System;
using Mirror;
using UnityEngine;

[RequireComponent(typeof(Unit))]
public class CoverSkill : NetworkBehaviour
{
    [SerializeField] private int newCoverBonusHalf = 15;
    [SerializeField] private int newCoverBonusFull = 25;

    private int personalCover;
    private int personalCoverMax;
    private int thisTurnStartingPersonalCover;

    private int currentTurnCoverBonus;

    [SyncVar] private bool hasMoved = false;

    protected Unit unit;

    private int _lastProcessedTurnId = -1;

    public event Action<int, int> OnCoverPoolChanged;

    protected virtual void Awake()
    {
        unit = GetComponent<Unit>();
    }

    private void Start()
    {
        if (unit.archetype != null)
        {
            personalCoverMax = unit.archetype.personalCoverMax;
        }

        personalCover = personalCoverMax;
        thisTurnStartingPersonalCover = personalCover;
        currentTurnCoverBonus = 0;
        hasMoved = false;

        OnCoverPoolChanged?.Invoke(personalCover, personalCoverMax);
    }

    private void OnEnable()
    {
        TurnSystem.Instance.OnTurnStarted += OnTurnStarted_HandleTurnStarted;
        TurnSystem.Instance.OnTurnEnded += OnTurnEnded_HandleTurnEnded;
    }
}
```

RogueShooter – All Scripts

```
private void OnDisable()
{
    TurnSystem.Instance.OnTurnStarted -= OnTurnStarted_HandleTurnStarted;
    TurnSystem.Instance.OnTurnEnded -= OnTurnEnded_HandleTurnEnded;
}

public int GetPersonalCover()
{
    return personalCover;
}

public void SetPersonalCover(int value)
{
    if (!NetworkServer.active && !NetworkClient.active)
    {
        ApplyCoverLocal(value);
        return;
    }

    if (NetworkServer.active)
    {
        ApplyCoverServer(value);
        return;
    }

    var ni = GetComponent<NetworkIdentity>();
    if (NetworkClient.active && NetworkSyncAgent.Local != null && ni != null)
    {
        NetworkSyncAgent.Local.CmdSetUnitCover(ni.netId, value);
    }
}

public void SetCoverBonus()
{
    // CLIENT: pyydä serveriä tekemään
    if (NetworkClient.active && !NetworkServer.active)
    {
        var ni = GetComponent<NetworkIdentity>();
        NetworkSyncAgent.Local?.CmdApplyCoverBonus(ni.netId);
        return;
    }

    // SERVER / OFFLINE: varsinainen työ
    ServerApplyCoverBonus();
}

//[Server]
public void ServerApplyCoverBonus()
{
    // Vain Server TAI Offline saa suorittaa
    if (NetworkClient.active && !NetworkServer.active) return;
}
```

RogueShooter – All Scripts

```
// TÄRKEÄ: Jos on jo liikuttu tällä vuorolla, resetoi bonus ENSIN
if (hasMoved && currentTurnCoverBonus != 0)
{
    int newCover = personalCover - currentTurnCoverBonus;
    if (newCover < thisTurnStartingPersonalCover)
        newCover = thisTurnStartingPersonalCover;

    personalCover = newCover;
    currentTurnCoverBonus = 0;
}
hasMoved = true;
if (unit.IsUnderFire)
{
    personalCover = thisTurnStartingPersonalCover;
    OnCoverPoolChanged?.Invoke(personalCover, personalCoverMax);
    NetworkSync.UpdateCoverUI(unit);
    return;
}

var gp = unit.GetGridPosition();
var pf = PathFinding.Instance;
if (pf == null) return;

var node = pf.GetNode(gp.x, gp.z, gp.floor);
if (node == null) return;

var t = CoverService.GetNodeAnyCover(node);
int bonus = t == CoverService.CoverType.High ? newCoverBonusFull :
            t == CoverService.CoverType.Low ? newCoverBonusHalf : 0;

currentTurnCoverBonus = bonus;
if (bonus > 0)
{
    if (unit.IsUnderFire)
    {
        SetPersonalCover(thisTurnStartingPersonalCover);
    }
    else
    {
        SetPersonalCover(personalCover + bonus);
    }
}
else
{
    NetworkSync.UpdateCoverUI(unit);
}
}

private void ApplyCoverLocal(int value)
{
    personalCover = Mathf.Clamp(value, 0, personalCoverMax);
}
```

RogueShooter – All Scripts

```
    OnCoverPoolChanged?.Invoke(personalCover, personalCoverMax);
}

//[Server]
private void ApplyCoverServer(int value)
{
    // Vain Server TAI Offline saa suorittaa
    if (NetworkClient.active && !NetworkServer.active) return;

    personalCover = Mathf.Clamp(value, 0, personalCoverMax);
    OnCoverPoolChanged?.Invoke(personalCover, personalCoverMax);
    NetworkSync.UpdateCoverUI(unit);
}

public void RegenCoverOnMove(int distance)
{
    if (NetworkClient.active && !NetworkServer.active)
    {
        var ni = GetComponent<NetworkIdentity>();
        NetworkSyncAgent.Local?.CmdRegenCoverOnMove(ni.netId, distance);
        return;
    }

    ServerRegenCoverOnMove(distance);
}

//[Server]
public void ServerRegenCoverOnMove(int distance)
{
    // Vain Server TAI Offline saa suorittaa
    if (NetworkClient.active && !NetworkServer.active) return;

    int regenPerTile = unit.archetype != null ? unit.archetype.coverRegenOnMove : 5;
    int tileDelta = distance / 10;
    int coverChange = regenPerTile * tileDelta;
    int newCover = personalCover + coverChange;

    if (newCover <= thisTurnStartingPersonalCover)
    {
        newCover = thisTurnStartingPersonalCover;
    }

    SetPersonalCover(Mathf.Clamp(newCover, 0, personalCoverMax));
}

public void RegenCoverBy(int amount)
{
    if (amount == 0) return;
    SetPersonalCover(personalCover + amount);
}

public int GetCoverRegenPerUnusedAP()
```

RogueShooter – All Scripts

```
{
    if (!unit.IsUnderFire)
    {
        return unit.archetype != null ? unit.archetype.coverRegenPerUnusedAP : 0;
    }
    return 0;
}

public int GetPersonalCoverMax() => personalCoverMax;

public float GetCoverNormalized()
{
    return (float)personalCover / personalCoverMax;
}

public void ApplyNetworkCover(int current, int max)
{
    personalCoverMax = max;
    personalCover = Mathf.Clamp(current, 0, max);
    OnCoverPoolChanged?.Invoke(personalCover, personalCoverMax);
}

public int GetCurrentCoverBonus()
{
    return currentTurnCoverBonus;
}

public void ResetCurrentCoverBonus()
{
    if (NetworkClient.active && !NetworkServer.active)
    {
        var ni = GetComponent<NetworkIdentity>();
        NetworkSyncAgent.Local?.CmdResetCurrentCoverBonus(ni.netId);
        return;
    }

    ServerResetCurrentCoverBonus();
}

//[Server]
public void ServerResetCurrentCoverBonus()
{
    // Vain Server TAI Offline saa suorittaa
    if (NetworkClient.active && !NetworkServer.active) return;

    if (currentTurnCoverBonus != 0)
    {
        int newCover = personalCover - currentTurnCoverBonus;
        if (newCover < thisTurnStartingPersonalCover)
            newCover = thisTurnStartingPersonalCover; // vuoron aloitus on minimi

        SetPersonalCover(newCover);
    }
}
```

RogueShooter – All Scripts

```
        currentTurnCoverBonus = 0; // estää tuplavähennykset
    }
}

public bool HasMoved()
{
    return hasMoved;
}

private void OnTurnStarted_HandleTurnStarted(Team startTurnTeam, int turnId)
{
    if (NetworkClient.active && !NetworkServer.active) return;
    // Vain oman puolen vuorolla
    if (unit.Team != startTurnTeam) return;

    // (Valinnainen) suoja duplikaateilta, jos eventti laukeaa useammin samassa vuorossa
    if (_lastProcessedTurnId == turnId) return;
    _lastProcessedTurnId = turnId;

    // Resetit vain omalle puolelle:
    thisTurnStartingPersonalCover = personalCover;
    currentTurnCoverBonus = 0;
    hasMoved = false;
}

private void OnTurnEnded_HandleTurnEnded(Team endTurnTeam, int turnId)
{
    if (NetworkClient.active && !NetworkServer.active) return;
    // Vain kun toisen vuoro alkaa. Unitit eivät ole enää tulen alla.
    if (unit.Team != endTurnTeam) return;
    unit.SetUnderFire(false);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitStatsUI/UnitUIBroadcaster.cs

```
using Mirror;

public class UnitUIBroadcaster : NetworkBehaviour
{
    public static UnitUIBroadcaster Instance { get; private set; }
    void Awake() { if (Instance == null) Instance = this; }

    // Tätä saa kutsua vain serveri (hostin serveripuoli)
    [Server]
    public void BroadcastUnitWorldUIVisibility(bool already)
    {
        if (!NetworkServer.active) return;

        // käy kaikki serverillä tunnetut unitit läpi
        foreach (var kvp in NetworkServer.spawned)
        {
            var unit = kvp.Value.GetComponent<Unit>();
            if (!unit) continue;

            // serveri voi laskea logiikan: pitääkö tämän unitin AP näkyä
            bool visible = ShouldBeVisible(unit, already);

            // lähetä client-puolelle että tämän unitin UI asetetaan
            RpcSetUnitUIVisibility(unit.netId, visible);
        }
    }

    // Tätä kutsuu serveri, suoritetaan kaikilla clienteilla
    [ClientRpc]
    private void RpcSetUnitUIVisibility(uint unitId, bool visible)
    {
        if (NetworkClient.spawned.TryGetValue(unitId, out var ni) && ni != null)
        {
            var ui = ni.GetComponentInChildren<UnitWorldUI>();
            if (ui != null) ui.SetVisible(visible);
        }
    }

    // serverilogiikka omistajan perusteella
    [Server]
    private bool ShouldBeVisible(Unit unit, bool already)
    {
        // Kaikki pelaajat ovat valmiina joten näytetään vain vihollisen AP pisteet.
        if (already)
        {
            return unit.IsEnemy();
        }

        // Co-Op
        bool playersPhase = TurnSystem.Instance.IsPlayerTurn();
    }
}
```


RogueShooter – All Scripts

```
bool ownerEnded = false;
if (unit.OwnerId != 0 &&
    NetworkServer.spawned.TryGetValue(unit.OwnerId, out var ownerId) &&
    ownerId != null)
{
    var pc = ownerId.GetComponent<PlayerController>();
    if (pc != null) ownerEnded = pc.hasEndedThisTurn;
}

// 2) Päättä näkyvyys
if (playersPhase)
{
    // Pelaajavaihe: näytä kaikki ei-viholliset, joiden omistaja EI ole lopettanut
    return !unit.IsEnemy() && !ownerEnded;
}
else
{
    // Vihollisvaihe: näytä vain viholliset
    return unit.IsEnemy();
}
}
```

RogueShooter – All Scripts

Assets/scripts/Units/UnitStatsUI/UnitWorldUI.cs

```
using UnityEngine;
using TMPro;
using System;
using UnityEngine.UI;
using Mirror;

/// <summary>
/// Displays world-space UI for a single unit, including action points and health bar.
/// Reacts to turn events and ownership rules to show or hide UI visibility
/// </summary>
public class UnitWorldUI : MonoBehaviour
{
    [SerializeField] private TextMeshProUGUI actionPointsText;
    [SerializeField] private Unit unit;

    [SerializeField] private Image healthBarImage;
    [SerializeField] private HealthSystem healthSystem;

    [SerializeField] private Image personalCoverBarImage;

    /// <summary>
    /// Reference to the unit this UI belongs to.
    /// Which object's visibility do we want to change?
    /// </summary>
    [Header("Visibility")]
    [SerializeField] private GameObject actionPointsRoot;

    /// <summary>
    /// Cached network identity for ownership.
    /// </summary>
    private NetworkIdentity unitIdentity;

    // --- NEW: tiny static registry for ready owners (co-op only) ---
    // private static readonly HashSet<uint> s_readyOwners = new();
    // public static bool HasOwnerEnded(uint ownerId) => s_readyOwners.Contains(ownerId);

    private void Awake()
    {
        unitIdentity = unit ? unit.GetComponent<NetworkIdentity>() : GetComponentInParent<NetworkIdentity>();
    }

    private void Start()
    {
        Unit.OnAnyActionPointsChanged += Unit_OnAnyActionPointsChanged;
        healthSystem.OnDamaged += HealthSystem_OnDamaged;
        unit.OnCoverPoolChanged += Unit_OnCoverPoolChanged;

        UpdateActionPointsText();
    }
}
```

RogueShooter – All Scripts

```
UpdateHealthBarUI();
Unit_OnCoverPoolChanged(unit.GetPersonalCover(), unit.GetPersonalCoverMax());

// Co-opissa. Ei paikallista seurantaa. Ainoastaan alku asettelu
if (GameManager.SelectedMode == GameMode.CoOp)
{
    if (unit.IsEnemy())
    {
        actionPointsRoot.SetActive(false);
    }

    return;
}

PlayerLocalTurnGate.LocalPlayerTurnChanged += PlayerLocalTurnGate_LocalPlayerTurnChanged;
PlayerLocalTurnGate_LocalPlayerTurnChanged(PlayerLocalTurnGate.LocalPlayerTurn);
}

private void OnDisable()
{
    Unit.OnAnyActionPointsChanged -= Unit_OnAnyActionPointsChanged;
    healthSystem.OnDamaged -= HealthSystem_OnDamaged;
    PlayerLocalTurnGate.LocalPlayerTurnChanged -= PlayerLocalTurnGate_LocalPlayerTurnChanged;
    unit.OnCoverPoolChanged -= Unit_OnCoverPoolChanged;
}

private void OnDestroy()
{
    Unit.OnAnyActionPointsChanged -= Unit_OnAnyActionPointsChanged;
    healthSystem.OnDamaged -= HealthSystem_OnDamaged;
    PlayerLocalTurnGate.LocalPlayerTurnChanged -= PlayerLocalTurnGate_LocalPlayerTurnChanged;
    unit.OnCoverPoolChanged -= Unit_OnCoverPoolChanged;
}

private void UpdateActionPointsText()
{
    actionPointsText.text = unit.GetActionPoints().ToString();
}

private void Unit_OnAnyActionPointsChanged(object sender, EventArgs e)
{
    UpdateActionPointsText();
}

private void UpdateCoverBarUI()
{
    personalCoverBarImage.fillAmount = unit.GetCoverNormalized();
}
```

RogueShooter – All Scripts

```
private void Unit_OnCoverPoolChanged(int current, int max)
{
    UpdateCoverBarUI();
}

private void UpdateHealthBarUI()
{
    healthBarImage.fillAmount = healthSystem.GetHealthNormalized();
}

/// <summary>
/// Event handler: refreshes the health bar UI when this unit takes damage.
/// </summary>
private void HealthSystem_OnDamaged(object sender, EventArgs e)
{
    UpdateHealthBarUI();
}

/// <summary>
/// SinglePlayer/Versus: paikallinen turn-gate. Co-opissa ei käytetä.
/// </summary>
private void PlayerLocalTurnGate_LocalPlayerTurnChanged(bool canAct)
{
    if (GameManager.SelectedMode == GameMode.CoOp) return; // Co-op: näkyvyys tulee RPC:stä
    if (!this || !gameObject) return;

    bool showAp;
    if (GameManager.SelectedMode == GameMode.SinglePlayer)
    {
        showAp = canAct ? !unit.IsEnemy() : unit.IsEnemy();
    }
    else // Versus
    {
        bool unitIsMine = unitIdentity && unitIdentity.isOwned;
        showAp = (canAct && unitIsMine) || (!canAct && !unitIsMine);
    }

    actionPointsRoot.SetActive(showAp);
}

public void SetVisible(bool visible)
{
    actionPointsRoot.SetActive(visible);
}
}
```

RogueShooter – All Scripts

Assets/scripts/Utilities/PriorityQueue.cs

```
using System;
using System.Collections.Generic;

/// <summary>
/// A lightweight, generic min-heap-based Priority Queue implementation used internally for game logic,
/// especially pathfinding and AI decision-making.
///
/// This class provides a simple and efficient way to retrieve the next element with the lowest priority value.
/// It avoids external dependencies for performance and maintainability within Unity builds.
///
/// Design notes specific to RogueShooter:
/// - Used by the pathfinding and tactical AI systems to determine optimal movement and action order.
/// - Provides deterministic and garbage-free priority management during runtime (no LINQ or heap allocations).
/// - Does not support key priority updates ("decrease-key") – instead, updated items are re-enqueued,
///   and outdated entries are safely ignored by the higher-level game logic.
///
/// In short, this queue enables efficient and predictable priority handling for all turn-based tactical calculations,
/// without relying on .NET's built-in PriorityQueue (which is unavailable in some Unity versions).
/// </summary>
public sealed class PriorityQueue<T>
{
    private (T item, int priority)[] _heap;
    private int _count;

    public int Count => _count;

    public PriorityQueue(int initialCapacity = 64)
    {
        if (initialCapacity < 1) initialCapacity = 1;
        _heap = new (T, int)[initialCapacity];
        _count = 0;
    }

    public void Clear()
    {
        Array.Clear(_heap, 0, _count);
        _count = 0;
    }

    public void Enqueue(T item, int priority)
    {
        if (_count == _heap.Length) Array.Resize(ref _heap, _heap.Length * 2);
        _heap[_count] = (item, priority);
        SiftUp(_count++);
    }

    public T Dequeue()
    {
        if (_count == 0) throw new InvalidOperationException("PriorityQueue is empty");
        T result = _heap[0].item;
    }
}
```

RogueShooter – All Scripts

```
    _heap[0] = _heap[--_count];
    _heap[_count] = default;
    if (_count > 0) SiftDown(0);
    return result;
}

public bool TryDequeue(out T item)
{
    if (_count == 0)
    {
        item = default;
        return false;
    }
    item = Dequeue();
    return true;
}

public T Peek()
{
    if (_count == 0) throw new InvalidOperationException("PriorityQueue is empty");
    return _heap[0].item;
}

public int PeekPriority()
{
    if (_count == 0) throw new InvalidOperationException("PriorityQueue is empty");
    return _heap[0].priority;
}

private void SiftUp(int idx)
{
    while (idx > 0)
    {
        int parent = (idx - 1) >> 1;
        if (_heap[parent].priority <= _heap[idx].priority) break;
        (_heap[parent], _heap[idx]) = (_heap[idx], _heap[parent]);
        idx = parent;
    }
}

private void SiftDown(int idx)
{
    while (true)
    {
        int left = (idx << 1) + 1;
        if (left >= _count) break;
        int right = left + 1;
        int smallest = (right < _count && _heap[right].priority < _heap[left].priority) ? right : left;
        if (_heap[idx].priority <= _heap[smallest].priority) break;
        (_heap[idx], _heap[smallest]) = (_heap[smallest], _heap[idx]);
        idx = smallest;
    }
}
```

```
}  
}
```

RogueShooter – All Scripts

Assets/scripts/Utilities/SircleCalculator.cs

```
using UnityEngine;

public static class SircleCalculator
{
    public static int Sircle(int x, int z)
    {
        int ax = Mathf.Abs(x);
        int az = Mathf.Abs(z);
        int diag = Mathf.Min(ax, az);
        int straight = Mathf.Abs(ax - az);
        int cost = 14 * diag + 10 * straight;

        return cost;
    }
}
```


RogueShooter – All Scripts

Assets/scripts/Weapons/BulletProjectile.cs

```
using Mirror;
using UnityEngine;

public class BulletProjectile : NetworkBehaviour
{
    [SyncVar] public uint actorUnitNetId;
    [SerializeField] private TrailRenderer trailRenderer;
    [SerializeField] private Transform bulletHitVfxPrefab;

    [SyncVar] private Vector3 targetPosition;

    public void Setup(Vector3 targetPosition)
    {
        this.targetPosition = targetPosition;
    }

    public override void OnStartClient()
    {
        base.OnStartClient();

        if (trailRenderer && !trailRenderer.emitting) trailRenderer.emitting = true;
    }

    private void Update()
    {
        Vector3 moveDirection = (targetPosition - transform.position).normalized;

        float distanceBeforeMoving = Vector3.Distance(transform.position, targetPosition);

        float moveSpeed = 200f; // Adjust the speed as needed
        transform.position += moveSpeed * Time.deltaTime * moveDirection;

        float distanceAfterMoving = Vector3.Distance(transform.position, targetPosition);

        // Check if we've reached or passed the target position
        if (distanceBeforeMoving < distanceAfterMoving)
        {
            transform.position = targetPosition;

            if (trailRenderer) trailRenderer.transform.parent = null;
            /*
            if (bulletHitVfxPrefab)
                Instantiate(bulletHitVfxPrefab, targetPosition, Quaternion.identity);
            */

            if (bulletHitVfxPrefab)
            {
                SpawnRouter.SpawnLocal(
                    bulletHitVfxPrefab.gameObject,
```

RogueShooter – All Scripts

```
        targetPosition,  
        Quaternion.identity,  
        source: transform // -> sama scene kuin luodilla  
    );  
}  
  
// Network-aware destruction  
if (isServer) NetworkServer.Destroy(gameObject);  
else Destroy(gameObject);  
}  
}
```

RogueShooter – All Scripts

Assets/scripts/Weapons/CombatRanges.cs

```
using UnityEngine;

[CreateAssetMenu(menuName="RogueShooter/Combat Ranges")]
public class CombatRanges : ScriptableObject
{
    [Header("Use tiles instead of world units")]
    public bool useTiles = true;

    [Header("Max distance per band (in tiles)")]
    public int meleeMaxTiles = 1; // "vieressä"
    public int closeMaxTiles = 5;
    public int mediumMaxTiles = 15;
    public int longMaxTiles = 20;

    [Header("Legacy world units (fallback if useTiles==false)")]
    public float meleeMaxWU = 1.2f;
    public float closeMaxWU = 4f;
    public float mediumMaxWU = 9f;
    public float longMaxWU = 15f;
}
```

RogueShooter – All Scripts

Assets/scripts/Weapons/GranadeProjectile.cs

```
using System;
using UnityEngine;
using Mirror;
using System.Collections;

public class GrenadeProjectile : NetworkBehaviour
{
    [SyncVar] public uint actorUnitNetId;
    public static event EventHandler OnAnyGranadeExploded;

    [SerializeField] private Transform grenadeExplodeVFXPrefab;
    [SerializeField] private float damageRadius = 4f;
    [SerializeField] private int damage = 30;
    [SerializeField] private float moveSpeed = 15f;
    [SerializeField] private int timer = 2;
    [SerializeField] private LayerMask floorMask = ~0;
    [SerializeField] private float landingJitterRadius = 0.18f;
    [SerializeField] private AnimationCurve arcYAnimationCurve;

    // Pieni hajonta, muutama sadasosan verran
    [SerializeField] private float explosionJitterMin = 0.02f;
    [SerializeField] private float explosionJitterMax = 0.08f;

    private bool _explosionScheduled; // vartija, ettei ajeta kahta kertaa

    [SyncVar(hook = nameof(OnTargetChanged))] private Vector3 targetPosition;

    private float totalDistance;
    private Vector3 positionXZ;
    private const float MIN_DIST = 0.01f;

    private bool isExploded = false;

    private bool isLanded = false;

    private bool _ready;

    public override void OnStartClient()
    {
        base.OnStartClient();
    }

    public void Setup(Vector3 targetWorld)
    {
        TurnSystem.Instance.OnTurnChanged += TurnSystem_OnTurnChanged;
        var groundTarget = SnapToGround(targetWorld);
        // Aseta SyncVar, hook kutsutaan kaikilla (server + clientit)
        targetPosition = groundTarget;
        RecalculateDerived(); // varmistetaan serverillä heti
```

RogueShooter – All Scripts

```
_ready = true;

if(GameModeManager.SelectedMode == GameMode.CoOp)
{
    timer += 1; // pidennä kranaatin aikaa COOPissa yhdellä vuorolla
} else
{
    timer = 2;
}
}

private void TurnSystem_OnTurnChanged(object sender, EventArgs e)
{
    timer -= 1;
    if (timer <= 0 && !_explosionScheduled && !isExploded)
    {
        _explosionScheduled = true;
        StartCoroutine(ExplodeAfterJitter());
    }
}

private IEnumerator ExplodeAfterJitter()
{
    // Deterministinen "satunnaisuus": sama viive serverillä ja clienteleillä tälle kranaatille
    uint id = GetComponent<NetworkIdentity>() ? GetComponent<NetworkIdentity>().netId : 0u;
    float t = Mathf.Abs(Mathf.Sin(id * 12.9898f + targetPosition.x * 78.233f + targetPosition.z * 37.719f));
    float delay = Mathf.Lerp(explosionJitterMin, explosionJitterMax, t);

    yield return new WaitForSeconds(delay);

    Explosion();
}

private void OnDestroy()
{
    TurnSystem.Instance.OnTurnChanged -= TurnSystem_OnTurnChanged;
}

private Vector3 SnapToGround(Vector3 worldXZ)
{
    return new Vector3(worldXZ.x, 0f, worldXZ.z);
}

void OnTargetChanged(Vector3 _old, Vector3 _new)
{
    // Kun SyncVar saapuu clientille, laske johdetut kentät sielläkin
    RecomputeDerived();
    _ready = true;
}

private void RecomputeDerived()
```

RogueShooter – All Scripts

```
{
    positionXZ = transform.position;
    positionXZ.y = 0f;

    totalDistance = Vector3.Distance(positionXZ, targetPosition);
    if (totalDistance < MIN_DIST) totalDistance = MIN_DIST; // suoja nollaa vastaan
}

private void Update()
{
    if (!_ready || isExploded) return;
    if (isLanded) return;

    Vector3 moveDir = targetPosition - positionXZ;
    if (moveDir.sqrMagnitude < 1e-6f) moveDir = Vector3.forward; // varadir, ettei normalized → NaN
    moveDir.Normalize();

    positionXZ += moveSpeed * Time.deltaTime * moveDir;

    float distance = Vector3.Distance(positionXZ, targetPosition);
    if (totalDistance < 1e-6f) totalDistance = 0.01f;
    float distanceNormalized = 1f - (distance / totalDistance);
    distanceNormalized = Mathf.Clamp01(distanceNormalized);

    float maxHeight = totalDistance / 4f;
    float positionY = arcYAnimationCurve != null
        ? arcYAnimationCurve.Evaluate(distanceNormalized) * maxHeight
        : 0f;

    if (float.IsNaN(positionY)) positionY = 0f; // viimeinen pelastus
    transform.position = new Vector3(positionXZ.x, positionY, positionXZ.z);

    float reachedTargetDistance = .2f;

    if (!isLanded && (positionXZ - targetPosition).sqrMagnitude <= reachedTargetDistance * reachedTargetDistance)
    {
        isLanded = true;

        // a) ruudun keskelle (x,z) + oikea kerros-Y LevelGridistä
        var gp = LevelGrid.Instance.GetGridPosition(targetPosition);
        var center = LevelGrid.Instance.GetWorldPosition(gp); // ruudun keskipiste & floor-Y

        // b) satunnainen siirto ruudun sisällä (XZ)
        Vector2 j2 = UnityEngine.Random.insideUnitCircle * landingJitterRadius;
        Vector3 p = new Vector3(center.x + j2.x, center.y, center.z + j2.y);

        // c) lattia-Y (voit myös käyttää pelkkää center.y)
        float y = p.y;
        if (Physics.Raycast(p + Vector3.up * 2f, Vector3.down, out var hit, 10f, floorMask, QueryTriggerInteraction.Ignore))
            y = hit.point.y;
```

RogueShooter – All Scripts

```
// d) jos pivot ei ole maassa, kompensoi kolliderin puoli-korkeus
if (TryGetComponent<Collider>(out var col)) y += col.bounds.extents.y;

// ASETUS
transform.position = new Vector3(p.x, y, p.z);
}
}

private void Exlosion()
{
    isExploded = true;
    if (NetMode.ServerOrOff) // Server or offline. NetworkServer.active || !NetworkClient.isConnected
    {
        Collider[] colliderArray = Physics.OverlapSphere(targetPosition, damageRadius);

        foreach (Collider collider in colliderArray)
        {
            if (collider.TryGetComponent<Unit>(out Unit targetUnit))
            {
                NetworkSync.ApplyDamageToUnit(targetUnit, damage, targetPosition, this.GetActorId());
            }
            if (collider.TryGetComponent<DestructibleObject>(out DestructibleObject targetObject))
            {
                NetworkSync.ApplyDamageToObject(targetObject, damage, targetPosition, this.GetActorId());
            }
        }
    }

    // Screen Shake
    OnAnyGranadeExploded?.Invoke(this, EventArgs.Empty);

    SpawnRouter.SpawnLocal(
        grenadeExplodeVFXPrefab.gameObject,
        targetPosition + Vector3.up * 1f,
        Quaternion.identity,
        source: transform // <- scene päätellään lähteestä
    );

    if (!NetMode.IsServer) // NetworkServer.active
    {
        Destroy(gameObject);
        return;
    }

    // Online: Hide Granade before destroy it, so that client have time to create own explode VFX from original Granade pose.
    SetSoftHiddenLocal(true);
    RpcSetSoftHidden(true);

    // Kerro asiakkaille missä scenessä VFX pitää luoda
    RpcExplodeVFX(gameObject.scene.name, targetPosition);
}
```

RogueShooter – All Scripts

```
        StartCoroutine(DestroyAfter(0.30f));
    }

    private IEnumerator DestroyAfter(float seconds)
    {
        yield return new WaitForSeconds(seconds);
        NetworkServer.Destroy(gameObject);
    }

    [ClientRpc]
    private void RpcSetSoftHidden(bool hidden)
    {
        SetSoftHiddenLocal(hidden);
    }

    [ClientRpc]
    private void RpcExplodeVFX(string sceneName, Vector3 pos)
    {
        OnAnyGranadeExploded?.Invoke(this, EventArgs.Empty);

        // Luodaan VFX oikeaan Level-sceeneen clientillä
        SpawnRouter.SpawnLocal(
            grenadeExplodeVFXPrefab.gameObject,
            pos + Vector3.up * 1f,
            Quaternion.identity,
            source: null,
            sceneName: sceneName
        );
    }

    private void SetSoftHiddenLocal(bool hidden)
    {
        foreach (var r in GetComponentsInChildren<Renderer>())
        {
            r.enabled = !hidden;
        }
    }
}
```


RogueShooter – All Scripts

Assets/scripts/Weapons/GrenadeDefinition.cs

```
using UnityEngine;

public enum EffectArea { Melee, Close, Medium }
public enum ThrowTier { CritMiss, Miss, Hit, Bullseye }
public enum GrenadeType {Frag, flash, Smoke}

[CreateAssetMenu(menuName = "RogueShooter/Grenade")]
public class GrenadeDefinition : ScriptableObject
{
    [Header("Base damage")]
    public int baseDamage = 300;
    public float pressureFactor = 0.2f; // Effects only Unit cover skill and light covers and objects.

    [Header("Base hit chance baseline by band (% before skill) Overall must be 100%")]
    public int critMiss = 10;
    public int miss = 20;
    public int hit = 60;
    public int Bullseye = 10;

    [Header("Timer(turns before explotion)")]
    public int timer = 1;
}
```

RogueShooter – All Scripts

Assets/scripts/Weapons/ShootingResolver.cs

```
using UnityEngine;

public struct ShotResult {
    public ShotTier tier;
    public int damage;
    public bool bypassCover;
    public bool coverOnly;
}

public static class ShootingResolver
{
    private static CombatRanges _cachedRanges;
    private static CombatRanges Ranges
    {
        get
        {
            if (!_cachedRanges)
                _cachedRanges = Resources.Load<CombatRanges>("CombatRanges");
            return _cachedRanges;
        }
    }

    /*
    // Euclidinen etäisyys ruutuina (vastaa aiempaa world-distancea, mutta gridissä)
    private static float TileDistance(GridPosition a, GridPosition b)
    {
        int dx = a.x - b.x;
        int dz = a.z - b.z;
        return Mathf.Sqrt(dx * dx + dz * dz);
    }
    */
    private static float TileDistance(GridPosition a, GridPosition b)
    {
        int dx = Mathf.Abs(a.x - b.x);
        int dz = Mathf.Abs(a.z - b.z);
        int cost = SircleCalculator.Sircle(dx, dz);
        return cost / 10f; // muunna takaisin "ruuduiksi"
    }

    // Uusi band-määrittäminen ruuduilla
    public static RangeBand GetBandTiles(Unit attacker, Unit target, WeaponDefinition w)
    {
        var gpA = attacker.GetGridPosition();
        var gpT = target.GetGridPosition();

        // (Valinta: jos kerros eri, voit palauttaa Extreme heti)
        // if (gpA.floor != gpT.floor) return RangeBand.Extreme;

        if (Ranges && Ranges.useTiles)
        {
```

RogueShooter – All Scripts

```
float tiles = TileDistance(gpA, gpT);
if (tiles <= Ranges.meleeMaxTiles) return RangeBand.Melee;
if (tiles <= Ranges.closeMaxTiles) return RangeBand.Close;
if (tiles <= Ranges.mediumMaxTiles) return RangeBand.Medium;
if (tiles <= Ranges.longMaxTiles) return RangeBand.Long;
return RangeBand.Extreme;
}

// Fallback: world-yksiköt (takaperin yhteensopiva)
Vector3 aw = attacker.GetWorldPosition();
Vector3 tw = target.GetWorldPosition();
float distWU = Vector3.Distance(aw, tw);
if (Ranges)
{
    if (distWU <= Ranges.meleeMaxWU) return RangeBand.Melee;
    if (distWU <= Ranges.closeMaxWU) return RangeBand.Close;
    if (distWU <= Ranges.mediumMaxWU) return RangeBand.Medium;
    if (distWU <= Ranges.longMaxWU) return RangeBand.Long;
    return RangeBand.Extreme;
}

// Jos ei CombatRanges.assetia → käytä asekohtaisia world-rajoja (nykyinen polku)
if (distWU <= 1.2f) return RangeBand.Melee;
if (distWU <= w.closeMax) return RangeBand.Close;
if (distWU <= w.mediumMax) return RangeBand.Medium;
if (distWU <= w.longMax) return RangeBand.Long;
return RangeBand.Extreme;
}

// Päälogiikka: 1) osuma vai huti, 2) tarkempi tier
public static ShotResult Resolve(Unit attacker, Unit target, WeaponDefinition w)
{
    Vector3 a = attacker.GetWorldPosition();
    Vector3 t = target.GetWorldPosition();
    float dist = Vector3.Distance(a, t);
    // var band = GetBand(dist, w);
    var band = GetBandTiles(attacker, target, w);

    // Skill + cover -muokkaukset vaikuttavat vain "vaihe 1: baseHitChance" -arvoon
    int baseHit = GetBaseHitChance(band, w);
    baseHit += GetSkillBonus(attacker);
    baseHit -= GetCoverPenalty(attacker, target);

    baseHit = Mathf.Clamp(baseHit, 0, 100);

    int roll1 = UnityEngine.Random.Range(1, 101);
    bool isHitPool = roll1 <= baseHit;

    ShotTier tier = isHitPool
        ? RollOnHit(band, w)
        : RollOnMiss(band, w);
}
```

RogueShooter – All Scripts

```
var res = new ShotResult { tier = tier };
ApplyDamageModel(ref res, w);

DebugShot(attacker, target, w, band, baseHit, roll1, res);
return res;
}

private static int GetBaseHitChance(RangeBand b, WeaponDefinition w)
{
    if (w.useAdvancedAccuracy)
        return w.GetTuning(b).baseHitChance;

    // Legacy polku (taaksepäin-yhteensopiva)
    switch (b)
    {
        case RangeBand.Melee: return w.meleeAcc;
        case RangeBand.Close: return w.closeAcc;
        case RangeBand.Medium: return w.mediumAcc;
        case RangeBand.Long: return w.longAcc;
        default: return w.extremeAcc;
    }
}

private static int GetSkillBonus(Unit attacker)
{
    if (attacker != null && attacker.archetype != null)
        return attacker.archetype.shootingSkillLevel * attacker.archetype.accuracyBonusPerSkillLevel;
    return 0;
}

private static int GetCoverPenalty(Unit attacker, Unit target)
{
    var targetGridPosition = target.GetGridPosition();
    var node = PathFinding.Instance.GetNode(targetGridPosition.x, targetGridPosition.z, targetGridPosition.floor);
    var ct = CoverService.EvaluateCoverHalfPlane(attacker.GetGridPosition(), target.GetGridPosition(), node);

    if (attacker != null && attacker.archetype != null)
    {
        var archA = attacker.archetype;
        if (ct == CoverService.CoverType.High) return archA.highCoverPenalty;
        if (ct == CoverService.CoverType.Low) return archA.lowCoverPenalty;
    }
    return 0;
}

private static ShotTier RollOnHit(RangeBand b, WeaponDefinition w)
{
    var t = w.GetTuning(b);

    int c = Mathf.Max(0, t.onHit_Close);
    int g = Mathf.Max(0, t.onHit_Graze);
    int h = Mathf.Max(0, t.onHit_Hit);
}
```

RogueShooter – All Scripts

```
int cr = Mathf.Max(0, t.onHit_Crit);

int sum = c + g + h + cr;
if (sum <= 0) return ShotTier.Hit; // fallback

int r = UnityEngine.Random.Range(1, sum + 1);
if (r <= c) return ShotTier.Miss; // "Close" = cover chip → käytetään ShotTier.Miss pipelinea
r -= c;
if (r <= g) return ShotTier.Graze;
r -= g;
if (r <= h) return ShotTier.Hit;
return ShotTier.Crit;
}

private static ShotTier RollOnMiss(RangeBand b, WeaponDefinition w)
{
    var t = w.GetTuning(b);

    int m = Mathf.Max(0, t.onMiss_Miss);
    int cm = Mathf.Max(0, t.onMiss_CritMiss);
    int sum = m + cm;
    if (sum <= 0) return ShotTier.CritMiss; // fallback: rankka huti

    int r = UnityEngine.Random.Range(1, sum + 1);
    return (r <= m) ? ShotTier.Miss : ShotTier.CritMiss;
}

private static void ApplyDamageModel(ref ShotResult res, WeaponDefinition w)
{
    switch (res.tier)
    {
        case ShotTier.CritMiss:
            res.damage = 0;
            res.coverOnly = false;
            res.bypassCover = false;
            break;

        case ShotTier.Miss: // "Close call" → chip cover only
            res.damage = Mathf.RoundToInt(w.baseDamage * w.missChipFactor);
            res.coverOnly = true;
            res.bypassCover = false;
            break;

        case ShotTier.Graze:
            res.damage = Mathf.RoundToInt(w.baseDamage * w.grazeFactor);
            res.coverOnly = true;
            res.bypassCover = false;
            break;

        case ShotTier.Hit:
            res.damage = w.baseDamage;
            res.coverOnly = false;
    }
}
```

RogueShooter – All Scripts

```
        res.bypassCover = false;
        break;

    case ShotTier.Crit:
        res.damage = w.baseDamage + w.critBonusDamage;
        res.coverOnly = false;
        res.bypassCover = true;
        break;
    }
}

private static void DebugShot(Unit attacker, Unit target, WeaponDefinition w, RangeBand band, int baseHit, int roll1, ShotResult result)
{
    string tierColor =
        result.tier == ShotTier.Crit ? "Green" :
        result.tier == ShotTier.Hit ? "Blue" :
        result.tier == ShotTier.Graze ? "yellow" : "red";

    string txt =
        $"<b>{attacker.name}</b> → <b>{target.name}</b>\n" +
        $"Weapon: {w.name}\n" +
        $"Range: {band} | Roll1: {roll1} vs Hit%:{baseHit}\n" +
        $"Result: <color={tierColor}>{result.tier}</color> | Dmg:{result.damage} | " +
        $" {(result.bypassCover ? "Bypass Cover" : result.coverOnly ? "Cover Only" : "Normal")}";

    Debug.Log(txt);
    // Halutessa voi näyttää world-labelin editorissa (Handles), jätetty pois runtime-käytön vuoksi.
}
}
```

RogueShooter – All Scripts

Assets/scripts/Weapons/WeaponDefinition.cs

```
using UnityEngine;

public enum RangeBand { Melee, Close, Medium, Long, Extreme }
public enum ShotTier { CritMiss, Miss, Graze, Hit, Crit }

[System.Serializable]
public struct RangeBandTuning
{
    [Header("Stage 1: Base chance to HIT (before skill/cover)")]
    [Range(0, 100)] public int baseHitChance;

    [Header("Stage 2a: On HIT distribution (Close/Graze/Hit/Crit)")]
    [Range(0, 100)] public int onHit_Close;
    [Range(0, 100)] public int onHit_Graze;
    [Range(0, 100)] public int onHit_Hit;
    [Range(0, 100)] public int onHit_Crit;

    [Header("Stage 2b: On MISS distribution (Miss/CritMiss)")]
    [Range(0, 100)] public int onMiss_Miss;
    [Range(0, 100)] public int onMiss_CritMiss;
}

[CreateAssetMenu(menuName = "RogueShooter/Weapon")]
public class WeaponDefinition : ScriptableObject
{
    [Header("Range: Weapon basic max Range (No upgrades)")]
    public int maxShootRange = 10;

    [Header("Bonus when the target is not behind cover")]
    public int NoCoverDamageBonus = 30;

    [Header("Base damage")]
    public int baseDamage = 10;
    public int critBonusDamage = 8;
    public float grazeFactor = 0.4f; // 40% damagesta
    public float missChipFactor = 0.2f; // 20% damagesta (vain coveriin)

    [Header("Legacy per-weapon ranges (used if no global CombatRanges found)")]
    public float closeMax = 4f;
    public float mediumMax = 9f;
    public float longMax = 15f;

    [Header("Advanced accuracy: per-band tunables")]
    public bool useAdvancedAccuracy = true;
    public RangeBandTuning melee;
    public RangeBandTuning close;
    public RangeBandTuning medium;
    public RangeBandTuning @long;
```

RogueShooter – All Scripts

```
public RangeBandTuning extreme;

public RangeBandTuning GetTuning(RangeBand b)
{
    switch (b)
    {
        case RangeBand.Melee:    return melee;
        case RangeBand.Close:    return close;
        case RangeBand.Medium:    return medium;
        case RangeBand.Long:     return @long;
        default:                 return extreme;
    }
}

// (TAKAISIN-YHTEENSOPIVA): jos haluat käyttää vanhaa baselinea joskus, jätä nämä.
[Header("Legacy baselines (ignored if useAdvancedAccuracy==true)")]
public int meleeAcc    = 95;
public int closeAcc    = 80;
public int mediumAcc   = 65;
public int longAcc     = 45;
public int extremeAcc  = 25;

[Header("Legacy crit starts (ignored if useAdvancedAccuracy==true)")]
public int critStartMelee    = 90;
public int critStartClose    = 85;
public int critStartMedium   = 80;
public int critStartLong     = 70;
public int critStartExtreme  = 60;
}
```


