

Namespace Bliss.CSharp

Classes

[Disposable](#)

[GlobalResource](#)

Class Disposable

Namespace: [Bliss.CSharp](#)

Assembly: Bliss.dll

```
public abstract class Disposable : IDisposable
```

Inheritance

[object](#) ← Disposable

Implements

[IDisposable](#)

Derived

[Effect](#), [Font](#), [FontStashRenderer2D](#), [FontStashTextureManager](#), [Mesh](#), [Model](#), [SimpleBufferLayout](#),
[SimpleStructuredBuffer](#)<THeader, TElement>, [SimpleUniformBuffer](#)<T>, [SimplePipeline](#),
[SimpleTextureLayout](#), [PrimitiveBatch](#), [SpriteBatch](#), [ForwardRenderer](#)<T>, [DynamicLightHandler](#),
[FixedLightHandler](#), [ShadowMap](#), [FullScreenRenderer](#), [ImmediateRenderer](#), [Sdl3InputContext](#),
[Sdl3Gamepad](#), [Sdl3Cursor](#), [Cubemap](#), [RenderTexture2D](#), [Texture2D](#), [Sdl3Window](#)

Inherited Members

[object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Properties

HasDisposed

Indicates whether the object has been disposed.

```
public bool HasDisposed { get; }
```

Property Value

[bool](#)

True if the object has been disposed; otherwise, false.

Methods

Dispose()

Disposes of the object, allowing for proper resource cleanup and finalization.

```
public void Dispose()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected abstract void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

~Disposable()

Disposes of the object, allowing for proper resource cleanup and finalization.

```
protected ~Disposable()
```

ThrowIfDisposed()

Throws an exception if the object has been disposed, indicating that it is no longer usable.

```
protected void ThrowIfDisposed()
```

Class GlobalResource

Namespace: [Bliss.CSharp](#)

Assembly: Bliss.dll

```
public static class GlobalResource
```

Inheritance

[object](#) ← GlobalResource

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Properties

Aniso4XClampSampler

A global 4x anisotropic sampler using clamp addressing mode.

```
public static Sampler Aniso4XClampSampler { get; }
```

Property Value

[Sampler](#)

DefaultFullScreenRenderPassEffect

Gets the default [Effect](#) used for full-screen render passes.

```
public static Effect DefaultFullScreenRenderPassEffect { get; }
```

Property Value

[Effect](#)

DefaultImmediateRendererEffect

Gets the default [Effect](#) used for immediate mode rendering operations.

```
public static Effect DefaultImmediateRendererEffect { get; }
```

Property Value

[Effect](#)

DefaultImmediateRendererTexture

The default [Texture2D](#) used for immediate mode rendering.

```
public static Texture2D DefaultImmediateRendererTexture { get; }
```

Property Value

[Texture2D](#)

DefaultModelEffect

The default [Effect](#) used for rendering 3D models.

```
public static Effect DefaultModelEffect { get; }
```

Property Value

[Effect](#)

DefaultModelTexture

The default [Texture2D](#) used for rendering 3D models.

```
public static Texture2D DefaultModelTexture { get; }
```

Property Value

[Texture2D](#)

DefaultPrimitiveEffect

Gets the [Effect](#) used for rendering primitive shapes.

```
public static Effect DefaultPrimitiveEffect { get; }
```

Property Value

[Effect](#)

DefaultSpriteEffect

Gets the default [Effect](#) used for rendering sprites.

```
public static Effect DefaultSpriteEffect { get; }
```

Property Value

[Effect](#)

GraphicsDevice

Provides access to the global graphics device used for rendering operations.

```
public static GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#) ↗

LinearClampSampler

A global linear sampler using clamp addressing mode.

```
public static Sampler LinearClampSampler { get; }
```

Property Value

[Sampler](#)

PointClampSampler

A global point sampler using clamp addressing mode.

```
public static Sampler PointClampSampler { get; }
```

Property Value

[Sampler](#)

Methods

Destroy()

Releases and disposes of all global resources.

```
public static void Destroy()
```

Init(GraphicsDevice)

Initializes global resources.

```
public static void Init(GraphicsDevice graphicsDevice)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device to be used for resource creation and rendering.

Namespace Bliss.CSharp.Audio

Classes

[Vector3FExtensions](#)

Class Vector3FExtensions

Namespace: [Bliss.CSharp.Audio](#)

Assembly: Bliss.dll

```
public static class Vector3FExtensions
```

Inheritance

[object](#) ← Vector3FExtensions

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

ToVector3(Vector3f)

Converts a MiniAudioEx.Core.StandardAPI.Vector3f instance to a [Vector3](#) instance.

```
public static Vector3 ToVector3(this Vector3f v)
```

Parameters

v Vector3f

The MiniAudioEx.Core.StandardAPI.Vector3f instance to convert.

Returns

[Vector3](#)

A [Vector3](#) instance corresponding to the given MiniAudioEx.Core.StandardAPI.Vector3f.

ToVector3F(Vector3)

Converts a [Vector3](#) instance to a MiniAudioEx.Core.StandardAPI.Vector3f instance.

```
public static Vector3f ToVector3F(this Vector3 v)
```

Parameters

v [Vector3](#)

The [Vector3](#) instance to convert.

Returns

Vector3f

A MiniAudioEx.Core.StandardAPI.Vector3f instance corresponding to the given [Vector3](#).

Namespace Bliss.CSharp.Camera

Interfaces

[ICam](#)

Interface ICam

Namespace: [Bliss.CSharp.Camera](#)

Assembly: Bliss.dll

```
public interface ICam
```

Methods

Begin()

Initializes the camera's usage in the current frame and sets it as the active camera.

```
void Begin()
```

End()

Concludes the camera's operations for the current frame.

```
void End()
```

Resize(uint, uint)

Resizes the viewport and updates the aspect ratio based on the given width and height.

```
void Resize(uint width, uint height)
```

Parameters

width [uint](#)

The new width of the viewport.

height [uint](#)

The new height of the viewport.

Update(double)

Updates the camera's state, recalculating its parameters as needed.

```
void Update(double timeStep)
```

Parameters

timeStep [double](#)

Namespace Bliss.CSharp.Camera.Dim2

Classes

[Cam2D](#)

Enums

[CameraFollowMode](#)

Class Cam2D

Namespace: [Bliss.CSharp.Camera.Dim2](#)

Assembly: Bliss.dll

```
public class Cam2D : ICam
```

Inheritance

[object](#) ← Cam2D

Implements

[ICam](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Cam2D(Vector2, Vector2, Rectangle, CameraFollowMode,
Vector2?, float, float)

Initializes a new instance of the [Cam2D](#) class.

```
public Cam2D(Vector2 position, Vector2 target, Rectangle size, CameraFollowMode mode,  
Vector2? offset = null, float rotation = 0, float zoom = 1)
```

Parameters

position [Vector2](#)

The initial position of the camera.

target [Vector2](#)

The target position the camera follows.

size [Rectangle](#)

The dimensions of the camera's viewport.

mode [CameraFollowMode](#)

The camera follow mode determining how the camera tracks the target.

offset [Vector2](#)?

Optional offset applied to the camera's position. Defaults to (0,0).

rotation [float](#)

The initial rotation of the camera in degrees.

zoom [float](#)

The zoom level of the camera. A value of 1.0 represents no zoom.

Fields

FractionFollowSpeed

Represents the fraction of the distance to the target that the camera covers per update cycle, used to determine the speed of the camera's follow movement.

```
public float FractionFollowSpeed
```

Field Value

[float](#)

MinFollowEffectLength

Represents the minimum distance at which the follow effect is activated.

```
public float MinFollowEffectLength
```

Field Value

[float](#)

MinFollowSpeed

Represents the minimum speed at which the camera follows its target.

```
public float MinFollowSpeed
```

Field Value

[float ↗](#)

Mode

Defines the camera's follow mode, determining how the camera follows its target.

```
public CameraFollowMode Mode
```

Field Value

[CameraFollowMode](#)

Offset

Gets or sets the offset position of the camera.

```
public Vector2 Offset
```

Field Value

[Vector2 ↗](#)

Position

Gets or sets the position of the camera in 2D space.

```
public Vector2 Position
```

Field Value

[Vector2](#)

Rotation

Gets or sets the rotation angle of the camera, in degrees.

```
public float Rotation
```

Field Value

[float](#)

Target

Gets or sets the target position of the camera.

```
public Vector2 Target
```

Field Value

[Vector2](#)

Zoom

Gets or sets the zoom level of the camera.

```
public float Zoom
```

Field Value

[float](#)

Properties

ActiveCamera

Gets or sets the active camera instance.

```
public static Cam2D? ActiveCamera { get; }
```

Property Value

[Cam2D](#)

Size

Gets the current viewport settings of the camera.

```
public Rectangle Size { get; }
```

Property Value

[Rectangle](#)

Methods

Begin()

Initializes the camera's usage in the current frame and sets it as the active camera.

```
public void Begin()
```

End()

Ends the current camera session, setting the active camera to null.

```
public void End()
```

GetScreenToWorld(Vector2)

Converts a screen position to a world position based on the camera's current view matrix.

```
public Vector2 GetScreenToWorld(Vector2 position)
```

Parameters

position [Vector2](#)

The screen position to be converted.

Returns

[Vector2](#)

The corresponding world position.

GetView()

Retrieves the current view matrix of the camera.

```
public Matrix4x4 GetView()
```

Returns

[Matrix4x4](#)

The [Matrix4x4](#) representing the camera's view matrix.

GetVisibleArea()

Calculates and returns the visible area of the camera based on its current position and viewport size.

```
public RectangleF GetVisibleArea()
```

Returns

[RectangleF](#)

A [RectangleF](#) representing the visible area in world coordinates.

GetWorldToScreen(Vector2)

Converts a given world position to screen coordinates based on the camera's current view matrix.

```
public Vector2 GetWorldToScreen(Vector2 position)
```

Parameters

position [Vector2](#)

The world position to convert.

Returns

[Vector2](#)

A [Vector2](#) representing the screen coordinates corresponding to the given world position.

Resize(uint, uint)

Resizes the camera's viewport to the specified width and height.

```
public void Resize(uint width, uint height)
```

Parameters

width [uint](#)

The new width of the viewport.

height [uint](#)

The new height of the viewport.

Update(double)

Updates the camera's state based on the elapsed time and current mode.

```
public void Update(double timeStep)
```

Parameters

timeStep [double](#)

The time elapsed since the last update, in seconds.

Enum CameraFollowMode

Namespace: [Bliss.CSharp.Camera.Dim2](#)

Assembly: Bliss.dll

```
public enum CameraFollowMode
```

Fields

`Custom = 0`

Custom follow behavior, allowing manual control of the camera's movement.

`FollowTarget = 1`

Directly follows the target position without any smoothing or delay.

`FollowTargetSmooth = 2`

Smoothly follows the target with a gradual transition, creating a smoother effect.

Namespace Bliss.CSharp.Camera.Dim3

Classes

[Cam3D](#)

Enums

[CameraMode](#)

[ProjectionType](#)

Class Cam3D

Namespace: [Bliss.CSharp.Camera.Dim3](#)

Assembly: Bliss.dll

```
public class Cam3D : ICam
```

Inheritance

[object](#) ← Cam3D

Implements

[ICam](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Cam3D(Vector3, Vector3, float, Vector3?, ProjectionType, CameraMode, float, float, float)

Initializes a new instance of the [Cam3D](#) class.

```
public Cam3D(Vector3 position, Vector3 target, float aspectRatio, Vector3? up = null,  
ProjectionType projectionType = ProjectionType.Perspective, CameraMode mode =  
CameraMode.Free, float fov = 70, float nearPlane = 0.01, float farPlane = 10000)
```

Parameters

position [Vector3](#)

The camera position in world space.

target [Vector3](#)

The target point the camera is looking at.

aspectRatio [float](#)

The aspect ratio (width / height). Must be greater than zero.

up [Vector3](#)?

The upward direction vector. Defaults to (0,1,0).

projectionType [ProjectionType](#)

The type of projection (Perspective or Orthographic).

mode [CameraMode](#)

The camera movement mode.

fov [float](#)

The field of view in degrees. Should be between 1 and 179.

nearPlane [float](#)

The near clipping plane. Must be positive and smaller than `farPlane`.

farPlane [float](#)

The far clipping plane. Must be positive and greater than `nearPlane`.

Fields

FarPlane

Specifies the far clipping plane distance for the camera, determining the maximum depth at which objects are rendered in the 3D scene.

```
public float FarPlane
```

Field Value

[float](#)

Fov

Defines the field of view (FOV) angle for the camera, determining the extent of the observable world that is seen at any given moment.

```
public float Fov
```

Field Value

[float](#)

Mode

Defines the current operational mode of the camera. This determines the behavior and control mechanics of the camera, such as whether it's in Free mode, Orbital mode, etc.

```
public CameraMode Mode
```

Field Value

[CameraMode](#)

MouseSensitivity

Determines the sensitivity of the camera to mouse movements. This affects how fast the camera rotates or moves in response to mouse inputs. Higher values result in faster and more responsive camera movements.

```
public float MouseSensitivity
```

Field Value

[float](#)

MovementSpeed

Specifies the speed at which the camera can move within the scene. Adjust this value to control how fast the camera translates in the 3D space. Typically used in conjunction with user input to navigate the

scene.

```
public float MovementSpeed
```

Field Value

[float](#)

NearPlane

Specifies the near clipping plane distance for the camera, determining the minimum depth at which objects are rendered in the 3D scene.

```
public float NearPlane
```

Field Value

[float](#)

OrbitalSpeed

Represents the speed at which the camera orbits around a target. Determines how quickly the camera moves when controlled to orbit in any direction. Typically used in orbital or tracking camera modes.

```
public float OrbitalSpeed
```

Field Value

[float](#)

Position

Represents the position of the camera in a 3D space. This defines the location from which the camera is capturing its view.

```
public Vector3 Position
```

Field Value

[Vector3](#)

ProjectionType

Represents the type of projection used by the camera, either Perspective or Orthographic, influencing how 3D scenes are rendered onto a 2D viewport.

`public ProjectionType ProjectionType`

Field Value

[ProjectionType](#)

Target

Represents the focal point that the camera is aimed at in the 3D space. Determines the direction in which the camera is looking.

`public Vector3 Target`

Field Value

[Vector3](#)

Up

Represents the upward direction vector for the camera, determining its orientation in the 3D space relative to its position and target.

`public Vector3 Up`

Field Value

[Vector3](#)

Properties

ActiveCamera

References the currently active instance of the Cam3D class. Used to determine which camera is currently rendering the scene. Can be accessed from other classes to retrieve camera-specific properties and methods.

```
public static Cam3D? ActiveCamera { get; }
```

Property Value

[Cam3D](#)

AspectRatio

Represents the ratio between the width and height of the camera's viewport. Used to adjust the projection matrix for rendering the 3D scene correctly on the screen.

```
public float AspectRatio { get; }
```

Property Value

[float](#)

Methods

Begin()

Activates the current camera instance as the active camera and updates its projection and view matrices.

```
public void Begin()
```

End()

Ends the current 3D rendering session and deactivates the camera.

```
public void End()
```

GetForward()

Computes and returns the forward direction vector based on the camera's position and target.

```
public Vector3 GetForward()
```

Returns

[Vector3](#)

A Vector3 representing the forward direction of the camera.

GetFrustum()

Retrieves the camera frustum by extracting the frustum planes based on the current view and projection matrices.

```
public Frustum GetFrustum()
```

Returns

[Frustum](#)

The updated frustum containing the extracted planes.

GetPitch()

Retrieves the current pitch angle of the camera.

```
public float GetPitch()
```

Returns

[float](#)

The current pitch angle in degrees.

GetProjection()

Generates the projection matrix based on the current camera settings, such as projection type, field of view (FOV), aspect ratio, near plane, and far plane distances.

```
public Matrix4x4 GetProjection()
```

Returns

[Matrix4x4](#)

The calculated projection matrix.

GetRight()

Computes and returns the right direction vector based on the camera's forward direction and up vector.

```
public Vector3 GetRight()
```

Returns

[Vector3](#)

A Vector3 representing the right direction of the camera.

GetRoll()

Retrieves the roll component of the camera's rotation.

```
public float GetRoll()
```

Returns

[float](#)

The roll angle in degrees.

GetRotation()

Retrieves the current rotation vector of the camera.

```
public Vector3 GetRotation()
```

Returns

[Vector3](#)

A Vector3 representing the current rotation of the camera.

GetScreenToWorld(Vector2)

Converts a given screen position to world coordinates using the camera projection and view matrices.

```
public Vector3 GetScreenToWorld(Vector2 position)
```

Parameters

`position` [Vector2](#)

The screen position to transform.

Returns

[Vector3](#)

A [Vector3](#) representing the corresponding world coordinates.

GetView()

Constructs and returns the view matrix for the camera based on its position, target, and up vector.

```
public Matrix4x4 GetView()
```

Returns

[Matrix4x4](#)

The view matrix of the camera.

GetWorldToScreen(Vector3)

Converts a given world position to screen coordinates based on the camera's current view and projection matrices.

```
public Vector2 GetWorldToScreen(Vector3 position)
```

Parameters

[position](#) [Vector3](#)

The world position to convert.

Returns

[Vector2](#)

A [Vector2](#) representing the screen coordinates corresponding to the given world position.

GetYaw()

Retrieves the current yaw (rotation around the Y-axis) of the camera.

```
public float GetYaw()
```

Returns

[float](#)

The yaw value in degrees.

MoveForward(float, bool)

Moves the camera forward by a specified distance.

```
public void MoveForward(float distance, bool moveInWorldPlane)
```

Parameters

distance [float](#)

The distance by which to move the camera forward.

moveInWorldPlane [bool](#)

Determines whether to constrain movement to the world plane, ignoring the Y component.

MoveRight(float, bool)

Moves the camera to the right by a specified distance, with an option to constrain the movement to the world plane.

```
public void MoveRight(float distance, bool moveInWorldPlane)
```

Parameters

distance [float](#)

The distance to move the camera to the right.

moveInWorldPlane [bool](#)

If set to `true`, the camera will move parallel to the ground plane and will not change its Y position.

MoveToTarget(float)

Moves the camera towards or away from its target by modifying the distance between the camera's position and its target point.

```
public void MoveToTarget(float delta)
```

Parameters

delta [float](#)

The amount by which to adjust the distance to the target. Positive values move the camera closer to the target, and negative values move it further away.

MoveUp(float)

Moves the camera upward by a specified distance.

```
public void MoveUp(float distance)
```

Parameters

distance [float](#)

The distance to move the camera upward.

Resize(uint, uint)

Resizes the viewport and updates the aspect ratio based on the given width and height.

```
public void Resize(uint width, uint height)
```

Parameters

width [uint](#)

The new width of the viewport.

height [uint](#)

The new height of the viewport.

SetPitch(float, bool)

Sets the pitch angle of the camera, rotating around the specified target if indicated.

```
public void SetPitch(float angle, bool rotateAroundTarget)
```

Parameters

angle [float ↗](#)

The desired pitch angle in degrees.

rotateAroundTarget [bool ↗](#)

If true, rotates the camera around the target point; otherwise rotates around its own position.

SetRoll(float)

Sets the roll angle of the camera by rotating around the forward axis.

```
public void SetRoll(float angle)
```

Parameters

angle [float ↗](#)

The angle in degrees by which to set the roll.

SetYaw(float, bool)

Sets the yaw of the camera by rotating it around the target or adjusting the target position, based on the specified angle.

```
public void SetYaw(float angle, bool rotateAroundTarget)
```

Parameters

angle [float ↗](#)

The angle in degrees to rotate the camera.

rotateAroundTarget [bool ↗](#)

A boolean indicating whether to rotate the camera around the target or adjust the target position.

Update(double)

Updates the camera's state, recalculating its parameters as needed.

```
public void Update(double timeStep)
```

Parameters

timeStep double

Enum CameraMode

Namespace: [Bliss.CSharp.Camera.Dim3](#)

Assembly: Bliss.dll

```
public enum CameraMode
```

Fields

Custom = 0

Custom mode, allowing for user-defined camera behavior and controls.

FirstPerson = 3

First-person mode, where the camera simulates the view of a character.

Free = 1

Free mode, where the camera can move freely in 3D space.

Orbital = 2

Orbital mode, where the camera orbits around a target point.

ThirdPerson = 4

Third-person mode, where the camera follows a character from a distance.

Enum ProjectionType

Namespace: [Bliss.CSharp.Camera.Dim3](#)

Assembly: Bliss.dll

```
public enum ProjectionType
```

Fields

Orthographic = 1

Perspective = 0

Namespace Bliss.CSharp.Colors

Structs

[Color](#)

Struct Color

Namespace: [Bliss.CSharp.Colors](#)

Assembly: Bliss.dll

```
public readonly struct Color : IEquatable<Color>
```

Implements

[IEquatable](#)<[Color](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Color(byte, byte, byte, byte)

Initializes a new instance of the [Color](#) class.

```
public Color(byte r, byte g, byte b, byte a)
```

Parameters

r [byte](#)

The red component.

g [byte](#)

The green component.

b [byte](#)

The blue component.

a [byte](#)

The alpha component.

Color(RgbaFloat)

Represents a color with red, green, blue, and alpha components.

```
public Color(RgbaFloat rgbaFloat)
```

Parameters

rgbaFloat [RgbaFloat](#)

Fields

A

Represents the alpha component of the color, indicating its transparency, in the range of 0 to 255.

```
public readonly byte A
```

Field Value

[byte](#)

B

Represents the blue component of the color in the range of 0 to 255.

```
public readonly byte B
```

Field Value

[byte](#)

Black

```
public static readonly Color Black
```

Field Value

[Color](#)

Blue

```
public static readonly Color Blue
```

Field Value

[Color](#)

Brown

```
public static readonly Color Brown
```

Field Value

[Color](#)

Cyan

```
public static readonly Color Cyan
```

Field Value

[Color](#)

DarkBlue

```
public static readonly Color DarkBlue
```

Field Value

[Color](#)

DarkBrown

```
public static readonly Color DarkBrown
```

Field Value

[Color](#)

DarkCyan

```
public static readonly Color DarkCyan
```

Field Value

[Color](#)

DarkGray

```
public static readonly Color DarkGray
```

Field Value

[Color](#)

DarkGreen

```
public static readonly Color DarkGreen
```

Field Value

[Color](#)

DarkMagenta

```
public static readonly Color DarkMagenta
```

Field Value

[Color](#)

DarkOrange

```
public static readonly Color DarkOrange
```

Field Value

[Color](#)

DarkPink

```
public static readonly Color DarkPink
```

Field Value

[Color](#)

DarkPurple

```
public static readonly Color DarkPurple
```

Field Value

[Color](#)

DarkRed

```
public static readonly Color DarkRed
```

Field Value

[Color](#)

DarkYellow

```
public static readonly Color DarkYellow
```

Field Value

[Color](#)

G

Represents the green component of the color in the range of 0 to 255.

```
public readonly byte G
```

Field Value

[byte](#)

Gray

```
public static readonly Color Gray
```

Field Value

[Color](#)

Green

```
public static readonly Color Green
```

Field Value

[Color](#)

LightBlue

```
public static readonly Color LightBlue
```

Field Value

[Color](#)

LightBrown

```
public static readonly Color LightBrown
```

Field Value

[Color](#)

LightCyan

```
public static readonly Color LightCyan
```

Field Value

[Color](#)

LightGray

```
public static readonly Color LightGray
```

Field Value

[Color](#)

LightGreen

```
public static readonly Color LightGreen
```

Field Value

[Color](#)

LightMagenta

```
public static readonly Color LightMagenta
```

Field Value

[Color](#)

LightOrange

```
public static readonly Color LightOrange
```

Field Value

[Color](#)

LightPink

```
public static readonly Color LightPink
```

Field Value

[Color](#)

LightPurple

```
public static readonly Color LightPurple
```

Field Value

[Color](#)

LightRed

```
public static readonly Color LightRed
```

Field Value

[Color](#)

LightYellow

```
public static readonly Color LightYellow
```

Field Value

[Color](#)

Magenta

```
public static readonly Color Magenta
```

Field Value

[Color](#)

Orange

```
public static readonly Color Orange
```

Field Value

[Color](#)

Pink

```
public static readonly Color Pink
```

Field Value

[Color](#)

Purple

```
public static readonly Color Purple
```

Field Value

[Color](#)

R

Represents the red component of the color in the range of 0 to 255.

```
public readonly byte R
```

Field Value

[byte](#)

Red

```
public static readonly Color Red
```

Field Value

[Color](#)

White

```
public static readonly Color White
```

Field Value

[Color](#)

Yellow

```
public static readonly Color Yellow
```

Field Value

[Color](#)

Methods

AdjustSaturation(float)

Adjusts the saturation of the current [Color](#).

```
public Color AdjustSaturation(float adjustment)
```

Parameters

adjustment [float](#)

A value between -1 and 1. Negative values decrease saturation, and positive values increase it.

Returns

[Color](#)

The [Color](#) with adjusted saturation.

Equals(Color)

Determines whether the current color object is equal to another color object.

```
public bool Equals(Color other)
```

Parameters

other [Color](#)

The color to compare to.

Returns

[bool](#)

True if the current color object is equal to the other color object; otherwise, false.

Equals(object?)

Determines whether the current color object is equal to another color object.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The color to compare to.

Returns

[bool](#)

True if the current color object is equal to the other color object; otherwise, false.

FromHsv(float, float, float)

Creates a new [Color](#) instance from the specified HSV (Hue, Saturation, Value) model values.

```
public static Color FromHsv(float hue, float saturation, float value)
```

Parameters

hue [float](#)

The hue component of the color, in degrees (0-360).

saturation [float](#)

The saturation component of the color, as a value between 0 and 1.

value [float](#)

The value (brightness) component of the color, as a value between 0 and 1.

Returns

[Color](#)

A new [Color](#) object representing the specified HSV color.

GetHashCode()

Returns the hash code for this instance.

```
public override int GetHashCode()
```

Returns

[int](#)

The hash code for this instance.

Invert(bool)

Returns the inverted color, with an option to maintain the alpha component.

```
public Color Invert(bool keepAlpha = true)
```

Parameters

[keepAlpha](#) [bool](#)

Specifies whether to retain the original alpha value. If set to false, the alpha value will also be inverted.

Returns

[Color](#)

A new [Color](#) instance with the RGB components inverted, and the alpha component either retained or inverted based on the [keepAlpha](#) value.

ToHsv()

Converts the current color to its HSV (Hue, Saturation, Value) representation.

```
public (float Hue, float Saturation, float Value) ToHsv()
```

Returns

([float](#), [Hue](#), [float](#), [Saturation](#), [float](#), [Value](#))

A tuple containing the Hue, Saturation, and Value components of the color.

ToRgbaFloat()

Converts the color to an [RgbaFloat](#) value.

```
public RgbaFloat ToRgbaFloat()
```

Returns

[RgbaFloat](#)

A new instance of the [RgbaFloat](#) struct representing the color.

ToRgbaFloatVec4()

Converts the color to a [Vector4](#) representation with each component normalized to the range of 0 to 1.

```
public Vector4 ToRgbaFloatVec4()
```

Returns

[Vector4](#)

A [Vector4](#) object representing the normalized RGBA components of the color.

ToString()

Returns a string that represents the current color.

```
public override string ToString()
```

Returns

[string](#)

A string representation of the current color.

ToVector4()

Converts the color to a Vector4 representation.

```
public Vector4 ToVector4()
```

Returns

[Vector4](#)

A Vector4 representing the color.

Operators

operator +(Color, Color)

Adds two colours together piece-wise.

```
public static Color operator +(Color left, Color right)
```

Parameters

left [Color](#)

The first color to add.

right [Color](#)

The second color to add.

Returns

[Color](#)

A [Color](#) that is the result of adding the two colors together.

operator /(Color, Color)

Implements the division operator for the [Color](#) structure.

```
public static Color operator /(Color left, Color right)
```

Parameters

left [Color](#)

The [Color](#) instance acting as the dividend.

right [Color](#)

The [Color](#) instance acting as the divisor.

Returns

[Color](#)

A new [Color](#) resulting from component-wise division of the two colors. If a component in the divisor is zero, the resulting component is clamped to 255.

operator ==(Color, Color)

Determines whether two Color objects are equal.

```
public static bool operator ==(Color left, Color right)
```

Parameters

left [Color](#)

The first Color to compare.

right [Color](#)

The second Color to compare.

Returns

[bool](#)

`true` if the specified `Color` objects are equal; otherwise, `false`.

operator !=(Color, Color)

Represents the equality operator for comparing two colors for equality.

```
public static bool operator !=(Color left, Color right)
```

Parameters

`left` [Color](#)

The first color to compare.

`right` [Color](#)

The second color to compare.

Returns

[bool](#)

`true` if the colors are equal; otherwise, `false`.

operator %(Color, Color)

Computes the component-wise remainder (modulo) of two colors, treating each channel separately.

```
public static Color operator %(Color left, Color right)
```

Parameters

`left` [Color](#)

The left operand representing the dividend color.

`right` [Color](#)

The right operand representing the divisor color.

Returns

[Color](#)

A new [Color](#) representing the component-wise remainder.

operator *(Color, Color)

Multiplies the color components of two [Color](#) instances component-wise.

```
public static Color operator *(Color left, Color right)
```

Parameters

left [Color](#)

The first [Color](#) instance.

right [Color](#)

The second [Color](#) instance.

Returns

[Color](#)

A new [Color](#) resulting from the component-wise multiplication of the two input colors.

operator -(Color, Color)

Subtracts two colours together piece-wise.

```
public static Color operator -(Color left, Color right)
```

Parameters

left [Color](#)

The first color to subtract.

right [Color](#)

The second color to subtract.

Returns

[Color](#)

A [Color](#) that is the result of subtracting the two colors together.

Namespace Bliss.CSharp.Effects

Classes

[Effect](#)

Class Effect

Namespace: [Bliss.CSharp.Effects](#)

Assembly: Bliss.dll

```
public class Effect : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Effect

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Effect(GraphicsDevice, VertexLayoutDescription, byte[], byte[], SpecializationConstant[]?)

Initializes a new instance of the [Effect](#) class using shader bytecode.

```
public Effect(GraphicsDevice graphicsDevice, VertexLayoutDescription vertexLayout, byte[] vertBytes, byte[] fragBytes, SpecializationConstant[]? constants = null)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for rendering.

vertexLayout [VertexLayoutDescription](#)

The [VertexLayoutDescription](#) defining the vertex structure.

vertBytes [byte](#)[]

The compiled bytecode for the vertex shader.

fragBytes [byte\[\]](#)

The compiled bytecode for the fragment shader.

constants [SpecializationConstant\[\]](#)

Optional specialization constants for shader customization.

Effect(GraphicsDevice, VertexLayoutDescription, string, string, SpecializationConstant[]?)

Initializes a new instance of the [Effect](#) class using shader file paths.

```
public Effect(GraphicsDevice graphicsDevice, VertexLayoutDescription vertexLayout, string vertPath, string fragPath, SpecializationConstant[]? constants = null)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for rendering.

vertexLayout [VertexLayoutDescription](#)

The [VertexLayoutDescription](#) defining the vertex structure.

vertPath [string](#)

The path to the vertex shader file.

fragPath [string](#)

The path to the fragment shader file.

constants [SpecializationConstant\[\]](#)

Optional specialization constants for shader customization.

Fields

Shader

Represents a pair of shaders consisting of a vertex shader and a fragment shader.

```
public readonly (Shader VertShader, Shader FragShader) Shader
```

Field Value

([Shader](#), [VertShader](#), [Shader](#), [FragShader](#))

ShaderSet

Represents a description of a shader set, including vertex layout details, shader information, and optional specialization constants.

```
public readonly ShaderSetDescription ShaderSet
```

Field Value

[ShaderSetDescription](#)

VertexLayout

Describes the layout of vertex data for a graphics pipeline.

```
public readonly VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#)

Properties

GraphicsDevice

The graphics device used for creating and managing graphical resources.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Methods

AddBufferLayout(string, uint, SimpleBufferType, ShaderStages)

Adds a new buffer layout to the effect with the specified parameters.

```
public void AddBufferLayout(string name, uint slot, SimpleBufferType bufferType,  
ShaderStages stages)
```

Parameters

name [string](#)

The name of the buffer layout to add. Must be unique within the effect.

slot [uint](#)

The slot index at which the buffer layout will be bound.

bufferType [SimpleBufferType](#)

The type of buffer being added, defined by the [SimpleBufferType](#) enum.

stages [ShaderStages](#)

The shader stages where the buffer will be accessible, specified by [ShaderStages](#).

Exceptions

[InvalidOperationException](#)

Thrown if a buffer layout with the specified name already exists.

AddTextureLayout(string, uint)

Adds a new texture layout to the effect with the specified parameters.

```
public void AddTextureLayout(string name, uint slot)
```

Parameters

name [string](#)

The unique name of the texture layout to add.

slot [uint](#)

The slot index where the texture layout will be bound.

Exceptions

[InvalidOperationException](#)

Thrown if a texture layout with the same name already exists.

Apply(CommandList, Material?)

Apply the state effect immediately before rendering it.

```
public virtual void Apply(CommandList commandList, Material? material = null)
```

Parameters

commandList [CommandList](#)

material [Material](#)

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

GetBufferLayout(string)

Retrieves the buffer layout identified by the specified name.

```
public SimpleBufferLayout GetBufferLayout(string name)
```

Parameters

`name` [string](#)

The name of the buffer layout to retrieve.

Returns

[SimpleBufferLayout](#)

The [SimpleBufferLayout](#) matching the specified name.

Exceptions

[KeyNotFoundException](#)

Thrown if no buffer layout with the specified name is found.

GetBufferLayoutSlot(string)

Retrieves the slot index of a buffer layout by its name.

```
public uint GetBufferLayoutSlot(string name)
```

Parameters

`name` [string](#)

The name of the buffer layout whose slot index is to be retrieved.

Returns

[uint](#)

The slot index of the specified buffer layout.

Exceptions

[KeyNotFoundException](#)

Thrown when the buffer layout with the specified name does not exist.

GetBufferLayouts()

Retrieves a collection of buffer layouts associated with the effect.

```
public IReadOnlyCollection<SimpleBufferLayout> GetBufferLayouts()
```

Returns

[IReadOnlyCollection](#)<[SimpleBufferLayout](#)>

A read-only collection of [SimpleBufferLayout](#) objects representing the buffer layouts.

GetPipeline(SimplePipelineDescription)

Retrieves or creates a pipeline for the given pipeline description.

```
public SimplePipeline GetPipeline(SimplePipelineDescription pipelineDescription)
```

Parameters

[pipelineDescription](#) [SimplePipelineDescription](#)

The description of the pipeline to retrieve or create.

Returns

[SimplePipeline](#)

A [SimplePipeline](#) configured with the specified description.

GetTextureLayout(string)

Retrieves a texture layout by its name from the list of available texture layouts.

```
public SimpleTextureLayout GetTextureLayout(string name)
```

Parameters

name [string](#) ↗

The name of the texture layout to retrieve.

Returns

[SimpleTextureLayout](#)

The [SimpleTextureLayout](#) matching the specified name.

Exceptions

[KeyNotFoundException](#) ↗

Thrown if no texture layout with the specified name is found.

GetTextureLayoutSlot(string)

Retrieves the texture slot index for the specified texture name in the effect's texture layouts.

```
public uint GetTextureLayoutSlot(string name)
```

Parameters

name [string](#) ↗

The name of the texture whose slot index is to be retrieved.

Returns

[uint](#)

The zero-based index of the texture slot corresponding to the specified texture name.

Exceptions

[KeyNotFoundException](#)

Thrown when the specified texture name does not exist in the texture layouts.

GetTextureLayouts()

Retrieves a collection of texture layouts associated with the effect.

```
public IReadOnlyCollection<SimpleTextureLayout> GetTextureLayouts()
```

Returns

[IReadOnlyCollection](#)<[SimpleTextureLayout](#)>

A read-only collection of [SimpleTextureLayout](#) objects representing the texture layouts.

LoadBytecode(string)

Loads the bytecode from the specified shader file path.

```
public static byte[] LoadBytecode(string path)
```

Parameters

[path](#) [string](#)

The file path to the shader source code.

Returns

[byte](#)[]

A byte array containing the bytecode from the shader file.

Namespace Bliss.CSharp.Fonts

Classes

[Font](#)

[FontStashRenderer2D](#)

[FontStashTextureManager](#)

Class Font

Namespace: [Bliss.CSharp.Fonts](#)

Assembly: Bliss.dll

```
public class Font : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Font

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Font(byte[], FontSystemSettings?)

Creates a new [Font](#) instance using the provided font data in memory.

```
public Font(byte[] data, FontSystemSettings? settings = null)
```

Parameters

data [byte](#)[]

A byte array containing the raw font data.

settings [FontSystemSettings](#)

Settings used to configure the internal font system.

Font(string, FontSystemSettings?)

Creates a new [Font](#) instance by loading font data from the specified file path.

```
public Font(string path, FontSystemSettings? settings = null)
```

Parameters

path [string](#)

The file path to the font file to load.

settings [FontSystemSettings](#)

Settings used to configure the internal font system.

Properties

FontData

Gets the byte array containing the raw font data.

```
public byte[] FontData { get; }
```

Property Value

[byte](#)[]

FontSystem

The font system used to manage and render fonts for the [Font](#) class.

```
public FontSystem FontSystem { get; }
```

Property Value

FontSystem

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

Draw(SpriteBatch, string, Vector2, float, float, float, Vector2?, float, Vector2?, float, Color?, TextStyle, FontSystemEffect, int)

Draws text using the specified parameters.

```
public void Draw(SpriteBatch batch, string text, Vector2 position, float size, float characterSpacing = 0, float lineSpacing = 0, Vector2? scale = null, float depth = 0.5, Vector2? origin = null, float rotation = 0, Color? color = null, TextStyle style = TextStyle.None, FontSystemEffect effect = FontSystemEffect.None, int effectAmount = 0)
```

Parameters

`batch` [SpriteBatch](#)

The sprite batch used for rendering.

`text` [string](#)

The text to be drawn.

`position` [Vector2](#)

The position where the text should be drawn.

`size` [float](#)

The size of the font.

characterSpacing [float](#)

The spacing between characters. Default is 0.0F.

lineSpacing [float](#)

The spacing between lines. Default is 0.0F.

scale [Vector2](#)?

The scaling factor for the text. Default is null.

depth [float](#)

The depth at which the text will be rendered. Default is 0.5F.

origin [Vector2](#)?

The origin for rotation and scaling. Default is null.

rotation [float](#)

The rotation angle for the text. Default is 0.0F.

color [Color](#)?

The color of the text. Default is white.

style TextStyle

The style of the text. Default is none.

effect FontSystemEffect

The effect to apply to the text. Default is none.

effectAmount [int](#)

The intensity of the applied effect. Default is 0.

GetSpriteFont(float)

Retrieves a FontStashSharp.DynamicSpriteFont object for the specified font size.

```
public DynamicSpriteFont GetSpriteFont(float fontSize)
```

Parameters

`fontSize float`

The desired font size for the retrieved sprite font.

Returns

DynamicSpriteFont

A FontStashSharp.DynamicSpriteFont instance corresponding to the specified font size.

MeasureText(string, float, Vector2?, float, float, FontSystemEffect, int)

Measures the dimensions of the specified text using the given font size and other parameters.

```
public Vector2 MeasureText(string text, float size, Vector2? scale = null, float characterSpacing = 0, float lineSpacing = 0, FontSystemEffect effect = FontSystemEffect.None, int effectAmount = 0)
```

Parameters

`text string`

The text to measure.

`size float`

The font size to use for measurement.

`scale Vector2?`

The scale to apply to the text, if any.

`characterSpacing float`

Spacing between characters, in pixels.

`lineSpacing float`

Spacing between lines, in pixels.

effect FontSystemEffect

Special visual effect to apply when measuring text.

effectAmount [int](#)

The intensity of the specified visual effect.

Returns

[Vector2](#)

A Vector2 representing the width and height of the text.

MeasureTextRect(string, float, Vector2?, float, float, FontSystemEffect, int)

Measures the rectangular bounds of the specified text with the given font size and additional text settings.

```
public RectangleF MeasureTextRect(string text, float size, Vector2? scale = null, float characterSpacing = 0, float lineSpacing = 0, FontSystemEffect effect = FontSystemEffect.None, int effectAmount = 0)
```

Parameters

text [string](#)

The text to be measured.

size [float](#)

The size of the font used for measurement.

scale [Vector2](#)?

Optional scale to be applied to the text. Defaults to null for no scaling.

characterSpacing [float](#)

Optional additional spacing between characters. Defaults to 0.0.

lineSpacing [float](#)

Optional additional spacing between lines. Defaults to 0.0.

effect FontSystemEffect

Optional font effect to apply. Defaults to FontStashSharp.FontSystemEffect.None.

effectAmount [int](#)

Optional intensity of the font effect. Defaults to 0.

Returns

[RectangleF](#)

A [RectangleF](#) representing the bounds of the measured text.

MeasureTextTrimmed(string, float, Vector2?, float, float, FontSystemEffect, int)

Measures the dimensions of the specified trimmed text using the provided font size.

```
public Vector2 MeasureTextTrimmed(string text, float size, Vector2? scale = null, float characterSpacing = 0, float lineSpacing = 0, FontSystemEffect effect = FontSystemEffect.None, int effectAmount = 0)
```

Parameters

text [string](#)

The text to measure.

size [float](#)

The size of the font.

scale [Vector2](#)?

An optional scaling factor for the text. Defaults to null.

characterSpacing [float](#)

The spacing between characters. Defaults to 0.0.

lineSpacing [float](#)

The spacing between lines. Defaults to 0.0.

effect [FontSystemEffect](#)

The text rendering effect to apply. Defaults to `FontStashSharp.FontSystemEffect.None`.

effectAmount [int](#)

The magnitude of the effect to apply. Defaults to 0.

Returns

[Vector2](#)

A [Vector2](#) representing the width and height of the trimmed text.

Class FontStashRenderer2D

Namespace: [Bliss.CSharp.Fonts](#)

Assembly: Bliss.dll

```
public class FontStashRenderer2D : Disposable, IDisposable, IFontStashRenderer
```

Inheritance

[object](#) ← [Disposable](#) ← FontStashRenderer2D

Implements

[IDisposable](#), IFontStashRenderer

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

FontStashRenderer2D(GraphicsDevice, SpriteBatch)

Initializes a new instance of the [FontStashRenderer2D](#) class.

```
public FontStashRenderer2D(GraphicsDevice graphicsDevice, SpriteBatch spriteBatch)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering.

spriteBatch [SpriteBatch](#)

The sprite batch used to draw textures.

Properties

GraphicsDevice

The graphics device used for rendering.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

SpriteBatch

The sprite batch used to draw font glyphs.

```
public SpriteBatch SpriteBatch { get; }
```

Property Value

[SpriteBatch](#)

TextureManager

Manages the texture used by the font renderer.

```
public ITexture2DManager TextureManager { get; }
```

Property Value

[ITexture2DManager](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

Draw(object, Vector2, Rectangle?, FSColor, float, Vector2, float)

Draws a font glyph texture at the specified position with the given rendering parameters.

```
public void Draw(object texture, Vector2 position, Rectangle? src, FSColor fsColor, float rotation, Vector2 scale, float depth)
```

Parameters

texture [object](#)

The texture object containing the glyph.

position [Vector2](#)

The screen position at which to render the texture.

src [Rectangle](#)?

An optional source rectangle within the texture to draw.

fsColor [FSColor](#)

The color to apply to the texture.

rotation [float](#)

The rotation to apply, in radians.

scale [Vector2](#)

The scaling factor to apply to the texture.

depth [float](#)

The depth value for draw ordering.

Class FontStashTextureManager

Namespace: [Bliss.CSharp.Fonts](#)

Assembly: Bliss.dll

```
public class FontStashTextureManager : Disposable, IDisposable, ITexture2DManager
```

Inheritance

[object](#) ← [Disposable](#) ← FontStashTextureManager

Implements

[IDisposable](#), ITexture2DManager

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

FontStashTextureManager(GraphicsDevice)

Initializes a new instance of the [FontStashTextureManager](#) class.

```
public FontStashTextureManager(GraphicsDevice graphicsDevice)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for texture operations.

Properties

GraphicsDevice

The graphics device used to create and manage textures.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Methods

CreateTexture(int, int)

Creates a new 2D texture with the specified dimensions.

```
public object CreateTexture(int width, int height)
```

Parameters

width [int](#)

The width of the texture.

height [int](#)

The height of the texture.

Returns

[object](#)

A new texture object.

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GetTextureSize([object](#))

Gets the size of the specified texture.

```
public Point GetTextureSize(object texture)
```

Parameters

[texture](#) [object](#)

The texture to query.

Returns

[Point](#)

A [Point](#) representing the width and height of the texture.

SetTextureData([object](#), [Rectangle](#), [byte](#)[])

Updates a region of the texture with the provided raw byte data.

```
public void SetTextureData(object texture, Rectangle bounds, byte[] data)
```

Parameters

[texture](#) [object](#)

The texture to update.

[bounds](#) [Rectangle](#)

The region of the texture to update.

[data](#) [byte](#)[]

The raw byte data to apply to the texture.

Namespace Bliss.CSharp.Geometry

Classes

[Mesh](#)

[Model](#)

Structs

[BoundingBox](#)

Struct BoundingBox

Namespace: [Bliss.CSharp.Geometry](#)

Assembly: Bliss.dll

```
public struct BoundingBox
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

BoundingBox(Vector3, Vector3)

Initializes a new instance of the [BoundingBox](#) struct with the specified minimum and maximum vectors.

```
public BoundingBox(Vector3 min, Vector3 max)
```

Parameters

min [Vector3](#)

The minimum vector defining one corner of the bounding box.

max [Vector3](#)

The maximum vector defining the opposite corner of the bounding box.

Fields

Max

Maximum box-corner.

```
public Vector3 Max
```

Field Value

[Vector3](#) ↗

Min

Minimum box-corner.

```
public Vector3 Min
```

Field Value

[Vector3](#) ↗

Class Mesh

Namespace: [Bliss.CSharp.Geometry](#)

Assembly: Bliss.dll

```
public class Mesh : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Mesh

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Mesh(GraphicsDevice, Material, Vertex3D[], uint[]?)

Initializes a new instance of the [Mesh](#) class with the specified properties.

```
public Mesh(GraphicsDevice graphicsDevice, Material material, Vertex3D[] vertices, uint[]?  
indices = null)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create buffers.

material [Material](#)

The material applied to the mesh.

vertices [Vertex3D\[\]](#)

The vertex data for the mesh.

`indices` [uint](#)[]

The index data defining triangle order (optional).

Fields

Material

The material used for rendering the mesh.

```
public Material Material
```

Field Value

[Material](#)

MaxBoneCount

The maximum number of bones supported for skeletal animations in a mesh.

```
public const int MaxBoneCount = 72
```

Field Value

[int](#)

Properties

GraphicsDevice

Represents the graphics device used for rendering operations. This property provides access to the underlying GraphicsDevice instance responsible for managing GPU resources and executing rendering commands.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#) ↗

HasBones

Indicates whether the mesh contains bone information.

```
public bool HasBones { get; }
```

Property Value

[bool](#) ↗

IndexBuffer

A buffer that stores index data used for indexed drawing in the graphics pipeline.

```
public DeviceBuffer? IndexBuffer { get; }
```

Property Value

[DeviceBuffer](#) ↗

IndexCount

The number of indices in the mesh used for rendering.

```
public uint IndexCount { get; }
```

Property Value

[uint](#) ↗

Indices

An array of indices that define the order in which vertices are drawn. Indices are used in conjunction with the vertex array to form geometric shapes such as triangles in a mesh. This allows for efficient reuse of vertex data.

```
public uint[] Indices { get; }
```

Property Value

[uint](#)[]

VertexBuffer

A buffer that stores vertex data used for rendering in the graphics pipeline.

```
public DeviceBuffer VertexBuffer { get; }
```

Property Value

[DeviceBuffer](#)[]

VertexCount

The total count of vertices present in the mesh. This value determines the number of vertices available for rendering within the mesh.

```
public uint VertexCount { get; }
```

Property Value

[uint](#)[]

Vertices

An array of Vertex3D structures that define the geometric points of a mesh. Each vertex contains attributes such as position, texture coordinates, normal, and optional color. Vertices are used to construct the shape and appearance of a 3D model.

```
public Vertex3D[] Vertices { get; }
```

Property Value

[Vertex3D\[\]](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GenBoundingBox()

Calculates the bounding box for the current mesh based on its vertices.

```
public BoundingBox GenBoundingBox()
```

Returns

[BoundingBox](#)

A BoundingBox object that encompasses all vertices of the mesh.

GenCapsule(GraphicsDevice, float, float, int)

Generates a capsule mesh with the specified radius, height, and number of slices.

```
public static Mesh GenCapsule(GraphicsDevice graphicsDevice, float radius, float height, int slices)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create and manage the mesh's GPU resources.

radius [float](#)

The radius of the capsule.

height [float](#)

The cylindrical midsection's height of the capsule.

slices [int](#)

The number of slices used to approximate the capsule. Must be at least 3.

Returns

[Mesh](#)

A [Mesh](#) representing a capsule with the given parameters.

GenCone(GraphicsDevice, float, float, int)

Generates a 3D cone mesh with a specified radius, height, and number of slices.

```
public static Mesh GenCone(GraphicsDevice graphicsDevice, float radius, float height, int slices)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used to manage GPU resources for the mesh.

radius [float](#)

The radius of the cone's base.

height [float](#)

The height of the cone from base to tip.

slices [int](#)

The number of slices dividing the circular base. Must be at least 3.

Returns

[Mesh](#)

A new instance of the [Mesh](#) class representing the generated cone.

GenCube(GraphicsDevice, float, float, float)

Generates a cuboid mesh with the specified dimensions and initializes it with default material and texture settings.

```
public static Mesh GenCube(GraphicsDevice graphicsDevice, float width, float height,  
float length)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device that manages GPU resources for the mesh.

width [float](#)

The width of the cuboid.

height [float](#)

The height of the cuboid.

length [float](#)

The length of the cuboid.

Returns

[Mesh](#)

A new instance of the [Mesh](#) class representing the cuboid.

GenCylinder(GraphicsDevice, float, float, int)

Generates a cylindrical mesh with specified dimensions and resolution.

```
public static Mesh GenCylinder(GraphicsDevice graphicsDevice, float radius, float height, int slices)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) responsible for managing GPU resources.

radius [float](#)

The radius of the cylinder's base and top.

height [float](#)

The height of the cylinder.

slices [int](#)

The number of slices (or segments) used to approximate the cylinder. Must be at least 3.

Returns

[Mesh](#)

A new instance of [Mesh](#) representing the generated cylindrical geometry.

GenHeightmap(GraphicsDevice, Image, Vector3)

Generates a heightmap-based 3D mesh from the given heightmap image and dimensions.

```
public static Mesh GenHeightmap(GraphicsDevice graphicsDevice, Image heightmap, Vector3 size)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for managing GPU resources and rendering the generated mesh.

heightmap [Image](#)

The heightmap image used to determine the height of each vertex in the mesh.

size [Vector3](#)

The 3D size of the heightmap mesh in world units, where X and Z represent the width and depth, and Y represents the height scale.

Returns

[Mesh](#)

A new [Mesh](#) instance representing the generated heightmap mesh based on the input parameters.

GenHemisphere(GraphicsDevice, float, int, int)

Generates a 3D hemisphere mesh with a specified radius, number of rings, and slices.

```
public static Mesh GenHemisphere(GraphicsDevice graphicsDevice, float radius, int rings, int slices)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) instance used to allocate GPU resources for the mesh.

radius [float](#)

The radius of the hemisphere.

rings [int](#)

The number of subdivisions along the vertical (Y-axis) direction of the hemisphere.

slices [int](#)

The number of subdivisions around the horizontal (XZ-plane) direction of the hemisphere.

Returns

[Mesh](#)

A new instance of the [Mesh](#) class representing the generated hemisphere model.

GenKnot(GraphicsDevice, float, float, int, int)

Generates a torus knot mesh with the specified parameters.

```
public static Mesh GenKnot(GraphicsDevice graphicsDevice, float radius, float tubeRadius,  
int radSeg, int sides)
```

Parameters

[graphicsDevice](#) [GraphicsDevice](#)

The [GraphicsDevice](#) used to manage GPU resources for the mesh.

[radius](#) [float](#)

The radius of the torus knot.

[tubeRadius](#) [float](#)

The thickness of the tube forming the torus knot.

[radSeg](#) [int](#)

The number of radial segments for the torus knot. The minimum value is 3.

[sides](#) [int](#)

The number of sides forming the cross-section of the tube. The minimum value is 3.

Returns

[Mesh](#)

A [Mesh](#) representing the torus knot with the specified parameters.

GenPoly(GraphicsDevice, int, float)

Generates a 3D polygon mesh with the specified number of sides and radius.

```
public static Mesh GenPoly(GraphicsDevice graphicsDevice, int sides, float radius)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to manage GPU resources for the generated mesh.

sides [int](#)

The number of sides of the polygon. Must be at least 3.

radius [float](#)

The radius of the polygon.

Returns

[Mesh](#)

A new instance of the [Mesh](#) class representing the 3D polygon.

GenSphere(GraphicsDevice, float, int, int)

Generates a sphere mesh with the specified radius, rings, and slices.

```
public static Mesh GenSphere(GraphicsDevice graphicsDevice, float radius, int rings, int slices)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create and manage the GPU resources needed for the mesh.

radius [float](#)

The radius of the sphere.

rings [int](#)

The number of horizontal segments dividing the sphere.

slices [int](#)

The number of vertical segments dividing the sphere.

Returns

[Mesh](#)

A new instance of the [Mesh](#) class representing the generated sphere.

GenTangents()

Generates tangent vectors for the mesh's vertices based on the provided geometric and UV coordinate data.

```
public void GenTangents()
```

GenTorus(GraphicsDevice, float, float, int, int)

Generates a torus-shaped mesh with specified dimensions and detail.

```
public static Mesh GenTorus(GraphicsDevice graphicsDevice, float radius, float size, int radSeg, int sides)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for managing GPU resources.

radius [float](#)

The radius of the torus from the center to the middle of the tube.

size [float](#)

The thickness of the torus tube.

radSeg [int ↗](#)

The number of radial segments in the torus.

sides [int ↗](#)

The number of segments around the tube's circular cross-section.

Returns

[Mesh](#)

A new instance of [Mesh](#) representing the generated torus.

SetIndexValue(int, uint)

Sets the index value in the mesh's index buffer at the specified position.

```
public void SetIndexValue(int index, uint value)
```

Parameters

index [int ↗](#)

The position in the index buffer to set the value.

value [uint ↗](#)

The value to assign to the specified index position.

SetIndexValueDeferred(CommandList, int, uint)

Updates the value of an index in the deferred rendering pipeline and applies the changes to the index buffer.

```
public void SetIndexValueDeferred(CommandList commandList, int index, uint value)
```

Parameters

commandList [CommandList ↗](#)

The command list used for recording GPU commands.

index [int](#)

The index of the element to be updated.

value [uint](#)

The new value to assign to the specified index.

SetIndexValueImmediate(int, uint)

Sets the value of an index in the index buffer and updates the buffer immediately.

```
public void SetIndexValueImmediate(int index, uint value)
```

Parameters

index [int](#)

The position in the index buffer to be updated.

value [uint](#)

The new index value to be set at the specified position.

SetVertexValue(int, Vertex3D)

Sets the value of a vertex at a specified index.

```
public void SetVertexValue(int index, Vertex3D value)
```

Parameters

index [int](#)

The index of the vertex to set.

value [Vertex3D](#)

The new value to assign to the vertex.

SetVertexValueDeferred(CommandList, int, Vertex3D)

Updates the vertex buffer with a new vertex value at the specified index in a deferred manner, using the provided command list.

```
public void SetVertexValueDeferred(CommandList commandList, int index, Vertex3D value)
```

Parameters

commandList [CommandList](#)

The [CommandList](#) used to issue the update commands.

index [int](#)

The index of the vertex to update.

value [Vertex3D](#)

The new [Vertex3D](#) value to set at the specified index.

SetVertexValueImmediate(int, Vertex3D)

Sets the vertex value at the specified index and updates the vertex buffer immediately.

```
public void SetVertexValueImmediate(int index, Vertex3D value)
```

Parameters

index [int](#)

The index at which the vertex value will be set.

value [Vertex3D](#)

The new vertex value to set at the specified index.

UpdateIndexBuffer(CommandList)

Updates the index buffer with the current index data on the specified command list.

```
public void UpdateIndexBuffer(CommandList commandList)
```

Parameters

commandList [CommandList](#)

The command list used to update the index buffer.

UpdateIndexBufferImmediate()

Updates the index buffer of the mesh immediately with the current index data.

```
public void UpdateIndexBufferImmediate()
```

UpdateVertexBuffer(CommandList)

Updates the vertex buffer with the current vertex data using the specified command list.

```
public void UpdateVertexBuffer(CommandList commandList)
```

Parameters

commandList [CommandList](#)

The command list used to update the vertex buffer.

UpdateVertexBufferImmediate()

Updates the vertex buffer with the current vertex data immediately on the GPU.

```
public void UpdateVertexBufferImmediate()
```

Class Model

Namespace: [Bliss.CSharp.Geometry](#)

Assembly: Bliss.dll

```
public class Model : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Model

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Model(GraphicsDevice, Mesh[], Skeleton?, ModelAnimation[])

Initializes a new instance of the [Model](#) class with the specified graphics device, meshes, and animations.

```
public Model(GraphicsDevice graphicsDevice, Mesh[] meshes, Skeleton? skeleton,  
ModelAnimation[] animations)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for rendering and resource management.

meshes [Mesh](#)[]

An array of [Mesh](#) objects representing the geometric components of the model.

skeleton [Skeleton](#)

The optional skeleton used for skeletal animation, or `null` if not present.

animations [ModelAnimation\[\]](#)

An array of [ModelAnimation](#) objects defining the animations for the model.

Properties

Animations

Collection of animations associated with the model.

```
public ModelAnimation[] Animations { get; }
```

Property Value

[ModelAnimation\[\]](#)

GraphicsDevice

The graphics device used for rendering the model.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#) ↗

Meshes

An array of meshes that make up the model.

```
public Mesh[] Meshes { get; }
```

Property Value

[Mesh\[\]](#)

Skeleton

The hierarchical skeletal structure of the model.

```
public Skeleton? Skeleton { get; }
```

Property Value

[Skeleton](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

GenBoundingBox()

Generates a bounding box that encapsulates all the vertices in the model's meshes.

```
public BoundingBox GenBoundingBox()
```

Returns

[BoundingBox](#)

A [BoundingBox](#) that represents the minimum and maximum bounds of the model.

Load(GraphicsDevice, string, bool, bool)

Loads a model from the specified file path using the provided graphics device and configuration options.

```
public static Model Load(GraphicsDevice graphicsDevice, string path, bool loadMaterial = true, bool flipUv = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering and managing model resources.

path [string](#)

The file path to the model to be loaded.

loadMaterial [bool](#)

Specifies whether the material should be loaded with the model. Default is true.

flipUv [bool](#)

Determines whether the UV coordinates of the model should be flipped. Default is false.

Returns

[Model](#)

Returns a new instance of the [Model](#) class containing the loaded meshes and animations.

Namespace Bliss.CSharp.Geometry.Animation

Classes

[BoneInfo](#)

[ModelAnimation](#)

[NodeAnimChannel](#)

[Skeleton](#)

Class BoneInfo

Namespace: [Bliss.CSharp.Geometry.Animation](#)

Assembly: Bliss.dll

```
public class BoneInfo
```

Inheritance

[object](#) ← BoneInfo

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

BoneInfo(string, uint, Matrix4x4)

Initializes a new instance of the [BoneInfo](#) class with the specified name, ID, and transformation.

```
public BoneInfo(string name, uint id, Matrix4x4 transformation)
```

Parameters

name [string](#)

The name of the bone.

id [uint](#)

The unique identifier of the bone.

transformation [Matrix4x4](#)

The transformation matrix for the bone.

Properties

Id

The unique identifier of the bone.

```
public uint Id { get; }
```

Property Value

[uint](#)

Name

The name of the bone.

```
public string Name { get; }
```

Property Value

[string](#)

Transformation

The transformation matrix representing the bone's transformation in the skeleton hierarchy.

```
public Matrix4x4 Transformation { get; }
```

Property Value

[Matrix4x4](#)

Class ModelAnimation

Namespace: [Bliss.CSharp.Geometry.Animation](#)

Assembly: Bliss.dll

```
public class ModelAnimation
```

Inheritance

[object](#) ← ModelAnimation

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ModelAnimation(string, float, float, int,
 IReadOnlyList<NodeAnimChannel>, IReadOnlyDictionary<int,
 Matrix4x4[]>)

Initializes a new instance of the [ModelAnimation](#) class with the specified properties and animation channels.

```
public ModelAnimation(string name, float durationInTicks, float ticksPerSecond,  
 int frameCount, IReadOnlyList<NodeAnimChannel> channels, IReadOnlyDictionary<int,  
 Matrix4x4[]> boneFrameTransformations)
```

Parameters

name [string](#)

The name of the animation.

durationInTicks [float](#)

The total duration of the animation in ticks.

ticksPerSecond [float](#)

The number of ticks per second, determining playback speed.

frameCount [int](#)

The total number of frames in the animation.

channels [IReadOnlyList](#)<[NodeAnimChannel](#)>

The list of animation channels associated with this animation.

boneFrameTransformations [IReadOnlyDictionary](#)<[int](#), [Matrix4x4](#)[]>

The dictionary containing the precomputed transformations for each bone at each animation frame.

Properties

AnimationChannels

A list of animation channels that define the per-node transformations during the animation.

```
public IReadOnlyList<NodeAnimChannel> AnimationChannels { get; }
```

Property Value

[IReadOnlyList](#)<[NodeAnimChannel](#)>

BoneFrameTransformations

A dictionary containing the precomputed transformations for each bone at each animation frame.

```
public IReadOnlyDictionary<int, Matrix4x4[]> BoneFrameTransformations { get; }
```

Property Value

[IReadOnlyDictionary](#)<[int](#), [Matrix4x4](#)[]>

DurationInTicks

The total duration of the animation in ticks.

```
public float DurationInTicks { get; }
```

Property Value

[float ↗](#)

FrameCount

The total number of frames in the animation, calculated based on duration and ticks per second.

```
public int FrameCount { get; }
```

Property Value

[int ↗](#)

Name

The name of the animation.

```
public string Name { get; }
```

Property Value

[string ↗](#)

TicksPerSecond

The number of ticks per second for the animation, determining its playback speed.

```
public float TicksPerSecond { get; }
```

Property Value

[float ↗](#)

Class NodeAnimChannel

Namespace: [Bliss.CSharp.Geometry.Animation](#)

Assembly: Bliss.dll

```
public class NodeAnimChannel
```

Inheritance

[object](#) ← NodeAnimChannel

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

NodeAnimChannel(string, IReadOnlyList<Vector3Key>, IReadOnlyList<QuatKey>, IReadOnlyList<Vector3Key>)

Initializes a new instance of the [NodeAnimChannel](#) class with the specified name, positions, rotations, and scales.

```
public NodeAnimChannel(string name, IReadOnlyList<Vector3Key> positions,  
IReadOnlyList<QuatKey> rotations, IReadOnlyList<Vector3Key> scales)
```

Parameters

name [string](#)

The name of the node being animated.

positions [IReadOnlyList](#)<[Vector3Key](#)>

A list of [Vector3Key](#) representing position keyframes.

rotations [IReadOnlyList](#)<[QuatKey](#)>

A list of [QuatKey](#) representing rotation keyframes.

scales [IReadOnlyList](#)<[Vector3Key](#)>

A list of [Vector3Key](#) representing scale keyframes.

Properties

Name

The name of the node being animated.

```
public string Name { get; }
```

Property Value

[string](#)

Positions

A list of [Vector3Key](#) representing the position keyframes for the node.

```
public IReadOnlyList<Vector3Key> Positions { get; }
```

Property Value

[IReadOnlyList](#)<[Vector3Key](#)>

Rotations

A list of [QuatKey](#) representing the rotation keyframes (quaternions) for the node.

```
public IReadOnlyList<QuatKey> Rotations { get; }
```

Property Value

[IReadOnlyList](#)<[QuatKey](#)>

Scales

A list of [Vector3Key](#) representing the scale keyframes for the node.

```
public IReadOnlyList<Vector3Key> Scales { get; }
```

Property Value

[IReadOnlyList](#) <[Vector3Key](#)>

Class Skeleton

Namespace: [Bliss.CSharp.Geometry.Animation](#)

Assembly: Bliss.dll

```
public class Skeleton
```

Inheritance

[object](#) ← Skeleton

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Skeleton(IReadOnlyList<BoneInfo>)

Initializes a new instance of the [Skeleton](#) class.

```
public Skeleton(IReadOnlyList<BoneInfo> bones)
```

Parameters

bones [IReadOnlyList](#)<[BoneInfo](#)>

The list of bones that define the skeleton.

Properties

BoneNameToIndex

A dictionary mapping bone names to their corresponding indices in the [Bones](#) list.

```
public IReadOnlyDictionary<string, uint> BoneNameToIndex { get; }
```

Property Value

[IReadOnlyDictionary](#)<[string](#), [uint](#)>

Bones

The list of bones that make up the skeleton.

```
public IReadOnlyList<BoneInfo> Bones { get; }
```

Property Value

[IReadOnlyList](#)<[BoneInfo](#)>

Namespace Bliss.CSharp.Geometry.AnimationBuilders

Classes

[ModelAnimationBuilder](#)

[SkeletonBuilder](#)

Class ModelAnimationBuilder

Namespace: [Bliss.CSharp.Geometry.AnimationBuilders](#)

Assembly: Bliss.dll

```
public class ModelAnimationBuilder
```

Inheritance

[object](#) ← ModelAnimationBuilder

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ModelAnimationBuilder(Node, Skeleton, Animation)

Initializes a new instance of the [ModelAnimationBuilder](#) class.

```
public ModelAnimationBuilder(Node rootNode, Skeleton skeleton, Animation animation)
```

Parameters

rootNode Node

The root node of the model hierarchy.

skeleton [Skeleton](#)

The skeleton associated with the model.

animation Animation

The raw Assimp animation data to convert.

Methods

Build()

Builds a [ModelAnimation](#) by processing the animation channels and baking bone transformations for all frames.

```
public ModelAnimation Build()
```

Returns

[ModelAnimation](#)

A fully constructed [ModelAnimation](#) containing per-frame bone transformations.

Class SkeletonBuilder

Namespace: [Bliss.CSharp.Geometry.AnimationBuilders](#)

Assembly: Bliss.dll

```
public class SkeletonBuilder
```

Inheritance

[object](#) ← SkeletonBuilder

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

SkeletonBuilder(Scene)

Initializes a new instance of the [SkeletonBuilder](#) class.

```
public SkeletonBuilder(Scene scene)
```

Parameters

scene Scene

The Assimp scene that contains the bone and mesh data.

Methods

Build()

Builds a [Skeleton](#) by collecting unique bones from the scene's meshes.

```
public Skeleton Build()
```

Returns

Skeleton

A [Skeleton](#) containing the collected bones and their offset matrices.

Namespace Bliss.CSharp.Geometry.Animation.Keyframes

Structs

[QuatKey](#)

[Vector3Key](#)

Struct QuatKey

Namespace: [Bliss.CSharp.Geometry.Animation.Keyframes](#)

Assembly: Bliss.dll

```
public struct QuatKey : IEquatable<QuatKey>
```

Implements

[IEquatable](#)<[QuatKey](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

QuatKey(double, Quaternion)

Initializes a new instance of the [QuatKey](#) struct with the specified time and value.

```
public QuatKey(double time, Quaternion value)
```

Parameters

time [double](#)

The time of the keyframe.

value [Quaternion](#)

The quaternion value (e.g., rotation) at the specified time.

Fields

Time

The time at which this keyframe occurs.

```
public double Time
```

Field Value

[double](#)

Value

The quaternion value (e.g., rotation) at the specified time.

```
public Quaternion Value
```

Field Value

[Quaternion](#)

Methods

Equals(QuatKey)

Compares this [QuatKey](#) to another for equality based on their quaternion value.

```
public bool Equals(QuatKey other)
```

Parameters

other [QuatKey](#)

The other [QuatKey](#) to compare.

Returns

[bool](#)

Returns true if the quaternion values of both keys are equal, otherwise false.

Equals(object?)

Compares this [QuatKey](#) to another object for equality.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare to.

Returns

[bool](#)

Returns true if the object is a [QuatKey](#) and has the same quaternion value.

GetHashCode()

Generates a hash code based on the quaternion value of the [QuatKey](#).

```
public override int GetHashCode()
```

Returns

[int](#)

The hash code for this key.

ToString()

Returns a string representation of the [QuatKey](#) including its time and quaternion value.

```
public override string ToString()
```

Returns

[string](#)

A string representing the [QuatKey](#).

Operators

operator ==(QuatKey, QuatKey)

Compares two [QuatKey](#) instances for equality based on their quaternion value.

```
public static bool operator ==(QuatKey left, QuatKey right)
```

Parameters

left [QuatKey](#)

The first [QuatKey](#) to compare.

right [QuatKey](#)

The second [QuatKey](#) to compare.

Returns

[bool](#)

Returns true if the quaternion values of both keys are equal, otherwise false.

operator >(QuatKey, QuatKey)

Compares two [QuatKey](#) instances to see if the first occurs after the second based on their time.

```
public static bool operator >(QuatKey left, QuatKey right)
```

Parameters

left [QuatKey](#)

The first [QuatKey](#) to compare.

right [QuatKey](#)

The second [QuatKey](#) to compare.

Returns

[bool](#) ↗

Returns true if the first key occurs after the second key in time.

operator !=(QuatKey, QuatKey)

Compares two [QuatKey](#) instances for inequality based on their quaternion value.

```
public static bool operator !=(QuatKey left, QuatKey right)
```

Parameters

left [QuatKey](#)

The first [QuatKey](#) to compare.

right [QuatKey](#)

The second [QuatKey](#) to compare.

Returns

[bool](#) ↗

Returns true if the quaternion values of both keys are not equal, otherwise false.

operator <(QuatKey, QuatKey)

Compares two [QuatKey](#) instances to see if the first occurs before the second based on their time.

```
public static bool operator <(QuatKey left, QuatKey right)
```

Parameters

left [QuatKey](#)

The first [QuatKey](#) to compare.

right [QuatKey](#)

The second [QuatKey](#) to compare.

Returns

[bool](#) ↗

Returns true if the first key occurs before the second key in time.

Struct Vector3Key

Namespace: [Bliss.CSharp.Geometry.Animation.Keyframes](#)

Assembly: Bliss.dll

```
public struct Vector3Key : IEquatable<Vector3Key>
```

Implements

[IEquatable](#) <[Vector3Key](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Vector3Key(double, Vector3)

Initializes a new instance of the [Vector3Key](#) struct with the specified time and value.

```
public Vector3Key(double time, Vector3 value)
```

Parameters

time [double](#)

The time of the keyframe.

value [Vector3](#)

The 3D vector value at the specified time.

Fields

Time

The time at which this keyframe occurs.

```
public double Time
```

Field Value

[double](#)

Value

The 3D vector value (e.g., position, rotation) at the specified time.

```
public Vector3 Value
```

Field Value

[Vector3](#)

Methods

Equals(Vector3Key)

Compares this [Vector3Key](#) to another for equality based on their value.

```
public bool Equals(Vector3Key other)
```

Parameters

other [Vector3Key](#)

The other [Vector3Key](#) to compare.

Returns

[bool](#)

Returns true if the value of both keys are equal, otherwise false.

Equals(object?)

Compares this [Vector3Key](#) to another object for equality.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare to.

Returns

[bool](#)

Returns true if the object is a [Vector3Key](#) and has the same value.

GetHashCode()

Generates a hash code based on the value of the [Vector3Key](#).

```
public override int GetHashCode()
```

Returns

[int](#)

The hash code for this key.

ToString()

Returns a string representation of the [Vector3Key](#) including its time and value.

```
public override string ToString()
```

Returns

[string](#)

A string representing the [Vector3Key](#).

Operators

operator ==(Vector3Key, Vector3Key)

Compares two [Vector3Key](#) instances for equality based on their value.

```
public static bool operator ==(Vector3Key left, Vector3Key right)
```

Parameters

left [Vector3Key](#)

The first [Vector3Key](#) to compare.

right [Vector3Key](#)

The second [Vector3Key](#) to compare.

Returns

[bool](#)

Returns true if the value of both keys are equal, otherwise false.

operator >(Vector3Key, Vector3Key)

Compares two [Vector3Key](#) instances to see if the first occurs after the second based on their time.

```
public static bool operator >(Vector3Key left, Vector3Key right)
```

Parameters

left [Vector3Key](#)

The first [Vector3Key](#) to compare.

right [Vector3Key](#)

The second [Vector3Key](#) to compare.

Returns

[bool](#) ↗

Returns true if the first key occurs after the second key in time.

operator !=(Vector3Key, Vector3Key)

Compares two [Vector3Key](#) instances for inequality based on their value.

```
public static bool operator !=(Vector3Key left, Vector3Key right)
```

Parameters

left [Vector3Key](#)

The first [Vector3Key](#) to compare.

right [Vector3Key](#)

The second [Vector3Key](#) to compare.

Returns

[bool](#) ↗

Returns true if the value of both keys are not equal, otherwise false.

operator <(Vector3Key, Vector3Key)

Compares two [Vector3Key](#) instances to see if the first occurs before the second based on their time.

```
public static bool operator <(Vector3Key left, Vector3Key right)
```

Parameters

left [Vector3Key](#)

The first [Vector3Key](#) to compare.

right [Vector3Key](#)

The second [Vector3Key](#) to compare.

Returns

[bool](#) ↗

Returns true if the first key occurs before the second key in time.

Namespace Bliss.CSharp.Graphics

Classes

[GraphicsHelper](#)

Enums

[SamplerType](#)

Class GraphicsHelper

Namespace: [Bliss.CSharp.Graphics](#)

Assembly: Bliss.dll

```
public static class GraphicsHelper
```

Inheritance

[object](#) ← GraphicsHelper

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

GetSampler(GraphicsDevice, SamplerType)

Retrieves a Sampler object based on the provided SamplerType.

```
public static Sampler GetSampler(GraphicsDevice graphicsDevice, SamplerType samplerType)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create the sampler.

samplerType [SamplerType](#)

The type of sampler to retrieve.

Returns

[Sampler](#)

A Sampler object corresponding to the specified SamplerType.

Exceptions

[ArgumentException](#)

Thrown when an unsupported sampler type is provided.

Enum SamplerType

Namespace: [Bliss.CSharp.Graphics](#)

Assembly: Bliss.dll

```
public enum SamplerType
```

Fields

Aniso4XClamp = 4

Uses 4x anisotropic filtering with clamped texture coordinates for improved texture quality at oblique viewing angles.

Aniso4XWrap = 5

Uses 4x anisotropic filtering with wrapping texture coordinates for improved texture quality at oblique viewing angles.

LinearClamp = 2

Uses linear (bilinear) filtering with clamped texture coordinates.

LinearWrap = 3

Uses linear (bilinear) filtering with wrapping texture coordinates.

PointClamp = 0

Uses point (nearest neighbor) filtering with clamped texture coordinates.

PointWrap = 1

Uses point (nearest neighbor) filtering with wrapping texture coordinates.

Namespace Bliss.CSharp.Graphics.Pipelines

Classes

[SimplePipeline](#)

Structs

[SimplePipelineDescription](#)

Class SimplePipeline

Namespace: [Bliss.CSharp.Graphics.Pipelines](#)

Assembly: Bliss.dll

```
public class SimplePipeline : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← SimplePipeline

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

SimplePipeline(GraphicsDevice, SimplePipelineDescription)

Initializes a new instance of the [SimplePipeline](#) class using the provided graphics device and pipeline description.

```
public SimplePipeline(GraphicsDevice graphicsDevice, SimplePipelineDescription  
pipelineDescription)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device that will be used to create the pipeline.

pipelineDescription [SimplePipelineDescription](#)

The description of the pipeline, containing configurations like blend state, shader set, and resource layouts.

Fields

PipelineDescription

Contains the configuration details for setting up a graphics pipeline, including states and resource layouts.

```
public SimplePipelineDescription PipelineDescription
```

Field Value

[SimplePipelineDescription](#)

Properties

GraphicsDevice

Represents the graphics device used by the pipeline for creating and managing graphics resources.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Pipeline

Represents the graphics pipeline used to render graphics objects.

```
public Pipeline Pipeline { get; }
```

Property Value

[Pipeline](#)

ResourceLayouts

Represents the array of resource layouts used by the pipeline to manage buffer and texture resources.

```
public ResourceLayout[] ResourceLayouts { get; }
```

Property Value

[ResourceLayout](#)[]

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GetBufferLayout(string)

Retrieves a buffer layout from the pipeline description by its name.

```
public SimpleBufferLayout? GetBufferLayout(string name)
```

Parameters

name [string](#)

The name of the buffer layout to retrieve.

Returns

[SimpleBufferLayout](#)

A [SimpleBufferLayout](#) object if a matching buffer layout is found; otherwise, null.

GetTextureLayout(string)

Retrieves the [SimpleTextureLayout](#) with the specified name from the pipeline description's texture layouts.

```
public SimpleTextureLayout? GetTextureLayout(string name)
```

Parameters

name [string](#) ↗

The name of the texture layout to retrieve.

Returns

[SimpleTextureLayout](#)

The [SimpleTextureLayout](#) if a matching layout is found; otherwise, null.

Struct SimplePipelineDescription

Namespace: [Bliss.CSharp.Graphics.Pipelines](#)

Assembly: Bliss.dll

```
public struct SimplePipelineDescription : IEquatable<SimplePipelineDescription>
```

Implements

[IEquatable](#)<[SimplePipelineDescription](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

SimplePipelineDescription()

Initializes a new instance of the [SimplePipelineDescription](#) struct.

```
public SimplePipelineDescription()
```

SimplePipelineDescription(BlendStateDescription, DepthStencilStateDescription, RasterizerStateDescription, PrimitiveTopology, List<SimpleBufferLayout>, List<SimpleTextureLayout>, ShaderSetDescription, OutputDescription)

Initializes a new instance of the [SimplePipelineDescription](#) struct with the provided pipeline configuration details.

```
public SimplePipelineDescription(BlendStateDescription blendState,  
DepthStencilStateDescription depthStencilState, RasterizerStateDescription  
rasterizerState, PrimitiveTopology primitiveTopology, List<SimpleBufferLayout>  
bufferLayouts, List<SimpleTextureLayout> textureLayouts, ShaderSetDescription shaderSet,  
OutputDescription outputs)
```

Parameters

blendState [BlendStateDescription](#)

The blend state configuration of the pipeline.

depthStencilState [DepthStencilStateDescription](#)

The depth and stencil state configuration of the pipeline.

rasterizerState [RasterizerStateDescription](#)

The rasterizer state configuration of the pipeline.

primitiveTopology [PrimitiveTopology](#)

The primitive topology that defines how vertex data is interpreted.

bufferLayouts [List](#) <[SimpleBufferLayout](#)>

A list of buffer layouts to be used by the pipeline.

textureLayouts [List](#) <[SimpleTextureLayout](#)>

A list of texture layouts to be used in the pipeline.

shaderSet [ShaderSetDescription](#)

The shader set description that defines the vertex and fragment shaders.

outputs [OutputDescription](#)

The output configuration of the pipeline, specifying the render targets and depth-stencil buffer.

Fields

BlendState

Configuration for how colors are blended during rendering.

```
public BlendStateDescription BlendState
```

Field Value

[BlendStateDescription](#)

BufferLayouts

Describes how vertex buffers are structured and laid out.

```
public IReadOnlyCollection<SimpleBufferLayout> BufferLayouts
```

Field Value

[IReadOnlyCollection](#) <[SimpleBufferLayout](#)>

DepthStencilState

Configuration for depth testing and stencil operations.

```
public DepthStencilStateDescription DepthStencilState
```

Field Value

[DepthStencilStateDescription](#)

Outputs

Specifies the render targets and optional depth-stencil buffer.

```
public OutputDescription Outputs
```

Field Value

[OutputDescription](#)

PrimitiveTopology

Specifies how the input vertices are assembled into primitives (e.g., triangles, lines).

```
public PrimitiveTopology PrimitiveTopology
```

Field Value

[PrimitiveTopology](#) ↗

RasterizerState

Configuration for rasterization, including culling and fill modes.

```
public RasterizerStateDescription RasterizerState
```

Field Value

[RasterizerStateDescription](#) ↗

ResourceBindingModel

Optional model describing how resources (textures, buffers) are mapped to the pipeline.

```
public ResourceBindingModel? ResourceBindingModel
```

Field Value

[ResourceBindingModel](#) ↗?

ShaderSet

Contains the vertex and fragment shaders used by the pipeline.

```
public ShaderSetDescription ShaderSet
```

Field Value

[ShaderSetDescription](#) ↗

TextureLayouts

Describes how textures are bound and accessed in the pipeline.

```
public IReadOnlyCollection<SimpleTextureLayout> TextureLayouts
```

Field Value

[IReadOnlyCollection](#) <[SimpleTextureLayout](#)>

Methods

Equals(SimplePipelineDescription)

Determines whether the current [SimplePipelineDescription](#) instance is equal to another specified instance.

```
public bool Equals(SimplePipelineDescription other)
```

Parameters

other [SimplePipelineDescription](#)

The other [SimplePipelineDescription](#) instance to compare with the current instance.

Returns

[bool](#)

A boolean value indicating whether the two instances are equal.

Equals(object?)

Determines whether the specified object is equal to the current [SimplePipelineDescription](#) instance.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current instance.

Returns

[bool](#)

A boolean value indicating whether the specified object is equal to the current instance.

GetHashCode()

Returns a hash code for this instance of [SimplePipelineDescription](#).

```
public override int GetHashCode()
```

Returns

[int](#)

A 32-bit signed integer hash code that is representative of the object's current state and its members.

ToString()

Returns a string representation of the [SimplePipelineDescription](#) instance, detailing its configuration and properties.

```
public override string ToString()
```

Returns

[string](#)

A string that includes the blend state, depth-stencil state, rasterizer state, primitive topology, buffers, texture layouts, shader set, outputs, and resource binding model of the pipeline description.

Operators

operator ==(SimplePipelineDescription, SimplePipelineDescription)

Determines whether two [SimplePipelineDescription](#) instances are equal based on their properties.

```
public static bool operator ==(SimplePipelineDescription left, SimplePipelineDescription right)
```

Parameters

left [SimplePipelineDescription](#)

The first [SimplePipelineDescription](#) instance to compare.

right [SimplePipelineDescription](#)

The second [SimplePipelineDescription](#) instance to compare.

Returns

[bool](#) ↗

true if the instances are equal; otherwise, **false**.

operator !=(SimplePipelineDescription, SimplePipelineDescription)

Determines whether two [SimplePipelineDescription](#) instances are equal.

```
public static bool operator !=(SimplePipelineDescription left, SimplePipelineDescription right)
```

Parameters

left [SimplePipelineDescription](#)

The first [SimplePipelineDescription](#) to compare.

right [SimplePipelineDescription](#)

The second [SimplePipelineDescription](#) to compare.

Returns

bool ↗

True if both instances are equal; otherwise, false.

Namespace Bliss.CSharp.Graphics.Pipelines.Buffers

Classes

[SimpleBufferLayout](#)

[SimpleStructuredBuffer<THeader, TElement>](#)

[SimpleUniformBuffer<T>](#)

Interfaces

[ISimpleBuffer](#)

Enums

[SimpleBufferType](#)

Interface ISimpleBuffer

Namespace: [Bliss.CSharp.Graphics.Pipelines.Buffers](#)

Assembly: Bliss.dll

```
public interface ISimpleBuffer : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#)

Properties

DeviceBuffer

Gets the GPU device buffer associated with this simple buffer.

```
DeviceBuffer DeviceBuffer { get; }
```

Property Value

[DeviceBuffer](#)

ShaderStages

Gets the shader stages where this buffer is used.

```
ShaderStages ShaderStages { get; }
```

Property Value

[ShaderStages](#)

Methods

GetResourceSet(SimpleBufferLayout)

Retrieves a resource set for this buffer using the specified layout.

```
ResourceSet GetResourceSet(SimpleBufferLayout layout)
```

Parameters

layout [SimpleBufferLayout](#)

The layout defining how the buffer is bound to the shader.

Returns

[ResourceSet](#)

A [ResourceSet](#) containing this buffer bound according to the given layout.

Class SimpleBufferLayout

Namespace: [Bliss.CSharp.Graphics.Pipelines.Buffers](#)

Assembly: Bliss.dll

```
public class SimpleBufferLayout : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← SimpleBufferLayout

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

SimpleBufferLayout(GraphicsDevice, string, SimpleBufferType, ShaderStages)

Creates a new instance of the [SimpleBufferLayout](#) class with the specified parameters.

```
public SimpleBufferLayout(GraphicsDevice graphicsDevice, string name, SimpleBufferType  
bufferType, ShaderStages stages)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for resource allocation.

name [string](#)

The name of the buffer layout.

bufferType [SimpleBufferType](#)

The type of buffer (e.g., Uniform, Structured).

stages [ShaderStages](#)

The shader stages where this layout will be used.

Properties

BufferType

The type of the buffer, determining its usage and binding.

```
public SimpleBufferType BufferType { get; }
```

Property Value

[SimpleBufferType](#)

GraphicsDevice

The graphics device used to create the layout and associated resources.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Layout

The resource layout representing the buffer's structure in the graphics pipeline.

```
public ResourceLayout Layout { get; }
```

Property Value

[ResourceLayout](#)

Name

The name assigned to the buffer layout.

```
public string Name { get; }
```

Property Value

[string](#)

ShaderStages

The shader stages where this buffer layout is accessible.

```
public ShaderStages ShaderStages { get; }
```

Property Value

[ShaderStages](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

Enum SimpleBufferType

Namespace: [Bliss.CSharp.Graphics.Pipelines.Buffers](#)

Assembly: Bliss.dll

```
public enum SimpleBufferType
```

Fields

StructuredReadOnly = 1

A read-only buffer that supports structured data access.

StructuredReadWrite = 2

A read-write buffer that supports structured data access.

Uniform = 0

A buffer type that holds uniform data.

Class SimpleStructuredBuffer<THeader, TElement>

Namespace: [Bliss.CSharp.Graphics.Pipelines.Buffers](#)

Assembly: Bliss.dll

```
public class SimpleStructuredBuffer<THeader, TElement> : Disposable, ISimpleBuffer,  
IDisposable where THeader : unmanaged where TElement : unmanaged
```

Type Parameters

THeader

TElement

Inheritance

[object](#) ← [Disposable](#) ← SimpleStructuredBuffer<THeader, TElement>

Implements

[ISimpleBuffer](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#), [Disposable.Dispose\(\)](#), [Disposable.ThrowIfDisposed\(\)](#), [object.Equals\(object\)](#),
[object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

SimpleStructuredBuffer(GraphicsDevice, uint, uint, ShaderStages, bool, bool)

Initializes a new instance of the [SimpleStructuredBuffer<THeader, TElement>](#) class with the specified device, sizes, shader stages, and usage options.

```
public SimpleStructuredBuffer(GraphicsDevice graphicsDevice, uint headerDataSize, uint  
elementDataSize, ShaderStages stages, bool readOnly = true, bool rawBuffer = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create the buffer.

headerDataSize [uint](#)

The number of header entries to allocate.

elementDataSize [uint](#)

The number of element entries to allocate.

stages [ShaderStages](#)

The shader stages where this buffer will be bound.

readOnly [bool](#)

Whether the buffer is read-only (default: true).

rawBuffer [bool](#)

Whether the buffer is treated as raw (default: false).

Properties

DeviceBuffer

Gets the GPU device buffer backing this structured buffer.

```
public DeviceBuffer DeviceBuffer { get; }
```

Property Value

[DeviceBuffer](#)

ElementData

Gets the element data stored in this buffer.

```
public TElement[] ElementData { get; }
```

Property Value

TElement[]

ElementContentSize

Gets the number of element entries stored in this buffer.

```
public uint ElementContentSize { get; }
```

Property Value

[uint](#)

GraphicsDevice

Gets the graphics device associated with this buffer.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

HeaderData

Gets the header data stored in this buffer.

```
public THeader[] HeaderData { get; }
```

Property Value

THeader[]

HeaderDataSize

Gets the number of header elements stored in this buffer.

```
public uint HeaderDataSize { get; }
```

Property Value

[uint](#)

RawBuffer

Gets a value indicating whether this buffer is treated as a raw buffer.

```
public bool RawBuffer { get; }
```

Property Value

[bool](#)

ReadOnly

Gets a value indicating whether this buffer is read-only.

```
public bool ReadOnly { get; }
```

Property Value

[bool](#)

ShaderStages

Gets the shader stages where this buffer will be used.

```
public ShaderStages ShaderStages { get; }
```

Property Value

[ShaderStages](#) ↗

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#) ↗

True if called from user code; false if called from a finalizer.

GetResourceSet(SimpleBufferLayout)

Retrieves a cached or newly created resource set for this buffer using the specified layout.

```
public ResourceSet GetResourceSet(SimpleBufferLayout layout)
```

Parameters

layout [SimpleBufferLayout](#)

The buffer layout for resource binding.

Returns

[ResourceSet](#) ↗

A resource set containing this buffer bound to the given layout.

SetElementValue(int, TElement)

Sets an element value in the CPU-side array without immediately updating the GPU buffer.

```
public void SetElementValue(int index, TElement value)
```

Parameters

index [int](#)

The index of the element.

value [TElement](#)

The value to assign to the element.

SetElementValueDeferred(CommandList, int, TElement)

Sets an element value and schedules it to be uploaded to the GPU using a [CommandList](#).

```
public void SetElementValueDeferred(CommandList commandList, int index, TElement value)
```

Parameters

commandList [CommandList](#)

The command list used to defer the buffer update.

index [int](#)

The index of the element.

value [TElement](#)

The value to assign to the element.

SetElementValueDeferred(CommandList, int, ref TElement)

Sets an element value and schedules it to be uploaded to the GPU using a [CommandList](#) with a reference value.

```
public void SetElementValueDeferred(CommandList commandList, int index, ref TElement value)
```

Parameters

commandList [CommandList](#)

The command list used to defer the buffer update.

index [int](#)

The index of the element.

value [TElement](#)

The reference to the value to assign to the element.

SetElementValueImmediate(int, TElement)

Sets an element value immediately in both the CPU-side array and GPU buffer.

```
public void SetElementValueImmediate(int index, TElement value)
```

Parameters

index [int](#)

The index of the element.

value [TElement](#)

The value to assign to the element.

SetElementValueImmediate(int, ref TElement)

Sets an element value immediately in both the CPU-side array and GPU buffer using a reference value.

```
public void SetElementValueImmediate(int index, ref TElement value)
```

Parameters

index [int](#)

The index of the element.

value TElement

The reference to the value to assign to the element.

SetHeaderValue(int, THeader)

Sets a header value in the CPU-side array without immediately updating the GPU buffer.

```
public void SetHeaderValue(int index, THeader value)
```

Parameters

index [int](#)

The index of the header element.

value THeader

The value to assign to the header element.

SetHeaderValueDeferred(CommandList, int, THeader)

Sets a header value and schedules it to be uploaded to the GPU using a [CommandList](#).

```
public void SetHeaderValueDeferred(CommandList commandList, int index, THeader value)
```

Parameters

commandList [CommandList](#)

The command list used to defer the buffer update.

index [int](#)

The index of the header element.

value THeader

The value to assign to the header element.

SetHeaderValueDeferred(CommandList, int, ref THeader)

Sets a header value and schedules it to be uploaded to the GPU using a [CommandList](#) with a reference value.

```
public void SetHeaderValueDeferred(CommandList commandList, int index, ref THeader value)
```

Parameters

commandList [CommandList](#)

The command list used to defer the buffer update.

index [int](#)

The index of the header element.

value THeader

The reference to the value to assign to the header element.

SetHeaderValueImmediate(int, THeader)

Sets a header value immediately in both the CPU-side array and GPU buffer.

```
public void SetHeaderValueImmediate(int index, THeader value)
```

Parameters

index [int](#)

The index of the header element.

value THeader

The value to set at the specified index.

SetHeaderValueImmediate(int, ref THeader)

Sets a header value immediately in both the CPU-side array and GPU buffer using a reference value.

```
public void SetHeaderValueImmediate(int index, ref THeader value)
```

Parameters

index [int](#)

The index of the header element.

value THeader

The reference to the value to set at the specified index.

UpdateBufferDeferred(CommandList)

Updates the entire buffer deferred using a [CommandList](#) with both header and element data.

```
public void UpdateBufferDeferred(CommandList commandList)
```

Parameters

commandList [CommandList](#)

The command list used to defer the buffer update.

UpdateBufferImmediate()

Updates the entire buffer immediately on the GPU with both header and element data.

```
public void UpdateBufferImmediate()
```

Class SimpleUniformBuffer<T>

Namespace: [Bliss.CSharp.Graphics.Pipelines.Buffers](#)

Assembly: Bliss.dll

```
public class SimpleUniformBuffer<T> : Disposable, ISimpleBuffer, IDisposable where T : unmanaged
```

Type Parameters

T

Inheritance

[object](#) ← [Disposable](#) ← SimpleUniformBuffer<T>

Implements

[ISimpleBuffer](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#), [Disposable.Dispose\(\)](#), [Disposable.ThrowIfDisposed\(\)](#), [object.Equals\(object\)](#),
[object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

SimpleUniformBuffer(GraphicsDevice, uint, ShaderStages)

Initializes a new instance of the [SimpleUniformBuffer<T>](#) class.

```
public SimpleUniformBuffer(GraphicsDevice graphicsDevice, uint size, ShaderStages stages)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create the buffer and related resources.

size [uint](#)

The total number of elements in the buffer.

stages [ShaderStages](#)

The shader stages where this buffer will be used.

Properties

Data

Gets the CPU-side data storage backing this buffer.

```
public T[] Data { get; }
```

Property Value

T[]

DeviceBuffer

Gets the GPU-side device buffer that stores this buffer's data.

```
public DeviceBuffer DeviceBuffer { get; }
```

Property Value

[DeviceBuffer](#)

GraphicsDevice

Gets the graphics device associated with this buffer.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

ShaderStages

Gets the shader stages where this buffer is bound and used.

```
public ShaderStages ShaderStages { get; }
```

Property Value

[ShaderStages](#)

Size

Gets the total number of elements in this buffer.

```
public uint Size { get; }
```

Property Value

[uint](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GetResourceSet(SimpleBufferLayout)

Gets or creates a resource set for the specified buffer layout.

```
public ResourceSet GetResourceSet(SimpleBufferLayout layout)
```

Parameters

layout [SimpleBufferLayout](#)

The layout describing how the buffer is bound.

Returns

[ResourceSet](#)

The [ResourceSet](#) associated with the layout.

SetValue(int, T)

Sets the value at the specified index in the buffer's data.

```
public void SetValue(int index, T value)
```

Parameters

index [int](#)

The zero-based index of the element to set.

value T

The new value to assign.

SetValueDeferred(CommandList, int, T)

Sets the value at the specified index and defers the GPU update using a command list.

```
public void SetValueDeferred(CommandList commandList, int index, T value)
```

Parameters

commandList [CommandList](#)

The command list used to defer the update.

index [int](#)

The zero-based index of the element to set.

value T

The new value to assign.

SetValueDeferred(CommandList, int, ref T)

Sets the value at the specified index in the buffer and defers the GPU update using the given command list.

```
public void SetValueDeferred(CommandList commandList, int index, ref T value)
```

Parameters

commandList [CommandList](#)

The command list used to schedule the deferred buffer update operation.

index [int](#)

The zero-based index of the element to update within the buffer.

value T

The value to set at the specified index within the buffer.

SetValueImmediate(int, T)

Sets the value at the specified index and immediately updates the GPU buffer.

```
public void SetValueImmediate(int index, T value)
```

Parameters

index [int ↗](#)

The zero-based index of the element to set.

value [T](#)

The new value to assign.

SetValueImmediate(int, ref T)

Sets the value at the specified index by reference and immediately updates the GPU buffer.

```
public void SetValueImmediate(int index, ref T value)
```

Parameters

index [int ↗](#)

The zero-based index of the element to set.

value [T](#)

The new value to assign by reference.

UpdateBufferDeferred(CommandList)

Updates the entire GPU buffer using a deferred command list.

```
public void UpdateBufferDeferred(CommandList commandList)
```

Parameters

commandList [CommandList ↗](#)

The command list used to defer the update.

UpdateBufferImmediate()

Updates the entire GPU buffer immediately with the current CPU data.

```
public void UpdateBufferImmediate()
```

Namespace Bliss.CSharp.Graphics.Pipelines.Textures

Classes

[SimpleTextureLayout](#)

Class SimpleTextureLayout

Namespace: [Bliss.CSharp.Graphics.Pipelines.Textures](#)

Assembly: Bliss.dll

```
public class SimpleTextureLayout : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← SimpleTextureLayout

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

SimpleTextureLayout(GraphicsDevice, string)

Initializes a new instance of the [SimpleTextureLayout](#) class with the specified graphics device and texture name.

```
public SimpleTextureLayout(GraphicsDevice graphicsDevice, string name)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used to create the resource layout.

name [string](#)

The name used for the texture and sampler resources.

Properties

GraphicsDevice

The graphics device used to create the resource layout for textures and samplers.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#) ↗

Layout

The resource layout associated with textures and samplers.

```
public ResourceLayout Layout { get; }
```

Property Value

[ResourceLayout](#) ↗

Name

The name used for the texture and sampler resources.

```
public string Name { get; }
```

Property Value

[string](#) ↗

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

Namespace Bliss.CSharp.Graphics.Rendering

Classes

[Frustum](#)

Enums

[RenderMode](#)

Class Frustum

Namespace: [Bliss.CSharp.Graphics.Rendering](#)

Assembly: Bliss.dll

```
public class Frustum
```

Inheritance

[object](#) ← Frustum

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Frustum()

Initializes a new instance of the Frustum class.

```
public Frustum()
```

Methods

ContainsBox(BoundingBox)

Checks if a bounding box is contained within the frustum.

```
public bool ContainsBox(BoundingBox box)
```

Parameters

box [BoundingBox](#)

The bounding box to check.

Returns

[bool](#)

True if the bounding box is contained within the frustum, otherwise false.

ContainsOrientedBox(BoundingBox, Vector3, Quaternion)

Checks if a oriented box is contained within the frustum.

```
public bool ContainsOrientedBox(BoundingBox box, Vector3 origin, Quaternion rotation)
```

Parameters

[box](#) [BoundingBox](#)

The oriented box to check.

[origin](#) [Vector3](#)

The origin of the oriented box.

[rotation](#) [Quaternion](#)

The rotation of the oriented box.

Returns

[bool](#)

True if the oriented box is contained within the frustum, otherwise false.

ContainsPoint(Vector3)

Checks if a point is contained within the frustum.

```
public bool ContainsPoint(Vector3 point)
```

Parameters

point [Vector3](#)

The point to check.

Returns

[bool](#)

True if the point is contained within the frustum, otherwise false.

ContainsSphere(Vector3, float)

Checks if a sphere is contained within the frustum.

```
public bool ContainsSphere(Vector3 center, float radius)
```

Parameters

center [Vector3](#)

The center of the sphere.

radius [float](#)

The radius of the sphere.

Returns

[bool](#)

True if the sphere is contained within the frustum, otherwise false.

Extract(Matrix4x4)

Extracts frustum planes from the view-projection matrix.

```
public void Extract(Matrix4x4 viewProjection)
```

Parameters

`viewProjection Matrix4x4`

Enum RenderMode

Namespace: [Bliss.CSharp.Graphics.Rendering](#)

Assembly: Bliss.dll

```
public enum RenderMode
```

Fields

Cutout = 1

Alpha cutout rendering (pixels fully transparent are discarded).

Solid = 0

Opaque rendering (no transparency).

Translucent = 2

Transparent rendering (blends with background).

Namespace Bliss.CSharp.Graphics.Rendering. Renderers

Classes

[FullScreenRenderer](#)

[ImmediateRenderer](#)

Class FullScreenRenderer

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers](#)

Assembly: Bliss.dll

```
public class FullScreenRenderer : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← FullScreenRenderer

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

FullScreenRenderer(GraphicsDevice)

Initializes a new instance of the [FullScreenRenderer](#) class, setting up the necessary buffers and pipeline for full-screen rendering.

```
public FullScreenRenderer(GraphicsDevice graphicsDevice)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for resource creation and rendering.

Properties

GraphicsDevice

The graphics device used for rendering.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

Draw(CommandList, RenderTexture2D, OutputDescription, Effect?, Sampler?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?)

Executes the draw operation using the specified resources, rendering configurations, and GPU states.

```
public void Draw(CommandList commandList, RenderTexture2D renderTexture, OutputDescription  
output, Effect? effect = null, Sampler? sampler = null, BlendStateDescription? blendState =  
null, DepthStencilStateDescription? depthStencilState = null, RasterizerStateDescription?  
rasterizerState = null)
```

Parameters

[commandList](#) [CommandList](#)

The command list for issuing draw commands to the graphics device.

renderTexture [RenderTexture2D](#)

The render texture used as the input or output target for rendering operations.

output [OutputDescription](#)

The output description detailing the format and layout of render targets and depth-stencil buffers.

effect [Effect](#)

An optional shader effect utilized for rendering. A default effect is applied if none is specified.

sampler [Sampler](#)

An optional sampler used for texture sampling in the rendering process. If not set, a default point sampler is used.

blendState [BlendStateDescription](#)?

An optional blend state configuration for blending operations. Defaults to alpha blending if not provided.

depthStencilState [DepthStencilStateDescription](#)?

An optional depth-stencil state description to control depth and stencil testing. A disabled state is used by default.

rasterizerState [RasterizerStateDescription](#)?

An optional rasterizer state description to configure rasterization settings. Defaults to a standard rasterizer configuration if not specified.

Class ImmediateRenderer

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers](#)

Assembly: Bliss.dll

```
public class ImmediateRenderer : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← ImmediateRenderer

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ImmediateRenderer(GraphicsDevice, uint)

Initializes a new instance of the [ImmediateRenderer](#) class with the specified graphics device, output, effect, and capacity.

```
public ImmediateRenderer(GraphicsDevice graphicsDevice, uint capacity = 10240)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering.

capacity [uint](#)

The maximum number of vertices. Defaults to 10.240.

Properties

Capacity

Gets the maximum number of vertices that can be drawn.

```
public uint Capacity { get; }
```

Property Value

[uint](#)

GraphicsDevice

Gets the graphics device used for rendering.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

DrawBillboard(CommandList, OutputDescription, Vector3, Vector2?, Color?)

Draws a billboard at the specified position with optional scaling and color parameters.

```
public void DrawBillboard(CommandList commandList, OutputDescription output, Vector3  
position, Vector2? scale = null, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for rendering commands.

`output` [OutputDescription](#)

The output description that defines rendering target properties.

`position` [Vector3](#)

The 3D position where the billboard will be rendered.

`scale` [Vector2](#)?

The optional scale factor for the billboard. Defaults to a scale of 1 if not specified.

`color` [Color](#)?

The optional color of the billboard. Defaults to white if not specified.

DrawBoundingBox(CommandList, OutputDescription, Transform, BoundingBox, Color?)

Draws the edges of the specified bounding box using the given transformation and color.

```
public void DrawBoundingBox(CommandList commandList, OutputDescription output, Transform  
transform, BoundingBox box, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for issuing rendering commands.

output [OutputDescription](#)

The output description for the rendering target.

transform [Transform](#)

The transformation to apply to the bounding box before rendering.

box [BoundingBox](#)

The bounding box to be drawn.

color [Color?](#)

The color to use for the bounding box edges. If null, white is used as the default color.

DrawCapsule(CommandList, OutputDescription, Transform, float, float, int, Color?)

Renders a 3D capsule using the specified transformation, dimensions, and visual properties.

```
public void DrawCapsule(CommandList commandList, OutputDescription output, Transform  
transform, float radius, float height, int slices, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used to issue draw commands.

output [OutputDescription](#)

The output description for the render target.

transform [Transform](#)

The transformation to apply to the capsule, including position, rotation, and scale.

radius [float](#)

The radius of the capsule's hemispherical ends and cylindrical body.

`height` [float](#)

The total height of the capsule.

`slices` [int](#)

The number of subdivisions around the circumference of the capsule. Must be 3 or greater.

`color` [Color?](#)

The color of the capsule. If null, defaults to white.

DrawCapsuleWires(CommandList, OutputDescription, Transform, float, float, int, Color?)

Draws the wireframe of a capsule based on the specified transform, dimensions, and color.

```
public void DrawCapsuleWires(CommandList commandList, OutputDescription output, Transform  
transform, float radius, float height, int slices, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for issuing draw commands.

`output` [OutputDescription](#)

The output description containing information about the render target and configurations.

`transform` [Transform](#)

The transformation applied to the capsule, such as position, rotation, and scale.

`radius` [float](#)

The radius of the capsule's hemispherical ends and cylindrical body.

`height` [float](#)

The height of the cylindrical body of the capsule.

`slices` [int](#)

The number of divisions for rendering the capsule's rounded surface. Must be at least 3.

color [Color?](#)

The optional color of the capsule wireframe. Defaults to white if not specified.

DrawCone(CommandList, OutputDescription, Transform, float, float, int, Color?)

Draws a 3D cone using the specified parameters.

```
public void DrawCone(CommandList commandList, OutputDescription output, Transform transform,
float radius, float height, int slices, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list to record drawing commands.

output [OutputDescription](#)

The output description specifying the target rendering surface.

transform [Transform](#)

The transform specifying the position, rotation, and scale of the cone in world space.

radius [float](#)

The radius of the base of the cone.

height [float](#)

The height of the cone from its base to its apex.

slices [int](#)

The number of slices used to construct the cone's base. Must be at least 3.

color [Color?](#)

An optional parameter to define the color of the cone. Defaults to white if not provided.

DrawConeWires(CommandList, OutputDescription, Transform, float, float, int, Color?)

Draws a wireframe representation of a cone in 3D space.

```
public void DrawConeWires(CommandList commandList, OutputDescription output, Transform transform, float radius, float height, int slices, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used to issue rendering commands.

`output` [OutputDescription](#)

The output description that specifies render target details.

`transform` [Transform](#)

The transformation to apply to the cone, including position, rotation, and scale.

`radius` [float](#)

The radius of the cone's base.

`height` [float](#)

The height of the cone from the base to its tip.

`slices` [int](#)

The number of slices used to approximate the circular base. Must be at least 3.

`color` [Color?](#)

An optional color for the wireframe. Defaults to white if null.

DrawCube(CommandList, OutputDescription, Transform, Vector3, Color?)

Draws a cube with the specified command list, output description, transformation, size, and optional color.

```
public void DrawCube(CommandList commandList, OutputDescription output, Transform transform,  
Vector3 size, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for submitting rendering commands.

output [OutputDescription](#)

The output description specifying the render target details.

transform [Transform](#)

The transformation to be applied to the cube.

size [Vector3](#)

The size of the cube in 3D space.

color [Color](#)?

An optional color for the cube; if null, white is used.

DrawCubeWires(CommandList, OutputDescription, Transform, Vector3, Color?)

Draws the wireframe of a cube with the specified transform, size, and optional color.

```
public void DrawCubeWires(CommandList commandList, OutputDescription output, Transform  
transform, Vector3 size, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used to issue rendering commands.

output [OutputDescription](#)

The output description that specifies the target render output.

transform [Transform](#)

The transformation to apply to the cube, including position, rotation, and scale.

size [Vector3](#)

The dimensions of the cube to be drawn.

color [Color?](#)

An optional color for the wireframe. If not provided, the default color is white.

DrawCylinder(CommandList, OutputDescription, Transform, float, float, int, Color?)

Renders a cylinder using the specified command list, output description, transform, dimensions, slice count, and optional color.

```
public void DrawCylinder(CommandList commandList, OutputDescription output, Transform  
transform, float radius, float height, int slices, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for issuing rendering commands.

output [OutputDescription](#)

The output description that defines the rendering target.

transform [Transform](#)

The transform used to position and orient the cylinder in 3D space.

radius [float](#)

The radius of the cylinder's top and bottom caps.

height [float](#)

The height of the cylinder from bottom to top cap.

slices [int](#)

The number of segments used to approximate the cylindrical surface. Minimum value is 3.

color [Color?](#)

The optional color of the cylinder. If null, a default white color is applied.

DrawCylinderWires(CommandList, OutputDescription, Transform, float, float, int, Color?)

Draws the wireframe representation of a cylinder using the specified transformation, radius, height, and number of slices.

```
public void DrawCylinderWires(CommandList commandList, OutputDescription output, Transform transform, float radius, float height, int slices, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used to issue rendering commands.

output [OutputDescription](#)

The output description that defines the rendering target.

transform [Transform](#)

The transformation applied to position, rotate, and scale the cylinder in the scene.

radius [float](#)

The radius of the cylinder.

height [float](#)

The height of the cylinder.

slices [int](#)

The number of divisions around the cylinder's circumference. Must be 3 or greater.

color [Color?](#)

The color of the cylinder's wireframe. Defaults to white if not specified.

DrawGrid(CommandList, OutputDescription, Transform, int, int, int, Color?, Color?, Color?)

Renders a grid using the specified command list, output description, transformation matrix, and grid parameters.

```
public void DrawGrid(CommandList commandList, OutputDescription output, Transform transform,
    int slices, int spacing, int majorLineSpacing, Color? color = null, Color? axisColorX =
    null, Color? axisColorZ = null)
```

Parameters

commandList [CommandList](#)

The command list used to issue rendering commands.

output [OutputDescription](#)

The output description for the target render resource.

transform [Transform](#)

The transformation matrix applied to the grid.

slices [int](#)

The number of grid divisions or slices. Must be greater than or equal to 1.

spacing [int](#)

The distance between adjacent grid lines. Must be greater than or equal to 1.

majorLineSpacing [int](#)

The interval of major grid lines, which are visually distinct. Must be greater than or equal to 1.

color [Color?](#)

The optional color of the grid lines. Defaults to white if not provided.

`axisColorX` [Color?](#)

The optional color for the X-axis grid line. Defaults to red if not provided.

`axisColorZ` [Color?](#)

The optional color for the Z-axis grid line. Defaults to blue if not provided.

`DrawHemisphere(CommandList, OutputDescription, Transform, float, int, int, Color?)`

Renders a 3D hemisphere with the specified transformation, radius, rings, slices, and optional color.

```
public void DrawHemisphere(CommandList commandList, OutputDescription output, Transform transform, float radius, int rings, int slices, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for issuing draw commands.

`output` [OutputDescription](#)

The output description for the current render target.

`transform` [Transform](#)

The transformation to apply to the hemisphere.

`radius` [float](#)

The radius of the hemisphere.

`rings` [int](#)

The number of rings used to construct the hemisphere. Must be 3 or greater.

`slices` [int](#)

The number of slices used to construct the hemisphere. Must be 3 or greater.

`color` [Color?](#)

An optional color to apply to the hemisphere. If null, the default color will be white.

DrawHemisphereWires(CommandList, OutputDescription, Transform, float, int, int, Color?)

Draws the wireframe outline of a hemisphere using the specified parameters.

```
public void DrawHemisphereWires(CommandList commandList, OutputDescription output, Transform transform, float radius, int rings, int slices, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for rendering commands.

`output` [OutputDescription](#)

The output description that determines the rendering target.

`transform` [Transform](#)

The transformation to apply to the hemisphere.

`radius` [float](#)

The radius of the hemisphere.

`rings` [int](#)

The number of horizontal subdivisions (rings) for the hemisphere.

`slices` [int](#)

The number of vertical subdivisions (slices) for the hemisphere.

`color` [Color?](#)

An optional color for the hemisphere. If null, it defaults to white.

DrawKnot(CommandList, OutputDescription, Transform, float, float, int, int, Color?)

Draws a knot shape with the specified parameters using a command list and defined properties such as transformations, radii, number of segments, and optional color.

```
public void DrawKnot(CommandList commandList, OutputDescription output, Transform transform,  
float radius, float tubeRadius, int radSeg, int sides, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for rendering commands.

output [OutputDescription](#)

The output description specifying the rendering context.

transform [Transform](#)

The transformation to apply to the knot during rendering.

radius [float](#)

The overall radius of the knot.

tubeRadius [float](#)

The radius of the tube forming the knot structure.

radSeg [int](#)

The number of radial segments forming the knot. Must be 3 or greater.

sides [int](#)

The number of sides of the tube forming the knot. Must be 3 or greater.

color [Color?](#)

An optional color to apply to the knot. Defaults to white when null.

DrawKnotWires(CommandList, OutputDescription, Transform, float, float, int, int, Color?)

Renders the wireframe of a knot shape using the specified transformation, radii, and segments.

```
public void DrawKnotWires(CommandList commandList, OutputDescription output, Transform transform, float radius, float tubeRadius, int radSeg, int sides, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for issuing rendering commands.

output [OutputDescription](#)

The output description specifying the rendering target.

transform [Transform](#)

The transformation applied to the knot wireframe.

radius [float](#)

The radius of the knot.

tubeRadius [float](#)

The radius of the tube comprising the knot's wireframe.

radSeg [int](#)

The number of radial segments making up the knot. Minimum value is 3.

sides [int](#)

The number of sides for the tube cross-section. Minimum value is 3.

color [Color?](#)

An optional color to use for the wireframe; if null, the default is white.

DrawLine(CommandList, OutputDescription, Vector3, Vector3, Color?)

Draws a line between two points in 3D space with a specified optional color.

```
public void DrawLine(CommandList commandList, OutputDescription output, Vector3 startPos, Vector3 endPos, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for recording drawing commands.

`output` [OutputDescription](#)

The output description of the render target.

`startPos` [Vector3](#)

The starting position of the line in 3D space.

`endPos` [Vector3](#)

The ending position of the line in 3D space.

`color` [Color?](#)

The optional color of the line. If not provided, defaults to white.

DrawSphere(CommandList, OutputDescription, Transform, float, int, int, Color?)

Draws a sphere with the specified transformation, radius, number of rings, slices, and optional color.

```
public void DrawSphere(CommandList commandList, OutputDescription output, Transform transform, float radius, int rings, int slices, Color? color = null)
```

Parameters

`commandList` [CommandList](#)

The command list used for issuing rendering commands.

output [OutputDescription](#)

The output description determining the render target.

transform [Transform](#)

The transformation to be applied to the sphere.

radius [float](#)

The radius of the sphere.

rings [int](#)

The number of horizontal subdivisions of the sphere.

slices [int](#)

The number of vertical subdivisions of the sphere.

color [Color?](#)

An optional color for the sphere; defaults to white if not provided.

DrawSphereWires(CommandList, OutputDescription, Transform, float, int, int, Color?)

Draws the wireframe of a sphere with the specified transform, radius, number of rings, slices, and optional color.

```
public void DrawSphereWires(CommandList commandList, OutputDescription output, Transform  
    transform, float radius, int rings, int slices, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for issuing draw commands to the GPU.

output [OutputDescription](#)

The output description of the render target where the sphere will be drawn.

transform [Transform](#)

The transformation to apply to the sphere, including position, rotation, and scale.

radius [float](#)

The radius of the sphere.

rings [int](#)

The number of horizontal subdivisions (rings) of the sphere.

slices [int](#)

The number of vertical subdivisions (slices) of the sphere.

color [Color?](#)

The optional color for the sphere's wireframe. Defaults to white if not specified.

DrawTorus(CommandList, OutputDescription, Transform, float, float, int, int, Color?)

Renders a torus shape using the specified transformation, dimensions, and color.

```
public void DrawTorus(CommandList commandList, OutputDescription output, Transform transform, float radius, float size, int radSeg, int sides, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for issuing rendering commands.

output [OutputDescription](#)

The output description specifying render target details.

transform [Transform](#)

The transformation to apply to the torus, including position, rotation, and scale.

radius [float](#)

The radius of the inner circle of the torus.

size [float](#)

The thickness of the torus.

radSeg [int](#)

The number of segments along the radial direction of the torus. Must be 3 or greater.

sides [int](#)

The number of sides to approximate the circular cross-section of the torus. Must be 3 or greater.

color [Color?](#)

The color of the torus. If null, the default color will be white.

DrawTorusWires(CommandList, OutputDescription, Transform, float, float, int, int, Color?)

Renders a wireframe torus using the specified transformation, dimensions, and color.

```
public void DrawTorusWires(CommandList commandList, OutputDescription output, Transform transform, float radius, float size, int radSeg, int sides, Color? color = null)
```

Parameters

commandList [CommandList](#)

The command list used for rendering the torus wireframe.

output [OutputDescription](#)

The output description used for the rendering pipeline.

transform [Transform](#)

The transformation applied to the torus, including position, rotation, and scale.

radius [float](#)

The radius of the inner circle of the torus.

size [float](#)

The thickness of the torus.

radSeg [int](#)

The number of radial segments. Must be 3 or greater.

sides [int](#)

The number of subdivisions around the circular cross-section. Must be 3 or greater.

color [Color?](#)

The optional color used for rendering the torus wireframe. Defaults to white if not specified.

DrawVertices(CommandList, OutputDescription, Transform, List<ImmediateVertex3D>, List<uint>?, PrimitiveTopology)

Draws a set of vertices using the specified command list, output description, transformation, vertex data, indices, and primitive topology.

```
public void DrawVertices(CommandList commandList, OutputDescription output, Transform transform, List<ImmediateVertex3D> vertices, List<uint>? indices = null, PrimitiveTopology topology = PrimitiveTopology.TriangleList)
```

Parameters

commandList [CommandList](#)

The command list used for issuing drawing commands.

output [OutputDescription](#)

The output description that defines how the rendered content is processed and displayed.

transform [Transform](#)

The transformation matrix to apply to the vertex data.

vertices [List](#)<ImmediateVertex3D>

The collection of vertices to render.

indices [List](#)<uint>

The collection of indices defining the order in which vertices are connected. Defaults to null.

topology [PrimitiveTopology](#)

The primitive topology that specifies how the vertex data should be interpreted (e.g., triangle list, line strip). Defaults to TriangleList.

GetBlendState()

Retrieves the current blend state used by the renderer.

```
public BlendStateDescription GetBlendState()
```

Returns

[BlendStateDescription](#)

The current [BlendStateDescription](#) instance.

GetCurrentDepthStencilState()

Retrieves the currently bound depth stencil state description.

```
public DepthStencilStateDescription GetCurrentDepthStencilState()
```

Returns

[DepthStencilStateDescription](#)

The current [DepthStencilStateDescription](#) instance being used.

GetCurrentEffect()

Retrieves the current effect being used by the renderer.

```
public Effect GetCurrentEffect()
```

Returns

[Effect](#)

The currently set [Effect](#) instance.

GetCurrentRasterizerState()

Retrieves the current rasterizer state description used by the renderer.

```
public RasterizerStateDescription GetCurrentRasterizerState()
```

Returns

[RasterizerStateDescription](#)

The currently bound rasterizer state.

GetCurrentSampler()

Retrieves the currently active sampler used by the renderer.

```
public Sampler GetCurrentSampler()
```

Returns

[Sampler](#)

The active [Sampler](#) instance.

GetCurrentSourceRec()

Retrieves the current source rectangle used for rendering operations.

```
public Rectangle GetCurrentSourceRec()
```

Returns

[Rectangle](#)

The current [Rectangle](#) source used for rendering.

GetCurrentTexture()

Retrieves the currently active texture being used by the renderer.

```
public Texture2D GetCurrentTexture()
```

Returns

[Texture2D](#)

The active [Texture2D](#) object currently bound to the renderer.

ResetSettings()

Resets the [ImmediateRenderer](#) to default settings.

```
public void ResetSettings()
```

SetBlendState(BlendStateDescription?)

Sets the current blend state for the renderer. If no blend state is provided, it defaults to [SINGLE ALPHA BLEND](#).

```
public void SetBlendState(BlendStateDescription? blendState)
```

Parameters

blendState [BlendStateDescription](#)?

The blend state to apply. Defaults to [SINGLE ALPHA BLEND](#) if null.

SetDepthStencilState(DepthStencilStateDescription?)

Sets the depth stencil state for the renderer. If no state is provided, a default state of depth-only less/equal is used.

```
public void SetDepthStencilState(DepthStencilStateDescription? depthStencilState)
```

Parameters

depthStencilState [DepthStencilStateDescription](#)?

The depth stencil state to set. If null, defaults to DepthStencilStateDescription.DEPTH_ONLY_LESS_EQUAL.

SetEffect(Effect?)

Sets the current rendering effect for the ImmediateRenderer. If the provided effect is null, it defaults to the global default immediate renderer effect.

```
public void SetEffect(Effect? effect)
```

Parameters

effect [Effect](#)

The effect to be used. If null, the default ImmediateRenderer effect will be used.

SetRasterizerState(RasterizerStateDescription?)

Updates the current rasterizer state for the renderer. If no rasterizer state is provided, the default state is used.

```
public void SetRasterizerState(RasterizerStateDescription? rasterizerState)
```

Parameters

rasterizerState [RasterizerStateDescription](#)?

The rasterizer state to apply to the pipeline. If null, the default rasterizer state is used.

SetTexture(Texture2D?, Sampler?, Rectangle?)

Sets the current texture, sampler, and optional source rectangle for rendering.

```
public void SetTexture(Texture2D? texture, Sampler? sampler = null, Rectangle? sourceRect = null)
```

Parameters

texture [Texture2D](#)

The texture to be used for rendering. If null, a default texture is used.

sampler [Sampler](#)

The sampler to be applied to the texture. Defaults to a point sampler if null.

sourceRect [Rectangle](#)?

The source rectangle specifying a portion of the texture to be used. If null, the entire texture is used.

Namespace Bliss.CSharp.Graphics.Rendering. Renderers.Batches.Primitives

Classes

[PrimitiveBatch](#)

Class PrimitiveBatch

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Batches.Primitives](#)

Assembly: Bliss.dll

```
public class PrimitiveBatch : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← PrimitiveBatch

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

PrimitiveBatch(GraphicsDevice, IWindow, uint)

Initializes a new instance of the PrimitiveBatch class for rendering 2D primitives.

```
public PrimitiveBatch(GraphicsDevice graphicsDevice, IWindow window, uint capacity = 4096)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering.

window [IWindow](#)

The window representing the rendering context.

capacity [uint](#)

Optional. The initial capacity of the vertex buffer.

Properties

Capacity

Specifies the maximum number of sprites that the PrimitiveBatch can process in a single draw call.

```
public uint Capacity { get; }
```

Property Value

[uint](#)

DrawCallCount

Gets the number of draw calls made during the current batch rendering session. This count is reset to zero each time [Begin\(CommandList, OutputDescription, Effect?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?, Matrix4x4?, Matrix4x4?, Rectangle?\)](#) is called and increments with each call to Bliss.CSharp.Graphics.Rendering.Renderers.Batches.Primitives.PrimitiveBatch.Flush().

```
public int DrawCallCount { get; }
```

Property Value

[int](#)

GraphicsDevice

Represents the graphics device used for rendering operations within the [PrimitiveBatch](#) class. The [GraphicsDevice](#) is used to create resources, manage rendering pipelines, and issue draw commands.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Window

Represents the window used for rendering graphics.

```
public IWindow Window { get; }
```

Property Value

[IWindow](#)

Methods

AddVertices(List<PrimitiveVertex2D>)

Adds a collection of vertices to the current batch for rendering.

```
public void AddVertices(List<PrimitiveVertex2D> vertices)
```

Parameters

vertices [List](#)<[PrimitiveVertex2D](#)>

The list of vertices to be added to the batch.

Begin(CommandList, OutputDescription, Effect?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?, Matrix4x4?, Matrix4x4?, Rectangle?)

Begins a new batch of primitive drawing operations with specified rendering configurations.

```
public void Begin(CommandList commandList, OutputDescription output, Effect? effect = null, BlendStateDescription? blendState = null, DepthStencilStateDescription? depthStencilState = null, RasterizerStateDescription? rasterizerState = null, Matrix4x4? projection = null, Matrix4x4? view = null, Rectangle? scissorRect = null)
```

Parameters

commandList [CommandList](#)

The command list to record drawing commands.

output [OutputDescription](#)

The output description defining the render target configuration.

effect [Effect](#)

Optional. The effect to use for rendering operations. Defaults to the global default primitive effect if not specified.

blendState [BlendStateDescription](#)?

Optional. The blend state description used for rendering. Defaults to a single alpha blend if not specified.

depthStencilState [DepthStencilStateDescription](#)?

Optional. The depth stencil state description used for rendering. Defaults to disabled depth-stencil testing if not specified.

rasterizerState [RasterizerStateDescription](#)?

Optional. The rasterizer state description used for rendering. Defaults to cull none if not specified.

projection [Matrix4x4](#)?

Optional. The projection matrix for the rendering. Defaults to an orthographic projection matrix if not specified.

view [Matrix4x4](#)?

Optional. The view matrix for the rendering. Defaults to the identity matrix if not specified.

scissorRect [Rectangle](#)?

An optional [Rectangle](#) that defines the scissor rectangle for rendering. No scissor rect is applied if not specified.

Exceptions

[Exception](#)

Thrown when the method is called before the previous batch has been properly ended.

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

DrawEmptyCircle(Vector2, float, int, int, float, Color?)

Draws an empty circle at the specified position with the given radius, thickness, and number of segments.

```
public void DrawEmptyCircle(Vector2 position, float radius, int thickness, int segments,
    float layerDepth = 0.5, Color? color = null)
```

Parameters

`position` [Vector2](#)

The center position of the circle.

`radius` [float](#)

The radius of the circle.

`thickness` [int](#)

The thickness of the circle's outline.

`segments` [int](#)

The number of segments to divide the circle into. Must be at least 4.

`layerDepth` [float](#)

The depth of the circle in the rendering pass. Defaults to 0.5.

color [Color](#)?

The color of the circle's outline. Defaults to white if not specified.

DrawEmptyCircleSector(Vector2, float, float, float, int, int, float, Color?)

Draws an empty circle sector using the specified parameters.

```
public void DrawEmptyCircleSector(Vector2 position, float radius, float startAngle, float endAngle, int thickness, int segments, float layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The position of the center of the circle.

radius [float](#)

The radius of the circle sector.

startAngle [float](#)

The starting angle of the sector in degrees.

endAngle [float](#)

The ending angle of the sector in degrees.

thickness [int](#)

The thickness of the circle sector line.

segments [int](#)

The number of segments used to draw the sector. Minimum value is 4.

layerDepth [float](#)

The depth of the layer for rendering. Defaults to 0.5.

color [Color](#)?

The color of the circle sector line. Defaults to white if null.

DrawEmptyEllipse(Vector2, Vector2, int, int, float, Color?)

Draws an empty ellipse at the specified position with the given radius, thickness, and number of segments.

```
public void DrawEmptyEllipse(Vector2 position, Vector2 radius, int thickness, int segments,  
    float layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The center position of the ellipse in 2D space.

radius [Vector2](#)

The radius of the ellipse along the X and Y axes.

thickness [int](#)

The thickness of the ellipse outline.

segments [int](#)

The number of segments to use for drawing the ellipse. Minimum value is 4.

layerDepth [float](#)

The depth layer for rendering the ellipse. Defaults to 0.5.

color [Color?](#)

The color to use for the ellipse outline. If not specified, defaults to white.

DrawEmptyRectangle(RectangleF, float, Vector2?, float, float, Color?)

Draws an empty rectangle with specified dimensions, thickness, rotation, and color.

```
public void DrawEmptyRectangle(RectangleF rectangle, float thickness, Vector2? origin = null, float rotation = 0, float layerDepth = 0.5, Color? color = null)
```

Parameters

rectangle [RectangleF](#)

The rectangle defining the dimensions and position of the empty rectangle.

thickness [float](#)

The thickness of the rectangle's outline.

origin [Vector2](#)?

Optional origin point for rotation and positioning. Defaults to (0,0).

rotation [float](#)

Optional rotation angle in degrees. Defaults to 0.0F.

layerDepth [float](#)

Optional depth layer for rendering. Defaults to 0.5F.

color [Color](#)?

Optional color for the rectangle's outline. Defaults to white.

DrawEmptyRing(Vector2, float, float, int, int, float, Color?)

Draws an empty ring at the specified position with the given inner radius, outer radius, thickness, segments, and optional color.

```
public void DrawEmptyRing(Vector2 position, float innerRadius, float outerRadius, int thickness, int segments, float layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The position where the ring will be drawn.

innerRadius [float](#)

The inner radius of the ring.

outerRadius [float](#)

The outer radius of the ring.

thickness [int](#)

The thickness of the ring.

segments [int](#)

The number of segments used to construct the ring. Must be at least 4.

layerDepth [float](#)

The depth layer for rendering the ring.

color [Color?](#)

Optional. The color of the ring. Defaults to white if not provided.

DrawEmptyTriangle(Vector2, Vector2, Vector2, int, float, Color?)

Draws an empty triangle between the specified points with a given thickness and color.

```
public void DrawEmptyTriangle(Vector2 point1, Vector2 point2, Vector2 point3, int thickness,  
    float layerDepth = 0.5, Color? color = null)
```

Parameters

point1 [Vector2](#)

The first vertex of the triangle.

point2 [Vector2](#)

The second vertex of the triangle.

point3 [Vector2](#)

The third vertex of the triangle.

thickness [int](#)

The thickness of the triangle edges.

layerDepth [float](#)

The depth of the triangle layer in the rendering order. Defaults to 0.5.

color [Color?](#)

The color of the triangle edges. Defaults to white if not specified.

DrawFilledCircle(Vector2, float, int, float, Color?)

Draws a filled circle at the specified position with the given radius, number of segments, and optional color.

```
public void DrawFilledCircle(Vector2 position, float radius, int segments, float layerDepth  
= 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The position of the center of the circle.

radius [float](#)

The radius of the circle.

segments [int](#)

The number of segments to use for drawing the circle.

layerDepth [float](#)

The drawing layer depth. Defaults to 0.5.

color [Color?](#)

The optional color of the circle. If null, defaults to white.

DrawFilledCircleSector(Vector2, float, float, float, int, float, Color?)

Draws a filled sector of a circle at a specified position with defined parameters.

```
public void DrawFilledCircleSector(Vector2 position, float radius, float startAngle, float endAngle, int segments, float layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The center position of the circle sector.

radius [float](#)

The radius of the circle sector.

startAngle [float](#)

The starting angle of the sector in degrees.

endAngle [float](#)

The ending angle of the sector in degrees.

segments [int](#)

The number of segments to use for drawing the sector.

layerDepth [float](#)

The depth layer for rendering the sector. Defaults to 0.5 if not provided.

color [Color?](#)

The color to use for the sector. Defaults to white if not provided.

DrawFilledEllipse(Vector2, Vector2, int, float, Color?)

Draws a filled ellipse at the specified position with the given radius, number of segments, and an optional color.

```
public void DrawFilledEllipse(Vector2 position, Vector2 radius, int segments, float  
layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The center position of the ellipse.

radius [Vector2](#)

The horizontal and vertical radii of the ellipse.

segments [int](#)

The number of segments to approximate the ellipse. Minimum is 4.

layerDepth [float](#)

The depth of the layer at which to draw the ellipse.

color [Color](#)?

The color to fill the ellipse. Defaults to white if not specified.

DrawFilledRectangle(RectangleF, Vector2?, float, float, Color?)

Draws a filled rectangle with optional origin, rotation, layer depth, and color.

```
public void DrawFilledRectangle(RectangleF rectangle, Vector2? origin = null, float rotation  
= 0, float layerDepth = 0.5, Color? color = null)
```

Parameters

rectangle [RectangleF](#)

The rectangular region to render.

origin [Vector2](#)?

Optional. The origin point of the rectangle for transformations, defaults to the top-left corner.

rotation [float](#)

Optional. The rotation angle of the rectangle in radians, defaults to 0.0F.

layerDepth [float](#)

Optional. The z-depth for rendering order, defaults to 0.5F.

color [Color?](#)

Optional. The fill color of the rectangle, defaults to White.

DrawFilledRing(Vector2, float, float, int, float, Color?)

Draws a filled ring at a specified position with given inner and outer radii, segment count, layer depth, and optional color.

```
public void DrawFilledRing(Vector2 position, float innerRadius, float outerRadius, int segments, float layerDepth = 0.5, Color? color = null)
```

Parameters

position [Vector2](#)

The center position of the ring.

innerRadius [float](#)

The inner radius of the ring.

outerRadius [float](#)

The outer radius of the ring.

segments [int](#)

The number of segments to use for constructing the ring. Must be at least 4.

layerDepth [float](#)

The layer depth for rendering the ring, where 0 is frontmost and 1 is backmost. Defaults to 0.5.

color [Color?](#)

The color of the ring. If not provided, defaults to white.

DrawFilledTriangle(Vector2, Vector2, Vector2, float, Color?)

Draws a filled triangle using the specified vertices, color, and layer depth.

```
public void DrawFilledTriangle(Vector2 point1, Vector2 point2, Vector2 point3, float  
layerDepth = 0.5, Color? color = null)
```

Parameters

point1 [Vector2](#)

The first vertex position of the triangle.

point2 [Vector2](#)

The second vertex position of the triangle.

point3 [Vector2](#)

The third vertex position of the triangle.

layerDepth [float](#)

The layer depth of the triangle, determining its rendering order. Default is 0.5.

color [Color?](#)

The color of the triangle. If null, the default color is white.

DrawLine(Vector2, Vector2, float, float, Color?)

Draws a line between two points with the specified thickness, layer depth, and color.

```
public void DrawLine(Vector2 start, Vector2 end, float thickness, float layerDepth = 0.5,  
Color? color = null)
```

Parameters

start [Vector2](#)

The starting point of the line.

end [Vector2](#)

The ending point of the line.

thickness [float](#)

The thickness of the line. Default is 1.0.

layerDepth [float](#)

The depth at which the line is drawn in the layer. Default is 0.5.

color [Color?](#)

The color of the line. If null, defaults to white.

End()

Ends the current batch of primitive drawing operations.

```
public void End()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentBlendState()

Retrieves the current blend state configuration used for rendering operations.

```
public BlendStateDescription GetCurrentBlendState()
```

Returns

[BlendStateDescription](#)

The current blend state configuration as a [BlendStateDescription](#).

Exceptions

[Exception ↗](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentDepthStencilState()

Retrieves the current depth-stencil state configuration used for rendering.

```
public DepthStencilStateDescription GetCurrentDepthStencilState()
```

Returns

[DepthStencilStateDescription ↗](#)

The current [DepthStencilStateDescription](#) being used in the rendering pipeline.

Exceptions

[Exception ↗](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentEffect()

Retrieves the currently active effect for the PrimitiveBatch.

```
public Effect GetCurrentEffect()
```

Returns

[Effect](#)

The [Effect](#) that is currently being used by the PrimitiveBatch.

Exceptions

[Exception ↗](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentOutput()

Retrieves the current output description for the primitive batch.

```
public OutputDescription GetCurrentOutput()
```

Returns

[OutputDescription](#)

The current [OutputDescription](#) associated with the batch.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentProjection()

Retrieves the current projection matrix being used for rendering operations.

```
public Matrix4x4 GetCurrentProjection()
```

Returns

[Matrix4x4](#)

The current projection as a [Matrix4x4](#).

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentRasterizerState()

Retrieves the current rasterizer state description used for rendering operations.

```
public RasterizerStateDescription GetCurrentRasterizerState()
```

Returns

[RasterizerStateDescription](#)

The current [RasterizerStateDescription](#) instance.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentScissorRect()

Retrieves the current scissor rectangle being used by the [PrimitiveBatch](#).

```
public Rectangle? GetCurrentScissorRect()
```

Returns

[Rectangle?](#)

The current scissor rectangle, or null if no scissor rectangle is set.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

GetCurrentView()

Retrieves the current view matrix being used for rendering operations.

```
public Matrix4x4 GetCurrentView()
```

Returns

[Matrix4x4](#)

The current [Matrix4x4](#) view matrix.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopBlendState()

Pop the current [BlendStateDescription](#) to the main blend state used by the [PrimitiveBatch](#).

```
public void PopBlendState()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopDepthStencilState()

Pop the current [DepthStencilStateDescription](#) to the main depth stencil state used by the [PrimitiveBatch](#).

```
public void PopDepthStencilState()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopEffect()

Pop the current [Effect](#) to the main effect used by the [PrimitiveBatch](#).

```
public void PopEffect()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopOutput()

Pop the output of the [OutputDescription](#) for the [PrimitiveBatch](#).

```
public void PopOutput()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopProjection()

Pop the current [Matrix4x4](#) to the main projection used by the [PrimitiveBatch](#).

```
public void PopProjection()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopRasterizerState()

Pop the current [RasterizerStateDescription](#) to the main rasterizer state used by the [PrimitiveBatch](#).

```
public void PopRasterizerState()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopScissorRect()

Pop the current [Rectangle](#) scissor to the main scissor used by the [PrimitiveBatch](#).

```
public void PopScissorRect()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PopView()

Pop the current [Matrix4x4](#) to the main view used by the [PrimitiveBatch](#).

```
public void PopView()
```

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushBlendState(BlendStateDescription)

Push the requested [BlendStateDescription](#) for the [PrimitiveBatch](#).

```
public void PushBlendState(BlendStateDescription blendState)
```

Parameters

blendState [BlendStateDescription](#)

The [BlendStateDescription](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushDepthStencilState(DepthStencilStateDescription)

Push the requested [DepthStencilStateDescription](#) for the [PrimitiveBatch](#).

```
public void PushDepthStencilState(DepthStencilStateDescription depthStencilState)
```

Parameters

depthStencilState [DepthStencilStateDescription](#)

The [DepthStencilStateDescription](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushEffect(Effect)

Push the requested [Effect](#) for the [PrimitiveBatch](#).

```
public void PushEffect(Effect effect)
```

Parameters

effect [Effect](#)

The [Effect](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushOutput(OutputDescription)

Push the requested [OutputDescription](#) for the [PrimitiveBatch](#).

```
public void PushOutput(OutputDescription output)
```

Parameters

output [OutputDescription](#)

The [OutputDescription](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushProjection(Matrix4x4)

Push the requested [Matrix4x4](#) projection for the [PrimitiveBatch](#).

```
public void PushProjection(Matrix4x4 projection)
```

Parameters

projection [Matrix4x4](#)

The [Matrix4x4](#) projection to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushRasterizerState(RasterizerStateDescription)

Push the requested [RasterizerStateDescription](#) for the [PrimitiveBatch](#).

```
public void PushRasterizerState(RasterizerStateDescription rasterizerState)
```

Parameters

rasterizerState [RasterizerStateDescription](#)

The [RasterizerStateDescription](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [PrimitiveBatch](#) has not begun.

PushScissorRect(Rectangle?)

Push the requested [Rectangle](#) scissor for the [PrimitiveBatch](#).

```
public void PushScissorRect(Rectangle? rectangle)
```

Parameters

rectangle [Rectangle](#)?

The [Rectangle](#) scissor to apply for rendering.

Exceptions

Exception

Thrown if the [PrimitiveBatch](#) has not begun.

PushView(Matrix4x4)

Push the requested [Matrix4x4](#) view for the [PrimitiveBatch](#).

```
public void PushView(Matrix4x4 view)
```

Parameters

view [Matrix4x4](#)

The [Matrix4x4](#) view to apply for rendering.

Exceptions

Exception

Thrown if the [PrimitiveBatch](#) has not begun.

Namespace Bliss.CSharp.Graphics.Rendering. Renderers.Batches.Sprites

Classes

[SpriteBatch](#)

Enums

[SpriteFlip](#)

Class SpriteBatch

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Batches.Sprites](#)

Assembly: Bliss.dll

```
public class SpriteBatch : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← SpriteBatch

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

SpriteBatch(GraphicsDevice, IWindow, uint)

Initializes a new instance of the [SpriteBatch](#) class for batching and rendering 2D sprites.

```
public SpriteBatch(GraphicsDevice graphicsDevice, IWindow window, uint capacity = 4096)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used for rendering.

window [IWindow](#)

The [IWindow](#) associated with the rendering context.

capacity [uint](#)

The maximum number of sprites the batch can hold. Defaults to 4.096.

Properties

Capacity

Specifies the maximum number of sprites that the SpriteBatch can process in a single draw call.

```
public uint Capacity { get; }
```

Property Value

[uint](#)

DrawCallCount

Gets the number of draw calls made during the current batch rendering session. This count is reset to zero each time [Begin\(CommandList, OutputDescription, Sampler?, Effect?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?, Matrix4x4?, Matrix4x4?, Rectangle?\)](#) is called and increments with each call to Bliss.CSharp.Graphics.Rendering.Renderers.Batches.Sprites.SpriteBatch.Flush().

```
public int DrawCallCount { get; }
```

Property Value

[int](#)

FontStashRenderer

Provides access to a font rendering system within the [SpriteBatch](#). Utilizes [FontStashRenderer2D](#) for efficient rendering of text with support for various styles and effects.

```
public FontStashRenderer2D FontStashRenderer { get; }
```

Property Value

[FontStashRenderer2D](#)

GraphicsDevice

Gets the [GraphicsDevice](#) associated with the [SpriteBatch](#). This device is responsible for managing and rendering graphics resources such as buffers, shaders, and textures.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Window

Represents the window used for rendering graphics.

```
public IWindow Window { get; }
```

Property Value

[IWindow](#)

Methods

AddQuad(Texture2D, SpriteVertex2D, SpriteVertex2D, SpriteVertex2D, SpriteVertex2D)

Adds a quad to the sprite batch for rendering.

```
public void AddQuad(Texture2D texture, SpriteVertex2D topLeft, SpriteVertex2D topRight,
SpriteVertex2D bottomLeft, SpriteVertex2D bottomRight)
```

Parameters

texture [Texture2D](#)

The [Texture2D](#) to be used for the quad's rendering.

topLeft [SpriteVertex2D](#)

The [SpriteVertex2D](#) defining the top-left vertex of the quad.

topRight [SpriteVertex2D](#)

The [SpriteVertex2D](#) defining the top-right vertex of the quad.

bottomLeft [SpriteVertex2D](#)

The [SpriteVertex2D](#) defining the bottom-left vertex of the quad.

bottomRight [SpriteVertex2D](#)

The [SpriteVertex2D](#) defining the bottom-right vertex of the quad.

Exceptions

[Exception](#)

Thrown if the SpriteBatch has not been started by calling [Begin](#).

Begin(CommandList, OutputDescription, Sampler?, Effect?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?, Matrix4x4?, Matrix4x4?, Rectangle?)

Begins a sprite batch operation, initializing the specified settings for rendering.

```
public void Begin(CommandList commandList, OutputDescription output, Sampler? sampler = null, Effect? effect = null, BlendStateDescription? blendState = null, DepthStencilStateDescription? depthStencilState = null, RasterizerStateDescription? rasterizerState = null, Matrix4x4? projection = null, Matrix4x4? view = null, Rectangle? scissorRect = null)
```

Parameters

commandList [CommandList](#)

The [CommandList](#) to which rendering commands will be submitted.

output [OutputDescription](#)

The [OutputDescription](#) that defines the render target and its properties.

sampler [Sampler](#)

An optional [Sampler](#) object used for texture sampling. Defaults to a point sampler if not specified.

effect [Effect](#)

An optional [Effect](#) to apply during rendering. Defaults to the global default sprite effect if not specified.

blendState [BlendStateDescription](#)?

An optional [BlendStateDescription](#) for configuring blend state. Defaults to single alpha blending if not specified.

depthStencilState [DepthStencilStateDescription](#)?

An optional [DepthStencilStateDescription](#) for configuring depth and stencil behavior. Defaults to a depth-only, less-equal test configuration if not specified.

rasterizerState [RasterizerStateDescription](#)?

An optional [RasterizerStateDescription](#) for defining rasterizer behavior. Defaults to no culling if not specified.

projection [Matrix4x4](#)?

An optional [Matrix4x4](#) for the projection matrix. Defaults to an orthographic projection based on the associated window dimensions if not specified.

view [Matrix4x4](#)?

An optional [Matrix4x4](#) for the view matrix. Defaults to the identity matrix if not specified.

scissorRect [Rectangle](#)?

An optional [Rectangle](#) that defines the scissor rectangle for rendering. No scissor rect is applied if not specified.

Exceptions

[Exception](#)

Thrown when the method is called before the previous batch has been properly ended.

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

DrawText(Font, string, Vector2, float, float, float, Vector2?, float, Vector2?, float, Color?, TextStyle, FontSystemEffect, int)

Draws the specified text at the given position with the provided font and styling options.

```
public void DrawText(Font font, string text, Vector2 position, float size, float characterSpacing = 0, float lineSpacing = 0, Vector2? scale = null, float layerDepth = 0.5, Vector2? origin = null, float rotation = 0, Color? color = null, TextStyle style = TextStyle.None, FontSystemEffect effect = FontSystemEffect.None, int effectAmount = 0)
```

Parameters

`font` [Font](#)

The font to be used for drawing the text.

`text` [string](#)

The text to be drawn.

`position` [Vector2](#)

The position on the screen where the text will be drawn.

`size` [float](#)

The size of the text.

`characterSpacing` [float](#)

Optional spacing between characters. Default is 0.0F.

lineSpacing [float](#)?

Optional spacing between lines of text. Default is 0.0F.

scale [Vector2](#)?

Optional scale applied to the text. Default is null.

layerDepth [float](#)?

Optional depth value for sorting layers. Default is 0.5F.

origin [Vector2](#)?

Optional origin point for rotation and scaling. Default is null.

rotation [float](#)?

Optional rotation angle in radians. Default is 0.0F.

color [Color](#)?

Optional color of the text. Default is null.

style TextStyle

Optional text style. Default is TextStyle.None.

effect FontSystemEffect

Optional effect applied to the text. Default is FontSystemEffect.None.

effectAmount [int](#)?

Optional amount for the effect applied. Default is 0.

DrawTexture(Texture2D, Vector2, float, Rectangle?, Vector2?, Vector2?, float, Color?, SpriteFlip)

Draws a texture onto the screen with configurable position, scaling, rotation, depth, and color.

```
public void DrawTexture(Texture2D texture, Vector2 position, float layerDepth = 0.5,
    Rectangle? sourceRect = null, Vector2? scale = null, Vector2? origin = null, float rotation
```

```
= 0, Color? color = null, SpriteFlip flip = SpriteFlip.None)
```

Parameters

texture [Texture2D](#)

The [Texture2D](#) to render.

position [Vector2](#)

The position on the screen where the texture will be drawn, specified in world coordinates.

layerDepth [float](#)

Optional depth value for sorting layers. Defaults to 0.5F.

sourceRect [Rectangle](#)?

An optional [Rectangle](#) specifying the region of the texture to be used. If null, the entire texture is used.

scale [Vector2](#)?

The scaling factor applied to the texture. Defaults to no scaling (1.0F, 1.0F).

origin [Vector2](#)?

The origin point for rotation and scaling, relative to the source rectangle. Defaults to the top-left corner.

rotation [float](#)

The angle, in degrees, to rotate the texture about the origin point. Defaults to 0.0F.

color [Color](#)?

The [Color](#) to apply to the texture for tinting. Defaults to White (no tint).

flip [SpriteFlip](#)

The flip mode to apply to the texture, such as horizontal or vertical flipping. Defaults to [None](#).

End()

Ends the current drawing session that was initiated by a call to [Begin\(CommandList, OutputDescription, Sampler?, Effect?, BlendStateDescription?, DepthStencilStateDescription?, RasterizerStateDescription?, ...\)](#).

[Matrix4x4?](#), [Matrix4x4?](#), [Rectangle?](#)). This method finalizes the batch operations by flushing all pending draw calls.

```
public void End()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentBlendState()

Retrieves the current [BlendStateDescription](#) used by the [SpriteBatch](#) for rendering operations.

```
public BlendStateDescription GetCurrentBlendState()
```

Returns

[BlendStateDescription](#)

The [BlendStateDescription](#) representing the current blending configuration.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentDepthStencilState()

Gets the current depth and stencil state configuration used for rendering in the [SpriteBatch](#).

```
public DepthStencilStateDescription GetCurrentDepthStencilState()
```

Returns

[DepthStencilStateDescription](#)

The current [DepthStencilStateDescription](#) used by the [SpriteBatch](#) for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentEffect()

Retrieves the current [Effect](#) being used by the [SpriteBatch](#).

```
public Effect GetCurrentEffect()
```

Returns

[Effect](#)

The active [Effect](#) instance used for rendering, or null if no effect is set.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentOutput()

Retrieves the current [OutputDescription](#) being used by the [SpriteBatch](#).

```
public OutputDescription GetCurrentOutput()
```

Returns

[OutputDescription](#)

The [OutputDescription](#) currently associated with the [SpriteBatch](#).

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentProjection()

Retrieves the current projection matrix used by the [SpriteBatch](#).

```
public Matrix4x4 GetCurrentProjection()
```

Returns

[Matrix4x4](#)

The current [Matrix4x4](#) projection matrix.

Exceptions

[Exception](#)

Thrown if the sprite batch operation has not been started.

GetCurrentRasterizerState()

Gets the current rasterizer state used for configuring rasterization settings in the rendering pipeline.

```
public RasterizerStateDescription GetCurrentRasterizerState()
```

Returns

[RasterizerStateDescription](#)

A [RasterizerStateDescription](#) representing the current rasterizer state.

Exceptions

[Exception](#)

Thrown if the sprite batch operation has not been started.

GetCurrentSampler()

Retrieves the current [Sampler](#) used for texture sampling operations in the [SpriteBatch](#).

```
public Sampler GetCurrentSampler()
```

Returns

[Sampler](#)

The current [Sampler](#) instance being used.

Exceptions

[Exception](#)

Thrown if the sprite batch operation has not been started.

GetCurrentScissorRect()

Retrieves the current scissor rectangle being used by the [SpriteBatch](#).

```
public Rectangle? GetCurrentScissorRect()
```

Returns

[Rectangle?](#)

The current scissor rectangle, or null if no scissor rectangle is set.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

GetCurrentView()

Retrieves the current view matrix used for rendering.

```
public Matrix4x4 GetCurrentView()
```

Returns

[Matrix4x4](#)

The current [Matrix4x4](#) view matrix.

Exceptions

[Exception](#)

Thrown if the sprite batch operation has not been started.

PopBlendState()

Pop the current [BlendStateDescription](#) to the main blend state used by the [SpriteBatch](#).

```
public void PopBlendState()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopDepthStencilState()

Pop the current [DepthStencilStateDescription](#) to the main depth stencil state used by the [SpriteBatch](#).

```
public void PopDepthStencilState()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopEffect()

Pop the current [Effect](#) to the main effect used by the [SpriteBatch](#).

```
public void PopEffect()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopOutput()

Pop the output of the [OutputDescription](#) for the [SpriteBatch](#).

```
public void PopOutput()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopProjection()

Pop the current [Matrix4x4](#) to the main projection used by the [SpriteBatch](#).

```
public void PopProjection()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopRasterizerState()

Pop the current [RasterizerStateDescription](#) to the main rasterizer state used by the [SpriteBatch](#).

```
public void PopRasterizerState()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopSampler()

Pop the current [Sampler](#) to the main sampler used by the [SpriteBatch](#).

```
public void PopSampler()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopScissorRect()

Pop the current [Rectangle](#) scissor to the main scissor used by the [SpriteBatch](#).

```
public void PopScissorRect()
```

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PopView()

Pop the current [Matrix4x4](#) to the main view used by the [SpriteBatch](#).

```
public void PopView()
```

Exceptions

[Exception ↗](#)

Thrown if the [SpriteBatch](#) has not begun.

PushBlendState(BlendStateDescription)

Push the requested [BlendStateDescription](#) for the [SpriteBatch](#).

```
public void PushBlendState(BlendStateDescription blendState)
```

Parameters

blendState [BlendStateDescription](#)

The [BlendStateDescription](#) to apply for rendering.

Exceptions

[Exception ↗](#)

Thrown if the [SpriteBatch](#) has not begun.

PushDepthStencilState(DepthStencilStateDescription)

Push the requested [DepthStencilStateDescription](#) for the [SpriteBatch](#).

```
public void PushDepthStencilState(DepthStencilStateDescription depthStencilState)
```

Parameters

depthStencilState [DepthStencilStateDescription](#)

The [DepthStencilStateDescription](#) to apply for rendering.

Exceptions

[Exception ↗](#)

Thrown if the [SpriteBatch](#) has not begun.

PushEffect(Effect)

Push the requested [Effect](#) for the [SpriteBatch](#).

```
public void PushEffect(Effect effect)
```

Parameters

[effect Effect](#)

The [Effect](#) to apply for rendering.

Exceptions

[Exception ↗](#)

Thrown if the [SpriteBatch](#) has not begun.

PushOutput(OutputDescription)

Push the requested [OutputDescription ↗](#) for the [SpriteBatch](#).

```
public void PushOutput(OutputDescription output)
```

Parameters

[output OutputDescription ↗](#)

The [OutputDescription ↗](#) to apply for rendering.

Exceptions

[Exception ↗](#)

Thrown if the [SpriteBatch](#) has not begun.

PushProjection(Matrix4x4)

Push the requested [Matrix4x4](#) projection for the [SpriteBatch](#).

```
public void PushProjection(Matrix4x4 projection)
```

Parameters

projection [Matrix4x4](#)

The [Matrix4x4](#) projection to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PushRasterizerState(RasterizerStateDescription)

Push the requested [RasterizerStateDescription](#) for the [SpriteBatch](#).

```
public void PushRasterizerState(RasterizerStateDescription rasterizerState)
```

Parameters

rasterizerState [RasterizerStateDescription](#)

The [RasterizerStateDescription](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PushSampler(Sampler)

Push the requested [Sampler](#) for the [SpriteBatch](#).

```
public void PushSampler(Sampler sampler)
```

Parameters

sampler [Sampler](#)

The [Sampler](#) to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PushScissorRect(Rectangle?)

Push the requested [Rectangle](#) scissor for the [SpriteBatch](#).

```
public void PushScissorRect(Rectangle? rectangle)
```

Parameters

rectangle [Rectangle](#)?

The [Rectangle](#) scissor to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

PushView(Matrix4x4)

Push the requested [Matrix4x4](#) view for the [SpriteBatch](#).

```
public void PushView(Matrix4x4 view)
```

Parameters

view [Matrix4x4](#)

The [Matrix4x4](#) view to apply for rendering.

Exceptions

[Exception](#)

Thrown if the [SpriteBatch](#) has not begun.

Enum SpriteFlip

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Batches.Sprites](#)

Assembly: Bliss.dll

```
public enum SpriteFlip
```

Fields

Both = 3

The sprite is flipped both vertically and horizontally.

Horizontal = 2

The sprite is flipped horizontally.

None = 0

No flipping applied to the sprite.

Vertical = 1

The sprite is flipped vertically.

Namespace Bliss.CSharp.Graphics.Rendering.Renderers.Forward

Classes

[ForwardRenderer<T>](#)

[Renderable](#)

Interfaces

[IRenderer](#)

Class ForwardRenderer<T>

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward](#)

Assembly: Bliss.dll

```
public class ForwardRenderer<T> : Disposable, IRenderer, IDisposable where T : unmanaged
```

Type Parameters

T

Inheritance

[object](#) ← [Disposable](#) ← ForwardRenderer<T>

Implements

[IRenderer](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#), [Disposable.Dispose\(\)](#), [Disposable.ThrowIfDisposed\(\)](#), [object.Equals\(object\)](#),
[object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

ForwardRenderer(GraphicsDevice, ILightHandler<T>?)

```
public ForwardRenderer(GraphicsDevice graphicsDevice, ILightHandler<T>? lightHandler = null)
```

Parameters

graphicsDevice [GraphicsDevice](#)

lightHandler [ILightHandler](#)<T>

Properties

GraphicsDevice

The graphics device used for rendering.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

LightHandler

The light handler responsible for managing and updating light data for rendering operations.

```
public ILightHandler<T>? LightHandler { get; }
```

Property Value

[ILightHandler](#)<T>

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

Draw(CommandList, OutputDescription)

Executes the rendering process for drawing opaque and translucent renderable objects.

```
public void Draw(CommandList commandList, OutputDescription output)
```

Parameters

commandList [CommandList](#)

The command list used to execute rendering commands.

output [OutputDescription](#)

The output description specifying the rendering target configuration.

DrawRenderable(Renderable)

Queues a renderable for drawing.

```
public void DrawRenderable(Renderable renderable)
```

Parameters

renderable [Renderable](#)

The renderable to draw.

Interface IRenderer

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward](#)

Assembly: Bliss.dll

```
public interface IRenderer : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#)

Methods

Draw(CommandList, OutputDescription)

Performs a rendering operation using the specified [CommandList](#) and [OutputDescription](#).

```
void Draw(CommandList commandList, OutputDescription output)
```

Parameters

commandList [CommandList](#)

The command list that records GPU draw commands.

output [OutputDescription](#)

The output description that defines the render target format and depth configuration.

DrawRenderable(Renderable)

Draws the specified [Renderable](#) object using the renderer's internal pipeline and state.

```
void DrawRenderable(Renderable renderable)
```

Parameters

renderable [Renderable](#)

The renderable object to be drawn.

Class Renderable

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward](#)

Assembly: Bliss.dll

```
public class Renderable
```

Inheritance

[object](#) ← Renderable

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Renderable(Mesh, Transform, Material)

Initializes a new [Renderable](#) with a specific material.

```
public Renderable(Mesh mesh, Transform transform, Material material)
```

Parameters

mesh [Mesh](#)

The mesh to render.

transform [Transform](#)

The transform to apply.

material [Material](#)

The material to use for this renderable.

Renderable(Mesh, Transform, bool)

Initializes a new [Renderable](#) using the mesh's material or a cloned material.

```
public Renderable(Mesh mesh, Transform transform, bool copyMeshMaterial = false)
```

Parameters

mesh [Mesh](#)

The mesh to render.

transform [Transform](#)

The transform to apply.

copyMeshMaterial [bool](#)

If true, creates a cloned copy of the mesh's material to allow independent modification. If false, uses the mesh's existing material.

Fields

Material

The material used for rendering.

```
public Material Material
```

Field Value

[Material](#)

Transform

The transformation (position, rotation, scale) applied to this renderable.

```
public Transform Transform
```

Field Value

Properties

BoneMatrices

Optional array of bone matrices for skinned meshes.

```
public Matrix4x4[]? BoneMatrices { get; }
```

Property Value

[Matrix4x4](#)[]

Mesh

The mesh associated with this renderable object.

```
public Mesh Mesh { get; }
```

Property Value

[Mesh](#)

Namespace Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lightning

Structs

[LightDefinition](#)

Enums

[LightType](#)

Struct LightDefinition

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting](#)

Assembly: Bliss.dll

```
public struct LightDefinition
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

LightDefinition(LightType, Vector3?, Vector3?, Vector3?, float, float, float)

Initializes a new instance of the [LightDefinition](#) struct.

```
public LightDefinition(LightType lightType, Vector3? position = null, Vector3? direction = null, Vector3? color = null, float intensity = 1, float range = 0, float spotAngle = 0)
```

Parameters

lightType [LightType](#)

The type of the light (Directional, Point, or Spot).

position [Vector3](#)?

The position of the light in world space.

direction [Vector3](#)?

The direction of the light in world space.

color [Vector3](#)?

The base color of the light as a [Vector3](#).

intensity [float](#)

The brightness or intensity of the light.

range [float](#)

The range of the light.

spotAngle [float](#)

The angle of the spotlight cone in radians.

Fields

Color

Gets or sets the color of the light as an RGB vector.

```
public Vector3 Color
```

Field Value

[Vector3](#)

Direction

Gets or sets the direction of the light in world space.

```
public Vector3 Direction
```

Field Value

[Vector3](#)

Intensity

Gets or sets the brightness or intensity of the light.

```
public float Intensity
```

Field Value

[float](#)

LightType

Gets or sets the type of the light (Directional, Point, or Spot).

```
public LightType LightType
```

Field Value

[LightType](#)

Position

Gets or sets the position of the light in world space.

```
public Vector3 Position
```

Field Value

[Vector3](#)

Range

Gets or sets the range of the light.

```
public float Range
```

Field Value

[float](#)

SpotAngle

Gets or sets the angle of the spotlight cone in radians.

```
public float SpotAngle
```

Field Value

[float](#)

Enum LightType

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting](#)

Assembly: Bliss.dll

```
public enum LightType
```

Fields

Directional = 0

A directional light, simulating a distant light source with parallel rays (e.g., sunlight).

Point = 1

A point light emitting light in all directions from a single position.

Spot = 2

A spotlight emitting light in a cone from a position in a specified direction.

Namespace Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lightning.Data

Structs

[DynamicLightData](#)

[FixedLightData](#)

[FixedLightData.LightArray](#)

Represents a fixed-size, inline array for storing light information.

[Light](#)

[NoLightData](#)

Represents an empty or placeholder structure for scenarios where no light data is required.

Struct DynamicLightData

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Data](#)

Assembly: Bliss.dll

```
public struct DynamicLightData
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Fields

AmbientColor

Gets or sets the global ambient color applied to the scene, where W stores intensity.

```
public Vector4 AmbientColor
```

Field Value

[Vector4](#)

NumOfLights

Gets or sets the current number of lights in the container.

```
public int NumOfLights
```

Field Value

[int](#)

Struct FixedLightData

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Data](#)

Assembly: Bliss.dll

```
public struct FixedLightData
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Fields

AmbientColor

Gets or sets the global ambient color applied to the scene, where W stores intensity.

```
public Vector4 AmbientColor
```

Field Value

[Vector4](#)

Lights

The collection of lights used in the rendering process.

```
public FixedLightData.LightArray Lights
```

Field Value

[FixedLightData.LightArray](#)

MaxLightCount

The maximum number of lights that can be stored in the container.

```
public const int MaxLightCount = 512
```

Field Value

[int↗](#)

NumOfLights

Gets or sets the current number of lights in the container.

```
public int NumOfLights
```

Field Value

[int↗](#)

Struct FixedLightData.LightArray

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Data](#)

Assembly: Bliss.dll

Represents a fixed-size, inline array for storing light information.

```
public struct FixedLightData.LightArray
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Methods

AsReadOnlySpan()

```
[UnscopedRef]  
public readonly ReadOnlySpan<Light> AsReadOnlySpan()
```

Returns

[ReadOnlySpan](#) <Light>

AsSpan()

```
[UnscopedRef]  
public Span<Light> AsSpan()
```

Returns

[Span](#) <Light>

Struct Light

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Data](#)

Assembly: Bliss.dll

```
public struct Light
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

`Light(LightType, int, Vector3, Vector3, Vector3, float, float, float)`

Initializes a new instance of the [Light](#) struct.

```
public Light(LightType type, int id, Vector3 position = default, Vector3 direction = default, Vector3 color = default, float intensity = 1, float range = 0, float spotAngle = 0)
```

Parameters

`type` [LightType](#)

The type of the light (Directional, Point, or Spot).

`id` [int](#)

The unique identifier of the light.

`position` [Vector3](#)

The position of the light in world space.

`direction` [Vector3](#)

The direction of the light (used for directional and spot lights).

`color` [Vector3](#)

The base color of the light as a [Vector3](#).

intensity [float](#)

The brightness or intensity of the light.

range [float](#)

The range of the light (used for point and spot lights).

spotAngle [float](#)

The angle of the spotlight cone in radians.

Properties

Color

Gets or sets the color of the light as an RGB vector.

```
public Vector3 Color { get; set; }
```

Property Value

[Vector3](#)

Direction

Gets or sets the direction of the light in world space. (Relevant for directional and spot lights)

```
public Vector3 Direction { get; set; }
```

Property Value

[Vector3](#)

Id

Gets the unique identifier of the [Light](#) instance.

```
public int Id { get; }
```

Property Value

[int](#)

Intensity

Gets or sets the intensity (brightness) of the light.

```
public float Intensity { get; set; }
```

Property Value

[float](#)

LightType

Gets or sets the type of the light (Directional, Point, or Spot).

```
public LightType LightType { get; set; }
```

Property Value

[LightType](#)

Position

Gets or sets the position of the light in world space.

```
public Vector3 Position { get; set; }
```

Property Value

[Vector3](#)

Range

Gets or sets the range of the light. (Relevant for point and spot lights)

```
public float Range { get; set; }
```

Property Value

[float](#) ↗

SpotAngle

Gets or sets the cone angle of the spotlight in radians. (Relevant for spot lights)

```
public float SpotAngle { get; set; }
```

Property Value

[float](#) ↗

Struct NoLightData

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Data](#)

Assembly: Bliss.dll

Represents an empty or placeholder structure for scenarios where no light data is required.

```
public struct NoLightData
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Namespace Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lightning.Handlers

Classes

[DynamicLightHandler](#)

[FixedLightHandler](#)

Interfaces

[ILightHandler<T>](#)

Class DynamicLightHandler

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Handlers](#)

Assembly: Bliss.dll

```
public class DynamicLightHandler : Disposable, ILightHandler<DynamicLightData>, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← DynamicLightHandler

Implements

[ILightHandler<DynamicLightData>](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

DynamicLightHandler(int, Vector3, float)

Initializes a new instance of the [DynamicLightHandler](#) class.

```
public DynamicLightHandler(int lightCapacity = 256, Vector3 ambientColor = default, float  
ambientColorIntensity = 0.1)
```

Parameters

lightCapacity [int](#)

The maximum number of lights that can be stored.

ambientColor [Vector3](#)

The global ambient color applied to the scene.

ambientColorIntensity [float](#)

The intensity of the ambient color.

Properties

AmbientColor

Gets or sets the global ambient color applied to the scene.

```
public Vector3 AmbientColor { get; set; }
```

Property Value

[Vector3](#)

AmbientColorIntensity

Gets or sets the intensity of the ambient color.

```
public float AmbientColorIntensity { get; set; }
```

Property Value

[float](#)

this[int]

Provides indexed access to the lights managed by this handler.

```
public ref Light this[int index] { get; }
```

Parameters

[index](#) [int](#)

The zero-based index of the light.

Property Value

[Light](#)

A reference to the light at the specified index.

LightCapacity

Gets the maximum number of lights supported by this handler.

```
public int LightCapacity { get; }
```

Property Value

[int](#)

LightData

Gets the underlying light data managed by this handler.

```
public DynamicLightData LightData { get; }
```

Property Value

[DynamicLightData](#)

UseStorageBuffer

Gets a value indicating whether this handler uses a storage buffer.

```
public bool UseStorageBuffer { get; }
```

Property Value

[bool](#)

Methods

AddLight(LightDefinition, out uint)

Adds a new light to this handler or throws if it cannot be added.

```
public void AddLight(LightDefinition lightDef, out uint id)
```

Parameters

lightDef [LightDefinition](#)

The light definition used to create the light.

id [uint](#)

The unique identifier assigned to the new light.

Exceptions

[Exception](#)

Thrown if the light cannot be added due to capacity or duplicate ID.

ClearLights()

Removes all lights from this handler.

```
public void ClearLights()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

GetLightById(uint)

Retrieves a reference to a light with the specified ID.

```
public ref Light GetLightById(uint id)
```

Parameters

[id](#) [uint](#)

The unique identifier of the light.

Returns

[Light](#)

A reference to the light with the given ID.

Exceptions

[KeyNotFoundException](#)

Thrown if no light with the given ID exists.

GetLights()

Retrieves all lights managed by this handler as a read-only span.

```
public ReadOnlySpan<Light> GetLights()
```

Returns

[ReadOnlySpan](#) <[Light](#)>

A [ReadOnlySpan](#) containing all lights.

GetNumOfLights()

Gets the current number of lights in this handler.

```
public int GetNumOfLights()
```

Returns

[int](#)

The number of lights currently stored.

RemoveLight(uint)

Removes the light with the specified ID or throws if it cannot be removed.

```
public void RemoveLight(uint id)
```

Parameters

[id](#) [uint](#)

The unique identifier of the light to remove.

Exceptions

[Exception](#)

Thrown if no light with the given ID exists.

TryAddLight(LightDefinition, out uint)

Attempts to add a new light to this handler.

```
public bool TryAddLight(LightDefinition lightDef, out uint id)
```

Parameters

`lightDef` [LightDefinition](#)

The light definition used to create the light.

`id` [uint](#)

The unique identifier assigned to the new light.

Returns

[bool](#)

`true` if the light was added successfully; otherwise, `false`.

`TryRemoveLight(uint)`

Attempts to remove the light with the specified ID.

```
public bool TryRemoveLight(uint id)
```

Parameters

`id` [uint](#)

The unique identifier of the light to remove.

Returns

[bool](#)

`true` if the light was removed successfully; otherwise, `false`.

Class FixedLightHandler

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Handlers](#)

Assembly: Bliss.dll

```
public class FixedLightHandler : Disposable, ILightHandler<FixedLightData>, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← FixedLightHandler

Implements

[ILightHandler<FixedLightData>](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

FixedLightHandler(Vector3, float)

Initializes a new instance of the [FixedLightHandler](#) class.

```
public FixedLightHandler(Vector3 ambientColor = default, float ambientColorIntensity = 0.1)
```

Parameters

ambientColor [Vector3](#)

The global ambient color applied to the scene.

ambientColorIntensity [float](#)

The intensity of the ambient color.

Properties

AmbientColor

Gets or sets the global ambient color applied to the scene.

```
public Vector3 AmbientColor { get; set; }
```

Property Value

[Vector3](#)

AmbientColorIntensity

Gets or sets the intensity of the ambient color.

```
public float AmbientColorIntensity { get; set; }
```

Property Value

[float](#)

this[int]

Provides indexed access to the lights managed by this handler.

```
public ref Light this[int index] { get; }
```

Parameters

[index](#) [int](#)

The zero-based index of the light.

Property Value

[Light](#)

A reference to the light at the specified index.

LightCapacity

Gets the maximum number of lights supported by this handler.

```
public int LightCapacity { get; }
```

Property Value

[int](#)

LightData

Gets the underlying light data managed by this handler.

```
public FixedLightData LightData { get; }
```

Property Value

[FixedLightData](#)

UseStorageBuffer

Gets a value indicating whether this handler uses a storage buffer.

```
public bool UseStorageBuffer { get; }
```

Property Value

[bool](#)

Methods

AddLight(LightDefinition, out uint)

Adds a new light to this handler or throws if it cannot be added.

```
public void AddLight(LightDefinition lightDef, out uint id)
```

Parameters

[lightDef LightDefinition](#)

The light definition used to create the light.

[id uint](#)

The unique identifier assigned to the new light.

Exceptions

[Exception](#)

Thrown if the light cannot be added due to capacity or duplicate ID.

ClearLights()

Removes all lights from this handler.

```
public void ClearLights()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing bool](#)

True if called from user code; false if called from a finalizer.

GetLightById(uint)

Retrieves a reference to a light with the specified ID.

```
public ref Light GetLightById(uint id)
```

Parameters

[id uint](#)

The unique identifier of the light.

Returns

[Light](#)

A reference to the light with the given ID.

Exceptions

[KeyNotFoundException](#)

Thrown if no light with the given ID exists.

GetLights()

Retrieves all lights managed by this handler as a read-only span.

```
public ReadOnlySpan<Light> GetLights()
```

Returns

[ReadOnlySpan](#)<[Light](#)>

A [ReadOnlySpan](#)<[T](#)> containing all lights.

GetNumOfLights()

Gets the current number of lights in this handler.

```
public int GetNumOfLights()
```

Returns

[int ↗](#)

The number of lights currently stored.

RemoveLight(uint)

Removes the light with the specified ID or throws if it cannot be removed.

```
public void RemoveLight(uint id)
```

Parameters

[id uint ↗](#)

The unique identifier of the light to remove.

Exceptions

[Exception ↗](#)

Thrown if no light with the given ID exists.

TryAddLight(LightDefinition, out uint)

Attempts to add a new light to this handler.

```
public bool TryAddLight(LightDefinition lightDef, out uint id)
```

Parameters

[lightDef LightDefinition](#)

The light definition used to create the light.

[id uint](#)

The unique identifier assigned to the new light.

Returns

[bool](#)

true if the light was added successfully; otherwise, **false**.

TryRemoveLight(uint)

Attempts to remove the light with the specified ID.

```
public bool TryRemoveLight(uint id)
```

Parameters

[id uint](#)

The unique identifier of the light to remove.

Returns

[bool](#)

true if the light was removed successfully; otherwise, **false**.

Interface ILightHandler<T>

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Handlers](#)

Assembly: Bliss.dll

```
public interface ILightHandler<T> : IDisposable where T : unmanaged
```

Type Parameters

T

Inherited Members

[IDisposable.Dispose\(\)](#)

Properties

AmbientColor

Gets or sets the ambient color applied globally to the scene.

```
Vector3 AmbientColor { get; set; }
```

Property Value

[Vector3](#)

AmbientColorIntensity

Gets or sets the intensity of the ambient color.

```
float AmbientColorIntensity { get; set; }
```

Property Value

[float](#)

this[int]

Gets a reference to the light at the specified index.

```
ref Light this[int index] { get; }
```

Parameters

`index` [int](#)

The zero-based index of the light.

Property Value

[Light](#)

A reference to the [Light](#) at the given index.

LightCapacity

Gets the maximum number of lights supported by this handler.

```
int LightCapacity { get; }
```

Property Value

[int](#)

LightData

Gets the underlying unmanaged light data structure.

```
T LightData { get; }
```

Property Value

T

UseStorageBuffer

Gets a value indicating whether this light handler uses a storage buffer.

```
bool UseStorageBuffer { get; }
```

Property Value

[bool](#)

Methods

AddLight(LightDefinition, out uint)

Adds a new light definition to the container and outputs its assigned identifier.

```
void AddLight(LightDefinition lightDef, out uint id)
```

Parameters

[lightDef](#) [LightDefinition](#)

The light definition to add.

[id](#) [uint](#)

The unique identifier assigned to the new light.

ClearLights()

Clears all lights stored within the container.

```
void ClearLights()
```

GetLightById(uint)

Gets a reference to the light with the specified unique identifier.

```
ref Light GetLightById(uint id)
```

Parameters

id [uint](#)

The unique identifier of the light.

Returns

[Light](#)

A reference to the [Light](#) with the given ID.

GetLights()

Retrieves all lights in this container as a read-only span.

```
ReadOnlySpan<Light> GetLights()
```

Returns

[ReadOnlySpan](#) <[Light](#)>

A [ReadOnlySpan](#) of [Light](#) instances.

GetNumOfLights()

Gets the number of active lights stored in the container.

```
int GetNumOfLights()
```

Returns

[int](#)

The total number of lights.

RemoveLight(uint)

Removes the light with the specified identifier from the container.

```
void RemoveLight(uint id)
```

Parameters

id [uint](#)

The unique identifier of the light to remove.

TryAddLight(LightDefinition, out uint)

Attempts to add a new light definition to the container and outputs its identifier if successful.

```
bool TryAddLight(LightDefinition lightDef, out uint id)
```

Parameters

lightDef [LightDefinition](#)

The light definition to add.

id [uint](#)

The unique identifier assigned to the new light.

Returns

[bool](#)

true if the light was added successfully; otherwise, **false**.

TryRemoveLight(uint)

Attempts to remove the light with the specified identifier from the container.

```
bool TryRemoveLight(uint id)
```

Parameters

id [uint](#)

The unique identifier of the light to remove.

Returns

[bool](#)

true if the light was removed successfully; otherwise, **false**.

Namespace Bliss.CSharp.Graphics.Rendering. Renderers.Forward.Lightning.Shadowing Classes

[ShadowMap](#)

Class ShadowMap

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Lighting.Shadowing](#)

Assembly: Bliss.dll

```
public class ShadowMap : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← ShadowMap

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ShadowMap(GraphicsDevice, int)

```
public ShadowMap(GraphicsDevice graphicsDevice, int resolution = 1024)
```

Parameters

graphicsDevice [GraphicsDevice](#)

resolution [int](#)

Properties

DepthTexture

```
public Texture DepthTexture { get; }
```

Property Value

[Texture](#) ↗

Framebuffer

```
public Framebuffer Framebuffer { get; }
```

Property Value

[Framebuffer](#) ↗

GraphicsDevice

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#) ↗

Resolution

```
public int Resolution { get; }
```

Property Value

[int](#) ↗

Methods

CreateFrameBuffer()

```
public void CreateFrameBuffer()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

Namespace Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Materials.Data

Structs

[MaterialData](#)

[MaterialMapData](#)

Struct MaterialData

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Materials.Data](#)

Assembly: Bliss.dll

```
public struct MaterialData
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Fields

MaxMaterialMapCount

The maximum number of material maps supported per material.

```
public const int MaxMaterialMapCount = 8
```

Field Value

[int](#)

Properties

this[int]

Gets a reference to the [MaterialMapData](#) at the specified index.

```
public ref MaterialMapData this[int index] { get; }
```

Parameters

index [int](#)

The zero-based index of the material map.

Property Value

[MaterialMapData](#)

A reference to the [MaterialMapData](#) at the given index.

RenderMode

Gets or sets the render mode of the material.

```
public RenderMode RenderMode { get; set; }
```

Property Value

[RenderMode](#)

Struct MaterialMapData

Namespace: [Bliss.CSharp.Graphics.Rendering.Renderers.Forward.Materials.Data](#)

Assembly: Bliss.dll

```
public struct MaterialMapData
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Fields

Color

The RGBA color associated with the material map.

```
public Vector4 Color
```

Field Value

[Vector4](#)

SizeInBytes

The total size of this structure in bytes.

```
public const int SizeInBytes = 32
```

Field Value

[int](#)

Value

A scalar value parameter used by the material map.

```
public float Value
```

Field Value

[float](#)

Namespace Bliss.CSharp.Graphics.VertexTypes

Structs

[CubemapVertex3D](#)

[ImmediateVertex3D](#)

[PrimitiveVertex2D](#)

[SpriteVertex2D](#)

[Vertex3D](#)

Struct CubemapVertex3D

Namespace: [Bliss.CSharp.Graphics.VertexTypes](#)

Assembly: Bliss.dll

```
public struct CubemapVertex3D
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

CubemapVertex3D(Vector3, Vector4)

Initializes a new instance of the [CubemapVertex3D](#) structure.

```
public CubemapVertex3D(Vector3 position, Vector4 color)
```

Parameters

position [Vector3](#)

The position of the vertex in 3D space.

color [Vector4](#)

The color of the vertex.

Fields

Color

The color of the vertex.

```
public Vector4 Color
```

Field Value

[Vector4](#) ↗

Position

The position of the vertex in 3D space.

```
public Vector3 Position
```

Field Value

[Vector3](#) ↗

VertexLayout

Represents the layout description for the [CubemapVertex3D](#) structure.

```
public static VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#) ↗

Struct ImmediateVertex3D

Namespace: [Bliss.CSharp.Graphics.VertexTypes](#)

Assembly: Bliss.dll

```
public struct ImmediateVertex3D
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

ImmediateVertex3D(Vector3, Vector2, Vector4)

Initializes a new instance of the [ImmediateVertex3D](#) structure with the specified position, texture coordinates, and color.

```
public ImmediateVertex3D(Vector3 position, Vector2 texCoords, Vector4 color)
```

Parameters

position [Vector3](#)

The position of the vertex in 3D space.

texCoords [Vector2](#)

The texture coordinates associated with the vertex.

color [Vector4](#)

The color of the vertex.

Fields

Color

The color of the vertex.

```
public Vector4 Color
```

Field Value

[Vector4](#)

Position

The position of the vertex in 3D space.

```
public Vector3 Position
```

Field Value

[Vector3](#)

TexCoords

The primary texture coordinates of the vertex.

```
public Vector2 TexCoords
```

Field Value

[Vector2](#)

VertexLayout

Represents the layout description for the [ImmediateVertex3D](#) structure.

```
public static VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#)

Struct PrimitiveVertex2D

Namespace: [Bliss.CSharp.Graphics.VertexTypes](#)

Assembly: Bliss.dll

```
public struct PrimitiveVertex2D
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

PrimitiveVertex2D(Vector3, Vector4)

Initializes a new instance of the [PrimitiveVertex2D](#) struct with the specified position and color values.

```
public PrimitiveVertex2D(Vector3 position, Vector4 color)
```

Parameters

position [Vector3](#)

The 2D position of the vertex (Z is used for layout depth).

color [Vector4](#)

The color of the vertex, represented as a Vector4 (RGBA).

Fields

Color

The color of the vertex.

```
public Vector4 Color
```

Field Value

[Vector4](#) ↗

Position

The position of the vertex in 2D space (Z is used for layout depth).

```
public Vector3 Position
```

Field Value

[Vector3](#) ↗

VertexLayout

Represents the layout description for the [PrimitiveVertex2D](#) structure.

```
public static VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#) ↗

Struct SpriteVertex2D

Namespace: [Bliss.CSharp.Graphics.VertexTypes](#)

Assembly: Bliss.dll

```
public struct SpriteVertex2D
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

SpriteVertex2D(Vector3, Vector2, Vector4)

Initializes a new instance of the [SpriteVertex2D](#) struct with the specified position, texture coordinates, and color.

```
public SpriteVertex2D(Vector3 position, Vector2 texCoords, Vector4 color)
```

Parameters

position [Vector3](#)

The 2D position of the vertex (Z is used for layout depth).

texCoords [Vector2](#)

The texture coordinates of the vertex.

color [Vector4](#)

The color of the vertex as a vector with RGBA components.

Fields

Color

The color of the vertex.

```
public Vector4 Color
```

Field Value

[Vector4](#)

Position

The position of the vertex in 2D space (Z is used for layout depth).

```
public Vector3 Position
```

Field Value

[Vector3](#)

TexCoords

The texture coordinates of the vertex.

```
public Vector2 TexCoords
```

Field Value

[Vector2](#)

VertexLayout

Represents the layout description for the [SpriteVertex2D](#) structure.

```
public static VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#)

Struct Vertex3D

Namespace: [Bliss.CSharp.Graphics.VertexTypes](#)

Assembly: Bliss.dll

```
public struct Vertex3D
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Vertex3D(Vector3, Vector4, UInt4, Vector2, Vector2, Vector3, Vector4, Vector4)

Initializes a new instance of the [Vertex3D](#) struct with the specified position, bone weights, bone indices, texture coordinates, normal, tangent, and color values.

```
public Vertex3D(Vector3 position, Vector4 boneWeights, UInt4 boneIndices, Vector2 texCoords,  
Vector2 texCoords2, Vector3 normal, Vector4 tangent, Vector4 color)
```

Parameters

position [Vector3](#)

The position of the vertex in 3D space.

boneWeights [Vector4](#)

The weights associated with bones for skeletal animation.

boneIndices [UInt4](#)

The indices of bones influencing this vertex.

texCoords [Vector2](#)

The primary texture coordinates of the vertex.

texCoords2 [Vector2](#)

The secondary texture coordinates of the vertex.

normal [Vector3](#)

The normal vector at the vertex, used for lighting calculations.

tangent [Vector4](#)

The tangent vector at the vertex, used for normal mapping. Also includes the sign for bitangent.

color [Vector4](#)

The color of the vertex, stored as an RGBA float vector.

Fields

BoneIndices

Represents the indices of the vertex's associated bones, used in conjunction with bone weights for skeletal animation.

```
public UInt4 BoneIndices
```

Field Value

[UInt4](#)

BoneWeights

Represents the weights of the vertex's associated bones, used for skinning in skeletal animation.

```
public Vector4 BoneWeights
```

Field Value

[Vector4](#)

Color

The color of the vertex.

```
public Vector4 Color
```

Field Value

[Vector4](#)

Normal

The normal vector of the vertex, used for lighting calculations.

```
public Vector3 Normal
```

Field Value

[Vector3](#)

Position

The position of the vertex in 3D space.

```
public Vector3 Position
```

Field Value

[Vector3](#)

Tangent

The tangent vector of the vertex, used for normal mapping.

```
public Vector4 Tangent
```

Field Value

[Vector4](#) ↗

TexCoords

The primary texture coordinates of the vertex.

```
public Vector2 TexCoords
```

Field Value

[Vector2](#) ↗

TexCoords2

The secondary texture coordinates of the vertex.

```
public Vector2 TexCoords2
```

Field Value

[Vector2](#) ↗

VertexLayout

Represents the layout description for the [Vertex3D](#) structure.

```
public static VertexLayoutDescription VertexLayout
```

Field Value

[VertexLayoutDescription](#) ↗

Methods

AddBone(uint, float)

Adds a bone to the vertex and assigns a weight to it.

```
public void AddBone(uint id, float weight)
```

Parameters

id [uint](#)

The identifier of the bone.

weight [float](#)

The weight of the bone influence.

Namespace Bliss.CSharp.Images

Classes

[AnimatedImage](#)

[Image](#)

Class AnimatedImage

Namespace: [Bliss.CSharp.Images](#)

Assembly: Bliss.dll

```
public class AnimatedImage
```

Inheritance

[object](#) ← AnimatedImage

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

AnimatedImage(Stream)

Initializes a new instance of the [AnimatedImage](#) class from a stream.

```
public AnimatedImage(Stream stream)
```

Parameters

stream [Stream](#)

The stream containing the animated image data.

AnimatedImage(string)

Initializes a new instance of the [AnimatedImage](#) class from a file path.

```
public AnimatedImage(string path)
```

Parameters

path [string](#)

The file path to the animated image (e.g., a GIF).

Properties

Frames

Gets a read-only dictionary containing the frames of the animated image and their respective delays (in milliseconds).

```
public IReadOnlyDictionary<Image, int> Frames { get; }
```

Property Value

[IReadOnlyDictionary](#)<Image, int>

SpriteSheet

Gets the sprite sheet representation of the animated image, where all frames are arranged in a single image.

```
public Image SpriteSheet { get; }
```

Property Value

[Image](#)

Methods

GetFrameCount()

Retrieves the total number of frames in the animated image.

```
public int GetFrameCount()
```

Returns

[int](#)

The number of frames in the animated image.

GetFrameInfo(int, out int, out int, out float)

Retrieves information of a specific frame in the animated image, including its dimensions and duration.

```
public void GetFrameInfo(int frameIndex, out int width, out int height, out float duration)
```

Parameters

frameIndex [int](#)

The index of the frame to retrieve information for.

width [int](#)

The output parameter that returns the width of the specified frame.

height [int](#)

The output parameter that returns the height of the specified frame.

duration [float](#)

The output parameter that returns the duration of the specified frame in milliseconds.

Class Image

Namespace: [Bliss.CSharp.Images](#)

Assembly: Bliss.dll

```
public class Image : ICloneable
```

Inheritance

[object](#) ← Image

Implements

[ICloneable](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Image(byte[])

Initializes a new instance of the [Image](#) class from raw byte data.

```
public Image(byte[] data)
```

Parameters

data [byte](#)[]

The raw image data in RGBA format.

Image(Stream)

Initializes a new instance of the [Image](#) class by loading an image from the specified stream.

```
public Image(Stream stream)
```

Parameters

`stream Stream`

The input stream containing image data to load.

Exceptions

`ArgumentException`

Thrown if the stream cannot be read.

`Image(int, int, Color)`

Initializes a new instance of the `Image` class with a solid color.

```
public Image(int width, int height, Color color)
```

Parameters

`width int`

The width of the image in pixels.

`height int`

The height of the image in pixels.

`color Color`

The color to fill the image with.

`Image(int, int, byte[]?)`

Initializes a new instance of the `Image` class with the specified dimensions and optional data.

```
public Image(int width, int height, byte[]? data = null)
```

Parameters

width [int](#)

The width of the image in pixels.

height [int](#)

The height of the image in pixels.

data [byte](#)[]

The optional raw data to initialize the image with.

Image(string)

Initializes a new instance of the [Image](#) class by loading an image from the specified file path.

```
public Image(string path)
```

Parameters

path [string](#)

The file path of the image to load.

Exceptions

[FileNotFoundException](#)

Thrown when the specified file does not exist.

Properties

Data

Gets or sets the raw image data as a byte array, typically in RGBA format.

```
public byte[] Data { get; set; }
```

Property Value

[byte](#)[]

Exceptions

[ArgumentException](#)

Thrown when the assigned data size does not match the product of the image's width, height, and the number of color components (4 for RGBA).

Height

Gets or sets the height of the image in pixels.

```
public int Height { get; set; }
```

Property Value

[int](#)

Exceptions

[ArgumentOutOfRangeException](#)

Thrown when a non-positive value is assigned to the height.

Width

Gets or sets the width of the image in pixels.

```
public int Width { get; set; }
```

Property Value

[int](#)

Exceptions

[ArgumentOutOfRangeException](#)

Thrown when a negative or zero value is assigned to the width.

Methods

Clone()

Creates a deep copy of this image.

```
public object Clone()
```

Returns

[object](#)

A new [Image](#) instance with identical data.

Crop(Rectangle)

Crops the image to the specified rectangular region.

```
public void Crop(Rectangle crop)
```

Parameters

`crop` [Rectangle](#)

The rectangular area to crop the image to.

Exceptions

[ArgumentOutOfRangeException](#)

Thrown when the specified rectangle is outside the bounds of the image.

FlipHorizontal()

Flips the image horizontally by mirroring its pixel data across the vertical axis.

```
public void FlipHorizontal()
```

FlipVertical()

Flips the image vertically by inverting the order of rows in the image data.

```
public void FlipVertical()
```

GetColor(int, int)

Gets the color of a specific pixel in the image.

```
public Color GetColor(int x, int y)
```

Parameters

x [int](#)

The x-coordinate of the pixel.

y [int](#)

The y-coordinate of the pixel.

Returns

[Color](#)

The color of the specified pixel.

Resize(int, int)

Resizes the image to the specified width and height, maintaining proportional scaling.

```
public void Resize(int newWidth, int newHeight)
```

Parameters

`newWidth` [int](#)

The desired width of the resized image.

`newHeight` [int](#)

The desired height of the resized image.

ResizeNN(int, int)

Resizes the image to the specified width and height using the nearest-neighbor algorithm.

```
public void ResizeNN(int newWidth, int newHeight)
```

Parameters

`newWidth` [int](#)

The new width of the image.

`newHeight` [int](#)

The new height of the image.

Rotate(int)

Rotates the image by the specified degrees in a clockwise direction.

```
public void Rotate(int degrees)
```

Parameters

`degrees` [int](#)

The angle in degrees to rotate the image. Must be a multiple of 90.

RotateCCW()

Rotates the current [Image](#) instance counterclockwise by 90 degrees.

```
public void RotateCCW()
```

RotateCW()

Rotates the current [Image](#) 90 degrees clockwise. Updates the image's dimensions and pixel data accordingly.

```
public void RotateCW()
```

SaveAsBmp(string)

Saves the image as a BMP file.

```
public void SaveAsBmp(string path)
```

Parameters

path [string](#) ↗

The path where the BMP file should be saved.

SaveAsHdr(string)

Saves the image as an HDR file.

```
public void SaveAsHdr(string path)
```

Parameters

path [string](#) ↗

The path where the HDR file should be saved.

SaveAsJpg(string, int)

Saves the image as a JPG file with the specified quality.

```
public void SaveAsJpg(string path, int quality)
```

Parameters

path [string](#)

The path where the JPG file should be saved.

quality [int](#)

The quality of the JPG image (1-100).

SaveAsPng(string)

Saves the image as a PNG file.

```
public void SaveAsPng(string path)
```

Parameters

path [string](#)

The path where the PNG file should be saved.

SaveAsTga(string)

Saves the image as a TGA file.

```
public void SaveAsTga(string path)
```

Parameters

path [string](#)

The path where the TGA file should be saved.

SetPixel(int, int, Color)

Sets the color of a specific pixel in the image.

```
public void SetPixel(int x, int y, Color color)
```

Parameters

x [int](#)

The x-coordinate of the pixel.

y [int](#)

The y-coordinate of the pixel.

color [Color](#)

The new color of the pixel.

Tint(Color)

Applies a tint to the image by adjusting its pixel color values based on the specified tint color.

```
public void Tint(Color tint)
```

Parameters

tint [Color](#)

The color tint to be applied to the image.

Namespace Bliss.CSharp.Interact

Classes

[Input](#)

Class Input

Namespace: [Bliss.CSharp.Interact](#)

Assembly: Bliss.dll

```
public static class Input
```

Inheritance

[object](#) ← Input

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Properties

InputContext

Gets the current input context used to manage and handle input events.

```
public static IInputContext InputContext { get; }
```

Property Value

[IInputContext](#)

Methods

Begin()

Begins input processing by interacting with the InputContext. This method should be called at the start of an input processing phase.

```
public static void Begin()
```

Destroy()

Destroys the Input context and releases any associated resources.

```
public static void Destroy()
```

DisableRelativeMouseMode()

Disables the relative mouse mode.

```
public static void DisableRelativeMouseMode()
```

DisableTextInput()

Disable the text input process, ending any active text input session.

```
public static void DisableTextInput()
```

EnableRelativeMouseMode()

Enables relative mouse mode, which locks the cursor to the center of the window and provides relative motion data instead of absolute position.

```
public static void EnableRelativeMouseMode()
```

EnableTextInput()

Activates text input mode, allowing the application to receive typed text events.

```
public static void EnableTextInput()
```

End()

Finalizes the input handling for the current frame.

```
public static void End()
```

GetAvailableGamepadCount()

Gets the count of available gamepads.

```
public static uint GetAvailableGamepadCount()
```

Returns

[uint](#)

The number of available gamepads.

GetClipboardText()

Retrieves the current text from the system clipboard via the InputContext.

```
public static string GetClipboardText()
```

Returns

[string](#)

The current clipboard text.

GetGamepadAxisMovement(uint, GamepadAxis)

Retrieves the movement value of the specified axis on the given gamepad.

```
public static float GetGamepadAxisMovement(uint gamepad, GamepadAxis axis)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

axis [GamepadAxis](#)

The axis of the gamepad to check.

Returns

[float](#)

The movement value of the specified axis.

GetGamepadName(uint)

Gets the name of the specified gamepad.

```
public static string GetGamepadName(uint gamepad)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

Returns

[string](#)

The name of the specified gamepad.

GetMouseCursor()

Gets the current mouse cursor from the input context.

```
public static ICursor GetMouseCursor()
```

Returns

GetMouseDelta()

Retrieves the change in mouse position since the last frame.

```
public static Vector2 GetMouseDelta()
```

Returns

[Vector2](#)

A Vector2 representing the delta of the mouse movement.

GetMousePosition()

Gets the current position of the mouse in window coordinates.

```
public static Vector2 GetMousePosition()
```

Returns

[Vector2](#)

The current position of the mouse as a Vector2.

GetTypedText(out string)

Retrieves any text that was typed since the last frame, but only while text input is active via [EnableTextInput\(\)](#).

```
public static bool GetTypedText(out string text)
```

Parameters

text [string](#)

The typed text collected since the previous frame. Will be empty if no text was entered.

Returns

[bool](#)

`true` if any text was entered; otherwise, `false`.

HideCursor()

Hides the mouse cursor.

```
public static void HideCursor()
```

Init(IInputContext)

Initializes the Input class with the specified input context.

```
public static void Init(IInputContext inputContext)
```

Parameters

`inputContext` [IInputContext](#)

The input context to initialize.

IsCursorShown()

Checks if the cursor is currently shown.

```
public static bool IsCursorShown()
```

Returns

[bool](#)

True if the cursor is shown; otherwise, false.

IsFileDragDropped(out string)

Determines whether a file has been drag-dropped onto the application.

```
public static bool IsFileDragDropped(out string path)
```

Parameters

`path` [string](#)

The path of the drag-dropped file, if one exists.

Returns

[bool](#)

True if a file was drag-dropped; otherwise, false.

IsGamepadAvailable(uint)

Checks if the specified gamepad is available.

```
public static bool IsGamepadAvailable(uint gamepad)
```

Parameters

`gamepad` [uint](#)

The index of the gamepad to check.

Returns

[bool](#)

True if the gamepad is available; otherwise, false.

IsGamepadButtonDown(uint, GamepadButton)

Checks if a specific gamepad button is currently pressed.

```
public static bool IsGamepadButtonDown(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The ID of the gamepad to check.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the button is pressed, otherwise false.

IsGamepadButtonPressed(uint, GamepadButton)

Checks if the specified button on the given gamepad is pressed.

```
public static bool IsGamepadButtonPressed(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad to check.

button [GamepadButton](#)

The button on the gamepad to check.

Returns

[bool](#)

True if the button is pressed; otherwise, false.

IsGamepadButtonReleased(uint, GamepadButton)

Checks if the specified gamepad button is released.

```
public static bool IsGamepadButtonReleased(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The gamepad identifier.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the specified gamepad button is released; otherwise, false.

IsGamepadButtonUp(uint, GamepadButton)

Checks if the specified gamepad button is not pressed.

```
public static bool IsGamepadButtonUp(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the specified gamepad button is up; otherwise, false.

IsKeyDown(KeyboardKey)

Checks if the specified keyboard key is currently pressed down.

```
public static bool IsKeyDown(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

True if the key is pressed down; otherwise, false.

IsKeyPressed(KeyboardKey, bool)

Checks if the specified keyboard key is currently pressed.

```
public static bool IsKeyPressed(KeyboardKey key, bool enableRepeat = false)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

enableRepeat [bool](#)

A flag indicating whether the key press should be considered a repeated action.

Returns

[bool](#)

True if the specified key is pressed; otherwise, false.

IsKeyReleased(KeyboardKey)

Checks if the specified key has been released.

```
public static bool IsKeyReleased(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

True if the key has been released; otherwise, false.

IsKeyUp(KeyboardKey)

Determines whether the specified key is currently up (not pressed).

```
public static bool IsKeyUp(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

True if the key is up; otherwise, false.

IsMouseButtonDoubleClicked(MouseButton)

Checks if the specified mouse button was double-clicked during the current frame.

```
public static bool IsMouseButtonDoubleClicked(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check for a double-click event.

Returns

[bool](#) ↗

True if the specified mouse button was double-clicked; otherwise, false.

IsMouseButtonDown(MouseButton)

Checks if the specified mouse button is currently being pressed down.

```
public static bool IsMouseButtonDown(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button is down; otherwise, false.

IsMouseButtonPressed(MouseButton)

Checks if the specified mouse button was pressed in the current frame.

```
public static bool IsMouseButtonPressed(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button was pressed; otherwise, false.

IsMouseButtonReleased(MouseButton)

Checks if the specified mouse button was released in the current frame.

```
public static bool IsMouseButtonReleased(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button was released; otherwise, false.

IsMouseButtonUp(MouseButton)

Checks if the specified mouse button is currently up (not pressed).

```
public static bool IsMouseButtonUp(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button is up; otherwise, false.

IsMouseMoving(out Vector2)

Checks if the mouse is currently moving and provides its position.

```
public static bool IsMouseMoving(out Vector2 position)
```

Parameters

position [Vector2](#) ↗

The current position of the mouse if it is moving.

Returns

[bool](#) ↗

True if the mouse is moving; otherwise, false.

IsMouseScrolling(out Vector2)

Checks if the mouse is currently scrolling and retrieves the wheel delta if it is.

```
public static bool IsMouseScrolling(out Vector2 wheelDelta)
```

Parameters

wheelDelta [Vector2](#) ↗

The vector representing the scroll delta of the mouse.

Returns

[bool](#)

True if the mouse is scrolling, otherwise false.

IsRelativeMouseModeEnabled()

Checks if relative mouse mode is enabled, where the cursor is locked to the window.

```
public static bool IsRelativeMouseModeEnabled()
```

Returns

[bool](#)

True if relative mouse mode is enabled; otherwise, false.

IsTextInputActive()

Determines whether text input mode is currently active.

```
public static bool IsTextInputActive()
```

Returns

[bool](#)

True if text input is active; otherwise, false.

RumbleGamepad(uint, ushort, ushort, uint)

Generates a rumble effect on the specified gamepad.

```
public static void RumbleGamepad(uint gamepad, ushort lowFrequencyRumble, ushort
```

```
highFrequencyRumble, uint durationMs)
```

Parameters

gamepad [uint](#)

The index of the gamepad to rumble.

lowFrequencyRumble [ushort](#)

The intensity of the low-frequency rumble.

highFrequencyRumble [ushort](#)

The intensity of the high-frequency rumble.

durationMs [uint](#)

Duration of the rumble effect in milliseconds.

SetClipboardText(string)

Sets the clipboard content to the specified text.

```
public static void SetClipboardText(string text)
```

Parameters

text [string](#)

The text to set to the clipboard.

SetMouseCursor(ICursor)

Sets the mouse cursor to the specified cursor.

```
public static void SetMouseCursor(ICursor cursor)
```

Parameters

`cursor` [ICursor](#)

The cursor to set.

SetMousePosition(Vector2)

Sets the mouse position to the specified coordinates.

```
public static void SetMousePosition(Vector2 position)
```

Parameters

`position` [Vector2](#)

The position to set the mouse to.

ShowCursor()

Shows the mouse cursor.

```
public static void ShowCursor()
```

Namespace Bliss.CSharp.Interact.Contexts

Classes

[Sdl3InputContext](#)

Interfaces

[IInputContext](#)

Interface IInputContext

Namespace: [Bliss.CSharp.Interact.Contexts](#)

Assembly: Bliss.dll

```
public interface IInputContext : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#) ↗

Methods

Begin()

Begins input processing for the current frame.

```
void Begin()
```

DisableRelativeMouseMode()

Disables relative mouse mode.

```
void DisableRelativeMouseMode()
```

DisableTextInput()

Disable the text input process, ending any active text input session.

```
void DisableTextInput()
```

EnableRelativeMouseMode()

Enables relative mouse mode.

```
void EnableRelativeMouseMode()
```

EnableTextInput()

Activates text input mode, allowing the application to receive typed text events.

```
void EnableTextInput()
```

End()

Ends input processing for the current frame.

```
void End()
```

GetAvailableGamepadCount()

Gets the count of available gamepads.

```
uint GetAvailableGamepadCount()
```

Returns

[uint](#)

The number of available gamepads.

GetClipboardText()

Retrieves the current text from the system clipboard.

```
string GetClipboardText()
```

Returns

[string](#)

The clipboard text.

GetGamepadAxisMovement(uint, GamepadAxis)

Retrieves the movement value of the specified axis on the given gamepad.

```
float GetGamepadAxisMovement(uint gamepad, GamepadAxis axis)
```

Parameters

[gamepad](#) [uint](#)

The index of the gamepad.

[axis](#) [GamepadAxis](#)

The axis of the gamepad to check.

Returns

[float](#)

The movement value of the specified axis.

GetGamepadName(uint)

Gets the name of the specified gamepad.

```
string GetGamepadName(uint gamepad)
```

Parameters

[gamepad](#) [uint](#)

The index of the gamepad.

Returns

[string](#)

The name of the specified gamepad.

GetMouseCursor()

Gets the current mouse cursor.

`ICursor GetMouseCursor()`

Returns

[ICursor](#)

The current mouse cursor.

GetMouseDelta()

Retrieves the change in mouse position since the last frame.

`Vector2 GetMouseDelta()`

Returns

[Vector2](#)

A Vector2 representing the delta of the mouse movement.

GetMousePosition()

Gets the current position of the mouse in window coordinates.

`Vector2 GetMousePosition()`

Returns

[Vector2](#)

The mouse position as a [Vector2](#).

GetTypedText(out string)

Retrieves any text that was typed since the last frame, but only while text input is active via [EnableTextInput\(\)](#).

```
bool GetTypedText(out string text)
```

Parameters

text [string](#)

The typed text collected since the previous frame. Will be empty if no text was entered.

Returns

[bool](#)

true if any text was entered; otherwise, **false**.

HideCursor()

Hides the mouse cursor.

```
void HideCursor()
```

IsCursorShown()

Checks if the cursor is currently shown.

```
bool IsCursorShown()
```

Returns

[bool](#)

True if the cursor is shown; otherwise, false.

IsFileDragDropped(out string)

Checks if a file has been drag-dropped onto the application.

```
bool IsFileDragDropped(out string path)
```

Parameters

path [string](#)

When this method returns, contains the path of the file that was drag-dropped.

Returns

[bool](#)

True if a file was drag-dropped; otherwise, false.

IsGamepadAvailable(uint)

Checks if the specified gamepad is available.

```
bool IsGamepadAvailable(uint gamepad)
```

Parameters

gamepad [uint](#)

The index of the gamepad to check.

Returns

[bool](#)

True if the gamepad is available; otherwise, false.

IsGamepadButtonDown(uint, GamepadButton)

Checks if the specified button on the given gamepad is currently being pressed.

```
bool IsGamepadButtonDown(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

button [GamepadButton](#)

The button on the gamepad to check.

Returns

[bool](#)

True if the specified button is pressed, otherwise false.

IsGamepadButtonPressed(uint, GamepadButton)

Checks if a specific gamepad button is pressed.

```
bool IsGamepadButtonPressed(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The button on the gamepad to check.

Returns

[bool](#)

True if the specified button is pressed; otherwise, false.

IsGamepadButtonReleased(uint, GamepadButton)

Determines whether a specific button on a specified gamepad has been released.

```
bool IsGamepadButtonReleased(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the button was released; otherwise, false.

IsGamepadButtonUp(uint, GamepadButton)

Determines whether a specified button on the specified gamepad is currently not pressed.

```
bool IsGamepadButtonUp(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The gamepad button to check.

Returns

`bool` ↗

True if the button is up (not pressed); otherwise, false.

IsKeyDown(KeyboardKey)

Checks if a specified key is currently pressed down.

`bool IsKeyDown(KeyboardKey key)`

Parameters

`key` [KeyboardKey](#)

The key to check the state of.

Returns

`bool` ↗

True if the key is pressed, false otherwise.

IsKeyPressed(KeyboardKey, bool)

Checks if the specified keyboard key is currently pressed.

`bool IsKeyPressed(KeyboardKey key, bool enableRepeat = false)`

Parameters

`key` [KeyboardKey](#)

The keyboard key to check.

`enableRepeat` `bool` ↗

A flag indicating whether the key press should be considered a repeated action.

Returns

[bool](#)

True if the specified key is pressed; otherwise, false.

IsKeyReleased(KeyboardKey)

Checks if a specified keyboard key has been released.

`bool IsKeyReleased(KeyboardKey key)`

Parameters

`key` [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

True if the key has been released, otherwise false.

IsKeyUp(KeyboardKey)

Checks if a specific keyboard key is currently in the released state.

`bool IsKeyUp(KeyboardKey key)`

Parameters

`key` [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

Returns true if the specified key is up; otherwise, false.

IsMouseButtonDoubleClicked(MouseButton)

Checks if the specified mouse button was double-clicked during the current frame.

```
bool IsMouseButtonDoubleClicked(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check for a double-click event.

Returns

[bool](#) ↗

True if the specified mouse button was double-clicked; otherwise, false.

IsMouseButtonDown(MouseButton)

Checks if the specified mouse button is currently being held down.

```
bool IsMouseButtonDown(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button is down; otherwise, false.

IsMouseButtonPressed(MouseButton)

Checks if the specified mouse button was pressed in the current frame.

```
bool IsMouseButtonPressed(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button was pressed; otherwise, false.

IsMouseButtonReleased(MouseButton)

Checks if the specified mouse button was released in the current frame.

```
bool IsMouseButtonReleased(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button was released; otherwise, false.

IsMouseButtonUp(MouseButton)

Checks if the specified mouse button is currently up (not pressed).

```
bool IsMouseButtonUp(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#)

True if the button is up; otherwise, false.

IsMouseMoving(out Vector2)

Checks if the mouse is moving and returns the current position if it is.

```
bool IsMouseMoving(out Vector2 position)
```

Parameters

position [Vector2](#)

The current mouse position.

Returns

[bool](#)

True if the mouse is moving; otherwise, false.

IsMouseScrolling(out Vector2)

Checks if the mouse is scrolling and returns the scroll delta if it is.

```
bool IsMouseScrolling(out Vector2 wheelDelta)
```

Parameters

`wheelDelta` [Vector2](#)

The scroll delta of the mouse.

Returns

[bool](#)

True if the mouse is scrolling; otherwise, false.

IsRelativeMouseModeEnabled()

Checks if relative mouse mode is enabled, where the cursor is locked to the window.

`bool IsRelativeMouseModeEnabled()`

Returns

[bool](#)

True if relative mouse mode is enabled; otherwise, false.

IsTextInputActive()

Determines whether text input mode is currently active.

`bool IsTextInputActive()`

Returns

[bool](#)

True if text input is active; otherwise, false.

RumbleGamepad(uint, ushort, ushort, uint)

Generates a rumble effect on the specified gamepad.

```
void RumbleGamepad(uint gamepad, ushort lowFrequencyRumble, ushort highFrequencyRumble,  
uint durationMs)
```

Parameters

gamepad [uint](#)

The index of the gamepad to rumble.

lowFrequencyRumble [ushort](#)

The intensity of the low-frequency rumble.

highFrequencyRumble [ushort](#)

The intensity of the high-frequency rumble.

durationMs [uint](#)

Duration of the rumble effect in milliseconds.

SetClipboardText(string)

Sets the clipboard content to the specified text.

```
void SetClipboardText(string text)
```

Parameters

text [string](#)

The text to set to the clipboard.

SetMouseCursor(ICursor)

Sets the mouse cursor to the specified cursor.

```
void SetMouseCursor(ICursor cursor)
```

Parameters

cursor [ICursor](#)

The cursor to set.

SetMousePosition(Vector2)

Sets the mouse position to the specified coordinates.

```
void SetMousePosition(Vector2 position)
```

Parameters

position [Vector2](#)

The position to set the mouse to.

ShowCursor()

Shows the mouse cursor.

```
void ShowCursor()
```

Class Sdl3InputContext

Namespace: [Bliss.CSharp.Interact.Contexts](#)

Assembly: Bliss.dll

```
public class Sdl3InputContext : Disposable, IInputContext, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Sdl3InputContext

Implements

[IInputContext](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Sdl3InputContext(IWindow)

Initializes a new instance of the [Sdl3InputContext](#) class for handling input events from a window.

```
public Sdl3InputContext(IWindow window)
```

Parameters

window [IWindow](#)

The window associated with the input context. Must be an SDL3 window.

Exceptions

[Exception](#)

Thrown if the provided window is not an SDL3 window.

Methods

Begin()

Begins input processing for the current frame.

```
public void Begin()
```

DisableRelativeMouseMode()

Disables relative mouse mode.

```
public void DisableRelativeMouseMode()
```

DisableTextInput()

Disable the text input process, ending any active text input session.

```
public void DisableTextInput()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing bool

True if called from user code; false if called from a finalizer.

EnableRelativeMouseMode()

Enables relative mouse mode.

```
public void EnableRelativeMouseMode()
```

EnableTextInput()

Activates text input mode, allowing the application to receive typed text events.

```
public void EnableTextInput()
```

End()

Ends input processing for the current frame.

```
public void End()
```

GetAvailableGamepadCount()

Gets the count of available gamepads.

```
public uint GetAvailableGamepadCount()
```

Returns

[uint](#)

The number of available gamepads.

GetClipboardText()

Retrieves the current text from the system clipboard.

```
public string GetClipboardText()
```

Returns

[string](#)

The clipboard text.

GetGamepadAxisMovement(uint, GamepadAxis)

Retrieves the movement value of the specified axis on the given gamepad.

```
public float GetGamepadAxisMovement(uint gamepad, GamepadAxis axis)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

axis [GamepadAxis](#)

The axis of the gamepad to check.

Returns

[float](#)

The movement value of the specified axis.

GetGamepadName(uint)

Gets the name of the specified gamepad.

```
public string GetGamepadName(uint gamepad)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

Returns

[string](#)

The name of the specified gamepad.

GetMouseCursor()

Gets the current mouse cursor.

```
public ICursor GetMouseCursor()
```

Returns

[ICursor](#)

The current mouse cursor.

GetMouseDelta()

Retrieves the change in mouse position since the last frame.

```
public Vector2 GetMouseDelta()
```

Returns

[Vector2](#)

A Vector2 representing the delta of the mouse movement.

GetMousePosition()

Gets the current position of the mouse in window coordinates.

```
public Vector2 GetMousePosition()
```

Returns

[Vector2](#)

The mouse position as a [Vector2](#).

GetTypedText(out string)

Retrieves any text that was typed since the last frame, but only while text input is active via [EnableTextInput\(\)](#).

```
public bool GetTypedText(out string text)
```

Parameters

text [string](#)

The typed text collected since the previous frame. Will be empty if no text was entered.

Returns

[bool](#)

true if any text was entered; otherwise, **false**.

HideCursor()

Hides the mouse cursor.

```
public void HideCursor()
```

IsCursorShown()

Checks if the cursor is currently shown.

```
public bool IsCursorShown()
```

Returns

[bool](#)

True if the cursor is shown; otherwise, false.

IsFileDragDropped(out string)

Checks if a file has been drag-dropped onto the application.

```
public bool IsFileDragDropped(out string path)
```

Parameters

[path](#) [string](#)

When this method returns, contains the path of the file that was drag-dropped.

Returns

[bool](#)

True if a file was drag-dropped; otherwise, false.

IsGamepadAvailable(uint)

Checks if the specified gamepad is available.

```
public bool IsGamepadAvailable(uint gamepad)
```

Parameters

[gamepad](#) [uint](#)

The index of the gamepad to check.

Returns

[bool](#)

True if the gamepad is available; otherwise, false.

IsGamepadButtonDown(uint, GamepadButton)

Checks if the specified button on the given gamepad is currently being pressed.

```
public bool IsGamepadButtonDown(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The index of the gamepad.

button [GamepadButton](#)

The button on the gamepad to check.

Returns

[bool](#)

True if the specified button is pressed, otherwise false.

IsGamepadButtonPressed(uint, GamepadButton)

Checks if a specific gamepad button is pressed.

```
public bool IsGamepadButtonPressed(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The button on the gamepad to check.

Returns

[bool](#)

True if the specified button is pressed; otherwise, false.

IsGamepadButtonReleased(uint, GamepadButton)

Determines whether a specific button on a specified gamepad has been released.

```
public bool IsGamepadButtonReleased(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the button was released; otherwise, false.

IsGamepadButtonUp(uint, GamepadButton)

Determines whether a specified button on the specified gamepad is currently not pressed.

```
public bool IsGamepadButtonUp(uint gamepad, GamepadButton button)
```

Parameters

gamepad [uint](#)

The identifier of the gamepad.

button [GamepadButton](#)

The gamepad button to check.

Returns

[bool](#)

True if the button is up (not pressed); otherwise, false.

IsKeyDown(KeyboardKey)

Checks if a specified key is currently pressed down.

```
public bool IsKeyDown(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The key to check the state of.

Returns

[bool](#)

True if the key is pressed, false otherwise.

IsKeyPressed(KeyboardKey, bool)

Checks if the specified keyboard key is currently pressed.

```
public bool IsKeyPressed(KeyboardKey key, bool enableRepeat = false)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

enableRepeat [bool](#)

A flag indicating whether the key press should be considered a repeated action.

Returns

[bool](#)

True if the specified key is pressed; otherwise, false.

IsKeyReleased(KeyboardKey)

Checks if a specified keyboard key has been released.

```
public bool IsKeyReleased(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

True if the key has been released, otherwise false.

IsKeyUp(KeyboardKey)

Checks if a specific keyboard key is currently in the released state.

```
public bool IsKeyUp(KeyboardKey key)
```

Parameters

key [KeyboardKey](#)

The keyboard key to check.

Returns

[bool](#)

Returns true if the specified key is up; otherwise, false.

IsMouseButtonDoubleClicked(MouseButton)

Checks if the specified mouse button was double-clicked during the current frame.

```
public bool IsMouseButtonDoubleClicked(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check for a double-click event.

Returns

[bool](#) ↗

True if the specified mouse button was double-clicked; otherwise, false.

IsMouseButtonDown(MouseButton)

Checks if the specified mouse button is currently being held down.

```
public bool IsMouseButtonDown(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#) ↗

True if the button is down; otherwise, false.

IsMouseButtonPressed(MouseButton)

Checks if the specified mouse button was pressed in the current frame.

```
public bool IsMouseButtonPressed(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#)

True if the button was pressed; otherwise, false.

IsMouseButtonReleased(MouseButton)

Checks if the specified mouse button was released in the current frame.

```
public bool IsMouseButtonReleased(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#)

True if the button was released; otherwise, false.

IsMouseButtonUp(MouseButton)

Checks if the specified mouse button is currently up (not pressed).

```
public bool IsMouseButtonUp(MouseButton button)
```

Parameters

button [MouseButton](#)

The mouse button to check.

Returns

[bool](#)

True if the button is up; otherwise, false.

IsMouseMoving(out Vector2)

Checks if the mouse is moving and returns the current position if it is.

```
public bool IsMouseMoving(out Vector2 position)
```

Parameters

position [Vector2](#)

The current mouse position.

Returns

[bool](#)

True if the mouse is moving; otherwise, false.

IsMouseScrolling(out Vector2)

Checks if the mouse is scrolling and returns the scroll delta if it is.

```
public bool IsMouseScrolling(out Vector2 wheelDelta)
```

Parameters

`wheelDelta` [Vector2](#)

The scroll delta of the mouse.

Returns

[bool](#)

True if the mouse is scrolling; otherwise, false.

IsRelativeMouseModeEnabled()

Checks if relative mouse mode is enabled, where the cursor is locked to the window.

`public bool IsRelativeMouseModeEnabled()`

Returns

[bool](#)

True if relative mouse mode is enabled; otherwise, false.

IsTextInputActive()

Determines whether text input mode is currently active.

`public bool IsTextInputActive()`

Returns

[bool](#)

True if text input is active; otherwise, false.

RumbleGamepad(uint, ushort, ushort, uint)

Generates a rumble effect on the specified gamepad.

```
public void RumbleGamepad(uint gamepad, ushort lowFrequencyRumble, ushort highFrequencyRumble, uint durationMs)
```

Parameters

gamepad [uint](#)

The index of the gamepad to rumble.

lowFrequencyRumble [ushort](#)

The intensity of the low-frequency rumble.

highFrequencyRumble [ushort](#)

The intensity of the high-frequency rumble.

durationMs [uint](#)

Duration of the rumble effect in milliseconds.

SetClipboardText(string)

Sets the clipboard content to the specified text.

```
public void SetClipboardText(string text)
```

Parameters

text [string](#)

The text to set to the clipboard.

SetMouseCursor(ICursor)

Sets the mouse cursor to the specified cursor.

```
public void SetMouseCursor(ICursor cursor)
```

Parameters

cursor [ICursor](#)

The cursor to set.

SetMousePosition(Vector2)

Sets the mouse position to the specified coordinates.

```
public void SetMousePosition(Vector2 position)
```

Parameters

position [Vector2](#)

The position to set the mouse to.

ShowCursor()

Shows the mouse cursor.

```
public void ShowCursor()
```

Namespace Bliss.CSharp.Interact.Gamepads

Classes

[Sdl3Gamepad](#)

Interfaces

[IGamepad](#)

Enums

[GamepadAxis](#)

[GamepadButton](#)

Enum GamepadAxis

Namespace: [Bliss.CSharp.Interact.Gamepads](#)

Assembly: Bliss.dll

```
public enum GamepadAxis
```

Fields

Invalid = -1

Invalid axis.

LeftX = 0

Left stick horizontal axis.

LeftY = 1

Left stick vertical axis.

Max = 6

Maximum axis value.

RightX = 2

Right stick horizontal axis.

RightY = 3

Right stick vertical axis.

TriggerLeft = 4

Left trigger axis.

TriggerRight = 5

Right trigger axis.

Enum GamepadButton

Namespace: [Bliss.CSharp.Interact.Gamepads](#)

Assembly: Bliss.dll

```
public enum GamepadButton
```

Fields

Back = 4

The "Back" button on the gamepad.

Count = 26

Represents the total number of available buttons.

DpadDown = 12

The directional pad "Down" button.

DpadLeft = 13

The directional pad "Left" button.

DpadRight = 14

The directional pad "Right" button.

DpadUp = 11

The directional pad "Up" button.

East = 1

The "East" face button (often the right button, typically labeled B or Circle).

Guide = 5

The "Guide" button, often used to open system menus.

Invalid = -1

Represents an invalid button.

LeftPaddle1 = 17

The first left paddle button.

LeftPaddle2 = 19

The second left paddle button.

LeftShoulder = 9

The left shoulder button.

LeftStick = 7

The left analog stick button (when pressed down).

Misc1 = 15

A miscellaneous button (Misc1).

Misc2 = 21

A miscellaneous button (Misc2).

Misc3 = 22

A miscellaneous button (Misc3).

Misc4 = 23

A miscellaneous button (Misc4).

Misc5 = 24

A miscellaneous button (Misc5).

Misc6 = 25

A miscellaneous button (Misc6).

North = 3

The "North" face button (often the top button, typically labeled Y or Triangle).

RightPaddle1 = 16

The first right paddle button.

RightPaddle2 = 18

The second right paddle button.

RightShoulder = 10

The right shoulder button.

RightStick = 8

The right analog stick button (when pressed down).

South = 0

The "South" face button (often the bottom button, typically labeled A or X).

Start = 6

The "Start" button on the gamepad.

Touchpad = 20

The touchpad button, commonly found on some controllers.

West = 2

The "West" face button (often the left button, typically labeled X or Square).

Interface IGamepad

Namespace: [Bliss.CSharp.Interact.Gamepads](#)

Assembly: Bliss.dll

```
public interface IGamepad : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#)

Methods

CleanStates()

Cleans or resets the internal states of the gamepad (e.g., button states).

```
void CleanStates()
```

GetAxisMovement(GamepadAxis)

Gets the movement value of a specified axis on the gamepad.

```
float GetAxisMovement(GamepadAxis axis)
```

Parameters

axis [GamepadAxis](#)

The axis to check.

Returns

[float](#)

A float representing the axis movement.

GetHandle()

Gets the handle of the gamepad.

```
nint GetHandle()
```

Returns

[nint](#)

An integer pointer representing the gamepad's handle.

GetIndex()

Gets the index of the gamepad.

```
uint GetIndex()
```

Returns

[uint](#)

An unsigned integer representing the gamepad's index.

GetName()

Gets the name of the gamepad.

```
string GetName()
```

Returns

[string](#)

A string representing the gamepad's name.

IsButtonDown(GamepadButton)

Checks if the specified button is currently being held down.

```
bool IsButtonDown(GamepadButton button)
```

Parameters

button [GamepadButton](#)

The button to check.

Returns

[bool](#)

True if the button is down; otherwise, false.

IsButtonPressed(GamepadButton)

Checks if the specified button was pressed in the current frame.

```
bool IsButtonPressed(GamepadButton button)
```

Parameters

button [GamepadButton](#)

The button to check.

Returns

[bool](#)

True if the button was pressed; otherwise, false.

IsButtonReleased(GamepadButton)

Checks if the specified button was released in the current frame.

```
bool IsButtonReleased(GamepadButton button)
```

Parameters

button [GamepadButton](#)

The button to check.

Returns

[bool](#)

True if the button was released; otherwise, false.

IsButtonUp(GamepadButton)

Checks if the specified button is currently up (not pressed).

```
bool IsButtonUp(GamepadButton button)
```

Parameters

button [GamepadButton](#)

The button to check.

Returns

[bool](#)

True if the button is up; otherwise, false.

Class Sdl3Gamepad

Namespace: [Bliss.CSharp.Interact.Gamepads](#)

Assembly: Bliss.dll

```
public class Sdl3Gamepad : Disposable, IGamepad, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Sdl3Gamepad

Implements

[IGamepad](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#), [Disposable.Dispose\(\)](#), [Disposable.ThrowIfDisposed\(\)](#), [object.Equals\(object\)](#),
[object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

Sdl3Gamepad(IWindow, uint)

Initializes a new instance of the [Sdl3Gamepad](#) class, which manages gamepad input for a specific window.

```
public Sdl3Gamepad(IWindow window, uint index)
```

Parameters

window [IWindow](#)

The window associated with the gamepad.

index [uint](#)

The index of the gamepad to be opened.

Properties

Window

Gets the window associated with the gamepad.

```
public IWindow Window { get; }
```

Property Value

[IWindow](#)

Methods

CleanStates()

Cleans or resets the internal states of the gamepad (e.g., button states).

```
public void CleanStates()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GetAxisMovement(GamepadAxis)

Gets the movement value of a specified axis on the gamepad.

```
public float GetAxisMovement(GamepadAxis axis)
```

Parameters

axis [GamepadAxis](#)

The axis to check.

Returns

[float](#)

A float representing the axis movement.

GetHandle()

Gets the handle of the gamepad.

```
public nint GetHandle()
```

Returns

[nint](#)

An integer pointer representing the gamepad's handle.

GetIndex()

Gets the index of the gamepad.

```
public uint GetIndex()
```

Returns

[uint](#)

An unsigned integer representing the gamepad's index.

GetName()

Gets the name of the gamepad.

```
public string GetName()
```

Returns

[string](#)

A string representing the gamepad's name.

IsButtonDown(GamepadButton)

Checks if the specified button is currently being held down.

```
public bool IsButtonDown(GamepadButton button)
```

Parameters

[button](#) [GamepadButton](#)

The button to check.

Returns

[bool](#)

True if the button is down; otherwise, false.

IsButtonPressed(GamepadButton)

Checks if the specified button was pressed in the current frame.

```
public bool IsButtonPressed(GamepadButton button)
```

Parameters

`button` [GamepadButton](#)

The button to check.

Returns

[bool](#) ↗

True if the button was pressed; otherwise, false.

`IsButtonReleased(GamepadButton)`

Checks if the specified button was released in the current frame.

```
public bool IsButtonReleased(GamepadButton button)
```

Parameters

`button` [GamepadButton](#)

The button to check.

Returns

[bool](#) ↗

True if the button was released; otherwise, false.

`IsButtonUp(GamepadButton)`

Checks if the specified button is currently up (not pressed).

```
public bool IsButtonUp(GamepadButton button)
```

Parameters

`button` [GamepadButton](#)

The button to check.

Returns

bool ↗

True if the button is up; otherwise, false.

Namespace Bliss.CSharp.Interact.Keyboards

Enums

[KeyboardKey](#)

Enum KeyboardKey

Namespace: [Bliss.CSharp.Interact.Keyboards](#)

Assembly: Bliss.dll

```
public enum KeyboardKey
```

Fields

A = 83

Letter key A.

AltLeft = 5

The left Alt key.

AltRight = 6

The right Alt key.

B = 84

Letter key B.

BackSlash = 129

The Backslash key.

BackSpace = 53

The Backspace key.

BracketLeft = 122

The left bracket key.

BracketRight = 123

The right bracket key.

C = 85

Letter key C.

CapsLock = 60

The Caps Lock key.

Clear = 65

The Clear key.

Comma = 126

The Comma key.

ControlLeft = 3

The left Control key.

ControlRight = 4

The right Control key.

D = 86

Letter key D.

Delete = 55

The Delete key.

Down = 46

The Down arrow key.

E = 87

Letter key E.

End = 59

The End key.

Enter = 49

The Enter key.

Escape = 50

The Escape key.

F = 88

Letter key F.

F1 = 10

Function key F1.

F10 = 19

Function key F10.

F11 = 20

Function key F11.

F12 = 21

Function key F12.

F13 = 22

Function key F13.

F14 = 23

Function key F14.

F15 = 24

Function key F15.

F16 = 25

Function key F16.

F17 = 26

Function key F17.

F18 = 27

Function key F18.

F19 = 28

Function key F19.

F2 = 11

Function key F2.

F20 = 29

Function key F20.

F21 = 30

Function key F21.

F22 = 31

Function key F22.

F23 = 32

Function key F23.

F24 = 33

Function key F24.

F25 = 34

Function key F25.

F26 = 35

Function key F26.

F27 = 36

Function key F27.

F28 = 37

Function key F28.

F29 = 38

Function key F29.

F3 = 12

Function key F3.

F30 = 39

Function key F30.

F31 = 40

Function key F31.

F32 = 41

Function key F32.

F33 = 42

Function key F33.

F34 = 43

Function key F34.

F35 = 44

Function key F35.

F4 = 13

Function key F4.

F5 = 14

Function key F5.

F6 = 15

Function key F6.

F7 = 16

Function key F7.

F8 = 17

Function key F8.

F9 = 18

Function key F9.

G = 89

Letter key G.

Grave = 119

The Grave key, also known as the Tilde key.

H = 90

Letter key H.

Home = 58

The Home key.

I = 91

Letter key I.

Insert = 54

The Insert key.

J = 92

Letter key J.

K = 93

Letter key K.

Keypad0 = 67

Numeric keypad key 0.

Keypad1 = 68

Numeric keypad key 1.

Keypad2 = 69

Numeric keypad key 2.

Keypad3 = 70

Numeric keypad key 3.

Keypad4 = 71

Numeric keypad key 4.

Keypad5 = 72

Numeric keypad key 5.

Keypad6 = 73

Numeric keypad key 6.

Keypad7 = 74

Numeric keypad key 7.

Keypad8 = 75

Numeric keypad key 8.

Keypad9 = 76

Numeric keypad key 9.

KeypadDecimal = 81

Numeric keypad decimal point key.

KeypadDivide = 77

Numeric keypad divide key.

KeypadEnter = 82

Numeric keypad Enter key.

KeypadMinus = 79

Numeric keypad minus key.

KeypadMultiply = 78

Numeric keypad multiply key.

KeypadPlus = 80

Numeric keypad plus key.

L = 94

Letter key L.

LastKey = 131

The last recognized key in the enumeration.

Left = 47

The Left arrow key.

M = 95

Letter key M.

Menu = 9

The Menu key, typically used to open context menus.

Minus = 120

The Minus key.

N = 96

Letter key N.

NonUsBackSlash = 130

The Non-US backslash key.

NumLock = 64

The Num Lock key.

Number0 = 109

Number key 0.

Number1 = 110

Number key 1.

Number2 = 111

Number key 2.

Number3 = 112

Number key 3.

Number4 = 113

Number key 4.

Number5 = 114

Number key 5.

Number6 = 115

Number key 6.

Number7 = 116

Number key 7.

Number8 = 117

Number key 8.

Number9 = 118

Number key 9.

O = 97

Letter key O.

P = 98

Letter key P.

PageDown = 57

The Page Down key.

PageUp = 56

The Page Up key.

Pause = 63

The Pause key.

Period = 127

The Period key.

Plus = 121

The Plus key.

PrintScreen = 62

The Print Screen key.

Q = 99

Letter key Q.

Quote = 125

The Quote key.

R = 100

Letter key R.

Right = 48

The Right arrow key.

S = 101

Letter key S.

ScrollLock = 61

The Scroll Lock key.

Semicolon = 124

The Semicolon key.

ShiftLeft = 1

The left Shift key.

ShiftRight = 2

The right Shift key.

Slash = 128

The Slash key.

Sleep = 66

The Sleep key.

Space = 51

The Spacebar key.

T = 102

Letter key T.

Tab = 52

The Tab key.

U = 103

Letter key U.

Unknown = 0

Represents an unknown key.

Up = 45

The Up arrow key.

V = 104

Letter key V.

W = 105

Letter key W.

WinLeft = 7

The left Windows key.

WinRight = 8

The right Windows key.

X = 106

Letter key X.

Y = 107

Letter key Y.

Z = 108

Letter key Z.

Namespace Bliss.CSharp.Interact.Mice

Enums

[MouseButton](#)

Enum MouseButton

Namespace: [Bliss.CSharp.Interact.Mice](#)

Assembly: Bliss.dll

```
public enum MouseButton
```

Fields

Left = 1

The left mouse button.

Middle = 2

The middle mouse button (typically the scroll wheel button).

Right = 3

The right mouse button.

X1 = 4

The first extra (X1) mouse button.

X2 = 5

The second extra (X2) mouse button.

Namespace Bliss.CSharp.Interact.Mice.Cursors

Classes

[Sdl3Cursor](#)

Interfaces

[ICursor](#)

Enums

[SystemCursor](#)

Interface ICursor

Namespace: [Bliss.CSharp.Interact.Mice.Cursors](#)

Assembly: Bliss.dll

```
public interface ICursor : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#)

Methods

GetHandle()

Retrieves the handle of the current cursor.

```
nint GetHandle()
```

Returns

[nint](#)

A pointer to the cursor handle.

Class Sdl3Cursor

Namespace: [Bliss.CSharp.Interact.Mice.Cursors](#)

Assembly: Bliss.dll

```
public class Sdl3Cursor : Disposable, ICursor, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Sdl3Cursor

Implements

[ICursor](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Sdl3Cursor(Image, int, int)

Initializes a new instance of the [Sdl3Cursor](#) class with a custom image cursor.

```
public Sdl3Cursor(Image image, int offsetX, int offsetY)
```

Parameters

image [Image](#)

The image used to create the cursor.

offsetX [int](#)

The X-axis offset for the cursor's hotspot.

offsetY [int](#)

The Y-axis offset for the cursor's hotspot.

Sdl3Cursor(SystemCursor)

Initializes a new instance of the [Sdl3Cursor](#) class with a system cursor type.

```
public Sdl3Cursor(SystemCursor systemCursor)
```

Parameters

systemCursor [SystemCursor](#)

The type of system cursor to create.

Sdl3Cursor(SDL_Cursor*)

Initializes a new instance of the [Sdl3Cursor](#) class with an existing SDL cursor pointer.

```
public Sdl3Cursor(SDL_Cursor* cursor)
```

Parameters

cursor [SDL_Cursor*](#)

A pointer to an existing SDL cursor.

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

True if called from user code; false if called from a finalizer.

GetHandle()

Retrieves the handle of the current cursor.

```
public nint GetHandle()
```

Returns

[nint](#)

A pointer to the cursor handle.

Enum SystemCursor

Namespace: [Bliss.CSharp.Interact.Mice.Cursors](#)

Assembly: Bliss.dll

```
public enum SystemCursor
```

Fields

Count = 20

The total number of cursor types available.

Crosshair = 3

The crosshair cursor, typically used for precise selection.

Default = 0

The default system cursor.

EResize = 15

The resize cursor for resizing from the east side.

EWResize = 7

The cursor used for horizontal resizing (E-W direction).

Move = 9

The move cursor, typically used for dragging objects.

NEResize = 14

The resize cursor for resizing from the northeast corner.

NESWResize = 6

The resize cursor used for diagonal resizing (NE-SW direction).

NResize = 13

The resize cursor for resizing from the north side.

NSResize = 8

The cursor used for vertical resizing (N-S direction).

NWResize = 12

The resize cursor for resizing from the northwest corner.

NWSEResize = 5

The resize cursor used for diagonal resizing (NW-SE direction).

NotAllowed = 10

The cursor indicating an action is not allowed.

Pointer = 11

The pointer cursor, typically used for links and clickable items.

Progress = 4

The cursor indicating progress without preventing interaction.

SEResize = 16

The resize cursor for resizing from the southeast corner.

SResize = 17

The resize cursor for resizing from the south side.

SWResize = 18

The resize cursor for resizing from the southwest corner.

Text = 1

The cursor displayed when over text.

WResize = 19

The resize cursor for resizing from the west side.

Wait = 2

The cursor indicating the system is busy (wait state).

Namespace Bliss.CSharp.Logging

Classes

[Logger](#)

Enums

[LogType](#)

Delegates

[Logger.OnMessage](#)

A delegate used to handle logging messages.

Enum LogType

Namespace: [Bliss.CSharp.Logging](#)

Assembly: Bliss.dll

```
public enum LogType
```

Fields

Debug = 0

Debug level logging, used for detailed diagnostic messages.

Error = 3

Error level logging, used for error messages that indicate a failure.

Fatal = 4

Fatal level logging, used for critical errors that cause termination.

Info = 1

Info level logging, used for general informational messages.

Warn = 2

Warn level logging, used to indicate potential issues or warnings.

Class Logger

Namespace: [Bliss.CSharp.Logging](#)

Assembly: Bliss.dll

```
public class Logger
```

Inheritance

[object](#) ← Logger

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

Debug(string, string, string, int)

Logs a debug message if the build configuration is set to DEBUG.

```
public static void Debug(string msg, string sourceFilePath = "", string memberName = "", int  
sourceLineNumber = 0)
```

Parameters

msg [string](#)

The debug message to log.

sourceFilePath [string](#)

The file path of the caller. Automatically set by the compiler.

memberName [string](#)

The name of the calling member. Automatically set by the compiler.

sourceLineNumber [int](#)

The line number of the call within the source file. Automatically set by the compiler.

Error(string, string, string, int)

Logs an error message.

```
public static void Error(string msg, string sourceFilePath = "", string memberName = "", int sourceLineNumber = 0)
```

Parameters

`msg` [string](#)

The error message to log.

`sourceFilePath` [string](#)

The file path of the caller. Automatically set by the compiler.

`memberName` [string](#)

The name of the calling member. Automatically set by the compiler.

`sourceLineNumber` [int](#)

The line number of the call within the source file. Automatically set by the compiler.

Fatal(Exception, string, string, int)

Logs a fatal error message.

```
public static void Fatal(Exception exception, string sourceFilePath = "", string memberName = "", int sourceLineNumber = 0)
```

Parameters

`exception` [Exception](#)

The exception to log and rethrow.

`sourceFilePath` [string](#)

The file path of the caller. Automatically set by the compiler.

`memberName` [string ↗](#)

The name of the calling member. Automatically set by the compiler.

`sourceLineNumber` [int ↗](#)

The line number of the call within the source file. Automatically set by the compiler.

Fatal(string, string, string, int)

Logs a fatal error message.

```
public static void Fatal(string msg, string sourceFilePath = "", string memberName = "", int sourceLineNumber = 0)
```

Parameters

`msg` [string ↗](#)

The fatal error message to log.

`sourceFilePath` [string ↗](#)

The file path of the caller. Automatically set by the compiler.

`memberName` [string ↗](#)

The name of the calling member. Automatically set by the compiler.

`sourceLineNumber` [int ↗](#)

The line number of the call within the source file. Automatically set by the compiler.

Info(string, string, string, int)

Logs an informational message.

```
public static void Info(string msg, string sourceFilePath = "", string memberName = "", int sourceLineNumber = 0)
```

Parameters

msg [string](#)

The informational message to log.

sourceFilePath [string](#)

The file path of the caller. Automatically set by the compiler.

memberName [string](#)

The name of the calling member. Automatically set by the compiler.

sourceLineNumber [int](#)

The line number of the call within the source file. Automatically set by the compiler.

Warn(string, string, string, int)

Logs a warning message.

```
public static void Warn(string msg, string sourceFilePath = "", string memberName = "", int sourceLineNumber = 0)
```

Parameters

msg [string](#)

The warning message to log.

sourceFilePath [string](#)

The file path of the caller. Automatically set by the compiler.

memberName [string](#)

The name of the calling member. Automatically set by the compiler.

sourceLineNumber [int](#)

The line number of the call within the source file. Automatically set by the compiler.

Events

Message

An event that is triggered when a log message is generated.

```
public static event Logger.OnMessage? Message
```

Event Type

[Logger.OnMessage](#)

Delegate Logger.OnMessage

Namespace: [Bliss.CSharp.Logging](#)

Assembly: Bliss.dll

A delegate used to handle logging messages.

```
public delegate bool Logger.OnMessage(LogType type, string msg, ConsoleColor color, string sourceFilePath, string memberName, int sourceLineNumber)
```

Parameters

type [LogType](#)

The type of the log message, represented by the [LogType](#) enum.

msg [string](#)

The log message content.

color [ConsoleColor](#)

The console color to display the message in.

sourceFilePath [string](#)

The file path of the caller. Automatically set by the compiler.

memberName [string](#)

The name of the calling member. Automatically set by the compiler.

sourceLineNumber [int](#)

The line number of the call within the source file. Automatically set by the compiler.

Returns

[bool](#)

Returns a boolean value indicating whether the message has been handled.

Namespace Bliss.CSharp.Materials

Classes

[Material](#)

[MaterialMap](#)

[MaterialMapTypeExtensions](#)

Enums

[MaterialMapType](#)

Class Material

Namespace: [Bliss.CSharp.Materials](#)

Assembly: Bliss.dll

```
public class Material : ICloneable
```

Inheritance

[object](#) ← Material

Implements

[ICloneable](#)

Inherited Members

[object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

Material(Effect, RasterizerStateDescription?,
BlendStateDescription?, RenderMode)

Initializes a new instance of the [Material](#) class.

```
public Material(Effect effect, RasterizerStateDescription? rasterizerState = null,  
BlendStateDescription? blendState = null, RenderMode renderMode = RenderMode.Solid)
```

Parameters

effect [Effect](#)

The effect (shader) to apply to the material.

rasterizerState [RasterizerStateDescription](#)?

The optional rasterizer state.

blendState [BlendStateDescription](#)?

The optional blend state to define how this material blends with others during rendering. If not specified, blending is disabled by default.

renderMode [RenderMode](#)

The rendering mode for this material. Defaults to [Solid](#).

Fields

BlendState

Specifies the blend state for rendering, determining how colors are blended on the screen.

```
public BlendStateDescription BlendState
```

Field Value

[BlendStateDescription](#)

Effect

The effect (shader program) applied to this material.

```
public Effect Effect
```

Field Value

[Effect](#)

Parameters

A list of floating-point parameters for configuring material properties.

```
public List<float> Parameters
```

Field Value

[List ↗](#) <[float ↗](#)>

RasterizerState

Defines the rasterizer state for the material.

```
public RasterizerStateDescription RasterizerState
```

Field Value

[RasterizerStateDescription ↗](#)

RenderMode

Specifies the rendering mode for the material, determining how the material is drawn (e.g., Solid, Cutout, Transparent).

```
public RenderMode RenderMode
```

Field Value

[RenderMode](#)

Methods

AddMaterialMap(MaterialMapType, MaterialMap)

Adds a material map to the material, associating it with the specified material map type.

```
public void AddMaterialMap(MaterialMapType type, MaterialMap map)
```

Parameters

type [MaterialMapType](#)

The type of the material map, represented as a [MaterialMapType](#) enum value.

`map` [MaterialMap](#)

The material map to associate with the specified type.

Clone()

Creates a new instance of the [Material](#) class that is a copy of the current instance.

```
public object Clone()
```

Returns

[object](#)

A new [Material](#) object that is a clone of the current instance.

GetMapColor(MaterialMapType)

Retrieves the color associated with a specific material map type, if defined.

```
public Color? GetMapColor(MaterialMapType type)
```

Parameters

`type` [MaterialMapType](#)

The type of the material map whose color is to be retrieved.

Returns

[Color?](#)

The color associated with the specified material map type, or null if the map is not defined.

GetMapTexture(MaterialMapType)

Retrieves the texture associated with the specified material map type.

```
public Texture2D? GetMapTexture(MaterialMapType type)
```

Parameters

type [MaterialMapType](#)

The type of material map for which the texture is requested.

Returns

[Texture2D](#)

The texture associated with the specified material map type, or null if no texture is found.

GetMapView(MaterialMapType)

Retrieves the value associated with the specified material map type.

```
public float GetMapView(MaterialMapType type)
```

Parameters

type [MaterialMapType](#)

The type of the material map whose value is to be retrieved.

Returns

[float](#) ↗

The value of the material map if it exists; otherwise, returns 0.0.

GetMaterialMap(MaterialMapType)

Retrieves a specific material map associated with the specified material map type.

```
public MaterialMap? GetMaterialMap(MaterialMapType type)
```

Parameters

type [MaterialMapType](#)

The type of the material map to retrieve.

Returns

[MaterialMap](#)

The [MaterialMap](#) associated with the specified type if it exists; otherwise, null.

GetMaterialMapTypes()

Retrieves the collection of material map types associated with the material.

```
public Dictionary<MaterialMapType, MaterialMap>.KeyCollection GetMaterialMapTypes()
```

Returns

[Dictionary](#)<[MaterialMapType](#), [MaterialMap](#)>.KeyCollection

A collection of keys representing the material map types defined for this material.

GetMaterialMaps()

Retrieves the collection of material maps associated with the material.

```
public Dictionary<MaterialMapType, MaterialMap>.ValueCollection GetMaterialMaps()
```

Returns

[Dictionary](#)<[MaterialMapType](#), [MaterialMap](#)>.ValueCollection

A collection containing the values of the material maps defined for this material.

SetMapColor(MaterialMapType, Color)

Sets the color for a specific material map type in the current material instance.

```
public void SetMapColor(MaterialMapType type, Color color)
```

Parameters

type [MaterialMapType](#)

The type of the material map to update, represented by [MaterialMapType](#).

color [Color](#)

The new color to assign to the specified material map.

SetMapTexture(MaterialMapType, Texture2D?)

Assigns a texture to a material map of the specified type. If the map type exists, its texture is updated; otherwise, a warning is logged.

```
public void SetMapTexture(MaterialMapType type, Texture2D? texture)
```

Parameters

type [MaterialMapType](#)

The type of material map to which the texture will be assigned. This determines the type of visual effect applied (e.g., Albedo, Normal, Metallic, etc.).

texture [Texture2D](#)

The texture to assign to the specified material map. If null, the texture will be removed from the map.

SetMapView(MaterialMapType, float)

Sets the numeric value associated with the specified material map type. If the map does not exist, a warning is logged instead of modifying any values.

```
public void SetMapView(MaterialMapType type, float value)
```

Parameters

type [MaterialMapType](#)

The type of material map whose value is being set.

value [float](#) ↗

The numeric value to assign to the material map.

Class MaterialMap

Namespace: [Bliss.CSharp.Materials](#)

Assembly: Bliss.dll

```
public class MaterialMap
```

Inheritance

[object](#) ← MaterialMap

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

MaterialMap(Texture2D?, Sampler?, Color?, float)

Initializes a new instance of the [MaterialMap](#) class.

```
public MaterialMap(Texture2D? texture = null, Sampler? sampler = null, Color? color = null,  
float value = 0)
```

Parameters

texture [Texture2D](#)

The texture associated with the material map. Can be [null](#).

sampler [Sampler](#)

The sampler to use with the texture, or [null](#) if not used.

color [Color?](#)

The color associated with the material map. Can be [null](#).

value [float](#)

The scalar value associated with the material map, defaulting to [0.0F](#).

Fields

Color

Represents color information with properties for red, green, blue, and alpha components. This structure is used for defining the color attributes of various graphical elements such as materials and textures.

```
public Color? Color
```

Field Value

[Color?](#)

Sampler

Represents a sampler used in a material map for texture sampling operations. A sampler defines how textures are sampled, including settings such as filtering, addressing mode, and LOD behavior, which influence rendering outcomes and texture mapping techniques.

```
public Sampler? Sampler
```

Field Value

[Sampler](#)

Texture

Represents a 2D texture used in a material map. This texture can include properties such as height, width, pixel format, and mip levels. It is used for rendering purposes in a graphics device.

```
public Texture2D? Texture
```

Field Value

[Texture2D](#)

Value

Represents a float value associated with a material map. This value can be used for various purposes such as setting shader parameters or controlling material properties in a rendering engine.

```
public float Value
```

Field Value

[float](#)

Methods

GetTextureResourceSet(Sampler, SimpleTextureLayout)

The texture resource set associated with the specified sampler and texture layout.

```
public ResourceSet? GetTextureResourceSet(Sampler sampler, SimpleTextureLayout layout)
```

Parameters

sampler [Sampler](#)

The sampler used for creating the resource set.

layout [SimpleTextureLayout](#)

The texture layout used for creating the resource set.

Returns

[ResourceSet](#)

The resource set associated with the texture, or [null](#) if the texture is not available.

Enum MaterialMapType

Namespace: [Bliss.CSharp.Materials](#)

Assembly: Bliss.dll

```
public enum MaterialMapType
```

Extension Methods

[MaterialMapTypeExtensions.GetName\(MaterialMapType\)](#)

Fields

[EnumMember(Value = "fAlbedo")] Albedo = 0

Albedo map, which defines the base color of the material.

[EnumMember(Value = "fEmissive")] Emission = 5

Emission map, which defines areas of the material that emit light.

[EnumMember(Value = "fHeight")] Height = 7

Height map, which provides height data for the material to simulate depth effects.

[EnumMember(Value = "fMetallic")] Metallic = 1

Metallic map, which defines the metallic properties of the material.

[EnumMember(Value = "fNormal")] Normal = 2

Normal map, which adds detail to the surface of the material by simulating bumps and grooves.

[EnumMember(Value = "fOcclusion")] Occlusion = 4

Occlusion map, which adds shadows in crevices to enhance the appearance of depth.

[EnumMember(Value = "fOpacity")] Opacity = 6

Opacity map, which defines the transparency levels of the material.

[EnumMember(Value = "fRoughness")] Roughness = 3

Roughness map, which defines the roughness level of the material's surface.

Class MaterialMapTypeExtensions

Namespace: [Bliss.CSharp.Materials](#)

Assembly: Bliss.dll

```
public static class MaterialMapTypeExtensions
```

Inheritance

[object](#) ← MaterialMapTypeExtensions

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

GetName(MaterialMapType)

Retrieves the name of the specified [MaterialMapType](#) enum value.

```
public static string GetName(this MaterialMapType type)
```

Parameters

type [MaterialMapType](#)

The [MaterialMapType](#) enum value whose name is to be retrieved.

Returns

[string](#)

A string representation of the [MaterialMapType](#) enum value, either from the [EnumMemberAttribute](#) or the enum's name.

Namespace Bliss.CSharp.Mathematics

Classes

[BlissMath](#)

Class BlissMath

Namespace: [Bliss.CSharp.Mathematics](#)

Assembly: Bliss.dll

```
public static class BlissMath
```

Inheritance

[object](#) ← BlissMath

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

EulerDegreesToQuaternion(float, float, float)

Creates a [Quaternion](#) from Euler angles specified in degrees.

```
public static Quaternion EulerDegreesToQuaternion(float pitch, float yaw, float roll)
```

Parameters

pitch [float](#)

The pitch angle in degrees (rotation around the X axis).

yaw [float](#)

The yaw angle in degrees (rotation around the Y axis).

roll [float](#)

The roll angle in degrees (rotation around the Z axis).

Returns

[Quaternion](#)

A [Quaternion](#) representing the combined rotation.

EulerDegreesToQuaternion(float, float, float, float)

Creates a delta [Quaternion](#) rotation from Euler angles in degrees, scaled by a time step.

```
public static Quaternion EulerDegreesToQuaternion(float pitch, float yaw, float roll,  
float deltaTime)
```

Parameters

pitch [float](#)

The pitch angle in degrees (rotation around the X axis).

yaw [float](#)

The yaw angle in degrees (rotation around the Y axis).

roll [float](#)

The roll angle in degrees (rotation around the Z axis).

deltaTime [float](#)

The elapsed time step to scale the rotation by.

Returns

[Quaternion](#)

A [Quaternion](#) representing the incremental rotation.

Vector3Angle(Vector3, Vector3)

Calculates the angle in radians between two vectors.

```
public static float Vector3Angle(Vector3 v1, Vector3 v2)
```

Parameters

v1 [Vector3](#)

The first vector.

v2 [Vector3](#)

The second vector.

Returns

[float](#)

The angle in radians between the two vectors.

Vector3RotateByAxisAngle(Vector3, Vector3, float)

Rotates a vector around a specified axis by a given angle.

```
public static Vector3 Vector3RotateByAxisAngle(Vector3 v, Vector3 axis, float angle)
```

Parameters

v [Vector3](#)

The vector to be rotated.

axis [Vector3](#)

The axis around which to rotate the vector.

angle [float](#)

The angle in radians by which to rotate the vector.

Returns

[Vector3](#)

The rotated vector.

Namespace Bliss.CSharp.Media

Classes

[VideoClip](#)

[VideoPlayer](#)

Class VideoClip

Namespace: [Bliss.CSharp.Media](#)

Assembly: Bliss.dll

```
public class VideoClip
```

Inheritance

[object](#) ← VideoClip

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Class VideoPlayer

Namespace: [Bliss.CSharp.Media](#)

Assembly: Bliss.dll

```
public class VideoPlayer
```

Inheritance

[object](#) ← VideoPlayer

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Namespace Bliss.CSharp.Textures

Classes

[MipmapHelper](#)

[RenderTexture2D](#)

[Texture2D](#)

Class MipmapHelper

Namespace: [Bliss.CSharp.Textures](#)

Assembly: Bliss.dll

```
public static class MipmapHelper
```

Inheritance

[object](#) ← MipmapHelper

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

GenerateMipmaps(Image)

Generates mipmaps for a given source image.

```
public static Image[] GenerateMipmaps(Image baseImage)
```

Parameters

baseImage [Image](#)

The base image from which the mipmaps are generated.

Returns

[Image](#)[]

A list of images representing the mipmap levels, including the original image as the first level.

Class RenderTexture2D

Namespace: [Bliss.CSharp.Textures](#)

Assembly: Bliss.dll

```
public class RenderTexture2D : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← RenderTexture2D

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

RenderTexture2D(GraphicsDevice, uint, uint, TextureSampleCount)

Initializes a new instance of the [RenderTexture2D](#) class, creating a render target texture with specified dimensions and sample count.

```
public RenderTexture2D(GraphicsDevice graphicsDevice, uint width, uint height,  
TextureSampleCount sampleCount = TextureSampleCount.Count1)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The [GraphicsDevice](#) used to create and manage the texture.

width [uint](#)

The width of the render texture in pixels.

`height` [uint](#)

The height of the render texture in pixels.

`sampleCount` [TextureSampleCount](#)

The number of samples for multisampling. Defaults to [Count1](#).

Properties

ColorTexture

Gets the color texture used for rendering operations within the render texture.

```
public Texture ColorTexture { get; }
```

Property Value

[Texture](#)

DepthTexture

Gets the depth texture associated with this render texture, used for depth and stencil operations.

```
public Texture DepthTexture { get; }
```

Property Value

[Texture](#)

DestinationTexture

Gets the destination texture used for sampling operations in this render texture.

```
public Texture DestinationTexture { get; }
```

Property Value

Framebuffer

Gets the framebuffer used for rendering to the textures associated with this render texture.

```
public Framebuffer Framebuffer { get; }
```

Property Value

[Framebuffer](#)

GraphicsDevice

Gets the graphics device associated with this render texture.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Height

Gets the height of the render texture.

```
public uint Height { get; }
```

Property Value

[uint](#)

SampleCount

Gets or sets the sample count for the render texture.

```
public TextureSampleCount SampleCount { get; set; }
```

Property Value

[TextureSampleCount](#)

Width

Gets the width of the render texture.

```
public uint Width { get; }
```

Property Value

[uint](#)

Methods

CreateFrameBuffer()

Creates a framebuffer with depth and color textures based on the specified width, height, and sample count.

```
public void CreateFrameBuffer()
```

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

GetResourceSet(Sampler, ResourceLayout)

Retrieves a [ResourceSet](#) for the specified [Sampler](#) and [ResourceLayout](#). If the resource set is not already cached, a new one is created, cached, and then returned.

```
public ResourceSet GetResourceSet(Sampler sampler, ResourceLayout layout)
```

Parameters

sampler [Sampler](#)

The sampler to be used in the resource set.

layout [ResourceLayout](#)

The resource layout defining how resources are bound to the pipeline.

Returns

[ResourceSet](#)

A [ResourceSet](#) that contains the specified sampler and layout.

Resize(uint, uint)

Resizes the render textures and framebuffer to the new specified width and height.

```
public void Resize(uint width, uint height)
```

Parameters

width [uint](#)

The new width of the render texture.

height [uint](#)

The new height of the render texture.

Class Texture2D

Namespace: [Bliss.CSharp.Textures](#)

Assembly: Bliss.dll

```
public class Texture2D : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Texture2D

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Texture2D(GraphicsDevice, Image, bool, bool)

Initializes a new instance of the [Texture2D](#) class using an [Image](#) object. Creates a device texture, applies the specified sampler, and stores mipmap and color format information.

```
public Texture2D(GraphicsDevice graphicsDevice, Image image, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering the texture.

image [Image](#)

The image object used to create the texture.

mipmap [bool](#)

Indicates whether to generate mipmaps for the texture.

srgb [bool](#)

Indicates whether to use sRGB color space for the texture.

Texture2D(GraphicsDevice, Stream, bool, bool)

Initializes a new instance of the [Texture2D](#) class using an image stream. Loads the texture from the specified stream and applies the given sampler, mipmap, and sRGB settings.

```
public Texture2D(GraphicsDevice graphicsDevice, Stream stream, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering the texture.

stream [Stream](#)

The image stream to load as a texture.

mipmap [bool](#)

Indicates whether to generate mipmaps for the texture.

srgb [bool](#)

Indicates whether to use sRGB color space for the texture.

Texture2D(GraphicsDevice, string, bool, bool)

Initializes a new instance of the [Texture2D](#) class using an image file path. Loads the texture from the specified path and applies the given sampler, mipmap, and sRGB settings.

```
public Texture2D(GraphicsDevice graphicsDevice, string path, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for rendering the texture.

path [string](#)

The file path of the image to load as a texture.

mipmap [bool](#)

Indicates whether to generate mipmaps for the texture.

srgb [bool](#)

Indicates whether to use sRGB color space for the texture.

Properties

DeviceTexture

Gets the device texture created from the images.

```
public Texture DeviceTexture { get; }
```

Property Value

[Texture](#)

Format

Gets the pixel format of the texture.

```
public PixelFormat Format { get; }
```

Property Value

[PixelFormat](#)

GraphicsDevice

Gets the graphics device associated with this texture.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Height

Gets the height of the texture in pixels.

```
public uint Height { get; }
```

Property Value

[uint](#)

Images

Gets the array of images representing the mip levels of the texture.

```
public Image[] Images { get; }
```

Property Value

[Image\[\]](#)

MipLevels

Gets the number of mip levels in the texture.

```
public uint MipLevels { get; }
```

Property Value

[uint](#)

PixelSizeInBytes

Gets the size of a pixel in bytes.

```
public uint PixelSizeInBytes { get; }
```

Property Value

[uint](#)

Width

Gets the width of the texture in pixels.

```
public uint Width { get; }
```

Property Value

[uint](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

GetDataFromBytes()

Retrieves the texture data as a byte array.

```
public byte[] GetDataFromBytes()
```

Returns

[byte](#)

A byte array containing the texture data.

GetDataFromImage()

Retrieves the image data from the first image in the texture array.

```
public Image GetDataFromImage()
```

Returns

[Image](#)

An [Image](#) representing the image data.

GetResourceSet(Sampler, SimpleTextureLayout)

Gets a resource set associated with the specified sampler and resource layout. If the resource set is already cached, it returns the cached resource set; otherwise, it creates and caches a new one.

```
public ResourceSet GetResourceSet(Sampler sampler, SimpleTextureLayout layout)
```

Parameters

sampler [Sampler](#)

The sampler used for the resource set.

layout [SimpleTextureLayout](#)

The resource layout used for the resource set.

Returns

[ResourceSet](#)

The resource set associated with the specified sampler and resource layout.

SetData(Image)

Loads the provided image data into the texture. If the image dimensions do not match the texture dimensions, an exception is thrown. The image data is then split into mip levels if required and updated in the device texture.

```
public void SetData(Image data)
```

Parameters

data [Image](#)

The image data to be loaded into the texture.

SetData(byte[], Rectangle?)

Sets the texture data from a byte array, optionally specifying a rectangular area within the texture to update.

```
public void SetData(byte[] data, Rectangle? area = null)
```

Parameters

data [byte](#)[]

The byte array containing the texture data.

area [Rectangle](#)?

The rectangular area within the texture to update. If null, it updates the entire texture.

Namespace Bliss.CSharp.Textures.Cubemaps

Classes

[Cubemap](#)

[CubemapHelper](#)

Enums

[CubemapLayer](#)

[CubemapLayout](#)

Class Cubemap

Namespace: [Bliss.CSharp.Textures.Cubemaps](#)

Assembly: Bliss.dll

```
public class Cubemap : Disposable, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Cubemap

Implements

[IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Cubemap(GraphicsDevice, Image, CubemapLayout, bool, bool)

Initializes a new instance of the [Cubemap](#) class by splitting a single image into cubemap faces.

```
public Cubemap(GraphicsDevice graphicsDevice, Image image, CubemapLayout layout =  
    CubemapLayout.AutoDetect, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for creating resources.

image [Image](#)

The source image containing all cubemap faces in the specified layout.

layout [CubemapLayout](#)

The layout format used to interpret the cubemap faces in the source image.

mipmap [bool](#)

Specifies whether to generate mipmaps for each cubemap face.

srgb [bool](#)

Specifies whether the images should be loaded as sRGB format.

Cubemap(GraphicsDevice, Stream, CubemapLayout, bool, bool)

Initializes a new instance of the [Cubemap](#) class by loading cubemap faces from a stream.

```
public Cubemap(GraphicsDevice graphicsDevice, Stream stream, CubemapLayout layout =  
    CubemapLayout.AutoDetect, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for creating resources.

stream [Stream](#)

The stream containing the image data for the cubemap faces.

layout [CubemapLayout](#)

The layout of the cubemap faces within the image.

mipmap [bool](#)

Specifies whether to generate mipmaps for the cubemap.

srgb [bool](#)

Specifies whether to load the image as sRGB.

Cubemap(GraphicsDevice, string, CubemapLayout, bool, bool)

Initializes a new instance of the [Cubemap](#) class by loading cubemap faces from a file path.

```
public Cubemap(GraphicsDevice graphicsDevice, string path, CubemapLayout layout = CubemapLayout.AutoDetect, bool mipmap = true, bool srgb = false)
```

Parameters

graphicsDevice [GraphicsDevice](#)

The graphics device used for creating resources.

path [string](#)

The file path to the image containing cubemap faces.

layout [CubemapLayout](#)

The layout of the cubemap faces within the image.

mipmap [bool](#)

Specifies whether to generate mipmaps for the cubemap.

srgb [bool](#)

Specifies whether to load the image as sRGB.

Properties

DeviceTexture

Gets the device texture.

```
public Texture DeviceTexture { get; }
```

Property Value

[Texture](#)

Format

Gets the pixel format of the cubemap.

```
public PixelFormat Format { get; }
```

Property Value

[PixelFormat](#)

GraphicsDevice

Gets the graphics device associated with the cubemap instance.

```
public GraphicsDevice GraphicsDevice { get; }
```

Property Value

[GraphicsDevice](#)

Height

Gets the height of the cubemap.

```
public uint Height { get; }
```

Property Value

[uint](#)

Images

Gets the mipmap levels of images for each face of the cubemap.

```
public Image[][] Images { get; }
```

Property Value

[Image](#)[][]

MipLevels

Gets the number of mip levels of the cubemap.

```
public uint MipLevels { get; }
```

Property Value

[uint](#)

PixelSizeInBytes

Gets the size of a pixel in bytes.

```
public uint PixelSizeInBytes { get; }
```

Property Value

[uint](#)

TextureView

Gets the texture view associated with the cubemap, allowing shaders to access the cubemap texture data.

```
public TextureView TextureView { get; }
```

Property Value

[TextureView](#)

Width

Gets the width of the cubemap.

```
public uint Width { get; }
```

Property Value

[uint](#)

Methods

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

[disposing](#) [bool](#)

True if called from user code; false if called from a finalizer.

GetDataFromBytes(CubemapLayer)

Retrieves the raw byte data for a specific array layer of the cubemap.

```
public byte[] GetDataFromBytes(CubemapLayer cubemapLayer)
```

Parameters

[cubemapLayer](#) [CubemapLayer](#)

The array layer of the cubemap to retrieve data from.

Returns

[byte](#)[]

An array of bytes containing the pixel data for the specified array layer.

GetDataFromImage(CubemapLayer)

Retrieves the image data associated with the specified array layer of the cubemap.

```
public Image GetDataFromImage(CubemapLayer cubemapLayer)
```

Parameters

cubemapLayer [CubemapLayer](#)

The specific array layer whose image data is to be retrieved.

Returns

[Image](#)

An [Image](#) object containing the image data for the specified array layer.

GetResourceSet(Sampler, ResourceLayout)

Retrieves a resource set from the cache or creates a new one using a specified sampler and texture layout.

```
public ResourceSet GetResourceSet(Sampler sampler, ResourceLayout layout)
```

Parameters

sampler [Sampler](#)

The sampler object to be used for the resource set.

layout [ResourceLayout](#)

The texture layout to be used for the resource set.

Returns

[ResourceSet](#)

A [ResourceSet](#) object associated with the provided sampler and layout.

SetData(Image, CubemapLayer)

Updates the data of a specified layer in the cubemap with the provided image data.

```
public void SetData(Image data, CubemapLayer cubemapLayer)
```

Parameters

data [Image](#)

The image data to set, which must match the dimensions of the texture.

cubemapLayer [CubemapLayer](#)

The layer of the cubemap to update.

Exceptions

[ArgumentException](#)

Throws if the dimensions of the provided image data do not match the dimensions of the cubemap.

SetData(byte[], CubemapLayer, Rectangle?)

Updates the cubemap's data for a specified array layer and a rectangular area.

```
public void SetData(byte[] data, CubemapLayer cubemapLayer, Rectangle? area = null)
```

Parameters

data [byte](#)[]

The raw byte array containing the pixel data to be set.

cubemapLayer [CubemapLayer](#)

The specific cubemap array layer to update.

area [Rectangle](#)?

An optional rectangle specifying the area to update. If null, the whole layer will be updated.

Class CubemapHelper

Namespace: [Bliss.CSharp.Textures.Cubemaps](#)

Assembly: Bliss.dll

```
public static class CubemapHelper
```

Inheritance

[object](#) ← CubemapHelper

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

GenCubemapImages(Image, CubemapLayout)

Generates an array of images, each representing one face of a cubemap, based on the input image and specified cubemap layout.

```
public static Image[] GenCubemapImages(Image image, CubemapLayout layout)
```

Parameters

image [Image](#)

The input image to generate cubemap face images from.

layout [CubemapLayout](#)

The layout of the cubemap in the source image. Determines how the image should be split into faces.

Returns

[Image](#)[]

An array of six images, each representing one face of the cubemap. The order of the images corresponds to the cubemap faces.

Exceptions

[ArgumentException](#)

Thrown when the dimensions of the input image are incompatible with the specified cubemap layout.

[ArgumentOutOfRangeException](#)

Thrown when the specified cubemap layout is not recognized or supported.

Enum CubemapLayer

Namespace: [Bliss.CSharp.Textures.Cubemaps](#)

Assembly: Bliss.dll

```
public enum CubemapLayer
```

Fields

NegativeX = 1

The negative X face of the cubemap (left).

NegativeY = 3

The negative Y face of the cubemap (bottom).

NegativeZ = 5

The negative Z face of the cubemap (back).

PositiveX = 0

The positive X face of the cubemap (right).

PositiveY = 2

The positive Y face of the cubemap (top).

PositiveZ = 4

The positive Z face of the cubemap (front).

Enum CubemapLayout

Namespace: [Bliss.CSharp.Textures.Cubemaps](#)

Assembly: Bliss.dll

```
public enum CubemapLayout
```

Fields

AutoDetect = 0

Automatically detects the cubemap layout based on the texture dimensions and aspect ratio.

CrossFourByThree = 4

Specifies a 4x3 cross layout for cubemaps, with four columns and three rows of faces.

CrossThreeByFour = 3

Specifies a 3x4 cross layout for cubemaps, with three columns and four rows of faces.

LineHorizontal = 2

Specifies a horizontal line layout where cubemap faces are aligned horizontally in a single row.

LineVertical = 1

Specifies a vertical line layout where cubemap faces are stacked vertically in a single column.

Panorama = 5

Specifies a panoramic layout, used for spherical or equirectangular textures that can be converted to cubemaps.

Namespace Bliss.CSharp.Transformations

Structs

[Point](#)

[Rectangle](#)

[RectangleF](#)

[Transform](#)

Struct Point

Namespace: [Bliss.CSharp.Transformations](#)

Assembly: Bliss.dll

```
public struct Point : IEquatable<Point>
```

Implements

[IEquatable](#)<[Point](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Point(int, int)

Initializes a new instance of the Point class with the specified X and Y coordinates.

```
public Point(int x, int y)
```

Parameters

x [int](#)

The X coordinate of the point.

y [int](#)

The Y coordinate of the point.

Fields

X

The X-coordinate of the Point structure. Represents the horizontal component in a 2D space.

```
public int X
```

Field Value

[int](#)

Y

The Y-coordinate of the Point structure. Represents the vertical component in a 2D space.

```
public int Y
```

Field Value

[int](#)

Methods

Equals(Point)

Indicates whether this instance and a specified Point object represent the same point.

```
public bool Equals(Point other)
```

Parameters

other [Point](#)

The Point to compare with the current instance.

Returns

[bool](#)

true if the specified Point is equal to the current Point; otherwise, false.

Equals(object?)

Determines whether this instance and a specified object represent the same point.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current instance.

Returns

[bool](#)

true if the specified object is a Point and is equal to the current Point; otherwise, false.

GetHashCode()

Returns the hash code for this Point instance.

```
public override int GetHashCode()
```

Returns

[int](#)

A hash code for the current Point, which is a unique identifier of the instance.

ToString()

Returns a string that represents the current Point instance.

```
public override string ToString()
```

Returns

[string](#)

A string that contains the X and Y coordinates of the Point instance.

Operators

operator ==(Point, Point)

Determines whether two specified Point instances have the same coordinates.

```
public static bool operator ==(Point left, Point right)
```

Parameters

left [Point](#)

The first Point to compare.

right [Point](#)

The second Point to compare.

Returns

[bool](#)

true if both Point instances have the same X and Y coordinates; otherwise, false.

operator !=(Point, Point)

Determines whether two specified Point instances have different coordinates.

```
public static bool operator !=(Point left, Point right)
```

Parameters

left [Point](#)

The first Point to compare.

right Point

The second Point to compare.

Returns

bool ↗

true if the Point instances do not have the same X and Y coordinates; otherwise, false.

Struct Rectangle

Namespace: [Bliss.CSharp.Transformations](#)

Assembly: Bliss.dll

```
public struct Rectangle : IEquatable<Rectangle>
```

Implements

[IEquatable](#)<[Rectangle](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Rectangle(int, int, int, int)

Initializes a new instance of the [Rectangle](#) struct with the specified position and size.

```
public Rectangle(int x, int y, int width, int height)
```

Parameters

x [int](#)

The X-coordinate of the rectangle's top-left corner.

y [int](#)

The Y-coordinate of the rectangle's top-left corner.

width [int](#)

The width of the rectangle.

height [int](#)

The height of the rectangle.

Fields

Height

The height of the rectangle.

```
public int Height
```

Field Value

[int ↗](#)

Width

The width of the rectangle.

```
public int Width
```

Field Value

[int ↗](#)

X

The X-coordinate of the rectangle's top-left corner.

```
public int X
```

Field Value

[int ↗](#)

Y

The Y-coordinate of the rectangle's top-left corner.

```
public int Y
```

Field Value

[int ↗](#)

Properties

Position

Gets or sets the position (X, Y) of the rectangle's top-left corner.

```
public Vector2 Position { get; set; }
```

Property Value

[Vector2 ↗](#)

Size

Gets or sets the size (Width, Height) of the rectangle.

```
public Vector2 Size { get; set; }
```

Property Value

[Vector2 ↗](#)

Methods

Contains(Vector2)

Determines whether the specified point is contained within the rectangle.

```
public bool Contains(Vector2 p)
```

Parameters

`p` [Vector2](#)

The point to check.

Returns

[bool](#)

True if the point is inside the rectangle; otherwise, false.

Contains(Vector2, Vector2, float)

Determines whether a specified point is contained within a rotated rectangle relative to a given origin.

```
public bool Contains(Vector2 p, Vector2 origin, float rotation)
```

Parameters

`p` [Vector2](#)

The point that is being checked for containment within the rectangle.

`origin` [Vector2](#)

The origin point relative to which the rotation is applied.

`rotation` [float](#)

The rotation angle, in degrees, applied counterclockwise to the rectangle.

Returns

[bool](#)

True if the point is contained within the rotated rectangle; otherwise, false.

Contains(float, float)

Determines whether the specified coordinates are contained within the rectangle.

```
public bool Contains(float x, float y)
```

Parameters

x [float](#)

The X-coordinate of the point to check.

y [float](#)

The Y-coordinate of the point to check.

Returns

[bool](#)

True if the point is inside the rectangle; otherwise, false.

Equals(Rectangle)

Determines whether the current rectangle is equal to another [Rectangle](#).

```
public bool Equals(Rectangle other)
```

Parameters

other [Rectangle](#)

The rectangle to compare with the current rectangle.

Returns

[bool](#)

True if the rectangles are equal; otherwise, false.

Equals(object?)

Determines whether the specified object is equal to the current rectangle.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current rectangle.

Returns

[bool](#)

True if the object is a [Rectangle](#) and is equal to the current rectangle; otherwise, false.

GetHashCode()

Returns a hash code for the current rectangle.

```
public override int GetHashCode()
```

Returns

[int](#)

A hash code for the current rectangle.

ToString()

Returns a string that represents the current rectangle.

```
public override string ToString()
```

Returns

[string](#)

A string that represents the rectangle's position and size.

Operators

operator ==(Rectangle, Rectangle)

Determines whether two [Rectangle](#) instances are equal.

```
public static bool operator ==(Rectangle left, Rectangle right)
```

Parameters

left [Rectangle](#)

The first [Rectangle](#) to compare.

right [Rectangle](#)

The second [Rectangle](#) to compare.

Returns

[bool](#) ↗

True if both rectangles are equal; otherwise, false.

operator !=(Rectangle, Rectangle)

Determines whether two [Rectangle](#) instances are not equal.

```
public static bool operator !=(Rectangle left, Rectangle right)
```

Parameters

left [Rectangle](#)

The first [Rectangle](#) to compare.

right [Rectangle](#)

The second [Rectangle](#) to compare.

Returns

bool ↗

True if the rectangles are not equal; otherwise, false.

Struct RectangleF

Namespace: [Bliss.CSharp.Transformations](#)

Assembly: Bliss.dll

```
public struct RectangleF : IEquatable<RectangleF>
```

Implements

[IEquatable](#)<[RectangleF](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

RectangleF(float, float, float, float)

Initializes a new instance of the [RectangleF](#) struct with the specified position and size.

```
public RectangleF(float x, float y, float width, float height)
```

Parameters

x [float](#)

The X-coordinate of the rectangle's top-left corner.

y [float](#)

The Y-coordinate of the rectangle's top-left corner.

width [float](#)

The width of the rectangle.

height [float](#)

The height of the rectangle.

Fields

Height

The height of the rectangle.

```
public float Height
```

Field Value

[float](#)

Width

The width of the rectangle.

```
public float Width
```

Field Value

[float](#)

X

The X-coordinate of the rectangle's top-left corner.

```
public float X
```

Field Value

[float](#)

Y

The Y-coordinate of the rectangle's top-left corner.

```
public float Y
```

Field Value

[float](#)

Properties

Position

Gets or sets the position (X, Y) of the rectangle's top-left corner.

```
public Vector2 Position { get; set; }
```

Property Value

[Vector2](#)

Size

Gets or sets the size (Width, Height) of the rectangle.

```
public Vector2 Size { get; set; }
```

Property Value

[Vector2](#)

Methods

Contains(Vector2)

Determines whether the specified point is contained within the rectangle.

```
public bool Contains(Vector2 p)
```

Parameters

`p` [Vector2](#)

The point to check.

Returns

[bool](#)

True if the point is inside the rectangle; otherwise, false.

Contains(Vector2, Vector2, float)

Determines whether a specified point is contained within a rotated rectangle relative to a given origin.

```
public bool Contains(Vector2 p, Vector2 origin, float rotation)
```

Parameters

`p` [Vector2](#)

The point that is being checked for containment within the rectangle.

`origin` [Vector2](#)

The origin point relative to which the rotation is applied.

`rotation` [float](#)

The rotation angle, in degrees, applied counterclockwise to the rectangle.

Returns

[bool](#)

True if the point is contained within the rotated rectangle; otherwise, false.

Contains(float, float)

Determines whether the specified coordinates are contained within the rectangle.

```
public bool Contains(float x, float y)
```

Parameters

x [float](#)

The X-coordinate of the point to check.

y [float](#)

The Y-coordinate of the point to check.

Returns

[bool](#)

True if the point is inside the rectangle; otherwise, false.

Equals(RectangleF)

Determines whether the current rectangle is equal to another [RectangleF](#).

```
public bool Equals(RectangleF other)
```

Parameters

other [RectangleF](#)

The rectangle to compare with the current rectangle.

Returns

[bool](#)

True if the rectangles are equal; otherwise, false.

Equals(object?)

Determines whether the specified object is equal to the current rectangle.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current rectangle.

Returns

[bool](#)

True if the object is a [RectangleF](#) and is equal to the current rectangle; otherwise, false.

GetHashCode()

Returns a hash code for the current rectangle.

```
public override int GetHashCode()
```

Returns

[int](#)

A hash code for the current rectangle.

ToString()

Returns a string that represents the current rectangle.

```
public override string ToString()
```

Returns

[string](#)

A string that represents the rectangle's position and size.

Operators

operator ==(RectangleF, RectangleF)

Determines whether two [RectangleF](#) instances are equal.

```
public static bool operator ==(RectangleF left, RectangleF right)
```

Parameters

left [RectangleF](#)

The first [RectangleF](#) to compare.

right [RectangleF](#)

The second [RectangleF](#) to compare.

Returns

[bool](#) ↗

True if both rectangles are equal; otherwise, false.

operator !=(RectangleF, RectangleF)

Determines whether two [RectangleF](#) instances are not equal.

```
public static bool operator !=(RectangleF left, RectangleF right)
```

Parameters

left [RectangleF](#)

The first [RectangleF](#) to compare.

right [RectangleF](#)

The second [RectangleF](#) to compare.

Returns

bool ↗

True if the rectangles are not equal; otherwise, false.

Struct Transform

Namespace: [Bliss.CSharp.Transformations](#)

Assembly: Bliss.dll

```
public struct Transform : IEquatable<Transform>
```

Implements

[IEquatable](#)<[Transform](#)>

Inherited Members

[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Transform()

Initializes a new instance of the [Transform](#) class with default values.

```
public Transform()
```

Properties

Forward

The forward Vector.

```
public Vector3 Forward { get; }
```

Property Value

[Vector3](#)

Right

The right vector.

```
public Vector3 Right { get; }
```

Property Value

[Vector3](#)

Rotation

Gets or sets the rotation component of the transform as a quaternion. Triggers the [OnUpdate](#) event when changed.

```
public Quaternion Rotation { get; set; }
```

Property Value

[Quaternion](#)

Scale

Gets or sets the scale component of the transform. Triggers the [OnUpdate](#) event when changed.

```
public Vector3 Scale { get; set; }
```

Property Value

[Vector3](#)

Translation

Gets or sets the translation (position) component of the transform. Triggers the [OnUpdate](#) event when changed.

```
public Vector3 Translation { get; set; }
```

Property Value

[Vector3](#) ↗

Up

The up vector.

```
public Vector3 Up { get; }
```

Property Value

[Vector3](#) ↗

Methods

Equals(Transform)

Determines whether the current instance is equal to another instance of the [Transform](#) struct.

```
public bool Equals(Transform other)
```

Parameters

other [Transform](#)

The [Transform](#) to compare with the current instance.

Returns

[bool](#) ↗

true if the current instance is equal to the specified [Transform](#); otherwise, **false**.

Equals(object?)

Determines whether the specified object is equal to the current [Transform](#) instance.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current [Transform](#).

Returns

[bool](#)

true if the specified object is equal to the current [Transform](#); otherwise, **false**.

GetHashCode()

Returns the hash code for the current instance of the [Transform](#) struct.

```
public override int GetHashCode()
```

Returns

[int](#)

An integer representing the hash code of the current [Transform](#) instance.

GetTransform()

Returns the transformation matrix for the current Transform object.

```
public Matrix4x4 GetTransform()
```

Returns

[Matrix4x4](#)

The transformation matrix.

ToString()

Returns a string representation of the current Transform object.

```
public override string ToString()
```

Returns

[string](#)

A string that represents the values of Translation, Rotation, and Scale.

Events

OnUpdate

Event triggered whenever the transformation is updated (translation, rotation, or scale changes).

```
public event Action<Transform>? OnUpdate
```

Event Type

[Action](#) <[Transform](#)>

Operators

operator ==(Transform, Transform)

Determines whether two instances of the [Transform](#) struct are equal.

```
public static bool operator ==(Transform left, Transform right)
```

Parameters

left [Transform](#)

The first instance of [Transform](#) to compare.

right Transform

The second instance of [Transform](#) to compare.

Returns

[bool](#) ↗

`true` if the two instances are equal; otherwise, `false`.

operator !=(Transform, Transform)

Determines whether two instances of the [Transform](#) struct are not equal.

```
public static bool operator !=(Transform left, Transform right)
```

Parameters

left Transform

The first instance of [Transform](#) to compare.

right Transform

The second instance of [Transform](#) to compare.

Returns

[bool](#) ↗

`true` if the two instances are not equal; otherwise, `false`.

Namespace Bliss.CSharp.Windowing

Classes

[Sdl3Window](#)

[Window](#)

Interfaces

[IWindow](#)

Enums

[WindowState](#)

[WindowType](#)

Interface IWindow

Namespace: [Bliss.CSharp.Windowing](#)

Assembly: Bliss.dll

```
public interface IWindow : IDisposable
```

Inherited Members

[IDisposable.Dispose\(\)](#) ↗

Properties

Exists

Indicates whether the window currently exists. This property can be used to check if the window has not been closed or destroyed.

```
bool Exists { get; }
```

Property Value

[bool](#) ↗

Handle

Gets the native handle of the window. This handle can be used to interact with low-level windowing operations directly through platform-specific APIs or libraries.

```
nint Handle { get; }
```

Property Value

[nint](#) ↗

Id

Gets the unique identifier for the window. This identifier can be used to reference the window in various windowing and event handling operations.

```
uint Id { get; }
```

Property Value

[uint](#)

IsFocused

Indicates whether the window is currently focused. A window is considered focused when it has received input focus and is the active window receiving user input. This property can be used to check if the window is the foreground window.

```
bool IsFocused { get; }
```

Property Value

[bool](#)

SwapchainSource

Gets the source of the swapchain tied to the window. This source provides the necessary information to create and manage swapchains for rendering graphics content within the window.

```
SwapchainSource SwapchainSource { get; }
```

Property Value

[SwapchainSource](#)

Methods

CaptureMouse(bool)

Enables or disables capturing of the mouse cursor for the window.

```
void CaptureMouse(bool enabled)
```

Parameters

`enabled` [bool](#)

A boolean value indicating whether to enable mouse capture. Pass true to enable mouse capture or false to disable it.

ClientToScreen(Point)

Converts the specified client-area point to screen coordinates.

```
Point ClientToScreen(Point point)
```

Parameters

`point` [Point](#)

The client-area point to be converted.

Returns

[Point](#)

The converted point in screen coordinates.

GetHeight()

Retrieves the current height of the window.

```
int GetHeight()
```

Returns

[int ↗](#)

The current window height as an integer.

GetOrCreateOpenGLPlatformInfo(GraphicsDeviceOptions, GraphicsBackend)

Retrieves or creates the OpenGL platform information required for the specified graphics device options and backend.

```
OpenGLPlatformInfo GetOrCreateOpenGLPlatformInfo(GraphicsDeviceOptions options,  
GraphicsBackend backend)
```

Parameters

[options](#) [GraphicsDeviceOptions ↗](#)

The graphics device options to use.

[backend](#) [GraphicsBackend ↗](#)

The graphics backend to use.

Returns

[OpenGLPlatformInfo ↗](#)

The OpenGL platform information.

GetPosition()

Retrieves the current position of the window.

```
(int, int) GetPosition()
```

Returns

[\(int ↗, int ↗\)](#)

A tuple containing the x and y coordinates of the window.

GetSize()

Retrieves the current size of the window.

```
(int, int) GetSize()
```

Returns

```
(int, int)
```

A tuple containing the width and height of the window.

GetState()

Retrieves the current state of the window.

```
WindowState GetState()
```

Returns

```
WindowState
```

The current state of the window as a `WindowState` enum value.

GetTitle()

Retrieves the current title of the window.

```
string GetTitle()
```

Returns

```
string
```

The current window title as a string.

GetWidth()

Retrieves the current width of the window.

```
int GetWidth()
```

Returns

[int](#)

The current window width as an integer.

GetX()

Retrieves the current X coordinate of the window.

```
int GetX()
```

Returns

[int](#)

The current X coordinate of the window as an integer.

GetY()

Retrieves the current y-coordinate of the window's position.

```
int GetY()
```

Returns

[int](#)

The current y-coordinate of the window as an integer.

HasState(WindowState)

Checks if the current state of the window matches the specified state.

```
bool HasState(WindowState state)
```

Parameters

state [WindowState](#)

The state to be checked against the current window state.

Returns

[bool](#)

True if the current state of the window matches the specified state, otherwise false.

Hide()

Hides the window, making it no longer visible on the screen.

```
void Hide()
```

Maximize()

Maximizes the window, filling the entire available screen space based on the current display settings.

```
void Maximize()
```

Minimize()

Minimizes the current window, reducing it to its icon on the taskbar or dock.

```
void Minimize()
```

PumpEvents()

Processes all pending window events.

```
void PumpEvents()
```

ScreenToClient(Point)

Converts the specified screen coordinates to client-area coordinates.

```
Point ScreenToClient(Point point)
```

Parameters

[point](#) [Point](#)

The screen coordinates to convert.

Returns

[Point](#)

The converted client-area coordinates as a Point.

SetBordered(bool)

Configures whether the window should have a visible border.

```
void SetBordered(bool bordered)
```

Parameters

[bordered](#) [bool](#) ↗

A boolean indicating if the window should be bordered (true) or not (false).

SetFullscreen(bool)

Sets the window into or out of fullscreen mode.

```
void SetFullscreen(bool fullscreen)
```

Parameters

fullscreen [bool](#)

True to enable fullscreen mode, false to disable it.

SetHeight(int)

Sets the height of the window to the specified value.

```
void SetHeight(int height)
```

Parameters

height [int](#)

The new height for the window.

SetIcon(Image)

Sets the icon of the window.

```
void SetIcon(Image image)
```

Parameters

image [Image](#)

The image to set as the window icon, represented as an Image of Rgba32 format.

SetPosition(int, int)

Sets the position of the window to the specified coordinates.

```
void SetPosition(int x, int y)
```

Parameters

x [int](#)

The x-coordinate to set for the window position.

y [int](#)

The y-coordinate to set for the window position.

SetResizable(bool)

Sets whether the window can be resized by the user.

```
void SetResizable(bool resizable)
```

Parameters

resizable [bool](#)

A boolean value indicating whether the window should be resizable.

SetSize(int, int)

Sets the size of the window to the specified width and height.

```
void SetSize(int width, int height)
```

Parameters

width [int](#)

The new width for the window.

height [int](#)

The new height for the window.

SetTitle(string)

Sets the title of the window.

```
void SetTitle(string title)
```

Parameters

title [string](#)

The new title to set for the window.

SetWidth(int)

Sets the width of the window to the specified value.

```
void SetWidth(int width)
```

Parameters

width [int](#)

The new width for the window.

SetWindowAlwaysOnTop(bool)

Configures the window to always remain on top of other windows.

```
void SetWindowAlwaysOnTop(bool alwaysOnTop)
```

Parameters

alwaysOnTop [bool](#)

A boolean value indicating whether the window should always be on top of other windows. Set to true to enable this behavior, or false to disable it.

SetX(int)

Sets the X coordinate of the window to the specified value.

```
void SetX(int x)
```

Parameters

x [int](#)

The new X coordinate for the window.

SetY(int)

Sets the y-coordinate of the window's position.

```
void SetY(int y)
```

Parameters

y [int](#)

The new y-coordinate to set for the window.

Show()

Makes the window visible to the user if it is currently hidden.

```
void Show()
```

Events

Closed

Occurs after the window has closed.

```
event Action? Closed
```

Event Type

[Action](#)

DragDrop

Occurs when a drag-and-drop operation is performed.

```
event Action<string>? DragDrop
```

Event Type

[Action](#) <[string](#)>

Exposed

Occurs when the window is exposed (made visible or unhidden).

```
event Action? Exposed
```

Event Type

[Action](#)

FocusGained

Occurs when the window gains focus.

```
event Action? FocusGained
```

Event Type

[Action](#)

FocusLost

Occurs when the window loses focus.

`event Action? FocusLost`

Event Type

[Action](#)

GamepadAdded

Occurs when a new gamepad is detected and added to the system. The event provides the ID of the newly connected gamepad.

`event Action<uint>? GamepadAdded`

Event Type

[Action](#) <[uint](#)>

GamepadAxisMoved

Invoked when a gamepad's axis is moved. This event provides details such as the gamepad ID, the specific axis, and the position value of the axis movement.

`event Action<uint, GamepadAxis, short>? GamepadAxisMoved`

Event Type

[Action](#) <[uint](#), [GamepadAxis](#), [short](#)>

GamepadButtonDown

Occurs when a gamepad button is pressed down. The event provides the gamepad ID and the button that was pressed.

```
event Action<uint, GamepadButton>? GamepadButtonDown
```

Event Type

[Action](#) <[uint](#), [GamepadButton](#)>

GamepadButtonUp

Event triggered when a gamepad button is released. The event handler receives two parameters: the ID of the gamepad and the button that was released.

```
event Action<uint, GamepadButton>? GamepadButtonUp
```

Event Type

[Action](#) <[uint](#), [GamepadButton](#)>

GamepadRemoved

Occurs when a gamepad is removed from the system. The event provides the ID of the removed gamepad as an argument.

```
event Action<uint>? GamepadRemoved
```

Event Type

[Action](#) <[uint](#)>

Hidden

Occurs when the window is hidden.

```
event Action? Hidden
```

Event Type

[Action](#)

KeyDown

Occurs when a key is pressed.

event Action<KeyEvent>? KeyDown

Event Type

[Action](#) <KeyEvent>

KeyUp

Occurs when a key is released.

event Action<KeyEvent>? KeyUp

Event Type

[Action](#) <KeyEvent>

MouseButtonDown

Occurs when a mouse button is pressed.

event Action<MouseEvent>? MouseButtonDown

Event Type

[Action](#) <MouseEvent>

MouseButtonUp

Occurs when a mouse button is released.

```
event Action<MouseEvent>? MouseButtonUp
```

Event Type

[Action ↗ <MouseEvent>](#)

MouseEntered

Occurs when the mouse enters the window.

```
event Action? MouseEntered
```

Event Type

[Action ↗](#)

MouseLeft

Occurs when the mouse leaves the window.

```
event Action? MouseLeft
```

Event Type

[Action ↗](#)

MouseMove

Occurs when the mouse is moved.

```
event Action<Vector2>? MouseMove
```

Event Type

[Action ↗ <Vector2 ↗ >](#)

MouseWheel

Occurs when the mouse wheel is scrolled.

event Action<Vector2>? MouseWheel

Event Type

[Action](#)<[Vector2](#)>

Moved

Occurs when the window is moved.

event Action<Point>? Moved

Event Type

[Action](#)<[Point](#)>

Resized

Occurs when the window is resized.

event Action? Resized

Event Type

[Action](#)

Shown

Occurs when the window is shown.

event Action? Shown

Event Type

[Action](#)

TextInput

Occurs when text input is received from the user.

```
event Action<string>? TextInput
```

Event Type

[Action](#) <[string](#)>

Class Sdl3Window

Namespace: [Bliss.CSharp.Windowing](#)

Assembly: Bliss.dll

```
public class Sdl3Window : Disposable, IWindow, IDisposable
```

Inheritance

[object](#) ← [Disposable](#) ← Sdl3Window

Implements

[IWindow](#), [IDisposable](#)

Inherited Members

[Disposable.HasDisposed](#) , [Disposable.Dispose\(\)](#) , [Disposable.ThrowIfDisposed\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Sdl3Window(int, int, string, WindowState, GraphicsBackend)

Initializes a new instance of the [Sdl3Window](#) class with the specified width, height, title, and window state.

```
public Sdl3Window(int width, int height, string title, WindowState state,  
GraphicsBackend backend)
```

Parameters

width [int](#)

The width of the window in pixels.

height [int](#)

The height of the window in pixels.

title [string](#)

The title of the window.

state [WindowState](#)

The initial state of the window, specified as a [WindowState](#) value.

backend [GraphicsBackend](#)

The graphics backend to use for rendering (e.g., Vulkan, OpenGL).

Exceptions

[Exception](#)

Thrown if SDL fails to initialize the subsystem required for creating the window.

Properties

Exists

Indicates whether the window currently exists.

```
public bool Exists { get; }
```

Property Value

[bool](#)

Handle

Represents the native handle of the SDL window, which is used for low-level window operations and interactions.

```
public nint Handle { get; }
```

Property Value

[nint](#)

Id

Represents the unique identifier for the SDL window. This identifier can be used to reference or differentiate between multiple windows.

```
public uint Id { get; }
```

Property Value

[uint](#)

IsFocused

Indicates whether the window is currently focused.

```
public bool IsFocused { get; }
```

Property Value

[bool](#)

SwapchainSource

Represents the source of the swapchain, which is used for managing the rendering surface and synchronization for the window.

```
public SwapchainSource SwapchainSource { get; }
```

Property Value

[SwapchainSource](#)

Methods

CaptureMouse(bool)

Captures or releases the mouse input for the window.

```
public void CaptureMouse(bool enabled)
```

Parameters

`enabled` [bool](#)

A boolean indicating whether to capture the mouse (true) or release it (false).

ClientToScreen(Point)

Converts a point from client-area coordinates to screen coordinates.

```
public Point ClientToScreen(Point point)
```

Parameters

`point` [Point](#)

The point in client-area coordinates to be converted.

Returns

[Point](#)

The point in screen coordinates.

Dispose(bool)

Disposes of the object and releases associated resources.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` [bool](#)

True if called from user code; false if called from a finalizer.

GetHeight()

Retrieves the height of the window.

```
public int GetHeight()
```

Returns

[int](#)

The height of the window in pixels.

GetOrCreateOpenGLPlatformInfo(GraphicsDeviceOptions, GraphicsBackend)

Retrieves or creates the OpenGL platform information for the current window.

```
public OpenGLPlatformInfo GetOrCreateOpenGLPlatformInfo(GraphicsDeviceOptions options, GraphicsBackend backend)
```

Parameters

[options](#) [GraphicsDeviceOptions](#)

Options for configuring the graphics device.

[backend](#) [GraphicsBackend](#)

The graphics backend to use.

Returns

[OpenGLPlatformInfo](#)

The OpenGL platform information associated with the current window.

Exceptions

[VeldridException](#)

Thrown if unable to create the OpenGL context, potentially due to insufficient system support for the requested profile, version, or swapchain format.

GetPosition()

Retrieves the current position of the window.

```
public (int, int) GetPosition()
```

Returns

([int](#), [int](#))

A tuple containing the x and y coordinates of the window's position.

Exceptions

[Exception](#)

Thrown if there is an error retrieving the window's position.

GetSize()

Retrieves the current width and height of the window in pixels.

```
public (int, int) GetSize()
```

Returns

([int](#), [int](#))

A tuple containing two integers representing the width and height of the window in pixels.

GetState()

Retrieves the current state of the window.

```
public WindowState GetState()
```

Returns

[WindowState](#)

The current state of the window represented by the [WindowState](#) enumeration.

GetTitle()

Retrieves the title of the window.

```
public string GetTitle()
```

Returns

[string](#)

The title of the window as a string.

GetWidth()

Gets the width of the window.

```
public int GetWidth()
```

Returns

[int](#)

The width of the window in pixels.

GetX()

Retrieves the current X-coordinate position of the window.

```
public int GetX()
```

Returns

[int](#)

The X-coordinate of the window's position.

GetY()

Retrieves the Y-coordinate of the window's position.

```
public int GetY()
```

Returns

[int](#)

The Y-coordinate of the window's position.

HasState(WindowState)

Determines if the current window state matches the specified state.

```
public bool HasState(WindowState state)
```

Parameters

state [WindowState](#)

The window state to compare with the current state.

Returns

[bool](#)

True if the current window state matches the specified state; otherwise, false.

Hide()

Hides the window, making it invisible to the user.

```
public void Hide()
```

Maximize()

Maximizes the window to occupy the entire screen space available within the current display's working area.

```
public void Maximize()
```

Minimize()

Minimizes the current window.

```
public void Minimize()
```

PumpEvents()

Processes all pending events for the window and invokes corresponding event handlers.

```
public void PumpEvents()
```

Exceptions

[Win32Exception](#)

Thrown if an error occurs when processing events.

ScreenToClient(Point)

Converts a point from screen coordinates to client coordinates.

```
public Point ScreenToClient(Point point)
```

Parameters

point [Point](#)

The point in screen coordinates to be converted.

Returns

[Point](#)

The point in client coordinates.

SetBordered(bool)

Sets whether the window should have a border.

```
public void SetBordered(bool bordered)
```

Parameters

bordered [bool](#) ↗

A boolean indicating whether the window should be bordered. Pass true to enable the border, or false to remove it.

SetFullscreen(bool)

Sets the fullscreen state of the window.

```
public void SetFullscreen(bool fullscreen)
```

Parameters

fullscreen [bool](#) ↗

A boolean value indicating whether the window should be fullscreen. Pass `true` to enable fullscreen mode, or `false` to disable it.

SetHeight(int)

Sets the height of the window to the specified value.

```
public void SetHeight(int height)
```

Parameters

`height` [int](#)

The new height of the window.

SetIcon(Image)

Sets the icon for the SDL3 window using the provided image.

```
public void SetIcon(Image image)
```

Parameters

`image` [Image](#)

The image to set as the window icon. It should be of type [Image](#).

Exceptions

[Exception](#)

Thrown if an error occurs while setting the window icon.

SetPosition(int, int)

Sets the position of the window on the screen.

```
public void SetPosition(int x, int y)
```

Parameters

x [int](#)

The x-coordinate of the window position.

y [int](#)

The y-coordinate of the window position.

SetResizable(bool)

Specifies whether the window should be resizable and updates its resizable state accordingly.

```
public void SetResizable(bool resizable)
```

Parameters

resizable [bool](#)

A boolean value indicating if the window should be resizable (true) or not resizable (false).

SetSize(int, int)

Sets the size of the window to the specified width and height.

```
public void SetSize(int width, int height)
```

Parameters

width [int](#)

The new width of the window.

height [int](#)

The new height of the window.

SetTitle(string)

Sets the title of the window.

```
public void SetTitle(string title)
```

Parameters

title [string](#)

The new title to set for the window.

Exceptions

[InvalidOperationException](#)

Thrown if the title could not be set due to an internal error.

SetWidth(int)

Sets the width of the window.

```
public void SetWidth(int width)
```

Parameters

width [int](#)

The new width of the window.

SetWindowAlwaysOnTop(bool)

Sets whether the window should always be displayed on top of other windows.

```
public void SetWindowAlwaysOnTop(bool alwaysOnTop)
```

Parameters

alwaysOnTop [bool](#)

A boolean indicating whether the window should be always on top. True to enable, false to disable.

SetX(int)

Sets the X coordinate of the window's position.

```
public void SetX(int x)
```

Parameters

x [int](#)

The new X coordinate of the window.

SetY(int)

Sets the Y-coordinate of the window's position.

```
public void SetY(int y)
```

Parameters

y [int](#)

The new Y-coordinate.

Show()

Makes the window visible if it is currently hidden.

```
public void Show()
```

Events

Closed

Occurs after the window has closed.

```
public event Action? Closed
```

Event Type

[Action](#)

DragDrop

Occurs when a drag-and-drop operation is performed.

```
public event Action<string>? DragDrop
```

Event Type

[Action](#) <[string](#)>

Exposed

Occurs when the window is exposed (made visible or unhidden).

```
public event Action? Exposed
```

Event Type

[Action](#)

FocusGained

Occurs when the window gains focus.

```
public event Action? FocusGained
```

Event Type

[Action](#)

FocusLost

Occurs when the window loses focus.

```
public event Action? FocusLost
```

Event Type

[Action](#)

GamepadAdded

Event triggered when a new gamepad is connected to the system.

```
public event Action<uint>? GamepadAdded
```

Event Type

[Action](#) <[uint](#)>

GamepadAxisMoved

Represents an event that is triggered when a gamepad axis is moved.

```
public event Action<uint, GamepadAxis, short>? GamepadAxisMoved
```

Event Type

[Action](#) <[uint](#), [GamepadAxis](#), [short](#)>

GamepadButtonDown

Occurs when a button on the gamepad is pressed.

```
public event Action<uint, GamepadButton>? GamepadButtonDown
```

Event Type

[Action](#) <[uint](#), [GamepadButton](#)>

GamepadButtonUp

Triggered when a gamepad button is released, providing the button identifier and related data.

```
public event Action<uint, GamepadButton>? GamepadButtonUp
```

Event Type

[Action](#) <[uint](#), [GamepadButton](#)>

GamepadRemoved

Event triggered when a gamepad is removed from the system.

```
public event Action<uint>? GamepadRemoved
```

Event Type

[Action](#) <[uint](#)>

Hidden

Occurs when the window is hidden.

```
public event Action? Hidden
```

Event Type

[Action](#)

KeyDown

Occurs when a key is pressed.

```
public event Action<KeyEvent>? KeyDown
```

Event Type

[Action](#) <[KeyEvent](#)>

KeyUp

Occurs when a key is released.

```
public event Action<KeyEvent>? KeyUp
```

Event Type

[Action](#) <[KeyEvent](#)>

MouseButtonDown

Occurs when a mouse button is pressed.

```
public event Action<MouseEvent>? MouseButtonDown
```

Event Type

[Action](#) <[MouseEvent](#)>

MouseButtonUp

Occurs when a mouse button is released.

```
public event Action<MouseEvent>? MouseButtonUp
```

Event Type

[Action ↗ <MouseEvent>](#)

MouseEntered

Occurs when the mouse enters the window.

```
public event Action? MouseEntered
```

Event Type

[Action ↗](#)

MouseLeft

Occurs when the mouse leaves the window.

```
public event Action? MouseLeft
```

Event Type

[Action ↗](#)

MouseMove

Occurs when the mouse is moved.

```
public event Action<Vector2>? MouseMove
```

Event Type

[Action ↗ <Vector2 ↗ >](#)

MouseWheel

Occurs when the mouse wheel is scrolled.

```
public event Action<Vector2>? MouseWheel
```

Event Type

[Action](#) <[Vector2](#)>

Moved

Occurs when the window is moved.

```
public event Action<Point>? Moved
```

Event Type

[Action](#) <[Point](#)>

Resized

Occurs when the window is resized.

```
public event Action? Resized
```

Event Type

[Action](#)

SdlEvent

Represents an event that is triggered whenever an SDL event occurs within the window.

```
public event Action<SDL_Event>? SdlEvent
```

Event Type

[Action](#) <SDL_Event>

Shown

Occurs when the window is shown.

```
public event Action? Shown
```

Event Type

[Action](#)

TextInput

Represents an event that triggers when text input is received.

```
public event Action<string>? TextInput
```

Event Type

[Action](#) <[string](#)>

Class Window

Namespace: [Bliss.CSharp.Windowing](#)

Assembly: Bliss.dll

```
public static class Window
```

Inheritance

[object](#) ← Window

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

CreateGraphicsDevice(IWindow, GraphicsDeviceOptions, GraphicsBackend)

Creates a graphics device for the specified window, based on the provided options and preferred backend.

```
public static GraphicsDevice CreateGraphicsDevice(IWindow window, GraphicsDeviceOptions  
options, GraphicsBackend preferredBackend)
```

Parameters

window [IWindow](#)

The window for which to create the graphics device.

options [GraphicsDeviceOptions](#)

Options for configuring the graphics device.

preferredBackend [GraphicsBackend](#)

The preferred graphics backend to use.

Returns

[GraphicsDevice](#)

A graphics device configured according to the specified options and preferred backend.

CreateWindow(WindowType, int, int, string, WindowState, GraphicsDeviceOptions, GraphicsBackend, out GraphicsDevice)

Creates a new window based on the specified parameters.

```
public static IWindow CreateWindow(WindowType type, int width, int height, string title, WindowState state, GraphicsDeviceOptions options, GraphicsBackend preferredBackend, out GraphicsDevice graphicsDevice)
```

Parameters

type [WindowType](#)

The type of window to create.

width [int](#)

The width of the window.

height [int](#)

The height of the window.

title [string](#)

The title of the window.

state [WindowState](#)

The state of the window (e.g., maximized, minimized).

options [GraphicsDeviceOptions](#)

Options for configuring the graphics device.

preferredBackend [GraphicsBackend](#)

The preferred graphics backend to use.

`graphicsDevice` [GraphicsDevice](#)

An output parameter that will hold the created graphics device.

Returns

[IWindow](#)

An implementation of [IWindow](#) corresponding to the specified parameters.

`GetPlatformDefaultBackend()`

Determines the default graphics backend for the current platform.

```
public static GraphicsBackend GetPlatformDefaultBackend()
```

Returns

[GraphicsBackend](#)

The default [GraphicsBackend](#) for the current platform.

Enum WindowState

Namespace: [Bliss.CSharp.Windowing](#)

Assembly: Bliss.dll

```
[Flags]
public enum WindowState
```

Fields

AlwaysOnTop = 8

The window is always on top of other windows, maintaining its topmost position.

Borderless = Resizable | FullScreen

The window is borderless, removing the title bar and window borders.

CaptureMouse = Resizable | Hidden

The window captures the mouse, confining its movement to the window area.

FullScreen = 2

The window is in full-screen mode, occupying the entire screen.

Hidden = FullScreen | Maximized

The window is hidden and not visible to the user.

HighPixelDensity = FullScreen | AlwaysOnTop

Enables rendering optimized for high-DPI (high pixel density) displays.

Maximized = 4

The window is maximized, taking up the largest possible area on the screen.

Minimized = Resizable | Maximized

The window is minimized, reducing it to an icon or taskbar entry.

None = 0

Indicates that the window has no specific state.

Resizable = 1

The window is resizable, allowing the user to adjust its size.

Transparent = Resizable | AlwaysOnTop

The window is transparent, allowing content behind it to be partially visible.

Enum WindowType

Namespace: [Bliss.CSharp.Windowing](#)

Assembly: Bliss.dll

```
public enum WindowType
```

Fields

Sdl3 = 0

Namespace Bliss.CSharp.Windowing.Events

Structs

[KeyEvent](#)

[MouseEvent](#)

Struct KeyEvent

Namespace: [Bliss.CSharp.Windowing.Events](#)

Assembly: Bliss.dll

```
public struct KeyEvent
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

KeyEvent(KeyboardKey, bool, bool)

Initializes a new instance of the [KeyEvent](#) class with the specified keyboard key, key state, and repeat flag.

```
public KeyEvent(KeyboardKey keyboardKey, bool isDown, bool repeat)
```

Parameters

keyboardKey [KeyboardKey](#)

The [KeyboardKey](#) representing the key involved in the event.

isDown [bool](#)

Indicates whether the key is pressed down ([true](#)) or released ([false](#)).

repeat [bool](#)

Indicates whether the key event is a repeated key press ([true](#)) or a single press ([false](#)).

Fields

IsDown

Indicates whether the key is currently pressed down.

```
public bool IsDown
```

Field Value

[bool](#)

KeyboardKey

Represents a key on the keyboard that can trigger key events.

```
public KeyboardKey KeyboardKey
```

Field Value

[KeyboardKey](#)

Repeat

Indicates whether the key press event is a repeat of the previous key press action.

```
public bool Repeat
```

Field Value

[bool](#)

Struct MouseEvent

Namespace: [Bliss.CSharp.Windowing.Events](#)

Assembly: Bliss.dll

```
public struct MouseEvent
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetType\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

MouseEvent(MouseButton, bool, bool)

Initializes a new instance of the MouseEvent class with the specified button and state.

```
public MouseEvent(MouseButton button, bool isDown, bool doubleClicked)
```

Parameters

button [MouseButton](#)

The mouse button that triggered the event.

isDown [bool](#)

A value indicating whether the button is pressed (true) or released (false).

doubleClicked [bool](#)

A value indicating whether the event was triggered by a double-click.

Fields

Button

Represents the mouse button involved in the event.

```
public MouseButton Button
```

Field Value

[MouseButton](#)

DoubleClicked

Indicates whether the mouse button was double-clicked during the event.

```
public bool DoubleClicked
```

Field Value

[bool](#) ↗

IsDown

Indicates whether the mouse button is pressed down.

```
public bool IsDown
```

Field Value

[bool](#) ↗