

SYKON SL20

Minimal Panoramic Sliding System



~162 mm

Frame depth (double rail)



EN AW 6063

Aluminium alloy



Up to 45 mm

Maximum glazing thickness



Polyamide thermal insulation inserts

Thermal break

Product Overview

SL20 is a minimal panoramic thermally broken sliding system designed to achieve ultra-slim sightlines with maximum transparency.

The system supports:

- Sliding doors and windows
- Double, triple and multi-track configurations
- Large glass panels with minimal aluminium visibility
- Pocket and corner sliding solutions

Technical Specifications

System type	Minimal sliding system
System concept	Slim / panoramic
Frame depth (double rail)	~162 mm
Aluminium alloy	EN AW 6063
Hardness	12 - 14 HB
Profile thickness	Varies by profile
Thermal break	Polyamide thermal insulation inserts
Thermal behavior	Thermally broken system
Glazing type	Double / Triple glazing
Typical glazing thickness	Variable (up to 45mm thick)

Tested Performance

Air infiltration / exfiltration — ASTM E283	$\leq 5.4 \text{ m}^3/\text{h}\cdot\text{m}^2 @ 75 \text{ Pa}$
Dynamic water penetration — AAMA 501.1	No water ingress observed
Wind resistance - serviceability — ASTM E330	$\pm 1211 \text{ Pa}$ (within L/175 limit)
Wind resistance - safety — ASTM E330	$\pm 1832 \text{ Pa}$ (no failure / no damage)
Air infiltration rate	$\leq 5.4 \text{ m}^3/\text{h}\cdot\text{m}^2 @ 75 \text{ Pa}$
Sample area	~6.9 m ²
Total airflow	~37.3 m ³ /h
Static water penetration	No water ingress
Dynamic water penetration	No water ingress

System Options

Double, triple, and quadruple track systems

Pocket sliding configurations

Corner opening systems (90°)

Locking and non-locking options

Recessed floor installation

Area of Usage

Luxury villas

High-end residential projects

Panoramic façades

Hospitality developments

www.sykon.ae | info@sykon.ae