

Toward Skill Evolution for Blind Vulnerability Analysis Agents

Authors omitted in working draft

August 2026

Abstract

Large language model agents are increasingly equipped with reusable natural-language skills, but their role in vulnerability analysis remains under-specified. In this domain, agents repeatedly perform similar procedural steps: locate an entry point, identify a dispatch branch, trace attacker-controlled data, reach a sink, and decide whether the path represents a real vulnerability. These recurring steps suggest that blind vulnerability analysis should benefit from reusable skills. At the same time, our early experiments show that static skill libraries are insufficient: a skill that helps one firmware family may be irrelevant or harmful on another, and apparently successful runs may still be poor candidates for long-term reuse.

This paper argues that *skill evolution for blind vulnerability analysis* is an important research problem in its own right. The key question is not merely how to write or retrieve skills, but how to decide when the result of a completed blind run should be converted into a reusable skill that future analyses will depend on. We therefore present a first framework-oriented formulation of this lifecycle: blind remote analysis, server-side skill selection and injection, local external confirmation, run-level feedback construction, candidate skill generation, and gated publication into a live library.

Our current contribution is intentionally scoped as a first arXiv-stage paper. We do not claim that stable autonomous skill improvement has already been achieved, nor that the current system can discover unknown vulnerabilities end-to-end. Instead, we aim to establish the problem, the lifecycle, and the initial evidence that make this line of work worth pursuing. Empirically, leakage-controlled reruns and frozen multi-case firmware studies show that skill usage can materially change vulnerability localization outcomes, but the effect is heterogeneous, family-dependent, and not yet sufficient to prove strict necessity across all cases. Archived gate outcomes further suggest that candidate generation is not the only difficulty: deciding whether a candidate skill should enter the live library is itself a central open problem. We present the current prototype and preliminary evidence as a foundation for future work on attribution, publication control, and discovery-oriented evaluation.

Keywords: LLM agents; skill evolution; blind vulnerability analysis; firmware security; external confirmation; reusable procedural knowledge.

1 Introduction

Large language model (LLM) agents increasingly rely on reusable memories, natural-language instructions, and explicit skill libraries to improve over repeated tasks. Systems such as Voyager [?], ExpeL [?], and SkillClaw [?] show that agents can accumulate procedural knowledge and reuse it later. Other recent work studies context-to-skill induction [?], on-policy skill distillation [?], environment-grounded skill refinement [? ?], and verifier-guided skill revision [? ?]. Together, these directions suggest that skill is becoming a practical interface between one-shot model behavior and longer-lived agentic adaptation.

Vulnerability analysis is a particularly natural setting for this idea. In blind analysis or discovery-oriented auditing, the agent repeatedly faces variations of the same procedural problem: identify where attacker-controlled input enters, decide which branch or handler deserves attention, trace data or control to a dangerous operation, and determine whether the behavior is exploitable.

These patterns recur across firmware families, binaries, and vulnerability types. If any domain should benefit from reusable skills, vulnerability analysis is one of them.

However, the presence of repeated structure does not imply that a fixed skill library is enough. Recent work has shown that skills can also be harmful: a topically relevant skill can push an agent toward the wrong abstraction level or the wrong execution path [?]. Our own experiments show the same pattern in firmware analysis. A skill that improves vulnerability localization on one family may hurt another; a more specific skill can outperform a generic one in some cases and underperform it in others. This means the real question is not simply whether vulnerability-analysis agents need skills, but why those skills must evolve from real runs instead of remaining static templates.

That requirement creates a second, harder problem. A completed run may appear successful, yet still be a bad source for long-term skill reuse. It may be correct only by chance, correct but redundant because the model would have succeeded anyway, or apparently correct while drifting to the wrong vulnerable function within the same firmware family. Thus, once we move from “should agents use skills?” to “should agents evolve skills?”, a new research object appears:

When should the result of a completed blind vulnerability-analysis run be converted into a reusable skill that will influence future analyses?

This paper focuses on the combination of *agent-based vulnerability analysis* and *skill evolution*, rather than on either topic in isolation. We do not claim that the full problem is already solved. Instead, we argue that the path itself remains under-explored: blind vulnerability analysis benefits from skills; static skills are not enough; and converting run outcomes into evolving skills introduces new questions of evidence, attribution, and publication control.

Our prototype setting couples remote blind analysis with local external confirmation. An agent operates in an isolated analysis environment; the local system archives the run, scores the final answer, checks it against external evidence, and only then allows an evolution service to propose candidate skill updates. The resulting workflow is not yet a mature autonomous discovery system. It is, however, a concrete and testable prototype for studying whether the outputs of blind vulnerability-analysis runs should become persistent skills.

This paper makes four contributions:

1. **We identify skill evolution for blind vulnerability analysis as a distinct research problem.** The core question is not merely how to write or retrieve skills, but how to move from a completed run to a reusable live skill without polluting future analyses.
2. **We propose a prototype lifecycle for that problem.** The lifecycle connects blind remote analysis, server-side skill injection, local external confirmation, run-level feedback, candidate skill generation, and gated publication.
3. **We present initial empirical evidence that skill matters but is heterogeneous.** Clean reruns and frozen firmware studies show that skill can materially change vulnerability localization, while family-specific experiments show that more specific skills are not uniformly better.
4. **We argue that candidate evaluation and publication are central future challenges.** Current gate results suggest that generating candidate skills is not enough; the harder question is deciding which candidates deserve to enter the live library.

The scope of the paper is therefore deliberate: this is a framework paper with preliminary evidence, written to establish the research direction early rather than to claim that stable autonomous skill evolution has already been achieved.

2 Why Skill, Why Evolution, Why Here

2.1 Why vulnerability analysis needs skills

Blind vulnerability analysis is not a single prediction problem. It is a repeated procedural task. In firmware and binary auditing, analysts frequently perform the same types of reasoning steps:

- find the entry point or handler that exposes attacker-controlled input;
- identify the relevant branch, mode, or dispatch path;
- follow dataflow toward dangerous operations or implicit sinks;
- distinguish the true target path from nearby but wrong high-risk paths;
- convert local evidence into a vulnerability-level conclusion.

These steps are too structured to be treated as fully one-off reasoning. A reusable skill can encode how to traverse such a path more reliably than a bare prompt that starts from scratch every time.

2.2 Why static skills are not enough

A fixed library is appealing, but our experiments suggest it is not sufficient. In some firmware families, a narrower family-specific skill improves localization by steering the model toward the right handler. In others, the same narrowing hurts because the family contains dense and overlapping handler clusters. Likewise, a skill that is topically relevant can still be procedurally wrong: it may talk about command injection in general, yet encourage the model to summarize a category of sinks rather than narrow to the correct branch and target function.

This means a vulnerability-analysis skill library cannot be treated as static reference text. It must be revised in response to real runs, real failures, and real case families.

2.3 Why skill evolution is harder than skill retrieval

Once we allow skill revision, we face a stronger requirement than ordinary task success. Suppose a run gets the right answer. That does not necessarily mean its selected skills were useful, or that the resulting procedural trace should be promoted into future runs. At least four cases are possible:

1. the skill was genuinely useful and should be retained;
2. the skill was harmless but unnecessary;
3. the run succeeded for reasons unrelated to the skill;
4. the run found a dangerous but wrong target path and should not be reinforced.

Skill evolution therefore raises a governance problem, not just a generation problem.

3 Problem Statement

We model a run as

$$r = (x, S_r, \tau, y, E), \tag{1}$$

where x is a blind vulnerability-analysis task, S_r is the set of selected skills, τ is the trajectory, y is the final answer, and E is the externally collected evidence.

The paper is centered on three questions:

1. **Skill effect:** how much do selected skills change the final analysis outcome?
2. **Run-to-skill transition:** when does a completed run contain reusable procedural knowledge?
3. **Publication control:** when should a candidate update be allowed to influence later runs through the live skill library?

The second and third questions are the ones we believe are still under-articulated in the current literature on security agents and skill libraries.

To make this concrete, let a completed run r produce a candidate skill update

$$\Delta s = \mathcal{C}(r), \quad (2)$$

where $\mathcal{C}$ is a candidate-construction procedure over the archived run. A separate publication policy then decides whether Δs should influence later runs:

$$\mathcal{P}(r, \Delta s, E) \in \{\text{publish}, \text{hold}, \text{reject}\}. \quad (3)$$

In principle, $\mathcal{P}$ should depend not only on final answer quality, but also on whether the run reached the right target path, whether the resulting procedural pattern is reusable, and whether promoting it would risk polluting later analyses. Our current prototype only approximates this policy, but the equation makes the intended research object explicit: skill evolution is not only about generating Δs , but also about studying the decision rule $\mathcal{P}$.

For the current prototype, $\mathcal{P}$ is operationalized through a replay-style gate. Given a baseline run r and a candidate skill update Δs , the system constructs a follow-up run

$$\hat{r} = \mathcal{R}(x, S_r \cup \{\Delta s\}), \quad (4)$$

where $\mathcal{R}$ re-executes the same task under the candidate-augmented skill set. The candidate is then evaluated under a conservative publication rule of the form

$$\mathcal{P}(r, \Delta s, E) = \text{publish} \iff [m(\hat{r}) \geq m(r) - \varepsilon] \wedge [c(\hat{r}, E) = \text{pass}], \quad (5)$$

where $m(\cdot)$ is a task-level quality signal and $c(\cdot)$ checks externally confirmed consistency. This replay gate is intentionally conservative: it is a practical approximation to publication control, not a complete solution to causal skill attribution.

4 Prototype Framework

4.1 Split-plane execution

The framework separates two planes:

- an **analysis plane**, where the agent performs blind vulnerability analysis in a remote environment; and
- a **confirmation plane**, where the local system scores outputs, gathers external evidence, archives sessions, and drives skill evolution.

This separation reduces direct answer leakage while still allowing the system to process evidence after the run.

4.2 Skill injection and session archival

Selected skills are injected server-side, and each run is archived together with its selected skill set and immutable session segment. This does not solve causal attribution, but it makes later analysis auditable: we can at least determine what procedural prior the model saw.

4.3 External confirmation

The current prototype supports multiple evidence forms:

- source-backed predicates;
- logic harnesses;
- behavioral oracles; and
- sanitizer-backed runtime evidence.

These signals are not treated as proofs of skill contribution. Instead, they constrain what kinds of run outcomes are eligible to enter the evolution loop.

4.4 Feedback, candidates, and gate

After scoring and confirmation, the system constructs run-level feedback, generates candidate skill updates, and stages them behind a gate before publication. This gate is the current boundary between *interesting candidate text* and *trusted live skill*.

5 Prototype Realization

The current implementation extends SkillClaw with:

- remote blind execution support;
- firmware- and source-oriented benchmark case descriptions;
- server-side skill selection with inline and catalog-style injection paths;
- target-aware scoring and diagnostic flags;
- run archival and handoff records;
- candidate skill generation through an evolution service; and
- validation-gated publication from candidate storage into a live skill directory.

The implementation is best viewed as a research prototype rather than a finalized product. Its value lies in making the run-to-skill transition measurable and debuggable.

Operationally, the system maintains a distinction between a *live* skill library used for subsequent analysis, a *candidate* area that stores evolution outputs awaiting review, and a *shared/archive* area that records historical skill states and session-linked artifacts. This separation is not only an engineering convenience. It is necessary if publication is itself treated as a research problem rather than as an automatic side effect of candidate generation.

6 Preliminary Experimental Evidence

6.1 What the current experiments are meant to show

The present experiments are not designed to prove that autonomous skill evolution is already reliable. They are designed to answer a narrower set of questions:

1. does skill materially change blind vulnerability-analysis outcomes?
2. are those effects uniform, or highly case-dependent?

Table 1: Current experimental suites used in this draft.

Study	Target	Conditions	Primary role in this paper
Leakage-controlled clean rerun	84 source/firmware reruns	no-skill / weak-skill / oracle-skill	Re-check whether earlier skill gains survive after removing answer-bearing prompt content
Frozen firmware necessity study	153 runs over 17 firmware targets	no-skill / weak-skill / oracle-skill	Measure whether stronger skills change true-target localization and decoy attraction under a fixed protocol
Family-specific distinguishing studies	Belkin F9K1122; Tenda FH451	generic oracle / distinguishing oracle	Test whether narrower family-specific skills help only when the family exposes usable discriminative cues
Gate archive analysis	94 archived gate decisions	candidate rerun + gate decision logs	Examine whether the main bottleneck already lies in candidate publication rather than candidate generation

3. does the evolution loop face its main difficulty in candidate generation or in candidate publication?

The reporting policy in this draft follows the same principle. Clean reruns, the frozen firmware protocol, family-specific distinguishing studies, and archived gate records are treated as *primary evidence*. Earlier development-time runs remain useful for diagnosis, but are not used as headline quantitative results once answer leakage, overly permissive scoring, or protocol contamination were identified.

6.2 Leakage-controlled reruns

An 84-run three-condition rerun was used to clean earlier overly optimistic oracle-style results. After removing answer-bearing skill content, oracle-skill still outperformed weak-skill and no-skill, while sharply reducing decoy hits. This shows that skill effects remain real after leakage cleanup, rather than collapsing entirely.

More specifically, under this cleaned protocol, oracle-skill achieved a 35.7% true hit rate, compared with 14.3% for weak-skill and 3.6% for no-skill. Just as importantly, decoy hits dropped from 9 and 12 down to 1. This matters because a large part of firmware-analysis failure is not “finding nothing,” but being pulled toward a wrong yet still dangerous handler that appears superficially plausible.

6.3 Frozen 153-run firmware study

A larger frozen protocol was then run across 17 firmware cases under three conditions: no-skill, weak-skill, and oracle-skill. Under the primary reporting protocol, oracle skill achieved 46.7% true hits, versus 11.1% for weak-skill and 6.7% for no-skill, while reducing decoy hits from 28/45 and 24/45 to 2/45. These numbers are not yet sufficient to prove strict necessity for every case, but they do show that skill materially changes localization quality.

The practical implication is that stronger skill formulation changes the agent’s target selection behavior, not merely its narrative quality. Several families that were previously dominated by nearby decoy handlers move toward the intended vulnerable path once the agent is given a more structured procedural prior. At the same time, a large residual “NO” region remains, which is why the current paper avoids claiming solved necessity or solved discovery.

6.4 Family-specific distinguishing studies

The current results also show that specificity is not uniformly beneficial. In the Belkin F9K1122 family, a distinguishing skill increased accuracy from 20.0% to 66.7%. In the Tenda FH451 family, the same idea reduced accuracy from 40.0% to 26.7%. This suggests that the usefulness of a refined skill depends on whether the family is structurally separable rather than merely topically similar.

Table 2: Condensed summary of the current main empirical signals.

Study	Weaker condition		Stronger condition	What it shows
Clean rerun (84 runs)	no-skill: 3.6%; weak-skill: 14.3%		oracle-skill: 35.7%	Skill effect remains after leakage cleanup; decoys collapse from 9/12 to 1
Frozen firmware study (153 runs)	no-skill: 6.7%; weak-skill: 11.1%		oracle-skill: 46.7%	Stronger skills change target localization, not only output wording
Belkin F9K1122	generic 20.0%	oracle:	distinguishing oracle: 66.7%	Family-specific refinement can recover the right target when separable cues exist
Tenda FH451	generic 40.0%	oracle:	distinguishing oracle: 26.7%	Narrower skills are not uniformly better across dense handler families
Gate archive (94 decisions)	82 rejected		12 published	Candidate generation is possible; publication remains the harder filtering problem

This contrast is important for the paper’s main argument. If narrower skills always helped, then skill evolution would mostly be a content-accumulation problem. Instead, the current evidence suggests that the *shape* of a skill must match the structure of the target family. In some families, a distinguishing cue is enough to dislodge a persistent attractor. In others, the same style of refinement only overcommits the model to unstable cues.

6.5 Gate behavior

Archived gate records show that candidate generation is not the only challenge. The system can already produce candidates and stage them for follow-up validation, but it still lacks a strong criterion for deciding which candidates genuinely deserve to enter the live library. Replay-only gates can reject obviously poor candidates, yet they do not by themselves prove that a published skill contributed something necessary rather than merely harmless.

Across 94 archived gate decisions, 12 were published and 82 were rejected. The important point is not the raw acceptance rate. The important point is that publication already behaves like a distinct filtering problem with its own failure modes, operating after candidate text has been generated. In other words, the main unsolved issue in the current prototype is no longer “can the system write candidate skill text?” but “under what evidence should that text be trusted enough to enter the live library?”

The deeper limitation is that a replay-only gate cannot cleanly separate three cases: genuine improvement, harmless redundancy, and wrong-path success that still survives a permissive metric. This is why the present paper treats gate design as a research problem rather than as a solved engineering component.

7 Current Evidence and Scope Boundaries

7.1 What the current work already supports

The present prototype and experiments already support the following claims:

- blind vulnerability analysis is a plausible setting for skill-based agents;
- skill usage can materially alter vulnerability localization results;
- the effect of skill is heterogeneous and family-dependent;
- a full run-to-candidate-to-gate loop can be prototyped and studied.

7.2 What remains unresolved

The current work does *not* yet prove:

- stable autonomous skill improvement over long horizons;
- strict necessity of a particular skill for all target cases;
- robust counterfactual attribution of skill contribution; or
- end-to-end unknown-vulnerability discovery in a fully autonomous sense.

This boundary is intentional. The first goal of this draft is to establish that the research path exists and is worth occupying now, not to over-claim that all of its hard subproblems are already solved.

7.3 What this draft is claiming

The intended claim of this paper is modest but concrete. We claim that *skill evolution for blind vulnerability analysis* is a distinct and under-explored research direction; that a complete run-to-skill lifecycle can already be prototyped and studied in a realistic firmware setting; and that early evidence is sufficient to justify treating candidate evaluation and publication as first-class research problems. We do not claim that the present system has solved skill evolution or autonomous vulnerability discovery.

8 Research Agenda

We view three follow-up directions as central.

Candidate evaluation. The next step is to determine whether a candidate skill merely preserves performance or actually improves later runs under controlled comparisons.

Publication policy. Future versions of the framework should move beyond replay-only gates toward stronger counterfactual or retention-aware publication policies.

Discovery-oriented evaluation. The benchmark should broaden from current firmware and confirmed-vulnerability settings toward more open-ended discovery tasks, while preserving leakage control and external confirmation.

9 Related Work

9.1 Skill libraries, induction, and accumulation

Voyager [?], ExpeL [?], Reflexion-style trajectory reuse, and SkillClaw [?] together establish the broader context in which LLM agents accumulate reusable procedural knowledge over time. Ctx2Skill [?] and OPID [?] show that skills can be induced from context or distilled from richer policies. These works motivate the present paper’s starting assumption: skill is a reasonable substrate for making agent behavior persistent across tasks.

9.2 Verifier- and environment-grounded skill refinement

Recent work increasingly grounds skill refinement in environment evidence or external verification rather than in unconstrained self-reflection alone. SPARK [?] emphasizes evidence-backed refinement, Trace2Skill [?] studies trajectory-to-skill conversion with verifier support, VeriSkill [?] specializes this idea to program-verification tasks, and SkillEvolBench [?] turns episodic-to-procedural evolution into an explicit evaluation problem. Our work is aligned with this trend, but shifts the focus to a security-specific question: how a blind vulnerability-analysis run should be archived, confirmed, and filtered before it can shape a live skill library.

9.3 Skill failure, attribution, and governance

Skill-induced failure is now a recognized problem. Skill Harmful [?] shows that apparently relevant skills can degrade performance by steering the model toward the wrong procedure. Misevolution [?] highlights that repeated self-improvement can preserve poor or unsafe behaviors as persistent skills. This line of work is directly relevant to our setting, because vulnerability analysis is unusually sensitive to wrong-but-plausible paths: a candidate skill can look useful while systematically biasing the model toward a nearby dangerous decoy. The present paper therefore treats publication control as a first-class research problem rather than as a simple engineering afterthought.

9.4 Security agents, playbooks, and realistic benchmarks

On the security side, PentestGPT [?], empirical studies of LLM-based vulnerability analysis [?], EvoHunt [?], and SEC-bench Pro [?] address different parts of the security-agent landscape: interactive offensive workflows, vulnerability reasoning, playbook evolution, and realistic long-horizon evaluation. Our paper sits closest to the intersection of these threads. Like EvoHunt, we care about reusable procedural knowledge in security workflows. Like SEC-bench Pro, we care about evaluation realism and leakage control. The difference is that we center the run-to-library transition itself: blind execution, external confirmation, candidate staging, and live-skill admission are the primary objects of study.

10 Threats to Validity

Sample scale. The current experiments are larger and cleaner than earlier development-time studies, but they are still modest in scale compared with mature security benchmarks. Our claims are therefore directional rather than universal.

Single primary model family. The main runs were conducted under a fixed upstream model configuration. Skill effects may look different under models with different priors, tool-use habits, or instruction following behavior.

Static-analysis-heavy evaluation. Much of the current firmware evidence comes from blind static reasoning rather than from fully executable live exploitation. This is sufficient for studying target selection, but weaker than a broader dynamic validation setting.

Attribution precision. The present gate and feedback signals can constrain what should not become a live skill, but they do not yet provide a full causal decomposition of why a run succeeded.

Benchmark scope. The current paper still draws primarily from confirmed-vulnerability and controlled family settings. Open-ended unknown-vulnerability discovery remains a future step.

11 Conclusion

This paper argues that skill evolution for blind vulnerability analysis deserves to be studied as a problem in its own right. Vulnerability-analysis agents appear to need skills because their work repeatedly follows structured procedures; static skills are not enough because the value of a skill depends on target family, task structure, and failure mode; and evolving skills introduces new questions about evidence, attribution, and publication.

Our current prototype does not solve the full problem. It does, however, make the path concrete enough to study. We provide a first lifecycle that connects blind execution, external confirmation, run archival, candidate generation, and publication control; and we provide preliminary evidence that skill usage materially changes vulnerability localization while leaving candidate evaluation as the main unresolved bottleneck.

We therefore present this draft as an early research claim: the combination of agent-based vulnerability analysis and skill evolution is both under-explored and promising, and it merits a dedicated line of follow-up work.

References

- [] Gelei Deng, Yi Liu, Victor Mayoral-Vilches, Peter Desmet, Pinjia Liu, Rui Pang, Yaowen Su, Tianwei Zhang, Stjepan Picek, and Carl Tripp. Pentestgpt: An llm-empowered automatic penetration testing tool, 2023. URL <https://arxiv.org/abs/2308.06782>.
- [] Gen Dong, Yanjie Gao, Liqun Li, Tianyin Xu, Yu Hua, and Fan Yang. Agent skills can be harmful: An empirical study of skill-induced failures in llm agents, 2026. URL <https://arxiv.org/abs/2608.11888>.
- [] Changguo Jia, Tianqi Zhao, Zhiyou Xiao, Weiming Zhang, and Minghui Zhou. Veriskill: A self-evolution framework for program verification skills, 2026. URL <https://arxiv.org/abs/2607.27733>.
- [] Hwiwon Lee, Jiawei Liu, Dongjun Kim, Wubing Xia, Ziqi Zhang, Chunqiu Steven Xia, and Lingming Zhang. Sec-bench pro: Can language models solve long-horizon software security tasks?, 2026. URL <https://arxiv.org/abs/2605.26548>.
- [] Yingtie Lei, Zhongwei Wan, Jiankun Zhang, Samiul Alam, Zixuan Zhong, Peizhou Huang, Xin Wang, Jingxuan Zhang, Donghao Zhou, Yunta Hsieh, Zhihao Dou, Hui Shen, Yan Xu, Dimitrios Dimitriadis, Tuo Zhang, and Mi Zhang. Skillevolbench: Benchmarking the evolution from episodic experience to procedural skills, 2026. URL <https://arxiv.org/abs/2605.24117>.
- [] Binglin Liu, Pavel Gurevich, Leigh Hext, Christina Rister, Carlos Castillo, Chia-Che Tsai, and Hao Sun. Transferable self-evolving playbooks for agentic security auditing, 2026. URL <https://arxiv.org/abs/2606.16420>.
- [] Ziyu Ma, Shidong Yang, Yuxiang Ji, Xucong Wang, Yong Wang, Yiming Hu, Tongwen Huang, and Xiangxiang Chu. Skillclaw: Let skills evolve collectively with agentic evolver. *arXiv preprint arXiv:2604.08377*, 2026. URL <https://arxiv.org/abs/2604.08377>.
- [] Xutao Mao, Liangjie Zhao, Xiang Zheng, and Cong Wang. Practice makes unsafe: Skill misevolution in self-improving llm agents, 2026. URL <https://arxiv.org/abs/2608.12851>.
- [] Jingwei Ni, Yihao Liu, Xinpeng Liu, Yutao Sun, Mengyu Zhou, Pengyu Cheng, Dexin Wang, Erchao Zhao, Xiaoxi Jiang, and Guanjuan Jiang. Trace2skill: Distill trajectory-local lessons into transferable agent skills, 2026. URL <https://arxiv.org/abs/2603.25158>.

- Shuzheng Si, Haozhe Zhao, Yu Lei, Qingyi Wang, Dingwei Chen, Zhitong Wang, Zhenhailong Wang, Kangyang Luo, Zheng Wang, Gang Chen, Fanchao Qi, Minjia Zhang, and Maosong Sun. From context to skills: Can language models learn from context skillfully?, 2026. URL <https://arxiv.org/abs/2604.27660>.
- Benjamin Steenhoeck, Md Mahbubur Rahman, Monoshi Kumar Roy, Mirza Sanjida Alam, Hengbo Tong, Swarna Das, Earl T. Barr, and Wei Le. To err is machine: Vulnerability detection challenges llm reasoning, 2024. URL <https://arxiv.org/abs/2403.17218>.
- Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, and Linxi An. Voyager: An open-ended embodied agent with large language models, 2023. URL <https://arxiv.org/abs/2305.16291>.
- Shuo Yang, Jinyang Wu, Zhengxi Lu, Yuhao Shen, Fan Zhang, Lang Feng, Shuai Zhang, Haoran Luo, Zheng Lian, Zhengqi Wen, and Jianhua Tao. Opid: On-policy skill distillation for agentic reinforcement learning, 2026. URL <https://arxiv.org/abs/2606.26790>.
- Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. Expel: Llm agents are experiential learners, 2023. URL <https://arxiv.org/abs/2308.10144>.
- Yang Zhou, Zihan Dong, Zhenting Wang, Can Jin, Shiyu Zhao, Bangwei Guo, Difei Gu, Linjun Zhang, Mu Zhou, and Dimitris N. Metaxas. Evidence over plans: Online trajectory verification for skill distillation, 2026. URL <https://arxiv.org/abs/2605.09192>.