

Argonaut | OBS testing

Clean capture, audio and existing recording

About version and full Build value

OS / architecture / OBS version / display scale

C64U firmware / API / PAL or NTSC (no passwords)

Check only after passing. Leave failures unchecked and describe them on page 2.

- ☐ Start preview with audio; confirm both picture and sound.
- ☐ Open capture window; confirm only the C64 image and black bars.
In OBS, exclude cursor and window decorations or crop them if needed.
- ☐ Resize with integer scaling on and off; no stretching or clipped image.
Check normal and fractional desktop scaling where available.
- ☐ Record a short OBS clip with C64 audio, microphone and webcam.
Replay it: check picture, each audio source, echo and duplicate audio.
- ☐ Record simultaneously in OBS and Argonaut; replay both files.
Argonaut WebM should contain C64 video/audio, not the OBS mic or webcam mix.
- ☐ Close/reopen the capture window and change tabs while recording.
Preview and recording should continue; no second network stream should start.
- ☐ Stop recording; verify saved-file message and playable WebM.
Test video-only recording and save a PNG screenshot as regression checks.
- ☐ Try an existing recording filename; Cancel must preserve the original.
Use a disposable test file for Replace; replacement occurs after finalization.
- ☐ Copy diagnostics; check counters and absence of secrets.
Network addresses must be hidden unless explicitly enabled.
- ☐ Quit during recording; UI remains responsive until cleanup finishes.
Restart Argonaut and replay the finalized file. Report any wait or damaged file.

Argonaut | OBS testing

Sync measurements and conditional interruption checks

Agree before replacing the running C64 program or interrupting its network.

Use an agreed repeated flash/click source for the longer synchronization test.

Proposed target: absolute offset ≤ 80 ms; start-to-end drift ≤ 40 ms.

Test source / duration / OBS sync adjustment (if any)

OBS offset at start / midpoint / 30 minutes (ms)

Argonaut WebM offset at start / midpoint / 30 minutes (ms)

☐ Both recordings meet the measured sync targets.

Record the sign convention used. Nominal-clock unit tests are not hardware proof.

☐ If agreed: unplug/reconnect Ethernet and inspect both views/files.

Stale video blanks; status explains the stop; no automatic recording restart.

☐ If agreed: repeat after changing video mode.

Current recording should stop clearly on a mode change; test a new recording.

Failures, skipped checks, capture-source names and other observations

Save a copy of this form and reopen it to verify your entries were retained.