

# Rajalakshmi Engineering College

Name: MRIDHULA DEVI M  
Email: 240701337@rajalakshmi.edu.in  
Roll no: 240701337  
Phone: 9840329629  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 7\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

##### ***Input Format***

The first line contains two integers,  $n$  and  $table\_size$  — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers – the roll numbers to insert.

The third line contains an integer q – the number of queries.

The fourth line contains q space-separated integers – the roll numbers to search for.

### **Output Format**

The output print q lines – for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5 10  
21 31 41 51 61  
3  
31 60 51

Output: Value 31: Found  
Value 60: Not Found  
Value 51: Found

### **Answer**

```
#include <stdio.h>

#define MAX 100

// You are using GCC
void initializeTable(int table[], int size) {
    //Type your code here
    for(int i=0;i<size;i++){
        table[i]=-1;
    }
}

int linearProbe(int table[], int size, int num) {
    //Type your code here
```

```

    int index=num%size;
    while(table[index]!=-1){
        index=(index+1)%size;
    }
    return index;
}

```

```

void insertIntoHashTable(int table[], int size, int arr[], int n) {
    //Type your code here
    for(int i=0;i<n;i++){
        int index=linearProbe(table,size,arr[i]);
        table[index]=arr[i];
    }
}

```

```

int searchInHashTable(int table[], int size, int num) {
    //Type your code here
    int index=num%size;
    int start=index;
    while(table[index]!=-1){
        if(table[index]==num){
            return 1;
        }
        index=(index+1)%size;
        if(index==start){
            break;
        }
    }
    return 0;
}

```

```

int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);

    int arr[MAX], table[MAX];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    initializeTable(table, table_size);
    insertIntoHashTable(table, table_size, arr, n);

    int q, x;
}

```

```
scanf("%d", &q);
for (int i = 0; i < q; i++) {
    scanf("%d", &x);
    if (searchInHashTable(table, table_size, x))
        printf("Value %d: Found\n", x);
    else
        printf("Value %d: Not Found\n", x);
}

return 0;
}
```

**Status :** Correct

**Marks :** 10/10