

# **Rajalakshmi Engineering College**

Name: MRIDHULA DEVI M  
Email: 240701337@rajalakshmi.edu.in  
Roll no:  
Phone: 9840329629  
Branch: REC  
Department: CSE - Section 8  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## **2024\_28\_III\_OOPS Using Java Lab**

### **2028\_REC\_OOPS using Java\_Week 6\_Q4**

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### **Section 1 : Coding**

##### **1. Problem Statement**

Mr.Kapoor wants to create a program to calculate the volume of a Cuboid and a Cube using method overriding.

Implements a base class Cuboid with attributes for length, width, and height. Include a method calculateVolume() that computes the volume of the cuboid.

Extends the base class with a subclass Cube representing a cube, where all sides are equal. Override the calculateVolume() method in the Cube class to compute the volume of the cube.

The program should take user input for the dimensions of the cuboid and the side length of the cube and display the calculated volumes with two decimal places.

### ***Input Format***

The first line of input consists of 3 space-separated double values, representing the cuboid length, width, and height, respectively.

The second line consists of a double value, representing the side length of the cube.

### ***Output Format***

The first line of output prints the volume of the cuboid, rounded off to two decimal places.

The second line prints the volume of the cube, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 60.0 60.0 60.0  
50.0

Output: Volume of Cuboid: 216000.00  
Volume of Cube: 125000.00

### ***Answer***

```
import java.util.Scanner;  
  
// You are using Java  
//import java.util.Scanner;
```

```
class Cuboid {  
    protected double length;  
    protected double width;  
    protected double height;  
  
    public Cuboid(double length, double width, double height) {  
        this.length = length;  
        this.width = width;  
        this.height = height;  
    }  
}
```

```

    public double calculateVolume() {
        return length * width * height;
    }
}

class Cube extends Cuboid {
    public Cube(double side) {
        super(side, side, side);
    }

    @Override
    public double calculateVolume() {
        // Because for a cube, all sides are the same
        return length * length * length;
        // Or: Math.pow(length, 3)
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double cuboidLength = scanner.nextDouble();
        double cuboidWidth = scanner.nextDouble();
        double cuboidHeight = scanner.nextDouble();

        // Regular object instantiation for Cuboid
        Cuboid cuboid = new Cuboid(cuboidLength, cuboidWidth, cuboidHeight);
        System.out.printf("Volume of Cuboid: %.2f\n", cuboid.calculateVolume());

        double cubeSide = scanner.nextDouble();

        // Upcasting - Using superclass reference for subclass object (DMD)
        Cuboid cube = new Cube(cubeSide); // Upcasting
        System.out.printf("Volume of Cube: %.2f", cube.calculateVolume()); // Calls
        Cube's method dynamically

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10