

IE630: Simulation Modelling & Analysis

Output Analysis – Steady State Systems

Saurabh Jain

Assistant Professor

Department of Industrial Engineering and Operations Research

IIT Bombay



IIT

BOMBAY

Department of Industrial Engineering and Operations Research



Quick Recap



IIT
BOMBAY

Department of Industrial Engineering and Operations Research



Topics of Discussion

- Obtain a CI for a steady-state mean, $\nu = E(Y)$, of the output process Y_1, Y_2, \dots
- On the other hand, $E(Y_2) \neq \nu$ for “small” i because of the initial condition

Topics to be covered:

- Determining and eliminating the initial warm-up bias
- Obtaining sample observations in this case
- Determining run length
 - Theoretically Infinite, but practical number?



Introduction

Things to check

- Starting and stopping is essence of model
- Interested in the long-run characteristics of the system

Let Y_1, Y_2, \dots be the output



single run of the non-terminating simulation


Issues.....

- The problem of initial start-up due to arbitrary initial conditions
- Eliminate warm-up bias
- Obtaining sample observations to build CIs - Need to choose, IID data points, which are “representative” of the “steady-state behavior”
- Determining run-length - Theoretically infinite, but practically how long?



How to compute Warm-up Period?

- System starts from empty and idle



- Run simulation model with a 'warm-up' period and remove data collected during warm-up, and use only remaining data
- Set initial conditions such that model starts in realistic / steady state conditions
- Set partial initial condition, then warm-up the model, and remove the warm-up data
- Run model for long time, making the bias effect negligible



How to compute Warm-up Period?

- **Methods:**

- Visually inspect the performance and choose warm-up period based on your judgement
- Time series inspection
- Ensemble methods
- Welch's moving average method
- Autocorrelation estimators
- Marginal Error rule
- Neural Networks
-
- Statistical Tests
- Goodness-of-Fit Test
- Kalman Filters
-



Welch moving average method



Welch moving average method

- Conduct n replications ($n \geq 5$) of simulation, each of length m
 - $Y_{ji} \rightarrow i^{\text{th}}$ observation from j^{th} replication ($j=1 \dots n$; $i=1 \dots m$).
- Compute the averaged process
- Compute ensemble moving averages, $\bar{Y}_i(w)$
 - For i -th datapoint, construct moving average centered at i with w values on either side.
- Choose T_0 to be value of i beyond which ensemble averages seems to have converged



Welch moving average method... TIPS

- Initially, make $n = 5$ replications;
 - m should as large as possible (larger than anticipated T_0 , allows infrequent events to occur)
- Plot $\bar{Y}_i(w)$ for several different values of w .
 - Choose the smallest value of w for which the corresponding plot is “reasonably smooth”. Use this plot to determine the length of the warm up period, T_0 .
- If no value of w is satisfactory, make 5 more replications of length m . Repeat step 2 using all available data.



Examples



IIT
BOMBAY

Department of Industrial Engineering and Operations Research



MSER Heuristic

- Collect 1 replication of the finite stochastic output data
- Compute the Truncated Mean

$$\bar{Y}_{n,d} = \frac{1}{n-d} \sum_{j=d+1}^n Y_j, \quad \forall d = 1..n$$

- Compute optimal truncation point (Test Statistic)

$$d^* = \arg \min_{n \gg d \geq 0} \left[\frac{1}{(n-d)^2} \sum_{j=d+1}^n (Y_j - \bar{Y}_{n,d})^2 \right],$$

- Advantages
 - Does not require multiple replication data. Can obtain truncation point/warm-up period for each output data series.



MSER Heuristic

- Variants
 - Using batch average of size, say, $m \rightarrow \text{MSER-}m$
- Takeaways:
 - If the MSER test statistic is non-increasing, perform MSER with larger data set.
 - Reject d^* value if $(d^* > n/2) \rightarrow$ Indicates that transient period is long. Perform MSER again with ()
 - MSER can be performed for each replication!



Examples



IIT
BOMBAY

Department of Industrial Engineering and Operations Research




Issues

- Determining and eliminating the initial warm-up bias
- Obtaining sample observations in this case
 - Need to choose, (), which are () of the ()
- Determining run length
 - Theoretically Infinite, but practical number?




Obtaining Sample Observation

- There are two methods obtaining independent sample observations for non-terminating simulations:
- **Truncated replications** (multiple replications)
- **Interval batching methods** (batch mean techniques)



Truncated replications (multiple replications)

- Same with the terminating simulation case except:
- I (bias) must be determined and removed (Welch's method)
- An appropriate run length must be determined (will be explained soon)
- **Advantage**
 - It ensures that samples are independent
- **Disadvantage**
 - Running through the warm up phase for every replication
 - takes a lot of time
 - Throw away $n \cdot I$ amount of data, where I is warm up period



Truncated replications (multiple replications)


- Warm-up Period = 30 hours
- Execute simulation for $10 \times \text{Warm-up} = 10 \times 30 \text{ hrs} = 300 \text{ hours}$
- Number of replications =
- Average throughput for each replication =

60.8	59.42	60.93	58.51	59.48
59.8	59.16	58.71	58.64	60.96



Batch Means Technique

- Still need to run about 5 to figure out the warm up period
- Then, a super long run (only 1 replication) is made, and statistics are collected during different periods (batches) of time => Beyond the warm up period, the run is divided into non-overlapping intervals
- **Intervals**
 - Equal amount of time (time-based): work in process, number of parts in the queue
 - Equal number of observations (observation-based): time spent in the queue, throughput times



Batch Means Technique

- Obtain output data from a single long replication
 - Remove warmup period data
 - Collect at least 10 times the data as deleted.
- For batches from output data
 - Batch means will be correlated if batch size is small (recall we need uncorrelated data for CI)
 - Need to check auto-correlation of data at different lags
- Determine the run length,
 - That is, the number of batches!
- Construct CI
 - Observations \rightarrow batch means
 - $n \rightarrow$ number of batches



Batch Run Length Determination

- Given a batch run length, it is suggested to have at least 10 batches => so that the percentiles of the t-distribution will be relatively close to those of normal
- The size of batch to be at least 100 under most circumstances
- If a **trade-off** must be made between the **number of batch intervals** and the **batch run length**, it's better to have a few independent observations than to have several **autocorrelated observations**
- The **batch means method** is robust with respect to errors in determining the length of the warm up period
 - Because it is likely that only the first batch mean has significant bias (assuming the batch sizes are large)



Batch Run Length Determination

- Lag
- Distances apart from each other
- Correlogram (or autocorrelation plot) Plot of the correlation between points at various lags



Autocorrelation diagram

- Mathematical Representation of Correlogram

$$\rho = \sum_{i=1}^{n-j} \frac{(x_i - \bar{x})(x_{i+j} - \bar{x})}{\sigma^2(n-j)}$$

where j is the lag and σ is the standard deviation of the sample (approximated by “s”).



Summary

- **Terminating system**
 - $n \times m$ data \Rightarrow use only n data (last average column) to calculate a CI
- **Steady state system**
 - Determination of a warm-up period
 - Informal visualization (multiple replications)
 - Formal method: Welch's moving average method
 - Run length determination
 - Informal method:
 - length which includes most of events (even rare ones)
 - Formal method: correlogram
 - Given a warm up period and run length
 - Truncated method: same with terminating except removal of warm up for each replication
 - Batch means method: one lengthy replication, decomposed to n independent samples

