IE630: Simulation Modelling & Analysis Agent-based Modelling & Simulation

Saurabh Jain
Assistant Professor
Department of Industrial Engineering and Operations Research
IIT Bombay





Quick Recap





Introduction

 Four paradigms of simulation

Abstraction Levels?

Discrete Event
Agent-based
System Dynamics
Dynamical
Systems

High Abstraction Less Details Macro Level Strategic Level

Middle
Abstraction
Medium Details
Meso Level
Tactical Level

Low Abstraction
More Details
Micro Level
Operational
Level

Agent Based (AB)

· Active objects

Aggregates, Global Causal Dependencies, Feedback Dynamics, ...

- Individual behavior rules
- Direct or indirect interaction
- Environment models

System Dynamics (SD)

- Levels (aggregates)
- Stock-and-Flow diagrams
- Feedback loops

Dynamic Systems (DS)

- Physical state variables
- Block diagrams and/or algebraic-differential equations

Mainly discrete ◆ ! → Mainly continuous

Individual objects, exact sizes, distances, velocities, timings, ...





"Discrete

Event" (DE)

· Flowcharts and/or

Entities (passive

objects)

transport networks

Resources

Agent-based Modelling

- Properties of the objects
 - Pro-activeness, ability to learn, mobility, cooperation etc.
 - Decentralized decision making
- Bottom up Modelling
- There is no place where global behaviour of the system is defined
 - () => Global Behaviour
- Object oriented based: class, instances, object encapsulation
- Components:
 - A collection of agents and their states
 - Rules governing the interactions of the agents
 - Environment within which they live





Agent-based Modelling

Agent Behaviour

Simulation Environment

AGENT


Properties

Current State Preferences Goals

Actions

Tasks Responses

Population reflective of heterogeneity identified in real population






BOMBAY



Agent-based Modelling

- Agent-behavior: UML state chart
- Environment: Housing, jobs, transport infrastructure
- Agent: Direct interaction with agent; indirect interaction with agent via environment








What is an Agent?

There is no universal agreement on the precise definition of the term "agent" in the context of ABMS.

Properties:


- Encapsulated
 - Clearly identifiable, with well-defined boundaries and interfaces
- Situated in a particular environment
 - Receives input through sensors and acts through effectors
- Capable of flexible action
 - Responds to changes and acts in anticipation
- Autonomous
 - Has control both over its internal state and over own behavior, reacts to environmental change and proactively changes its behavior
- Designed to meet objectives
 - Attempts to fulfill a purpose, solve a problem, or achieve goals






Agent Interactions

 An underlying topology of connectedness defines how and with whom the agent interacts



 Depending on the environment, agent interacts with a subset of other agents.


 Typically, an agent interacts with its neighbors









Agent Environment









(b) Cellular Automata (von Neumann)



(c) Euclidean Space (2-D)







BOMBAY



Correspondence between DE and AB models

 It only makes sense to do this in case we wish to model some extra individual behaviour later on that is hard to capture in DE style

 Alternative 1: Use of dispatcher (environment model): indirect communication between agents, e.g. queueing Resource
Delay
Exit

Resource granted
In Service
Finished
Release Resource
Play
Release Resource
Play
Release Resource
Play
Release Resource
Delay Time
Delay Time
Delete this agent

Alternative 2: agents may see each other and communicate directly to manage resource




access



Multi-Paradigm Hybrid Modelling & Simulation

- Supply Chain
 - Intra supply member process are SD
 - Communication between members are AB
- Hospital
 - Agents interact with other agents in a DE flowchart
 - Like Dispatcher: Overall interaction is somewhat "centralized";







Software

| Platform | Scalability | Execution Speed | Programming Language | Primary Domain | Web site |
|----------|----------------------|--------------------|-------------------------|--|---|
| NetLogo | desktop computing | intermediate | NetLogo | social and natural sciences | www.ccl.northwestern.ed u/netlogo/ |
| MASON | large-scale | fast | Java | social complexity, physical modeling, AI/machine learning | www.cs.gmu.edu/~eclab/ projects/mason/ |
| Swarm | large-scale | slow | Objective-C; Java | general purpose | http://alumni.media.mit.e du/~nelson/research/swar m/ |
| Repast | large-scale | fast | Java; Python; C++ | social sciences | http://repast.sourceforge.n et/ |
| Ascape | large-scale | fast | Java | general purpose | http://ascape.sourceforge. net |
| AnyLogic | large-scale | fast | Java | general purpose, distributed simulation | www.anylogic.com |



BOMBAY

