🏢 Enterprise-Level MCQs (Highly Detailed Scenarios)

🔹 Case 1: Financial Reconciliation Engine (Python Basics)

A multinational bank runs a nightly batch reconciliation system that processes millions of transactions from different countries. During testing, the system crashes intermittently.

A code snippet used in fee calculation:

```
invoice_amount = "7500"

processing_fee = 250.75

total_amount = invoice_amount + processing_fee
```

This error is not caught during compilation but causes failure at runtime in production.

Q1. What is the most likely root cause of this failure?

Answer: B. Type mismatch between string and numeric values causing runtime error

A. Floating point rounding issue due to currency conversion

B. Type mismatch between string and numeric values causing runtime error

C. Incorrect operator precedence in arithmetic operation

D. Memory overflow due to large transaction volume

🔹 Case 2: Telecom Data Deduplication Pipeline (Data Types)

A telecom company ingests real-time customer data streams from multiple vendors. Due to integration issues, duplicate phone numbers frequently appear, causing incorrect billing and analytics.

Q2. Which data structure is most suitable for this requirement?

Answer: B. Set (ensures uniqueness and fast lookup)

A. List (allows dynamic storage)

B. Set (ensures uniqueness and fast lookup)

C. Tuple (immutable and memory efficient)

D. Dictionary (key-value mapping)

- Case 3: ETL Pipeline Resilience (Control Flow)

A retail analytics platform processes daily sales logs. Some records are corrupted due to upstream system failures.

Q3. Which control flow statement best satisfies this requirement?

Answer: B. continue (skips current iteration and proceeds)

A. break (terminates loop execution)

B. continue (skips current iteration and proceeds)

C. pass (does nothing but does not skip logic)

D. return (exits function entirely)

- Case 4: Fraud Detection System (Critical Stop)

A banking fraud detection system monitors transactions in real-time.

Q4. Which control statement is most appropriate?

Answer: B. break (terminate loop execution immediately)

A. continue (skip current transaction only)

B. break (terminate loop execution immediately)

C. pass (no operation)

D. return (exit entire program)

- Case 5: Microservices-Based Logistics Platform (Functions)

A logistics company uses a microservices architecture where pricing, routing, and delivery estimation are handled by separate services.

Q5. Why are functions critical in this architecture?

Answer: B. Promote modular, reusable, and maintainable code

A. Reduce server CPU usage

B. Promote modular, reusable, and maintainable code

C. Eliminate need for APIs

D. Automatically scale services

- Case 6: Streaming Data Transformation (Lambda)

A real-time analytics system processes streaming data where transformations must be lightweight and inline.

Q6. Which approach is most suitable?

Answer: B. lambda x: x*2

A. lambda x: return x*2

B. lambda x: x*2

C. def lambda(x): x*2

D. lambda(x): x*2

- Case 7: Cybersecurity Log Analyzer (Regex)

A cybersecurity firm analyzes logs to detect suspicious activities.

Q7. Which regex method is best suited?

Answer: B. findall() (returns all occurrences)

A. match() (checks only beginning of string)

B. findall() (returns all occurrences)

C. search() (returns first occurrence only)

D. replace() (modifies string)

- Case 8: Distributed Logging System (File Handling)

Logs must be preserved historically and appended without overwriting.

Q8. Which file mode should be used?

Answer: B. 'a' (appends to existing file)

A. 'w' (overwrites file)

B. 'a' (appends to existing file)

C. 'r' (read-only mode)

D. 'x' (creates new file only)

- Case 9: Payment Gateway Stability (Exception Handling)

A payment gateway processes thousands of transactions per second.

Q9. What is the best approach?

Answer: B. Use try-except blocks to handle errors gracefully

A. Ignore invalid inputs

B. Use try-except blocks to handle errors gracefully

C. Log errors without handling

D. Restart service on failure

- Case 10: Banking Domain Error Handling (Custom Exception)

A banking application defines a custom exception InsufficientFundsException.

Q10. Why is this approach used?

Answer: B. Handle domain-specific business rules clearly

A. Improve performance

B. Handle domain-specific business rules clearly

C. Replace built-in exceptions

D. Reduce memory usage

- Case 11: Healthcare Management System (OOP)

A hospital system manages patients, doctors, and appointments using Python classes.

Q11. Why is OOP preferred here?

Answer: B. Enables abstraction and encapsulation of real-world entities

A. Reduces syntax complexity

B. Enables abstraction and encapsulation of real-world entities

C. Improves UI rendering

D. Eliminates need for databases

- Case 12: Shared Configuration Across Services

A system requires a common configuration (e.g., tax rate) to be shared across all objects.

Q12. Which variable type should be used?

Answer: B. Class variable

A. Instance variable

B. Class variable

C. Local variable

D. Temporary variable

- Case 13: Payment Gateway Expansion (Polymorphism)

A payment gateway supports Credit Card, UPI, and Wallet.

Q13. Which concept is applied?

Answer: B. Polymorphism

A. Inheritance

B. Polymorphism

C. Encapsulation

D. Aggregation

- Case 14: Dynamic Behavior in Subclasses

Each payment method modifies the same method implementation.

Q14. What is this concept?

Answer: B. Method overriding

A. Method overloading

B. Method overriding

C. Composition

D. Encapsulation

- Case 15: Client Communication (Power Skills)

A consultant sends a project status email to stakeholders including executives.

Q15. What is the best practice?

Answer: B. Clear, structured, and professional communication

A. Informal messaging style

B. Clear, structured, and professional communication

C. Long unstructured paragraphs

D. No subject line

- Case 16: Client Onboarding Meeting

During the first meeting with a new client, expectations must be aligned.

Q16. What should be done first?

Answer: B. Ice breaking and objective alignment

A. Technical deep dive

B. Ice breaking and objective alignment

C. Immediate solution presentation

D. Code demonstration

- Case 17: Hierarchical Data Processing (Recursion)

A system processes hierarchical organizational data.

Q17. What is mandatory for recursion to work correctly?

Answer: B. Base condition to stop recursion

A. Loop structure

B. Base condition to stop recursion

C. Global variables

D. Exception handling

- Case 18: Data Conversion Pipeline

User input from a web form is received as string but needs numerical processing.

Q18. What is the correct approach?

Answer: B. Use float() for conversion

A. Use str()

B. Use float() for conversion

C. Use eval()

D. Use input() again

- Case 19: Configuration Storage Optimization

A system stores configuration values that must remain ordered and immutable.

Q19. Which structure is most suitable?

Answer: B. Tuple

A. List

B. Tuple

C. Set

D. Dictionary

- Case 20: Production Script Execution

A Python script is deployed in production.

Q20. What is the correct practice?

Answer: B. Use if __name__ == '__main__': guard

A. Use global variables

B. Use if __name__ == "__main__": guard

C. Use print statements

D. Avoid functions