

Introduction

Welcome to **YShared**! This is a basic example page demonstrating the various Markdown features supported by the documentation.

Headings

Markdown supports multiple heading levels:

Heading 1

Heading 2

Heading 3

Heading 4

Heading 5

Heading 6

Text Formatting

You can use **bold text**, *italic text*, and ***bold italic text***.

You can also use ~~strikethrough text~~.

You can highlight `inline code` using backticks.

You can combine formatting, such as **bold with inline code**.

Links

You can create links to other pages:


[Getting Started](#)

You can also link to external websites:

[Unity](#)↗

Images

Images can be embedded using:



You can also add alternative text describing the image.

Lists

Unordered List

- Item one
- Item two
- Item three
 - Nested item
 - Another nested item
 - Even deeper

Ordered List

1. First item
2. Second item
3. Third item
 1. Nested item
 2. Another nested item

Task List

- [x] Completed task
 - [] Incomplete task
 - [] Another task
-

Blockquotes

This is a blockquote.

It can span multiple lines.

Blockquotes can also be nested.

Code

Inline code:

```
Debug.Log("Hello World");
```

C# Code Block

```
using UnityEngine;

public class Example : MonoBehaviour
{
    private void Start()
    {
        Debug.Log("Hello World!");
    }
}
```

Although....

Namespace YShared.Console

Classes

[AliasAttribute](#)

Define an alias / shortcut for the command. You may also optionally provide arguments.

- Shorthand - Shorthand for the command. (ie, Shortcut: "gm", for the command "gamemode")
- Arguments - If provided, the shortcut will be ran with those arguments. (ie, Shorthand: "gmc" and Arguments: "creative" to run "gamemode creative")

[AliasData](#)

[Autocomplete](#)

[Command](#)

[CommandNode](#)

[CommandRegistry](#)

[CommandsHelper](#)

[Console](#)

[DefaultCommands](#)

[DevConsole](#)

[DevConsoleException](#)

[DevConsoleUI](#)

[ScreenshotClipboard](#)

[YCBool](#)

Use `YCBool` for boolean arguments.

[YCCmdArg](#)

Use `YCCmdArg` to get registered commands as an input. (Use `Command[]`)

[YCEnum](#)

Use `YCEnum(typeof(Enum))` for enum arguments.

[YCFloat](#)

Use `YCFloat(min, max)` for float arguments. (min / max optional)

[YCInt](#)

Use `YCInt(min, max)` for integer arguments. (min / max optional)

[YCString](#)

Use `YCString` for string arguments.

[YCmdArgumentAttribute](#)

[YCommandAttribute](#)

Define a new command.

- Use `YCInt(min, max)` for integer arguments. (min / max optional)
- Use `YCFloat(min, max)` for float arguments. (min / max optional)
- Use `YCEnum(sizeof(Enum))` for enum arguments.
- Use `YCBool` for boolean arguments.
- Use `YCString` for string arguments.
- Use `YCCmdArg` to get registered commands as an input. (Use `Command[]`)

Structs

[MethodSignature](#)

[Parameter](#)

Enums

[FeedbackFlavor](#)

[ObjectFindType](#)