

Namespace YShared.Console

Classes

[AliasAttribute](#)

Define an alias / shortcut for the command. You may also optionally provide arguments.

- Shorthand - Shorthand for the command. (ie, Shortcut: "gm", for the command "gamemode")
- Arguments - If provided, the shortcut will be ran with those arguments. (ie, Shorthand: "gmc" and Arguments: "creative" to run "gamemode creative")

[AliasData](#)

[Autocomplete](#)

[Command](#)

[CommandNode](#)

[CommandRegistry](#)

[CommandsHelper](#)

[Console](#)

[DefaultCommands](#)

[DevConsole](#)

[DevConsoleException](#)

[DevConsoleUI](#)

[ScreenshotClipboard](#)

[YArgumentAttribute](#)

[YAutocompleteListAttribute](#)

[YCBool](#)

Use `YCBool` for boolean arguments.

[YCCmdArg](#)

Use `YCCmdArg` to get registered commands as an input. (Use `Command[]`)

[YCEnum](#)

Use `YCEnum(typeof(Enum))` for enum arguments.

[YCFloat](#)

Use `YCFloat(min, max)` for float arguments. (min / max optional)

[YCInt](#)

Use `YCInt(min, max)` for integer arguments. (min / max optional)

[YCString](#)

Use `YCString` for string arguments.

[YCmdParser](#)

[YCmdParser<T>](#)

[YCommandAttribute](#)

Define a new command.

- Use `YCInt(min, max)` for integer arguments. (min / max optional)
- Use `YCFloat(min, max)` for float arguments. (min / max optional)
- Use `YCEnum(typeof(Enum))` for enum arguments.
- Use `YCBool` for boolean arguments.
- Use `YCString` for string arguments.
- Use `YCCmdArg` to get registered commands as an input. (Use `Command[]`)

[YDynamicAutocompleteAttribute](#)

[YRangeAttribute](#)

[YToggleAttribute](#)

Structs

[MethodSignature](#)

[Parameter](#)

Enums

[FeedbackFlavor](#)

[FieldValueCommandType](#)

[ObjectFindType](#)

Class AliasAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Define an alias / shortcut for the command. You may also optionally provide arguments.

- Shorthand - Shorthand for the command. (ie, Shortcut: "gm", for the command "gamemode")
- Arguments - If provided, the shortcut will be ran with those arguments. (ie, Shorthand: "gmc" and Arguments: "creative" to run "gamemode creative")

```
[AttributeUsage(AttributeTargets.Method)]  
public class AliasAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← AliasAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,

[Attribute.TypeId](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

AliasAttribute(string, string)

```
public AliasAttribute(string Shorthand, string Arguments = "")
```

Parameters

Shorthand [string](#)

Arguments [string](#)

Properties

Arguments

```
public string Arguments { get; }
```

Property Value

[string](#)

Shorthand

```
public string Shorthand { get; }
```

Property Value

[string](#)

Class AliasData

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public class AliasData
```

Inheritance

[object](#)  ← AliasData

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

AliasData(AliasAttribute)

```
public AliasData(AliasAttribute attr)
```

Parameters

attr [AliasAttribute](#)

Fields

Alias

```
public string Alias
```

Field Value

[string](#) 

Command

`public string` Command

Field Value

[string](#)

Class Autocomplete

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class Autocomplete
```

Inheritance

[object](#)  ← Autocomplete

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Fields

RootCommandArray

```
public static string[] RootCommandArray
```

Field Value

[string](#)  []

Methods

AddToAutocompleteList(Command, int, ref List<string>)

```
public static void AddToAutocompleteList(Command cmd, int word_at, ref List<string> list)
```

Parameters

cmd [Command](#)

word_at [int](#) 

list [List](#) <[string](#)>

CommandAsAnArgumentAutocompleteArray()

```
public static string[] CommandAsAnArgumentAutocompleteArray()
```

Returns

[string](#)[]

GetAutocompleteList(string)

```
public static string[] GetAutocompleteList(string line)
```

Parameters

line [string](#)

Returns

[string](#)[]

Class Command

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public sealed class Command
```

Inheritance

[object](#)  ← Command

Inherited Members

[object.GetType\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#) , [CommandsHelper.GetHelpText\(Command, int\)](#)

Constructors

Command()

```
public Command()
```

Fields

ProperUsageWordAmount

```
public int ProperUsageWordAmount
```

Field Value

[int](#) 

action

```
public MemberInfo action
```

Field Value

[MemberInfo](#)

aliases

```
public Dictionary<string, AliasData> aliases
```

Field Value

[Dictionary](#) <[string](#), [AliasData](#)>

command

```
public string command
```

Field Value

[string](#)

description

```
public string description
```

Field Value

[string](#)

fieldValueCommandType

```
public FieldValueCommandType fieldValueCommandType
```

Field Value

[FieldValueCommandType](#)

findObjectsInactive

```
public FindObjectsInactive findObjectsInactive
```

Field Value

FindObjectsInactive

objectFindType

```
public ObjectFindType objectFindType
```

Field Value

[ObjectFindType](#)

parameters

```
public Parameter[] parameters
```

Field Value

[Parameter\[\]](#)

Properties

CommandWords

```
public string[] CommandWords { get; }
```

Property Value

[string](#)[↗][]

FormattedArguments

```
public string FormattedArguments { get; }
```

Property Value

[string](#)[↗]

IsStatic

```
public bool IsStatic { get; set; }
```

Property Value

[bool](#)[↗]

ProperUsage

```
public string ProperUsage { get; }
```

Property Value

[string](#)[↗]

hasReturnType

```
public bool hasReturnType { get; set; }
```

Property Value

[bool](#)

Methods

parser(int)

```
public YCmdParser parser(int ind)
```

Parameters

ind [int](#)

Returns

[YCmdParser](#)

Class CommandNode

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public class CommandNode
```

Inheritance

[object](#)  ← CommandNode

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

CommandNode()

```
public CommandNode()
```

Fields

children

```
public Dictionary<string, CommandNode> children
```

Field Value

[Dictionary](#)  <[string](#)  , [CommandNode](#)>

commands

```
public List<Command> commands
```

Field Value

[List](#) <[Command](#)>

Methods

Clear()

```
public void Clear()
```

Class CommandRegistry

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class CommandRegistry
```

Inheritance

[object](#)  ← CommandRegistry

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Fields

HighestDuplicateCommandAmt

```
public static int HighestDuplicateCommandAmt
```

Field Value

[int](#) 

HighestDuplicateCommandName

```
public static string HighestDuplicateCommandName
```

Field Value

[string](#) 

Root

```
public static readonly CommandNode Root
```

Field Value

[CommandNode](#)

alphabeticalCommands

The list of all top-level commands active, sorted alphabetically. Note that there may be duplicate entries because of commands with the same name but with different signatures.

```
public static Command[] alphabeticalCommands
```

Field Value

[Command\[\]](#)

parserRegistry

```
public static readonly Dictionary<Type, Type> parserRegistry
```

Field Value

[Dictionary](#) <[Type](#), [Type](#)>

Methods

CreateFieldCommand(FieldInfo, YCommandAttribute, FieldValueCommandType)

```
public static Command CreateFieldCommand(FieldInfo field, YCommandAttribute attribute, FieldValueCommandType fct)
```

Parameters

field [FieldInfo](#)

attribute [YCommandAttribute](#)

fct [FieldValueCommandType](#)

Returns

[Command](#)

CreateMethodCommand(MethodInfo, YCommandAttribute)

```
public static Command CreateMethodCommand(MethodInfo method, YCommandAttribute attribute)
```

Parameters

method [MethodInfo](#)

attribute [YCommandAttribute](#)

Returns

[Command](#)

GetCommands(string, out List<Command>)

```
public static bool GetCommands(string command_str, out List<Command> cmd)
```

Parameters

command_str [string](#)

cmd [List](#) <[Command](#)>

Returns

[bool](#)

GetRecursiveCommands(CommandNode, List<Command>)

Find all the commands under this CommandNode. Pass in `CommandsRegistry.Root` to find all commands.

```
public static void GetRecursiveCommands(CommandNode node, List<Command> commands)
```

Parameters

node [CommandNode](#)

Root node

commands [List](#) <[Command](#)>

Recursive Filled List

RegisterCommand(Command)

```
public static void RegisterCommand(Command cmd)
```

Parameters

cmd [Command](#)

Class CommandsHelper

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class CommandsHelper
```

Inheritance

[object](#)  ← CommandsHelper

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Methods

GetHelpText(Command, int)

```
public static string GetHelpText(this Command cmd, int padding = 0)
```

Parameters

cmd [Command](#)

padding [int](#) 

Returns

[string](#) 

PrintCommands(List<Command>, string)

```
public static string PrintCommands(List<Command> commands, string spaceAtStart = "")
```

Parameters

commands [List](#) <[Command](#)>

spaceAtStart [string](#)

Returns

[string](#)

SplitCommand(string)

```
public static string[] SplitCommand(string line)
```

Parameters

line [string](#)

Returns

[string](#)[]

Class Console

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public class Console : YSingleton<Console>
```

Inheritance

[object](#)  ← [YSingleton](#)<[Console](#)> ← Console

Inherited Members

[YSingleton<Console>.Awake\(\)](#), [YSingleton<Console>.OnDestroy\(\)](#), [YSingleton<Console>.Instance](#),
[YSingleton<Console>.CallDontDestroyOnLoad](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

Console()

```
public Console()
```

Fields

FPS_Limit

```
public int FPS_Limit
```

Field Value

[int](#) 

textStyle

```
public GUIStyle textStyle
```

Field Value

GUIStyle

Properties

instance

```
public static Console instance { get; }
```

Property Value

[Console](#)

Methods

OnGUI()

```
public void OnGUI()
```

Write(int, string, object)

```
public static void Write(int id, string _key, object _value)
```

Parameters

id [int](#)

_key [string](#)

_value [object](#)

Write(int, string, float, int)

```
public static void Write(int id, string _key, float _float_value, int decimals = 2)
```

Parameters

id [int](#)

_key [string](#)

_float_value [float](#)

decimals [int](#)

Write(int, string, Vector2, int)

```
public static void Write(int id, string _key, Vector2 _float_value, int decimals = 2)
```

Parameters

id [int](#)

_key [string](#)

_float_value Vector2

decimals [int](#)

Write(int, string, Vector3, int)

```
public static void Write(int id, string _key, Vector3 _float_value, int decimals = 2)
```

Parameters

id [int](#)

_key [string](#)

`_float_value` [Vector3](#)

`decimals` [int](#)

WriteFloat(int, string, float, int)

```
public static void WriteFloat(int id, string _key, float _float_value, int decimals = 2)
```

Parameters

`id` [int](#)

`_key` [string](#)

`_float_value` [float](#)

`decimals` [int](#)

Class DefaultCommands

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class DefaultCommands
```

Inheritance

[object](#)  ← DefaultCommands

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Class DevConsole

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class DevConsole
```

Inheritance

[object](#)  ← DevConsole

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Fields

CommandFeedback

```
public static Action<string, FeedbackFlavor> CommandFeedback
```

Field Value

[Action](#)  <[string](#) , [FeedbackFlavor](#)>

CommandLog

```
public static Action<string, FeedbackFlavor> CommandLog
```

Field Value

[Action](#)  <[string](#) , [FeedbackFlavor](#)>

Properties

commandAutocompleteLists

```
public static Dictionary<string, string[]> commandAutocompleteLists { get; }
```

Property Value

[Dictionary](#) <[string](#), [string](#)[]>

Methods

Execute(string)

```
public static bool Execute(string line)
```

Parameters

line [string](#)

Returns

[bool](#)

Feedback(object, FeedbackFlavor)

```
public static void Feedback(object text, FeedbackFlavor flavor = FeedbackFlavor.Feedback)
```

Parameters

text [object](#)

flavor [FeedbackFlavor](#)

Log(object, FeedbackFlavor)

```
public static void Log(object text, FeedbackFlavor flavor = FeedbackFlavor.Feedback)
```

Parameters

text [object](#)[↗]

flavor [FeedbackFlavor](#)

Class DevConsoleException

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public class DevConsoleException : Exception, ISerializable
```

Inheritance

[object](#) ← [Exception](#) ← DevConsoleException

Implements

[ISerializable](#)

Inherited Members

[Exception.GetBaseException\(\)](#), [Exception.GetObjectData\(SerializationInfo, StreamingContext\)](#), [Exception.ToString\(\)](#), [Exception.GetType\(\)](#), [Exception.TargetSite](#), [Exception.Message](#), [Exception.Data](#), [Exception.InnerException](#), [Exception.HelpLink](#), [Exception.Source](#), [Exception.HResult](#), [Exception.StackTrace](#), [Exception.SerializeObjectState](#), [object.MemberwiseClone\(\)](#), [object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.ReferenceEquals\(object, object\)](#), [object.GetHashCode\(\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

DevConsoleException(string)

```
public DevConsoleException(string message)
```

Parameters

message [string](#)

Class DevConsoleUI

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public class DevConsoleUI : YSingleton<DevConsoleUI>
```

Inheritance

[object](#)  ← [YSingleton](#)<[DevConsoleUI](#)> ← DevConsoleUI

Inherited Members

[YSingleton<DevConsoleUI>.Awake\(\)](#), [YSingleton<DevConsoleUI>.Instance](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

DevConsoleUI()

```
public DevConsoleUI()
```

Fields

ShowErrors

```
[YCommand]  
[YToggle]  
public bool ShowErrors
```

Field Value

[bool](#) 

ShowInfo

```
[YCommand]  
[YToggle]  
public bool ShowInfo
```

Field Value

[bool](#)

ShowWarnings

```
[YCommand]  
[YToggle]  
public bool ShowWarnings
```

Field Value

[bool](#)

Properties

CallDontDestroyOnLoad

```
public override bool CallDontDestroyOnLoad { get; }
```

Property Value

[bool](#)

IsOpen

```
public bool IsOpen { get; }
```

Property Value

[bool](#)

Methods

Clear()

[YCommand]

```
public static void Clear()
```

CreateAutocomplete()

```
public void CreateAutocomplete()
```

IsDownArrow()

```
public bool IsDownArrow()
```

Returns

[bool](#)

IsUpArrow()

```
public bool IsUpArrow()
```

Returns

[bool](#)

OnDestroy()

```
protected override void OnDestroy()
```

OnInputChanged(string)

```
public void OnInputChanged(string text)
```

Parameters

text [string](#)

SetAutocompleteList(string[])

```
public void SetAutocompleteList(string[] commands)
```

Parameters

commands [string](#) []

SetFontSize(int)

```
public void SetFontSize(int size)
```

Parameters

size [int](#)

SetFontSizeCmd(int)

```
[YCommand]
```

```
public static void SetFontSizeCmd(int val = 0)
```

Parameters

val [int](#)

Enum FeedbackFlavor

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public enum FeedbackFlavor
```

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

Command = 3

Blue color. Should generally not be used - it is the flavor of the submitted commands shown in the console history.

Error = 5

Red color. Should be used when a command fails entirely. Exceptions are automatically handled by the DevConsole and are shown in this flavor.

Feedback = 1

White color, and the default feedback flavor. Should be used when a command completes successfully, giving details on how the operation was handled.

Info = 0

Gray color. Should be used when a command simply gives back info without doing anything.

Misc = 6

Blue-ish color. Should generally not be used - it is the flavor of the introductory text.

Return = 2

Blue-ish color. Should generally not be used - it is the flavor of the return values shown in the console history.

Warning = 4

Yellow color. Should be used when a command completes with warnings.

Enum FieldValueCommandType

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public enum FieldValueCommandType
```

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

```
get = 0
```

```
set = 1
```

```
toggle = 2
```

```
toggleSet = 3
```

Struct MethodSignature

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public readonly struct MethodSignature : IEquatable<MethodSignature>
```

Implements

[IEquatable](#)  <[MethodSignature](#)>

Inherited Members

[ValueType.ToString\(\)](#) , [object.GetType\(\)](#) , [object.Equals\(object, object\)](#) ,
[object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

MethodSignature(string, Type[])

```
public MethodSignature(string name, Type[] parameterTypes)
```

Parameters

name [string](#) 

parameterTypes [Type](#)  []

Fields

Name

```
public readonly string Name
```

Field Value

[string](#)

ParameterTypes

```
public readonly Type[] ParameterTypes
```

Field Value

[Type](#) []

Methods

Create(MethodInfo)

```
public static MethodSignature Create(MethodInfo method)
```

Parameters

method [MethodInfo](#)

Returns

[MethodSignature](#)

Equals(object)

```
public override bool Equals(object obj)
```

Parameters

obj [object](#)

Returns

[bool](#)

Equals(MethodSignature)

```
public bool Equals(MethodSignature other)
```

Parameters

other [MethodSignature](#)

Returns

[bool](#)

GetHashCode()

```
public override int GetHashCode()
```

Returns

[int](#)

Enum ObjectFindType

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public enum ObjectFindType
```

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

All = 0

Finds all objects with this class and calls this method on all of them. Internally uses `GameObject.FindObjectsByType`.

Any = 1

Finds any object with this class and calls this method on it. Internally uses `GameObject.FindAnyByType`.

Argument = 3

The first argument of this command will be the instance to run this command on.

Note: You do not need to make the first argument of this method this class, but if you do it will be automatically filled in.

ArgumentArray = 4

The first argument of this command will be the array of instances to run this command on.

Note: You do not need to make the first argument of this method an array of this class, but if you do it will be automatically filled in.

First = 2

Finds the first object with this class and calls this method on it. Internally uses `GameObject.FindFirstByType`.

Struct Parameter

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public struct Parameter
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) , [object.GetType\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

Parser

```
public YCmdParser Parser
```

Field Value

[YCmdParser](#)

cacheAutocompleteList

```
public bool cacheAutocompleteList
```

Field Value

[bool](#)

defaultval

```
public object defaultval
```

Field Value

[object](#)

hasDefault

```
public bool hasDefault
```

Field Value

[bool](#)

suggestionModifiers

```
public SuggestionModifierAttribute[] suggestionModifiers
```

Field Value

[SuggestionModifierAttribute](#)[]

Methods

getAutocomplete()

```
public List<string> getAutocomplete()
```

Returns

[List](#) <[string](#)>

Class ScreenshotClipboard

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public static class ScreenshotClipboard
```

Inheritance

[object](#)  ← ScreenshotClipboard

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Methods

CopyScreenshot()

```
public static IEnumerable CopyScreenshot()
```

Returns

[IEnumerable](#) 

TakeScreenshot()

[YCommand]

```
public static void TakeScreenshot()
```

Class YArgumentAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = false)]  
public class YArgumentAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YArgumentAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YArgumentAttribute(string, string)

```
public YArgumentAttribute(string Name, string Description = "")
```

Parameters

Name [string](#)

Description [string](#)

Fields

Description

```
public string Description
```

Field Value

[string](#)

Name

```
public string Name
```

Field Value

[string](#)

Class YAutocompleteListAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = false)]  
public class YAutocompleteListAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YAutocompleteListAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YAutocompleteListAttribute(params string[])

```
public YAutocompleteListAttribute(params string[] autocompleteList)
```

Parameters

autocompleteList [string](#)[]

Fields

autocompleteList

```
public string[] autocompleteList
```

Field Value

[string](#)[]

Class YCBool

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use **YCBool** for boolean arguments.

```
public sealed class YCBool : YCmdParser<bool>
```

Inheritance

[object](#) < < [YCmdParser](#) < [YCmdParser](#) < [bool](#) > < YCBool

Inherited Members

[YCmdParser<bool>.ParsingType](#) , [YCmdParser.variableName](#) , [YCmdParser.variableDescription](#) , [YCmdParser.Initialize\(string, string\)](#) , [object.GetType\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCBool()

```
public YCBool()
```

Properties

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out bool)

Return the thing.

```
public override bool Parse(string s, out bool val)
```

Parameters

`s` [string](#)

`val` [bool](#)

Returns

[bool](#)

Validate(bool)

Validate type.

```
protected override bool Validate(bool s)
```

Parameters

s [bool](#)

Returns

[bool](#)

IsValid

defaultAutocompleteArray()

The default autocomplete array used for this value type. For example, "bool"s default array is ["true", "false"]. Optionally return "null" for no autocomplete.

```
public override string[] defaultAutocompleteArray()
```

Returns

[string](#)[]

Autocomplete Array

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#)

Descriptor

Class YCCmdArg

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use **YCCmdArg** to get registered commands as an input. (Use `Command[]`)

```
public sealed class YCCmdArg : YCmdParser<Command[]>
```

Inheritance

[object](#)  ← [YCmdParser](#) ← [YCmdParser<Command\[\]>](#) ← YCCmdArg

Inherited Members

[YCmdParser<Command\[\]>.Parse\(string, out Command\[\]\)](#), [YCmdParser<Command\[\]>.ParsingType](#), [YCmdParser.variableName](#), [YCmdParser.variableDescription](#), [YCmdParser.Initialize\(string, string\)](#), [YCmdParser.ParsingType](#), [object.GetType\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCCmdArg()

```
public YCCmdArg()
```

Properties

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out Command[])

Return the thing.

```
public override bool Parse(string s, out Command[] val)
```

Parameters

`s` [string](#)

`val` [Command\[\]](#)

Returns

[bool](#)

Validate(Command[])

Validate type.

```
protected override bool Validate(Command[] s)
```

Parameters

s [Command\[\]](#)

Returns

[bool](#)

IsValid

defaultAutocompleteArray()

The default autocomplete array used for this value type. For example, "bool"s default array is ["true", "false"]. Optionally return "null" for no autocomplete.

```
public override string[] defaultAutocompleteArray()
```

Returns

[string](#) []

Autocomplete Array

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#)

Descriptor

Class YCEnum

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use `YCEnum(typeof(Enum))` for enum arguments.

```
public sealed class YCEnum : YCmdParser<Enum>
```

Inheritance

[object](#)  ← [YCmdParser](#) ← [YCmdParser](#) [<Enum](#)  > ← YCEnum

Inherited Members

[YCmdParser<Enum>.ParsingType](#) , [YCmdParser.variableName](#) , [YCmdParser.variableDescription](#) ,
[YCmdParser.Initialize\(string, string\)](#) , [object.GetType\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

YCEnum()

```
public YCEnum()
```

Properties

enumType

```
public Type enumType { get; }
```

Property Value

[Type](#) 

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out Enum)

Return the thing.

```
public override bool Parse(string s, out Enum val)
```

Parameters

`s` [string](#)

`val` [Enum](#)

Returns

[bool](#)

SetEnumType(Type)

```
public void SetEnumType(Type enumtype)
```

Parameters

enumtype [Type](#)

Validate(Enum)

Validate type.

```
protected override bool Validate(Enum s)
```

Parameters

s [Enum](#)

Returns

[bool](#)

IsValid

defaultAutocompleteArray()

The default autocomplete array used for this value type. For example, "bool"s default array is ["true", "false"]. Optionally return "null" for no autocomplete.

```
public override string[] defaultAutocompleteArray()
```

Returns

[string](#)[]

Autocomplete Array

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#) 

Descriptor

Class YCFloat

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use `YCFloat(min, max)` for float arguments. (min / max optional)

```
public sealed class YCFloat : YCmdParser<float>
```

Inheritance

[object](#) $\leftarrow$ [YCmdParser](#) $\leftarrow$ [YCmdParser](#)<[float](#)> $\leftarrow$ YCFloat

Inherited Members

[YCmdParser<float>.ParsingType](#) , [YCmdParser.variableName](#) , [YCmdParser.variableDescription](#) , [YCmdParser.defaultAutocompleteArray\(\)](#) , [YCmdParser.Initialize\(string, string\)](#) , [object.GetType\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

YCFloat()

```
public YCFloat()
```

Properties

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out float)

Return the thing.

```
public override bool Parse(string s, out float val)
```

Parameters

`s` [string](#)

`val` [float](#)

Returns

[bool](#)

Validate(float)

Validate type.

```
protected override bool Validate(float s)
```

Parameters

s [float](#) 

Returns

[bool](#) 

IsValid

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#) 

Descriptor

Class YCInt

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use `YCInt(min, max)` for integer arguments. (min / max optional)

```
public sealed class YCInt : YCmdParser<int>
```

Inheritance

[object](#)  ← [YCmdParser](#) ← [YCmdParser<int](#)  > ← YCInt

Inherited Members

[YCmdParser<int>.ParsingType](#) , [YCmdParser.variableName](#) , [YCmdParser.variableDescription](#) , [YCmdParser.defaultAutocompleteArray\(\)](#) , [YCmdParser.Initialize\(string, string\)](#) , [object.GetType\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

YCInt()

```
public YCInt()
```

Properties

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out int)

Return the thing.

```
public override bool Parse(string s, out int val)
```

Parameters

`s` [string](#)

`val` [int](#)

Returns

[bool](#)

Validate(int)

Validate type.

```
protected override bool Validate(int s)
```

Parameters

s [int](#)

Returns

[bool](#)

IsValid

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#)

Descriptor

Class YCString

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Use **YCString** for string arguments.

```
public sealed class YCString : YCmdParser<string>
```

Inheritance

[object](#) $\leftarrow$ [YCmdParser](#) $\leftarrow$ [YCmdParser](#) $\leftarrow$ [YCString](#)

Inherited Members

[YCmdParser<string>.ParsingType](#) , [YCmdParser.variableName](#) , [YCmdParser.variableDescription](#) , [YCmdParser.Initialize\(string, string\)](#) , [object.GetType\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCString()

```
public YCString()
```

Properties

getTypeName

The string name of this argument's type

```
public override string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public override bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Parse(string, out string)

Return the thing.

```
public override bool Parse(string s, out string val)
```

Parameters

`s` [string](#)

`val` [string](#)

Returns

[bool](#)

Validate(string)

Validate type.

```
protected override bool Validate(string s)
```

Parameters

s [string](#) 

Returns

[bool](#) 

IsValid

defaultAutocompleteArray()

The default autocomplete array used for this value type. For example, "bool"s default array is ["true", "false"]. Optionally return "null" for no autocomplete.

```
public override string[] defaultAutocompleteArray()
```

Returns

[string](#)  []

Autocomplete Array

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public override string getDescriptorText()
```

Returns

[string](#) 

Descriptor

Class YCmdParser

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public abstract class YCmdParser
```

Inheritance

[object](#)  ← YCmdParser

Derived

[YCmdParser<T>](#)

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCmdParser()

```
protected YCmdParser()
```

Fields

variableDescription

```
public string variableDescription
```

Field Value

[string](#) 

variableName

Name of the argument used when previewing command arguments.

```
public string variableName
```

Field Value

[string](#)

Properties

ParsingType

```
public virtual Type ParsingType { get; }
```

Property Value

[Type](#)

getTypeName

The string name of this argument's type

```
public abstract string getTypeName { get; }
```

Property Value

[string](#)

hasDefaultAutocompleteArray

Check for whether this argument has an autocomplete array. If it returns `true`, `getAutocompleteArray` is called to retrieve the list.

```
public abstract bool hasDefaultAutocompleteArray { get; }
```

Property Value

[bool](#)

Methods

Initialize(string, string)

```
public void Initialize(string Name, string Description)
```

Parameters

Name [string](#)

Description [string](#)

defaultAutocompleteArray()

The default autocomplete array used for this value type. For example, "bool"s default array is ["true", "false"]. Optionally return "null" for no autocomplete.

```
public virtual string[] defaultAutocompleteArray()
```

Returns

[string](#)[]

Autocomplete Array

getDescriptorText()

Returns the name and type information of this argument in a nice, descriptive way.

```
public abstract string getDescriptorText()
```

Returns

[string](#) 

Descriptor

Class YCmdParser<T>

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
public abstract class YCmdParser<T> : YCmdParser
```

Type Parameters

T

Inheritance

[object](#)  ← [YCmdParser](#) ← YCmdParser<T>

Derived

[YCBool](#), [YCCmdArg](#), [YCEnum](#), [YCFloat](#), [YCInt](#), [YCString](#)

Inherited Members

[YCmdParser.variableName](#), [YCmdParser.variableDescription](#), [YCmdParser.getDescriptorText\(\)](#), [YCmdParser.defaultAutocompleteArray\(\)](#), [YCmdParser.Initialize\(string, string\)](#), [YCmdParser.getTypeName](#), [YCmdParser.hasDefaultAutocompleteArray](#), [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCmdParser()

```
protected YCmdParser()
```

Properties

ParsingType

```
public override Type ParsingType { get; }
```

Property Value

[Type](#)

Methods

Parse(string, out T)

Return the thing.

```
public abstract bool Parse(string s, out T val)
```

Parameters

s [string](#)

val T

Returns

[bool](#)

Validate(T)

Validate type.

```
protected virtual bool Validate(T s)
```

Parameters

s T

Returns

[bool](#)

IsValid

Class YCommandAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

Define a new command.

- Use `YCInt(min, max)` for integer arguments. (min / max optional)
- Use `YCFloat(min, max)` for float arguments. (min / max optional)
- Use `YCEnum(typeof(Enum))` for enum arguments.
- Use `YCBool` for boolean arguments.
- Use `YCString` for string arguments.
- Use `YCCmdArg` to get registered commands as an input. (Use `Command[]`)

```
[AttributeUsage(AttributeTargets.Method|AttributeTargets.Property|AttributeTargets.Field,  
AllowMultiple= false)]  
public class YCommandAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YCommandAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,

[Attribute.IsDefined\(Assembly, Type, bool\)](#), [Attribute.GetCustomAttribute\(Assembly, Type\)](#), [Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#), [Attribute.Equals\(object\)](#), [Attribute.GetHashCode\(\)](#), [Attribute.Match\(object\)](#), [Attribute.IsDefaultAttribute\(\)](#), [Attribute.TypeId](#), [object.GetType\(\)](#), [object.MemberwiseClone\(\)](#), [object.ToString\(\)](#), [object.Equals\(object, object\)](#), [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YCommandAttribute(string, string, ObjectFindType, FindObjectsInactive)

Define a new command.

```
public YCommandAttribute(string Name, string Description = "", ObjectFindType objectFindType = ObjectFindType.All, FindObjectsInactive findObjectsInactive = 0)
```

Parameters

Name [string](#)

The name of the command. This will be the name used in the console.

Description [string](#)

(Optional) Description of the command, shown when using the "help" command.

objectFindType [ObjectFindType](#)

(Optional) Used only when the function is not static to determine which objects to run the method on.

findObjectsInactive FindObjectsInactive

(Optional) Used only when the function is not static to determine whether non-active objects should be able to run the method.

YCommandAttribute(string, YCommandAttribute)

```
public YCommandAttribute(string NameAddendum, YCommandAttribute @base)
```

Parameters

NameAddendum [string](#) 

base [YCommandAttribute](#)

Properties

Desc

```
public string Desc { get; }
```

Property Value

[string](#) 

Name

```
public string Name { get; }
```

Property Value

[string](#) 

findObjectsInactive

```
public FindObjectsInactive findObjectsInactive { get; }
```

Property Value

FindObjectsInactive

objectFindType

```
public ObjectFindType objectFindType { get; }
```

Property Value

[ObjectFindType](#)

Class YDynamicAutocompleteAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = false)]  
public class YDynamicAutocompleteAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YDynamicAutocompleteAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YDynamicAutocompleteAttribute(string)

```
public YDynamicAutocompleteAttribute(string methodName)
```

Parameters

methodName [string](#)

Fields

autocompleteList

```
public string[] autocompleteList
```

Field Value

[string](#) []

Class YRangeAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = false)]  
public class YRangeAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YRangeAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YRangeAttribute(int, int)

```
public YRangeAttribute(int min, int max)
```

Parameters

min [int](#)

max [int](#)

Fields

max

```
public int max
```

Field Value

[int](#)

min

```
public int min
```

Field Value

[int](#)

Class YToggleAttribute

Namespace: [YShared.Console](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Field, AllowMultiple = false)]  
public class YToggleAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← YToggleAttribute

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YToggleAttribute()

```
public YToggleAttribute()
```

Namespace YShared.Console.Suggestion

Classes

[DynamicSuggestionModifierAttribute](#)

[ExcludeAttribute](#)

Removes the `exclude_list` to the list of possible suggestions.

[IncludeAttribute](#)

Adds the `include_list` to the list of possible suggestions.

[IncludeDynamicAttribute](#)

Adds the `include_list` to the list of possible suggestions.

[NoSuggestionsAttribute](#)

Removes the suggestion list.

[OverrideAttribute](#)

Replaces the existing list of possible suggestions with `override_list`.

[SuggestionModifierAttribute](#)

[SuggestionRangeAttribute](#)

Adds the values in the given range to the suggestion list. The start is inclusive, the end is exclusive.

Example Usage: [`SuggestionRangeAttribute(1, 13, 2)`]

The values, "1", "3", "5", "7", "9", "11"

Class DynamicSuggestionModifierAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = true, Inherited = true)]  
public abstract class DynamicSuggestionModifierAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← DynamicSuggestionModifierAttribute

Derived

[IncludeDynamicAttribute](#)

Inherited Members

[SuggestionModifierAttribute.modifyAutocompleteList\(List<string>\)](#) ,
[SuggestionModifierAttribute.thisMethodOrField](#) , [Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

DynamicSuggestionModifierAttribute()

```
protected DynamicSuggestionModifierAttribute()
```

Fields

isCacheCompatible

```
protected bool isCacheCompatible
```

Field Value

[bool](#)

Properties

cacheCompatible

```
public override bool cacheCompatible { get; }
```

Property Value

[bool](#)

Class ExcludeAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Removes the `exclude_list` to the list of possible suggestions.

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class ExcludeAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← ExcludeAttribute

Inherited Members

[SuggestionModifierAttribute.cacheCompatible](#) , [SuggestionModifierAttribute.thisMethodOrField](#) ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

ExcludeAttribute(params string[])

```
public ExcludeAttribute(params string[] exclude_list)
```

Parameters

exclude_list [string](#)[]

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#)<[string](#)>

Class IncludeAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Adds the `include_list` to the list of possible suggestions.

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class IncludeAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← IncludeAttribute

Inherited Members

[SuggestionModifierAttribute.cacheCompatible](#) , [SuggestionModifierAttribute.thisMethodOrField](#) ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

IncludeAttribute(params string[])

```
public IncludeAttribute(params string[] include_list)
```

Parameters

include_list [string](#)[]

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#)<[string](#)>

Class IncludeDynamicAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Adds the `include_list` to the list of possible suggestions.

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class IncludeDynamicAttribute : DynamicSuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← [DynamicSuggestionModifierAttribute](#)  ←
IncludeDynamicAttribute

Inherited Members

[DynamicSuggestionModifierAttribute.isCacheCompatible](#) ,
[SuggestionModifierAttribute.thisMethodOrField](#) , [Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Constructors

IncludeDynamicAttribute(string, bool)

```
public IncludeDynamicAttribute(string functionName, bool cacheCompatible = false)
```

Parameters

functionName [string](#)

cacheCompatible [bool](#)

Properties

cacheCompatible

```
public override bool cacheCompatible { get; }
```

Property Value

[bool](#)

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#) <[string](#)>

Class NoSuggestionsAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Removes the suggestion list.

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class NoSuggestionsAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← NoSuggestionsAttribute

Inherited Members

[SuggestionModifierAttribute.cacheCompatible](#) , [SuggestionModifierAttribute.thisMethodOrField](#) ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

NoSuggestionsAttribute()

```
public NoSuggestionsAttribute()
```

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#) <[string](#)>

Class OverrideAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Replaces the existing list of possible suggestions with `override_list`.

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class OverrideAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← OverrideAttribute

Inherited Members

[SuggestionModifierAttribute.cacheCompatible](#) , [SuggestionModifierAttribute.thisMethodOrField](#) ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

OverrideAttribute(params string[])

```
public OverrideAttribute(params string[] override_list)
```

Parameters

override_list [string](#)[]

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#)<[string](#)>

Class SuggestionModifierAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

```
[AttributeUsage(AttributeTargets.Parameter, AllowMultiple = true, Inherited = true)]  
public abstract class SuggestionModifierAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← SuggestionModifierAttribute

Derived

[DynamicSuggestionModifierAttribute](#), [ExcludeAttribute](#), [IncludeAttribute](#), [NoSuggestionsAttribute](#), [OverrideAttribute](#), [SuggestionRangeAttribute](#)

Inherited Members

[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,
[Attribute.TypeId](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\).](#)

Constructors

SuggestionModifierAttribute()

```
protected SuggestionModifierAttribute()
```

Properties

cacheCompatible

```
public virtual bool cacheCompatible { get; }
```

Property Value

[bool](#)

thisMethodOrField

```
public MemberInfo thisMethodOrField { get; set; }
```

Property Value

[MemberInfo](#)

Methods

modifyAutocompleteList(List<string>)

```
public abstract void modifyAutocompleteList(List<string> strings)
```

Parameters

`strings` [List](#) [<string>](#)

Class SuggestionRangeAttribute

Namespace: [YShared.Console.Suggestion](#)

Assembly: YShared.Runtime.dll

Adds the values in the given range to the suggestion list. The start is inclusive, the end is exclusive.

Example Usage: [[SuggestionRangeAttribute](#)(1, 13, 2)]

The values, "1", "3", "5", "7", "9", "11"

```
[AttributeUsage(AttributeTargets.Parameter)]  
public class SuggestionRangeAttribute : SuggestionModifierAttribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← [SuggestionModifierAttribute](#)  ← [SuggestionRangeAttribute](#)

Inherited Members

[SuggestionModifierAttribute.cacheCompatible](#) , [SuggestionModifierAttribute.thisMethodOrField](#) ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  , [Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.IsDefined\(MemberInfo, Type\)](#)  , [Attribute.IsDefined\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  , [Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  , [Attribute.IsDefined\(ParameterInfo, Type\)](#)  ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  , [Attribute.GetCustomAttributes\(Module\)](#)  ,
[Attribute.GetCustomAttributes\(Module, bool\)](#)  , [Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.IsDefined\(Module, Type\)](#)  , [Attribute.IsDefined\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  , [Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  , [Attribute.IsDefined\(Assembly, Type\)](#)  ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  , [Attribute.Equals\(object\)](#)  ,
[Attribute.GetHashCode\(\)](#)  , [Attribute.Match\(object\)](#)  , [Attribute.IsDefaultAttribute\(\)](#)  ,

[Attribute.GetType\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

SuggestionRangeAttribute(int, int, int)

Adds the values in the given range to the suggestion list. The start is inclusive, the end is exclusive.

Example Usage: `[SuggestionRangeAttribute(1, 13, 2)]`

The values, "1", "3", "5", "7", "9", "11"

```
public SuggestionRangeAttribute(int start_inclusive, int end_exclusive, int step = 1)
```

Parameters

`start_inclusive` [int](#)

Start. Inclusive

`end_exclusive` [int](#)

End. Exclusive.

`step` [int](#)

Step number. Defaults to 1.

Methods

modifyAutocompleteList(List<string>)

```
public override void modifyAutocompleteList(List<string> strings)
```

Parameters

strings [List](#) <[string](#)>

Namespace YShared.MathHelper

Classes

[ArrayFunctions](#)

[SinValue](#)

[TrackedVariable<T>](#)

Wrapper for a value type to track the changes to it. T[] values array - index 0 stores the latest version, while history_to_record - 1 stores the oldest stored version.

[YMathHelper](#)

Class ArrayFunctions

Namespace: [YShared.MathHelper](#)

Assembly: YShared.Runtime.dll

```
public static class ArrayFunctions
```

Inheritance

[object](#)  ← ArrayFunctions

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Methods

AvgArray(float[])

```
public static float AvgArray(this float[] floats)
```

Parameters

floats [float](#) []

Returns

[float](#) 

ForEach<ArrType>(ArrType[], Action<ArrType>)

```
public static void ForEach<ArrType>(this ArrType[] array, Action<ArrType> act)
```

Parameters

array ArrType[]

act [Action](#) <ArrType>

Type Parameters

ArrType

Map<ArrType, ReturnType>(ArrType[], Func<ArrType, ReturnType>)

```
public static ReturnType[] Map<ArrType, ReturnType>(this ArrType[] array, Func<ArrType,
ReturnType> func)
```

Parameters

array ArrType[]

func [Func](#) <ArrType, ReturnType>

Returns

ReturnType[]

Type Parameters

ArrType

ReturnType

MergeDictionary<TKey, TValue>(Dictionary<TKey, TValue>, Dictionary<TKey, TValue>)

```
public static Dictionary<TKey, TValue> MergeDictionary<TKey, TValue>(this Dictionary<TKey,
TValue> first, Dictionary<TKey, TValue> second)
```

Parameters

first [Dictionary](#) <TKey, TValue>

second [Dictionary](#) <TKey, TValue>

Returns

[Dictionary](#) <TKey, TValue>

Type Parameters

TKey

TValue

PickRandomly<T>(List<T>)

```
public static T PickRandomly<T>(this List<T> arr)
```

Parameters

arr [List](#) <T>

Returns

T

Type Parameters

T

PickRandomly<T>(T[])

```
public static T PickRandomly<T>(this T[] arr)
```

Parameters

arr T[]

Returns

T

Type Parameters

T

PickRandomly<T>(T[], out int)

```
public static T PickRandomly<T>(this T[] arr, out int index)
```

Parameters

arr T[]

index [int](#)

Returns

T

Type Parameters

T

PrintArray<T>(T[])

```
public static void PrintArray<T>(this T[] arr)
```

Parameters

arr T[]

Type Parameters

T

PrintList<T>(IEnumerable<T>)

```
public static void PrintList<T>(this IEnumerable<T> arr)
```

Parameters

arr [IEnumerable](#) <T>

Type Parameters

T

Reduce<ArrType, ReturnType>(ArrType[], Func<ArrType, ReturnType, int, ReturnType>, ReturnType)

```
public static ReturnType Reduce<ArrType, ReturnType>(this ArrType[] array, Func<ArrType,
ReturnType, int, ReturnType> func, ReturnType start_value)
```

Parameters

array ArrType[]

func [Func](#) <ArrType, ReturnType, [int](#), ReturnType>

start_value ReturnType

Returns

ReturnType

Type Parameters

ArrType

ReturnType

RepeatToArray<T>(T, int)

```
public static T[] RepeatToArray<T>(T obj, int amount)
```

Parameters

obj T

amount [int](#)

Returns

T[]

Type Parameters

T

ShiftArray<T>(T[,], int, int)

```
public static T[,] ShiftArray<T>(this T[,] array, int shiftX, int shiftY)
```

Parameters

array T[,]

shiftX [int](#)

shiftY [int](#)

Returns

T[,]

Type Parameters

T

SpiralLoop<T>(T[,])

```
public static List<T> SpiralLoop<T>(this T[,] arr)
```

Parameters

arr T[]

Returns

[List](#)<T>

Type Parameters

T

StringifyArray<T>(T[])

```
public static string StringifyArray<T>(this T[] arr)
```

Parameters

arr T[]

Returns

[string](#)

Type Parameters

T

StringifyList<T>(IEnumerable<T>)

```
public static string StringifyList<T>(IEnumerable<T> arr)
```

Parameters

arr [IEnumerable](#) <T>

Returns

[string](#)

Type Parameters

T

SumArray(int[])

```
public static int SumArray(this int[] floats)
```

Parameters

floats [int](#)[]

Returns

[int](#)

SumArray(float[])

```
public static float SumArray(this float[] floats)
```

Parameters

floats [float](#)[]

Returns

[float](#)

Class SinValue

Namespace: [YShared.MathHelper](#)

Assembly: YShared.Runtime.dll

```
public class SinValue
```

Inheritance

[object](#)  ← SinValue

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

SinValue()

```
public SinValue()
```

Fields

Amplitude

```
public float Amplitude
```

Field Value

[float](#) 

Frequency

`public float` Frequency

Field Value

[float](#)

Offset

`public float` Offset

Field Value

[float](#)

Properties

Value

`public float` Value { `get`; }

Property Value

[float](#)

Class TrackedVariable<T>

Namespace: [YShared.MathHelper](#)

Assembly: YShared.Runtime.dll

Wrapper for a value type to track the changes to it. T[] values array - index 0 stores the latest version, while history_to_record - 1 stores the oldest stored version.

```
public class TrackedVariable<T> where T : struct
```

Type Parameters

T

Type to track.

Inheritance

[object](#)  ← TrackedVariable<T>

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

TrackedVariable(int, T)

```
public TrackedVariable(int history_to_record, T initial_value = default)
```

Parameters

history_to_record [int](#) 

initial_value T

Fields

values

```
public T[] values
```

Field Value

T[]

Methods

Get(int)

```
public T Get(int point_to_get = 0)
```

Parameters

point_to_get [int](#)

Returns

T

GetFromEnd(int)

```
public T GetFromEnd(int point_to_get = 0)
```

Parameters

point_to_get [int](#)

Returns

T

GetOldest()

```
public T GetOldest()
```

Returns

T

Reset()

```
public void Reset()
```

Set(T)

```
public void Set(T new_value)
```

Parameters

new_value T

ToString()

```
public override string ToString()
```

Returns

[string](#)[↗]

Class YMathHelper

Namespace: [YShared.MathHelper](#)

Assembly: YShared.Runtime.dll

```
public static class YMathHelper
```

Inheritance

[object](#)  ← YMathHelper

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Fields

indentLevel

```
public static readonly string[] indentLevel
```

Field Value

[string](#)  []

Methods

Abs(int)

```
public static int Abs(this int number)
```

Parameters

number [int](#) 

Returns

[int](#)

Abs(float)

```
public static float Abs(this float number)
```

Parameters

number [float](#)

Returns

[float](#)

AsInt0(bool)

```
public static int AsInt0(this bool b)
```

Parameters

b [bool](#)

Returns

[int](#)

AsIntN1(bool)

```
public static int AsIntN1(this bool b)
```

Parameters

b [bool](#)

Returns

[int](#)

Ceil(int)

```
public static int Ceil(this int number)
```

Parameters

number [int](#)

Returns

[int](#)

Ceil(float)

```
public static int Ceil(this float number)
```

Parameters

number [float](#)

Returns

[int](#)

Damp(float, float, float, float)

```
public static float Damp(float current, float target, float dampingFactor, float deltaTime)
```

Parameters

current [float](#)

target [float](#)

dampingFactor [float](#)

deltaTime [float](#)

Returns

[float](#)

Damp(Vector2, Vector2, float, float)

```
public static Vector2 Damp(Vector2 current, Vector2 target, float dampingFactor, float deltaTime)
```

Parameters

current Vector2

target Vector2

dampingFactor [float](#)

deltaTime [float](#)

Returns

Vector2

Flip(int, int)

```
public static int Flip(this int number, int origin = 0)
```

Parameters

number [int](#)

origin [int](#)

Returns

[int](#)

Flip(float, float)

```
public static float Flip(this float number, float origin = 0)
```

Parameters

number [float](#)

origin [float](#)

Returns

[float](#)

Floor(int)

```
public static int Floor(this int number)
```

Parameters

number [int](#)

Returns

[int](#)

Floor(float)

```
public static int Floor(this float number)
```

Parameters

number [float](#)

Returns

[int](#)

GetLookAngleAndDir(Transform, Vector3, float)

```
public static (float, Vector3) GetLookAngleAndDir(Transform t, Vector3 target, float offset = 0)
```

Parameters

t Transform

target Vector3

offset [float](#)

Returns

([float](#), Vector3)

GetRandomEnum<T>()

```
public static T GetRandomEnum<T>() where T : struct, Enum
```

Returns

T

Type Parameters

T

GetRandomPoint(Vector2)

```
public static float GetRandomPoint(this Vector2 v)
```

Parameters

v Vector2

Returns

[float](#)

GetRandomPointInBounds(Vector3, Vector3)

```
public static Vector3 GetRandomPointInBounds(Vector3 min, Vector3 max)
```

Parameters

min Vector3

max Vector3

Returns

Vector3

IsColorCloseEnough(Color, Color, float)

```
public static bool IsColorCloseEnough(Color a, Color b, float threshold = 0.1)
```

Parameters

a Color

b Color

threshold [float](#)

Returns

[bool](#)

IsInBounds(int, int, int)

```
public static bool IsInBounds(this int i, int lower, int upper)
```

Parameters

i [int](#)

lower [int](#)

upper [int](#)

Returns

[bool](#)

IsInBounds(int, int, int, int, int, int)

```
public static bool IsInBounds(int x, int y, int low_x, int low_y, int high_x, int high_y)
```

Parameters

x [int](#)

y [int](#)

low_x [int](#)

low_y [int](#)

high_x [int](#)

high_y [int](#)

Returns

[bool](#)

IsInBounds(float, float, float)

```
public static bool IsInBounds(this float i, float lower, float upper)
```

Parameters

i [float](#)

lower [float](#)

upper [float](#)

Returns

[bool](#)

IsInBounds(Vector2Int, Vector2Int, Vector2Int)

```
public static bool IsInBounds(this Vector2Int i, Vector2Int lower, Vector2Int upper)
```

Parameters

i Vector2Int

lower Vector2Int

upper Vector2Int

Returns

[bool](#)

IsInDistance(Vector3, Vector3, float)

```
public static bool IsInDistance(Vector3 a, Vector3 b, float dst)
```

Parameters

a Vector3

b Vector3

dst [float](#)

Returns

[bool](#)

MakeLookAtLocation(Transform, Vector3, float)

```
public static (float, Vector3) MakeLookAtLocation(Transform t, Vector3 target, float offset = 0)
```

Parameters

t Transform

target Vector3

offset [float](#)

Returns

([float](#), Vector3)

ResolveTimeForGivenAccelerationAndDistance(float, float)

```
public static float ResolveTimeForGivenAccelerationAndDistance(float distance, float acceleration)
```

Parameters

distance [float](#)

acceleration [float](#)

Returns

[float](#)

RoundToNearestMultiple(int, int)

```
public static int RoundToNearestMultiple(int value, int multiple)
```

Parameters

value [int](#)

multiple [int](#)

Returns

[int](#)

RoundToNearestMultiple(float, int)

```
public static int RoundToNearestMultiple(float value, int multiple)
```

Parameters

value [float](#)

multiple [int](#)

Returns

[int](#)

RoundToNearestMultiple(float, float)

```
public static float RoundToNearestMultiple(float value, float multiple)
```

Parameters

value [float](#)

multiple [float](#)

Returns

[float](#)

RoundToXDecimals(float, int)

```
public static float RoundToXDecimals(this float number, int x)
```

Parameters

number [float](#)

x [int](#)

Returns

[float](#)

RoundToXDecimalsButAsString(float, int)

```
public static string RoundToXDecimalsButAsString(this float number, int x)
```

Parameters

number [float](#)

x [int](#)

Returns

[string](#)

TryAs<T>(object, out T)

```
public static bool TryAs<T>(this object value, out T casted) where T : class
```

Parameters

value [object](#)

casted T

Returns

[bool](#)

Type Parameters

T

V2IString(Vector2Int)

```
public static string V2IString(this Vector2Int a)
```

Parameters

a Vector2Int

Returns

[string](#)

V2I_to_V3(Vector2Int, float)

```
public static Vector3 V2I_to_V3(this Vector2Int a, float b = 0)
```

Parameters

a Vector2Int

b [float](#)

Returns

Vector3

addBytes(byte, byte)

```
public static byte addBytes(byte a, byte b)
```

Parameters

a [byte](#)

b [byte](#)

Returns

[byte](#)

fmod(float, float)

```
public static float fmod(this float a, float modnum)
```

Parameters

a [float](#)

modnum [float](#)

Returns

[float](#)

imod(int, int)

```
public static int imod(this int x, int m)
```

Parameters

x [int](#)

m [int](#)

Returns

[int](#)

Namespace YShared.NamedTimers

Classes

[Extension](#)

[Extension.TimerBehaviour](#)

[Timer](#)

[TimerHandler](#)

[TimerWindow](#)

Structs

[GameObjectBinding](#)

[TimerOptions](#)

[TimerState](#)

Enums

[SetTimerResult](#)

Class Extension

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public static class Extension
```

Inheritance

[object](#)  ← Extension

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Methods

AddNamelessTimer(GameObject, float, Action)

```
[Obsolete("Use SetTimeout instead")]  
public static void AddNamelessTimer(this GameObject go, float a, Action callback)
```

Parameters

go [GameObject](#)

a [float](#) 

callback [Action](#) 

ClearFromGameObject(GameObject)

```
public static int ClearFromGameObject(this GameObject go)
```

Parameters

go [GameObject](#)

Returns

[int](#)

GetTimer(GameObject, int)

```
public static float GetTimer(this GameObject go, int name)
```

Parameters

go GameObject

name [int](#)

Returns

[float](#)

GetTimer(GameObject, string)

```
public static float GetTimer(this GameObject go, string name)
```

Parameters

go GameObject

name [string](#)

Returns

[float](#)

GetTimerClass(GameObject, string)

```
public static Timer GetTimerClass(this GameObject go, string name)
```

Parameters

go [GameObject](#)

name [string](#)

Returns

[Timer](#)

GetTimers(GameObject)

```
public static List<long> GetTimers(this GameObject go)
```

Parameters

go [GameObject](#)

Returns

[List](#) <[long](#)>

Hash(string)

```
public static int Hash(string str)
```

Parameters

str [string](#)

Returns

[int](#)

OnInitializeLoad()

```
public static void OnInitializeLoad()
```

RegisterTimer(GameObject, string, TimerOptions)

```
public static void RegisterTimer(this GameObject go, string name, TimerOptions opts)
```

Parameters

go [GameObject](#)

name [string](#)

opts [TimerOptions](#)

RemoveTimer(GameObject, int)

```
public static bool RemoveTimer(this GameObject go, int name)
```

Parameters

go [GameObject](#)

name [int](#)

Returns

[bool](#)

RemoveTimer(GameObject, string)

```
public static bool RemoveTimer(this GameObject go, string name)
```

Parameters

go [GameObject](#)

name [string](#)

Returns

[bool](#)

RunNextFrame(GameObject, Action)

```
public static void RunNextFrame(this GameObject go, Action callback)
```

Parameters

go `GameObject`

callback [Action](#)

SetTimeout(GameObject, float, Action)

```
public static void SetTimeout(this GameObject go, float a, Action callback)
```

Parameters

go `GameObject`

a [float](#)

callback [Action](#)

SetTimer(GameObject, int, float)

```
public static SetTimerResult SetTimer(this GameObject go, int name, float time)
```

Parameters

go `GameObject`

name [int](#)

time [float](#)

Returns

[SetTimerResult](#)

SetTimer(GameObject, int, float, Action)

```
public static SetTimerResult SetTimer(this GameObject go, int name, float time,
Action callback)
```

Parameters

go GameObject

name [int](#)

time [float](#)

callback [Action](#)

Returns

[SetTimerResult](#)

SetTimer(GameObject, int, float, TimerOptions)

```
public static SetTimerResult SetTimer(this GameObject go, int name, float time,
TimerOptions opts)
```

Parameters

go GameObject

name [int](#)

time [float](#)

opts [TimerOptions](#)

Returns

[SetTimerResult](#)

SetTimer(GameObject, string, float)

```
public static SetTimerResult SetTimer(this GameObject go, string name, float time)
```

Parameters

go [GameObject](#)

name [string](#)[↗]

time [float](#)[↗]

Returns

[SetTimerResult](#)

SetTimer(GameObject, string, float, Action)

```
public static SetTimerResult SetTimer(this GameObject go, string name, float a,  
Action callback)
```

Parameters

go [GameObject](#)

name [string](#)[↗]

a [float](#)[↗]

callback [Action](#)[↗]

Returns

[SetTimerResult](#)

SetTimer(GameObject, string, float, TimerOptions)

```
public static SetTimerResult SetTimer(this GameObject go, string name, float a,
TimerOptions opts)
```

Parameters

go [GameObject](#)

name [string](#)

a [float](#)

opts [TimerOptions](#)

Returns

[SetTimerResult](#)

TimerCooldown(GameObject, int, float)

```
public static bool TimerCooldown(this GameObject go, int name, float time)
```

Parameters

go [GameObject](#)

name [int](#)

time [float](#)

Returns

[bool](#)

TimerCooldown(GameObject, string, float)

```
public static bool TimerCooldown(this GameObject go, string name, float time)
```

Parameters

go GameObject

name [string](#)

time [float](#)

Returns

[bool](#)

TriggerChronometer(GameObject, int, float)

```
public static bool TriggerChronometer(this GameObject go, int name, float target)
```

Parameters

go GameObject

name [int](#)

target [float](#)

Returns

[bool](#)

TriggerChronometer(GameObject, string, float)

```
public static bool TriggerChronometer(this GameObject go, string name, float target)
```

Parameters

go GameObject

name [string](#)

target [float](#)

Returns

[bool](#)

Update2()

```
public static void Update2()
```

iCombine(GameObject, int)

```
public static long iCombine(GameObject go, int id)
```

Parameters

go GameObject

id [int](#)

Returns

[long](#)

iGetId(long)

```
public static int iGetId(long id)
```

Parameters

id [long](#)

Returns

[int](#) 

Class Extension.TimerBehaviour

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public class Extension.TimerBehaviour : MonoBehaviour
```

Inheritance

[object](#)  ← Extension.TimerBehaviour

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

TimerBehaviour()

```
public TimerBehaviour()
```

Struct GameObjectBinding

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public struct GameObjectBinding
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) , [object.GetType\(\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

bound_object

```
public GameObject bound_object
```

Field Value

GameObject

is_bound

```
public bool is_bound
```

Field Value

[bool](#)

noAutomaticBind

```
public bool noAutomaticBind
```

Field Value

[bool](#)

Enum SetTimerResult

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public enum SetTimerResult
```

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Fields

ChangedTimeLeft = 1

NewTimer = 0

ReplacedAction = 2

Class Timer

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public class Timer
```

Inheritance

[object](#)  ← Timer

Inherited Members

[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ToString\(\)](#)  , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.GetHashCode\(\)](#) 

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

Timer()

```
public Timer()
```

Fields

duration

```
public float duration
```

Field Value

[float](#) 

name

```
public long name
```

Field Value

[long](#)

state

```
public TimerState state
```

Field Value

[TimerState](#)

time_left

```
public float time_left
```

Field Value

[float](#)

Class TimerHandler

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public static class TimerHandler
```

Inheritance

[object](#)  ← TimerHandler

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Methods

AddNamelessTimer(float, Action)

```
[Obsolete("Use SetTimeout instead")]  
public static void AddNamelessTimer(float a, Action callback)
```

Parameters

a [float](#) 

callback [Action](#) 

BindObjectToTimer(GameObject, long)

```
public static bool BindObjectToTimer(GameObject go, long name)
```

Parameters

go [GameObject](#)

name [long](#) 

Returns

[bool](#)

ClearAll()

```
public static void ClearAll()
```

ClearFromGameObject(GameObject)

```
public static int ClearFromGameObject(GameObject go)
```

Parameters

go [GameObject](#)

Returns

[int](#)

GetTimer(long)

```
public static float GetTimer(long name)
```

Parameters

name [long](#)

Returns

[float](#)

GetTimerClass(long)

```
public static Timer GetTimerClass(long name)
```

Parameters

name [long](#)

Returns

[Timer](#)

GetTimerClass(string)

```
public static Timer GetTimerClass(string name)
```

Parameters

name [string](#)

Returns

[Timer](#)

GetTimers()

Returns all timers

```
public static List<long> GetTimers()
```

Returns

[List](#) <[long](#)>

GetTimers(GameObject)

Returns all timers on a specific gameobject

```
public static List<long> GetTimers(GameObject go)
```

Parameters

go [GameObject](#)

Returns

[List](#) <[long](#)>

Hash(string)

```
public static int Hash(string str)
```

Parameters

str [string](#)

Returns

[int](#)

RegisterTimer(string, long, TimerOptions)

```
public static void RegisterTimer(string name, long id, TimerOptions opts = default)
```

Parameters

name [string](#)

id [long](#)

opts [TimerOptions](#)

RegisterTimer(string, TimerOptions)

```
public static void RegisterTimer(string name, TimerOptions opts = default)
```

Parameters

name [string](#)

opts [TimerOptions](#)

RemoveTimer(long)

```
public static bool RemoveTimer(long name)
```

Parameters

name [long](#)

Returns

[bool](#)

RunNextFrame(Action)

```
public static void RunNextFrame(Action callback)
```

Parameters

callback [Action](#)

SetTimeout(float, Action)

```
public static void SetTimeout(float a, Action callback)
```

Parameters

a [float](#)

callback [Action](#)

SetTimer(long, float)

```
public static SetTimerResult SetTimer(long name, float time)
```

Parameters

name [long](#)

time [float](#)

Returns

[SetTimerResult](#)

SetTimer(long, float, Action)

```
public static SetTimerResult SetTimer(long name, float a, Action callback)
```

Parameters

name [long](#)

a [float](#)

callback [Action](#)

Returns

[SetTimerResult](#)

SetTimer(long, float, TimerOptions)

```
public static SetTimerResult SetTimer(long name, float a, TimerOptions opts)
```

Parameters

name [long](#)

a [float](#)

opts [TimerOptions](#)

Returns

[SetTimerResult](#)

SetTimer(string, float)

```
public static SetTimerResult SetTimer(string name, float time)
```

Parameters

name [string](#)

time [float](#)

Returns

[SetTimerResult](#)

SetTimer(string, float, Action)

```
public static SetTimerResult SetTimer(string name, float a, Action callback)
```

Parameters

name [string](#)

a [float](#)

callback [Action](#)

Returns

[SetTimerResult](#)

SetTimer(string, float, TimerOptions)

```
public static SetTimerResult SetTimer(string name, float a, TimerOptions opts)
```

Parameters

name [string](#)↗

a [float](#)↗

opts [TimerOptions](#)

Returns

[SetTimerResult](#)

Tick()

```
public static void Tick()
```

TimerCooldown(long, float)

```
public static bool TimerCooldown(long name, float timer)
```

Parameters

name [long](#)↗

timer [float](#)↗

Returns

[bool](#)↗

TriggerChronometer(long, float)

```
public static bool TriggerChronometer(long name, float target)
```

Parameters

name [long](#)

target [float](#)

Returns

[bool](#)

Struct TimerOptions

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public struct TimerOptions
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) , [object.GetType\(\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Fields

Callback

```
public Action Callback
```

Field Value

[Action](#)

CallbackCondition

```
public Func<Timer, bool> CallbackCondition
```

Field Value

[Func](#) <[Timer](#), [bool](#) >

OnUpdate

```
public Action<float, float> OnUpdate
```

Field Value

[Action](#) <[float](#), [float](#)>

loopInfinitely

```
public bool loopInfinitely
```

Field Value

[bool](#)

loops

```
public int loops
```

Field Value

[int](#)

preserve

```
public bool preserve
```

Field Value

[bool](#)

runOnUnscaledTime

```
public bool runOnUnscaledTime
```

Field Value

[bool](#)

stringName

```
public string stringName
```

Field Value

[string](#)

Struct TimerState

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public struct TimerState
```

Inherited Members

[ValueType.Equals\(object\)](#) , [ValueType.GetHashCode\(\)](#) , [ValueType.ToString\(\)](#) , [object.GetType\(\)](#) , [object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

TimerState(TimerOptions)

```
public TimerState(TimerOptions opts)
```

Parameters

opts [TimerOptions](#)

Fields

binding

```
public GameObjectBinding binding
```

Field Value

[GameObjectBinding](#)

callbackSent

```
public bool callbackSent
```

Field Value

[bool](#)

hasConditional

```
public bool hasConditional
```

Field Value

[bool](#)

opts

```
public TimerOptions opts
```

Field Value

[TimerOptions](#)

pause

```
public bool pause
```

Field Value

[bool](#)

Class TimerWindow

Namespace: [YShared.NamedTimers](#)

Assembly: YShared.Runtime.dll

```
public class TimerWindow : EditorWindow
```

Inheritance

[object](#)  ← TimerWindow

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

TimerWindow()

```
public TimerWindow()
```

Methods

ShowWindow()

```
public static void ShowWindow()
```

Namespace YShared.RandomHelper

Classes

[YRandom](#)

Class YRandom

Namespace: [YShared.RandomHelper](#)

Assembly: YShared.Runtime.dll

```
public static class YRandom
```

Inheritance

[object](#)  ← YRandom

Inherited Members

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ToString\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.GetHashCode\(\)](#) 

Methods

Array<T>(T[])

```
public static T Array<T>(T[] arr)
```

Parameters

arr T[]

Returns

T

Type Parameters

T

Bool(float)

```
public static bool Bool(float true_chance)
```

Parameters

`true_chance` [float](#)

Returns

[bool](#)

Enum<T>()

```
public static T Enum<T>() where T : struct, Enum
```

Returns

T

Type Parameters

T

GetWeightedRandom<T>(List<(T item, float weight)>)

```
public static T GetWeightedRandom<T>(List<(T item, float weight)> items)
```

Parameters

`items` [List](#)<(T [item](#), [float](#) [weight](#))>

Returns

T

Type Parameters

T

NormalNumber(float, float, int, int)

```
public static int NormalNumber(float mean, float standardDeviation, int min = -2147483648,
int max = 2147483647)
```

Parameters

mean [float](#)

standardDeviation [float](#)

min [int](#)

max [int](#)

Returns

[int](#)

NormalNumber(float, float, float, float)

```
public static float NormalNumber(float mean, float standardDeviation, float min =
-3.4028235E+38, float max = 3.4028235E+38)
```

Parameters

mean [float](#)

standardDeviation [float](#)

min [float](#)

max [float](#)

Returns

[float](#)

OneOrZero(float)

```
public static int OneOrZero(float one_chance)
```

Parameters

one_chance [float](#)

Returns

[int](#)

Sign(float)

```
public static int Sign(float plus_chance)
```

Parameters

plus_chance [float](#)

Returns

[int](#)

Namespace YShared.Singleton

Classes

[Singleton<T>](#)

[YSceneSingleton<T>](#)

[YSingleton<T>](#)

Singeton.

Class Singleton<T>

Namespace: [YShared.Singleton](#)

Assembly: YShared.Runtime.dll

```
[Obsolete("Use YSingleton instead.", false)]  
public class Singleton<T> : YSingleton<T> where T : MonoBehaviour
```

Type Parameters

T

Inheritance

[object](#)  ← [YSingleton](#)<T> ← Singleton<T>

Inherited Members

[YSingleton<T>.Awake\(\)](#), [YSingleton<T>.OnDestroy\(\)](#), [YSingleton<T>.Instance](#),
[YSingleton<T>.CallDontDestroyOnLoad](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

Singleton()

```
public Singleton()
```

Class YSceneSingleton<T>

Namespace: [YShared.Singleton](#)

Assembly: YShared.Runtime.dll

```
public abstract class YSceneSingleton<T> : YSingleton<T> where T : MonoBehaviour
```

Type Parameters

T

Inheritance

[object](#)  ← [YSingleton](#) <T> ← YSceneSingleton <T>

Inherited Members

[YSingleton<T>.Awake\(\)](#), [YSingleton<T>.OnDestroy\(\)](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#)

Constructors

YSceneSingleton()

```
protected YSceneSingleton()
```

Properties

CallDontDestroyOnLoad

```
public override bool CallDontDestroyOnLoad { get; }
```

Property Value

[bool](#) 

Instance

```
public static T Instance { get; }
```

Property Value

T

Class YSingleton<T>

Namespace: [YShared.Singleton](#)

Assembly: YShared.Runtime.dll

Singleton.

```
public abstract class YSingleton<T> : MonoBehaviour where T : MonoBehaviour
```

Type Parameters

T

This class

Inheritance

[object](#)  ← YSingleton<T>

Derived

[Console](#), [DevConsoleUI](#), [Singleton<T>](#), [YSceneSingleton<T>](#)

Extension Methods

[YMathHelper.TryAs<T>\(object, out T\)](#).

Constructors

YSingleton()

```
protected YSingleton()
```

Properties

CallDontDestroyOnLoad

```
public virtual bool CallDontDestroyOnLoad { get; }
```

Property Value

[bool](#)

Instance

```
public static T Instance { get; }
```

Property Value

T

Methods

Awake()

```
protected virtual void Awake()
```

OnDestroy()

```
protected virtual void OnDestroy()
```