

Compare Results

Old File:

2024.emnlp-main.1026.pdf

13 pages (12.25 MB)

versus

New File:

2024_emnlp-main_1026.pdf

11 pages (210 KB)

2/8/2026 4:47:04 AM

Total Changes

35

Content

13	Replacements
10	Insertions
12	Deletions

Styling and Annotations

0	Styling
0	Annotations

[Go to First Change \(page 1\)](#)

CasiMedicos-Arg: A Medical Question Answering Dataset Annotated with Explanatory Argumentative Structures

Ekaterina Sviridova¹

Anar Yeginbergen²

Ainara Estarrona²

Elena Cabrio¹

Serena Villata¹

Rodrigo Agerri²

¹Université Côte d'Azur, CNRS, Inria, I3S, France

²HiTZ Center - Ixa, University of the Basque Country UPV/EHU

{sviridova,cabrio,villata}@i3s.unice.fr, {anar.yeginbergen, ainara.estarrona, rodrigo.agerri}@ehu.eus

Abstract

Explaining Artificial Intelligence (AI) decisions is a major challenge nowadays in AI, in particular when applied to sensitive scenarios like medicine and law. However, the need to explain the rationale behind decisions is a main issue also for human-based deliberation as it is important to justify why a certain decision has been taken. Resident medical doctors for instance are required not only to provide a (possibly correct) diagnosis, but also to explain how they reached a certain conclusion. Developing new tools to aid residents to train their explanation skills is therefore a central objective of AI in education. In this paper, we follow this direction, and we present, to the best of our knowledge, the first multilingual dataset for Medical Question Answering where correct and incorrect diagnoses for a clinical case are enriched with a natural language explanation written by doctors. These explanations have been manually annotated with argument components (i.e., premise, claim) and argument relations (i.e., attack, support). The Multilingual CasiMedicos-arg dataset consists of 558 clinical cases in four languages (English, Spanish, French, Italian) with explanations, where we annotated 5021 claims, 2313 premises, 2431 support relations, and 1106 attack relations. We conclude by showing how competitive baselines perform over this challenging dataset for the argument mining task.

1 Introduction

There is an increasingly large body of research on AI applied to the medical domain with the objective of developing technology to assist and support medical doctors in explaining their decisions or how they have reached a certain conclusion. For example, resident medical doctors preparing for licensing exams may get AI support to explain what and why is the treatment or diagnosis correct given some background information (Safranek et al., 2023; Goenaga et al., 2024).

A prominent example of this is the recent proliferation of Medical Question Answering (QA) datasets and benchmarks, in which the task often involves processing and acquiring relevant specialized medical knowledge to be able to answer a medical question based on the con-

text provided by a clinical case (Singhal et al., 2023a; Nori et al., 2023; Xiong et al., 2024).

The development of Large Language Models (LLMs), both general purpose and specialized in the medical domain, has enabled rapid progress in Medical QA tasks which has led in turn to claims about LLMs being able to pass official medical exams such as the United States Medical Licensing Examination (USMLE) (Singhal et al., 2023b; Nori et al., 2023). Thus, publicly available LLMs such as LLaMa (Touvron et al., 2023) or Mistral (Jiang et al., 2023) and their respective medical-specific versions PMC-LLaMa (Wu et al., 2024) and BioMistral (Labrak et al., 2024), or proprietary models such as MedPaLM (Singhal et al., 2023b) and GPT-4 (Nori et al., 2023), to name but a few, have been reporting high-accuracy scores in a variety of Medical QA benchmarks (Singhal et al., 2023a,b; Xiong et al., 2024).

While these results constitute impressive progress, currently the Medical QA research field still presents a number of shortcomings. First, experimentation has been mostly focused on providing the correct answer in medical exams, usually in a multiple-choice setting. However, as doctors are also required to explain and argue about their predictions, research on Medical QA should also address the generation of argumentative explanations. Unfortunately, and to the best of our knowledge, no Medical QA dataset, that currently exists, includes correct and incorrect diagnoses enriched with natural language explanations written by medical doctors. Second, the large majority of Medical QA benchmarks are available only in English (Singhal et al., 2023a; Xiong et al., 2024), which makes it impossible to know the ability of current LLMs for Medical QA in other languages.

In this paper, we address these issues by presenting CasiMedicos-Arg, the first Multilingual (English, French, Italian, Spanish) dataset for Medical QA with manually annotated gold explanatory argumentation about incorrect and correct predictions written by medical doctors. More specifically, the corpus consists of 558 documents with reference gold doctors' explanations which are enriched with manual annotations for argument components (5021 claims and 2313 premises) and relations (2431 support and 1106 attack). This

new resource will make it possible, for the first time, to research not only on Argument Mining but also on generative techniques to argue about and explain predictions in Medical QA settings. Finally, strong baselines on argument component detection, a challenging sequence labelling task, using encoder (Devlin et al., 2019; He et al., 2021), encoder-decoder (García-Ferrero et al., 2024) and decoder-only LLMs (Jiang et al., 2023; Touvron et al., 2023) demonstrate the validity of our annotated resource. Data, code and fine-tuned models are publicly available (<https://github.com/ixa-ehu/antidote-casimedicos>).

2 Related Work

In this section, we will focus on reviewing datasets for Medical QA and on Explanatory Argumentation, the two main features of our main contribution, CasiMedicos- Arg.

2.1 Medical Question Answering

Several of the most popular Medical QA datasets (Jin et al., 2019; Abacha et al., 2019b,a; Jin et al., 2021; Pal et al., 2022) have been grouped into three multi-task English benchmarks, namely, MultiMedQA (Singhal et al., 2023a), MIRAGE (Xiong et al., 2024), and the Open Medical- LLM Leaderboard (Pal et al., 2024), with the aim of providing comprehensive experimental evaluation benchmarks of LLMs for Medical QA.

MultiMedQA includes MedQA (Jin et al., 2021), MedMCQA (Pal et al., 2022), PubMedQA (Jin et al., 2019), LiveQA (Abacha et al., 2019b), MedicationQA (Abacha et al., 2019a), MMLU clinical topics (Hendrycks et al., 2020) and HealthSearchQA (Singhal et al., 2023a). Except for the last one, all of them consist of a multiple-choice format and MedQA, MedMCQA and MMLU’s source data come from licensing medical exams. In terms of size, MedQA includes almost 15K questions, MedMCQA 187K while the rest of them are of more moderate sizes, namely, 500 QA pairs in PubMedQA, around 1200 in MMLU, 738 in LiveQA and 674 in MedicationQA.

While every dataset except MedQA and HealthSearchQA includes long form correct answers, they are not considered really usable for benchmarking LLMs because they were not optimally constructed as a ground-truth by medical doctors or professional clinicians (Singhal et al., 2023a).

The Open Medical- LLM Leaderboard also includes MedQA, MedMCQA, PubMedQA and MMLU clinical topics. General purpose LLMs such as GPT- 4 (Nori et al., 2023), PaLM (Chowdhery et al., 2022), LLaMa (Touvron et al., 2023) or Mistral (Jiang et al., 2023) report high- accuracy scores on these Medical QA benchmarks, although recently a number of specialized LLMs for the medical domain sometimes appear with even stronger performances. Some popular models include MedPaLM (Singhal et al., 2023a), MedPaLM- 2 (Singhal et al., 2023b), PMC- LLaMa (Wu et al., 2024), and more recently, BioMistral (Labrak et al., 2024).

The MIRAGE benchmark includes subsets of MedQA, MedMCQA, PubMedQA, MMLU clinical topics and adds the BioASQ- YN dataset (Tsatsaronis et al., 2015) with the aim of evaluating Retrieval Augmented Generation (RAG) techniques for LLMs in Medical QA tasks. According to the authors, their MEDRAG method not only helps to address the problem of hallucinated content by grounding the generation on specific contexts, but it also provides relevant up-to-date knowledge that may not be encoded in the LLM (Xiong et al., 2024). By employing MEDRAG, they are able to clearly improve the zero-shot results of some of the tested LLMs, although the results for others are rather mixed.

To summarize, no Medical QA dataset currently provides reference gold argumentative explanations regarding the incorrect and correct predictions. Furthermore, and with the exception of Vilares and Gómez-Rodríguez (2019), they have been mostly developed for English, leaving a huge gap regarding the evaluation of LLMs in Medical QA for other languages. Motivated by this we present CasiMedicos- Arg, the first Medical QA dataset including gold reference explanations which has been manually annotated with argumentative structures, including argument components (premises and claims) and their relations (support and attack).

2.2 Explanatory Argumentation in the Medical Domain

Explanatory argumentation in natural language refers to the process of generating or analyzing explanations within argumentative texts. In recent years, natural language explanation generation has gained significant attention due to the advancements of generative models that are leveraged to develop specialized explanatory systems. The need for explanation generation is also driven by the predominant use of non-transparent algorithms which lack interpretability, thus being unsuitable for sensitive domains such as medical.

Camburu et al. (2018) tackle the task of explanation generation by introducing an extension of the Stanford Natural Language Inference (SNLI) dataset (Bowman et al., 2015), which includes a new layer of annotations providing explanations for the entailment, neutrality, or contradiction labels. The generation of these explanations is addressed with a bi-LSTM encoder trained on the new e-SNLI dataset. e-SNLI (Camburu et al., 2018) is also exploited to generate explanations for a NLI method, which first generates possible explanations for predicted labels (Label-specific Explanations) and then takes a final label decision (Kumar and Talukdar, 2020). The authors use GPT- 2 (Radford et al., 2019) for label-specific generation and classify explanations with RoBERTa (Liu et al., 2019).

Narang et al. (2020) focus on generating complete explanations in natural language following a prediction step, utilizing a T5 model. The model is trained to predict both the label and the explanation. Li et al. (2021) also propose to generate explanations along with predicting NLI labels. The generation step is leveraged for

the question- answering task exploiting domain- specific or commonsense knowledge, while the NLI step allows to predict relations between a premise and a hypothesis. Kotonya and Toni (2024) propose a framework to rationalize explanations taking into account not only free- form explanations, but also argumentative explanations. Furthermore, authors provide metrics for explanation evaluation.

In the medical domain, Molinet et al. (2024) propose generating template- based explanations for medical QA tasks. Their system incorporates medical knowledge from the Human Phenotype Ontology, making the explanations more verifiable and sound for the medical domain. At the same time, quality assessment of medical explanations remains challenging, as the process of decision- making is not transparent. In this regard, Marro et al. (2023) propose a new methodology to evaluate reasons of explanations in clinical texts.

Despite the extensive research proposing various approaches to generate explanations, these approaches are not grounded on any argumentation model. This is particularly important in sensitive domains like medicine, where sound and well- founded explanations are essential to justify the taken decision. Moreover, medical explanations require verified medical knowledge at their core, which the described methods lack, as discussed in (Molinet et al., 2024).

3 CasiMedicos-Arg Annotation

The Spanish Ministry of Health yearly publishes the Resident Medical or Médico Interno Residente (MIR) licensing exams including the correct answer. Every year the CasiMedicos MIR Project (2.0)² takes the published exams by the ministry and provide gold explanatory arguments written by volunteer Spanish medical doctors to reason about the correct and incorrect options in the exam.

The Antidote CasiMedicos corpus consists of the original Spanish commented exams by the CasiMedicos doctors which were cleaned, structured and freely released for research purposes (Agerri et al., 2023). The original Spanish data was automatically translated and manually revised into English, French, and Italian. The corpus includes 622 documents each with a short clinical case, the multiple- choice questions and the explanations written by medical doctors.

In the rest of this section we describe the process of manually annotating argumentative structures in the raw Antidote CasiMedicos dataset.

3.1 Argumentation Annotation Guidelines

In line with the guidelines proposed by Mayer et al. (2021) for Randomized Controlled Trials (RCT) annotation, we identify two main argument components: Claims and Premises, and their relations, Support and Attack. Furthermore, we also propose to annotate Markers and labels specific to the medical domain,

namely, Disease, Treatment and Diagnostics. In the following, we define and describe the annotation of each label.

Claim is a concluding statement made by the author about the outcome of the study (Mayer et al., 2021):

1. The patient’s presenting picture is presumably erythema nodosum. (CasiMedicos)
2. We propose immunotherapy with thymoglobulin and cyclosporine as a proper treatment. (CasiMedicos)

Premise corresponds to an observation or measurement in the study, which supports or attacks another argument component, usually a claim. It is important that they are observed facts, therefore, credible without further evidence (Mayer et al., 2021):

1. In addition, pancytopenia is not observed. (CasiMedicos)
2. What is important is that the eye that has received the blow does not go up, and therefore there is double vision in the superior gaze. (CasiMedicos)

Analyzing the CasiMedicos dataset, we found certain ambiguity between claims and premises. Thus, statements representing general medical knowledge about a disease, symptoms, or treatments must be annotated as claims. Although these statements may support or attack the main claim, they are not premises since they do not involve case- specific evidence but represent medical facts:

[The patient’s presenting picture is presumably erythema nodosum]. [About 10% of cases of erythema nodosum are associated with inflammatory bowel disease, both ulcerative colitis and Crohn’s disease]. [As mentioned, in most cases, erythema nodosum has a self-limited course]. [When associated with inflammatory bowel disease, erythema nodosum usually resolves with treatment of the intestinal flare, and recurs with disease recurrences. Local measures include elevation of the legs and bed rest]. (CasiMedicos)

Here the first statement in square brackets represents a claim that asserts the patient’s diagnosis (erythema nodosum). The following ones represent information about the diagnosis, its symptoms and its possible treatment. They are not based on the evidences given in the case, but on general medical knowledge available to the doctor. Therefore, these examples should be annotated as Claims.

Additionally, long statements with multiple self- contained pieces of evidence must be divided into single premises to differentiate their relations to specific claims. For example, a given evidence in a sentence may support a claim while others may attack it. To preserve these distinctions, such sentences should be split into independent premises.

As well as Claims and Premises we annotate Markers - discourse markers that are relevant for arguments as they help to identify the spans of argument components and the type of argumentative relations. In the following examples markers are written in bold:

1. Other causes related to this picture are autoimmune diseases leading to transverse myelitis (Behmet's, FAS, SLE,...) or inflammatory diseases such as sarcoidosis, although our patient does not seem to meet the criteria for them. (CasiMedicos)
2. Although this usually gives a subacute or chronic picture. (CasiMedicos)

The possible answers proposed in the CasiMedicos multiple-choice options correspond to predicting a Disease, a Treatment or a Diagnosis. We decided to also annotate them as they help to identify the type of doctor's arguments (whether to look justification of a diagnosis or about a possible treatment) and the type of argumentative relations.

For advanced reasoning comprehension, we need to explore argumentative relations connecting argument components (claims and premises) and forming a structure of an argument (Mayer et al., 2021). Here we provide the definitions of support and attack relations, as well as real examples illustrating them.

Support. All statements or observations justifying the proposition of a target argument component are considered as supportive (Mayer et al., 2021):

In the examination there is a clear dissociation with thermoalgesic anesthesia and preservation of anthropokinetic and vibratory. [1] Reflexes are normal, neither abolished nor exalted. [2] In addition, the rest of the examination is strictly normal. [3] With all this I believe that the correct answer is 5, that is a syringomyelic lesion, whose initial characteristic is the sensitive dissociation with anesthesia for the thermoalgesic and conservation of the posterior chordal. (CasiMedicos)

This example provides premises (in italics) that justify a claim (bold) which they are related to. The supportive nature is highlighted by the marker *With all this I believe....*

Attack. An argument component is attacking another one if (i) it contradicts the proposition of a target component or (ii) it undercuts its implicit assumption of significance or relevance, for example, stating that the observations related to a target component are not significant or not relevant (Mayer et al., 2021):

1. It might be tempting to answer 3 Fracture of the superior wall of the orbit with entrapment of the superior rectus muscle. However, muscles trapped in a fracture do not automatically lose their muscular action. (CasiMedicos)
2. The palpebral hematoma and hyposphagma (subconjunctival hemorrhage) does not give us the key data. (CasiMedicos)

These examples represent premises (in italics) which either contradict their claims (bold) in Example 9 or which are not considered significant to justify or reject target components (Example 10).

3.2 CasiMedicos Real Case Example

In this section we demonstrate a real CasiMedicos case annotated with argument components - Premises (in

square brackets in italics) and Claims (in square brackets in bold), as well as Markers (M). We consider this case to be exemplary because its explanation includes reasons on why the correct answer is correct and why the incorrect answers are incorrect. We do not include argumentative relations for the sake of space and clarity.

QUESTION TYPE: PEDIATRICS CLINICAL CASE

[A woman comes to the office with her 3 year old daughter because she has detected a slight mammary development since 3 months without taking any medication or any relevant history.] Indeed, [the physical examination shows a Tanner stage IV, with no growth of pubic or axillary hair.] [The external genitalia are normal.] [Ultrasonography reveals a small uterus and radiology reveals a bone age of 3 years.] What attitude should be adopted?

- 1- [Follow-up every 3- 4 months, as this is a temporary condition that often resolves on its own.] 2-[Breast biopsy.] 3- [Mammography.] 4- [Administration of GnRh analogues.]

CORRECT ANSWER: 1

[It seems that they want to present us with precocious puberty (or premature telarche)] (M)but [they do not provide any analytical data] and [the ultrasound data are ambiguous] (we should assume that by a small uterus they are referring to a prepubertal uterus), (M)but [they do not provide any data on ovarian size]. [We are presented with the case of a three-year-old girl with advanced mammary development, in principle without any associated cause] ([in principle she does not take drugs that can increase the level of estrogen in the blood], [she does not seem to use body creams or eat a lot of chicken meat]). [If we follow the diagnostic scheme for a premature telarche or suspicion of precocious puberty, we request bone age and abdominal ultrasound] ([the EO is not advanced as in precocious puberty, and we assume that with a small uterus they mean a prepubertal uterus]); [according to the complementary examinations that we are given, it does not seem to be precocious puberty, except for the clinical (Tanner IV)]. [Strictly speaking, without analytical hormonal data, it seems that we could mark option 1, being necessary to follow the girl closely.] [If we take all the above data for granted, we could (M)rule out option 4, which would be the treatment of a central precocious puberty.] [Regarding the option of mammography, breast ultrasound is used in pediatrics, and in this case it would be indicated if we were told that there is breast asymmetry] ([we discard option 3]). [Regarding breast biopsy, it would only be indicated if there are warning signs.]

3.3 Annotation Process and Results

The annotation process consisted of three stages: training, reconciliation, and complete dataset annotation. During training, annotators worked on 10 CasiMedicos cases. We then calculated the inter-annotator agreement (IAA) results of the training phase to highlight weak spots, guideline flaws, and any issues in the

dataset needing further analysis.

At the reconciliation phase, the descriptions of Claim and Premise labels were discussed and agreed upon. After this, we started the complete dataset annotation. As mentioned earlier, the original CasiMedicos dataset included 622 medical cases, but 64 cases were excluded during the annotation phase. Some of them did not have gold explanations while others were cases with confusing relations: the correct answer is a wrong disease, treatment, or diagnosis as asked in a question, thus, it is attacked by its premises instead of being supported. Therefore, the final number of annotated cases is 558. In the following subsections, we present the IAA of the entire dataset (3.4), annotation results and their description (3.5).

3.3.1 Inter-Annotator Agreement (IAA)

The IAA is calculated over a random batch of 100 CasiMedicos cases. Since one instance (e.g. a claim) is usually an entire self-contained sentence, we measured the IAA at both the instance level and at the token level. In other words, we compute agreement over entire instances and over the tokens of each instance.

Table 1 illustrates the IAA at the instance level. Since instances are very long, annotators may be uncertain about which elements to include, leading to lower agreement scores for some labels. However, the major labels Claim and Premise have relatively good results with scores of 0.765 and 0.659, respectively. The mean F1 over all labels is 0.669.

Table 2 shows the IAA at the token level. Here we compute the agreement over tokens of each instance. The highest agreement score is of a Claim label being 0.915, while the lowest is of a Diagnostics label accounting for 0.638. The mean F1 over all tokens is 0.880.

Table 1: Instance-based F1 agreement.

Label	Mean F1
Claim	0.765
Premise	0.659
Marker	0.642
Disease	0.639
Treatment	0.586
Diagnostics	0.527

Table 2: Token-based F1 agreement.

Label	Mean F1
Claim	0.915
Premise	0.891
Marker	0.634
Disease	0.738
Treatment	0.777
Diagnostics	0.638

3.3.2 Annotation Results

In this part, we report the stats about label distribution over entire cases (documents) and the label distribution over the doctor’s explanations only. Additionally, we also discuss the distribution of argumentative relations.

Table 3 reports the total number of entities over the dataset and the average number of entities per case. Table 4 shows the label distributions only for the explanations, namely, the total number of entities in explanations and the average number of entities per explanation. In both tables, we notice that the discrepancy between the average number of claims per explanation and of premises per explanation is rather high. This may seem strange since premises are needed to accept or reject claims in order to complete one argumentation unit.

However, there are plausible reasons for such distribution. First, there is a certain number of cases where the explanation is based on the evidence from a doctor’s knowledge rather than clinical facts described in the case itself. Such explanations take into account the information given about the patient (e.g. age, symptoms, vital signs), but do not repeat any of these facts (as in Example 1 in Appendix A). Second, explanations that do not repeat evidence from the case are frequent, e.g. “Here we must suspect ... disease. All the symptoms fall perfectly within the picture”; “This is a fairly easy epidemiology question, in adults without other data, Pneumococcus is the 1st”). Last but not least, there is a group of cases with implicit premises or implicit warrants: the explanation presents claims (e.g. a conclusion about a disease and a treatment) implying that some evidences from the case text and implying certain medical knowledge to align evidences with a disease and a choice of treatment (as in Example 2 in Appendix A).

In Table 5 we present the distribution of argumentative relations. Support relations appear twice as much as Attack ones, making this argumentation pattern frequent and probably more convincing. In cases where the conclusion is made solely by excluding wrong propositions by attacking them, there is a lack of confidence about the claim.

As a result, we present CasiMedicos- Arg, a multi-layer argument-based annotation of the English version of CasiMedicos consisting of 558 clinical cases with explanations. In the following sections, we describe the experiments performed on argument component detection (claims and premises) to establish strong baselines on the task and validate our annotations.

Table 3: Label Distribution over Entire Cases.

Label	Total	Mean per case
Claim	5021	8.998
Premise	2313	4.145
Marker	1117	2.0
Disease	1791	3.21
Treatment	1278	2.29
Diagnostics	786	1.40

Table 4: Label Distribution in Explanations.

Label	Total	Mean per explanation
Claim	3003	5.948
Premise	470	0.935
Marker	974	1.833

Table 5: Distribution of Argumentative Relations.

Relation	Total	Mean per case
Support	2431	4.357
Attack	1106	1.982

4 Experimental Setup

We first describe the process of projecting the manually annotated argumentation labels from the source English data to the other three target languages, namely, French, Italian and Spanish. Since the annotators of the argument components were English speakers, we treated it as the source when projecting labels to the target languages. This process will result in the Multilingual CasiMedicos- Arg which will then be leveraged to produce strong baselines on argument component detection using a variety of LMs, including encoders (Devlin et al., 2019; He et al., 2021), encoder-decoders (Garcia- Ferrero et al., 2024) and decoder-only LLMs (Touvron et al., 2023; Jiang et al., 2023).

4.1 Multilingual CasiMedicos-Arg

Taking the manually annotated English CasiMedicos- Arg as a starting point, we first needed to project the annotations to Spanish (original text), French and Italian (revised translations) following the method described in Yeginbergenova and Agerri (2023); Yeginbergen et al. (2024). Second, and to ensure that the projection method correctly leveraged the annotations to the new data we additionally performed an automatic post-processing step of the newly generated data to correct any misalignments. Finally, to guarantee the quality of annotations and the validity of our evaluations, the translated and projected data is manually revised by native speakers.

Label projection is performed using word alignments calculated by AWESOME (Dou and Neubig, 2021) and Easy Label Projection (Garcia- Ferrero et al., 2022) to automatically map the word alignments into sequences (argument components) and project them from the source (English) to the target language (French, Italian and Spanish).

A particular feature of argument components is that the sequences could span over the entire length of the sentences. Therefore, after revising the automatically projected data, an extra post-processing step was performed by correcting the projections in the sequences where some annotations were placed incorrectly. The most common correction was fixing articles at the beginning of the argument components, which were sys-

tematically missed out during the automatic projection step. Other sequences were labeled only by half instead of the whole sequence. This post-processing step was essential to minimize human labor during manual correction. The number of corrections introduced during the post-processing step can be found in Appendix B.

The final manual correction step involved checking the translation quality and projected labels by native expert annotators fixing any misprojections or errors in the translation. The result of this process is the Multilingual CasiMedicos- Arg dataset, obtained by projecting the manual annotations from English to Italian, French and Spanish.

4.2 Sequence Labelling with LLMs

We leverage Multilingual CasiMedicos- Arg to perform cross-lingual and multilingual argument component detection, a task that, due to the heterogeneity and length of the sequences, is usually a rather challenging task (Stab and Gurevych, 2017; Eger et al., 2018; Yeginbergenova and Agerri, 2023). Furthermore, in addition to classic encoder-only models like mBERT (Devlin et al., 2019) and mDeBERTa (He et al., 2021), we decided to also perform the task using encoder-decoder and decoder-only models. For the encoder-decoder category, we chose two variants of Medical mT5, a multilingual text-to-text model adapted to multilingual medical texts: med-mT5-large and med-mT5-large-multitask (García-Ferrero et al., 2024). For the decoder-only architecture, we selected the LLaMa-2 (Touvron et al., 2023) and Mistral (Jiang et al., 2023) models with 7B parameters. The domain-specific versions of these models produced less promising results, so we opted to report the results of the aforementioned models.

5 Results and Discussion

Due to space constraints, we focus on the main results for argument component detection. The detailed table (Table 7) is presented in the appendix. We conducted three types of experiments: monolingual data-transfer, multilingual data-transfer, and cross-lingual model-transfer. The results are evaluated using F1-score (macro average) for the detection of claims and premises.

The main observations from the results (Table 7) are: (i) In the monolingual setting, Mistral (81.55 avg. F1) and the Medical mT5 models (around 80.5 avg. F1) perform best. (ii) In the multilingual setting, Mistral again shows the best overall performance (81.97 avg. F1), slightly outperforming its monolingual result. (iii) Cross-lingual model transfer yields significantly lower results, with the best average being 79.28 from med-mT5-large. (iv) For cross-lingual model transfer the best results are obtained by the Medical mT5 models, which may be due to this model being trained on multilingual medical data (García-Ferrero et al., 2024).

Summarizing, in this section we present competitive baselines for argument component detection on

Table 6: F1-scores and their standard deviations of data-transfer (monolingual and multilingual), and cross-lingual model-transfer experiments using Spanish, French, and Italian data; bold: best overall result; underlined: best result per model across the three language settings.

Model	Spanish	French	Italian	Avg.
monolingual data-transfer				
mBERT	75.39(0.49)	73.66(0.66)	74.78(0.59)	74.61
mDeBERTa	77.39(0.83)	76.35(0.29)	76.98(0.76)	76.91
med-mT5-large	80.79(0.19)	80.12(0.59)	80.32(0.04)	80.41
med-mT5-large-multitask	80.69(0.65)	80.13(0.56)	80.70(0.08)	80.51
LLaMa2-7B	80.39(0.52)	80.89(0.54)	80.69(0.46)	80.66
Mistral0.1-7B	81.71(0.29)	81.38(0.52)	81.56(0.44)	81.55
multilingual data-transfer				
mBERT	75.08(0.89)	74.92(0.62)	74.95(1.38)	74.98
mDeBERTa	76.06(1.42)	76.22(0.89)	77.06(0.65)	76.45
med-mT5-large	82.07(0.12)	80.85(0.26)	80.89(0.72)	81.27
med-mT5-large-multitask	82.09(0.26)	80.83(0.28)	80.57(0.49)	81.16
LLaMa2-7B	81.56(0.28)	81.03(0.49)	81.16(0.20)	81.25
Mistral0.1-7B	82.40(0.12)	82.10(0.33)	81.41(0.69)	81.97
cross-lingual model-transfer				
mBERT	72.75(0.24)	71.47(1.27)	72.49(0.09)	72.24
mDeBERTa	76.05(0.14)	74.63(0.53)	75.22(0.32)	75.30
med-mT5-large	79.91(1.26)	78.51(1.20)	79.41(0.87)	79.28
med-mT5-large-multitask	79.81(0.83)	77.96(0.13)	77.07(0.34)	78.28
LLaMa2-7B	75.31(0.68)	68.56(1.07)	73.86(0.51)	72.58
Mistral0.1-7B	79.27(0.42)	70.62(7.37)	78.36(0.37)	76.08

CasiMedicos- Arg, validating both the manual annotations and the strategy of projecting English labels to other languages to facilitate the application of cross-lingual and multilingual techniques.

6 Conclusion

In this paper, we present CasiMedicos- Arg, a multilingual (French, English, Italian and Spanish) Medical QA dataset including gold reference explanations written by medical doctors which has been annotated with argumentative structures. This dataset aims to bridge a glaring gap in the Medical QA ecosystem by facilitating the evaluation of explanations generated to argue or justify a given prediction.

The final dataset includes 558 documents (parallel in four languages) with reference gold doctors' explanations which are enriched with manual annotations for argument components (5021 claims and 2313 premises) and relations (2431 support and 1106 attack).

Both inter- annotator agreement results and the baselines provided for argument component detection demonstrate the validity of our annotations.

Furthermore, experiments show the advantage of performing argument component detection from a multilingual data- transfer perspective.

7 Limitations

We consider two main limitations in our work that we would like to address in the short term future. First, the choice of languages. We would have liked to include languages from different language families and with different morphological and grammatical characteristics, but we were limited by the native expertise available to us to perform the manual corrections of the projected

labels and translations. Second, the size of the dataset (558 documents) could be larger.

Regarding the first limitation, we still think that our experiments demonstrate the superiority of performing multilingual data- transfer over crosslingual model transfer, at least with the LLMs currently available. With respect to the size of the dataset, we would like to point out that its size is similar to other datasets reviewed in Section 2, which are being widely used to benchmark LLMs for Medical QA.

Another issue worth considering in the future is the need to further research the generation of explanations for the predictions while taking into account a crucial unsolved issue, namely, the evaluation explanation generation in the highly specialized medical domain.

Acknowledgments

We thank the CasiMedicos Proyecto MIR 2.0 for their permission to share their data for research purposes. This work has been supported by the French government, through the 3IA Côte d'Azur Investments in the Future project managed by the National Research Agency (ANR) with the reference number ANR-19- P3IA- 0002. This work has also been supported by the CHIST- ERA grant of the Call XAI 2019 of the ANR with the grant number Project- ANR- 21- CHR4- 0002. We are also thankful to several MCIN/AEI/10.13039/501100011033 projects: (i) Antidote (PCI2020- 120717- 2), and by European Union NextGenerationEU/PRTR; (ii) DeepKnowledge (PID2021- 127777OB- C21) and ERDF A way of making Europe; (iii) DeepMinor (CNS2023- 144375) and European Union NextGenerationEU/PRTR. We also thank the European High Performance Computing Joint Undertaking (EuroHPC Joint Undertaking, EXT-2023E01- 013) for the GPU hours. Anar Yeginbergen's PhD contract is part of the PRE2022- 105620 grant, financed by MCIN/AEI/10.13039/501100011033 and by the FSE+.

Appendix A: CasiMedicos Real Cases

Example 1:

QUESTION TYPE: DERMATOLOGY CLINICAL CASE:

A 62- year- old man with a history of significant alcohol abuse, carrier of hepatitis C virus, treated with Ibuprofen for tendinitis of the right shoulder, goes to his dermatologist because after spending two weeks on vacation at the beach he notices the appearance of tense blisters on the dorsum of his hands. On examination, in addition to localization and slight malar hypertrichosis. The most likely diagnosis is:

- 1- Epidermolysis bullosa acquisita. 2- Porphyria cutanea tarda. 3- Phototoxic reaction. 4- Contact dermatitis. 5- Acute intermittent porphyria.

CORRECT ANSWER: 2

Porphyria Cutanea Tarda: 60% of patients with PCT are male, many of them drink alcohol in excess, women who develop it are usually treated with drugs containing estrogens. Most are males with signs of iron overload, this overload reduces the activity of the enzyme uroporphyrinogen decarboxylase, which leads to the elevation of uroporphyrins. HCV and HIV infections have been implicated in the precipitation of acquired PCT. There is a hereditary form with AD pattern. Patients with PCT present with blistering of photoexposed skin, most frequently on the dorsum of the hands and scalp. In addition to fragility, they may develop hypertrichosis, hyperpigmentation, cicatricial alopecia and sclerodermal induration.

Example 2:

QUESTION TYPE: PEDIATRICS CLINICAL CASE:

6- month- old infant presenting to the emergency department for respiratory distress. Examination: axillary temperature 37.2°C respiratory rate 40 rpm, heart rate 160 bpm, blood pressure 90 / 45 mmHg , SatO₂ 95% on room air. He shows moderate respiratory distress with intercostal and subcostal retraction. Pulmonary auscultation: scattered expiratory rhonchi, elongated expiration and slight decrease in air entry in both lung fields. Cardiac auscultation: no murmurs. It is decided to keep the patient under observation in the hospital for a few hours. What do you consider the most appropriate attitude at this time with regard to the complementary tests?

- 1- Request venous blood gas, leukocyte count and acute phase reactants.
- 2- Request chest X- ray.
- 3- Request arterial blood gases and acute phase reactants.
- 4- Do not request complementary tests.

CORRECT ANSWER: 4

The patient probably presents with bronchiolitis. At this stage, no additional tests should be performed unless there is a clinical worsening.

Appendix B: Number of corrections after annotation projection

The number of corrections required after automatically projecting the annotations.

References

- [1] Asma Ben Abacha, Yassine Mrabet, Mark Sharp, Travis R Goodwin, Sonya E Shooshan, and Dina Demner- Fushman. 2019a. Bridging the Gap Between Consumers' Medication Questions and Trusted Answers. In MedInfo, pages 25- 29.
- [2] Asma Ben Abacha, Chaitanya Shivade, and Dina Demner- Fushman. 2019b. Overview of the MEDIQA 2019 Shared Task on Textual Inference, Question Entailment and Question Answering. In

Table 7: Number of corrections introduced in the postprocessing step after automatic label projection.

Set (Language)	Number of corrections
Train (ES)	450
Test (ES)	153
Dev (ES)	64
Train (FR)	378
Test (FR)	109
Dev (FR)	49
Train (IT)	336
Test (IT)	117
Dev (IT)	55

Proceedings of the 18th BioNLP Workshop and Shared Task, pages 370- 379.

- [3] Rodrigo Agerri, Inigo Alonso, Aitziber Atutxa, Ander Berondo, Ainara Estarrona, Iker Garcia- Ferrero, Iakes Goenaga, Koldo Gojenola, Maite Oronoz, Igor Perez- Tejedor, German Rigau, and Anar Yeginbergenova. 2023. Hitz@antidote: Argumentationdriven explainable artificial intelligence for digital medicine. In SEPLN 2023: 39th International Conference of the Spanish Society for Natural Language Processing.
- [4] Samuel R Bowman, Gabor Angeli, Christopher Potts, and Christopher D Manning. 2015. A large annotated corpus for learning natural language inference. In EMNLP.
- [5] Oana- Maria Camburu, Tim Rocktaschel, Thomas Lukasiewicz, and Phil Blunsom. 2018. e- snli: Natural language inference with natural language explanations. In NeurIPS.
- [6] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam M. Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Benton C. Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur- Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathleen S. Meier- Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. 2022. Palm: Scaling language modeling with pathways. J. Mach. Learn. Res., 24:240:1- 240:113.

- [7] Jacob Devlin, Ming- Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre- training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171- 4186.
- [8] Zi- Yi Dou and Graham Neubig. 2021. Word alignment by fine- tuning embeddings on parallel corpora.
- [9] Steffen Eger, Johannes Daxenberger, Christian Stab, and Iryna Gurevych. 2018. Cross- lingual argumentation mining: Machine translation (and a bit of projection) is all you need! In Proceedings of the 27th International Conference on Computational Linguistics, pages 831- 844, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- [10] Iker Garcia- Ferrero, Rodrigo Agerri, and German Rigau. 2022. Model and data transfer for cross- lingual sequence labelling in zero- resource settings. In Findings of EMNLP.
- [11] Iker Garcia- Ferrero, Rodrigo Agerri, Aitziber Atutxa Salazar, Elena Cabrio, Iker de la Iglesia, Alberto Lavelli, Bernardo Magnini, Benjamin Molinet, Johana Ramirez- Romero, German Rigau, Jose Maria Villa- Gonzalez, Serena Villata, and Andrea Zannello. 2024. Medical mT5: An Open- Source Multilingual Text- to- Text LLM for The Medical Domain. In Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LRECOLING).
- [12] Lakes Goenaga, Aitziber Atutxa, Koldo Gojenola, Maite Oronoz, and Rodrigo Agerri. 2024. Explanatory argument extraction of correct answers in resident medical exams. Artificial Intelligence in Medicine.
- [13] Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2021. Debertav3: Improving deberta using electra- style pretraining with gradient1- disentangled embedding sharing. arXiv preprint arXiv:2111.09543.
- [14] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2020. Measuring massive multitask language understanding. In ICLR 2020.
- [15] Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. arXiv preprint arXiv:2310.06825.
- [16] Di Jin, Eileen Pan, Nassim Oufattolle, Wei- Hung Weng, Hanyi Fang, and Peter Szolovits. 2021. What disease does this patient have? a large- scale open domain question answering dataset from medical exams. Applied Sciences, 11(14):6421.
- [17] Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William Cohen, and Xinghua Lu. 2019. PubMedQA: A dataset for biomedical research question answering. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP- IJCNLP), pages 2567- 2577. Association for Computational Linguistics.
- [18] Neema Kotonya and Francesca Toni. 2024. Towards a framework for evaluating explanations in automated fact verification. In Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LRECOLING 2024), pages 16364- 16377, Torino, Italia. ELRA and ICCL.
- [19] Sawan Kumar and Partha Talukdar. 2020. NILE : Natural language inference with faithful natural language explanations. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 8730- 8742.
- [20] Yanis Labrak, Adrien Bazoge, Emmanuel Morin, Pierre- Antoine Gourraud, Mickael Rouvier, and Richard Dufour. 2024. Biomistral: A collection of open- source pretrained large language models for medical domains. In ACL.
- [21] Dongfang Li, Jingcong Tao, Qingcai Chen, and Baotian Hu. 2021. You can do better! if you elaborate the reason when making prediction. arXiv preprint arXiv:2103.14919.
- [22] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692.
- [23] Santiago Marro, Theo Alkiabides Collias, Elena Cabrio, and Serena Villata. 2023. On the automatic assessment of natural language expert explanations in medicine. In HC@AIxIA, pages 83- 98.
- [24] Tobias Mayer, Santiago Marro, Elena Cabrio, and Serena Villata. 2021. Enhancing evidence- based medicine with natural language argumentative analysis of clinical trials. Artificial Intelligence in Medicine, 118:102098.
- [25] Benjamin Molinet, Santiago Marro, Elena Cabrio, and Serena Villata. 2024. Explanatory argumentation in natural language for correct and incorrect medical diagnoses. Journal of Biomedical Semantics, 15.
- [26] Sharan Narang, Colin Raffel, Katherine Lee, Adam Roberts, Noah Fiedel, and Karishma Malkan. 2020. Wt5?! training text- to- text models to explain their predictions. arXiv preprint arXiv:2004.14546.



- [27] Harsha Nori, Nicholas King, Scott Mayer McKinney, Dean Carignan, and Eric Horvitz. 2023. Capabilities of gpt- 4 on medical challenge problems. arXiv preprint arXiv:2303.13375.
- [28] Ankit Pal, Pasquale Minervini, Andreas Geert Motzfeldt, Aryo Pradipta Gema, and Beatrice Alex. 2024. open- life-scienceai/open_medical_llm.leaderboard. https://huggingface.co/spaces/openlifescienceai/open__medical__llm__leaderboard.
- [29] Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. 2022. MedMCQA: A large- scale multi- subject multi- choice dataset for medical domain question answering. In Conference on Health, Inference, and Learning, pages 248- 260. PMLR.
- [30] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. OpenAI blog, 1(8):9.
- [31] Conrad W Safranek, Anne Elizabeth Sidamon-Eristoff, Aidan Gilson, and David Chartash. 2023. The role of large language models in medical education: Applications and implications. JMIR Med Educ, 9:e50945.
- [32] Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfahl, et al. 2023a. Large language models encode clinical knowledge. Nature, 620(7972):172- 180.
- [33] Karan Singhal, Tao Tu, Juraj Gottweis, Rory Sayres, Ellery Wulczyn, Le Hou, Kevin Clark, Stephen Pfahl, Heather Cole- Lewis, Darlene Neal, et al. 2023b. Towards expert- level medical question answering with large language models. arXiv preprint arXiv:2305.09617.
- [34] Christian Stab and Iryna Gurevych. 2017. Parsing argumentation structures in persuasive essays. Computational Linguistics, 43(3):619- 659.
- [35] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenjin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie- Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Bin Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharani Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. Llama 2: Open foundation and fine- tuned chat models. Preprint, arXiv:2307.09288.
- [36] George Tsatsaronis, Georgios Balikas, Prodromos Malakasiotis, Ioannis Partalas, Matthias Zschunke, Michael R Alvers, Dirk Weissenborn, Anastasia Krithara, Sergios Petridis, Dimitris Polychronopoulos, et al. 2015. An overview of the bioasq large- scale biomedical semantic indexing and question answering competition. BMC bioinformatics, 16:1- 28.
- [37] David Vilares and Carlos Gomez- Rodriguez. 2019. HEAD- QA: A Healthcare Dataset for Complex Reasoning. In Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pages 960- 966, Florence, Italy. Association for Computational Linguistics.
- [38] Shuhe Wang, Xiaofei Sun, Xiaoya Li, Rongbin Ouyang, Fei Wu, Tianwei Zhang, Jiwei Li, and Guoyin Wang. 2023. Gpt- ner: Named entity recognition via large language models. arXiv preprint arXiv:2304.10428.
- [39] Chaoyi Wu, Weixiong Lin, Xiaoman Zhang, Ya Zhang, Yanfeng Wang, and Weidi Xie. 2024. PMC- LLaMA: Towards Building Open- source Language Models for Medicine. Journal of the American Medical Informatics Association: JAMIA.
- [40] Guangzhi Xiong, Qiao Jin, Zhiyong Lu, and Aidong Zhang. 2024. Benchmarking retrieval- augmented generation for medicine. In ACL.
- [41] Anar Yeginbergen, Maite Oronoz, and Rodrigo Agerri. 2024. Argument mining in data scarce settings: Cross- lingual transfer and few- shot techniques. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 11687- 11699.
- [42] Anar Yeginbergenova and Rodrigo Agerri. 2023. Cross- lingual argument mining in the medical domain. Procesamiento del Lenguaje Natural, 73.

