DSA through C++

Introduction to Heap

Mohammad Tasin (Tasin Coder)

Agenda

- Complete Binary Tree
- Almost Complete Binary Tree
- Introduction to Heap
- Insertion in heap
- Deletion in heap
- Heap sort

Complete Binary Tree

- **All levels must be completely filled called Complete Binary Tree.**



Almost Complete Binary Tree

- **All level must be completely filled except possibly the last level and all the nodes in the last level must be left aligned.**



Introduction to Heap

- Heap is a data structure.
- Heap is used in a sorting algorithm known as heap sort.
- Heap must be an almost complete binary tree.
- Heap are of two types :-
  - Max Heap (default).
  - Min Heap.

- A heap is a specialized tree-based data structure that satisfies the heap property.
- Heaps are commonly used to implement priority queues and are often used in algorithms that require quick access to the maximum or minimum element in a collection.
- The heap property depends on whether it is a max heap or a min heap.
- The value at Node is greater than or equal to value at each children of Node

Heap Properties

- **Root Node** का **value** आपके **children** से बड़ा या बराबर होना चाहिए।
- इसमें **duplicate value allow** है |

If(N_0 >= N_1 && N_0 >= N_2)



Max Heap

If(N_0 <= N_1 && N_0 <= N_2)



Min Heap

Heap Representation

0	1	2	3	4	5	6
100	80	70	40	60	50	30



80 10 20 50 90 30



How to Find Parent or child Node



0	1	2	3	4	5	6
100	80	70	40	60	50	30

- **How to find index of child Node?**

  index of left child = 2*index+1

  index of right child = 2*index+2

- **How to find index of parent node?**

index of Parent node of N = $\frac{(\text{index} - 1)}{2}$

Insertion in heap

0	1	2	3	4	5	6
40	70	25	60	80	20	50

0	1	2	3	4	5	6
80	70	25	40	60		

Heap = 0 1 2 3 4 5



temp

Deletion in heap

0	1	2	3	4	5	6
60	40	25				



Heap = 3

temp

Heap Sort

- **Delete values from the heap (Max - heap) and store them in an array from right to left.**
- **As a result, at the end of deleting all the elements of heap, array becomes sorted.**