

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT on

Machine Learning (23CS6PCMAL)

Submitted by

S M MRUNALINI (1BM22CS228)

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

Sep-2024 to Jan-2025

B.M.S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “Machine Learning (23CS6PCMAL)” carried out by **S M Mrunalini(1BM22CS228)**, who is a bonafide student of **B.M.S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum. The Lab report has been approved as it satisfies the academic requirements in respect of an Machine Learning (23CS6PCMAL) work prescribed for the said degree.

Saritha A N
Assistant Professor
Department of CSE , BMSCE

Dr. Kavitha Sooda
Professor & HOD
Department of CSE , BMSCE

Index

Sl. No.	Date	Experiment Title	Page No.
1	3-3-2025	Write a python program to import and export data using Pandas library functions	4
2	9-3-2025	Demonstrate various data pre-processing techniques for a given dataset	8
3	17-3-2025	Implement Linear and Multi-Linear Regression algorithm using appropriate dataset	10
4	17-3-2025	Build Logistic Regression Model for a given dataset	13
5	24-3-2025	Use an appropriate data set for building the decision tree (ID3) and apply this knowledge to classify a new sample.	16
6	7-4-2025	Build KNN Classification model for a given dataset.	19
7	7-4-2025	Build Support vector machine model for a given dataset	22
8	21-4-2025	Implement Random forest ensemble method on a given dataset.	24
9	21-4-2025	Implement Boosting ensemble method on a given dataset.	25
10	21-4-2025	Build k-Means algorithm to cluster a set of data stored in a .CSV file.	27
11	21-4-2025	Implement Dimensionality reduction using Principal Component Analysis (PCA) method.	28


Github Link:

<https://github.com/Mrunalinishettar/ml-lab>


Program 1

Write a python program to import and export data using Pandas library functions


Screenshots:



Scanned with OKEN Scanner



Scanned with OKEN Scanner



Scanned with OKEN Scanner

Code:

```
import pandas as pd
data = {
    'Name': ['Alice', 'Bob', 'Charlie', 'David'],
    'Age': [25, 30, 35, 40],
    'City': ['New York', 'Los Angeles', 'Chicago', 'Houston']
}
df = pd.DataFrame(data)
print("Sample data:")
print(df.head())
from sklearn.datasets import load_iris
iris = load_iris()
df = pd.DataFrame(iris.data, columns=iris.feature_names)
df['target'] = iris.target
print("Sample data:")
print(df.head())
file_path = 'data.csv'
df = pd.read_csv(file_path)
print("Sample data:")
print(df.head())
print("\n")
file_path = 'mobiles-dataset-2025.csv'
```

```
df = pd.read_csv(file_path, encoding='latin-1') # or 'cp1252' or other suitable encoding
print("Sample data:")
print(df.head())
import pandas as pd
```

```
data = {
'USN': ['IS001','IS002','IS003','IS004','IS005'],
'Name': ['Alice', 'Bob', 'Charlie', 'David','Eve'],
'Marks': [25, 30, 35, 40,45]
}
```

```
df = pd.DataFrame(data)
print("Sample data:")
print(df.head())
from sklearn.datasets import load_diabetes
iris = load_diabetes()
df = pd.DataFrame(iris.data, columns=iris.feature_names)
```

```
print("Sample data:")
print(df.head())
```

```
file_path = 'sample_sales_data.csv'
df = pd.read_csv(file_path)
print("Sample data:")
print(df.head())
print("\n")
```

```
df = pd.read_csv("/content/dataset-of-diabetes .csv",encoding='latin-1')
print("Sample data:")
print(df.head())
print("\n")
```

```
df=pd.read_csv('sample_sales_data.csv')
print("Sample data:")
print(df.head())
```

```
df.to_csv('output.csv',index=False)
print("Data saved to output.csv")
sales_df=pd.read_csv('sample_sales_data.csv')
print("Sample data:")
print(sales_df.head())
sales_by_region=sales_df.groupby('Region')['Sales'].sum()
print("\nTotal sales by region:")
print(sales_by_region)
best_selling_products
=sales_df.groupby('Product')['Quantity'].sum().sort_values(ascending=False) print("\nBest-selling
products by quantity:")
print(best_selling_products)
sales_by_region.to_csv('sales_by_region.csv')
best_selling_products.to_csv('best_selling_products.csv')
print("Data saved to sales_by_region.csv and best_selling_products.csv")
```

```
import yfinance as yf
import matplotlib.pyplot as plt
tickers = ["RELIANCE.NS", "TCS.NS", "INFY.NS"]
data = yf.download(tickers, start="2022-10-01", end="2023-10-01",
group_by='ticker')
print("First 5 rows of the dataset:")
print(data.head())
print("\nShape of the dataset:")
print(data.shape)
print("\nColumn names:")
print(data.columns)
print("\n")
reliance_data = data['RELIANCE.NS']
print("\nSummary statistics for Reliance Industries:")
print(reliance_data.describe())
reliance_data['Daily Return'] = reliance_data['Close'].pct_change()
print("\n")
plt.figure(figsize=(12, 6))
plt.subplot(2, 1, 1)
reliance_data['Close'].plot(title="Reliance Industries - Closing Price")
```



```

plt.subplot(2, 1, 2)
reliance_data['Daily Return'].plot(title="Reliance Industries - Daily Returns", color='orange')
plt.tight_layout()
plt.show()
reliance_data.to_csv('reliance_stock_data.csv')

```

```

tickers = ["HDFCBANK.NS", "ICICI.NS", "KOTAKBANK.NS"]
data = yf.download(tickers, start="2024-01-01", end="2024-12-30",
group_by='ticker')
print("First 5 rows of the dataset:")
print(data.head())
print("\nShape of the dataset:")
print(data.shape)
print("\nColumn names:")
print(data.columns)
print("\n")
reliance_data = data['HDFCBANK.NS']
print("\nSummary statistics for Reliance Industries:")
print(reliance_data.describe())
reliance_data['Daily Return'] = reliance_data['Close'].pct_change()
print("\n")
plt.figure(figsize=(12, 6))
plt.subplot(2, 1, 1)
reliance_data['Close'].plot(title="HDFC Industries - Closing Price")
plt.subplot(2, 1, 2)
reliance_data['Daily Return'].plot(title="HDFC Industries - Daily Returns", color='red')
plt.tight_layout()
plt.show()
reliance_data.to_csv('hdfc_stock_data.csv')
print("\nhdfc stock data saved to 'hdfc_stock_data.csv'.")

```

```

tickers = ["HDFCBANK.NS", "ICICIBANK.NS", "KOTAKBANK.NS"]
data = yf.download(tickers, start="2024-01-01", end="2024-12-30",
group_by='ticker')
print("First 5 rows of the dataset:")
print(data.head())
print("\nShape of the dataset:")
print(data.shape)
print("\nColumn names:")
print(data.columns)
print("\n")
reliance_data = data['ICICIBANK.NS']
print("\nSummary statistics for ICICI Industries:")
print(reliance_data.describe())
reliance_data['Daily Return'] = reliance_data['Close'].pct_change()
print("\n")
plt.figure(figsize=(12, 6))
plt.subplot(2, 1, 1)
reliance_data['Close'].plot(title="ICICI Industries - Closing Price")
plt.subplot(2, 1, 2)
reliance_data['Daily Return'].plot(title="ICICI Industries - Daily Returns", color='BLACK')
plt.tight_layout()

```

```
plt.show()
reliance_data.to_csv('icici_stock_data.csv')
print("\nicici stock data saved to 'icici_stock_data.csv'.")
```

```
tickers = ["HDFCBANK.NS", "ICICI.NS", "KOTAKBANK.NS"]
data = yf.download(tickers, start="2024-01-01", end="2024-12-30",
group_by='ticker')
print("First 5 rows of the dataset:")
print(data.head())
print("\nShape of the dataset:")
print(data.shape)
print("\nColumn names:")
print(data.columns)
print("\n")
reliance_data = data['KOTAKBANK.NS']
print("\nSummary statistics for Reliance Industries:")
print(reliance_data.describe())
reliance_data['Daily Return'] = reliance_data['Close'].pct_change()
print("\n")
plt.figure(figsize=(12, 6))
plt.subplot(2, 1, 1)
reliance_data['Close'].plot(title="KOTAK Industries - Closing Price")
plt.subplot(2, 1, 2)
reliance_data['Daily Return'].plot(title="kotak Industries - Daily Returns", color='red')
plt.tight_layout()
plt.show()
reliance_data.to_csv('kotak_stock_data.csv')
print("\nkotak stock data saved to 'kotak_stock_data.csv'.")
```

Program 2

Demonstrate various data pre-processing techniques for a given dataset

Screenshot:

ad-hut

Index (['longitude', 'latitude', 'housing-median-age', 'total_rooms', 'total_rooms', 'population', 'household', 'median-income', 'median-house-value', 'ocean-proximity'])

Column Information:

Data Column	non-null Count	Byte
longitude	20640 non-null	Float 64
latitude	20640 non-null	Float 64
housing-median-age	20640 non-null	Float 64
ocean-proximity	20640 non-null	Object

Statistical Summary

	longitude	latitude	housing-median-age	population
Count	20640.0000	20640.0000	20640.0000	20640.0000
mean	-119.5697	35.6318	38.6314	2635.54
std	2.0035	2.1259	18.5843	2.18153
min	-134.3000	3.7900	15.0000	144.7503
max	-114.3000	37.3000	78.100	277.7400

Scanned with OKEN Scanner

Demonstrating Various data pre-processing techniques for

1) Data cleaning: Handling missing values, Handling categorical data, handling outliers

2) Data Transformation: min-max scaler / Normalization, Standardization, Scaling

3) Housing dataset

4) Column information (i) Statistical Summary of columns
(ii) Unique values in Ocean proximity column
(iii) Columns with missing values

Code: In Jupyter Notebook

```
housing_df = pd.read_csv('data/housing.csv')  
Print ("Column Information")  
Print (housing_df.info())  
Print ("\n Statistical Summary:")  
Print (housing_df.describe())  
Print ("\n Unique values in 'Ocean proximity':")  
Print (housing_df['ocean proximity'].value_counts())  
Print ("\n Columns with missing values:")  
Print (housing_df.isnull().sum())
```

Scanned with OKEN Scanner

unique values in 'ocean proximity'

ocean proximity

1. Ocean 9136

Inland 6551

Near Ocean 2658

Near Bay 2290

Island 5

dtype: int

Columns with missing values

longitude 0

latitude 0

housing-median-age 0

ocean proximity 0

dtype: int

Scanned with OKEN Scanner

1) Which column in dataset had missing values?
How did you handle them?

- Adult Income dataset (adult.csv)
no columns had missing values
- Diabetes dataset (Diabetes of diabetes.csv)
no columns had missing values
- handling threshold since no missing value were found, no imputation has performed

2) Which categorical column did you identify in dataset? How did you encode them?

Adult Income Dataset (adult.csv)

→ Categorical columns

- Workclass
- Education
- occupation
- race
- gender
- income
- relationship

Scanned with OKEN Scanner

3) Python code to implement the following data preprocessing techniques for Diabetes & adult income dataset.

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt


df = pd.read_csv('data/diabetes.csv')
df.head(100)

df = pd.read_csv('data/adult_data.csv')
df.head(10)

import numpy as np
# Introduce some missing values for demonstration
df.loc[5, 'AGE'] = np.nan
df.loc[9, 'BMR'] = np.nan
df.head(10)
```

	Index	No. Patient	Gender	Age	Wage	CX	BMR	clat3
0	502	17975	F	50.0	4.7	46	NaN	N
1	412	47975	M	43.0	4.5	62	0.17313	N
2	327	87656	F	32.0	4.2	72	0.17313	N
3	634	67643	M	NaN	4.7	2.3	0.49	N

Scanned with OKEN Scanner



Scanned with OKEN Scanner

Code:

```
from google.colab import files
diabetes=files.upload()
```

```
from google.colab import files
adult_income=files.upload()
```

```
df1=pd.read_csv("Dataset of Diabetes .csv")
df1.head()
```

```
df2=pd.read_csv("adult.csv")
df2.head()
```

```
df1.info()
df2.info()
```

```

df1.describe()
df2.describe()

missing_values1 = df1.isnull().sum()
print(missing_values1)
missing_values2 = df2.isnull().sum()
print(missing_values2)

df1['Gender'] = df1['Gender'].replace('f', 'F')
ordinal_encoder = OrdinalEncoder(categories=[["F", "M"]])
df1["Gender_Encoded"] = ordinal_encoder.fit_transform(df1[["Gender"]])
onehot_encoder = OneHotEncoder()
encoded_data = onehot_encoder.fit_transform(df1[["CLASS"]])
encoded_array = encoded_data.toarray()
encoded_df = pd.DataFrame(encoded_array, columns=onehot_encoder.get_feature_names_out(["CLASS"]))
df_encoded = pd.concat([df1, encoded_df], axis=1)
df1 = pd.concat([df1, encoded_df], axis=1)
df1.drop("CLASS", axis=1, inplace=True)
df1.drop("Gender", axis=1, inplace=True)
print(df2.head())
from sklearn.preprocessing import OrdinalEncoder, OneHotEncoder
df_copy2 = df2
ordinal_encoder = OrdinalEncoder(categories=[["Male", "Female"]])
df_copy2["Gender_Encoded"] = ordinal_encoder.fit_transform(df_copy2[["gender"]])
print(df_copy2[["gender", "Gender_Encoded"]])

onehot_encoder = OneHotEncoder()
encoded_data =
onehot_encoder.fit_transform(df2[["occupation", "workclass", "education", "marital-status", "relationship", "race", "
native-country", "income"]])
encoded_array = encoded_data.toarray()
encoded_df = pd.DataFrame(encoded_array,
columns=onehot_encoder.get_feature_names_out(["occupation", "workclass", "education", "marital-status", "relatio
nship", "race", "native-country", "income"]))
df_encoded = pd.concat([df_copy2, encoded_df], axis=1)

df_encoded.drop("gender", axis=1, inplace=True)
df_encoded.drop("occupation", axis=1, inplace=True)
df_encoded.drop("workclass", axis=1, inplace=True)
df_encoded.drop("education", axis=1, inplace=True)
df_encoded.drop("marital-status", axis=1, inplace=True)
df_encoded.drop("relationship", axis=1, inplace=True)
df_encoded.drop("race", axis=1, inplace=True)
df_encoded.drop("native-country", axis=1, inplace=True)
df_encoded.drop("income", axis=1, inplace=True)
print(df_encoded.head())

normalizer = MinMaxScaler()
df_encoded[["fnlwgt", "educational-num", "capital-gain", "capital-loss", "hours-per-week"]] =
normalizer.fit_transform(df_encoded[["fnlwgt", "educational-num", "capital-gain", "capital-loss", "hours-per-week"
]])
df_encoded.head()



```


```
normalizer = MinMaxScaler()
df1[["No_Pation", "AGE", "Urea", "Cr", "HbA1c", "Chol", "TG", "HDL", "LDL", "VLDL", "BMI"]] =
normalizer.fit_transform(df1[["No_Pation", "AGE", "Urea", "Cr", "HbA1c",
"Chol", "TG", "HDL", "LDL", "VLDL", "BMI"]])
df1.head()
```

Program 3

Implement Linear and Multi-Linear Regression algorithm using appropriate dataset

Screenshot:





Code:

```
from google.colab import files
per_capita_income=files.upload()

from google.colab import files
salary=files.upload()

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.impute import SimpleImputer
from sklearn.preprocessing import OrdinalEncoder, OneHotEncoder
from sklearn.preprocessing import StandardScaler, MinMaxScaler
from scipy import stats
from sklearn import linear_model

df1=pd.read_csv("canada_per_capita_income.csv")
df1.head()

df2=pd.read_csv("salary.csv")
df2.YearsExperience.median()
df2.YearsExperience =
df2.YearsExperience.fillna(df2.YearsExperience.median()) df2

plt.xlabel("year")
plt.ylabel("per capita income (US$)")
plt.scatter(df1.year, df1['per capita income (US$)'])

plt.xlabel("YearsExperience")
plt.ylabel("Salary")
plt.scatter(df2.YearsExperience, df2.Salary)

reg1 = linear_model.LinearRegression()
reg1.intercept_
reg1.predict([[2020]])

reg2 = linear_model.LinearRegression()
reg2.fit(df2.drop('Salary', axis='columns'), df2['Salary'])
reg2.coef_
reg2.intercept_
reg2.predict([[12]])

from google.colab import files
hiring=files.upload()

from google.colab import files
companies=files.upload()
```

```

df3=pd.read_csv("hiring.csv")
df3.head()

df4=pd.read_csv("1000_Companies.csv")
df4.head()

df3.isnull().sum()
df4.isnull().sum()

df3_copy = df3.copy()
experience_mapping = {'two': 2, 'three': 3, 'five': 5, 'seven': 7, 'ten': 10, 'eleven': 11}
df3_copy['experience'] = df3_copy['experience'].map(experience_mapping)
median_experience = df3_copy['experience'].median()
df3_copy['experience'] = df3_copy['experience'].fillna(median_experience)
df3_copy
df3_copy['test_score(out of 10)'] = df3_copy['test_score(out of 10)'].fillna(df3_copy['test_score(out of 10)'].mean())
reg3 = linear_model.LinearRegression()
reg3.fit(df3_copy.drop('salary($)', axis='columns'), df3_copy['salary($)'])
reg3.coef_
reg3.intercept_
reg3.predict([[2,9,6]])
reg3.predict([[12,10,10]])

ohe = OneHotEncoder(sparse_output=False, handle_unknown='ignore')
state_encoded = ohe.fit_transform(df4[['State']])
state_encoded_df = pd.DataFrame(state_encoded, columns=ohe.get_feature_names_out(['State']))

df4 = pd.concat([df4, state_encoded_df], axis=1).drop(columns=['State'])
print(df4)
reg4 = linear_model.LinearRegression()
reg4.fit(df4.drop('Profit',axis='columns'),df4.Profit)
print(reg4.coef_)
print(reg4.intercept_)
reg4.predict([[91694.48, 515841.3, 11931.24,0,1,0]])

```

Program 4

Build Logistic Regression Model for a given dataset

Screenshot:

```
1) logistic regression
import numpy as np
import matplotlib.pyplot as plt

def sigmoid(z):
    return 1 / (1 + np.exp(-z))

X = np.array([
    [0, 50], [1, 55], [1, 60], [1, 65],
    [1, 65], [1, 70], [1, 75], [1, 78],
    [1, 85], [1, 90], [1, 95]
])
Y = np.array([0, 0, 0, 1, 1, 1, 1, 1, 1, 1, 1])
# 0 = fail, 1 = Pass

X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=0.2, random_state=0)

# Logistic Regression
def logistic_regression(X_train, Y_train):
    n = X_train.shape[0]
    W = np.zeros(X_train.shape[1])
    b = 0
    lr = 0.01
    epochs = 1000

    for i in range(epochs):
        predictions = sigmoid(np.dot(X_train, W) + b)
        gradient = np.dot(X_train.T, (predictions - Y_train)) / n
        W = W - lr * gradient
        b = b - lr * gradient

    return W, b

W, b = logistic_regression(X_train, Y_train)

def predict(X_test):
    z = np.dot(X_test, W) + b
    return sigmoid(z)

plt.scatter(X_test[:, 0], Y_test, label='Real', s=100)
plt.scatter(X_test[:, 0], predict(X_test), label='Predicted', s=100)
plt.xlabel('Hours Studied')
plt.ylabel('Probability of Passing')
plt.legend()
plt.show()
```

```
Y_test = [predict(x, b) for x in X_test]
plt.plot(X_test, Y_test, label='Real')
plt.plot(X_test, Y_test, label='Predicted')
plt.xlabel('Hours Studied')
plt.ylabel('Probability of Passing')
plt.legend()
plt.show()

# Probability of passing for
# hours studied 85 to 95
logistic_regression(X_train, Y_train)
# hours studied 85 to 95
```

Code:

```
from google.colab import files
hr=files.upload()

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.impute import SimpleImputer
from sklearn.preprocessing import OrdinalEncoder, OneHotEncoder
from sklearn.preprocessing import StandardScaler, MinMaxScaler
from scipy import stats
from sklearn import linear_model
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score

df1=pd.read_csv("HR_comma_sep.csv")
df1.head()
df1.isnull().sum()
plt.figure(figsize=(12, 6))
sns.barplot(x='Department', y='left', data=df1)
plt.title('Employee Retention Rate by Department')
plt.xlabel('Department')
plt.ylabel('Proportion of Employees Left')
plt.xticks(rotation=45, ha='right')
plt.show()

ohe = OneHotEncoder(handle_unknown='ignore', sparse_output=False)
department_encoded = ohe.fit_transform(df1[['Department']])
department_encoded_df = pd.DataFrame(department_encoded,
columns=ohe.get_feature_names_out(['Department']))
df1 = pd.concat([df1, department_encoded_df], axis=1)
df1 = df1.drop('Department', axis=1)
ordinal_encoder = OrdinalEncoder(categories=[['low', 'medium', 'high']], dtype=np.int64)
salary_encoded = ordinal_encoder.fit_transform(df1[['salary']])
df1['salary_encoded'] = salary_encoded
df1 = df1.drop('salary', axis=1)
df1.head()

correlation_matrix = df1.corr()
plt.figure(figsize=(12, 10))
sns.heatmap(correlation_matrix, annot=True, cmap='coolwarm', fmt=".2f")
plt.title('Correlation Matrix of Features')
plt.show()
plt.figure(figsize=(8, 6))
sns.barplot(x='salary_encoded', y='left', data=df1)
plt.title('Impact of Employee Salary on Retention')
plt.xlabel('Salary Level (Encoded)')
plt.ylabel('Proportion of Employees Left')
plt.show()
```

```

df_copy = df1[['number_project', 'average_monthly_hours', 'time_spend_company', 'left', 'salary_encoded',
'satisfaction_level', 'Work_accident']]
df_copy.head()
X = df_copy.drop('left', axis=1)
y = df_copy['left']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
model = LogisticRegression(max_iter=1000)
model.fit(X_train, y_train)
y_pred = model.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy of the Logistic Regression model: {accuracy}")

```

```

from google.colab import files
zoodata=files.upload()
zootype=files.upload()

```

```

zoo_data = pd.read_csv('zoo-data.csv')
zoo_class = pd.read_csv('zoo-class-type.csv')
merged_data = pd.merge(zoo_data, zoo_class, left_on='class_type', right_on='Class_Number')
merged_data = merged_data.drop(['Animal_Names', 'Number_Of_Animal_Species_In_Class',
'Class_Number', 'class_type', 'animal_name'], axis=1)
X = merged_data.drop('Class_Type', axis=1)
y = merged_data['Class_Type']
print(merged_data.head())
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
model = LogisticRegression(max_iter=1000)
model.fit(X_train, y_train)
y_pred = model.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")
cm = confusion_matrix(y_test, y_pred)
disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=np.unique(y_test))
disp.plot(cmap="Blues", values_format="d")
plt.title("Confusion Matrix")
plt.show()

```

Program 5

Use an appropriate data set for building the decision tree (ID3) and apply this knowledge to classify a new sample.

Screenshot:

```

ID3
Algorithm
import numpy as np
import pandas as pd
from graphviz import Digraph

def entropy(dataset):
    class_count = dataset.iloc[:, -1].value_counts()
    prob = class_count / len(dataset)
    return -np.sum(prob * np.log2(prob))

def information_gain(dataset, feature):
    total_entropy = entropy(dataset)
    feature_values = dataset[feature].value_counts()
    weighted_entropy = 0
    for value, count in feature_values.items():
        subset = dataset[dataset[feature] == value]
        weighted_entropy += (count / len(dataset)) * entropy(subset)
    return total_entropy - weighted_entropy

def best_feature(dataset):
    features = dataset.columns[:-1]
    best_feature = None
    for feature in features:
        info_gain = information_gain(dataset, feature)
        if info_gain > best_info_gain:
            best_info_gain = info_gain
            best_feature = feature
    return best_feature
    
```

Scanned with OKEN Scanner

```

def id3(dataset, max_depth=None, depth=0):
    if len(dataset.iloc[:, -1].unique()) == 1:
        return dataset.iloc[:, -1]
    if len(dataset.columns) == 1:
        return dataset.iloc[:, -1].mode()[0]
    if max_depth is not None and depth > max_depth:
        return dataset.iloc[:, -1].mode()[0]
    best = best_feature(dataset)
    tree = {}
    for value in dataset[best].unique():
        subset = dataset[dataset[best] == value]
        tree[best][value] = id3(subset.drop(columns=[best]), max_depth=max_depth, depth=depth+1)
    def create_tree_diagram(tree, dot=None, parent_name="root", parent_value=None):
        if dot is None:
            dot = Digraph(format="png", engine="dot")
        for feature, branches in tree.items():
            feature_name = f"{parent_name}_{feature}"
            dot.node(feature_name, feature)
            dot.node(parent_name, feature_name)
            label = str(value)
        create_tree_diagram(subtree, dot, value_name, str(value))
    
```

Scanned with OKEN Scanner

Use:

```
dot . node (parent-name + "-class", fill:#fff,stroke:#333,stroke-width:1px)
```

```
dot . edge (parent-name, parent-name + "-class", fill:#fff,stroke:#333,stroke-width:1px)
```

```
return dot
```

```
data = pd.read_csv ("content/Weather_forecast.csv")
```


```
dt = pd.DataFrame (data)
```

```
tree = id3 (dt, max_depth=3)
```

```
dot = create_tree_diagram (tree)
```

```
dot . render ("decision_tree", view=True)
```

Output:



Code:

```
from google.colab import files
iris=files.upload()
df1=pd.read_csv("iris.csv")
df1.head()

df1.isnull().sum()

X = df1.drop('species', axis=1)
y = df1['species']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
clf = DecisionTreeClassifier(criterion='entropy')
clf.fit(X_train, y_train)
y_pred = clf.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print(f'Accuracy: {accuracy:.2f}')
print(classification_report(y_test, y_pred))
plt.figure(figsize=(12, 8))
plot_tree(clf, filled=True, feature_names=X.columns, class_names=y.unique())
plt.show()

cm = confusion_matrix(y_test, y_pred)
disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=clf.classes_)
cmap = plt.cm.get_cmap('PuBuGn')
disp.plot(cmap=cmap)
plt.show()

drug=files.upload()
df2=pd.read_csv("drug.csv")
df2.head()
df2.isnull().sum()

label_encoders = {}
for column in df2.columns:
    le = LabelEncoder()
    df2[column] = le.fit_transform(df2[column])
    label_encoders[column] = le
X = df2.drop('Drug', axis=1)
y = df2['Drug']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
clf = DecisionTreeClassifier(criterion='entropy')
clf.fit(X_train, y_train)
y_pred = clf.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print(f'Accuracy: {accuracy:.2f}')
print(classification_report(y_test, y_pred))
plt.figure(figsize=(12, 8))
plot_tree(clf, filled=True, feature_names=X.columns, class_names=[str(c) for c in y.unique()])
plt.show()

cm = confusion_matrix(y_test, y_pred)
disp = ConfusionMatrixDisplay(confusion_matrix=cm, display_labels=clf.classes_)
```



```

cmap = plt.cm.Blues
disp.plot(cmap=cmap)
plt.show()

pc=files.upload()
df3=pd.read_csv("petrol_consumption.csv")
df3.head()
df3.isnull().sum()
X = df3.drop('Petrol_Consumption', axis=1)
y = df3['Petrol_Consumption']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
regressor = DecisionTreeRegressor(random_state=42)
regressor.fit(X_train, y_train)
y_pred = regressor.predict(X_test)
mse = mean_squared_error(y_test, y_pred)
rmse = sqrt(mse)
mae = mean_absolute_error(y_test, y_pred)
r2 = r2_score(y_test, y_pred)
print(f'Mean Squared Error: {mse:.2f}')
print(f'Root Mean Squared Error: {rmse:.2f}')
print(f'Mean Absolute Error: {mae:.2f}')
print(f'R-squared: {r2:.2f}')
plt.figure(figsize=(30, 30))
plot_tree(regressor, filled=True, feature_names=X.columns, fontsize=10)
plt.show()

```

Program 6

Build KNN Classification model for a given dataset.

Screenshot:

```

lab-4
knn (k nearest Neighbour algorithm)
import numpy as np
import matplotlib.pyplot as plt
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split

X, y = load_iris(return_X_y=True)
n_samples = 150, n_features = 4,
n_classes = 3, random_state = 42,
n_informative = 2, n_redundant = 0, n_noisy = 0

X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.3, random_state=42)

Scaler = StandardScaler()
X_train = Scaler.fit_transform(X_train)
X_test = Scaler.transform(X_test)

knn = KNeighborsClassifier(n_neighbors=3)
knn.fit(X_train, y_train)


y_pred = knn.predict(X_test)

# Accuracy
acc = 0
for i in range(y_test.size):
    if y_test[i] == y_pred[i]:
        acc += 1
accuracy = acc / y_test.size

# Error Rate
error_rate = 1 - accuracy

```

Scanned with OKEN Scanner



Scanned with OKEN Scanner

Code:

```

from google.colab import files
iris=files.upload()
df1=pd.read_csv("iris (2).csv")
df1.head()
df1.isnull().sum()
X = df1.drop('species', axis=1)
y = df1['species']

```

```

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
best_k = 1
best_accuracy = 0
for k in range(1, 11):
    knn = KNeighborsClassifier(n_neighbors=k)
    knn.fit(X_train, y_train)
    y_pred = knn.predict(X_test)
    accuracy = accuracy_score(y_test, y_pred)
    print(f"Accuracy for k={k}: {accuracy}, Error Rate for k={k}: {1-accuracy}")

```

```

        if accuracy >
            best_accuracy:
            best_accuracy = accuracy
            best_k = k
print(f"Best k value: {best_k}")
knn = KNeighborsClassifier(n_neighbors=3)
knn.fit(X_train, y_train)
y_pred = knn.predict(X_test)
print("Accuracy Score:", accuracy_score(y_test, y_pred))
print("\nConfusion Matrix:")
cm = confusion_matrix(y_test, y_pred)
print(cm)
print("\nClassification Report:")
print(classification_report(y_test, y_pred))
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt="d", cmap="Blues",
            xticklabels=knn.classes_, yticklabels=knn.classes_)
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.title('Confusion Matrix')
plt.show()

diabetes=files.upload()
df2=pd.read_csv("diabetes.csv")
df2.head()
df2.isnull().sum()
from sklearn.preprocessing import StandardScaler
scaler = StandardScaler()
X_scaled = scaler.fit_transform(df2.drop('Outcome', axis=1))
X_train, X_test, y_train, y_test = train_test_split(X_scaled, df2['Outcome'], test_size=0.2, random_state=42)
best_k = 1
best_accuracy = 0
for k in range(1, 11):
    knn = KNeighborsClassifier(n_neighbors=k)
    knn.fit(X_train, y_train)
    y_pred = knn.predict(X_test)
    accuracy = accuracy_score(y_test, y_pred)
    print(f"Accuracy for k={k}: {accuracy}")
    if accuracy > best_accuracy:
        best_accuracy = accuracy
        best_k = k
print(f"Best k value: {best_k}")

knn = KNeighborsClassifier(n_neighbors=best_k)
knn.fit(X_train, y_train)
y_pred = knn.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print("Accuracy:", accuracy)
cm = confusion_matrix(y_test, y_pred)
print("Confusion Matrix:")
print(cm)
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues')

```

```

plt.xlabel("Predicted")
plt.ylabel("Actual")
plt.title("Confusion Matrix")
plt.show()
print("\nClassification
Report:")
print(classification_report(y_test, y_pred))


heart=files.upload()
df3=pd.read_csv("heart.csv")
df3.head()
df3.isnull().sum()
X = df3.drop('target', axis=1)
y = df3['target']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
best_k = 1
best_accuracy = 0
for k in range(1, 11):
    knn = KNeighborsClassifier(n_neighbors=k)
    knn.fit(X_train, y_train)
    y_pred = knn.predict(X_test)
    accuracy = accuracy_score(y_test, y_pred)
    print(f'Accuracy for k={k}: {accuracy}, Error Rate for k={k}: {1-accuracy}')
    if accuracy > best_accuracy:
        best_accuracy = accuracy
        best_k = k
print(f'Best k value: {best_k}')
knn = KNeighborsClassifier(n_neighbors=optimal_k)
knn.fit(X_train, y_train)
y_pred = knn.predict(X_test)
print("Accuracy Score:", accuracy_score(y_test, y_pred))
print("\nConfusion Matrix:")
cm = confusion_matrix(y_test, y_pred)
print(cm)
print("\nClassification Report:")
print(classification_report(y_test, y_pred))
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt="d", cmap="Blues",
            xticklabels=knn.classes_, yticklabels=knn.classes_)
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.title('Confusion Matrix')
plt.show()

```

Program7

Build Support vector machine model for a given dataset

Screenshot:




```
SVM

import numpy as np
import matplotlib.pyplot as plt

class SVM:
    def __init__(self, learning_rate=0.001,
                 lambda_param=0.01, n_iters=1000):
        self.lr = learning_rate
        self.lambda_param = lambda_param
        self.n_iters = n_iters
        self.w = None
        self.b = None

    def fit(self, X, y):
        y = np.where(y <= 0, -1, 1)
        n_samples, n_features = X.shape
        self.w = np.zeros(n_features)
        self.b = 0

        for i in range(self.n_iters):
            for idx, x_i in enumerate(X):
                condition = y[idx] * (np.dot(x_i, self.w) + self.b) >= 1
                if condition:
                    continue
                self.w -= self.lr * (2 * self.lambda_param *
                                     self.w)
            else:
                self.w -= self.lr * (2 * self.lambda_param *
                                     np.dot(X, y[idx]))
```



Code:

```

from google.colab import files
iris=files.upload()
df1=pd.read_csv("iris (1).csv")
df1.head()
X = df1.drop('species', axis=1)
y = df1['species']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
rbf_svm = SVC(kernel='rbf')
rbf_svm.fit(X_train, y_train)
rbf_y_pred = rbf_svm.predict(X_test)
print("RBF Kernel SVM:")
print("Accuracy:", accuracy_score(y_test, rbf_y_pred))
cm = confusion_matrix(y_test, rbf_y_pred)
sns.heatmap(cm, annot=True, fmt='d', cmap="Blues")
plt.title('Confusion Matrix for RBF Kernel SVM')
plt.xlabel('Predicted')

```

```

plt.ylabel('True')
plt.show()
print(classification_report(y_test, rbf_y_pred))
linear_svm = SVC(kernel='linear')
linear_svm.fit(X_train, y_train)
linear_y_pred = linear_svm.predict(X_test)
print("\nLinear Kernel SVM:")
print("Accuracy:", accuracy_score(y_test, linear_y_pred))
cm = confusion_matrix(y_test, linear_y_pred)
sns.heatmap(cm, annot=True, fmt='d', cmap="Blues")
plt.title('Confusion Matrix for Linear Kernel SVM')
plt.xlabel('Predicted')
plt.ylabel('True')
plt.show()
print(classification_report(y_test, linear_y_pred))
letter=files.upload()
df2=pd.read_csv("letter-recognition.csv")
df2.head()
X = df2.drop('letter', axis=1)
y = df2['letter']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
svm_classifier = SVC(kernel='linear', probability=True)
svm_classifier.fit(X_train, y_train)
y_pred = svm_classifier.predict(X_test)
print("Accuracy:", accuracy_score(y_test, y_pred))
print(classification_report(y_test, y_pred))
cm = confusion_matrix(y_test, y_pred)
plt.figure(figsize=(10,10))
sns.heatmap(cm, annot=True, fmt='d', cmap="Blues")
plt.title('Confusion Matrix for SVM')
plt.xlabel('Predicted')
plt.ylabel('True')
plt.show()
lb = LabelBinarizer()
lb.fit(y_test)
y_test_lb = lb.transform(y_test)
y_pred_prob = svm_classifier.predict_proba(X_test)
fpr = {}
tpr = {}
thresh = {}
roc_auc = dict()
n_class = y_test_lb.shape[1]
for i in range(n_class):
    fpr[i], tpr[i], thresh[i] = roc_curve(y_test_lb[:,i], y_pred_prob[:,i])
    roc_auc[i] = auc(fpr[i], tpr[i])
plt.plot(fpr[0], tpr[0], linestyle='--', color='orange', label='SVM (AUC = %0.2f)' % roc_auc[0])
plt.title('ROC Curve for Class 0')
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive rate')
plt.legend(loc='best')
plt.show()
print(f'AUC score for class 0: {roc_auc[0]}')

```

Program 8

Implement Random forest ensemble method on a given dataset

Screenshot:

Lab-5

Random Forest Algorithm

```
Function RANDOM-FOREST (Data D, Integer c, T, Integer m):  
    Trees ← []  
    for t from 1 to T do:  
        Bootstrapsample ← sample-with-replacement  
        Tree ← Build-decision-tree (Bootstrapsample)  
        Append Tree to Trees  
    Return Trees
```

Function Build-decision-tree (Data D, Integer m):
 At each node in tree:
 Randomly select m features from all features
 Find the best split using only these m features
 Recursively Split until Stopping Condition is met
 return decision tree

```
Function PREDICT-RANDOM-FOREST (Trees, Instance x)  
    votes ← []  
    for Each Tree in Trees do:  
        Prediction ← Tree(x)  
        Append Prediction to votes  
    Return MAJORITY-VOTE (votes)
```



Code:

```
from google.colab import files
iris=files.upload()
df1=pd.read_csv("iris (4).csv")
df1.head()
X = df1.drop('species', axis=1)
y = df1['species']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=0)
rf_classifier = RandomForestClassifier(random_state=0)
rf_classifier.fit(X_train, y_train)
y_pred = rf_classifier.predict(X_test)
default_accuracy = accuracy_score(y_test, y_pred)
print(f'Accuracy with default n_estimators: {default_accuracy}')
best_accuracy = 0
best_n_estimators = 0
for n_estimators in range(1, 101):
    rf_classifier = RandomForestClassifier(n_estimators=n_estimators, random_state=0)
    rf_classifier.fit(X_train, y_train)
    y_pred = rf_classifier.predict(X_test)
    accuracy = accuracy_score(y_test, y_pred)
    if accuracy > best_accuracy:
        best_accuracy = accuracy
        best_n_estimators = n_estimators
print(f'\nBest accuracy: {best_accuracy} achieved with n_estimators = {best_n_estimators}')
cm = confusion_matrix(y_test, y_pred)
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt="d", cmap="Blues",
            xticklabels=np.unique(y_test), yticklabels=np.unique(y_test))
plt.xlabel("Predicted")
plt.ylabel("Actual")
plt.title("Confusion Matrix")
plt.show()
```

```
best_accuracy = accuracy
best_n_estimators = n_estimators
print(f"\nBest accuracy: {best_accuracy} achieved with n_estimators = {best_n_estimators}")
cm = confusion_matrix(y_test, y_pred)
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt="d", cmap="Blues",
            xticklabels=np.unique(y_test), yticklabels=np.unique(y_test))
plt.xlabel("Predicted")
plt.ylabel("Actual")
plt.title("Confusion Matrix")
plt.show()
```

Program 9

Implement Boosting ensemble method on a given dataset

Screenshot:

4) Ada Boost (Adaptive Boosting) algorithm

```
Function ADABOOST (Dataset D, Integer T):  
    Initialize weights  $w_i = 1/n$  for each training  
    sample  $(x_i, y_i)$   
    Classifiers  $\leftarrow \emptyset$   
    Alphas  $\leftarrow \emptyset$   
    for t from 1 to T do:  
        Classifier  $h_t \leftarrow \text{TRAIN-WEAK-LEARNER}$   
        ( $D, \text{weights } w$ )  
        Error  $\epsilon_t \leftarrow \sum [w_i * I(h_t(x_i) \neq y_i)]$   
        Alpha  $\alpha_t \leftarrow 0.5 * \log((1 - \epsilon_t) / \epsilon_t)$   
        for each i from 1 to n do:  
             $w_i \leftarrow w_i * \exp(-\alpha_t * y_i * h_t(x_i))$   
        normalize weights:  $w_i \leftarrow w_i / \sum w_i$   
        Append  $h_t$  to Classifiers  
        Append  $\alpha_t$  to Alphas  
    Return Classifiers, Alphas
```

```
Function PREDICT-ADABOOST (Classifiers,  
    Alphas, Instance x):  
    Total  $\leftarrow 0$   
    for t from 1 to T do:  
        Total  $\leftarrow \text{Total} + \alpha_t * h_t(x)$   
    Return SIGN(Total)
```

09.04

Scanned with OKEN Scanner

Code:

```
from google.colab import files  
income=files.upload()  
df1=pd.read_csv("income.csv")  
df1.head()  
X = df1.drop('income_level', axis
```

```

y = df1['income_level']
X = pd.get_dummies(X)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_state=42)
abc = AdaBoostClassifier(n_estimators=10, random_state=42)
abc.fit(X_train, y_train)
y_pred = abc.predict(X_test)
accuracy = accuracy_score(y_test, y_pred)
print(f"Initial AdaBoost accuracy (10 trees): {accuracy}")
param_grid = {'n_estimators': [50, 100, 150, 200]}
grid_search = GridSearchCV(AdaBoostClassifier(random_state=42), param_grid, cv=5, scoring='accuracy')
grid_search.fit(X_train, y_train)
print(f"Best parameters: {grid_search.best_params_}")
print(f"Best cross-validation score: {grid_search.best_score_}")
best_abc = grid_search.best_estimator_
y_pred_best = best_abc.predict(X_test)
best_accuracy = accuracy_score(y_test, y_pred_best)
print(f"Accuracy of the best model on the test set: {best_accuracy}")
cm = confusion_matrix(y_test, y_pred_best)
plt.figure(figsize=(8, 6))
sns.heatmap(cm, annot=True, fmt='d', cmap='Blues',
            xticklabels=['<=50K', '>50K'], yticklabels=['<=50K', '>50K'])
plt.xlabel('Predicted')
plt.ylabel('Actual')
plt.title('Confusion Matrix')
plt.show()

```

Program 10

Build k-Means algorithm to cluster a set of data stored in a .CSV file

Screenshot:

2) k-Means Clustering

Function k-Means (Data D, Integer k, Integer max-iter):

Initialize k random Centroids: $\mu_1, \mu_2, \dots, \mu_k$

For iter from 1 to max-iter do:

 clusters \leftarrow empty lists for each cluster

 For each data point $x \in D$ do:

 Find the closest centroid μ_j

 Assign x to cluster j

 For each cluster j do:

$\mu_j \leftarrow \text{MEAN}$ of all points assigned to cluster j

 If centroids do not change:

 Break

Return clusters, Centroids.

Scanned with OKEN Scanner

Code:

```
from google.colab import files
iris=files.upload()
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from scipy import stats
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score
from sklearn.metrics import classification_report, confusion_matrix, accuracy_score
from sklearn.cluster import KMeans
from sklearn.preprocessing import StandardScaler

df1=pd.read_csv("iris (4).csv")
df1.head()
df = df1.drop(['sepal_length','sepal_width','species'],axis=1)
scaler = StandardScaler(
```

```

scaled_df = scaler.fit_transform(df)
wcss = []
for i in range(1, 11):
    kmeans = KMeans(n_clusters=i, init='k-means++', max_iter=300, n_init=10, random_state=0)
    kmeans.fit(scaled_df)
    wcss.append(kmeans.inertia_)
plt.plot(range(1, 11), wcss)
plt.title('Elbow Method')
plt.xlabel('Number of clusters')
plt.ylabel('WCSS')
plt.show()
kmeans = KMeans(n_clusters=3, init='k-means++', max_iter=300, n_init=10, random_state=0)
pred_y = kmeans.fit_predict(scaled_df)
df['cluster'] = pred_y
plt.scatter(df['petal_length'], df['petal_width'], c=df['cluster'])
plt.title('Clusters of Iris Flowers')
plt.xlabel('Petal Length')
plt.ylabel('Petal Width')
plt.show()

```

Program 11

Implement Dimensionality reduction using Principal Component Analysis (PCA) method.

Screenshot:

3) Principal Component Analysis (PCA)

Function PCA (Data, D, Integer K):

Standardized \leftarrow STANDARDIZE_DATA (D)

CovMatrix \leftarrow COMPUTE_COVARIANCE_MATRIX (Standardized)

Eigenvalues, Eigenvectors \leftarrow Eigen-Decomposition (CovMatrix)

Sorted \leftarrow Sort-Eigen Vectors by Eigen values (Eigenvectors)

Top-k-Vectors \leftarrow select-Top-k-Eigen vectors (Sorted)

Reduced Data \leftarrow Project-data (Standardized, Top-k-Vectors)

Return Reduced Data

function STANDARDIZE_DATA (Data D):

for each feature in D:

Subtract mean and divide by Standard variation

Return Standardized D

function Project-data (Data, Eigenvectors):

Return Matrix-Multiplication (Data, Eigenvectors)

Code:

```
from google.colab import files
heart=files.upload()
```

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from scipy import stats
import seaborn as sns
from sklearn.preprocessing import LabelEncoder, OneHotEncoder
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score
from sklearn.metrics import classification_report, confusion_matrix, accuracy_score
from sklearn.preprocessing import StandardScaler
from sklearn.svm import SVC
from sklearn.linear_model import LogisticRegression
from sklearn.ensemble import RandomForestClassifier
from sklearn.decomposition import PCA
```

```
df1=pd.read_csv("heart (1).csv")
df1.head()
text_cols = df1.select_dtypes(include=['object']).columns
label_encoder = LabelEncoder()
for col in text_cols:
    df1[col] =
label_encoder.fit_transform(df1[col])
print(df1.head())
X = df1.drop('HeartDisease', axis=1)
y = df1['HeartDisease']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)
# Support Vector Machine
svm_model = SVC(kernel='linear', random_state=42)
svm_model.fit(X_train, y_train)
svm_predictions = svm_model.predict(X_test)
svm_accuracy = accuracy_score(y_test, svm_predictions)
print(f"SVM Accuracy: {svm_accuracy}")
```

```
# Logistic Regression
lr_model = LogisticRegression(random_state=42)
```

```

lr_model.fit(X_train, y_train)
lr_predictions = lr_model.predict(X_test)
lr_accuracy = accuracy_score(y_test, lr_predictions)
print(f"Logistic Regression Accuracy: {lr_accuracy}")

# Random Forest
rf_model = RandomForestClassifier(random_state=42)
rf_model.fit(X_train, y_train)
rf_predictions = rf_model.predict(X_test)
rf_accuracy = accuracy_score(y_test, rf_predictions)
print(f"Random Forest Accuracy: {rf_accuracy}")

models = {
    "SVM": svm_accuracy,
    "Logistic Regression": lr_accuracy,
    "Random Forest": rf_accuracy
}

best_model = max(models, key=models.get)
print(f"\nBest Model: {best_model} with accuracy {models[best_model]}")
pca = PCA(n_components=0.95)
X_train_pca = pca.fit_transform(X_train)
X_test_pca = pca.transform(X_test)

svm_model_pca = SVC(kernel='linear', random_state=42)
svm_model_pca.fit(X_train_pca, y_train)
svm_predictions_pca = svm_model_pca.predict(X_test_pca)
svm_accuracy_pca = accuracy_score(y_test, svm_predictions_pca)
print(f"SVM Accuracy (with PCA): {svm_accuracy_pca}")

lr_model_pca = LogisticRegression(random_state=42)
lr_model_pca.fit(X_train_pca, y_train)
lr_predictions_pca = lr_model_pca.predict(X_test_pca)
lr_accuracy_pca = accuracy_score(y_test, lr_predictions_pca)
print(f"Logistic Regression Accuracy (with PCA): {lr_accuracy_pca}")

rf_model_pca = RandomForestClassifier(random_state=42)
rf_model_pca.fit(X_train_pca, y_train)
rf_predictions_pca = rf_model_pca.predict(X_test_pca)
rf_accuracy_pca = accuracy_score(y_test, rf_predictions_pca)
print(f"Random Forest Accuracy (with PCA): {rf_accuracy_pca}")

models_pca = {
    "SVM": svm_accuracy_pca,
    "Logistic Regression": lr_accuracy_pca,
    "Random Forest": rf_accuracy_pca
}

best_model_pca = max(models_pca, key=models_pca.get)
print(f"\nBest Model (with PCA): {best_model_pca} with accuracy {models_pca[best_model_pca]}")

```