



A Rolls-Royce solution

designation

circuit-diagram "control-panel" BR4000 ECU9 / without controller (V1+)

project number

XZ54934000030 (ZNG00040839)

material number

X54934400436 (ZNG00040965)

serial number

type-of-system

[illegible]

Table of contents

Page Structure		Page	Page description	Date	Edited by
		0	Revisions overview	15.10.2021	Dieter Ehrlich
	EAA	1	Cover sheet	13.10.2021	M.Mayer
	EAA	2	Projekt Information	15.10.2021	Dieter Ehrlich
	EAA	3	Information switchgear assembly	20.10.2021	00044190
	EAB	4	Table of contents	20.10.2021	00044190
	EAB	5	Table of contents	20.10.2021	00044190
	EAB	6	Table of contents	20.10.2021	00044190
	EDB	7	Description	13.10.2021	M.Mayer
	EDB	8	Technical data	18.10.2021	Dieter Ehrlich
	EDB	9	Technical data	15.10.2021	Dieter Ehrlich
	EDB	10	Information to terminals	18.10.2021	M.Mayer
BSF	EFS	1	Jacket water heating	18.10.2021	Dieter Ehrlich
BSF	EFS	2	Fuel water separator 1-6	18.10.2021	Dieter Ehrlich
ENG	EFS	3	Engine-Control-Unit ECU9 Plug -X1 start - maintenance	18.10.2021	Dieter Ehrlich
ENG	EFS	4	Engine-Control-Unit ECU9 Plug -X1 E-Stop - analog - power	18.10.2021	Dieter Ehrlich
ENG	EFS	5	Engine-Control-Unit ECU9 Plug -X1 overview	15.10.2021	Dieter Ehrlich
ENG	EFS	6	Power unit battery + starter	18.10.2021	Dieter Ehrlich
GEN	EFS	7	Generator heater Customer 500/1000W	20.10.2021	00044190
GEN	EFS	8	Generator Signal Automatic voltage regulator	20.10.2021	00044190
GEN	EFS	9	Generator winding and bearing temperature	20.10.2021	00044190
MIP	EFS	10	Power supply 400V	20.10.2021	00044190
MIP	EFS	11	Power supply 400V	19.10.2021	M.Mayer
MIP	EFS	12	Supply 24VDC Charger	18.10.2021	Dieter Ehrlich
MIP	EFS	13	Supply 24VDC Charger	18.10.2021	M.Mayer
MIP	EFS	14	General signals	18.10.2021	Dieter Ehrlich
MIP	EFS	15	Module control enclosure	20.10.2021	00044190
MIP	EFS	16	emergency-stop	19.10.2021	Dieter Ehrlich
MIP	EFS	17	Bus-overview DEIF AGC4	18.10.2021	Dieter Ehrlich
MIP	EFS	18	Control cabinet cooling	18.10.2021	Dieter Ehrlich
MIP	ETL	19	Switch-cabinet front outside	19.10.2021	M.Mayer
MIP	ETL	20	Switch-cabinet front and MPL	19.10.2021	M.Mayer
MIP	ETL	21	Switch-Cabinet Side outside	19.10.2021	M.Mayer
MIP	ETL	22	Mounting plate overview	19.10.2021	M.Mayer
MIP	ETL	23	Cabinet drilling diagram	19.10.2021	M.Mayer
GCB	EFS	24	GCB-Generator circuit breaker	18.10.2021	M.Mayer
MCB	EFS	25	MCB-Mains circuit breaker	18.10.2021	M.Mayer
FAN	EFS	26	FAN-Engine fan	18.10.2021	M.Mayer
TNK	EFS	27	Fuel transfer pump	18.10.2021	M.Mayer
EXT	EFS	28	Customer page	18.10.2021	M.Mayer

TECHNICAL DATA AND CONSTRUCTION DETAILS

Wire colors within enclosure			
According IEC EN 60204-1			
Rated voltage	Above 48VAC	black	
Neutral wire	N	light blue	
Protective earth	PE	green/yellow	
Control voltage	24-240V AC	red	
	0V AC	red/white	
	24-110V DC	dark blue	
PLC-Controller	0V DC	grey	
		white	
		grey	
Measuring technique			
wires before Mainswitch		orange	

L1 - L2 - L3 1L1 - 1L2 - 1L3 N PE			
Main power before main switch			
Main power main switch on			
Neutral wire			
Protective conductor			
Mains power supply	400VAC	-XD00	
Power supply Heating GEN	230VAC	-XD01	
Power supply heatg. cool. water	400VAC	-XD02	
Emergency stop		-XD06	
Supply DC	24VDC	-XDL+	
Supply DC	0VDC	-XDL-	
Harness W011-ECU9 Digital		-1XD01	
Harness W011-ECU9 Analog		-1XD02	
Harness W020 Engine		-2XD01	
Harness W030 Generator signal		-3XD01/-3XD02	
Harness W031 Generator PT100		-3XD03	
Option		-XDTP	
Customer interface WD04.1 / WG04.2 / WG04.3		-4XD01/-4XD02/ -4XD03	
Harness W050 Power panel		-5XD01	
Control cable WD06.1 Generator circuit breaker		-6XD01	
Control cable WD07.1 Mains circuit breaker		-7XD01	
Control cable WD08.1 Fan control enclosure		-8XD01	
Control cable WD09.1/WD09.2 Fuel control		-9XD01/-9XD02	
CAN bus		-XF01	

Tightening torque			
Power relay	75A	M3,5x5 M5x8	1,1-1,2 Nm 3,2-3,5 Nm
Starter	Prestolite 9KW	M5 M12	2,0-3,0 Nm 27-33 Nm
Starter	Prestolite 15KW	M5 M10	1,5-1,7 Nm 9-10 Nm
Starter	Delco 9KW	Housing 10-32 INCH 1/2-13 INCH	18-23 Nm 1,8-3,4 Nm 27-34 Nm
Battery disconnect switches		M10 M12	15-20 Nm 18-22 Nm
Battery terminals	DIN 72331	Cable M6 M8	5-6 Nm Class 4,6 / 3,5 Nm Class 4,6 / 8,4 Nm
Grounding		M8 M10 M12 M14	Class 8,8 / 28 Nm Class 8,8 / 54 Nm Class 8,8 / 93 Nm Class 8,8 / 148 Nm