



Diesel Generator Set

mtu 20V4000 DS3300

380V – 11 kV/50 Hz/prime power for stationary emergency/
NEA (ORDE) optimized/20V4000G34F/water charge air cooling



Optional equipment and finishing shown. Standard may vary.

Product highlights

Benefits

- Low fuel consumption
- Optimized system integration ability
- High reliability
- High availability of power
- Long maintenance intervals

Support

- Global product support offered

Standards

- Engine-generator set is designed and manufactured in facilities certified to standards ISO 2008:9001 and ISO 2004:14001
- Generator set complies to ISO 8528
- Generator meets NEMA MG1, BS 5000, ISO, DIN EN and IEC standards
- NFPA 110

Power rating

- System ratings: 2830 kVA - 2940 kVA
- Accepts rated load in one step per NFPA 110*
- Generator set complies to G3 according to ISO 8528-5
- Generator set exceeds load steps according to ISO 8528-5*

Performance assurance certification (PAC)

- Engine-generator set tested to ISO 8528-5 for transient response
- 85% load factor
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

Complete range of accessories available

- Control panel
- Power panel
- Circuit breaker/power distribution
- Fuel system
- Fuel connections with shut-off valve mounted to base frame
- Starting/charging system
- Exhaust system
- Mechanical and electrical driven radiators
- Medium and oversized voltage alternators

Emissions

- NEA (ORDE) optimized

Certifications

- CE certification option
- Unit certificate acc. to VDE-AR-N 4110

* Changes to the standard parameter sets (alternator-regulator and genset-controller) are necessary



A Rolls-Royce
solution

Application data ¹⁾

Engine			Liquid capacity (lubrication)		
Manufacturer	mtu		Total oil system capacity: l	390	
Model	20V4000G34F		Engine jacket water capacity: l	205	
Type	4-cycle		Intercooler coolant capacity: l	50	
Arrangement	20V		Combustion air requirements		
Displacement: l	95.4				
Bore: mm	170			Combustion air volume: m³/s	2.9
Stroke: mm	210			Max. air intake restriction: mbar	50
Compression ratio	16.4		Cooling/radiator system		
Rated speed: rpm	1500				
Engine governor	ECU 9			Coolant flow rate (HT circuit): m³/hr	80
Max power: kWm	2590			Coolant flow rate (LT circuit): m³/hr	32.5
Air cleaner	dry		Heat rejection to coolant: kW	1020	
Fuel system			Heat radiated to charge air cooling: kW	480	
			Heat radiated to ambient: kW	105	
	Maximum fuel lift: m	5	Fan power for electr. radiator (40°C): kW	70	
	Total fuel flow: l/min	27			
			Exhaust system		
Fuel consumption ²⁾	l/hr	g/kwh	Exhaust gas temp. (after turbocharger): °C	560	
At 100% of power rating:	617.9	198	Exhaust gas volume: m³/s	8.5	
At 75% of power rating:	479.8	205	Maximum allowable back pressure: mbar	85	
At 50% of power rating:	333.9	214	Minimum allowable back pressure: mbar	30	

Standard and optional features

System ratings (kW/kVA)

Generator model	Voltage	NEA (ORDE) optimized					
		without radiator			with mechanical radiator		
		kWel	kVA*	AMPS	kWel	kVA*	AMPS
Leroy Somer LSA53.2 M12 (Low voltage Leroy Somer standard)	380 V	2336	2920	4436	2272	2840	4315
	400 V	2336	2920	4215	2272	2840	4099
	415 V	2336	2920	4062	2272	2840	3951
Marathon 1030FDL7094 (Low voltage Marathon)	380 V	2336	2920	4436	2264	2830	4300
	400 V	2336	2920	4215	2264	2830	4085
	415 V	2336	2920	4062	2264	2830	3937
Marathon 1040FDH7102 (Medium volt. marathon)	11 kV	2336	2920	153	2272	2840	149
Leroy Somer LSA54.2 XL11 (Medium volt. Leroy Somer)	11 kV	2352	2940	154	2280	2850	150

* cos phi = 0.8

1 All data refers only to the engine and is based on ISO standard conditions (25°C and 100m above sea level).
2 Values referenced are in accordance with ISO 3046-1. Conversion calculated with fuel density of 0.83 g/ml. All fuel consumption values refer to rated engine power.