



Diesel Generator Set

mtu 12V4000 DS2000

380V – 11 kV/50 Hz/prime power for stationary emergency/
NOx emission optimized/12V4000G24F/water charge air cooling



Optional equipment and finishing shown. Standard may vary.

Product highlights

Benefits

- Low fuel consumption
- Optimized system integration ability
- High reliability
- High availability of power
- Long maintenance intervals

Support

- Global product support offered

Standards

- Engine-generator set is designed and manufactured in facilities certified to standards ISO 2008:9001 and ISO 2004:14001
- Generator set complies to ISO 8528
- Generator meets NEMA MG1, BS 5000, ISO, DIN EN and IEC standards
- NFPA 110

Power rating

- System ratings: 1790 kVA - 1880 kVA
- Accepts rated load in one step per NFPA 110*
- Generator set complies to G3 according to ISO 8528-5
- Generator set exceeds load steps according to ISO 8528-5*

Performance assurance certification (PAC)

- Engine-generator set tested to ISO 8528-5 for transient response
- 85% load factor
- Verified product design, quality and performance integrity
- All engine systems are prototype and factory tested

Complete range of accessories available

- Control panel
- Power panel
- Circuit breaker/power distribution
- Fuel system
- Fuel connections with shut-off valve mounted to base frame
- Starting/charging system
- Exhaust system
- Mechanical and electrical driven radiators
- Medium and oversized voltage alternators

Emissions

- NOx emission optimized

Certifications

- CE certification option
- Unit certificate acc. to VDE-AR-N 4110

* Changes to the standard parameter sets (alternator-regulator and genset-controller) are necessary



A Rolls-Royce
solution

Application data ¹⁾

Engine			Liquid capacity (lubrication)	
Manufacturer		<i>mtu</i>	Total oil system capacity: l	260
Model		12V4000G24F	Engine jacket water capacity: l	160
Type		4-cycle	Intercooler coolant capacity: l	40
Arrangement		12V	Combustion air requirements	
Displacement: l		57.2	Combustion air volume: m³/s	2.2
Bore: mm		170	Max. air intake restriction: mbar	50
Stroke: mm		210	Cooling/radiator system	
Compression ratio		16.4	Coolant flow rate (HT circuit): m³/hr	56
Rated speed: rpm		1500	Coolant flow rate (LT circuit): m³/hr	30
Engine governor		ECU 9	Heat rejection to coolant: kW	670
Max power: kWm		1575	Heat radiated to charge air cooling: kW	410
Air cleaner		dry	Heat radiated to ambient: kW	75
Fuel system			Fan power for electr. radiator (40°C): kW	70
Maximum fuel lift: m		5	Exhaust system	
Total fuel flow: l/min		16	Exhaust gas temp. (after turbocharger): °C	480
Fuel consumption ²⁾			Exhaust gas volume: m³/s	5.6
At 100% of power rating:	l/hr	g/kwh	Maximum allowable back pressure: mbar	85
At 75% of power rating:	419.4	221	Minimum allowable back pressure: mbar	30
At 50% of power rating:	306	213		
	204	216		

Standard and optional features

System ratings (kW/kVA)

Generator model	Voltage	NOx emission optimized					
		without radiator			with mechanical radiator		
		kWel	kVA*	AMPS	kWel	kVA*	AMPS
Leroy Somer LSA52.3 S6 (Low voltage Leroy Somer standard)	380 V	1504	1880	2856	1440	1800	2735
	400 V	1504	1880	2714	1440	1800	2598
	415 V	1504	1880	2615	1440	1800	2504
Marathon 743RSL7091 (Low voltage Marathon)	380 V	1496	1870	2841	1432	1790	2720
	400 V	1504	1880	2714	1432	1790	2584
	415 V	1496	1870	2602	1432	1790	2490
Marathon 744RSL7092 (Low voltage Marathon oversized)	380 V	1496	1870	2841	1432	1790	2720
	400 V	1504	1880	2714	1432	1790	2584
	415 V	1496	1870	2602	1432	1790	2490
Marathon 1020FDH7096 (Medium volt. marathon)	11 kV	1496	1870	98	1432	1790	94
Leroy Somer LSA53.2 VL7 (Med. volt. Leroy Somer)	11 kV	1504	1880	99	1440	1800	94

* cos phi = 0.8

1 All data refers only to the engine and is based on ISO standard conditions (25°C and 100m above sea level).
2 Values referenced are in accordance with ISO 3046-1. Conversion calculated with fuel density of 0.83 g/ml. All fuel consumption values refer to rated engine power.