



Gas system

SERIES 4000 BIOGAS

480V/60 Hz/NOx < 500 mg/Nm³

System ratings

Gas genset

Genset type	Engine type	Output	Therm. ²⁾	Exhaust ³⁾	Low Temp.	Energy input ⁴⁾	Efficiency		Methane number ⁵⁾
		Elect. ¹⁾					Electr.	Total	
		kW _{el}	kW _{th}	kW _{th} (°C)	kW _{th} (°C)	kW	η _{el} (%)	η _{tot} (%)	
MTU 8V4000 GS	L32	764	427	349 (180)	67 (53)	1854	41.2	83.1	≥ 120
MTU 8V4000 GS	L32	764	388	321 (180)	74 (40)	1806	42.3	81.6	≥ 120
MTU 12V4000 GS	L32	1152	629	519 (180)	90 (53)	2755	41.8	83.5	≥ 120
MTU 12V4000 GS	L32	1152	581	488 (180)	103 (40)	2716	42.4	81.8	≥ 120
MTU 16V4000 GS*	L32	1549	638	652 (180)	313 (40)	3616	42.8	87.2	≥ 120
MTU 16V4000 GS*	L32	1549	659	671 (180)	330 (53)	3652	42.4	87.9	≥ 120
MTU 20V4000 GS*	L32	1932	745	873 (180)	373 (40)	4493	43.0	87.3	≥ 120
MTU 20V4000 GS*	L32	1934	797	856 (180)	425 (53)	4576	42.3	87.7	≥ 120

- 1 Rated power at nominal voltage, power factor = 1,0 and nominal frequency
 - 2 Heat output from engine cooling with tolerance of ± 8%
 - 3 Heat output from exhaust (exhaust cooling to 180°C) with tolerance of ± 8%
 - 4 Performance data in accordance with ISO 3046/I-2002 with tolerance of 5%
 - 5 Referenced methane number
- * with HT-extraction

Project specific data on request:

- different alternator voltage
- different flow-/return-temperatures, hot cooling, methane number, installation conditions etc.
- Container



A Rolls-Royce solution