



Gas system

SERIES 4000 NATURAL GAS

480V/60 Hz/NO_x < 1g/bhp-hr

System ratings

Gas genset

Genset type	Engine type	Output	Therm. ²⁾	Exhaust ³⁾	Low Temp.	Energy	Efficiency		Methane number ⁵⁾
		Elect. ¹⁾				input ⁴⁾	Electr.	Total	
		kW _{el}	kBTU/hr	kBTU/hr (°F)	kBTU/hr (°F)	kBTU/hr	η _{el} (%)	η _{tot} (%)	
MTU 8V4000 GS	L33	762	1421	1458 (248)	164 (104)	6349	41.0	86.3	≥ 70
MTU 8V4000 GS	L33	840	1561	1540 (248)	167 (104)	6865	41.8	87.0	≥ 80
MTU 12V4000 GS	L33	1151	2121	2162 (248)	277 (104)	9470	41.5	86.7	≥ 70
MTU 12V4000 GS	L33	1268	2326	2261 (248)	304 (104)	10235	42.3	87.1	≥ 80
MTU 16V4000 GS	L33	1542	3104	2678 (248)	345 (104)	12629	41.7	87.5	≥ 70
MTU 16V4000 GS	L33	1697	3391	2818 (248)	393 (104)	13743	42.2	87.4	≥ 80
MTU 20V4000 GS	L33	1924	3678	3564 (248)	434 (104)	15785	41.6	87.1	≥ 70
MTU 20V4000 GS	L33	2120	4030	3695 (248)	492 (104)	17151	42.2	87.3	≥ 80

Hot ambient conditions

MTU 8V4000 GS	L32	762	1564	1445 (248)	103 (127)	6380	40.8	88.0	≥ 80
MTU 12V4000 GS	L32	1151	2336	2336 (248)	167 (127)	9805	40.1	87.7	≥ 80
MTU 16V4000 GS	L32	1542	3009	2766 (248)	263 (127)	12568	41.9	87.9	≥ 80
MTU 20V4000 GS	L32	1924	3600	3784 (248)	270 (127)	15747	41.7	88.6	≥ 80
MTU 16V4000 GS	L64FNER	2014	4091	3415 (248)	345 (136)	16038	42.9	89.7	≥ 80
MTU 20V4000 GS	L64FNER	2516	5007	4276 (248)	526 (136)	19895	43.3	90.1	≥ 80

- 1 Rated power at nominal voltage, power factor = 1,0 and nominal frequency
- 2 Heat output from engine cooling with tolerance of ± 8%
- 3 Heat output from exhaust (exhaust cooling to 248°F or 356°F) with tolerance of ± 8%
- 4 Performance data in accordance with ISO 3046/I-2002 with tolerance of 5%
- 5 Referenced methane number

Project specific data on request:

- different alternator voltage
- different flow-/return-temperatures, hot cooling, methane number, installation conditions etc.
- Container



A Rolls-Royce solution