

CleverTap Multi-Instance Demo

A short guide to what this Android app does and how it's put together

What it does

The app sends data to **two separate CleverTap accounts** from one Android app, using the CleverTap SDK's multi-instance support. Each account uses a different rule for who the user is (the `Identity` field) when `onUserLogin` is called:

Project 1 — default instance

Identity = the phone number the user types in
e.g. Identity: +14155551234

+

Project 2 — additional instance

Identity = a random id generated fresh on every login
e.g. Identity: user_12a14da9

Both instances also fire a `Logged In` event right after login, so activity shows up on both CleverTap dashboards independently.

How the two instances are wired up

Concept	Project 1	Project 2
CleverTap SDK role	Default instance obtained via <code>CleverTapAPI.getDefaultInstance()</code>	Additional instance created via <code>CleverTapInstanceConfig.createInstance()</code> + <code>CleverTapAPI.getInstanceWithConfig()</code>
Where credentials are declared	<code>AndroidManifest.xml</code> meta-data tags	<code>CleverTapMultiInstanceApp.kt</code> , via generated <code>BuildConfig</code> fields
Where credentials actually live	<code>local.properties</code> (gitignored, never committed) — injected into the manifest as placeholders and into <code>BuildConfig</code> at build time by <code>app/build.gradle.kts</code>	

Nothing in the committed source ever contains a real account ID or token. Anyone cloning the repo copies `local.properties.example` to `local.properties` and fills in their own values before building.

Key files

File	Purpose
<code>AndroidManifest.xml</code>	Declares Project 1's credentials (as placeholders resolved at build time) and the app's single activity/permissions.
<code>CleverTapMultiInstanceApp.kt</code>	App startup: gets the Project 1 default instance, creates the Project 2 additional instance, fires a launch event on both.

<code>MainActivity.kt</code>	The login screen: reads the phone number, calls <code>onUserLogin</code> on both instances with their respective <code>Identity</code> values, and pushes a <code>LoggedIn</code> event to each.
<code>app/build.gradle.kts</code>	Reads credentials from <code>local.properties</code> and injects them as manifest placeholders / <code>BuildConfig</code> fields.
<code>local.properties.example</code>	Template showing which four credential keys are needed. Safe to commit — contains no real values.

Building & running it

1. Clone the repo, open it in Android Studio (it generates the Gradle wrapper and syncs automatically).
2. Copy `local.properties.example` to `local.properties` and fill in the four CleverTap credential values for your two accounts.
3. Run on a device or emulator.
4. Type a phone number and tap the login button.
5. Check both CleverTap dashboards' Profiles/Events views for the two different `Identity` values.

Repository

github.com/MrunmayiS2600/CleverTapMultiInstanceDemo
