


# Chapter 2

## Application Layer



### A note on the use of these ppt slides:

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- ❖ If you use these slides (e.g., in a class) in substantially unaltered form, that you mention their source (after all, we'd like people to use our book!)
- ❖ If you post any slides in substantially unaltered form on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2010  
J.F Kurose and K.W. Ross, All Rights Reserved

*Computer Networking:  
A Top Down Approach,  
5<sup>th</sup> edition.*

*Jim Kurose, Keith Ross  
Addison-Wesley, April  
2009.*

# Socket programming

Goal: learn how to build client/server application that communicate using sockets

## Socket API

- ❖ introduced in BSD4.1 UNIX, 1981
- ❖ explicitly created, used, released by apps
- ❖ client/server paradigm
- ❖ two types of transport service via socket API:
  - unreliable datagram
  - reliable, byte stream-oriented


### socket

a *host-local*,  
*application-created*,  
*OS-controlled* interface  
(a "door") into which  
application process can  
*both send and*  
*receive* messages to/from  
another application  
process

# Socket-programming using TCP

Socket: a door between application process and end-end-transport protocol (UCP or TCP)

TCP service: reliable transfer of *bytes* from one process to another



# Socket programming *with TCP*

## Client must contact server

- ❖ server process must first be running
- ❖ server must have created socket (door) that welcomes client's contact

## Client contacts server by:

- ❖ creating client-local TCP socket
- ❖ specifying IP address, port number of server process
- ❖ when **client creates socket**: client TCP establishes connection to server TCP

- ❖ when contacted by client, **server TCP creates new socket** for server process to communicate with client
  - allows server to talk with multiple clients
  - source port numbers used to distinguish clients (more in Chap 3)


## application viewpoint

*TCP provides reliable, in-order transfer of bytes ("pipe") between client and server*

# Client/server socket interaction: TCP


Server (running on `hostid`)

Client



# Stream jargon

- ❖ **stream** is a sequence of characters that flow into or out of a process.
- ❖ **input stream** is attached to some input source for the process, e.g., keyboard or socket.
- ❖ **output stream** is attached to an output source, e.g., monitor or socket.



# Socket programming with TCP

## Example client-server app:

- 1) client reads line from standard input (`inFromUser` stream) , sends to server via socket (`outToServer` stream)
- 2) server reads line from socket
- 3) server converts line to uppercase, sends back to client
- 4) client reads, prints modified line from socket (`inFromServer` stream)

# Example: Java client (TCP)

```
import java.io.*;  
import java.net.*;  
class TCPClient {
```

← This package defines Socket()  
and ServerSocket() classes

```
    public static void main(String argv[]) throws Exception  
    {
```

```
        String sentence;  
        String modifiedSentence;
```

create  
input stream →

```
        BufferedReader inFromUser =  
            new BufferedReader(new InputStreamReader(System.in));
```

create  
clientSocket object  
of type Socket,  
connect to server →

```
        Socket clientSocket = new Socket("hostname", 6789);
```

server name,  
e.g., www.umass.edu  
server port #

create  
output stream  
attached to socket →

```
        DataOutputStream outToServer =  
            new DataOutputStream(clientSocket.getOutputStream());
```



# Example: Java client (TCP), cont.

```
        create
        input stream attached to socket → BufferedReader inFromServer =
                                           new BufferedReader(new
                                           InputStreamReader(clientSocket.getInputStream()));

                                           sentence = inFromUser.readLine();

        send line to server → outToServer.writeBytes(sentence + '\n');

        read line from server → modifiedSentence = inFromServer.readLine();

                                           System.out.println("FROM SERVER: " + modifiedSentence);

        close socket (clean up behind yourself!) → clientSocket.close();

                                           }
                                           }
```

# Example: Java server (TCP)

```
import java.io.*;  
import java.net.*;
```

```
class TCPServer {
```

```
    public static void main(String argv[]) throws Exception  
    {
```

```
        String clientSentence;  
        String capitalizedSentence;
```

create  
welcoming socket  
at port 6789

```
        ServerSocket welcomeSocket = new ServerSocket(6789);
```

wait, on welcoming  
socket accept() method  
for client contact create,  
new socket on return

```
        while(true) {
```

```
            Socket connectionSocket = welcomeSocket.accept();
```

create input  
stream, attached  
to socket

```
            BufferedReader inFromClient =  
                new BufferedReader(new  
                    InputStreamReader(connectionSocket.getInputStream()));
```

# Example: Java server (TCP), cont

create output  
stream, attached  
to socket

→ `DataOutputStream outToClient =  
new DataOutputStream(connectionSocket.getOutputStream());`

read in line  
from socket

→ `clientSentence = inFromClient.readLine();`

`capitalizedSentence = clientSentence.toUpperCase() + '\n';`

write out line  
to socket

→ `outToClient.writeBytes(capitalizedSentence);`

`}  
}  
}`

end of while loop,  
loop back and wait for  
another client connection

# Chapter 2: Application layer

2.1 Principles of network applications

2.2 Web and HTTP

2.3 FTP

2.4 Electronic Mail

- SMTP, POP3, IMAP

2.5 DNS

2.6 P2P applications

2.7 Socket programming with TCP

2.8 Socket programming with UDP

# Socket programming *with UDP*

UDP: no "connection" between client and server

- ❖ no handshaking
- ❖ sender explicitly attaches IP address and port of destination to each packet
- ❖ server must extract IP address, port of sender from received packet

UDP: transmitted data may be received out of order, or lost

application viewpoint:

*UDP provides unreliable transfer of groups of bytes ("datagrams") between client and server*

# Client/server socket interaction: UDP

Server (running on `hostid`)

Client

create socket,  
port= x.  
`serverSocket =`  
`DatagramSocket()`

read datagram from  
`serverSocket`

write reply to  
`serverSocket`  
specifying  
client address,  
port number


create socket,  
`clientSocket =`  
`DatagramSocket()`

Create datagram with server IP and  
port=x; send datagram via  
`clientSocket`

read datagram from  
`clientSocket`

close  
`clientSocket`

# Example: Java client (UDP)



# Example: Java client (UDP)

```
import java.io.*;  
import java.net.*;
```

```
class UDPClient {  
    public static void main(String args[]) throws Exception  
    {
```

create  
input stream

```
        BufferedReader inFromUser =  
            new BufferedReader(new InputStreamReader(System.in));
```

create  
client socket

```
        DatagramSocket clientSocket = new DatagramSocket();
```

translate  
hostname to IP  
address using DNS

```
        InetAddress IPAddress = InetAddress.getByName("hostname");
```

```
        byte[] sendData = new byte[1024];  
        byte[] receiveData = new byte[1024];
```

```
        String sentence = inFromUser.readLine();
```

```
        sendData = sentence.getBytes();
```



# Example: Java client (UDP), cont.

create datagram  
with data-to-send,  
length, IP addr, port

send datagram  
to server

read datagram  
from server

```
DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length, IPAddress, 9876);  
  
clientSocket.send(sendPacket);  
  
DatagramPacket receivePacket =  
    new DatagramPacket(receiveData, receiveData.length);  
  
clientSocket.receive(receivePacket);  
  
String modifiedSentence =  
    new String(receivePacket.getData());  
  
System.out.println("FROM SERVER:" + modifiedSentence);  
clientSocket.close();  
}  
}
```

# Example: Java server (UDP)

```
import java.io.*;  
import java.net.*;
```

```
class UDPServer {  
    public static void main(String args[]) throws Exception  
    {
```

create  
datagram socket  
at port 9876

```
        DatagramSocket serverSocket = new DatagramSocket(9876);
```

```
        byte[] receiveData = new byte[1024];  
        byte[] sendData = new byte[1024];
```

```
        while(true)  
        {
```

create space for  
received datagram

```
            DatagramPacket receivePacket =  
                new DatagramPacket(receiveData, receiveData.length);
```

receive  
datagram

```
            serverSocket.receive(receivePacket);
```

# Example: Java server (UDP), cont

```
String sentence = new String(receivePacket.getData());
```

get IP addr  
port #, of  
sender

```
InetAddress IPAddress = receivePacket.getAddress();
```

```
int port = receivePacket.getPort();
```

```
String capitalizedSentence = sentence.toUpperCase();
```

```
sendData = capitalizedSentence.getBytes();
```

create datagram  
to send to client

```
DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length, IPAddress,  
                        port);
```

write out  
datagram  
to socket

```
serverSocket.send(sendPacket);
```

```
}  
}  
}
```

end of while loop,  
loop back and wait for  
another datagram