메인	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	68.1	68.1	68.1	68.1	68.1	78.6	78.6
총연장길이	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
어댑터1	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
연장붐1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
연장붐2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
연장붐3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
연장붐4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
어댑터2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
러핑길이	21	28	35	42	49	56	63	70	21	28	35	42	49	21	28
러핑메인각도	75	75	75	75	75	75	75	75	75	75	75	75	75	75	75
workingArea(SlewingGear)	360	360	360	360	360	360	360	360	360	360	360	360	360	360	360
무게추	165	165	165	165	165	165	165	165	165	165	165	165	165	165	165
overRear	х	Х	х	Х	Х	Х	х	х	х	х	х	Х	х	х	Х
optional	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	X
guyedAngle	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
30	17														
32	15.9														
34	14.9	13.4							8.5						
36	14	12.5	100						7.8					0.0	
38		11.7	10.8						7.2	5.3				2.9	
40		11	10.1	9					6.6	4.9	4.2			2.7	4.2
42		10.4	9.4	8.4	6.5					4.6	3.9	2.0		2.5	1.3
44		9.8	8.8	7.7	6.5	4.5				4.3	3.6	2.8			1.1
46			8.3	7.2	5.9	4.5				4	3.4	2.6	1 -		
48			7.8	6.6	5.3	4.2	2				3.1	2.4	1.5		
50			7.4	6.1	4.9	3.9	3				2.9	2.1	1.3		
52 54				5.9 5.6	4.6 4.4	3.6 3.4	2.7 2.5	1.6			2.8 2.6	2 1.8	1.1 1		
56				5.6	4.4 4.1	3.4	2.5	1.0			2.0	1.8	ı		
58				5.1	4.1	2.9	2.2	1.4				1.7			
60				5.1	3.8	2.9	1.8	1.2				1.4			
62					3.6	2.5	1.6					1.7			
64					3.5	2.3	1.4								
66					5.5	2.3	1.4								
68						2.1	1.1								
70						2	1								
72						1.9									
1 &						1.5								TAD	221122