메인	11.5	11.5	11.5	41.3	41.3	41.3	45	45	45	48.8	48.8	48.8	52	52	52
총연장길이	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
어댑터1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
연장붐1	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
연장붐2	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
연장붐3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
연장붐 4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
어댑터2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
픽스길이	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8
픽스각도	0	20	40	0	20	40	0	20	40	0	20	40	0	20	40
무게추	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35
overRear	х	х	х	х	х	х	х	х	х	х	х	х	х	х	х
optional	х	х	х	x	х	x	х	х	x	х	х	х	х	х	х
6	4.2														
7	3.9														
8	3.7														
9	3.6	3.8													
10	3.4	3.6	2.4	4.0											
12	3.1	3.3	3.4	4.2			2.0			2.2					
14 16	2.9 2.6	3 2.7	3.1 2.8	4 3.7	3.7		3.9			3.3 3.3			2.6		
18	2.6	2.7	2.6	3.6	3.5		3.6 3.5	3.4		3.3	3.3		2.6	2.6	
20	2.4	2.3	2.3	3.4	3.3	3.3	3.3	3.4	3.2	3.3	3.5 3.1		2.6	2.6	
22	2.2	2.3	2.3	3.4	3.2	3.1	3.2	3.1	3.1	3.1	3.1	3	2.5	2.5	2.5
24	1.9	1.9	2.1	3.1	3.2	3.1	3.2	3.1	2.9	2.9	2.8	2.8	2.4	2.4	2.4
26	1.8	1.8	1.8	2.9	2.8	2.8	2.9	2.8	2.8	2.8	2.7	2.7	2.2	2.2	2.3
28	1.7	1.7	1.7	2.8	2.7	2.7	2.8	2.7	2.7	2.7	2.6	2.6	2.1	2.1	2.2
30	1.5	1.6		2.7	2.6	2.6	2.6	2.6	2.5	2.6	2.5	2.5	2	2	2.1
32	1.4	1.4		2.5	2.5	2.4	2.5	2.4	2.4	2.5	2.4	2.4	1.9	1.9	2
34				2.4	2.3	2.3	2.4	2.3	2.3	2.4	2.3	2.3	1.8	1.8	1.9
36				2.3	2.2	2.2	2.3	2.2	2.2	2.3	2.2	2.2	1.7	1.7	1.8
38				2.2	2.1	2.1	2.2	2.2	2.1	2.2	2.1	2.1	1.7	1.7	1.7
40				2.1	2.1	2	2.1	2.1	2.1	2.1	2.1	2	1.6	1.6	1.6
42				2	2	2	2	2	2	2	2	2	1.5	1.5	1.5
44				1.9	1.9	1.9	2	1.9	1.9	1.9	1.9	1.9	1.4	1.5	1.5
46				1.9	1.8	1.8	1.9	1.8	1.9	1.9	1.9	1.9	1.4	1.4 1.3	1.4
48				1.8	1.8	1.8	1.8	1.8 1.7	1.8 1.7	1.8 1.7	1.8	1.8 1.7	1.3 1.3	1.3	1.3
50 52				1.8 1.7	1.7 1.7		1.8 1.7	1.7	1.7	1.7	1.7 1.6	1.7	1.3	1.3	1.3 1.2
54				1.7	1.7		1.7	1.7		1.4	1.6	1.7	1.1	1.2	1.2
56				1.5	1.5		1.3	1.6		1.2	1.4	1.5	0.9	1.2	1.1
58				1.3	1.4		1.1	1.4		0.8	0.9		0.5	0.8	1.1
60				1.2			0.9	1		0.0	0.5			0.0	
62				1				0.8							
UL								0.0					TAD 4740	62 / 17127	0 / 171277