=11.01											
메인	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	50	50
총연장길이	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
어댑터1 연장붐1	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	2.2 0	0
연장붐2	0	0	0	0	0	0	0	0	0	0	0
연장붐3	0	0	0	0	0	0	0	0	0	0	0
연장붐4	0	0	0	0	0	0	0	0	0	0	0
어댑터2	0	0	0	0	0	0	0	0	0	0	0
픽스길이	6	14	21	28	35	42	49	56	63	6	63
픽스각도	20	20	20	20	20	20	20	20	20	20	20
무게추	135	135	135	135	135	135	135	135	135	135	135
overRear	x	х	х	х	х	х	х	х	х	х	х
optional	0	Х	Х	Х	Х	Х	Х	Х	Х	0	Х
12 14	59 54									49.5 45	
16	50	35								41	
18	46.5	33.5								37.5	
20	43	32	25.7							34.5	
22	40	31	24.7	10.3						32	
24 26	37 34.5	29.9 28.8	23.7 22.9	18.3 17.6						29.9 27.7	
28	32	27.3	22.1	16.9	13.2					25.6	
30	29.9	25.7	21.2	16.3	12.7					23.7	
32	27.7	24.2	20.4	15.7	12.2	10				21.9	
34	25.8	22.8	19.6	15.2	11.7	9.6				20.4	
36	24.2	21.5	18.8	14.6	11.3	9.2	7.2			19.1	
38	22.6	20.2	17.9	14.1	10.9	8.9	6.9			18	
40	21.1	19.2	17	13.5	10.5	8.5	6.6	5.1		16.9	
42 44	19.8 18.7	18.2 17.3	16.1 15.2	13.1 12.6	10.2 9.8	8.2 7.9	6.3 6	4.9 4.7	3.7	15.8 14.8	3.6
46	17.7	16.4	14.5	12.0	9.4	7.7	5.8	4.7	3.7	13.8	3.4
48	16.7	15.4	13.8	11.7	9.1	7.4	5.6	4.3	3.3	13.0	3.3
50	15.8	14.5	13.2	11.3	8.8	7.2	5.4	4.2	3.2	12.1	3.1
52		13.7	12.6	11	8.4	7	5.2	4	3	11.3	3
54		13	12	10.7	8.1	6.8	5	3.8	2.9		2.9
56		12.3	11.4	10.2	7.9	6.5	4.9	3.7	2.8		2.7
58			10.8	9.7	7.6	6.3	4.7	3.6	2.6		2.6
60			10.3	9.2	7.4	6	4.6	3.5	2.5		2.5
62 64			9.7 9.2	8.8	7.2 7	5.8	4.4	3.3	2.4		2.4
66			9.2	8.4 8.1	6.8	5.7 5.5	4.2 4.1	3.2 3.1	2.3 2.1		2.2 2.1
68				7.7	6.6	5.3	3.9	3	2		2
70				7.2	6.4	5.2	3.8	2.8	1.9		1.8
72					6.2	5	3.7	2.7	1.8		
74					5.9	4.9	3.6	2.6	1.6		
76					5.7	4.8	3.5	2.5			
78 80					5.3	4.7	3.4	2.4			
80 82						4.6 4.5	3.3 3.2	2.3 2.2			
84						4.3	3.1	2.2			
86						5	3.1	2			
88							3.1	1.9			
90							3	1.8			
92							2.9	1.8			
94								1.8			
96								1.8			
98								1.7			TAB 221412