

Timeline Of Learner Success

As learners engage in a blended eLearning ecosystem, they will build up a history of learning experiences. When that eLearning ecosystem adheres to a framework dedicated to supporting and understanding the learner, such as the Total Learning Architecture (TLA), it becomes possible to retell their story through data. One important aspect of that story is the learner's history of success.

1 Ideal Statements

In order to accurately portray a learner's timeline of success, there are a few requirements of the data produced by a Learning Record Provider (LRP). They are as follows:

- the learner must be uniquely and consistently identified across all LRPs
- learning activities which access a learner's understanding of material should report if the learner was successful or not
 - if the assessment is scored, the grade earned by the learner should be reported
 - if the assessment is scored, the minimum and maximum possible grade should be reported
- The learning activities must be uniquely and consistently identified across all LRPs
- The time at which a learner completed a learning activity must be recorded
 - The timestamp should contain an appropriate level of specificity.
 - ie. Year, Month, Day, Hour, Minute, Second, Timezone

1.1 statement parameters to utilize

The statement parameter locations here are written in JSONPath. This notation is also compatible with the xAPI Z notation

- *\$.timestamp*
- *\$.result.success*
- *\$.actor*
- *\$.verb.id*

2 TLA Statement problems

The data collected at the TLA pilot run supports the following algorithm.

3 Algorithm

3.1 Summary

1. Query an LRS via a GET request to the statements endpoint using the parameters agent, since and until
2. Filter the results to the set of statements where:
 - *\$.verb.id* is one of:
 - <http://adlnet.gov/expapi/verbs/passed>
 - <https://w3id.org/xapi/dod-isd/verbs/answered>
 - <http://adlnet.gov/expapi/verbs/completed>
 - *\$.result.success* is true

3.2 Query an LRS via REST

How to query an LRS via a GET request to the Statements Resource ^{1 2}

```
Agent = "agent={\"account\":  
          {\"homePage\": \"https://example.homepage\",  
            \"name\": 123456}}\"  
  
Since = \"since=2018-07-20T12:08:47Z\"  
  
Until = \"until=2018-07-21T12:08:47Z\"  
  
Base = \"https://example.endpoint/statements?\"  
  
endpoint = Base + Agent + "&" + Since + "&" + Until  
  
Auth = Hash generated from basic auth  
  
S = curl -X GET -H \"Authorization: Auth\"  
        -H \"Content-Type: application/json\"  
        -H \"X-Experience-API-Version: 1.0.3\"  
        Endpoint
```

¹ *S* is the set of all statements parsed from the statements array within the HTTP response to the Curl request. It may be possible that multiple Curl requests are needed to retrieve all query results. If multiple requests are necessary, *S* is the result of concatenating the result of each request into a single set

² Querying an LRS will not be defined within the following Z specifications but the Results of the Query will be

3.3 xAPI Z Specifications

An xAPI statement(s) is only defined abstractly within the context of Z. A concrete definition for an xAPI statement(s) is outside the scope of this specification.

3.3.1 Basic Types

$IFI ::= mbox \mid mbox_sha1sum \mid openid \mid account$

- Type unique to Agents and Groups, The concrete definition of the listed values is outside the scope of this specification

$OBJECTTYPE ::= Agent \mid Group \mid SubStatement \mid StatementRef \mid Activity$

- A type which can be present in all activities as defined by the xAPI specification

$INTERACTIONTYPE ::= true-false \mid choice \mid fill-in \mid long-fill-in \mid matching \mid performance \mid sequencing \mid likert \mid numeric \mid other$

- A type which represents the possible interactionTypes as defined within the xAPI specification

$INTERACTIONCOMPONENT ::= choices \mid scale \mid source \mid target \mid steps$

- A type which represents the possible interaction components as defined within the xAPI specification
- the concrete definition of the listed values is outside the scope of this specification

$CONTEXTTYPES ::= parent \mid grouping \mid category \mid other$

- A type which represents the possible context types as defined within the xAPI specification

$[STATEMENT]$

- Basic types for the results of querying an LRS

$[AGENT, GROUP]$

- Basic types for Agents and collections of Agents

3.3.2 Id Schema

Id
$id : \mathbb{F}_1 \#1$

- the schema Id introduces the component id which is a non-empty finite set of 1 value

3.3.3 Schemas for Agents and Groups

<i>Agent</i>	
<i>agent</i> : <i>AGENT</i>	
<i>objectType</i> : <i>OBJECTTYPE</i>	
<i>name</i> : $\mathbb{F}_1 \#1$	
<i>ifi</i> : <i>IFI</i>	
<i>objectType</i> = <i>Agent</i>	
<i>agent</i> = $\{ifi\} \cup \mathbb{P}\{name, objectType\}$	

- The schema *Agent* introduces the component *agent* which is a set consisting of an *ifi* and optionally an *objectType* and/or *name*

<i>Member</i>	
<i>Agent</i>	
<i>member</i> : \mathbb{F}_1	
<i>member</i> = $\{a : AGENT \mid \forall a : a_0..a_n \bullet a = agent\}$	

- The schema *Member* introduces the component *member* which is a set of objects *a*, where for every *a* within $a_0..a_n$, *a* is an *agent*

<i>Group</i>	
<i>Member</i>	
<i>group</i> : <i>GROUP</i>	
<i>objectType</i> : <i>OBJECTTYPE</i>	
<i>ifi</i> : <i>IFI</i>	
<i>name</i> : $\mathbb{F}_1 \#1$	
<i>objectType</i> = <i>Group</i>	
<i>group</i> = $\{objectType, name, member\} \vee \{objectType, member\} \vee \{objectType, ifi\} \cup \mathbb{P}\{name, member\}$	

- The schema *Group* introduces the component *group* which is of type *GROUP* and is a set of either *objectType* and *member* with optionally *name* or *objectType* and *ifi* with optionally *name* and/or *member*

<i>Actor</i>	
<i>Agent</i>	
<i>Group</i>	
<i>actor</i> : <i>AGENT</i> \vee <i>GROUP</i>	
<i>actor</i> = <i>agent</i> \vee <i>group</i>	

- The schema *Actor* introduces the component *actor* which is either an *agent* or *group*

3.3.4 Verb Schema

<i>Verb</i>	_____
<i>Id</i>	
$display, verb : \mathbb{F}_1$	
$verb = \{id, display\} \vee \{id\}$	

- The schema *Verb* introduces the component *verb* which is a set that consists of either *id* and the finite set *display* or just *id*

3.3.5 Object Schema

<i>Extensions</i>	_____
$extensions, extensionVal : \mathbb{F}_1$	
$extensionId : \mathbb{F}_1 \# 1$	
$extensions = \{e : (extensionId, extensionVal) \mid \forall i, j : e_i..e_j \bullet$ $(extensionId_i, extensionVal_i) \vee (extensionId_i, extensionVal_j) \wedge$ $(extensionId_j, extensionVal_i) \vee (extensionId_j, extensionVal_j) \wedge$ $extensionId_i \neq extensionId_j\}$	

- The schema *Extensions* introduces the component *extensions* which is a non-empty finite set that consists of ordered pairs of *extensionId* and *extensionVal*. Different *extensionIds* can have the same *extensionVal* but there can not be two identical *extensionId* values
- *extensionId* is a non-empty finite set with one value
- *extensionVal* is a non-empty finite set

<i>InteractionActivity</i>	_____
$interactionType : INTERACTIONTYPE$	
$correctResponsePattern : seq_1$	
$interactionComponent : INTERACTIONCOMPONENT$	
$interactionActivity = \{interactionType, correctReponsePattern, interactionComponent\} \vee$ $\{interactionType, correctResponsePattern\}$	

- The schema *InteractionActivity* introduces the component *interactionActivity* which is a set of either *interactionType* and *correctResponsePattern* or *interactionType* and *correctResponsePattern* and *interactionComponent*

<i>Definition</i>
<i>InteractionActivity</i>
<i>Extensions</i>
$definition, name, description : \mathbb{F}_1$
$type, moreInfo : \mathbb{F}_1 \#1$
$definition = \mathbb{P}_1\{name, description, type, moreInfo, extensions, interactionActivity\}$

- The schema *Definition* introduces the component *definition* which is the non-empty, finite power set of *name*, *description*, *type*, *moreInfo* and *extensions*

<i>Object</i>
<i>Id</i>
<i>Definition</i>
<i>Agent</i>
<i>Group</i>
<i>Statement</i>
$objectTypeA, objectTypeS, objectTypeSub, objectType : OBJECTTYPE$
$substatement : STATEMENT$
$object : \mathbb{F}_1$
$substatement = statement$
$objectTypeA = Activity$
$objectTypeS = StatementRef$
$objectTypeSub = SubStatement$
$objectType = objectTypeA \vee objectTypeS$
$object = \{id\} \vee \{id, objectType\} \vee \{id, objectTypeA, definition\}$
$\vee \{id, definition\} \vee \{agent\} \vee \{group\} \vee \{objectTypeSub, substatement\}$
$\vee \{id, objectTypeA\}$

- The schema *Object* introduces the component *object* which is a non-empty finite set of either *id*, *id* and *objectType*, *id* and *objectTypeA* and *definition*, *agent*, *group*, or *substatement*
- The schema *Statement* and the corresponding component *statement* will be defined later on in this specification

3.3.6 Result Schema

<i>Score</i>
<i>score</i> : \mathbb{F}_1
<i>scaled, min, max, raw</i> : \mathbb{Z}
<i>scaled</i> = $\{n : \mathbb{Z} \mid -1.0 \leq n \leq 1.0\}$
<i>min</i> = $n < max$
<i>max</i> = $n > min$
<i>raw</i> = $\{n : \mathbb{Z} \mid min \leq n \leq max\}$
<i>score</i> = $\mathbb{P}_1\{scaled, raw, min, max\}$

- The schema *Score* introduces the component *score* which is the non-empty powerset of *min*, *max*, *raw* and *scaled*

<i>Result</i>
<i>Score</i>
<i>Extensions</i>
<i>success, completion, response, duration</i> : $\mathbb{F}_1 \#1$
<i>result</i> : \mathbb{F}_1
<i>success</i> = $\{true\} \vee \{false\}$
<i>completion</i> = $\{true\} \vee \{false\}$
<i>result</i> = $\mathbb{P}_1\{score, success, completion, response, duration, extensions\}$

- The schema *Result* introduces the component *result* which is the non-empty power set of *score*, *success*, *completion*, *response*, *duration* and *extensions*

3.3.7 Context Schema

<i>Instructor</i>
<i>Agent</i>
<i>Group</i>
<i>instructor</i> : $AGENT \vee GROUP$
<i>instructor</i> = $agent \vee group$

- The schema *Instructor* introduces the component *instructor* which can be ether an *agent* or a *group*

<i>Team</i>
<i>Group</i>
<i>team</i> : $GROUP$
<i>team</i> = $group$

- The schema *Team* introduces the component *team* which is a *group*

<i>Context</i> <i>Instructor</i> <i>Team</i> <i>Object</i> <i>Extensions</i> <i>registration, revision, platform, language</i> : $\mathbb{F}_1 \#1$ <i>parentT, groupingT, categoryT, otherT</i> : <i>CONTEXTTYPES</i> <i>contextActivities, statement</i> : \mathbb{F}_1
<i>statement</i> = <i>object</i> \ (<i>id, objectType, agent, group, definition</i>) <i>parentT</i> = <i>parent</i> <i>groupingT</i> = <i>grouping</i> <i>categoryT</i> = <i>category</i> <i>otherT</i> = <i>other</i> <i>contextActivity</i> = { <i>ca</i> : <i>object</i> \ (<i>agent, group, objectType, objectTypeSub, substatement</i>)} <i>contextActivityParent</i> = (<i>parentT, contextActivity</i>) <i>contextActivityCategory</i> = (<i>categoryT, contextActivity</i>) <i>contextActivityGrouping</i> = (<i>groupingT, contextActivity</i>) <i>contextActivityOther</i> = (<i>otherT, contextActivity</i>) <i>contextActivities</i> = $\mathbb{P}_1\{\textit{contextActivityParent}, \textit{contextActivityCategory},$ <i>contextActivityGrouping, contextActivityOther</i> $\}$ <i>context</i> = $\mathbb{P}_1\{\textit{registration}, \textit{instructor}, \textit{team}, \textit{contextActivities}, \textit{revision},$ <i>platform, language, statement, extensions</i> $\}$

- The schema *Context* introduces the component *context* which is the non-empty powerset of *registration, instructor, team, contextActivities, revision, platform, language, statement* and *extensions*

3.3.8 Timestamp and Stored Schema

<i>Timestamp</i> <i>timestamp</i> : $\mathbb{F}_1 \#1$
<i>Stored</i> <i>stored</i> : $\mathbb{F}_1 \#1$

- The schema *Timestamp* and *stored* introduce the components *timestamp* and *stored* respectively. Each are non-empty finite sets containing one value

3.3.9 Attachements Schema

<i>Attachments</i>
$display, description, attachment, attachments : \mathbb{F}_1$ $usageType, sha2, fileUrl, contextType : \mathbb{F}_1 \#1$ $length : \mathbb{N}$
$attachment = \{usageType, display, contentType, length, sha2\} \cup \mathbb{P}\{description, fileUrl\}$ $attachments = \{a : attachment\}$

3.3.10 Statement and Statements Schema

<i>Statement</i>
Id $Actor$ $Verb$ $Object$ $Result$ $Context$ $Timestamp$ $Stored$ $Attachments$ $statement, \$: STATEMENT$
$statement = \{actor, verb, object, stored\} \cup \mathbb{P}\{id, result, context, timestamp, attachments\}$

- The schema *Statement* introduces the component *statement* which consists of the components *actor*, *verb*, *object* and *stored* and the optional components *id*, *result*, *context*, *timestamp*, and/or *attachments*
- The schema *Statement* allows for subcomponent of *statement* to be referenced via the . (selection) operator

<i>Statements</i>
$Statement$ $statements : \mathbb{F}$
$statements = \{s : statement\}$

- The schema *Statements* introduces the component *statements* which is a non-empty finite set of components *statement*

3.4 Timeline Learner Success Z Specifications

The following Z Schemas define the system state, initialization and operations necessary to perform the Timeline Learner Success Algorithm

3.4.1 Timeline Leaner Success Basic Types

$COMPLETION ::=$
 $\{http : //adlnet.gov/expapi/verbs/passed\} |$
 $\{https : //w3id.org/xapi/dod - isd/verbs/answered\} |$
 $\{http : //adlnet.gov/expapi/verbs/completed\}$

$SUCCESS ::= \{true\}$

3.4.2 Timeline Leaner Success System State

$TimelineLearnerSuccess$
$Statements$
$S_{all} : \mathbb{F}_1$
$S_{completion}, S_{success} : \mathbb{F}$
$S_{all} = statements$
$S_{completion} \subseteq S_{all}$
$S_{success} \subseteq S_{completion}$

- The set S_{all} is a non-empty finite set and is the component *statements*
- The sets $S_{completion}$ and $S_{success}$ are both finite sets
- the set $S_{completion}$ is a subset of S_{all}
- the set $S_{success}$ is a subset of $S_{completion}$

3.4.3 Initial State of Timeline Learner Success System

$InitTimelineLearnerSuccess$
$TimelineLearnerSuccess$
$S_{all} \neq \emptyset$
$S_{completion} = \emptyset$
$S_{success} = \emptyset$

- The set S_{all} is a non-empty set
- The sets $S_{completion}, S_{success}$ are both initially empty

3.4.4 Filter for Completion

<i>Completion</i> <i>Statement</i> $completion : STATEMENT \rightarrow \mathbb{F}$ $s? : STATEMENT$ $s! : \mathbb{F}$
$s? = statement$ $s! = completion(s?)$ $completion(s?) = \text{if } s?.verb.id : COMPLETION \text{ then } s! = s? \text{ else } s! = \emptyset$

- The schema *Completion* introduces the function *completion* which takes in the variable *s?* and returns the variable *s!*
- The variable *s?* is the component *statement*
- *s!* is equal to *s?* if *\$.verb.id* is of the type *COMPLETION* otherwise *s!* is an empty set

<i>FilterForCompletion</i> $\Delta TimelineLearnerSuccess$ <i>Completion</i> $completions : \mathbb{F}$
$completions = S_{all}$ $completions' = \{s : STATEMENT \mid completion(s) \neq \emptyset\}$ $S'_{completion} = S_{completion} \cup completions'$

- the set *completions* is the set *S_{all}*
- The set *completions'* is the set of all statements *s* where the result of *completion(s)* is not an empty set
- the updated set *S'_{completion}* is the union of the previous state of set *S_{completion}* and the set *completions*

3.4.5 Filter for Success

<i>Success</i> <i>Statement</i> $success : STATEMENT \rightarrow \mathbb{F}$ $s? : STATEMENT$ $s! : \mathbb{F}$
$s? = statement$ $s! = success(s?)$ $success(s?) = \text{if } s?.result.success : SUCCESS \text{ then } s! = s? \text{ else } s! = \emptyset$

- the schema *Success* introduces the function *success* which takes in the variable *s*? and returns the variable *s*!
- the variable *s*? is the component *statement*
- *s*! is equal to *s*? if *\$.result.success* is of the type *SUCCESS* otherwise *s*! is an empty set

<i>FilterForSuccess</i>	_____
$\Delta TimelineLearnerSuccess$	
<i>Success</i>	
<i>successes</i> : \mathbb{F}	
$successes = S_{completion}$	
$successes' = \{s : STATEMENT \mid success(s) \neq \emptyset\}$	
$S'_{success} = S_{success} \cup successes$	

- the set *successes* is the set *S_{completion}*
- The set *successes'* contains elements *s* of type *STATEMENT* where *success(s)* is not an empty set
- The updated set *S'_{success}* is the union of the previous state of *S_{success}* and *successes*

3.4.6 Sequence of Operations

FilterStatements $\hat{=}$ *FilterForCompletion* ; *FilterForSuccess*

- The schema *FilterStatements* is the sequential composition of operation schemas *FilterForCompletion* and *FilterForSuccess*
- *FilterForCompletion* happens before *FilterForSuccess*

3.4.7 Return

<i>Return</i>	_____
$\Xi TimelineLearnerSuccess$	
<i>FilterStatements</i>	
<i>S_{success}!</i> : \mathbb{F}	
$S_{success}! = S_{success}$	

- The returned variable *S_{success}!* is equal to the current state of variable *S_{success}* after the operations *FilterForCompletion* and *FilterForSuccess*

3.5 Pseudocode

Algorithm 1: Timeline of Learner Success

```
Input:  $S_{all}$ 
Result:  $S_{success}$ 
while  $S_{all}$  is not empty do
  for each statement  $s$  in  $S_{all}$ 
    if  $s.verb.id = COMPLETION$  then
      | add  $s$  to  $S_{completion}$ 
    else
      | noop
    end
  end
while  $S_{completion}$  is not empty do
  for each statement  $sc$  in  $S_{completion}$ 
    if  $sc.result.success = SUCCESS$  then
      | add  $sc$  to  $S_{success}$ 
    else
      | noop
    end
  end
end
```

3.6 Result JSON Schema

```
{
  "$schema": "http://json-schema.org/draft-04/schema#",
  "id": "#statement_list",
  "type": "array",
  "items": {"$ref": "#statement"}
}
```

3.7 Visualization Description

description of the associated visualization in english

3.8 Visualization prototype

This section will be updated to a prototype viz