

Annual Performance Review 2024: Mark Simmons

by
Mark Simmons

Annual Performance Review submitted to the Department of Mathematics,
College of Natural Sciences and Mathematics,
University of Houston.

Chair of Committee: Loic Cappanera

Committee Member: TBD

Committee Member: TBD

Committee Member: TBD

University of Houston
March, 2024

Copyright 2019, Mark Simmons

ABSTRACT

Write abstract here.

TABLE OF CONTENTS

ABSTRACT	iii
LIST OF FIGURES	v
LIST OF TABLES	vi
1 Introduction	1
1.1 Context and motivations	1
1.2 APR Outline	1
2 Model problem and Equations	3
2.1 Chapter 2-section 1	3
3 Chapter 3-Convergence Results	4
3.1 Chapter 3 - Section 1	4
3.1.1 Quarter of Five Spot Problem	4
3.1.2 Numerical Results	5
4 Conclusion	8
4.1 Outcome	8
4.2 Outlook	8

LIST OF FIGURES

LIST OF TABLES

3.1	Template table-description for list of tables.	5
3.2	Template table-description for list of tables.	5
3.3	Template table-description for list of tables.	6
3.4	Template table-description for list of tables.	6
3.5	Template table-description for list of tables.	6
3.6	Template table-description for list of tables.	6
3.7	Template table-description for list of tables.	7
3.8	Template table-description for list of tables.	7
3.9	Template table-description for list of tables.	7

Chapter 1

Introduction

Contents

1.1	Context and motivations	1
1.2	APR Outline	1

1.1 Context and motivations

Modeling three-phase flow has important application in petroleum engineering, and environmental science. Accurately capturing physical outcomes from fluids such as oil, gas, and water in an underground reservoir is crucial for the oil and gas industry. The following discussion and analysis of numerical solutions provide a robust model to solve these coupled non-linear partial differential equations in a way that accurately describes physical phenomenon we can observe.

1.2 APR Outline

This APR includes 4 chapters. Chapter 1 provides a brief overview of the model problem and equations on the 3-phase 3-component black oil model. Chapter 2 gives information and detail surrounding time discretization and a new stabilization method proof. Chapter 3 will give details surrounding space discretization. Chapter 4 will give convergence results for a test on manufactured

solutions and simulation results on a 2-D domain. Finally, a conclusion including a summary of the APR and details surrounding future work.

Chapter 2

Model problem and Equations

Contents

2.1	Chapter 2-section 1	3
-----	-------------------------------	---

2.1 Chapter 2-section 1

Chapter 3

Chapter 3 Title

Contents

3.1	Chapter 3 - Section 1	4
3.1.1	Quarter of Five Spot Problem	4
3.1.2	Numerical Results	5

3.1 Chapter 3 - Section 1

3.1.1 Quarter of Five Spot Problem

The domain is $\Omega = [0, 100]^2 \setminus \{[0, 5]^2 \cup [95, 100]^2\} m^2$, i.e., it is the square $[0, 100]^2 m^2$ where two corners have been cut out; see following figure.

The boundary conditions are

Inflow on $\Gamma_1 : p_\ell = 3 \times 10^5 Pa, s_a = 0.7$

Outflow on $\Gamma_4 : p_\ell = 10^5 Pa, \lambda_a \kappa \nabla p_c \cdot \mathbf{n} = 0$

No-Flow on $\Gamma_2 \cup \Gamma_3 \cup \Gamma_5 \cup \Gamma_6 : \lambda_\ell \kappa \nabla p_\ell \cdot \mathbf{n} = 0, \lambda_a \kappa \nabla p_c \cdot \mathbf{n} = 0$.

The initial conditions are $s_a = 0.2$ and $p_\ell = 10^5 \text{ Pa}$. The rest of the flow properties are given by:

$$\phi = 0.2, \quad \mu_\ell = 2 \times 10^{-3} \text{ Pa} \cdot \text{s}, \quad \mu_a = 5 \times 10^{-4} \text{ Pa} \cdot \text{s}.$$

The relative permeability for each phase and capillary pressure follow a Brooks-Corey model:

$$\kappa_\ell = (1 - s_a)^2(1 - s_a^{5/3}), \quad \kappa_a = s_a^{11/3}, \quad p_c = 5 \times 10^3 s_a^{-1/3}$$

We consider a heterogeneous medium where $\kappa = 5 \times 10^{-8} m^2$ everywhere, except for in the square $[25, 50] \times [25, 50]$ where κ is 1,000 times lower.

3.1.2 Numerical Results

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	64	2.20E-2	-	8.81E-3	-	3.58E-2	-
0.125	256	5.70E-3	1.95	4.41E-3	0.99	1.15E-2	1.64
0.0625	1024	1.31E-3	2.12	2.24E-3	0.98	5.55E-3	1.06
0.03125	4096	4.43E-4	1.56	1.12E-3	0.96	2.56E-3	1.11
0.015625	16384	1.67E-4	1.41	5.80E-4	0.99	1.26E-3	1.03

Table 3.1: rates of convergence for $\mathbb{Q}_1 - \mathbb{RT}_1 - \text{BDF1}$

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	64	2.11E-2	-	8.44E-3	-	4.08E-2	-
0.0625	256	5.55E-3	1.94	2.20E-3	1.94	5.08E-3	3.01
0.015625	1024	1.38E-3	1.99	5.55E-4	1.98	1.17E-3	2.12
0.003906	4096	3.44E-4	2.01	1.39E-4	2.00	2.89E-4	2.02
0.000976	16384	8.71E-5	1.98	3.47E-5	2.00	7.21E-5	2.00

Table 3.2: rates of convergence for $\mathbb{Q}_1 - \mathbb{RT}_1 - \text{BDF1}$ where $\Delta t = h^2$

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	144	3.94E-3	-	8.62E-3	-	3.43E-2	-
0.125	576	3.14E-3	0.32	4.41E-3	0.97	1.12E-2	1.55
0.0625	2304	6.22E-4	2.34	2.25E-3	0.97	5.54E-3	1.08
0.03125	9216	3.21E-4	0.96	1.15E-3	0.94	2.57E-3	1.11
0.015625	36864	1.49E-4	1.10	5.81E-5	0.99	1.26E-3	1.03

Table 3.3: rates of convergence for $\mathbb{Q}_2 - \mathbb{RT}_2 - \text{BDF1}$

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	144	3.61E-3	-	8.62E-3	-	3.43E-2	-
0.0625	576	7.33E-4	2.30	4.41E-3	1.83	1.12E-2	2.96
0.015625	2304	1.81E-4	2.02	2.25E-3	1.96	5.54E-3	2.11
0.00390625	9216	4.35E-5	2.06	1.15E-3	1.99	2.57E-3	2.02
0.000976	36384	1.08E-5	2.01	3.76E-5	2.00	7.16E-5	2.01

Table 3.4: rates of convergence for $\mathbb{Q}_2 - \mathbb{RT}_2 - \text{BDF1}$ where $\Delta t = h^2$

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	64	3.61E-3	-	8.62E-3	-	3.43E-2	-
0.0625	256	7.33E-4	2.30	4.41E-3	1.83	1.12E-2	2.96
0.015625	1024	1.81E-4	2.02	2.25E-3	1.96	5.54E-3	2.11
0.00390625	4096	4.35E-5	2.06	1.15E-3	1.99	2.57E-3	2.02
0.000976	16384	1.08E-5	2.01	3.76E-5	2.00	7.16E-5	2.01

Table 3.5: rates of convergence for $\mathbb{Q}_1 - \mathbb{RT}_1 - \text{BDF1 STAB METHOD}$

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	64	2.38E-2	-	9.23E-3	-	2.39E-2	-
0.0625	256	5.52E-3	2.11	2.37E-3	1.96	5.27E-3	2.18
0.015625	1024	1.39E-3	1.99	6.04E-4	1.97	1.19E-3	2.15
0.00390625	4096	3.50E-4	1.99	1.51E-4	2.00	2.91E-4	2.03
0.000976	16384	8.79E-5	2.00	3.78E-5	2.00	7.25E-5	2.00

Table 3.6: rates of convergence for $\mathbb{Q}_1 - \mathbb{RT}_1 - \text{BDF1}$ where $\Delta t = h^2$ STAB METHOD

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	144	4.72E-3	-	9.11E-3	-	2.22E-2	-
0.0625	576	1.88E-3	1.33	4.69E-3	0.96	1.27E-2	0.80
0.015625	2304	9.48E-4	0.99	2.43E-3	0.94	5.31E-3	1.26
0.00390625	9216	4.40E-4	1.11	1.24E-3	0.97	2.50E-3	1.09
0.000976	36384	2.08E-4	1.08	6.27E-4	0.99	1.12E-3	1.04

Table 3.7: rates of convergence for $\mathbb{Q}_2 - \mathbb{RT}_2$ - BDF1 STAB METHOD

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	144	3.61E-3	-	8.62E-3	-	3.43E-2	-
0.0625	576	7.33E-4	2.30	4.41E-3	1.83	1.12E-2	2.96
0.015625	2304	1.81E-4	2.02	2.25E-3	1.96	5.54E-3	2.11
0.00390625	9216	4.35E-5	2.06	1.15E-3	1.99	2.57E-3	2.02
0.000976	36384	1.08E-5	2.01	3.76E-5	2.00	7.16E-5	2.01

Table 3.8: rates of convergence for $\mathbb{Q}_2 - \mathbb{RT}_2$ - BDF1 where $\Delta t = h^2$ STAB METHOD

Δt	DOF's	p_ℓ		S_a		S_v	
		L^2 error	Rate	L^2 error	Rate	L^2 error	Rate
0.25	144	4.72E-3	-	9.11E-3	-	2.22E-2	-
0.0625	576	4.42E-4	3.42	1.12E-3	2.87	2.51E-3	3.15
0.015625	2304	5.03E-5	3.13	1.58E-4	2.98	2.97E-4	3.08
0.00390625	9216	6.29E-6	3.00	1.98E-5	3.00	3.68E-5	3.01

Table 3.9: rates of convergence for $\mathbb{Q}_2 - \mathbb{RT}_2$ - BDF1 where $\Delta t = h^3$ STAB METHOD

Chapter 4

Conclusion

4.1 Outcome

4.2 Outlook

