

Logging & Monitoring

Owner: Mark Stolte, Founder — markstolte02@gmail.com

Last reviewed: 2026-07-05

Stage: Pre-launch / active development

Purpose

States what Penny Pilot currently observes about its own systems, what it deliberately does not log, and what monitoring gaps exist while the app is pre-launch.

What's logged today

Source	What it captures	Access
Supabase Auth logs	Sign-in events, token refresh, provider (Apple/Google) errors	Supabase project dashboard (founder only)
Supabase Postgres logs	Query errors, slow queries	Supabase project dashboard (founder only)
Supabase Edge Function logs (<code>plaid-create-link-token</code> , <code>plaid-exchange-public-token</code> , <code>plaid-sync-transactions</code>)	Request handling, Plaid API errors, thrown exceptions	Supabase project dashboard (founder only)
Expo/EAS build logs	Build success/failure, native build warnings	Expo/EAS dashboard (founder only)
Client-side console warnings (development only)	React/Expo runtime warnings during local development (e.g., surfaced via the browser dev preview)	Local machine only; not collected or transmitted from end-user devices

What is deliberately never logged

- Full Plaid access tokens, in either plaintext or ciphertext form, are not written to application logs — Edge Functions reference stored Plaid items by their database `id`, not by token value.
- The Plaid token-encryption key and other Edge Function secrets are never logged or printed.
- Raw transaction detail is not intentionally logged beyond what Supabase/Plaid's own request logging captures as part of normal API operation; application code should log identifiers (transaction id, user id) rather than merchant/amount detail when debugging.

What's not in place yet

- **No centralized log aggregation or SIEM.** Logs are viewed per-vendor (Supabase dashboard, Expo dashboard) rather than in one place. Appropriate for the current scale and user count (effectively pre-launch), but a real gap once there's a production user base to protect.
- **No automated alerting** on security-relevant signals — e.g., a spike in failed sign-ins, Edge Function error rate, or Plaid `ITEM_LOGIN_REQUIRED`/reconnect events. These are currently only visible if manually checked in the Supabase dashboard.
- **No anomaly detection** on access patterns (e.g., a single account's data being read from an unusual location or at unusual volume).

Planned improvements (before scaling past pre-launch)

1. Enable Supabase log drains or scheduled alerts for Edge Function error-rate spikes and repeated Auth failures.
2. Add an explicit alert on Plaid item status transitioning to `needs-reconnect` or `error` in bulk (could indicate either a Plaid-side incident or a problem in the sync function), building on the `status` column already present on `plaid_items`.
3. Define a minimum retention period for security-relevant logs once a log aggregation solution is chosen, rather than relying on each vendor's default retention window.

Retention

Log retention today follows each vendor's default retention for the current plan tier (Supabase, Expo/EAS) — not independently configured or extended. This is noted as a baseline to revisit once compliance or investigative needs require a longer window.