

Coherent PDF Library (libcpdf)

Developer's Manual

Version 1.8 (December 2013)



Coherent Graphics Ltd

For bug reports, feature requests and comments, email
contact@coherentgraphics.co.uk

©2013 Coherent Graphics Limited. All rights reserved.

Adobe, Acrobat, Adobe PDF, Adobe Reader and PostScript are registered trademarks of Adobe Systems Incorporated. Windows is a registered trademarks of Microsoft Corporation.

Contents

Contents	iii
1 Preliminaries	5
2 Basics	7
3 Merging and Splitting	9
4 Pages	11
5 Encryption	13
6 Compression	15
7 Bookmarks	17
8 Presentations	19
9 Logos, Watermarks and Stamps	21
10 Multipage Facilities	23
11 Document Information and Metadata	25
12 File Attachments	27
13 Miscellaneous	29
14 Page Labels	31
15 Special functionality 1. – Encryption and Permission status	33
16 Special functionality 2. – Undo	35
A Dates	37
B Example Program in C	39

Notes

The chapters are numbered to be the same as those in the manual for the Coherent PDF Command Line Tools ([cpdfmanual.pdf](#)).

Installation

The Coherent PDF Library is provided either in compiled form (the archive file `libcpdf.a` and the library header `cpdfplibwrapper.h`), or as source code. Instructions for building from source are included in the distribution.

Place `libcpdf.a` somewhere suitable. Instruct your C linker to link with it. Place `cpdfplibwrapper.h` somewhere suitable and instruct your C compiler to search for headers there. The library is now ready for use.

1 Preliminaries

```
/* The function cpdf_startup must be called with argv before using the
library. */
void cpdf_startup (char **);

/* Set demo mode. Upon library startup is false. If set, files written will
 * have the text DEMO stamped over each page. This stamping will also slow down
 * the library significantly. */
void cpdf_setDemo(int);

/* Errors. lastError and lastErrorString hold information about the last error
 * to have occurred. They should be consulted after each call. If
 * cpdf_lastError is non-zero, there was an error, and cpdf_lastErrorString
 * gives details. If cpdf_lastError is zero, there was no error on the most
 * recent cpdf call. */
int cpdf_lastError;
char* cpdf_lastErrorString;

/* Clear the current error state. */
void cpdf_clearError (void);

/* A debug function which prints some information about resource usage. This
 * can be used to detect if PDFs or ranges are being deallocated properly. */
void cpdf_onExit (void);

/* Remove a PDF from memory, given its number. */
void cpdf_deletePdf(int);

/* Calling replacePdf(a, b) places PDF b under number a. Original a and b are
 * no longer available. */
void cpdf_replacePdf(int, int);

/* To enumerate the list of currently allocated PDFs, call
 * cpdf_startEnumeratePDFs which gives the number, n, of PDFs allocated, then
 * cpdf_enumeratePDFsInfo and cpdf_enumeratePDFsKey with index numbers from
 * 0...(n - 1). Call cpdf_endEnumeratePDFs to clean up. */
int cpdf_startEnumeratePDFs(void);
int cpdf_enumeratePDFsKey(int);
char* cpdf_enumeratePDFsInfo(int);
void cpdf_endEnumeratePDFs(void);
```

2 Basics

3 Merging and Splitting

4 Pages

5 Encryption

6 Compression

7 Bookmarks

8 Presentations

9 Logos, Watermarks and Stamps

10 Multipage Facilities

11 Document Information and Metadata

12 File Attachments

13 Miscellaneous

14 Page Labels

15 Special functionality 1. – Encryption and Permission status

16 Special functionality 2. – Undo

A Dates

Dates in PDF are specified according to the following format:

`D : YYYYMMDDHHmmSSOHH' mm'`

where:

- YYYY is the year;
- MM is the month;
- DD is the day (01-31);
- HH is the hour (00-23);
- mm is the minute (00-59);
- SS is the second (00-59);
- O is the relationship of local time to Universal Time (UT), denoted by '+', '-' or 'Z';
- HH is the absolute value of the offset from UT in hours (00-23);
- mm is the absolute value of the offset from UT in minutes (00-59).

A contiguous prefix of the parts above can be used instead, for lower accuracy dates. For example:

`D : 2011 (2011)`

`D : 20110103 (3rd March 2011)`

`D : 201101031854-08' 00' (3rd March 2011, 6:54PM, US Pacific Standard Time)`

B Example Program in C

This program loads a file from disk, adds page numbers, and then writes the file encrypted to disk.

