Pre Plane Assembly Summary

Panel No	Plane No	Cleaned/ Prepped		Missing wires	Missing wires confirmed	PFN & stnd. off epoxy	install	Ear leak test	Prep Finished	Pre Assy gas leak test -
mn 175	. 24	0 V	#0 et	#0	#0	U MAN O	girey /		0	· / -
Repairs •	ear fl added ep	coded oxy to mi	iddle rib or	n HV side						
HV issues	·jas lea l'vire	th at 01	UB HVSi	de <del>appor</del>	-) grepain -) -) disconne	ok new				
Notes ?	Fess test - O No blocked straw  Fess test - O Should put the kapten dish at straw 28, 29 to present prevent  HN test - O should put the kapten dish at straw 28, 29 to prevent  pars acfest  Bad) Inner (short) cover screw hole - test side (marked) Cover screw  That an insert - barb needs filing down  Standoffs are good  Air tested for blocked straws - #O/Rt,  Making special screw  Making special screw  Making special screw  The leader under 10m 8 t 5 mil Kanlandrak - OK									
,	Standof Air lester Air Les	fs are d	good oclod Str	aws -	-#O/Rt, 1 (Capton che	ck-oK	Ĭ.	laking spe	ly allows	1.75 turns + washer
t (	Pfn's che	ck-ok	conns							