

# Artificial Intelligence

## Constraint Satisfaction Problems




# What is Search For?

- Assumptions about the world: a single agent, deterministic actions, fully observed state, discrete state space
- Planning: sequences of actions
  - The path to the goal is the important thing
  - Paths have various costs, depths
  - Heuristics give problem-specific guidance
- Identification: assignments to variables
  - The goal itself is important, not the path
  - All paths at the same depth (for some formulations)
  - CSPs are a specialized class of identification problems





# Constraint Satisfaction Problems

---




# Constraint Satisfaction Problems

- Standard search problems:
  - State is a “black box”: arbitrary data structure
  - Goal test can be any function over states
  - Successor function can also be anything
- Constraint satisfaction problems (CSPs):
  - A special subset of search problems
  - State is defined by **variables  $X_i$**  with values from a **domain  $D$**  (sometimes  $D$  depends on  $i$ )
  - Goal test is a **set of constraints** specifying allowable combinations of values for subsets of variables
- Simple example of a *formal representation language*
- Allows useful general-purpose algorithms with more power than standard search algorithms



# CSP Examples



# Example: Map Coloring



- Variables: WA, NT, Q, NSW, V, SA, T
- Domains:  $D = \{\text{red, green, blue}\}$
- Constraints: adjacent regions must have different colors

Implicit:  $WA \neq NT$

Explicit:  $(WA, NT) \in \{(\text{red, green}), (\text{red, blue}), \dots\}$

- Solutions are assignments satisfying all constraints, e.g.:

$\{WA=\text{red}, NT=\text{green}, Q=\text{red}, NSW=\text{green}, V=\text{red}, SA=\text{blue}, T=\text{green}\}$







# Example: N-Queens

## ■ Formulation 1:

- Variables:  $X_{ij}$
- Domains:  $\{0, 1\}$
- Constraints



$$\forall i, j, k \quad (X_{ij}, X_{ik}) \in \{(0, 0), (0, 1), (1, 0)\}$$

$$\forall i, j, k \quad (X_{ij}, X_{kj}) \in \{(0, 0), (0, 1), (1, 0)\}$$

$$\forall i, j, k \quad (X_{ij}, X_{i+k, j+k}) \in \{(0, 0), (0, 1), (1, 0)\}$$

$$\forall i, j, k \quad (X_{ij}, X_{i+k, j-k}) \in \{(0, 0), (0, 1), (1, 0)\}$$

$$\sum_{i,j} X_{ij} = N$$

# Example: N-Queens

- Formulation 2:

- Variables:  $Q_k$


- Domains:  $\{1, 2, 3, \dots, N\}$

- Constraints:

Implicit:  $\forall i, j \text{ non-threatening}(Q_i, Q_j)$

Explicit:  $(Q_1, Q_2) \in \{(1, 3), (1, 4), \dots\}$


...






# Constraint Graphs

---



# Constraint Graphs

- Binary CSP: each constraint relates (at most) two variables
- Binary constraint graph: nodes are variables, arcs show constraints
- General-purpose CSP algorithms use the graph structure to speed up search. E.g., Tasmania is an independent subproblem!



# Example: Cryptarithmic

- Variables:

$F T U W R O X_1 X_2 X_3$

- Domains:

$\{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$


- Constraints:

$\text{alldiff}(F, T, U, W, R, O)$


$O + O = R + 10 \cdot X_1$

...

$$\begin{array}{r} T W O \\ + T W O \\ \hline F O U R \end{array}$$





# Example: Sudoku



- Variables:
  - Each (open) square
- Domains:
  - $\{1,2,\dots,9\}$
- Constraints:
  - 9-way alldiff for each column
  - 9-way alldiff for each row
  - 9-way alldiff for each region
  - (or can have a bunch of pairwise inequality constraints)

# Example: The Waltz Algorithm

- The Waltz algorithm is for interpreting line drawings of solid polyhedra as 3D objects
- An early example of an AI computation posed as a CSP



- Approach:
  - Each intersection is a variable
  - Adjacent intersections impose constraints on each other
  - Solutions are physically realizable 3D interpretations


# Varieties of CSPs and Constraints



# Varieties of CSPs

## ■ Discrete Variables

- Finite domains
  - Size  $d$  means  $O(d^n)$  complete assignments
  - E.g., Boolean CSPs, including Boolean satisfiability (NP-complete)
- Infinite domains (integers, strings, etc.)
  - E.g., job scheduling, variables are start/end times for each job
  - Linear constraints solvable, nonlinear undecidable



## ■ Continuous variables

- E.g., start/end times for Hubble Telescope observations
- Linear constraints solvable in polynomial time by LP methods (see cs170 for a bit of this theory)





# Varieties of Constraints

- Varieties of Constraints

- Unary constraints involve a single variable (equivalent to reducing domains), e.g.:

$$SA \neq \text{green}$$

- Binary constraints involve pairs of variables, e.g.:

$$SA \neq WA$$

- Higher-order constraints involve 3 or more variables: e.g., cryptarithmic column constraints


- Preferences (soft constraints):

- E.g., red is better than green
- Often representable by a cost for each variable assignment
- Gives constrained optimization problems
- (We'll ignore these until we get to Bayes' nets)



# Real-World CSPs

- Scheduling problems: e.g., when can we all meet?
- Timetabling problems: e.g., which class is offered when and where?
- Assignment problems: e.g., who teaches what class
- Hardware configuration
- Transportation scheduling
- Factory scheduling
- Circuit layout
- Fault diagnosis
- ... lots more!



- Many real-world problems involve real-valued variables...


# Solving CSPs

---




# Standard Search Formulation

- Standard search formulation of CSPs
- States defined by the values assigned so far (partial assignments)
  - Initial state: the empty assignment,  $\{\}$
  - Successor function: assign a value to an unassigned variable
  - Goal test: the current assignment is complete and satisfies all constraints
- We'll start with the straightforward, naïve approach, then improve it




# Search Methods

- What would BFS do?
- What would DFS do?



# Backtracking Search


---







# Backtracking Search

- Backtracking search is the basic uninformed algorithm for solving CSPs
- Idea 1: One variable at a time
  - Variable assignments are commutative, so fix ordering
  - I.e., [WA = red then NT = green] same as [NT = green then WA = red]
  - Only need to consider assignments to a single variable at each step
- Idea 2: Check constraints as you go
  - I.e. consider only values which do not conflict with previous assignments
  - Might have to do some computation to check the constraints
  - “Incremental goal test”
- Depth-first search with these two improvements is called *backtracking search* (not the best name)
- Can solve n-queens for  $n \approx 25$





# Backtracking Example



# Backtracking Search

```
function BACKTRACKING-SEARCH(csp) returns solution/failure
  return RECURSIVE-BACKTRACKING({ }, csp)

function RECURSIVE-BACKTRACKING(assignment, csp) returns soln/failure
  if assignment is complete then return assignment
  var ← SELECT-UNASSIGNED-VARIABLE(VARIABLES[csp], assignment, csp)
  for each value in ORDER-DOMAIN-VALUES(var, assignment, csp) do
    if value is consistent with assignment given CONSTRAINTS[csp] then
      add {var = value} to assignment
      result ← RECURSIVE-BACKTRACKING(assignment, csp)
      if result ≠ failure then return result
      remove {var = value} from assignment
  return failure
```

- Backtracking = DFS + variable-ordering + fail-on-violation
- What are the choice point?

# Improving Backtracking

- General-purpose ideas give huge gains in speed
- Ordering:
  - Which variable should be assigned next?
  - In what order should its values be tried?
- Filtering: Can we detect inevitable failure early?
- Structure: Can we exploit the problem structure?




# Filtering




# Filtering: Forward Checking

- Filtering: Keep track of domains for unassigned variables and cross off bad options
- Forward checking: Cross off values that violate a constraint when added to the existing assignment



# Filtering: Constraint Propagation

- Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:





WA	NT	Q	NSW	V	SA
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>

- NT and SA cannot both be blue!
- Why didn't we detect this yet?
- Constraint propagation*: reason from constraint to constraint

# Consistency of A Single Arc

- An arc  $X \rightarrow Y$  is **consistent** iff for *every*  $x$  in the tail there is *some*  $y$  in the head which could be assigned without violating a constraint





*Delete from the tail!*

- Forward checking: Enforcing consistency of arcs pointing to each new assignment



# Arc Consistency of an Entire CSP

- A simple form of propagation makes sure **all** arcs are consistent:





- Important: If X loses a value, neighbors of X need to be rechecked!
- Arc consistency detects failure earlier than forward checking
- Can be run as a preprocessor or after each assignment
- What's the downside of enforcing arc consistency?

*Remember:  
Delete from  
the tail!*

# Limitations of Arc Consistency

- After enforcing arc consistency:
  - Can have one solution left
  - Can have multiple solutions left
  - Can have no solutions left (and not know it)
- Arc consistency still runs inside a backtracking search!



*What went  
wrong here?*